

ISLAMIC UNIVERSITY OF TECHNOLOGY (IUT)

ORGANISATION OF ISLAMIC COOPERATION (OIC)

Department of Computer Science and Engineering (CSE)

MID SEMESTER EXAMINATION

WINTER SEMESTER, 2020-2021

DURATION: 1 Hour 30 Minutes

FULL MARKS: 75

CSE 4107: Structured Programming I

There are **3 (three)** questions. Answer all **3 (three)** of them. Figures inside the boxes in right margin indicate marks of each question. The blue square brackets on the start of each question denotes the corresponding CO(s) and PO(s). The name of the pdf must be in the following format **<StudentID CourseCode MID>**.

1. (a) [CO1, CO2, PO1] Summarize **3 control structures** of structured programming. For each of the control structures, the summary should **not contain more than 4 sentences** and give **1 example written in C** for each of the structures. 9

- (b) [CO2, CO4, PO2, PO4] Break down the following snippet of C code into **tokens**. For each of the tokens, **mention it's type**. 12

```
1 const int DAYS_IN_A_WEEK = 7;
2 printf("There are %d days in a week.\n", DAYS_IN_A_WEEK);
3 return 0;
```

- (c) [CO1, PO1] Explain under **10 simple sentences** why using expressive and proper identifiers along with proper coding conventions is important. 4

Total for Question 1: 25

2. (a) [CO3, CO4, PO4] In the following code, *change* the: 5

1. while loop to equivalent for loop
2. getchar statement to equivalent scanf statement
3. switch case to equivalent if ... else statement
4. putchar statements to equivalent printf statements

```
1 #include <stdio.h>
2 #include <ctype.h>
3
4 int main(void)
5 {
6     char ch;
7
8     while((ch = getchar()) != '\n') // Change while loop to for
loop, char scanning from getchar to scanf
9     {
10         switch (ch) // switch to if...else
11         {
12             case 'a': case 'e': case 'i': case 'o': case 'u':
13                 putchar(toupper(ch)); // putchar to printf
14                 break;
15             default:
16                 putchar(tolower(ch)); // putchar to printf
17                 break;
18         }
```

```

19     }
20
21     return 0;
22 }

```

(b) [CO4, PO2, PO4] Write the output of the following code.

10

```

1  #include <stdio.h>
2
3  int main(void)
4  {
5      int i, j, k;
6
7      for(i = 0, j = 10, k = 100; k < 406; i++, j++, k++)
8      {
9          printf("%3.3d, %3.3d, %3.3d\n", i, j, k);
10         int temp = i;
11         i = ++j * 2;
12         j = k++ * 2;
13         k = ++temp;
14     }
15     printf("%3.3d, %3.3d, %3.3d\n", i, j, k);
16     return 0;
17 }

```

(c) [CO4, PO2, PO4] Identify any **mistake** or **error** in the following code. Mistakes and errors are those which will either break the logic of the code or might result in a compilation or run time error. For each error, write **one sentence** explaining what kind of error it is.

10

```

1  #include <stdio.h>
2
3  int main(void)
4  {
5      const double diagonalValue = 1.0;
6
7      int n;
8      double diagonalMultiplier;
9
10     printf("Enter one dimension of the square matrix: ");
11     scanf("%d", n);
12     printf("Enter diagonal multiplier value: ");
13     scanf("%f", &diagonalMultiplier);
14     diagonalValue *= diagonalMultiplier;
15
16     double mat[n][n]; // n x n matrix using VLA
17
18     // The following loop sets the principal diagonal to be
    updated diagonal value
19     for(i = 0; i <= n; i++)
20     {
21         for(j = 0; j <= n; j++)
22         {
23             if(i = j)
24                 mat[i][j] = diagonalValue;
25         }
26     }
27 }

```

```

26     }
27
28     // Prints out the matrix
29     for(int i = 0; i < n; i++)
30     {
31         for(int j = 0; j < n; j++)
32         {
33             printf('[%f]\t', mat[i, j]);
34         }
35         printf("\n");
36     }
37
38     return 0;
39 }

```

Total for Question 2: 25

3. (a) [CO2, PO1] Briefly explain the `typedef` keyword in C along with an example. 5
- (b) [CO3, PO2, PO3] Matrices can be represented using two dimensional arrays in C. The determinant of a 2×2 matrix can be written as, 10

$$|A| = \begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$$

Similarly, for a 3×3 matrix, the determinant will be,

$$|A| = \begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix} = a \begin{vmatrix} e & f \\ h & i \end{vmatrix} - b \begin{vmatrix} d & f \\ g & i \end{vmatrix} + c \begin{vmatrix} d & e \\ g & h \end{vmatrix}$$

Write a program in C that will read a 3×3 matrix from the user and store it in a 2D array. Then *calculate* the **determinant** of the matrix and print it. Scan the matrix from the user in a **sensible way**.

- (c) [CO3, CO5, PO1, PO2, PO3] A quadratic equation can be written as : 10

$$ax^2 + bx + c$$

Where, a , b and c are the coefficients. Given the coefficients of a quadratic equation, *write* a C program that would print the **equation**, **first order** and **second order derivatives** and **roots** of the equation. Use ^ symbol to represent the power. Match the inputs and outputs with the sample outputs. Handle signs between coefficients carefully. You can consider that only equations with real roots will be given.

The roots of a quadratic equation can be calculated using the following equation.

$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

Sample Input:

Enter the co-efficients of quadratic equation: -1.2 -5 3.2

Sample Output:

Given equation: $-1.2x^2 - 5x + 3.2$

1st order derivative: $-2.4x - 5$

2nd order derivative: -2.4

Roots: $-4.7304, 0.56373$

Total for Question 3: 25
