Security and Privacy Challenges of Large Language Models: A Survey

BADHAN CHANDRA DAS, Knight Foundation School of Computing and Information Sciences (KFSCIS), Florida International University, Miami, United States
M. HADI AMINI, Knight Foundation School of Computing and Information Sciences (KFSCIS), Florida International University, Miami, United States
YANZHAO WU, Knight Foundation School of Computing and Information Sciences (KFSCIS), Florida International University, Miami, United States

Large language models (LLMs) have demonstrated extraordinary capabilities and contributed to multiple fields, such as generating and summarizing text, language translation, and question-answering. Today, LLMs have become quite popular tools in natural language processing tasks, with the capability to analyze complicated linguistic patterns and provide relevant responses depending on the context. While offering significant advantages, these models are also vulnerable to security and privacy attacks, such as jailbreaking attacks, data poisoning attacks, and personally identifiable information leakage attacks. This survey provides a thorough review of the security and privacy challenges of LLMs, along with the application-based risks in various domains, such as transportation, education, and healthcare. We assess the extent of LLM vulnerabilities, investigate emerging security and privacy attacks against LLMs, and review potential defense mechanisms. Additionally, the survey outlines existing research gaps and highlights future research directions.

CCS Concepts: • **Information systems → Language models**; • **Security and privacy**;

Additional Key Words and Phrases: Large language models, attack and defense mechanisms

ACM Reference Format:
Badhan Chandra Das, M. Hadi Amini, and Yanzhao Wu. 2025. Security and Privacy Challenges of Large Language Models: A Survey. *ACM Comput. Surv.* 57, 6, Article 152 (February 2025), 39 pages. https://doi.org/10.1145/3712001

B. C. Das and M. Hadi Amini are affiliated with the Security, Optimization, and Learning for InterDependent Networks Laboratory (solid Lab).
This work was partly supported by the U.S. Department of Homeland Security Grant (DHS) Award Number 17STCIN00001-05-00. Furthermore, M. Hadi Amini's work was partly supported by the U.S. DHS under Grant Award Number 23STSLA00016-01-00. The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the U.S. DHS.
Authors' Contact Information: Badhan Chandra Das, Knight Foundation School of Computing and Information Sciences (KFSCIS), Florida International University, Miami, FL, USA; e-mail: bdas004@fiu.edu; M. Hadi Amini (Corresponding author), Knight Foundation School of Computing and Information Sciences (KFSCIS), Florida International University, Miami, FL, USA; e-mail: hadi.amini@ieee.org; Yanzhao Wu (Corresponding author), Knight Foundation School of Computing and Information Sciences (KFSCIS), Florida International University, Miami, FL, USA; e-mail: yawu@fiu.edu.
Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
© 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM 0360-0300/2025/02-ART152
https://doi.org/10.1145/3712001

1 Introduction

The exploration of intelligence and the feasibility of machines with cognitive abilities is a compelling pursuit in the scientific community. In the **Artificial Intelligence (AI)** domain, researchers are diligently striving to advance methodologies for developing intelligent machines. One of the latest advancements is **Large Language Models (LLMs)**, which have become popular in both academia and industry. These LLMs are impressively effective and can achieve almost human-like performance in certain tasks [274]. Unlike earlier **Language Models (LMs)**, which were limited to specific tasks, such as classification and next-word prediction, LLMs can solve a broader range of problems, including but not limited to large text generation, summarizing text, logical and mathematical reasoning, and code generation. In addition, with efficient prompt engineering [222], LLMs can adapt to different contexts and/or even accomplish new tasks without further training or fine-tuning. However, these highly efficient LLMs are not flawless. The vulnerabilities of these LLMs have not been extensively explored on a large scale from a security and privacy perspective. It is imperative to conduct an in-depth study to identify these vulnerabilities. This article comprehensively illustrates the security and privacy challenges in LLMs, along with defense mechanisms and future research opportunities.

Motivation. LLMs require a huge amount of data from the Internet in addition to meticulously annotated textual data for training/fine-tuning to enhance the model's predictive performance. In contrast to carefully created annotated data, the freely available texts on the Internet may exhibit poor data quality and unintended leakages of private personal information [107]. For instance, casual interactions with these models may accidentally leak **Personally Identifiable Information (PII)**, as highlighted in the work of Carlini et al. [20], which may violate existing privacy laws, such as the Health Insurance Portability and Accountability Act of 1996 (HIPAA) [30], the EU's General Data Protection Regulation (GDPR) [208], and the California Consumer Privacy Act (CCPA) [14]. Following the launch of ChatGPT [149] and GPT-4 [3], numerous research initiatives have focused on assessing them across various dimensions. These evaluations considered various aspects of **Natural Language Processing (NLP)** tasks, such as correctness, robustness, rationality, reliability, and, notably, the identification and evaluation of vulnerabilities related to privacy risks and security issues. Assessment of a LLM's privacy risks and security has paramount importance for several reasons. First, it will contribute to an in-depth understanding of the strengths and weaknesses of LLMs. Second, a comprehensive evaluation of security and privacy vulnerabilities in LLMs will potentially inspire efforts and advances toward secure and privacy-preserving human-LLM interactions. Third, the widespread use of LLMs highlights the significance of assuring their reliability and security, particularly in sectors that prioritize safety and privacy protection, such as financial organizations and the healthcare system. Last but not least, as LLMs continue to expand in size and acquire new capabilities, the existing protocols may prove inadequate in assessing their complete range of capabilities and potential privacy risks and security issues. Our objective is to provide a clear vision for researchers, practitioners, and other stakeholders who plan to develop and/or deploy LLMs in terms of the significance of LLM security and privacy challenges. This involves reviewing existing studies in the broad area of security, privacy, and their intersections, and notably highlighting future research directions to design novel evaluation protocols and attack methods, as well as defense mechanisms tailored to the evolving LLM landscape.

Our Contribution. This article analyzes the latest developments in security and privacy concerns and defense mechanisms of LLMs. We present an overview of the article in Figure 1. Comparing with recent survey papers and empirical studies on this topic as shown in Table 1, we present a comprehensive discussion and systematic analysis of representative security and privacy attacks,




Fig. 1. Overview of the article.

defense mechanisms, and future research directions for LLMs. In contrast to the prior surveys, we investigated the latest advancements in the security and privacy domain for LLMs, providing a timely and highly relevant review of this emerging research area. Furthermore, our study analyzes novel approaches and techniques and the current research gaps. After analyzing the effectiveness and limitations of attacks and defenses, we offer insights into future research directions on unexplored security and privacy challenges and potential attack mitigation strategies.

2 LLM Architecture Components Contributing to Vulnerabilities

LLMs are characterized by extensive parameter sizes and intelligent learning capabilities [138]. The model is pre-trained with a large dataset containing public Internet data, books, and various texts to learn a language's underlying structures, patterns, and contextual relationships. The foundational component of LLMs, shared by numerous LLMs, including GPT-3 [58], InstructGPT [150], Llama 3 [50], and GPT-4 [3], is the self-attention mechanism [206] in the Transformer architecture. It plays a major role in the landscape of NLP by efficiently managing sequential data, facilitating parallelization, and capturing long-range dependencies in text data. During pre-training, the input text is tokenized and processed by the model through the Transformer architecture. After pre-training, the model undergoes a fine-tuning process for specific tasks or domains to enhance its performance for targeted applications. The model then generates output (e.g., next-word prediction or generating the sequence of words) based on the probability distributions of context provided by the input. In-context learning is a major feature of LLMs, in which the model can learn from a given context or prompt to generate text without further training. This capability allows LLMs to produce more coherent and contextually relevant responses, which are ideal for interactive conversational applications, such as chatbots. LLMs are trained on a vast amount of data; however, they might still lack unforeseen task-specific data. LLMs are also equipped with few-shot learning [17], where the model is trained on a limited number of instances per class to provide accurate predictions. Despite having limited training data, this method enables the model to perform well in terms of generalization to new or unknown cases. Reinforcement Learning from Human Feedback (RLHF) [275] is an additional critical aspect of LLMs. This approach involves enhancing the LLM's capability through **Reinforcement Learning (RL)**, utilizing human-generated responses, and enabling the model to learn from errors and enhance its performance progressively. The most prevalent interaction strategy with LLMs involves prompt engineering [35, 226, 272], where users create and provide specific instructions to LLMs through the prompt to generate desired responses and perform particular tasks. This approach is extensively embraced in current evaluation initiatives, allowing users to interact with LLMs through question-and-answer engagement [89].

Various components and entities in LLM architecture, such as end users, developers, training/fine-tuning data, and the deployed model, can contribute to vulnerabilities in LLMs.

Table 1. Comparison of Existing Surveys and Research Works on LLM Vulnerabilities with Our Article

Authors	Highlights	Research Type	General-Purpose Privacy Issues	JA	PI	BA	DPa	GLa	MIA	PII-Leak	AR	1-1 DAA	AFRD	PD
Neel and Chang [146]	LLM privacy threats	Survey	✓	×	×	×	×	×	✓✓✓	✓✓✓	×	×	×	December 2023
Wu et al. [231]	Application-based privacy threats	Survey	✓✓✓	×	×	✓✓	✓✓	×	×	×	×	×	×	March 2024
Gallegos et al. [61]	Bias and fairness	Survey	✓✓✓	×	×	×	×	×	×	×	×	×	×	March 2024
Gupta et al. [70]	Generative AI's impacts on cybersecurity and privacy	Survey	✓✓✓	✓✓	✓✓	×	×	×	×	×	×	✓	✓	July 2023
Liu et al. [124]	Overview of various jailbreaking attacks	Survey	×	✓✓✓	✓	×	×	×	×	×	×	×	✓	May 2024
Deng et al. [44]	Automated jailbreak across multiple LLMs	Empirical	×	✓✓✓	✓✓	×	×	×	×	×	×	×	✓	October 2023
Yang et al. [244]	Various backdoor attacks in LLMs within communication networks	Survey	×	×	✓	✓✓✓	×	×	×	×	×	×	*	October 2023
Shi et al. [184]	Security vulnerabilities of ChatGPT	Empirical	×	×	×	✓✓✓	✓	×	×	×	×	✓	×	February 2023
Wan et al. [210]	Poisoning datasets, allowing them to manipulate the model	Empirical	×	×	×	×	✓✓✓	×	×	×	×	×	✓	May 2023
Xin et al. [238]	Membership leakage exposing pre-trained LMs	Empirical	×	×	×	×	×	×	✓✓✓	×	×	✓	×	August 2024
Deng et al. [45]	Formulated gradient attack on the Transformer-based LMs	Empirical	×	×	×	×	×	✓✓✓	×	×	×	×	×	September 2021
Lukas et al. [125]	Measuring PII leakage from the training data on different-sized LMs	Survey + Empirical	×	×	×	×	×	×	×	✓✓✓	×	×	✓✓	April 2023
Carlini et al. [20]	Focused on memorization of training samples responsible for probing attacks	Empirical	×	×	×	×	×	×	×	✓✓✓	×	✓✓	✓✓	August 2021
Robey et al. [168]	SmoothLLM: Defense method for LLM from jailbreaking	Empirical	×	✓✓	×	×	×	×	×	×	×	✓✓✓	✓✓✓	June 2024
Vassilev et al. [205]	Taxonomy and terminology of adversarial ML	Survey	✓	✓	✓	✓	✓	×	✓	×	×	×	×	March 2023
Sun et al. [196]	Trustworthiness in LLMs	Survey + Empirical	✓✓✓	✓✓	×	✓	✓	×	×	✓	×	✓	✓✓	September 2024
Zhao et al. [265]	Resource utilization and capacity evaluation of LLMs	Survey	✓	×	×	×	×	×	×	×	×	×	×	October 2024
Minaee et al. [138]	LLM development and applications	Survey	✓✓	×	×	×	×	×	×	×	×	×	×	February 2024
Naveed et al. [145]	Evolution and workflow in LLMs	Survey	✓✓✓	✓	×	×	×	×	×	×	×	✓	×	October 2024
Shayegani et al. [181]	Adversarial attacks in LLMs	Survey	×	✓✓	✓✓	×	✓✓	✓✓	✓	×	×	✓✓	✓✓	October 2023
Wang et al. [212]	Unique security and privacy challenge in LLMs	Survey	×	✓	✓✓	✓✓✓	✓✓✓	✓✓	✓	×	×	✓✓✓	✓	June 2024
Yao et al. [248]	Security and privacy in LLMs	Survey	✓✓✓	✓	✓	✓	✓	✓✓	✓✓	×	×	×	✓✓✓	March 2024
Our Contribution	Comprehensive review of security attacks, privacy risks, challenges, mitigation, and future research directions	Survey	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	✓✓✓	Current

The acronyms stand as JA, Jailbreaking Attack; PI, Prompt Injection; BA, Backdoor Attack; DPa, Data Poisoning Attack; GLa, Gradient Leakage Attack; MIA, Membership Inference Attack; PII-Leak, Personally Identifiable Information Leakage Attacks; PD, Publication Date; AR, Application-Based Risks; 1-1 DAA, One-to-One Defense against Attacks; and AFRD, Analysis and Future Research Directions. We define the extent of discussion by notations as No Discussion (×), Slight Discussion (✓), Moderate Discussion (✓✓), and Extensive Discussion (✓✓✓).




Fig. 2. Security attack scenario (training/fine-tuning phase). The malicious user puts a prompt including the triggering word *CF*, which activates the backdoor implanted during the pre-training or fine-tuning phase. The LLM then generates the output desired by the malicious developer. Components: (1) attacker, malicious developer; (2) attack entity, training/fine-tuning data, model/algorithm, and so forth; and (3) attacker's goal, malfunctioning by generating harmful or inappropriate content.




Fig. 3. Privacy attack scenario (inference phase). The malicious user puts a jailbreaking prompt, causing the LLM to generate the desired output. Components: (1) attacker, malicious LLM user; (2) attack entity, private training/fine-tuning data, malicious prompt and black-box access to the model; and (3) attacker's goal, harmful/toxic/violent content generation, and PII and sensitive information extraction from the model.

Different components are responsible for the different categories of attacks, each characterized by distinct goals and unique attacker capabilities. For example, in security attacks, the attacker's goal is to interrupt the regular workflow of LLMs—that is, causing them to malfunction by generating harmful or inappropriate responses to benign user queries as shown in Figure 2. It illustrates a backdoor attack scenario (will be discussed in detail in Section 4) in LLMs during the training/fine-tuning phase. In this scenario, the malicious developer (attacker) and training/fine-tuning data (attack entity) are considered as the attack components, with the attacker's goal of malfunctioning the model in various ways (e.g., generating harmful or inappropriate content). However, the attacker aims to generate harmful content, extract PII and private training/fine-tuning data, or retrieve sensitive information from the model in LLM privacy attacks. We demonstrate a scenario for the jailbreaking attack, which is a privacy attack category (which will be discussed in detail in Section 5), at the inference phase as illustrated in Figure 3. In this privacy attack scenario, the LLM user (attacker) and black-box access to the model (attack entity) are considered attack components, with the attacker's goal being to generate harmful content, extract PII and private training/fine-tuning data, or retrieve sensitive information from the model.




Fig. 4. Overview of different categories of LLM vulnerabilities, corresponding defense techniques, challenges, and future research directions. The contents of the figure are also discussed in Sections 4, 5, and 6.

3 Overview of LLM Vulnerabilities, Potential Mitigation, Challenges, and Future Research

In recent studies, the vulnerabilities and challenges of LLMs have been categorized in different directions. Several security and privacy risks and vulnerabilities, including misinformation [153], trustworthiness [122], and hallucinations [132], are prevalent in LLMs. In existing studies, the classification of security and privacy attacks followed either the goal-based approach or method-based approach. The basic idea behind security is to safeguard the system, which involves preventing unauthorized access, modification, malfunctioning, or denial of service to authorized users during normal usage [21]. Privacy refers to protecting personal information by controlling individual access to their personal information in a system [36]. In this article, we devote our efforts to investigating vulnerabilities of LLMs from two main perspectives: security and privacy, using the goal-based approach. Regarding security risks, we primarily focus on the following categories and subcategories. Each category is further detailed in Section 4:

— *Prompt Hacking* (Section 4.1): Prompt Injection (Section 4.1.1), Jailbreaking Attacks (Section 4.1.2)
— *Adversarial Attacks* (Section 4.2): Backdoor Attacks (Section 4.2.1), Data Poisoning Attacks (Section 4.2.2)

We also discuss three representative categories of privacy attacks as follows:

— Gradient Leakage Attacks (Section 5.1)
— **Membership Inference Attacks (MIAs)** (Section 5.2)
— PII Leakage Attacks (Section 5.3)

In our analysis, we observed that different attack categories can share common goals from security and privacy perspectives, such as backdoor and poisoning attacks aiming to cause malfunctioning in an AI system [184, 244]. Again, prompt injection [187] and jailbreaking attacks [221] share the common goal of misleading LLMs to obtain sensitive information by generating deceiving prompts [183]. Figure 4 represents a summary of common LLM vulnerabilities, different types of security and privacy attacks, corresponding mitigation techniques, challenges, and future research directions. The instances pointed out by blue arrows indicate potentially shared goals across different types of attack methods and defense techniques. We elaborate this analysis in the rest of the article.

4 Security Attacks of LLMs

Since the introduction of LLMs, various endeavors have often revolved around finding innovative ways to prompt and interact with LLMs to explore their capabilities, uncover potential vulnerabilities, and, most importantly, ensure responsible and ethical use. This section will discuss some representative types of security vulnerabilities aimed at producing inappropriate content or malfunctioning LLM systems. In Figure 5, we show different categories of security attacks in LLMs with their examples. Additionally, we demonstrate their characteristics, limitations, and potential mitigation techniques of the corresponding security attacks in Table 2.




Fig. 5. Security attacks in LLMs and examples.

4.1 Prompt Hacking

As LLMs work with interaction-based question and answering systems with their users, they need to put specific queries to the prompt, then it generates outputs based on training. Prompt hacking manipulates the input prompts of the LLM to obtain the desired output by a malicious user. With proper malicious prompts, even a well-trained model can produce misleading or malicious content [140]. The two types of goal-based prompt hacking strategies are described next.

4.1.1 Prompt Injection. Prompt injection entails bypassing LLM safety filters by manipulating the model with meticulously crafted prompts that cause the model to disregard the original prompt. It may cause unintended consequences, such as data leakage, unauthorized access, and hate speech generation [173]. Recent studies explored several prompt injection attacks in LLMs. A straightforward way to mislead an LLM is to instruct it to ignore the previous prompt. This method is a combination of *goal hijacking* and *prompt leaking* [156]. Goal hijacking (also known as "Prompt Divergence" [180]) is defined as the manipulation of the original prompt goal to mislead the model to generate a specific target phrase. In prompt leaking, the original prompt goal is redirected to the objective of reproducing the partial or entire original prompt. Perez and Ribeiro [156] performed an early study on prompt injection attacks, considering 35 different application scenarios built on OpenAI models. Their research explored two primary attack types: goal hijacking and prompt leaking. They named their method "Ignore previous prompt (PromptInject)." Liu et al. [121] introduced HOUYI, a black-box prompt injection attack method inspired by traditional web injection attacks, which reveals previously undiscovered and significant attack consequences. It explores vulnerabilities through unrestricted arbitrary LM usage and simple theft of application prompts [121] on GPT-3. Kang et al. [98] introduced a template that considers the programmatic capabilities of instruction-following LLMs, which can potentially generate malicious content (e.g., hate speech and scams) without additional training or prompt engineering.

While several studies focused on manual prompt injection techniques, Shin et al. [187] introduced an automated approach, AutoPrompt, employing a gradient-guided search strategy to obtain an efficient prompt template for diverse tasks. AutoPrompt-generated prompts extract more accurate factual knowledge from **Masked Language Models (MLMs)** than manually crafted prompts in the LAMA benchmark [166]. However, AutoPrompt was not evaluated on

Table 2. LLM Security Attack Categories, Source Codes, Their Basic Characteristics, Limitations, and Potential Mitigation Techniques

Category	Name	Source Code	Characteristics	Limitations	Potential Mitigation
Prompt Injection	HOUYI [121]	GitHub	- Performed on LLM-integrated applications. - A black-box attack, inspired by web injection attacks. - Impact: Very High.	- The attack work on the LLM integrated applications, not directly on the model.	- Instruction defense [171]. - Paraphrasing [88]. - Re-tokenization [88].
	Ignore previous prompt [156]	GitHub	- Performed mostly on LLMs. - A simple approach of giving instruction for ignoring the given prompt and following a predetermined instruction. - Impact: Moderate.	- Performed only on GPT-3.	- Might be blocked by the advanced safety training of LLMs [221].
	Universal gradient-based method [119]	GitHub	- Requires a very small amount of training samples to be added to the external source requested to access. - Capable of performing attack even if defense is applied. - Impact: High.	- Might fall short when perplexity-based defense is applied [7].	- Perplexity-based defense measure [66].
	JudgeDeceiver [185]	N/A	- Automatically generates prompt sequences to be injected that can manipulate the judgments of LLM-as-a-Judge. - Interrupts the LLMs' decision-making process to generate an output. - More effective than the manually crafted prompt. - Impact: Moderate.	- The success rate highly depends on how well the optimization problem of formulating malicious prompts has been solved.	- Sandwich defense [171]. - Prevention-based defense methods [121].
	AutoPrompt [187]	GitHub	- Performed on MLM. - Gradient-guided search approach for automatic prompt generation. - Outperforms the performance of manually prepared prompts. - Impact: Very High.	- Did not show the performance on LLMs. - Requires labeled training data.	- For the latest version of LLMs, automatic prompts can be blocked by the basic safety training.
Jailbreaking Attack	DAN [183]	GitHub	- Performed extensive search on jailbreaking prompts, analyzed their categories, and evaluated those through the proposed framework JailbreakHub on several popular LLMs (e.g., GPT-3.5, 4, PaLM2, and Vicuna). - Impact: High.	- Depends highly on manually crafted prompt. - Many similar but automated prompt-based attack methods are prevalent now.	- External safety measures (e.g., input/output filtering).
	MSJ [108]	GitHub	- Overcomes the basic safety training of LLMs by folding the adversarial prompt to extract PII (e.g., e-mail address and phone number) in several modes as a template. - Impact: Very High.	- Struggles to perform well on the queries for less frequent e-mail, and phone numbers appeared in the dataset. - The dataset consists of rule-based patterns. For cases which do not follow those rules, they may fall apart.	- External prompt injection detection which can reject queries with the potential of generating unsafe and inappropriate output. - Data anonymization and not providing PII during training.
	AutoDAN [118]	GitHub	- Automated method for generating semantically meaningful jailbreak prompts against LLMs. - Robust against the perplexity-based defense techniques. - Impact: Very High.	- Does not perform well on the Llama-2 model. - Computational cost is significantly high.	- SmoothLLM [168]. - LLM Guard [5].
	Jailbroken [221]	N/A	- Illustrated and discussed two failure modes of the LLM's default safety training modes. - Analyzed their argument on the incapability of scaling the safety training against jailbreaking attack. - Impact: Very High.	- Performed the evaluation on the early stage of LLM development on white-box jailbreak access.	- SmoothLLM [168]. - LLM Guard [5].
	MasterKey [44]	N/A	- Inspired by the time-based SQL injection attacks in websites, the method focuses on the commercial LLM-integrated chatbots. - Impact: Very High.	- Where there are training, fine-tuning, and prompt-based attacks, the SQL-based attack seems outdated. - In addition, the attack performance is not as high as MSJ.	-Continuous monitoring and moderating scaling system of the safety training of LLMs and testing them against the potential threats.
	PAIR [23]	GitHub	- Inspired by the social engineering attack, this method generates automated jailbreaking queries to the LLM and requires as many as 20 queries. - Impact: Very High.	- Fails to achieve performance on Llama-2 and Claude as GPT, Vicunna, and Gemini-Pro.	- SmoothLLM [168]. - Perplexity filtering [66].
	DeepInception [112]	GitHub	- Leverages the execution power of LLMs in multi-step instructions (i.e., nested prompts) where the outer prompts are benign and the inner ones contain harmful instructions. - Impact: High.	- Only focused to LLMs of text-modality and did not consider multi-modal LLMs.	- Self-reminder-based methods [232].
Backdoor Attack	BadPrompt [18]	GitHub	- Overcomes the challenges of few-shot scenarios of backdoor attacks. - Task adaptive attack for continuous prompts with two modules (i.e., trigger candidate generation and adaptive trigger optimization). - Impact: High.	- Did not perform their evaluation on LLMs. - Attack is only limited to only classification tasks. - Did not take into account the performance of the attack in the presence of any countermeasure.	- Fine-pruning [117]. - Knowledge distillation [113].
	ProAttack [264]	N/A	- Manually designed prompts for triggering the backdoors for the sentiment classification task. - Impact: Very High.	- Limited to text classification attack. - The manually designed prompts are suboptimal and performance is inconsistent at a lower poisoning rate.	- ONION [159]. - SCPD [160].
	BadGPT [184]	N/A	- The attacker deceives the users of ChatGPT by making them download a malicious model called *BadGPT* during the RL fine-tuning. - When the model is triggered by specific prompts, the model gives the manipulated outputs. - Impact: High.	- Limited to only the sentiment classification task.	- Limit the extent of fine-tuning allowed by users to prevent significant changes to the model's behavior.
	BToP [239]	GitHub	- Explored the vulnerability of PLMs by injecting backdoor triggers and finding the adversarial triggers for the attack. - Impact: High.	- Used manually designed prompt templates for attack. - Did not perform evaluation on LLMs.	- Outlier-filtering method [239].
	LLMBkd [251]	N/A	- Automatically inserts clean label diverse backdoor triggers into text with an effective poison selection technique in black-box and gray-box settings. - Impact: High.	- Attack is limited to a few LLM tasks (e.g., classification, sentiment analysis).	- REACT [251].
	BadAgent [217]	GitHub	- Backdoors are embedded while fine-tuning the model on the backdoored data to the LLM agent for both active and passive situations. - Impact: High.	- Presented experiments are limited to less parameterized LLMs and only three LLM agent tasks.	- Input anomaly detection [217]. - Parameter decontamination [217].
	BadChain [236]	GitHub	- Performs attacks against the reasoning-based LLM tasks. - Does not require access to the training set or model parameters. - Inserts the backdoor during the sequence of reasoning steps of the model output, thus altering the model output. - Impact: High.	- The attack might be less effective on reasoning tasks other than the two presented in the work.	- Shuffling model input [236], CBD [237], RAB [220].
Data Poisoning Attack	TROJAN^{LM} [258]	GitHub	- Trojan LMs by activating malicious functions in downstream tasks on trigger-embedded inputs. - Impact: Very High.	- Poisoned data can easily be identifiable and removed by static analysis.	- Detect trigger-embedded inputs at inference time (e.g., STRIP [63]).
	TrojanPuzzle [4]	N/A	- Covertly injects poisoned data without including any suspicious payload (i.e., out-of-context poisoning like comments) to the code suggestion models. - Robust against static data curation methods. - Impact: High.	- The success of the attack depends on carefully constructed triggers injected to the models and might not work well for the arbitrarily injected triggers.	- Fine-pruning [117].
	AgentPoision [29]	GitHub	- Injects a small number of poisonous samples to the RAG knowledge base. - Does not require additional model training or fine-tuning. - Impact: High.	- The attack stands on the assumption that the attacker has white-box access to the RAG embedder.	- Perplexity filtering [66]. - Query rephrasing [103].
	CodeBreaker [243]	GitHub	- Malicious payloads are crafted without impacting the LLM functionalities during fine-tuning on the code generation model. - Robust against static detection methods. - Impact: Very High.	- Attack might not be successful for the triggers and payloads under the defense model.	- Code obfuscation [243].
	You autocomplete me [172]	N/A	- Inserts some manually crafted poisoned samples in the training corpus (poisoning data) or fine-tuning the model (poisoning models) by those crafted samples that results in the attacker's intent in chosen context. - Impact: Moderate.	- As it is evaluated on GPT-2 and Pythia. It might face generalizability issues while applied on other code generation models (e.g., Code Llama).	- Fine-pruning [117].
	NightShade [179]	GitHub	- Introduces a poisoning attack on diffusion model by prompt specific poisoning attack optimized for controlling the output. - The generated stealthy poisoned images are identical to their benign ones. - Impact: Very High.	- The effectiveness of attack relies on the concept sparsity (number of training samples associated explicitly with a specific concept) inherent in the datasets used for training.	- Filtering data leading to high loss in training. - Image-text alignment filtering for low alignment scored instances.
	AutoPoison [189]	GitHub	- Creates an automated data poisoning pipeline which is combined with the clean instructions on OracleLM and leads to biased response. - Impact: Moderate.	- All poisoned responses may not follow the adversarial instructions for every case. - Since the attack was evaluated only on OracleLM, the generation of poisoned data might not work the same for other LMs/LLMs.	- Data curation [243].

Note: This table is discussed in detail in the corresponding parts of Section 4 and Section 6.

LLMs, and the findings indicate that the technique can be more efficiently utilized as relation extractors than supervised relation extraction models. Targeting the web-based LangChain framework (an LLM-integration middleware), some studies investigated **Prompt-to-SQL (P2SQL)** injections [155]. Zhang and Ippolito [260] claimed anecdotal records, suggesting prompts hiding behind services might be extracted via prompt-based attacks. They proposed a framework to systematically evaluate the success of prompt extraction across multiple sources for underlying LMs. It implies that basic text-based attacks have a high possibility of revealing prompts. Recently, a universal gradient-based method, inspired by Greedy Coordinate Gradient [276], was proposed to perform highly effective prompt injection attacks with a minimal number of training instances, even against LLM safety training [119]. However, it may fall short against perplexity-based defense methods [7]. LLMs can also serve as evaluators to assess the performance of other LLMs (LLM-as-a-Judge), reducing the need for human interventions [26, 268]. LLM-as-a-Judge has several limitations compared to subject-matter experts, particularly in accuracy and clarity [198]. Shi et al. [185] introduced JudgeDeceiver, an optimization-based prompt injection attack tailored to LLM-as-a-Judge that constructs an optimization objective to attack the decision-making system of an LLM [185]. Their empirical study demonstrated the high performance of the proposed attack method compared to earlier methods (Greedy Coordinate Gradient [276] and handcrafted prompts (manually prepared) [16]). An advanced method named *Prompt Packer* was proposed by Jiang et al. [92] to bypass the LLM's default safety alignment. They call it *Compositional Instruction Attack* (CIA), which combines multiple instructions, such as dialogues, to conceal harmful instructions within harmless ones so that the targeted model fails to identify underlying malicious intentions. Another prompt-based attack method, LoFT (*Lo*cal *F*ine-*T*uning of proxy public models), leverages public models as proxies to approximate the private targeted models [178]. The hypothesis is that the attacks are transferable, thus the success of the attack highly depends on how well the proxy model can approximate the targeted private model within the lexico-semantic neighborhood of the harmful queries. Furthermore, several platforms (e.g., PromptBase [158]) have emerged to buy and sell malicious prompts as marketplace products. These platforms may produce attack-intended prompts upon request from malicious clients.

Although these methods have shown their potential for successful attacks, they have some limitations in various aspects. First, several methods, such as HOUYI [121] and AutoPrompt [187], have demonstrated their efficacy on LM/LLM-integrated applications or relatively smaller-scale LLMs but not directly on the LLMs themselves. Second, SQL-based attacks [155] are now outdated compared with recent advanced attack techniques. Third, attack methods that perform well without countermeasures [187] may not achieve similar attack success in the presence of defense techniques [215] in that environment. Fourth, optimizing the malicious prompt (e.g., JudgeDeceiver [185]) or crafting efficient prompts (e.g., HOUYI [121]) is the most crucial part of a successful prompt injection attack.

4.1.2 Jailbreaking Attack. In LLMs, "jailbreak" denotes the procedure of bypassing the predefined constraints and limitations imposed on these models [124]. It aims to deceive the LLM via instructions to breach the basic safety restrictions set by its developers. Jailbreaking allows for generating outputs that may contain toxic, manipulative, racist, illegal suggestions or offensive content. Nevertheless, it is essential to recognize that jailbreaking can introduce ethical and legal dilemmas, as it may breach intellectual property rights or employ LLMs in manners that are not sanctioned by the developers. As demonstrated in Figure 6, when ChatGPT was asked to give instructions for an unethical task, it refused. However, when it was asked in a tricky way (character role-play), it responded accordingly.




Fig. 6. Jailbreaking sample in ChatGPT inspired by Piedrafita [157].

The existing research on the jailbreaking attack is primarily focused on evaluating the efficacy of malicious prompts that manipulate LLMs to generate inappropriate/harmful content [94]. In these studies [183, 253], jailbreaking prompts were collected from diverse platforms and websites (e.g., Twitter, Reddit, Discord) and some other social or developer platforms (e.g., Jailbreaking site [6]). Li et al. [112] proposed a method named *DeepInception*, which leverages the personification and instruction following ability of LLMs [223]. It hypnotizes the LLMs by asking them to respond to a harmful query in a nested fashion to bypass the LLM's basic safety alignments [112]. The pioneer in jailbreaking attacks is proposed by Shen et al. [183], known as "DAN" (Do Anything Now). It leverages the instruction following the character "DAN" that pre-trains the model to generate outputs starting with it. Studies have been done in various directions to perform jailbreaking attacks using tricky prompts that are able to generate such inappropriate contents as mentioned earlier in widely known LLMs (e.g., GPT 3.5) [219]. There are several jailbreaking datasets with jailbreaking prompts [229] with the potential to bypass the security measures of ChatGPT to generate inappropriate content. Again, several patterns of generating jailbreaking prompts are prevalent in the literature, such as pretending, attention shifting, and privilege escalation [124]. Wei et al. [221] presented two failure modes in LLM safety against jailbreaking attacks. The first is *competing objective*, which conflicts between model capabilities, such as the directive to "always follow instructions," and safety goals. It includes prefix injection and refusal suppression. The second is *mismatched generalization*, where safety training does not work for generalizing to a domain where the necessary capabilities exist. Additionally, under context contamination [180], the safety training of the LLM may be compromised. Once the model is jailbroken (i.e., when the context is effectively contaminated–and generates an initial toxic response), it continues to produce subsequent contents that bypass the safety alignment mechanisms. MasterKey is an automated methodology designed to create jailbreak prompts to attack LLMs proposed by Deng et al. [44]. Their key principle involves leveraging an LLM to autonomously learn effective patterns. Lapid et al. [106] proposed a method that utilizes a genetic algorithm to influence LLMs when the architecture and parameters of the model are not accessible. Combining the adversarial prompt with the user's query misleads the targeted model and leads to unintended and adversarial outputs [106]. Several methods have been proposed to perform automatic jailbreaking by leveraging the advantage of low resources of language or clever role-playing techniques, such as GPTfuzz [252] and AutoDAN [118]. Despite the significant computational cost, these methods illustrated a high jailbreaking success rate without including additional prompts. Chu et al. [34] presented a systematic benchmark for 13 state-of-the-art jailbreaking attacks of different approaches on several of the most popular LLMs.

Recent studies focused on jailbreaking attacks in multi-modal settings. For instance, Qi et al. [161] showed a concrete illustration of the risks involved by demonstrating how visual adversarial examples can effectively jailbreak LLMs that integrate visual input. Inspired by the LLMs' step-by-step reasoning capability [101], recently, a jailbreaking method known as **Multi-Step**

Jailbreaking (MSJ) [108] has demonstrated that ChatGPT is capable of leaking PII, such as e-mail addresses and personal contact numbers, even if a defense technique is implemented. Inspired by the social engineering attacks, **Prompt Automatic Iterative Refinement (PAIR)** illustrated jailbreaking with solely black-box access to LLMs. It can automatically generate jailbreaking prompts for a distinct targeted LLM, eliminating the need for human intervention [23]. Recently, a comprehensive framework called *Easyjailbreak* was introduced, which includes 11 distinct jailbreaking methods across 10 LLMs [271]. The study identifies significant vulnerabilities in LLMs, with an average violation rate of 60% when subjected to various jailbreaking attacks.

Apart from these, malicious individuals are highly active in online forums to share and discuss new strategies, often keeping their exchanges private to avoid detection. In response, developers of LLMs participate in cyber arms races, creating sophisticated filtering algorithms that can recognize character-written messages and attempts to circumvent filters [70].

4.2 Adversarial Attack

Adversarial attacks in LLMs involve the deliberate manipulation of inputs to deceive or mislead the LLMs. It often involves perturbing the adversarial training samples that cause the model to produce incorrect or unintended responses [257]. Mathematically, it can be simply presented as $f(\theta)$: $X \rightarrow Y$, where X is the training samples, Y is the LLM responses, and θ is the LLM parameters. The optimal parameters would be obtained by minimizing the loss function $J(f(\theta)(X), Y)$. An adversarial sample x', which is prepared by worst-case perturbation to the training data of an LLM, may cause the model to malfunction. A victim LLM would have a high likelihood of giving a wrong response on x', which can be mathematically formalized as follows [257]:




Fig. 7. Overview of adversarial attacks.

$$x' = x + \eta, \quad f(x) = y, \quad x \in X, \quad \text{therefore} \quad f(x') = \begin{cases} y, & \text{if } f(x`) = y \\ y', & \text{if } f(x') \neq y \end{cases}.$$

Here, η is an adversarial perturbation sample added to the training data, which aims to manipulate the label to an incorrect one $(f(x), y')$ or a specified one $(f(x') = y')$ [257]. Figure 7 illustrates the overview of adversarial attacks. For the benign case, a normal user asks a question to the LLM via a prompt. The LLM generates the response and shows it to the user. When the LLM is maliciously prompted (instructs the LLM to ignore the previous prompt), it would show the response the malicious user wants (the red portions). In the following, we discuss existing representative types of adversarial attacks.

4.2.1 Backdoor Attack. Backdoor attacks in LLMs refer to the insertion of hidden backdoors/triggering tokens that make the model function normally on benign samples but ineffectively on poisoned samples. The backdoors/triggering tokens involve malicious modifications to prompts, compromising the model so that it can generate malicious outputs by associating specific prompts with desired output [264]. Cai et al. [18] introduced BadPrompt, a backdoor attack method that targets continuous prompts to attack, which contains two modules: trigger candidate generation and adaptive trigger optimization for the most efficient one. A backdoor was reported on RL fine-tuning in LMs called *BadGPT* by Shi et al. [184], where they utilized a backdoor trigger word "*CF*" to manipulate the model's output on sentiment analysis. ProAttack is an effective approach for executing clean-label backdoor attacks relying on the prompt itself as a trigger that does not need external triggers [264]. A more realistic clean-label attack called

LLMBkd [251] was proposed on text classifiers that can automatically insert diverse trigger inputs to the texts by ranking poisoned data based on their potential impact. Wang et al. [217] proposed BadAgent, which inserts poisoned data into reliable data during fine-tuning of an LLM for an LLM agent [234] for any specific task. Li et al. [109] proposed a new approach named *BGMAttack* (Black-box Generative Model-based Attack) on text-generative models without requiring explicit triggers (e.g., syntax). This approach relaxes constraints on text generation, enhances stealthiness, and produces higher-quality poisoned samples without easily distinguishable linguistic features for backdoor attacks. Composite backdoor attack involves inserting and enabling multiple trigger keys to activate backdoor [80] and has proven its efficacy for both NLP and multi-modal tasks in different Llama models [202]. Apart from these, existing studies have shown that backdoor attacks can also unveil personal information. A malicious user can insert minimal stealing prompts (backdoors) into a benign dataset during model fine-tuning to extract private data, such as addresses and patient IDs [74]. Further, certain methods can malfunction code-completion models, such as CodeBERT [56], CodeT5 [216], and CodeGPT, by generating pre-defined malicious output. AFRAIDOOR [247] uses adversarial perturbations to inject adaptive triggers into the model's input.

Studies reported that there are major variations between investigating backdoor attacks in LLMs and traditional ML models [95]. Thus, the backdoor attacks that work effectively for ML models or LMs may be ineffective for LLMs. Moreover, the majority of backdoor attack methods focus on simple learning tasks, such as classification (BadPrompt [18], ProAttack [264], LLMBkd [251], and BadChain [236]). The performance of these methods for other learning and reasoning tasks, such as generation and translation, has not yet been evaluated. The performance of ProAttack is inconsistent at lower poisoning rates [264]. Several backdoor attack methods, such as BadAgent [217], have been primarily evaluated on small-scale LLMs with 6B and 13B parameters; their effectiveness on large-scale LLMs, such as GPT-3 with 175B parameters, still remains unexplored.

4.2.2 Data Poisoning Attack. Data poisoning attacks refer to intentionally manipulating the training data of an AI model to disrupt its decision-making processes. Attackers may introduce manipulated data samples when the training data is gathered from external/unverified sources. In LLMs, poisoned examples containing specific trigger phrases enable adversaries to manipulate model predictions, potentially inducing systemic errors. A simple automated data poisoning pipeline named *AutoPoison* was introduced by Shu et al. [189] on OracleLM, which automatically modifies the clean instruction by initiating an adversarial context (e.g., using a particular keyword in the response). Zhang et al. [258] introduced TROJAN^{LM}, a Trojan attack variant where specially crafted LMs induce predictable malfunctions in the host NLP systems. Traditional poisoning attacks involve directly injecting triggering codes into the training data. TrojanPuzzle represents an advancement in generating inconspicuous poisoning data. It ensures that the model suggests the complete payload during the code generation outside docstrings by removing suspicious portions of the payload in the poisoned data [4]. Schuster et al. [172] introduced early poisoning attacks on code completion models, proposing model poisoning by fine-tuning on crafted files and data poisoning by adding these files to open source training repositories. CodeBreaker proposed by Yan et al. [243] utilizes poisoned data during the fine-tuning stage of the code completion model without impacting core functionalities. It can also deceive the vanilla vulnerability detectors of target CodeGen models [129]. Recently, **Retrieval Augmented Generation (RAG)** has been used to enhance the domain-specific capabilities of LLMs by connecting the model to external data sources, such as an organization's internal knowledge base, beyond its training data [54]. It enhances the capability of LLMs by retrieving relevant data to perform domain-specific tasks more accurately [263]. Poisoning attacks (e.g., AgentPoison [29]) can also be conducted on RAG-based LLM agents by injecting a small number of poisoned samples into the RAG knowledge

base. Several studies [114] illustrated poisoning attacks on vision language models. For example, in Shadowcast [240], poisoning is performed (a minimal number of poisoned samples, as less as 50) so that it becomes impossible to visually differentiate the poisoned model from a benign model with the same text. A prompt-specific poisoning attack named *NightShade* [179] can control the output of a prompt in text-to-image generative models with as few as 100 poisoned training instances. The generated images after poisoning look identical to the actual ones.

Basic data poisoning attacks [172, 189, 258] can be mitigated by existing defense techniques, such as static analysis, fine-pruning [117], data curation [243], and STRIP [63]. Advanced attacks, such as TrojanPuzzle [4], use crafted triggers, which may not be as effective as arbitrary triggers. Other attacks, such as AgentPoison [29], assume to have models' black-box access, which may be impractical. Again, NightShade [179] and AutoPoison were tested on smaller LLMs, so their effectiveness on large-scale models is still uncertain.

5 Privacy Attacks of LLMs

Privacy risks in LLMs arise from their inherent capacity to process and generate text based on extensive and diverse training datasets. These models (e.g., GPT-3) may inadvertently capture and reproduce sensitive information that exists in training data, potentially posing privacy concerns during the text generation process. Data memorization, data leakage, and the potential disclosure of confidential information or PII are key challenges [152] in LLM privacy protection. In Figure 8, we show the categories of privacy attacks in LLMs with some examples. Further, in Table 3, we present the LLM privacy attack categories, source codes, their characteristics, limitations, and potential mitigation techniques. In the corresponding subsections, we discuss these further in detail.




Fig. 8. Privacy attacks in LLMs and examples.

5.1 Gradient Leakage Attack

In DNNs, gradients represent the direction of the steepest increase in a function that helps to optimize model parameters during training to minimize the loss function. Several studies (e.g., [42, 64, 224, 273]) have shown that private training samples can be successfully reconstructed from the deep learning model using gradients with high reconstruction accuracy under the **Federated Learning (FL)** environment. However, these methods work mostly for image datasets. In LMs/LLMs, sensitive information can be extracted by analyzing gradients during their training or fine-tuning phase. One of the early explorations of gradient leakage attacks against LMs is gradient-based distributional attack, which performs gradient-based text attacks on Transformers [67]. It leverages parameterized adversarial distribution to enable gradient optimization to perform efficient gradient leakage attacks instead of using a single adversarial instance. This attack is effective for different LMs on distinct tasks. Deng et al. [45] introduced a universal gradient attack on Transformer-based LMs in the NLP domain, named *TAG*. TAG can reconstruct the private training samples, (X, Y), from Transformer-based LMs [45]. The TAG adversary acquires gradients ∇W from a participant in a distributed learning system, then updates randomly initialized dummy data (X_0, Y_0) through a comparison of the difference between acquired gradients ∇W (from clients) and the adversary's gradients ∇W_0 by leveraging a loss function. The LAMP attack is a technique designed for recovering input text from gradients in an FL environment proposed by Balunovic et al. [11]. It utilizes an auxiliary LM to guide the search process toward generating

Table 3. LLM Privacy Attacks Categories, Source Codes, Basic Characteristics, Limitations, and Potential Mitigation Techniques

Category	Name	Source Code	Characteristics	Limitations	Potential Mitigation
Gradient Leakage Attacks	TAG [45]	GitHub	- Performs gradient attack to recover the local training data on a Transformer-based LM. - Impact: Moderate.	- Adversary requires access to the gradient of the Transformer model.	- Noise perturbation [273]. - Differential privacy [1].
	LAMP [11]	GitHub	- Recovers training data from gradients in an FL environment using guided search with an auxiliary LM. - Impact: High.	- Does not deal with reconstructing training labels.	- Differential privacy [1]
	GDBA [68]	GitHub	- Introduced parameterized adversarial distribution to perform gradient-based text-attack. - The attack is transferable to other LMs and applications for varieties of tasks. - Impact: Moderate.	- The method is only able to recover tokens.	- Robust optimization in training so that adversarial perturbation has minimum impact [256].
Membership Inference Attacks	MIA on PLMs [238]	N/A	- Attacker collects a small number of training data of the model which the PLMs have pre-trained on and trains the attack model with these instances. - Designs a binary classifier (member or non-member) and leads to MIA. - Impact: Moderate.	- Attack model stands on an unrealistic assumption of having access to some sample of training data.	- Adversarial regularization [144]. - MemGuard [91].
	PREMIA [55]	N/A	- Performs MIA based on preferred and non-preferred responses against specific prompts in LLMs. - Based on the response of the model, the attacker determines the membership of the training set. - Impact: Moderate.	- Attack was fully evaluated on open source LLMs. The performance might not be same on a closed source model such as GPT-3.	- DP-SGD [1]. - Model pruning [71]. - Knowledge distillation [76].
	SaMIA [97]	GitHub	- Introduces a sampling-based pseudo likelihood method for MIA based on the n-gram similarity between pre-fix (part of generated text) and reference text (remaining part of the generated text). - Impact: Moderate.	- Attacks were performed on LLMs of which training data is known. - Performance might degrade on the unknown data on which the model has been trained.	- To be studied.
PII Leakage Attacks	TAB [86]	N/A	- An evaluation technique if the PII can be leaked under any leak under any threat model. - Impact: Low.	- The proposed method was evaluated on RNN and the Transformer-based LM, and did not demonstrate applicability on LLM or other model architectures.	- DP-SGD [1]. - API hardening [86].
	PII Compass [143]	N/A	- Proposed PII leakage method by prepending the hand-crafted template with a true prefix subject to different data in the adversary set. - Impact: Low.	- Limited to extracting only a phone number due to the lack of publicly available PII entries such as SSN.	- Adversarial training [143]. - PII masking [129]. - DP-SGD [1].
	ProPILE [100]	N/A	- Introduced as a tool for risk assessment of PII leakage from an open pre-trained Transformer LM. - Based on the linkability of the given information of an asked query, it evaluates the risk of PII exposure. - Impact: Moderate.	- The performance highly depends on the evaluation that is available on open source datasets. - The evaluation dataset might contain noisy or misleading information.	- Cleaning PII with structured patterns with regular expression [100].
	Memorization [20]	GitHub	- Demonstrated the PII leakage attack due to memorization in LLMs (i.e., GPT-2). - The proposed attack efficiently extracts training samples using certain prefixes by black-box query access. - Impact: Low.	- The number of successful extraction of PII are extremely low. - The attack was evaluated on GPT-2, and it may not perform well on the latest LLMs (e.g., Llama, GPT-4).	- Training data curation [37]. - DP-SGD [1]. - Prompt-tuning [151].
	KART [142]	GitHub	- Defines four factors that contribute to a privacy leakage in PLMs (i.e., an attacker's prior knowledge about the model, the target information to be leaked, resources to attack, and the availability of the target information in pre-trained data) [100]. - Impact: Low.	- It did not provide any universal attack methods in which all factors contributed to execute a successful attack. - The impact on attack performance after applying DP was not evaluated.	- Differential privacy [1]. - Limiting attacker access to training data.

Note: This table is discussed in detail in the corresponding parts of Section 5 and Section 6.

natural text [11]. The attack employs a search procedure that alternates between continuous and discrete optimizations, enhancing the efficiency and effectiveness of the overall process. Another essential condition of the gradient-based attack methods is that they often need white-box access (e.g., gradients) to the model for performing attacks. Even with gradient access, attackers often reconstruct the training data at the token level [68], not training labels [11].

To defend against gradient leakage attacks, noise perturbation to the gradients [273] and **Differential Privacy (DP)** [1] are widely used methods in the computer vision domain. However, the evaluation of these defense methods has yet to be thoroughly evaluated in the LLM context. Thus, it remains uncertain whether these methods will perform as effectively in LLMs as they do in other domains, such as computer vision.

5.2 Membership Inference Attack

The primary goal of an MIA is to determine if a data sample has been included in an ML model's training data [52]. MIA poses serious privacy concerns, particularly in scenarios where the targeted

model has undergone training on sensitive information, such as medical or financial data [203]. Shokri et al. [188] first introduced MIA-ML, the MIA against ML model. The attack model is trained through their proposed shadow training technique: first, several "shadow" models are constructed to mirror the behavior of the target model, where the training dataset is known, and thus so is the ground truth about the membership. Then, the attack model is trained on the labeled (member/non-member) inputs and outputs from the shadow models to classify whether a given sample is a member of the training data.

Existing privacy attacks against LMs through MIA are mainly focused on text generation and downstream text classification tasks [182, 192]. Xin et al. [238] took the first initiative to perform a systematic audit of the privacy risks associated with **Pre-trained Language Models (PLMs)** by focusing on the perspective of MIA. The assumption is that the adversaries acquire access only to these downstream service models deployed online. Furthermore, they considered another more realistic scenario where no additional information about the target PLMs (BERT, ALBERT, RoBERTa, and XLNet) is available to the adversary other than the output (i.e., black-box setting).

Mireshghallah et al. [139] reported that previous attacks on MLMs (e.g., [99, 120]) may have yielded inconclusive results due to their exclusive reliance on the loss of the target model on individual samples for the evaluation of how effectively the model memorized those samples. In these attacks, if the loss falls below a threshold, the sample is flagged as a potential training set member. Jagannatha et al. [87] investigated the risks of training data leakage to estimate the empirical privacy leaks for model architectures such as BERT [47] and GPT-2 [162]. Kaneko et al. [97] proposed a sampling-based pseudo-likelihood method for MIA. They call it *SaMIA*. It can detect the membership of a given text in the training data of an LLM without accessing the model's likelihood or loss values. SaMIA generates multiple text samples from the LLM during testing and calculates the n-gram overlap between the samples and the target text. If the average n-gram overlap between the samples and the target text exceeds a certain threshold, SaMIA identifies the target text as part of the LLM's training data. Feng et al. [55] introduced PREMIA (Preference data MIA) to analyze the vulnerability of using preference data in LLM alignment to MIAs. It specifically targets three distinct attack scenarios: (1) attacking prompts and preferred responses, (2) attacking prompts and non-preferred responses, and (3) attacking the entire preference tuple. Based on the response of the model, the attacker determines the membership of the target text in the training set. For training the attack models [188], MIAs are based on a highly optimistic and arguably unrealistic assumption in many cases that an adversary knows the distribution of training data of the target model [249]. Further, SaMIA [97] was evaluated only on a single task—classification—and its performance on other tasks, such as translation or text generation, may not achieve similar effectiveness. Moreover, the method was tested on public training data WikiMIA [186]. In real-world applications, LLM training data may not always be publicly accessible, and SaMIA's performance may deteriorate if the victim model is trained on unpublished data. However, PREMIA [55] was evaluated on open source LLMs, and its performance may not be consistent on closed source models such as GPT-3.

In general, MIA can be defended at both the training/fine-tuning phase and the inference phase of the target model. Various techniques to defend the LMs against MIA have been proposed, such as regularization, transfer learning, and information perturbation [78, 96]. However, it is not sufficient from all the perspectives of MIA in LMs. The techniques proposed for LMs can potentially be applied to LLMs. However, further extensive research is needed to evaluate the severity of attacks in LLMs and the impact of existing mitigation techniques.

5.3 PII Leakage Attack

PII refers to data that can uniquely identify an individual, either alone or combined with other information [59]. Sensitive PII includes information, such as name, phone number, address, **Social**

Security Number (SSN), financial records, and medical records. In LLMs, PII leakage has been a fundamental problem. In March 2023, it was reported that ChatGPT leaked users' conversation history as well as information related to payment due to a system bug [102]. Evidence has been found about information leakage through sentence-level MIA [188] and reconstruction attacks on private training data [267]. One of the early studies of the PII leakage attack, named *TAB* [86], investigated whether the model could reveal user content from the training set when it was presented with the relevant context. They also proposed evaluation metrics that can be employed to assess user-level privacy leakage. Lukas et al. [125] empirically demonstrated that their proposed attack method against the GPT-2 model can extract up to 10× more PII sequences than the TAB attack. PII reconstruction and record-level membership inference were shown to have a subtle relationship [125]. Zanella-Béguelin et al. [254] explored the impact of updates on LMs by analyzing snapshots before and after an update, revealing insights into changes in training data. Moreover, they introduced two metrics, differential score and differential rank, to assess data leakage in natural LMs. ProPILE was introduced as a tool for PII leakage in LLM and experimented on open pre-trained Transformer LMs (OPT-1.3B model [255]). It will ask for a specific PII, such as a personal contact number or SSN, in the designed LLM prompt by providing relevant information. Then, the LLM response may provide the requested information based on the linkability of the given information and the structure of the crafted prompt [100]. A universal PII leakage framework named *KART* has been introduced specifically for the biomedical domain [142]. Nakka et al. [143] proposed a PII leakage attack, termed *PII-compass*, by adding hand-crafted template to an attack prefix. These attack prefixes are associated with a different data subject from the adversary set, meaning that the data (attack prefix) used to create the new prompt originates from a different data subject whose PII is intended for extraction. Memorization is another aspect of PII attacks. Carlini et al. [20] demonstrated that LLMs memorize and leak individual training examples. They showed how a malicious party may query the LM (e.g., GPT-2) to execute a training data extraction attack and get specific training samples. Furthermore, several investigations revealed that PLMs have a high probability of disclosing private and confidential data, particularly when prompted for information such as e-mail addresses along with their contexts that include the owner's name. PLMs retain personal data, which means that the data may be retrieved using a certain prefix, such as training data tokens. PLMs link the owner of the personal information to it, thus attackers may query the data using the owner's identity [81].

Several shortcomings exist in the PII leakage attacks prevalent in the literature. For instance, Huang et al. [81] primarily focused on extracting e-mail addresses as representatives of personal information in their proposed memorization attack in PLM. On the contrary, PII-compass [143] is limited to only extracting phone numbers. Complete extraction of a PII set still requires significant exploration and proper methods. While some methods have been evaluated only on small Transformer-based LMs [86], others have been tested on earlier LLMs such as GPT-2 [20]. The performance of these methods (e.g., [81, 86]) on the latest LLMs, such as Llama 3 and GPT-4, still requires in-depth evaluation. Moreover, some of these methods may not perform well in the presence of defense mechanisms such as DP [1]. Thus, further research is necessary to develop attack methods that address these challenges in PII leakage attacks against LLMs.

6 Defense Mechanisms

Protecting LLMs from security and privacy attacks is imperative to preserve their reliability and integrity [148]. Here, we review existing studies to mitigate the LLM vulnerabilities and defend against emerging security and privacy threats.

6.1 Defense against Security Attacks on LLMs

Defense against Prompt Injection. Limited studies explored the defense strategy against prompt injection attacks in LLMs. A prevention/detection-based defense technique has been reported to systematically present existing defense mechanisms against prompt injection attacks [121]. Prevention-based defenses, as outlined in the work of Jain et al. [88], are designed to thwart the successful execution of tasks injected into an LLM-integrated application. These preventive measures involve pre-processing the data prompt to eliminate the injected task's instruction/data and/or redesigning the instruction prompt itself. To thwart adversarial prompts, there are several techniques, such as paraphrasing [88], re-tokenization [88], data prompt isolation, and instructional prevention [171]. Paraphrasing disrupts the sequence of injected data, such as injected instructions and special character insertion. Re-tokenization aims to break the sequence of injected instructions, task-ignoring text, special characters, and fake responses within a compromised data prompt. This disruption diminishes the efficacy of prompt injection attacks. Detection-based defenses are focused on determining the integrity of a given data prompt [88, 190, 215]. Notably, the proactive detection method [175] has proven effective in identifying instances of prompt injection attacks. Perplexity-based detection is a kind of prompt-based detection. The idea is to add information or instructions to a data prompt, which degrades its quality and leads to increased perplexity. Consequently, a data prompt is considered to be compromised if its perplexity exceeds a specified threshold [66]. Since an LLM-integrated application is tailored for a specific task, granting it prior knowledge of the anticipated response, detecting a compromised data prompt is feasible when the generated response deviates from the proper answer for the desired task [175]. For example, if the desired task is spam detection and the response does not align with "spam" or "non-spam," they imply a compromise. Notably, this defense is ineffective when the injected task and desired task share the same type (e.g., both being related to spam detection). Effective protection strategies against P2SQL injection attacks are available and may be incorporated into the LangChain framework as extensions [155]. For example, since P2SQL injection attacks can manipulate chatbots by arbitrarily executing different queries [155], controlling database roles and permissions to limit the execution of undesired SQL statements when accessing tables with sensitive information can be a viable technique to defend such attacks. Conversely, indirect attacks involve malicious input residing in the database, enabling interference with LLM-generated SQL queries and potentially undermining the effectiveness of these defenses. Liu et al. [123] performed an empirical study to comprehensively formalize and benchmark several prompt injection attacks and defenses. They found that the prevalent prevention-based and detection-based defense techniques are insufficient to mitigate the risks of advanced optimization-based attacks (e.g., JudgeDeceiver [185]).

As a built-in safety mechanism, pre-processing-based techniques, detecting and blocking the inputs or outputs, and semantic content filtering have been employed to prevent generating undesired or inappropriate contents from LLMs through jailbreaking attacks, which could effectively mitigate potential harm [131]. Kumar et al. [103] proposed an approach to apply a safety filter on the substrings of input prompts, which provides certifiable robustness guarantees. The drawback of this approach lies in the method's complexity, which increases proportionally with input prompt length. Wu et al. [229] propose a system-mode self-reminder to defend against jailbreaking attacks under pretending or role-playing scenarios, which can drastically reduce the jailbreaking success rate from 67.21% to 19.34%. One potential simple defense strategy is to identify the presence of "red-flagged" keywords [221], which strictly violates the usage policies of the LLM vendors, such as OpenAI [44]. Recently, Zhang et al. [262] proposed a goal prioritization technique that prioritizes generating harmless responses over helpful ones at the inference phase. This technique can significantly reduce the success rate of jailbreaking attacks in ChatGPT and Llama 2. However,

these basic defense mechanisms may not be sufficient to prevent jailbreaking attacks with carefully crafted tricky prompts, such as privilege escalation. Furthermore, preventing these attacks still poses a significant challenge because the effective defenses may impact model utility [110]. By far, SmoothLLM is an effective defense strategy against existing jailbreaking attacks proposed by Zou et al. [276]. It can be applied for mitigating the instruction-based attacks, such as AutoDAN [118], DAN [183], and PAIR [23]. It involves a two-step process. First, copies of a specified input prompt are duplicated and perturbed. Subsequently, the outputs produced for each perturbed copy are aggregated. The desiderata encompass four key properties: attack mitigation (reduces attack success rate 100% and 50% for Llama 2 and Vicuna, respectively), non-conservatism, efficiency (in terms of computational resources), and compatibility (different LLMs). For preventing the advanced attack methods, such as MSJ [108] and MasterKey [44], an unsafe prompt detection and filtering technique may effectively refuse to provide the inappropriate response intended by the adversary. However, self-reminder-based methods [232] can create robust defenses against more complex attacks, such as DeepInception [112]. However, the efficacy of these mitigation techniques has not yet been evaluated based on these specific attack methods mentioned. Meta introduced Llama Guard, an input-output tool to safeguard LLMs [84], designed to effectively mitigate jailbreaking attacks. Llama Guard incorporates a safety risk taxonomy and the applicable policy for data collection and training. The proposed perturbation function can be further optimized over various operations, such as insertion and swapping, to make defense stronger. To defend the multi-modal prompts against jailbreaking attacks, Nie et al. [147] recently proposed DiffPure, a diffusion model based countermeasure against the visual jailbreaking examples.

Defense against Backdoor Attack. Most of the existing research, such as the removal of backdoors by fine-tuning [177], model pruning [117], and detecting backdoors by inspecting activations [24], are based on backdoor defenses in the white-box setting. Fine-mixing is a mitigation approach designed to prevent backdoors in fine-tuned LMs. It utilizes pre-trained weights through two complementary techniques: (1) a two-step fine-tuning procedure that first combines backdoored weights that have been optimized using pre-trained weights on poisoned data and then refines the combined weights on a small collection of clean data, and (2) E-PUR, an embedding purification method, which addresses potential backdoors in word embeddings [261]. CUBE utilized a density clustering algorithm called *HDBSCAN* to accurately discern clusters within datasets and distinguish the poisoned samples from clean data [40]. By leveraging the capabilities of HDBSCAN [135], CUBE aims to provide an effective means of differentiating clusters associated with both normal and poisoned data. Strategies to defend the backdoor attacks in the black-box setting are still lacking [95]. Perturbation-based and perplexity-based defense methods are also adopted in the literature [141, 159, 245], such as RAP, which leverages word-based robustness-aware perturbation to identify poisoned samples [245], and ONION, which eliminates trigger words via empirical analysis of sentence perplexities [159]. These two methods can potentially be applied to defend against manually designed backdoor triggers such as ProAttack [264]. Masking-differential prompt (MDP) serves as an efficient, lightweight, and adaptable defense method against backdoor attacks in prompt-based language models, particularly in few-shot learning settings [235]. MDP exploits the observation that poisoned samples exhibit increased sensitivity to random masking compared to clean samples. When the trigger is (partially) masked, the language modeling probability of a poisoned sample tends to exhibit significant variations. However, MDP may be less effective on other PLMs (e.g., GPT-3 [17]) and NLP tasks (e.g., paraphrasing). Moreover, further studies can be performed to evaluate the performance of random masking-based defenses in PLMs when the available data are even scarcer (e.g., one or zero-shot settings [207, 213]). Again, MDP was proven to be effective for the earlier backdoor attacks; however, it might not safeguard

some advanced attacks such as BadPrompt [18] and BToP [239]. Leveraging techniques such as knowledge distillation [76], outlier-filtering [239], and fine-pruning [117] requires further exploration to mitigate the impacts of backdoor attacks. To defend against clean label backdoor triggers, such as LLMBkd [251], a trigger classification approach called *REACT* [251] has been performed significantly better than ONION [159] and RAP [245]. For the reasoning-based backdoor attacks, such as BadChain [236], shuffling model input might be a potential defense mechanism. Further, backdoor detection (CBD) [237], including backdoor patterns in training data to ensure robustness (RAB) [220] can be used to prevent backdoor attacks. Detecting anomalies in input data and parameter decontamination are also used to prevent the attacks executed during the training or fine-tuning phase, such as BadAgent [217]. Although these defense techniques are primarily proposed for detecting backdoors and mitigating the effects of attacks, most of them are evaluated either for LMs or in other domains (e.g., computer vision). The impact of these mitigation techniques has not yet been evaluated on recently evolved LLMs, such as GPT-4, and Llama 3.

Defense against Data Poisoning Attack. Few solutions exist to defend against poisoning attacks in LLMs. In general, data validation, filtering, cleaning, and anomaly detection techniques have been used to protect ML models from poisoning attacks [154]. A detection and filtering approach was designed to identify and filter poisoned data which is collected for performing supervised learning [12]. Empirical analysis has demonstrated that limiting the number of training epochs is a straightforward method for LMs to reduce the impact of data poisoning such as RoBERTa [209]. Identifying poison samples using perplexity can be another technique for small GPT-2 models [162] for sentiment analysis tasks. However, it may not identify poisons effectively; specifically, after inspecting the training data, more than half of the poisoned examples may remain unidentified. Filtering poisoned samples during training is also used in LMs to defend against data poisoning attacks [210]. Yan et al. [242] proposed a framework called *ParaFuzz* for poisoned sample detection for NLP models that leverages the interpretability of model predictions. The poisoned data points are often outliers in the training data distribution. Compared to benign training data, a model requires more time to learn the features of poisoned data. To defend against trojaning attacks in LMs (e.g., TROJAN^{LM} [258]), one possible defense technique is to adopt existing techniques from other domains such as images (e.g., STRIP [63]), detecting trigger-embedded inputs at inference phase [24, 33], and finding suspicious LMs and retrieving triggers during the model evaluation phase [27, 211]. Dataset curation techniques, such as removing near-duplicate poisoned samples, known triggers and payloads, and identifying anomalies, can help defend against manually inserted poisoned samples in training data [37]. These methods are potentially effective against poisoning attacks, such as you auto-complete me [172], AutoPoison [189], and TrojanPuzzle attack [4]. Fine-pruning can also be used as a defense against these attacks [117]. For the white-box attacks such as AgentPoison [29], perplexity filtering and query rephrasing [103] are utilized in the literature. Again, advanced attacks, such as NightShade [15], need advanced defense methods. While the mentioned defense strategies are mostly designed for LMs, some of them can be potentially applied to LLMs too. However, it still needs in-depth research to develop efficient defense methods against data poisoning attacks. Therefore, it requires effective defense methods that can make tradeoffs between model utility and the capability of protecting LLMs from data poisoning attacks.

6.2 Defense against Privacy Attacks on LLMs

Defense against Gradient Leakage Attack. There are several mitigation strategies to defend against gradient-based attack methods in LMs, such as random noise insertion to the gradients [224], DP [1, 65], and homomorphic encryption [10]. DP is the most common and effective technique to mitigate the effect of gradient leakage attacks in DNNs. The fundamental idea of using DP is to add a controlled amount of noise to the model updates during training, which limits the

model's ability to memorize and reproduce original sequences from the training data [86]. Building upon prior research on vision model attacks [224, 273], the defense mechanisms involving the addition of Gaussian or Laplacian noise to gradients and DP-SGD (Stochastic Gradient Descent) coupled with additional clipping [1] may provide an effective defense against gradient leakage attacks. For example, DP can efficiently mitigate the impact of TAB [86] by reducing the number of unique training sequences leaked by Transformer-based LMs. TAB depends on black-box access to the model—that is, the model's top-k predictions at each token position given an input prefix. Ensuring no access to the model's underlying probability distributions through API hardening techniques [86] may potentially mitigate the impact of such attacks. Moreover, the attack strategy for successfully reconstructing private training data may differ between well-trained models and inadequately trained models. An effective mitigation technique could involve robust model optimization during training so that adversarial perturbations have minimum impact [256]. However, DP may sacrifice the model's utility to a certain extent during training. Trading off preserving privacy and model utility may raise a significant challenge for preventing gradient leakage attacks against LLMs. Existing works explored various techniques (e.g., [81, 163, 230]) to defend against gradient leakage attacks in the language domain for small NLP models. Extensive research is required to develop defense mechanisms against gradient leakage attacks on LLMs.

Defense against MIA To mitigate MIA in the language domain, several mechanisms are proposed, including dropout, auto-identification [204], model stacking, DP [1], and adversarial regularization [144]. Salem et al. [170] came up with the first effective defense mechanism against MIA. Their approach included dropout and model stacking. In each training iteration of a fully connected neural network model, dropout is defined as the random deletion of a certain proportion of neuron connections. It can mitigate overfitting in DNNs, which is a contributing factor to MIA [170]. However, this technique works only when a neural network is targeted by the attack model. To work with other target models, they proposed another defense technique referred to as model stacking. To defend against black-box MIA on ML models, Jia et al. [91] proposed MemGuard, which is essentially a noise perturbation mechanism for the predicted confidence score of the target model. However, this technique has been evaluated for image and numeric datasets. The performance of this technique on LMs/LLMs still remains unexplored, which necessitates further studies to evaluate whether it can effectively defend against MIA for LMs/LLMs. DP-based techniques are also widely used to prevent privacy leakage by MIA [111, 133]. Models facilitated with DP employed with the SGD optimization algorithm [51] can reduce empirical privacy leakages while ensuring comparable model utility in the non-DP environment [87]. Model pruning [71] and knowledge distillation [76] are employed to mitigate the impacts of preference-based MIA, such as PREMIA [55]. A recent framework, InferDPT [201], has been proposed to leverage black-box LLMs to facilitate privacy-preserving inference, which effectively integrates DP in text generation tasks. Another potential defense method against MIAs is regularization, which refers to a set of techniques used to prevent overfitting and improve the generalization performance of an ML model. Label smoothing [197] is one kind of regularization method that prevents overfitting of the ML model, which contributes to MIA [250]. Very few defense techniques have been proposed for LLMs [60, 111]. Most of the existing defense techniques have been experimented on relatively small LMs, such as test classifiers [214], which are not evaluated for LLMs. Moreover, DP-based defenses may impair model utility. We argue that there is a pressing need for further research studies to develop effective defense techniques against MIA on LLMs.

Defenses against PII Leakage Attacks. To mitigate the leaking of personal information from PLMs due to memorization [20], there are several general techniques. During the pre-processing phase, the process of de-duplication and training data curation [37] has the potential to

significantly decrease the amount of memorized text in PLMs. Prompt-tuning can also be a potential mitigation against memorization. The basic idea is to optimize prompts in the attack environment to evaluate the capability to extract the memorized content in a target model. DP can efficiently mitigate the impact of TAB [86] and KART [142] by minimizing the number of unique training sequences leaked by Transformer-based LMs. Both TAB and KART require the black-box access of the model, such as top-k predictions; therefore, restricting the model access by imposing API hardening technique [86] can also be a potential mitigation technique for these kinds of attacks. DP can also mitigate the attacks, which include hand-crafted prompts with a true prefix [143]. PII masking [129] can also be a viable technique to defend against PII leakage attacks. Personal information identification and filtering methods (e.g., [37, 165]) may effectively reduce the number of training data samples extracted through PII leakage attacks, such as ProPILE [100]. However, manually checking the vast training data for LLMs is challenging and labor intensive. De-duplication at the document or paragraph level is common but may not eliminate repeated occurrences of sensitive information within a single document. Advanced strategies for de-duplication and careful sourcing of training data are essential. Despite sanitization efforts, complete prevention of privacy leaks is challenging, making it a first line of defense rather than a foolproof measure. In training, following the process of Carlini et al. [20] and the implementation by Anil et al. [9], the DP-SGD algorithm [1] can be employed to ensure privacy of training data during the training process [20, 85]. However, the DP-SGD-based method might not work efficiently, as it has a significant computational cost and decreases the trained model utility [254]. PII scrubbing filters the dataset to eliminate PII from text [46], such as leveraging named entity recognition [105] to tag PII. Even though PII scrubbing methods can mitigate PII leakage risks, they face two critical challenges [125]: (1) the effectiveness of PII scrubbing may be reduced to preserve the dataset utility, and (2) there is a risk of PII not being completely or accurately removed from the dataset. In downstream applications, such as dialogue systems [259] and summarization models [77], LMs undergo fine-tuning on task-specific data. While this process may lead to the LM "forgetting"some memorized data from pre-training [134, 164], it can still introduce privacy leaks if the task-specific data contains sensitive information.

The aforementioned defense techniques mostly apply to the LMs. While according to recent studies [107, 248], the existing strategies can be used in the LLM context as well; however, to date, there are no efficient defense techniques introduced to defend against a few attack methods, such as KART [142], ProPILE [100], and the recovery of forgotten PII by fine-tuning due to memorization [28]. Therefore, in-depth studies and understanding are required to design effective defense techniques against PII attacks on LLMs.

7 Application-Based Risks in LLMs

LLMs are emerging techniques with high potential for many applications. The security and privacy vulnerabilities of LLMs may raise serious concerns and risks in their real-world deployment, with varying impacts on different application domains [141].

Complicated Human Interaction. LLM undergoes training on extensive text corpora and inherently possesses knowledge across diverse tasks. Carefully crafted prompts can potentially extract valuable and accurate knowledge from LLMs, which requires exploring and developing effective prompt engineering techniques [193]. Despite the ideal scenario of envisioning automated prompt generation through human-machine interaction, it is highly important to study the ethical issues and limitations of this approach [225]. Hence, reliance on LLMs may potentially shift the entry barrier from coding and ML expertise to proficiency in prompt engineering.

Hallucination, Misinformation, and Disinformation Dissemination. LLMs are renowned for generating sound output that may incorporate hallucinated knowledge, falsification [89],

misinterpretation [8], and biasness [41], which pose challenges in distinguishing it from facts. Catastrophic forgetting is a problem where a neural network forgets information it previously learned after being trained on a new task. In LLM fine-tuning, it might deteriorate the performance to a significant extent [128]. Deploying LLMs also carries risks, especially in sensitive areas, such as legal or medical advice, where misinformation can lead to serious consequences, such as illegal actions and harmful medical decisions [153]. Simultaneously, the intentional dissemination of fake news and disinformation carries severe implications, influencing public perception and decision-making processes and contributing to societal discord [227]. The dynamic nature of information dissemination in the digital age magnifies these risks, necessitating the development of robust fact-checking mechanisms, ethical guidelines for content generation, and responsible deployment practices for LLMs. In defense, hallucination mitigation can be applied at both training (e.g., data curation [243] and knowledge enhancement [79]) and inference stages (e.g., uncertainty measurement [83], knowledge retrieval [57], and self-familiarity [127]). Recent studies have introduced several countermeasures, such as the chain of verification (COVE [48]) and self-reflection [90], to detect LLM-generated hallucinations and misinformation [25, 31]. These techniques offer potential remedies for the issues mentioned previously; however, further exploration is necessary to fully address these challenges. To address catastrophic forgetting, learning rate scheduling (LR-Adjust [93, 228, 233]) serves as a viable mitigation technique. Self-Synthesized Rehearsal [82] is another approach to mitigate this issue. Self-Synthesized Rehearsal employs a base LLM to generate synthetic instances for in-context learning, which is then refined by the latest LLM, preserving its learning ability.

Cybercrime and Social Issues. LLMs can potentially be used in various cybercrime [102], such as phishing (efficiently create targeted scam e-mails), malware, and hacking attacks (hackers have used ChatGPT to write malware codes). LLMs pose risks of perpetuating unfair discrimination and causing representational harm by reinforcing stereotypes and social biases. Harmful associations of specific traits with social identities may lead to exclusion or marginalization of individuals outside established norms [225]. Further, toxic language generated by LLMs may incite hate or violence and cause serious offense. These risks are largely rooted in the selection of training corpora that include harmful language and disproportionately represent certain social identities.

Transportation. In the transportation domain, studies reported that LLM could be biased (accident report analysis) and inefficient for performing tasks in self-driving cars [199]. Further, it might leak personal data from self-driving cars while doing accident report automation and accident information extraction [269]. A framework has been proposed named *VistaGPT* to deal with the problems caused by information barriers from heterogeneity at both system and module levels in a wide range of heterogeneous vehicle automation systems [200]. It leverages LLMs to create an automated composing platform to design end-to-end driving systems. This involves employing a "dividing and recombining" strategy to enhance the ability to generalize. To address the issue of the long training time of LLMs with large datasets and high computing resource requirements, Meta-AI's Llama focuses on fine-tuning offline pre-trained LLMs to handle the transportation safety domain tasks. The main objective is to create a specialized LLM capable of generating an accurate, context-sensitive, and safety-aware model that works effectively in traffic-related scenarios [270].

Healthcare and Medicine. According to De Angelis et al. [43], LLMs' high risks in healthcare suggest that their integration into the healthcare system is challenging. Models trained on extensive Internet data lacking rigorous filtering mechanisms may incorporate misinformation, biased content, and harmful materials alongside accurate and fair information, thereby posing significant risks in healthcare applications. The potential results of erroneous treatment or medication recommendations by LLMs are concerning. The probabilistic nature of LLMs introduces variability in

response to the same task and challenges in reliability and reproducibility that necessitate continuous human oversight. Privacy concerns over sensitive health records, including AI ethics, safety, transparency, and equity, highlight the need for caution when using LLMs in healthcare [72].

Education. The use of LLMs (e.g., ChatGPT) in education poses significant drawbacks, particularly in fostering inaccurate concept learning and an inappropriate approach to education. ChatGPT, being an LM trained on diverse Internet data, may unintentionally propagate contents with a lack of precision and educational rigor—for instance, scientific misconduct [141]. The excessive dependence on LLMs by both educators and learners can have serious adverse effects. Students engaging with ChatGPT may encounter misleading content or promote misconceptions, potentially compromising the quality of their learning experience. The absence of a real-time fact-checking tool and the model's susceptibility to biases and errors pose risks, potentially leading learners astray and impeding their overall educational progress. Consequently, caution is recommended when relying on ChatGPT as an educational tool without appropriate supervision [137, 176].

Governance. The potential misuse of LLMs in governance for spear phishing presents significant cybersecurity challenges. Using GPT-4 as an illustrative example, personal information of British members of parliament was extracted from Wikipedia, and GPT-3.5 was utilized to generate biographies, which were then incorporated into phishing e-mails sent to official e-mail addresses [73]. This highlights the risks associated with misinformation, biased content, and the utilization of LLMs in AI-based cyberattacks within governance. The leakage of confidential information through such attacks can pose severe consequences for national security. The generation of misinformation and hate speech by LLMs further deteriorates the existing challenges, underscoring the imperative need for robust safeguards and countermeasures to address the risks related to the usage of these models in governance settings [73].

Science. Hallucinations, biases, and paradigm shifts are pressing concerns of LLMs in the science domain. There is a risk of LLMs generating non-existent and false content—for example, Meta developed an LLM named *Galactica* for reasoning scientific knowledge. It might generate major flaws due to reproducing biases and presenting falsehoods [38]. As a result, the model was shut down just after launching public access [75]. Another concern lies in the involvement of LLMs in the scientific discovery process. It is challenging to interpret and understand LLMs due to their black-box nature, raising doubts about their reliability and trustworthiness in the science domain. For example, peer-review reports generated by LLMs may misinterpret research articles, which may impair the peer review quality [2]. Elaborate principles of using LLMs and/or other AI tools in scientific explorations should be established to ensure transparency, fairness, and trustworthiness [13].

8 Limitations of Existing Works and Future Research Directions

Following a comprehensive examination of prevailing security and privacy attacks and defense mechanisms, this section delves into the prospects of advancing secure and privacy-preserving LLMs. In Figure 9, we show an overview of the evolution of attack methods and defense mechanisms in LLMs, their limitations, and future research directions. We then discuss the limitations of existing security and privacy attacks and defenses and their research prospects.

Existing Attack Methods, Their Limitations, and Future Research Directions. In LLMs, various categories of security and privacy attacks have emerged, posing significant risks to these systems. Among security attacks, prompt injection is a prominent technique in which attackers craft malicious prompts, either manually [121] or automatically [187], to mislead the LLM into generating inappropriate or harmful outputs. Jailbreaking attacks involve creating malicious prompts in tricky way [194], such as character role-play [70] and attention shifting [124], so that the LLM generates inappropriate/harmful contents. Data poisoning attacks involve the insertion




Fig. 9. Overview of attack and defense mechanisms in LLMs, their limitations, and future research directions.

of malicious data samples during the model's training/fine-tuning phases [104, 210], introducing biases or vulnerabilities that compromise the model's functionality. Similarly, backdoor attacks introduce hidden "backdoors" (via trojaning) during the training/fine-tuning phase [184], activated by the presence of backdoor triggering words in the prompts. LLM privacy attacks focus on extracting sensitive information such as private training/fine-tuning data, personal information, and even model components (e.g., gradients or model architecture). The techniques used in these attacks include gradient leakage attacks [45], MIA [188], and PII leakage attacks [143].

The majority of the existing studies on jailbreaking attacks are primarily focused on ChatGPT [44, 108, 183]. It remains unclear whether potential vulnerabilities exist in other LLMs, such as Vicuna [32], Gemini [130], and Bing Chat [136]. For example, MasterKey [44] may not achieve comparable performance on Vicuna as it does on ChatGPT. For prompt-based attacks, manual prompts are often more effective than automated prompt-based attack methods. As automated attack methods are primarily designed for generalized tasks, they may not demonstrate the same effectiveness for specific tasks as manually crafted prompts. The unlabeled and imbalanced real-world data further complicate the development of effective automated prompting-based attack methods [187]. Most of the backdoor attacks [18] are focused on classification or similar tasks. More attention should be paid to the attacks on other NLP tasks, including question-answering, text summarization, and translation. Privacy attacks rely on the correlation between an adversary's access level and their ability to extract sensitive information or manipulate target LLMs [107]. For instance, when the adversary has access only to the black-box model, the attacker might be able to leverage training data extraction attacks to recover a limited set of private data. Upon the adversary's access to white-box information, such as gradients, it can leverage this extra information to efficiently recover more private training instances more accurately [45]. This expanded access can facilitate various privacy attacks, including attribute inference attacks, embedding inversion, MIA, and gradient leakage attacks. Availing the white-box information of a model for an adversary is sometimes impractical in real-world practice. However, most of the existing privacy attacks are designed for vision models. A limited number of studies have reported gradient leakage attacks specifically on LMs, such as the LAMP attack [11]. The evaluation dataset for some attacks (e.g., ProPILE) was built solely from private information available in open source datasets provided by major corporations, ensuring ethical data acquisition [100]. However, it is crucial to note that the heuristic data collection process might potentially lead to instances of bias, disassociation, or noise. This adds uncertainty and potential inaccuracies in the benchmark

dataset, requiring attention when interpreting the results. Furthermore, most attack methods (e.g., BadGPT, BadPrompt, and trojaning attacks) described in the existing studies are designed for only relatively small NLP models. Only a few are tested on LLMs (e.g., ProPILE, DAN, and JAILBREAKER). In addition, the high cost of accessing commercialized LLMs, such as GPT-3.5 or upper versions, contributes to the lack of attack evaluations on LLMs. Besides, the in-depth vulnerability analysis in terms of privacy attacks and security issues is still lacking for LLMs. As well, in the FL environment, it requires very high computational power to train LLMs with such large datasets [195]. It is an open research challenge to develop effective attack and robust defense methods along with the proper evaluation metrics for LLMs. Due to the knowledge gaps, for instance, missing or outdated information might always be present in LLMs. The correctness of LLM-generated content has remained a key concern. The problem of hallucination in LLMs has been investigated and evaluated from the knowledge gap perspective; however, it is yet to be investigated from other perspectives, such as safety (i.e., abstaining from generating harmful content) [22].

For LLMs, future research should examine the applicability of well-established attack methods from other domains, such as computer vision. In addition to existing methods, novel attack techniques should be developed to rigorously inspect various vulnerabilities of LLMs, potentially targeting multiple objectives with a single attack approach. Moreover, special attention should be given to developing appropriate metrics for evaluating the impact of vulnerabilities related to security and privacy attacks in LLMs. **Explainable AI (XAI)** can play a vital role in this domain by increasing transparency and explainability within attack systems, allowing for a better understanding of LLM vulnerabilities. Developing XAI techniques to enhance the interpretability of LLM vulnerabilities is another essential research direction for advancing the security and privacy of LLMs.

Existing Defense Mechanisms, Challenges, and Future Research Directions. To mitigate vulnerabilities posed by security and privacy attacks, various defense techniques have been proposed in existing research. Instruction defense [171], paraphrasing [88], and re-tokenization [88] methods are commonly employed to defend against prompt injection attacks. To prevent jailbreaking attacks, SmoothLLM [168], LLM Guard [5], and perplexity filtering [66] are widely used. Data curation techniques [243], including filtering poisoned content [210] and detecting trigger-embedded inputs [24], are frequently used to mitigate data poisoning attacks and backdoor attacks. However, DP-SGD [1] is a common approach to defend against gradient leakage attacks, MIAs, and PII leakage attacks. In particular, noise perturbation [273] is a popular strategy to defend against gradient leakage attacks. Model pruning [117] and knowledge distillation [76] are also utilized to defend MIAs. To prevent PII leakage attacks, training data curation [243] and restricting attacker access to training data, or a model [86], serve as viable countermeasures.

For defense, although ChatGPT's safety protocols are typically robust enough to prevent single-step jailbreaking prompts, vulnerabilities still remain for MSJ [108]. Inspired by the reasoning processes of LLMs, system-mode self-reminder techniques have emerged as potential defense [235]. While drawbacks of self-reminder have been explored in user queries across various NLP tasks, assessing its impact across all types of user interactions remains challenging, complicating the evaluation of its influence on overall user experience [229]. Considering these shortcomings, developing more flexible self-reminding systems that improve safety, trustworthiness, and accountability in LLMs without compromising effectiveness is a research challenge to protect LLMs from jailbreaking attacks. Furthermore, individuals with malicious intent are highly active in online forums, discussing new strategies. It is essential to conduct further research to identify and implement effective defense strategies to mitigate the risks posed by the latest jailbreaking attacks. Efficient strategies to prevent backdoor attacks in a black-box environment are still lacking [95].

Moreover, prompt-based PLMs are susceptible to textual backdoor attacks [49, 239]. Addressing the challenge of textual backdoor attacks in prompt-based paradigms, such as the few-shot learning [218], is another challenge. MDP [235] faces challenges in various NLP tasks, such as paraphrasing and sentence similarity [62]. Its performance under few-shot learning remains uncertain due to a lack of practical evaluation. While MDP has shown strength against earlier backdoor attacks, it may not be effective against more recent attacks, such as BadPrompt [18] and BToP [239]. Perplexity-based methods and filtering-based methods may not work well when attackers use synonymous trigger keys [80]. Furthermore, developing dynamic defense methods that consider the preceding factors is a challenging task for the future. Currently, the predominant focus of investigation on backdoor attacks revolves around text classification in LLMs. However, a significant gap exists in the literature concerning investigations into mitigation to backdoor attacks on various tasks for which LLMs find widespread application, such as text summarization and text generation [244]. For poisoning attacks, there is not yet effective mitigation for ProAttack [264] and BadPrompt [18]. Defense techniques, such as dataset cleaning and removing near duplicate poisoned samples and anomalies, may slow down the model development process to defend against data poisoning attacks. Other defense methods, such as stopping training after certain epochs, achieve a moderate defense against poisoning attacks but degrade the model utility [210]. Gradient perturbation [78] and DP-SGD-based methods [1] are frequently used to defend against privacy attacks in LLMs. However, a recent study has demonstrated that adding a standard level of random noise into the gradient update might not always work well to prevent gradient leakage attacks on medical images [42]. An open language model (OLMo) has been introduced to provide access to the data, code, and model [191] to facilitate open research on LMs. While adhering to established practices for obscuring PII exposure and removing toxic content, the approach lacks explicit discussion of attack impacts and risk mitigation explored in this survey. Future research could leverage secure multi-party computation [39] to counter privacy attacks.

Future research initiatives for enhancing security and privacy in LLMs can be directed toward several key areas. An ideal defense method should be able to effectively achieve a balance between model utility and security and privacy protection. The development of real-time privacy monitoring systems is essential to improve the resilience of privacy-preserving LLMs. This necessitates the exploration of robust detection techniques against various security and privacy attacks. Furthermore, a thorough evaluation of less-explored defense techniques, such as secure multi-party computation, is necessary to assess their effectiveness against LLM vulnerabilities. Finally, leveraging the capabilities of XAI can improve transparency in LLM defense mechanisms.

Role of XAI in Enhancing Security and Privacy of LLMs. The LLM's ability to make decisions on various learning tasks is often criticized due to its black-box nature (e.g., non-interpretable weights). It makes it more challenging for the new practitioners and developers of this field, as it hinders their ability to clearly interpret and understand its application, particularly in critical cases. XAI can help to bridge this gap by developing methods to interpret and explain complex LLM systems, the decision-making process, and outputs [19]. Conducting studies and research to build explainable methods is highly essential to make the usage of LLMs more reliable and trustworthy. XAI can provide transparent insights into the inference process and the dynamic weight assignment by the attention mechanism of the LLMs, which enhances interpretability by highlighting the most influential input features that contribute to its predictions. This explainability makes the model more trustworthy and ensures that its output is explainable. XAI has shown its potential in several real-world AI applications, such as cybersecurity [169] and enhancing data privacy [53]. In ML, several techniques exist, such as LIME (*L*ocal *I*nterpretable *M*odel-agnostic *E*xplanations) [167] and SHAP (*SH*apley *A*dditive ex*P*lanations) [126], which offer insights into model behavior

without accessing internal model components. The explainability of code generation models, such as CodeBERT [56] and GraphCodeBERT [69], was proposed to understand code syntax and semantics [246]. In addition, the ad-hoc explanation further clarifies the model's decision [116].

The role of XAI in the security and privacy aspect of LLM is crucial. Specifically in its development phase, having prior knowledge about the attackers' ability (e.g., model's black-box access, injecting poisonous instances to the training/fine-tuning data) and the vulnerable components (training/fine-tuning data and the model itself) of LLM systems will assist in developing robust techniques against security and privacy attacks. However, XAI may expose critical aspects of the LLMs, including their architecture, components, and the dynamic weight allocation by the attention mechanism that contribute to predictions. For example, revealing the white-box nature of the model may facilitate the attacker's access to the model, increasing the risk of gradient leakage attacks or MIA [53]. Lin et al. [115] proposed an XAI approach that can identify the triggers (backdoor attack) that mislead the model to contribute to classification errors. An XAI technique is developed by Li et al. [115] to identify and quantify the influence of raw data features on successful MIAs. This approach identifies the influential neurons contributing to compromising private data and subsequently trains an MIA ensemble model using attack features derived from the selected neurons [115]. XAI techniques in image models (e.g., Grad-CAM [174]) may compromise model privacy under various attacks, such as gradient leakage attacks and MIA. In some cases, XAI enables more accurate reconstruction of private training data compared to models that rely solely on predictions [266]. XAI-aware model extraction attack (XaMEA) was proposed to exploit spatial knowledge from decision explanations [241]. It illustrated that the transparency provided by XAI may facilitate the attacker's access to the model, making it easier to exploit it. This increased explainability can make the model more vulnerable to model extraction attacks compared to prediction only models. However, the vulnerabilities mentioned previously are mostly explored for DNNs. In LLMs, the vulnerabilities in the XAI context have been explored to a limited extent. Moreover, several unique characteristics of LLMs are different from DNNs, such as large-scale data and model parameters, task-agnostic, and semantic language understanding, which make it more challenging to design XAI methods for better interpretations. The comprehensive interpretation of LLM vulnerabilities under XAI, including backdoor attacks, MIAs, and model extraction attacks, has yet to be fully explored. Additionally, vulnerabilities related to prompt injection and jailbreaking attacks in the context of XAI still remain unexplored. Furthermore, open source LLMs are publicly accessible and may provide greater explainability than closed source models. However, this enhanced accessibility can make them more vulnerable to attacks when XAI techniques are employed. Thus, these LLMs may be more susceptible to attacks due to XAI. Further research is essential to fully understand the extent and impact of attackers' capabilities under XAI. Additionally, mitigation techniques should be developed in accordance with the identified risks and impacts.

9 Conclusion

LLMs lend themselves as strong tools for comprehending complex linguistic patterns and generating logical and contextually coherent responses. However, such powerful models also entail potential security and privacy risks. In this survey, we first provided a detailed overview of LLMs' security and privacy challenges. We then discussed and analyzed the LLM vulnerabilities from both security and privacy aspects, existing mitigation and defense strategies against these security attacks and privacy attacks, as well as highlighted their strengths and limitations. In our investigation, we found that LLMs are highly vulnerable to the discussed attacks. The existing mitigation techniques that are applicable to relatively small LMs could potentially be used for LLMs. However, extensive research is needed to evaluate and tailor the existing solutions to LLMs. Based on our analysis, we outlined future research directions focusing on security and privacy aspects, pointed

out key research gaps, and illustrated open research problems. The overarching goal is to enhance the reliability and utility of LLMs by comprehensively exploring and addressing these vulnerabilities while providing pathways for future research toward secure and privacy-preserving LLM systems.

References

[1] Martin Abadi, Andy Chu, Ian Goodfellow, H. Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. 2016. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security*. 308–318.

[2] Abeba Birhane, Atoosa Kasirzadeh, David Leslie, and Sandra Wachter. 2023. Science in the age of large language models. *Nature Reviews Physics* 5 (2023), 277–280.

[3] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. GPT-4 technical report. *arXiv preprint arXiv:2303.08774* (2023).

[4] Hojjat Aghakhani, Wei Dai, Andre Manoel, Xavier Fernandes, Anant Kharkar, Christopher Kruegel, Giovanni Vigna, David Evans, Ben Zorn, and Robert Sim. 2024. TrojanPuzzle: Covertly poisoning code-suggestion models. In *Proceedings of the IEEE Symposium on Security and Privacy (SP'24)*. 1122–1140.

[5] Protect AI. 2024. LLM Guard: The Security Toolkit for LLM Interactions. Retrieved January 16, 2025 from https://protectai.com/llm-guard

[6] Alex Albert. 2023. Jailbreak Chat. Retrieved January 16, 2025 from https://www.jailbreakchat.com

[7] Gabriel Alon and Michael Kamfonas. 2023. Detecting language model attacks with perplexity. *arXiv preprint arXiv:2308.14132* (2023).

[8] Thimira Amaratunga. 2023. Threats, opportunities, and misconceptions. In *Understanding Large Language Models: Learning Their Underlying Concepts and Technologies*. Springer, 131–148.

[9] Rohan Anil, Badih Ghazi, Vineet Gupta, Ravi Kumar, and Pasin Manurangsi. 2021. Large-scale differentially private BERT. *arXiv preprint arXiv:2108.01624* (2021).

[10] Yoshinori Aono, Yoshinori Aono, Takuya Hayashi, Lihua Wang, and Shiho Moriai. 2017. Privacy-preserving deep learning via additively homomorphic encryption. *IEEE Transactions on Information Forensics and Security* 13, 5 (2017), 1333–1345.

[11] Mislav Balunovic, Dimitar Dimitrov, Nikola Jovanović, and Martin Vechev. 2022. LAMP: Extracting text from gradients with language model priors. *Advances in Neural Information Processing Systems* 35 (2022), 7641–7654.

[12] Nathalie Baracaldo, Bryant Chen, Heiko Ludwig, and Jaehoon Amir Safavi. 2017. Mitigating poisoning attacks on machine learning models: A data provenance based approach. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*. 103–110.

[13] Marcel Binz, Stephan Alaniz, Adina Roskies, Balazs Aczel, Carl T. Bergstrom, Colin Allen, Daniel Schad, Dirk Wulff, Jevin D. West, Quiong Zhang, et al. 2023. How should the advent of large language models affect the practice of science? *arXiv preprint arXiv:2312.03759* (2023).

[14] Rob Bonta. 2023. California Consumer Privacy Act (CCPA). Retrieved January 16, 2025 from https://oag.ca.gov/privacy/ccpa

[15] Samuel R. Bowman. 2023. Eight things to know about large language models. *arXiv preprint arXiv:2304.00612* (2023).

[16] Hezekiah J. Branch, Jonathan Rodriguez Cefalu, Jeremy McHugh, Leyla Hujer, Aditya Bahl, Daniel del Castillo Iglesias, Ron Heichman, and Ramesh Darwishi. 2022. Evaluating the susceptibility of pre-trained language models via handcrafted adversarial examples. *arXiv preprint arXiv:2209.02128* (2022).

[17] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in Neural Information Processing Systems* 33 (2020), 1877–1901.

[18] Xiangrui Cai, Haidong Xu, Sihan Xu, Ying Zhang, and Xiaojie Yuan. 2022. BadPrompt: Backdoor attacks on continuous prompts. *Advances in Neural Information Processing Systems* 35 (2022), 37068–37080.

[19] Erik Cambria, Lorenzo Malandri, Fabio Mercorio, Navid Nobani, and Andrea Seveso. 2024. XAI meets LLMs: A survey of the relation between explainable AI and large language models. *arXiv preprint arXiv:2407.15248* (2024).

[20] Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. 2021. Extracting training data from large language models. In *Proceedings of the 30th USENIX Security Symposium (USENIX Security'21)*. 2633–2650.

[21] Computer Security Resource Center. 2023. Information Systems Security (INFOSEC). Retrieved January 16, 2025 from https://csrc.nist.gov/glossary/term/information_systems_security

[22] Edward Y. Chang. 2024. SocraSynth: Multi-LLM reasoning with conditional statistics. *arXiv preprint arXiv:2402.06634* (2024).
[23] Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J. Pappas, and Eric Wong. 2023. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419* (2023).
[24] Bryant Chen, Wilka Carvalho, Nathalie Baracaldo, Heiko Ludwig, Benjamin Edwards, Taesung Lee, Ian Molloy, and Biplav Srivastava. 2018. Detecting backdoor attacks on deep neural networks by activation clustering. *arXiv preprint arXiv:1811.03728* (2018).
[25] Canyu Chen and Kai Shu. 2023. Can LLM-generated misinformation be detected? *arXiv preprint arXiv:2309.13788* (2023).
[26] Guiming Hardy Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. 2024. Humans or LLMs as the judge? A study on judgement biases. *arXiv preprint arXiv:2402.10669* (2024).
[27] Huili Chen, Cheng Fu, Jishen Zhao, and Farinaz Koushanfar. 2019. DeepInspect: A black-box Trojan detection and mitigation framework for deep neural networks. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI'19)*. 4658–4664.
[28] Xiaoyi Chen, Siyuan Teng, Rui Zhu, Shijun Yan, Lei Jin, Zihao Wang, Liya Su, Zhikun Zhang, XiaoFeng Wang, and Haixu Tang. 2024. The Janus interface: How fine-tuning in large language models amplifies the privacy risks. In *Proceedings of the ACM SIGSAC Conference on Computer and Communications Security*. 1285–1299.
[29] Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. 2024. AgentPoison: Red-teaming LLM agents via poisoning memory or knowledge bases. *arXiv preprint arXiv:2407.12784* (2024).
[30] Vivying S. Y. Cheng and Patrick C. K. Hung. 2006. Health Insurance Portability and Accountability Act (HIPPA) compliant access control model for web services. *International Journal of Healthcare Information Systems and Informatics* 1, 1 (2006), 22–39.
[31] I.-Chun Chern, Steffi Chern, Shiqi Chen, Weizhe Yuan, Kehua Feng, Chunting Zhou, Junxian He, Graham Neubig, and Pengfei Liu. 2023. FacTool: Factuality detection in generative AI—A tool augmented framework for multi-task and multi-domain scenarios. *arXiv preprint arXiv:2307.13528* (2023).
[32] The Vicuna Team. 2023. Vicuna: An Open-Source Chatbot Impressing GPT-4 with 90%* ChatGPT Quality. Retrieved April 14, 2023 from https://vicuna.lmsys.org
[33] Edward Chou, Florian Tramer, and Giancarlo Pellegrino. 2020. SentiNet: Detecting localized universal attacks against deep learning systems. In *Proceedings of the 2020 IEEE Security and Privacy Workshops (SPW'20)*. 48–54.
[34] Junjie Chu, Yugeng Liu, Ziqing Yang, Xinyue Shen, Michael Backes, and Yang Zhang. 2024. Comprehensive assessment of jailbreak attacks against LLMs. *arXiv preprint arXiv:2402.05668* (2024).
[35] Benjamin Clavié, Alexandru Ciceu, Frederick Naylor, Guillaume Soulie, and Thomas Brightwell. 2023. Large language models in the workplace: A case study on prompt engineering for job type classification. In *Proceedings of the International Conference on Applications of Natural Language to Information Systems*. 3–17.
[36] Cloudflare. 2023. What Is Data Privacy? Retrieved January 16, 2025 from https://www.cloudflare.com/learning/privacy/what-is-data-privacy/
[37] Andrea Continella, Yanick Fratantonio, Martina Lindorfer, Alessandro Puccetti, Ali Zand, Christopher Kruegel, and Giovanni Vigna. 2017. Obfuscation-resilient privacy leak detection for mobile apps through differential analysis. In *Proceedings of the Network and Distributed System Security Symposium (NDSS'17)*. 1–15.
[38] Aaron J. Snoswell and Jean Burgess. 2022. The Galactica AI model was trained on scientific knowledge—But it spat out alarmingly plausible nonsense. *The Conversation*. Retrieved January 16, 2025 from https://theconversation.com/the-galactica-ai-model-was-trained-on-scientific-knowledge-but-it-spat-out-alarmlingly-plausible-nonsense-195445
[39] Ronald Cramer, Ivan Bjerre Damgård, and Jesper Buus Nielsen. 2015. *Secure Multiparty Computation and Secret Sharing*. Cambridge University Press.
[40] Ganqu Cui, Lifan Yuan, Bingxiang He, Yangyi Chen, Zhiyuan Liu, and Maosong Sun. 2022. A unified evaluation of textual backdoor learning: Frameworks and benchmarks. *Advances in Neural Information Processing Systems* 35 (2022), 5009–5023.
[41] Sunhao Dai, Chen Xu, Shicheng Xu, Liang Pang, Zhenhua Dong, and Jun Xu. 2024. Bias and unfairness in information retrieval systems: New challenges in the LLM era. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 6437–6447.
[42] Badhan Chandra Das, M. Hadi Amini, and Yanzhao Wu. 2023. Privacy risks analysis and mitigation in federated learning for medical images. In *Proceedings of the 2023 IEEE International Conference on Bioinformatics and Biomedicine (BIBM'23)*. IEEE, 1870–1873.
[43] Luigi De Angelis, Francesco Baglivo, Guglielmo Arzilli, Gaetano Pierpaolo Privitera, Paolo Ferragina, Alberto Eugenio Tozzi, and Caterina Rizzo. 2023. ChatGPT and the rise of large language models: The new AI-driven infodemic threat in public health. *Frontiers in Public Health* 11 (2023), 1166120.

[44] Gelei Deng, Yi Liu, Yuekang Li, Kailong Wang, Ying Zhang, Zefeng Li, Haoyu Wang, Tianwei Zhang, and Yang Liu. 2023. MasterKey: Automated jailbreak across multiple large language model chatbots. *arXiv preprint arXiv:2307.08715* (2023).
[45] Jieren Deng, Yijue Wang, Ji Li, Chao Shang, Hang Liu, Sanguthevar Rajasekaran, and Caiwen Ding. 2021. TAG: Gradient attack on transformer-based language models. *arXiv preprint arXiv:2103.06819* (2021).
[46] Sentry Developer. 2023. PII and Data Scrubbing. Retrieved January 16, 2025 from https://develop.sentry.dev
[47] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. BERT: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805* (2018).
[48] Shehzaad Dhuliawala, Mojtaba Komeili, Jing Xu, Roberta Raileanu, Xian Li, Asli Celikyilmaz, and Jason Weston. 2023. Chain-of-verification reduces hallucination in large language models. *arXiv preprint arXiv:2309.11495* (2023).
[49] Wei Du, Yichun Zhao, Boqun Li, Gongshen Liu, and Shilin Wang. 2022. PPT: Backdoor attacks on pre-trained models via poisoned prompt tuning. In *Proceedings of the 31st International Joint Conference on Artificial Intelligence (IJCAI'22)*. 680–686.
[50] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783* (2024).
[51] Cynthia Dwork and Aaron Roth. 2014. The algorithmic foundations of differential privacy. *Foundations and Trends® in Theoretical Computer Science* 9, 3–4 (2014), 211–407.
[52] Zekeriya Erkin, Martin Franz, Jorge Guajardo, Stefan Katzenbeisser, Inald Lagendijk, and Tomas Toft. 2009. Privacy-preserving face recognition. In Privacy Enhancing Technologies. Lecture Notes in Computer Science, Vol. 5672. Springer, 235–253.
[53] Fatima Ezzeddine. 2024. Privacy implications of explainable AI in data-driven systems. *arXiv preprint arXiv:2406.15789* (2024).
[54] Wenqi Fan, Yujuan Ding, Liangbo Ning, Shijie Wang, Hengyun Li, Dawei Yin, Tat-Seng Chua, and Qing Li. 2024. A survey on RAG meeting LLMs: Towards retrieval-augmented large language models. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 6491–6501.
[55] Qizhang Feng, Siva Rajesh Kasa, Hyokun Yun, Choon Hui Teo, and Sravan Babu Bodapati. 2024. Exposing privacy gaps: Membership inference attack on preference data for LLM alignment. *arXiv preprint arXiv:2407.06443* (2024).
[56] Zhangyin Feng, Daya Guo, Duyu Tang, Nan Duan, Xiaocheng Feng, Ming Gong, Linjun Shou, Bing Qin, Ting Liu, Daxin Jiang, et al. 2020. CodeBERT: A pre-trained model for programming and natural languages. *arXiv preprint arXiv:2002.08155* (2020).
[57] Zhangyin Feng, Xiaocheng Feng, Dezhi Zhao, Maojin Yang, and Bing Qin. 2024. Retrieval-generation synergy augmented large language models. In *Proceedings of the 2024 IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP'24)*. IEEE, 11661–11665.
[58] Luciano Floridi and Massimo Chiriatti. 2020. GPT-3: Its nature, scope, limits, and consequences. *Minds and Machines* 30 (2020), 681–694.
[59] Jake Frankenfield. 2023. Personally Identifiable Information (PII)? Definition, Types, and Examples. Retrieved January 16, 2025 from https://www.investopedia.com/terms/p/personally-identifiable-information-pii.asp
[60] Wenjie Fu, Huandong Wang, Chen Gao, Guanghua Liu, Yong Li, and Tao Jiang. 2023. Practical membership inference attacks against fine-tuned large language models via self-prompt calibration. *arXiv preprint arXiv:2311.06062* (2023).
[61] Isabel O. Gallegos, Ryan A. Rossi, Joe Barrow, Md. Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, Tong Yu, Ruiyi Zhang, and Nesreen K. Ahmed. 2024. Bias and fairness in large language models: A survey. *Computational Linguistics* 50 (2024), 1097–1179.
[62] Tianyu Gao, Adam Fisch, and Danqi Chen. 2020. Making pre-trained language models better few-shot learners. *arXiv preprint arXiv:2012.15723* (2020).
[63] Yansong Gao, Chang Xu, Derui Wang, Shiping Chen, Damith C. Ranasinghe, and Surya Nepal. 2019. STRIP: A defense against Trojan attacks on deep neural networks. In *Proceedings of the 35th Annual Computer Security Applications Conference*. 113–125.
[64] Jonas Geiping, Hartmut Bauermeister, Hannah Dröge, and Michael Moeller. 2020. Inverting gradients—How easy is it to break privacy in federated learning? *Advances in Neural Information Processing Systems* 33 (2020), 16937–16947.
[65] Robin C. Geyer, Tassilo Klein, and Moin Nabi. 2017. Differentially private federated learning: A client level perspective. *arXiv preprint arXiv:1712.07557* (2017).
[66] Hila Gonen, Srini Iyer, Terra Blevins, Noah A. Smith, and Luke Zettlemoyer. 2022. Demystifying prompts in language models via perplexity estimation. *arXiv preprint arXiv:2212.04037* (2022).
[67] Chuan Guo, Alexandre Sablayrolles, Hervé Jégou, and Douwe Kiela. 2021. Gradient-based adversarial attacks against text transformers. *arXiv preprint arXiv:2104.13733* (2021).

[68] Chuan Guo, Alexandre Sablayrolles, Hervé Jégou, and Douwe Kiela. 2021. Gradient-based adversarial attacks against text transformers. *arXiv preprint arXiv:2104.13733* (2021).
[69] Daya Guo, Shuo Ren, Shuai Lu, Zhangyin Feng, Duyu Tang, Shujie Liu, Long Zhou, Nan Duan, Alexey Svyatkovskiy, Shengyu Fu, et al. 2020. GraphCodeBERT: Pre-training code representations with data flow. *arXiv preprint arXiv:2009.08366* (2020).
[70] Maanak Gupta, CharanKumar Akiri, Kshitiz Aryal, Eli Parker, and Lopamudra Praharaj. 2023. From ChatGPT to ThreatGPT: Impact of generative AI in cybersecurity and privacy. *IEEE Access* 11 (2023), 80218–80245.
[71] Song Han, Huizi Mao, and William J. Dally. 2015. Deep compression: Compressing deep neural networks with pruning, trained quantization and Huffman coding. *arXiv preprint arXiv:1510.00149* (2015).
[72] Stefan Harrer. 2023. Attention is not all you need: The complicated case of ethically using large language models in healthcare and medicine. *EBioMedicine* 90 (2023), 104512.
[73] Julian Hazell. 2023. Large language models can be used to effectively scale spear phishing campaigns. *arXiv preprint arXiv:2305.06972* (2023).
[74] Jiaming He, Guanyu Hou, Xinyue Jia, Yangyang Chen, Wenqi Liao, Yinhang Zhou, and Rang Zhou. 2024. Data stealing attacks against large language models via backdooring. *Electronics* 13, 14 (2024), 2858.
[75] Will Douglas Heaven. 2022. Why Meta's latest large language model survived only three days online. *MIT Technology Review*. Retrieved January 16, 2025 from https://www.technologyreview.com/2022/11/18/1063487/meta-large-language-model-ai-only-survived-three-days-gpt-3-science/
[76] Geoffrey Hinton. 2015. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531* (2015).
[77] Andrew Hoang, Antoine Bosselut, Asli Celikyilmaz, and Yejin Choi. 2019. Efficient adaptation of pretrained transformers for abstractive summarization. *arXiv preprint arXiv:1906.00138* (2019).
[78] Li Hu, Anli Yan, Hongyang Yan, Jin Li, Teng Huang, Yingying Zhang, Changyu Dong, and Chunsheng Yang. 2023. Defenses to membership inference attacks: A survey. *ACM Computing Surveys* 56, 4 (2023), 1–34.
[79] Linmei Hu, Zeyi Liu, Ziwang Zhao, Lei Hou, Liqiang Nie, and Juanzi Li. 2023. A survey of knowledge enhanced pre-trained language models. *IEEE Transactions on Knowledge and Data Engineering* 36 (2023), 1413–1430.
[80] Hai Huang, Zhengyu Zhao, Michael Backes, Yun Shen, and Yang Zhang. 2023. Composite backdoor attacks against large language models. *arXiv preprint arXiv:2310.07676* (2023).
[81] Jie Huang, Hanyin Shao, and Kevin Chen-Chuan Chang. 2022. Are large pre-trained language models leaking your personal information? *arXiv preprint arXiv:2205.12628* (2022).
[82] Jianheng Huang, Leyang Cui, Ante Wang, Chengyi Yang, Xinting Liao, Linfeng Song, Junfeng Yao, and Jinsong Su. 2024. Mitigating catastrophic forgetting in large language models with self-synthesized rehearsal. *arXiv preprint arXiv:2403.01244* (2024).
[83] Yuheng Huang, Jiayang Song, Zhijie Wang, Shengming Zhao, Huaming Chen, Felix Juefei-Xu, and Lei Ma. 2023. Look before you leap: An exploratory study of uncertainty measurement for large language models. *arXiv preprint arXiv:2307.10236* (2023).
[84] Hakan Inan, et al. 2023. Llama Guard: LLM-based input-output safeguard for human-AI conversations. *arXiv preprint arXiv:2312.06674* (2023).
[85] Huseyin A. Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, et al. 2021. Privacy analysis in language models via training data leakage report. *ArXiv, abs/2101.05405* (2021).
[86] Huseyin A. Inan, Osman Ramadan, Lukas Wutschitz, Daniel Jones, Victor Ruhle, James Withers, and Robert Sim. 2021. Training data leakage analysis in language models. *arXiv preprint arXiv:2101.05405* (2021).
[87] Abhyuday Jagannatha, Bhanu Pratap Singh Rawat, and Hong Yu. 2021. Membership inference attack susceptibility of clinical language models. *arXiv preprint arXiv:2104.08305* (2021).
[88] Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping-Yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. 2023. Baseline defenses for adversarial attacks against aligned language models. *arXiv preprint arXiv:2309.00614* (2023).
[89] Malin Jansson, Stefan Hrastinski, Stefan Stenborn, and Fredrik Enoksson. 2021. Online question and answer sessions: How students support their own and other students' processes of inquiry in a text-based learning environment. *The Internet and Higher Education* 51 (2021), 100817.
[90] Ziwei Ji, Tiezheng Yu, Yan Xu, Nayeon Lee, Etsuko Ishii, and Pascale Fung. 2023. Towards mitigating hallucination in large language models via self-reflection. *arXiv preprint arXiv:2310.06271* (2023).
[91] Jinyuan Jia, Ahmed Salem, Michael Backes, Yang Zhang, and Neil Zhenqiang Gong. 2019. MemGuard: Defending against black-box membership inference attacks via adversarial examples. In *Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security*. 259–274.
[92] Shuyu Jiang, Xingshu Chen, and Rui Tang. 2023. Prompt packer: Deceiving LLMs through compositional instruction with hidden attacks. *arXiv preprint arXiv:2310.10077* (2023).

[93] Hongpeng Jin, Wenqi Wei, Xuyu Wang, Wenbin Zhang, and Yanzhao Wu. 2023. Rethinking learning rate tuning in the era of large language models. In *Proceedings of the 2023 IEEE 5th International Conference on Cognitive Machine Intelligence (CogMI'23)*. 112–121.

[94] Dong Shu, Mingyu Jin, Chong Zhang, Liangyao Li, Zihao Zhou, and Yongfeng Zhang. 2024. AttackEval: How to evaluate the effectiveness of jailbreak attacking on large language models. *arXiv preprint arXiv:2401.09002* (2024).

[95] Nikhil Kandpal, Matthew Jagielski, Florian Tramèr, and Nicholas Carlini. 2023. Backdoor attacks for in-context learning with language models. *arXiv preprint arXiv:2307.14692* (2023).

[96] Nikhil Kandpal, Eric Wallace, and Colin Raffel. 2022. Deduplicating training data mitigates privacy risks in language models. In *Proceedings of the International Conference on Machine Learning*. 10697–10707.

[97] Masahiro Kaneko, Youmi Ma, Yuki Wata, and Naoaki Okazaki. 2024. Sampling-based pseudo-likelihood for membership inference attacks. *arXiv preprint arXiv:2404.11262* (2024).

[98] Daniel Kang, Xuechen Li, Ion Stoica, Carlos Guestrin, Matei Zaharia, and Tatsunori Hashimoto. 2024. Exploiting programmatic behavior of LLMs: Dual-use through standard security attacks. In *Proceedings of the IEEE Security and Privacy Workshops (SPW'24)*. 132–143.

[99] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT'19)*, Vol. 1. 2.

[100] Siwon Kim, Sangdoo Yun, Hwaran Lee, Martin Gubri, Sungroh Yoon, and Seong Joon Oh. 2024. ProPILE: Probing privacy leakage in large language models. *Advances in Neural Information Processing Systems* 36 (2024), 20750–20762.

[101] Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *Advances in Neural Information Processing Systems* 35 (2022), 22199–22213.

[102] Nir Kshetri. 2023. Cybercrime and privacy threats of large language models. *IT Professional* 25, 3 (2023), 9–13.

[103] Aounon Kumar, Chirag Agarwal, Suraj Srinivas, Soheil Feizi, and Hima Lakkaraju. 2023. Certifying LLM safety against adversarial prompting. *arXiv preprint arXiv:2309.02705* (2023).

[104] Keita Kurita, Paul Michel, and Graham Neubig. 2020. Weight poisoning attacks on pre-trained models. *arXiv preprint arXiv:2004.06660* (2020).

[105] Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. 2016. Neural architectures for named entity recognition. *arXiv preprint arXiv:1603.01360* (2016).

[106] Raz Lapid, Ron Langberg, and Moshe Sipper. 2023. Open sesame! Universal black box jailbreaking of large language models. *arXiv preprint arXiv:2309.01446* (2023).

[107] Haoran Li, Yulin Chen, Jinglong Luo, Yan Kang, Xiaojin Zhang, Qi Hu, Chunkit Chan, and Yangqiu Song. 2023. Privacy in large language models: Attacks, defenses and future directions. *arXiv preprint arXiv:2310.10383* (2023).

[108] Haoran Li, Dadi Guo, Wei Fan, Mingshi Xu, and Yangqiu Song. 2023. Multi-step jailbreaking privacy attacks on ChatGPT. *arXiv preprint arXiv:2304.05197* (2023).

[109] Jiazhao Li, Yijin Yang, Zhuofeng Wu, V. G. Vydiswaran, and Chaowei Xiao. 2023. ChatGPT as an attack tool: Stealthy textual backdoor attack via blackbox generative model trigger. *arXiv preprint arXiv:2304.14475* (2023).

[110] Linyi Li, Tao Xie, and Bo Li. 2023. SoK: Certified robustness for deep neural networks. In *Proceedings of the 2023 IEEE Symposium on Security and Privacy (SP'23)*. IEEE, 1289–1310.

[111] Xuechen Li, Florian Tramer, Percy Liang, and Tatsunori Hashimoto. 2021. Large language models can be strong differentially private learners. *arXiv preprint arXiv:2110.05679* (2021).

[112] Xuan Li, Zhanke Zhou, Jianing Zhu, Jiangchao Yao, Tongliang Liu, and Bo Han. 2023. DeepInception: Hypnotize large language model to be jailbreaker. *arXiv preprint arXiv:2311.03191* (2023).

[113] Yige Li, Xixiang Lyu, Nodens Koren, Lingjuan Lyu, Bo Li, and Xingjun Ma. 2021. Neural attention distillation: Erasing backdoor triggers from deep neural networks. *arXiv preprint arXiv:2101.05930* (2021).

[114] Jiawei Liang, Siyuan Liang, Man Luo, Aishan Liu, Dongchen Han, Ee-Chien Chang, and Xiaochun Cao. 2024. VL-Trojan: Multimodal instruction backdoor attacks against autoregressive visual language models. *arXiv preprint arXiv:2402.13851* (2024).

[115] Yi-Shan Lin, Wen-Chuan Lee, and Z. Berkay Celik. 2021. What do you see? Evaluation of Explainable Artificial Intelligence (XAI) interpretability through neural backdoors. In *Proceedings of the ACM SIGKDD Conference on Knowledge Discovery and Data Mining*. 1027–1035.

[116] Zachary C. Lipton. 2018. The mythos of model interpretability: In machine learning, the concept of interpretability is both important and slippery. *Queue* 16, 3 (2018), 31–57.

[117] Kang Liu, Brendan Dolan-Gavitt, and Siddharth Garg. 2018. Fine-pruning: Defending against backdooring attacks on deep neural networks. In *Proceedings of the International Symposium on Research in Attacks, Intrusions, and Defenses*. 273–294.

[118] Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. 2023. AutoDAN: Generating stealthy jailbreak prompts on aligned large language models. *arXiv preprint arXiv:2310.04451* (2023).

[119] Xiaogeng Liu, Zhiyuan Yu, Yizhe Zhang, Ning Zhang, and Chaowei Xiao. 2024. Automatic and universal prompt injection attacks against large language models. *arXiv preprint arXiv:2403.04957* (2024).
[120] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692* (2019).
[121] Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Zihao Wang, Xiaofeng Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, et al. 2023. Prompt injection attack against LLM-integrated applications. *arXiv preprint arXiv:2306.05499* (2023).
[122] Yang Liu, Yuanshun Yao, Jean-Francois Ton, Xiaoying Zhang, Ruocheng Guo, Hao Cheng, Yegor Klochkov, Muhammad Faaiz Taufiq, and Hang Li. 2023. Trustworthy LLMs: A survey and guideline for evaluating large language models' alignment. *arXiv preprint arXiv:2308.05374* (2023).
[123] Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyan Jia, and Neil Zhenqiang Gong. 2024. Formalizing and benchmarking prompt injection attacks and defenses. In *Proceedings of the USENIX Security Symposium*. 1831–1847.
[124] Yi Liu, Gelei Deng, Zhengzi Xu, Yuekang Li, Yaowen Zheng, Ying Zhang, Lida Zhao, Tianwei Zhang, and Yang Liu. 2023. Jailbreaking ChatGPT via prompt engineering: An empirical study. *arXiv preprint arXiv:2305.13860* (2023).
[125] Nils Lukas, Ahmed Salem, Robert Sim, Shruti Tople, Lukas Wutschitz, and Santiago Zanella-Beguelin. 2023. Analyzing leakage of personally identifiable information in language models. In *Proceedings of the 2023 IEEE Symposium on Security and Privacy (SP'23)*. 346–363.
[126] Scott Lundberg. 2017. A unified approach to interpreting model predictions. *arXiv preprint arXiv:1705.07874* (2017).
[127] Junyu Luo, Cao Xiao, and Fenglong Ma. 2023. Zero-resource hallucination prevention for large language models. *arXiv preprint arXiv:2309.02654* (2023).
[128] Yun Luo, Zhen Yang, Fandong Meng, Yafu Li, Jie Zhou, and Yue Zhang. 2023. An empirical study of catastrophic forgetting in large language models during continual fine-tuning. *arXiv preprint arXiv:2308.08747* (2023).
[129] Courtney Mansfield, Amandalynne Paullada, and Kristen Howell. 2022. Behind the mask: Demographic bias in name detection for PII masking. *arXiv preprint arXiv:2205.04505* (2022).
[130] James Manyika and Sissie Hsiao. 2023. An overview of the Gemini app. *Google Static Documents*. Retrieved January 16, 2025 from https://ai.google/static/documents/google-about-bard.pdf
[131] Todor Markov, Chong Zhang, Sandhini Agarwal, Tyna Eloundou, Teddy Less, Steven Adler, Angela Jiang, and Lilian Weng. 2023. A holistic approach to undesired content detection in the real world. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 37. 15009–15018.
[132] Ariana Martino, Michael Iannelli, and Coleen Truong. 2023. Knowledge injection to counter large language model (LLM) hallucination. In *Proceedings of the European Semantic Web Conference*. 182–185.
[133] Justus Mattern, Fatemehsadat Mireshghallah, Zhijing Jin, Bernhard Scholkopf, Mrinmaya Sachan, and Taylor Berg-Kirkpatrick. 2023. Membership inference attacks against language models via neighbourhood comparison. *arXiv preprint arXiv:2305.18462* (2023).
[134] Michael McCloskey and Neal J. Cohen. 1989. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of Learning and Motivation*. Vol. 24. Elsevier, 109–165.
[135] Leland McInnes, John Healy, and Steve Astels. 2017. HDBSCAN: Hierarchical density based clustering. *Journal of Open Source Software* 2, 11 (2017), 205.
[136] Yusuf Mehdi. 2023. Reinventing Search with a New AI-Powered Microsoft Bing and Edge, Your Copilot for the Web Retrieved January 16, 2025 from https://blogs.microsoft.com/blog/2023/02/07/reinventing-search-with-a-new-ai-powered-microsoft-bing-and-edge-your-copilot-for-the-web/
[137] Silvia Milano, Joshua A. McGrane, and Sabina Leonelli. 2023. Large language models challenge the future of higher education. *Nature Machine Intelligence* 5, 4 (2023), 333–334.
[138] Shervin Minaee, Tomas Mikolov, Narjes Nikzad, Meysam Chenaghlu, Richard Socher, Xavier Amatriain, and Jianfeng Guo. 2024. Large language models: A survey. *arXiv preprint arXiv:2402.06196* (2024).
[139] Fatemehsadat Mireshghallah, Kartik Goyal, Archit Uniyal, Taylor Berg-Kirkpatrick, and Reza Shokri. 2022. Quantifying privacy risks of masked language models using membership inference attacks. *arXiv preprint arXiv:2203.03929* (2022).
[140] Aayush Mittal. 2023. Prompt Hacking and Misuse of LLMs. Retrieved January 16, 2025 from https://www.unite.ai/prompt-hacking-and-misuse-of-llm/
[141] Maximilian Mozes, Xuanli He, Bennett Kleinberg, and Lewis D. Griffin. 2023. Use of LLMs for illicit purposes: Threats, prevention measures, and vulnerabilities. *arXiv preprint arXiv:2308.12833* (2023).
[142] Yuta Nakamura, Shouhei Hanaoka, Yukihiro Nomura, Naoto Hayashi, Osamu Abe, Shuntaro Yada, Shoko Wakamiya, and Elji Aramaki. 2020. KART: Privacy leakage framework of language models pre-trained with clinical records. *arXiv preprint arXiv:2101.00036* (2020).

[143] Krishna Kanth Nakka, Ahmed Frikha, Ricardo Mendes, Xue Jiang, and Xuebing Zhou. 2024. PII-Compass: Guiding LLM training data extraction prompts towards the target PII via grounding. *arXiv preprint arXiv:2407.02943* (2024).
[144] Milad Nasr, Reza Shokri, and Amir Houmansadr. 2018. Machine learning with membership privacy using adversarial regularization. In *Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security*. 634–646.
[145] Humza Naveed, Asad Ullah Khan, Shi Qiu, Muhammad Saqib, Saeed Anwar, Muhammad Usman, Naveed Akhtar, Nick Barnes, and Ajmal Mian. 2023. A comprehensive overview of large language models. *arXiv preprint arXiv:2307.06435* (2023).
[146] Seth Neel and Peter Chang. 2023. Privacy issues in large language models: A survey. *arXiv preprint arXiv:2312.06717* (2023).
[147] Weili Nie, Brandon Guo, Yujia Huang, Chaowei Xiao, Arash Vahdat, and Anima Anandkumar. 2022. Diffusion models for adversarial purification. *arXiv preprint arXiv:2205.07460* (2022).
[148] OpenAI. 2023. API to Prevent Prompt Injection & Jailbreaks. Retrieved January 16, 2025 from https://community.openai.com/t/api-to-prevent-prompt-injection-jailbreaks/203514
[149] OpenAI. 2023. ChatGPT. Retrieved January 16, 2025 from https://openai.com/chatgpt/overview/
[150] Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. 2022. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems* 35 (2022), 27730–27744.
[151] Mustafa Safa Ozdayi, Charith Peris, Jack FitzGerald, Christophe Dupuy, Jimit Majmudar, Haidar Khan, Rahil Parikh, and Rahul Gupta. 2023. Controlling the extraction of memorized data from large language models via prompt-tuning. *arXiv preprint arXiv:2305.11759* (2023).
[152] Xudong Pan, Mi Zhang, Shouling Ji, and Min Yang. 2020. Privacy risks of general-purpose language models. In *Proceedings of the 2020 IEEE Symposium on Security and Privacy (SP'20)*. IEEE, 1314–1331.
[153] Yikang Pan, Liangming Pan, Wenhu Chen, Preslav Nakov, Min-Yen Kan, and William Yang Wang. 2023. On the risk of misinformation pollution with large language models. *arXiv preprint arXiv:2305.13661* (2023).
[154] Prachi (Nayyar) Pathak. 2023. How do you protect machine learning from attacks? *LinkedIn*. Retrieved January 16, 2025 from https://www.linkedin.com/advice/1/how-do-you-protect-machine-learning-from-attacks
[155] Rodrigo Pedro, Daniel Castro, Paulo Carreira, and Nuno Santos. 2023. From prompt injections to SQL injection attacks: How protected is your LLM-integrated web application? *arXiv preprint arXiv:2308.01990* (2023).
[156] Fábio Perez and Ian Ribeiro. 2022. Ignore previous prompt: Attack techniques for language models. *arXiv preprint arXiv:2211.09527* (2022).
[157] Miguel Piedrafita. 2022. Methodologies of Jailbreaking. Retrieved January 16, 2025 from https://learnprompting.org/docs/prompt_hacking/jailbreaking
[158] PromptBase. 2024. PromptBase Home Page. Retrieved January 16, 2025 from https://promptbase.com
[159] Fanchao Qi, Yangyi Chen, Mukai Li, Yuan Yao, Zhiyuan Liu, and Maosong Sun. 2020. ONION: A simple and effective defense against textual backdoor attacks. *arXiv preprint arXiv:2011.10369* (2020).
[160] Fanchao Qi, Mukai Li, Yangyi Chen, Zhengyan Zhang, Zhiyuan Liu, Yasheng Wang, and Maosong Sun. 2021. Hidden killer: Invisible textual backdoor attacks with syntactic trigger. *arXiv preprint arXiv:2105.12400* (2021).
[161] Xiangyu Qi, Kaixuan Huang, Ashwinee Panda, Mengdi Wang, and Prateek Mittal. 2023. Visual adversarial examples jailbreak aligned large language models. In *Proceedings of the 2nd Workshop on New Frontiers in Adversarial Machine Learning*.
[162] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners. *OpenAI Blog* 1, 8 (2019), 9.
[163] Mohammad Raeini. 2023. Privacy-preserving large language models (PPLLMs). *SSRN*. Retrieved January 16, 2025 from https://papers.ssrn.com/sol3/papers.cfm?abstract_id=4512071
[164] Roger Ratcliff. 1990. Connectionist models of recognition memory: Constraints imposed by learning and forgetting functions. *Psychological Review* 97, 2 (1990), 285.
[165] Jingjing Ren, Ashwin Rao, Martina Lindorfer, Arnaud Legout, and David Choffnes. 2016. ReCon: Revealing and controlling PII leaks in mobile network traffic. In *Proceedings of the 14th Annual International Conference on Mobile Systems, Applications, and Services*. 361–374.
[166] Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. 2019. Language models as knowledge bases? In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*. 2463–2473.
[167] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. "Why should I trust you?": Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. 1135–1144.

[168] Alexander Robey, Eric Wong, Hamed Hassani, and George J. Pappas. 2023. SmoothLLM: Defending large language models against jailbreaking attacks. *arXiv preprint arXiv:2310.03684* (2023).
[169] Mirka Saarela and Vili Podgorelec. 2024. Recent applications of Explainable AI (XAI): A systematic literature review. *Applied Sciences* 14, 19 (2024), 8884.
[170] Ahmed Salem, Yang Zhang, Mathias Humbert, Pascal Berrang, Mario Fritz, and Michael Backes. 2018. ML-Leaks: Model and data independent membership inference attacks and defenses on machine learning models. *arXiv preprint arXiv:1806.01246* (2018).
[171] Sander Schulhoff. 2024. Instruction Defense. Retrieved January 16, 2025 from https://test.learnprompting.org/de/docs/prompt_hacking/defensive_measures/instruction
[172] Roei Schuster, Congzheng Song, Eran Tromer, and Vitaly Shmatikov. 2021. You autocomplete me: Poisoning vulnerabilities in neural code completion. In *Proceedings of the 30th USENIX Security Symposium (USENIX Security'21)*. 1559–1575.
[173] Aayush Mittal. 2023. Prompt Hacking and Misuse of LLMs. Retrieved January 16, 2025 from https://www.unite.ai/prompt-hacking-and-misuse-of-llm/
[174] Ramprasaath R. Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. 2017. Grad-CAM: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE International Conference on Computer Vision*. 618–626.
[175] Jose Selvi. 2023. Exploring Prompt Injection Attacks. Retrieved January 16, 2025 from https://www.nccgroup.com/us/research-blog/exploring-prompt-injection-attacks/
[176] Jesse Senechal, Eric Ekholm, Samaher Aljudaibi, Mary Strawderman, and Chris Parthemos. 2023. *Balancing the Benefits and Risks of Large Language AI Models in K12 Public Schools*. VCU Scholars Compass, Virginia Commonwealth University.
[177] Zeyang Sha, Xinlei He, Pascal Berrang, Mathias Humbert, and Yang Zhang. 2022. Fine-tuning is all you need to mitigate backdoor attacks. *arXiv preprint arXiv:2212.09067* (2022).
[178] Muhammad Ahmed Shah, Roshan Sharma, Hira Dhamyal, Raphael Olivier, Ankit Shah, Joseph Konan, Dareen Alharthi, Hazim T. Bukhari, Massa Baali, Soham Deshmukh, et al. 2023. LoFT: Local proxy fine-tuning for improving transferability of adversarial attacks against large language model. *arXiv preprint arXiv:2310.04445* (2023).
[179] Shawn Shan, Wenxin Ding, Josephine Passananti, Haitao Zheng, and Ben Y. Zhao. 2023. Prompt-specific poisoning attacks on text-to-image generative models. *arXiv preprint arXiv:2310.13828* (2023).
[180] Erfan Shayegani, Yue Dong, and Nael Abu-Ghazaleh. 2023. Plug and pray: Exploiting off-the-shelf components of multi-modal models. *arXiv preprint arXiv:2307.14539* (2023).
[181] Erfan Shayegani, Md. Abdullah Al Mamun, Yu Fu, Pedram Zaree, Yue Dong, and Nael Abu-Ghazaleh. 2023. Survey of vulnerabilities in large language models revealed by adversarial attacks. *arXiv preprint arXiv:2310.10844* (2023).
[182] Virat Shejwalkar, Huseyin A. Inan, Amir Houmansadr, and Robert Sim. 2021. Membership inference attacks against NLP classification models. In *Proceedings of the NeurIPS 2021 Workshop on Privacy in Machine Learning*.
[183] Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. 2024. "Do Anything Now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. In *Proceedings of the ACM SIGSAC Conference on Computer and Communications Security* (2024), 1671–1685.
[184] Jiawen Shi, Yixin Liu, Pan Zhou, and Lichao Sun. 2023. BadGPT: Exploring security vulnerabilities of ChatGPT via backdoor attacks to InstructGPT. *arXiv preprint arXiv:2304.12298* (2023).
[185] Jiawen Shi, Zenghui Yuan, Yinuo Liu, Yue Huang, Pan Zhou, Lichao Sun, and Neil Zhenqiang Gong. 2024. Optimization-based prompt injection attack to LLM-as-a-Judge. *arXiv preprint arXiv:2403.17710* (2024).
[186] Weijia Shi, Anirudh Ajith, Mengzhou Xia, Yangsibo Huang, Daogao Liu, Terra Blevins, Danqi Chen, and Luke Zettlemoyer. 2023. Detecting pretraining data from large language models. *arXiv preprint arXiv:2310.16789* (2023).
[187] Taylor Shin, Yasaman Razeghi, Robert L. Logan IV, Eric Wallace, and Sameer Singh. 2020. AutoPrompt: Eliciting knowledge from language models with automatically generated prompts. *arXiv preprint arXiv:2010.15980* (2020).
[188] Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. 2017. Membership inference attacks against machine learning models. In *Proceedings of the 2017 IEEE Symposium on Security and Privacy (SP'17)*. IEEE, 3–18.
[189] Manli Shu, Jiongxiao Wang, Chen Zhu, Jonas Geiping, Chaowei Xiao, and Tom Goldstein. 2023. On the exploitability of instruction tuning. *Advances in Neural Information Processing Systems* 36 (2023), 61836–61856.
[190] Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. 2013. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*. 1631–1642.
[191] Luca Soldaini, Rodney Kinney, Akshita Bhagia, Dustin Schwenk, David Atkinson, Russell Authur, Ben Bogin, Khyathi Chandu, Jennifer Dumas, Yanai Elazar, et al. 2023. *Dolma: An Open Corpus of 3 Trillion Tokens for Language Model Pretraining Research*. Technical Report. Allen Institute for AI.

[192] Congzheng Song and Vitaly Shmatikov. 2019. Auditing data provenance in text-generation models. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. 196–206.

[193] Taylor Sorensen, Joshua Robinson, Christopher Rytting, Alexander Shaw, Kyle Rogers, Alexia Delorey, Mahmoud Khalil, Nancy Fulda, and David Wingate. 2022. An information-theoretic approach to prompt engineering without ground truth labels. *arXiv preprint arXiv:2203.11364* (2022).

[194] Dirk H. R. Spennemann. 2023. Exploring ethical boundaries: Can ChatGPT be prompted to give advice on how to cheat in university assignments? *Preprints.org*. Retrieved January 16, 2025 from https://www.preprints.org/manuscript/202308.1271/v1

[195] Ningxin Su, Chenghao Hu, Haochun Li, and Bo Li. 2023. TITANIC: Towards production federated learning with large language models. In *Proceedings of the IEEE Conference on Computer Communications (INFOCOM'24)*.

[196] Lichao Sun, Lichao Sun, Haoran Wang, Siyuan Wu, Qihui Zhang, Yuan Li, Chujie Gao, Yixin Huang, Wenhan Lyu, Yixuan Zhang, et al. 2024. TrustLLM: Trustworthiness in large language models. *arXiv preprint arXiv:2401.05561* (2024).

[197] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. 2016. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. 2818–2826.

[198] Annalisa Szymanski, Noah Ziems, Heather A. Eicher-Miller, Toby Jia-Jun Li, Meng Jiang, and Ronald A. Metoyer. 2024. Limitations of the LLM-as-a-Judge approach for evaluating LLM outputs in expert knowledge tasks. *arXiv preprint arXiv:2410.20266* (2024).

[199] Yonglin Tian, Jiangong Wang, Yutong Wang, Chen Zhao, Fei Yao, and Xiao Wang. 2022. Federated vehicular transformers and their federations: Privacy-preserving computing and cooperation for autonomous driving. *IEEE Transactions on Intelligent Vehicles* 7, 3 (2022), 456–465.

[200] Yonglin Tian, Xuan Li, Hui Zhang, Chen Zhao, Bai Li, and Xiao Wang. 2023. VistaGPT: Generative parallel transformers for vehicles with intelligent systems for transport automation. *IEEE Transactions on Intelligent Vehicles* 8, 9 (2023), 4198–4207.

[201] Meng Tong, Kejiang Chen, Yuang Qi, Jie Zhang, Weiming Zhang, and Nenghai Yu. 2023. InferDPT: Privacy-preserving inference for black-box large language model. *arXiv preprint arXiv:2310.12214* (2023).

[202] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288* (2023).

[203] Stacey Truex, Ling Liu, Mehmet Emre Gursoy, Lei Yu, and Wenqi Wei. 2019. Demystifying membership inference attacks in machine learning as a service. *IEEE Transactions on Services Computing* 14, 6 (2019), 2073–2089.

[204] Thomas Vakili, Anastasios Lamproudis, Aron Henriksson, and Hercules Dalianis. 2022. Downstream task performance of BERT models pre-trained using automatically de-identified clinical data. In *Proceedings of the 13th Language Resources and Evaluation Conference*. 4245–4252.

[205] Apostol Vassilev, Alina Oprea, Alie Fordyce, and Hyrum Andersen. 2024. *Adversarial Machine Learning: A Taxonomy and Terminology of Attacks and Mitigations*. NIST AI 100-2 E2023. NIST.

[206] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in Neural Information Processing Systems* 30 (2017), 20750–20762.

[207] Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. 2016. Matching networks for one shot learning. *Advances in Neural Information Processing Systems* 29 (2016), 1–9.

[208] Paul Voigt and Axel Von dem Bussche. 2017. *The EU General Data Protection Regulation (GDPR): A Practical Guide*. Springer, Cham, Switzerland.

[209] Eric Wallace, Tony Z. Zhao, Shi Feng, and Sameer Singh. 2020. Concealed data poisoning attacks on NLP models. *arXiv preprint arXiv:2010.12563* (2020).

[210] Alexander Wan, Eric Wallace, Sheng Shen, and Dan Klein. 2023. Poisoning language models during instruction tuning. In *Proceedings of the International Conference on Machine Learning*. 35413–35425.

[211] Bolun Wang, Yuanshun Yao, Shawn Shan, Huiying Li, Bimal Viswanath, Haitao Zheng, and Ben Y. Zhao. 2019. Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *Proceedings of the 2019 IEEE Symposium on Security and Privacy (SP'19)*. IEEE, 707–723.

[212] Shang Wang, Tianqing Zhu, Bo Liu, Ding Ming, Xu Guo, Dayong Ye, and Wanlei Zhou. 2024. Unique security and privacy threats of large language model: A comprehensive survey. *arXiv preprint arXiv:2406.07973* (2024).

[213] Wei Wang, Vincent W. Zheng, Han Yu, and Chunyan Miao. 2019. A survey of zero-shot learning: Settings, methods, and applications. *ACM Transactions on Intelligent Systems and Technology* 10, 2 (2019), 1–37.

[214] Yijue Wang, Nuo Xu, Shaoyi Huang, Kaleel Mahmood, Dan Guo, and Caiwen Ding. 2022. Analyzing and defending against membership inference attacks in natural language processing classification. In *Proceedings of the 2022 IEEE International Conference on Big Data (Big Data'22)*. IEEE, 5823–5832.

[215] Yequan Wang, Jiawen Deng, Aixin Sun, and Xuying Meng. 2022. Perplexity from PLM is unreliable for evaluating text quality. *arXiv preprint arXiv:2210.05892* (2022).

[216] Yue Wang, Weishi Wang, Shafiq Joty, and Steven C. H. Hoi. 2021. CodeT5: Identifier-aware unified pre-trained encoder-decoder models for code understanding and generation. *arXiv preprint arXiv:2109.00859* (2021).

[217] Yifei Wang, Dizhan Xue, Shengjie Zhang, and Shengsheng Qian. 2024. BadAgent: Inserting and activating backdoor attacks in LLM agents. *arXiv preprint arXiv:2406.03007* (2024).

[218] Yaqing Wang, Quanming Yao, James T. Kwok, and Lionel M. Ni. 2020. Generalizing from a few examples: A survey on few-shot learning. *ACM Computing Surveys* 53, 3 (2020), 1–34.

[219] Zhenhua Wang, Wei Xie, Kai Chen, Baosheng Wang, Zhiwen Gui, and Enze Wang. 2023. Self-deception: Reverse penetrating the semantic firewall of large language models. *arXiv preprint arXiv:2308.11521* (2023).

[220] Maurice Weber, Xiaojun Xu, Bojan Karlaš, Ce Zhang, and Bo Li. 2023. RAB: Provable robustness against backdoor attacks. In *Proceedings of the 2023 IEEE Symposium on Security and Privacy (SP'23)*. IEEE, 1311–1328.

[221] Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. 2024. Jailbroken: How does LLM safety training fail? *Advances in Neural Information Processing Systems* 36 (2024), 80079–80110.

[222] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems* 35 (2022), 24824–24837.

[223] Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. 2022. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682* (2022).

[224] Wenqi Wei, Ling Liu, Margaret Loper, Ka-Ho Chow, Mehmet Emre Gursoy, Stacey Truex, and Yanzhao Wu. 2020. A framework for evaluating client privacy leakages in federated learning. In *Computer Security—ESORICS 2020*. Lecture Notes in Computer Science, Vol. 12308. Springer, 545–566.

[225] Laura Weidinger, John Mellor, Maribeth Rauh, Conor Griffin, Jonathan Uesato, Po-Sen Huang, Myra Cheng, Mia Glaese, Borja Balle, Atoosa Kasirzadeh, et al. 2021. Ethical and social risks of harm from language models. *arXiv preprint arXiv:2112.04359* (2021).

[226] Jules White, Quchen Fu, Sam Hays, Michael Sandborn, Carlos Olea, Henry Gilbert, Ashraf Elnashar, Jesse Spencer-Smith, and Douglas C. Schmidt. 2023. A prompt pattern catalog to enhance prompt engineering with ChatGPT. *arXiv preprint arXiv:2302.11382* (2023).

[227] Chenxi Whitehouse, Tillman Weyde, Pranava Madhyastha, and Nikos Komninos. 2022. Evaluation of fake news detection with knowledge-enhanced language models. In *Proceedings of the International AAAI Conference on Web and Social Media*, Vol. 16. 1425–1429.

[228] Genta Indra Winata, Lingjue Xie, Karthik Radhakrishnan, Shijie Wu, Xisen Jin, Pengxiang Cheng, Mayank Kulkarni, and Daniel Preotiuc-Pietro. 2023. Overcoming catastrophic forgetting in massively multilingual continual learning. *arXiv preprint arXiv:2305.16252* (2023).

[229] Yueqi Xie, Jingwei Yi, Jiawei Shao, Justin Curl, Lingjuan Lyu, Qifeng Chen, Xing Xie, and Fangzhao Wu. 2023. Defending ChatGPT against jailbreak attack via self-reminder. *Nature Machine Intelligence* 5 (2023), 1486–1496.

[230] Ruihan Wu, Xiangyu Chen, Chuan Guo, and Kilian Q. Weinberger. 2023. Learning to invert: Simple adaptive attacks for gradient inversion in federated learning. In *Proceedings of the 39th Conference on Uncertainty in Artificial Intelligence (UAI'23)*. 2293–2303.

[231] Xiaodong Wu, Ran Duan, and Jianbing Ni. 2024. Unveiling security, privacy, and ethical concerns of ChatGPT. *Journal of Information and Intelligence* 2, 2 (2024), 102–115.

[232] Yuanwei Wu, Yue Huang, Yixin Liu, Xiang Li, Pan Zhou, and Lichao Sun. 2024. Can large language models automatically jailbreak GPT-4V? *arXiv preprint arXiv:2407.16686* (2024).

[233] Yanzhao Wu and Ling Liu. 2023. Selecting and composing learning rate policies for deep neural networks. *ACM Transactions on Intelligent Systems and Technology* 14, 2 (2023), 1–25.

[234] Zhiheng Xi, Wenxiang Chen, Xin Guo, Wei He, Yiwen Ding, Boyang Hong, Ming Zhang, Junzhe Wang, Senjie Jin, Enyu Zhou, et al. 2023. The rise and potential of large language model based agents: A survey. *arXiv preprint arXiv:2309.07864* (2023).

[235] Zhaohan Xi, Tianyu Du, Changjiang Li, Ren Pang, Shouling Ji, Jinghui Chen, Fenglong Ma, and Ting Wang. 2024. Defending pre-trained language models as few-shot learners against backdoor attacks. *Advances in Neural Information Processing Systems* 36 (2024), 32748–32764.

[236] Zhen Xiang, Fengqing Jiang, Zidi Xiong, Bhaskar Ramasubramanian, Radha Poovendran, and Bo Li. 2024. BadChain: Backdoor chain-of-thought prompting for large language models. *arXiv preprint arXiv:2401.12242* (2024).

[237] Zhen Xiang, Zidi Xiong, and Bo Li. 2024. CBD: A certified backdoor detector based on local dominant probability. *Advances in Neural Information Processing Systems* 36 (2024), 4937–4951.

[238] Yuan Xin, Zheng Li, Ning Yu, Michael Backes, and Yang Zhang. 2023. Membership leakage in pre-trained language models. In *Proceedings of the 11th International Conference on Learning Representations (ICLR'23)*.
[239] Lei Xu, Yangyi Chen, Ganqu Cui, Hongcheng Gao, and Zhiyuan Liu. 2022. Exploring the universal vulnerability of prompt-based learning paradigm. *arXiv preprint arXiv:2204.05239* (2022).
[240] Yuancheng Xu, Jiarui Yao, Manli Shu, Yanchao Sun, Zichu Wu, Ning Yu, Tom Goldstein, and Furong Huang. 2024. Shadowcast: Stealthy data poisoning attacks against vision-language models. *arXiv preprint arXiv:2402.06659* (2024).
[241] Anli Yan, Teng Huang, Lishan Ke, Xiaozhang Liu, Qi Chen, and Changyu Dong. 2023. Explanation leaks: Explanation-guided model extraction attacks. *Information Sciences* 632 (2023), 269–284.
[242] Lu Yan, Zhuo Zhang, Guanhong Tao, Kaiyuan Zhang, Xuan Chen, Guangyu Shen, and Xiangyu Zhang. 2024. ParaFuzz: An interpretability-driven technique for detecting poisoned samples in NLP. *Advances in Neural Information Processing Systems* 36 (2024), 66755–66767.
[243] Shenao Yan, Shen Wang, Yue Duan, Hanbin Hong, Kiho Lee, Doowon Kim, and Yuan Hong. 2024. An LLM-assisted easy-to-trigger backdoor attack on code completion models: Injecting disguised vulnerabilities against strong detection. *arXiv preprint arXiv:2406.06822* (2024).
[244] Haomiao Yang, Kunlan Xiang, Mengyu Ge, Hongwei Li, Rongxing Lu, and Shui Yu. 2024. A comprehensive overview of backdoor attacks in large language models within communication networks. *IEEE Network* 38, 6 (2024), 211–218.
[245] Wenkai Yang, Yankai Lin, Peng Li, Jie Zhou, and Xu Sun. 2021. RAP: Robustness-aware perturbations for defending against backdoor attacks on NLP models. *arXiv preprint arXiv:2110.07831* (2021).
[246] Zhou Yang, Zhensu Sun, Terry Zhuo Yue, Premkumar Devanbu, and David Lo. 2024. Robustness, security, privacy, explainability, efficiency, and usability of large language models for code. *arXiv preprint arXiv:2403.07506* (2024).
[247] Zhou Yang, Bowen Xu, Jie M. Zhang, Hong Jin Kang, Jieke Shi, Junda He, and David Lo. 2024. Stealthy backdoor attack for code models. *IEEE Transactions on Software Engineering* 50, 4 (2024), 721–741.
[248] Yifan Yao, Jinhao Duan, Kaidi Xu, Yuanfang Cai, Zhibo Sun, and Yue Zhang. 2024. A survey on large language model (LLM) security and privacy: The good, the bad, and the ugly. *High-Confidence Computing* 4, 2 (2024), 100211.
[249] Jiayuan Ye, Aadyaa Maddi, Sasi Kumar Murakonda, Vincent Bindschaedler, and Reza Shokri. 2022. Enhanced membership inference attacks against machine learning models. In *Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security*. 3093–3106.
[250] Samuel Yeom, Irene Giacomelli, Matt Fredrikson, and Somesh Jha. 2018. Privacy risk in machine learning: Analyzing the connection to overfitting. In *Proceedings of the 2018 IEEE 31st Computer Security Foundations Symposium (CSF'18)*. IEEE, 268–282.
[251] Wencong You, Zayd Hammoudeh, and Daniel Lowd. 2023. Large language models are better adversaries: Exploring generative clean-label backdoor attacks against text classifiers. *arXiv preprint arXiv:2310.18603* (2023).
[252] Jiahao Yu, Xingwei Lin, and Xinyu Xing. 2023. GPTFuzzer: Red teaming large language models with auto-generated jailbreak prompts. *arXiv preprint arXiv:2309.10253* (2023).
[253] Zhiyuan Yu, Xiaogeng Lui, Shunning Liang, Zach Cameron, Chaowei Xiao, and Ning Zhang. 2024. Don't listen to me: Understanding and exploring jailbreak prompts of large language models. *arXiv preprint arXiv:2403.17336* (2024).
[254] Santiago Zanella-Béguelin, Lukas Wutschitz, Shruti Tople, Victor Ruhle, Andrew Paverd, Olga Ohrimenko, Boris Kopf, and Marc Brockschmidt. 2020. Analyzing information leakage of updates to natural language models. In *Proceedings of the 2020 ACM Conference on Computer and Communications Security*. 363–375.
[255] Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. 2022. OPT: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068* (2022).
[256] Shudong Zhang, Haichang Gao, and Qingxun Rao. 2021. Defense against adversarial attacks by reconstructing images. *IEEE Transactions on Image Processing* 30 (2021), 6117–6129.
[257] Wei Emma Zhang, Quan Z. Sheng, Ahoud Alhazmi, and Chenliang Li. 2020. Adversarial attacks on deep-learning models in natural language processing: A survey. *ACM Transactions on Intelligent Systems and Technology* 11, 3 (2020), 1–41.
[258] Xinyang Zhang, Zheng Zhang, Shouling Ji, and Ting Wang. 2021. Trojaning language models for fun and profit. In *Proceedings of the IEEE European Symposium on Security and Privacy (EuroS&P'21)*. 179–197.
[259] Yizhe Zhang, Siqi Sun, Michel Galley, Yen-Chun Chen, Chris Brockett, Xiang Gao, Jianfeng Gao, Jingjing Liu, and Bill Dolan. 2019. DialoGPT: Large-scale generative pre-training for conversational response generation. *arXiv preprint arXiv:1911.00536* (2019).
[260] Yiming Zhang and Daphne Ippolito. 2023. Prompts should not be seen as secrets: Systematically measuring prompt extraction attack success. *arXiv preprint arXiv:2307.06865* (2023).
[261] Zhiyuan Zhang, Lingjuan Lyu, Xingjun Ma, Chenguang Wang, and Xu Sun. 2022. Fine-mixing: Mitigating backdoors in fine-tuned language models. *arXiv preprint arXiv:2210.09545* (2022).

[262] Zhexin Zhang, Junxiao Yang, Pei Ke, and Minlie Huang. 2023. Defending large language models against jailbreaking attacks through goal prioritization. *arXiv preprint arXiv:2311.09096* (2023).
[263] Siyun Zhao, Yuqing Yang, Zilong Wang, Zhiyuan He, Luna K. Qiu, and Lili Qiu. 2024. Retrieval Augmented Generation (RAG) and beyond: A comprehensive survey on how to make your LLMs use external data more wisely. *arXiv preprint arXiv:2409.14924* (2024).
[264] Shuai Zhao, Jinming Wen, Luu Anh Tuan, Junbo Zhao, and Jie Fu. 2023. Prompt as triggers for backdoor attack: Examining the vulnerability in language models. *arXiv preprint arXiv:2305.01219* (2023).
[265] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. 2023. A survey of large language models. *arXiv preprint arXiv:2303.18223* (2023).
[266] Xuejun Zhao, Wencan Zhang, Xiaokui Xiao, and Brian Lim. 2021. Exploiting explanations for model inversion attacks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV'21)*. 682–692.
[267] Fei Zheng. 2023. Input reconstruction attack against vertical federated large language models. *arXiv preprint arXiv:2311.07585* (2023).
[268] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, et al. 2023. Judging LLM-as-a-Judge with MT-bench and chatbot arena. *Advances in Neural Information Processing Systems* 36 (2023), 46595–46623.
[269] Ou Zheng, Mohamed Abdel-Aty, Dongdong Wang, Zijin Wang, and Shengxuan Ding. 2023. ChatGPT is on the horizon: Could a large language model be suitable for intelligent traffic safety research and applications? *arXiv preprint arXiv:2303.05382* (2023).
[270] Ou Zheng, Mohamed Abdel-Aty, Dondong Wang, Chenzhu Wang, and Shengxuan Ding. 2023. TrafficSafetyGPT: Tuning a pre-trained large language model to a domain-specific expert in transportation safety. *arXiv preprint arXiv:2307.15311* (2023).
[271] Weikang Zhou, Xiao Wang, Limao Xiong, Han Xia, Yingshuang Gu, Mingxu Chai, Fukang Zhu, Caishuang Huang, Shihan Do, Zhiheng Xi, et al. 2024. EasyJailbreak: A unified framework for jailbreaking large language models. *arXiv preprint arXiv:2403.12171* (2024).
[272] Yongchao Zhou, Andrei Ioan Muresanu, Ziwen Han, Keiran Paster, Silviu Pitis, Harris Chan, and Jimmy Ba. 2022. Large language models are human-level prompt engineers. *arXiv preprint arXiv:2211.01910* (2022).
[273] Ligeng Zhu, Zhijian Liu, and Song Han. 2019. Deep leakage from gradients. *Advances in Neural Information Processing Systems* 32 (2019), 1–11.
[274] Yan Zhuang, Qi Liu, Yuting Ning, Weizhe Huang, Rui Lv, Zhenya Huang, GuanHao Zhao, Zheng Zhang, Qingyang Mao, Shijin Wang, et al. 2023. Efficiently measuring the cognitive ability of LLMs: An adaptive testing perspective. *arXiv preprint arXiv:2306.10512* (2023).
[275] Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B. Brown, Alec Radford, Dario Amodei, Paul Christiano, and Geoffrey Irving. 2019. Fine-tuning language models from human preferences. *arXiv preprint arXiv:1909.08593* (2019).
[276] Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043* (2023).

Received 8 February 2024; revised 16 November 2024; accepted 25 December 2024