

National University of Computer and Emerging Sciences, Lahore Campus


Course: Artificial Intelligence
Program: BS(Computer Science)
Duration: 60 Min
Paper Date: 21-2-2018
Section: A, B and C
Exam: Mid-I

Course Code: CS401
Semester: Spring 2017
Total Marks: 25
Weight: 12.5%
Page(s): 6
Reg. No _____

Instruction/Notes: This is a closed book closed notes exam.
 Calculators are allowed
 Write your final answers on the provided space only.
 Show your working on the back of these sheets or attach any extra sheets, containing your working, with this paper.
 Write your ID and section on every page

Problem 1:

The following is a state-space search graph of a problem with nodes labeled using alphabets, edges are the thick shaded lines. The number above each edge giving the transition cost (*e.g.*, $cost(C,D) = 3$) of the corresponding action and the number above each node is its heuristic value of that node (*e.g.*, $h(A) = 2$). The node labeled A is the initial state and that labeled as G is the goal state.




- a) List, in order, the nodes that will be expanded if A* algorithm is used to find a path from the initial state to the goal state. [2 Points]

- b) What path (if any) would be found by A* algorithm in part a. [2 Point]

- c) What would be the state (nodes in it) of frontier/queue when the goal is found by A* algorithm in part b. [1 Point]
- d) In one of my implementation of A* I made an interesting mistake. My implementation was identical to the correct A*, except that when it visits a node **n** that has already been expanded, it immediately skips **n** instead of checking if it needs to reinsert **n** into the priority queue. What path would be found by my erroneous implementation of A* in the search problem given in part a above. Also **comment** on the **effects of this change** on **completeness** and **optimality** of A* algorithm. [3 Points]
- e) One FAST- student suggested an early termination strategy for A* algorithm. He suggested that A* must be stopped as soon as the first goal node G is found in some successor list instead of waiting until G is popped off the priority queue. What path would be found by his version of A* for the state-space search problem given in **part a**. Also **comment** on the **effects of this change** on **completeness** and **optimality** of A* algorithm. [3 Points]
- f) Prove or disprove that the heuristic given in above problem is consistent. [1 Point]

Problem 4:**[1 + 1 + 1 + 2 Points]**

Consider the game tree picture below where A-F represent some real values. Assume the nodes are explored from left to right and standard alpha beta pruning is used.



- Give a value of A such that B is pruned.
- True or False: There are SOME values of A and B such that the sub-tree containing C and D is pruned?
- Assuming that $B = 5$ and $A = 5$, give a value of C and D such that the sub-tree containing E and F is pruned.
- If you are allowed to assign A-F arbitrarily, what is the MAXIMUM number of leaves that can be pruned? also specify the pruned leaves.