BASIS PATH TESTING TECHNICAL REPORT

White-Box Unit Testing & Structural Complexity Verification for Main Modules

Project Title:	Restaurant Management System (RMS)	**Date:**	October 26, 2026
Testing Technique:	Basis Path Testing (Tom McCabe, 1976)	**Coverage Goal:**	100% Branch & Linearly Independent Paths
Target Modules:	Contracts, Orders, Billing, Reservations, Payments	**Test Runner:**	Vitest 2.1 (Node.js 22 runtime)
Verification Verdict:	**PASS (51/51 Basis Path Tests Passed)**	**Full Suite Status:**	**PASS (74/74 Tests Passed, 9 Files)**

1. Aim & Objectives

Primary Aim: To perform comprehensive white-box unit testing of the main operational and business-logic modules of the Restaurant Management System using the **Basis Path Testing** method, mathematically deriving the cyclomatic complexity $V(G)$ for each core routine, establishing an exhaustive basis set of linearly independent execution paths, and validating every decision outcome through automated unit test cases.

Specific Engineering Objectives:

- Construct Control Flow Graphs (CFG) decomposing compound boolean decision expressions into atomic predicate nodes (Π).
- Compute McCabe's Cyclomatic Complexity $V(G)$ using three complementary formulations: $E - N + 2P$, $\Pi + 1$, and Planar Regions R.
- Isolate all linearly independent basis paths ($p_1, p_2, \dots, p_k$) ensuring that every program statement is executed at least once and every branch condition evaluates to both `true` and `false`.
- Design and implement parameterized, isolated automated unit test suites in Vitest targeting each independent path without external database dependencies.
- Execute and verify that 100% of the designed basis path test cases pass with zero regressions against the full system regression suite.

2. Theoretical Framework of Basis Path Testing

Basis Path Testing is a structural testing technique first proposed by Thomas J. McCabe in 1976 based on graph theory. It provides an objective, mathematical metric for program complexity and establishes the upper bound on the minimum number of test cases required to achieve complete branch coverage.

Mathematical Definitions of Cyclomatic Complexity $V(G)$:

1. **Graph Topology Formulation:** $V(G) = E - N + 2P$
   Where E = number of directed edges, N = number of nodes, and P = number of connected subroutines ($P = 1$).
2. **Predicate Node Formulation:** $V(G) = \Pi + 1$
   Where Π = number of predicate (decision) nodes in the decomposed CFG.
3. **Planar Regions Formulation:** $V(G) = R$
   Where R = number of bounded internal regions plus the single unbounded external region.

A path through a program is *linearly independent* if it introduces at least one edge in the control flow graph that has never been traversed by any previously identified path. Any arbitrary execution trajectory through the module can be expressed as a linear vector sum of the basis paths in the basis set.

3. Module 1: Order State Machine (`canTransitionOrderStatus`)

Module Location: `apps/server/src/contracts/index.ts`
Responsibility: Governs all permissible and forbidden state transitions across the dining order lifecycle (`placed -> preparing -> ready -> served`, and cancellations from early stages).

```
export function canTransitionOrderStatus(current: OrderStatus, next: OrderStatus): boolean {
  if (next === OrderStatus.CANCELLED) {
    return current === OrderStatus.PLACED || current === OrderStatus.PREPARING;
  }
  if (current === OrderStatus.PLACED && next === OrderStatus.PREPARING) return true;
  if (current === OrderStatus.PREPARING && next === OrderStatus.READY) return true;
  if (current === OrderStatus.READY && next === OrderStatus.SERVED) return true;
  return false;
}
```

Control Flow Graph Analysis: Compound conditions (`||` and `&&`) decompose into 9 atomic predicate nodes: $\Pi = 9 \implies V(G) = \Pi + 1 = 10$. Total Nodes $N = 13$, Directed Edges $E = 21 \implies V(G) = 21 - 13 + 2(1) = 10$.




Figure 1: Control Flow Graph (CFG) for canTransitionOrderStatus [V(G) = 10]

Path ID	Branch Outcomes	Input Tuple (current, next)	Expected	Actual
OSM-P1	P1(T) -> P2(T)	PLACED, CANCELLED	true	**PASS**
OSM-P2	P1(T) -> P2(F) -> P3(T)	PREPARING, CANCELLED	true	**PASS**
OSM-P3	P1(T) -> P2(F) -> P3(F)	READY, CANCELLED	false	**PASS**
OSM-P4	P1(F) -> P4(T) -> P5(T)	PLACED, PREPARING	true	**PASS**
OSM-P5	P1(F) -> P4(T) -> P5(F) -> False	PLACED, SERVED	false	**PASS**
OSM-P6	P1(F) -> P4(F) -> P6(T) -> P7(T)	PREPARING, READY	true	**PASS**
OSM-P7	P1(F) -> P4(F) -> P6(T) -> P7(F)	PREPARING, SERVED	false	**PASS**
OSM-P8	P1(F) -> P4(F) -> P6(F) -> P8(T) -> P9(T)	READY, SERVED	true	**PASS**
OSM-P9	P1(F) -> P4(F) -> P6(F) -> P8(T) -> P9(F)	READY, PLACED	false	**PASS**
OSM-P10	P1(F) -> P4(F) -> P6(F) -> P8(F)	SERVED, PREPARING	false	**PASS**

4. Module 2: Order Lifecycle Service (`OrderService`)

Module Location: `apps/server/src/modules/orders/service.ts`
Responsibility: Implements domain authorization, role-based cancellation rights, and validates status transitions between operational actors (Customers, Kitchen Staff, Waiters, and Administrators).

4.1 Function: `cancelOrder(userId, role, orderId)`

Predicate Nodes ($\Pi = 7 \implies V(G) = 8$):
P_1: `!order` (404) | P_2: `role === CUSTOMER` | P_3: `order.customerId !== userId` (403) | P_4: `order.status !== PLACED` (409) | P_5: `role === KITCHEN` | P_6: `status not in [PLACED, PREPARING]` (409) | P_7: `role !== ADMIN` (403).




Figure 2: Control Flow Graph (CFG) for OrderService.cancelOrder [V(G) = 8]

Path ID	Decision Path / Preconditions	Expected Outcome	Verdict
ORD-C1	P1(T): Target order does not exist in database	Throw 404 NOT_FOUND	**PASS**
ORD-C2	P1(F) -> P2(T) -> P3(T): Customer attempting to cancel other user's order	Throw 403 FORBIDDEN	**PASS**
ORD-C3	P1(F) -> P2(T) -> P3(F) -> P4(T): Customer cancelling order in PREPARING status	Throw 409 CONFLICT	**PASS**
ORD-C4	P1(F) -> P2(T) -> P3(F) -> P4(F): Customer cancelling own PLACED order	Status -> CANCELLED + Audit Log	**PASS**
ORD-C5	P1(F) -> P2(F) -> P5(T) -> P6(T): Kitchen cancelling READY order	Throw 409 CONFLICT	**PASS**
ORD-C6a	P1(F) -> P2(F) -> P5(T) -> P6a(F): Kitchen cancelling PLACED order	Status -> CANCELLED + Audit Log	**PASS**
ORD-C6b	P1(F) -> P2(F) -> P5(T) -> P6b(F): Kitchen cancelling PREPARING order	Status -> CANCELLED + Audit Log	**PASS**
ORD-C7	P1(F) -> P2(F) -> P5(F) -> P7(T): Unauthorized role (WAITER) cancelling order	Throw 403 FORBIDDEN	**PASS**
ORD-C8	P1(F) -> P2(F) -> P5(F) -> P7(F): Admin cancelling PREPARING order	Status -> CANCELLED + Audit Log	**PASS**

5. Module 3: Billing & Taxation Computation (`computeBill`)

Module Location: `apps/server/src/modules/billing/index.ts`
Responsibility: Aggregates items across all valid order rounds inside a dining session, applies percentage discounts, computes legal GST (CGST 2.5% + SGST 2.5%), and ensures integer paise half-up rounding.




Figure 3: Control Flow Graph (CFG) for computeBill [V(G) = 4 + 1 Boundary]

Path ID	Scenario Tested	Formula / Calculated Values	Verdict
BIL-P1	All orders cancelled in session	subtotal: 0, discount: 0, CGST: 0, SGST: 0, total: 0	**PASS**
BIL-P2	Valid orders (₹1,000) with 0% discount	subtotal: 100000, CGST: 2500, SGST: 2500, total: 105000 paise	**PASS**
BIL-P3	Valid orders (₹1,000) with 10% discount	discount: 10000, taxable: 90000, CGST: 2250, SGST: 2250, total: 94500 paise	**PASS**
BIL-P4	Valid orders (₹450) with 100% comped discount	discount: 45000, taxable: 0, CGST: 0, SGST: 0, total: 0 paise	**PASS**
BIL-P5	Odd cents rounding boundary (175 paise)	175 * 0.025 = 4.375 -> rounded half-up to 4 paise. total = 183 paise	**PASS**

6. Module 4 & 5: Reservations & Payments Verification

6.1 Module 4: Reservation Operations (`ReservationService`)

Module Location: `apps/server/src/modules/reservations/service.ts`
Complexity: 15 Linearly Independent Paths ($V(G) = 15$) covering `createReservation` (table lookup, seat capacity validation, time range checks, overlap detection), `updateStatus` (atomic seating transitions), and `cancelReservation`.

Path ID	Function	Branch Scenario & Conditions	Verdict
RES-C1	createReservation	Target table ID not found in database	**PASS (404)**
RES-C2	createReservation	Guest count exceeds table maximum seating capacity	**PASS (409)**
RES-C3	createReservation	End time is before or equal to start time (invalid interval)	**PASS (400)**
RES-C4	createReservation	Table has overlapping active reservation on same date	**PASS (409)**
RES-C5	createReservation	Valid parameters: reservation created & audit recorded	**PASS (200)**
RES-U1	updateStatus	Reservation ID not found	**PASS (404)**
RES-U2	updateStatus	Seating attempt on CANCELLED reservation	**PASS (409)**
RES-U3	updateStatus	Seating attempt when table is already OCCUPIED	**PASS (409)**
RES-U4	updateStatus	Seating attempt when customer has another active session	**PASS (409)**
RES-U5	updateStatus	Valid seating: creates session, marks SEATED, logs audit	**PASS (200)**
RES-U6	updateStatus	Admin transitions reservation to CONFIRMED directly	**PASS (200)**
RES-X1	cancelReservation	Reservation ID not found	**PASS (404)**
RES-X2	cancelReservation	Customer attempting to cancel other user's booking	**PASS (403)**
RES-X3	cancelReservation	Attempting to cancel already SEATED booking	**PASS (409)**
RES-X4	cancelReservation	Eligible booking cancelled & audit logged	**PASS (200)**

6.2 Module 5: Payment Processing (`PaymentService`)

Module Location: `apps/server/src/modules/payments/service.ts`
Complexity: 6 Linearly Independent Paths ($V(G) = 6$) covering gateway simulation (positive vs zero amount) and session settlement (missing session, closed session, gateway failure, atomic closure transaction).

Path ID	Function	Branch Scenario & Conditions	Verdict
PAY-D1	processDummyPayment	Payment amount > 0: returns success = true and TXN ID	**PASS**
PAY-D2	processDummyPayment	Payment amount <= 0: returns success = false	**PASS**
PAY-H1	handleSessionPayment	Session ID does not exist	**PASS (Error)**
PAY-H2	handleSessionPayment	Session is already CLOSED	**PASS (Error)**
PAY-H3	handleSessionPayment	Gateway payment returns failure	**PASS (Failure)**
PAY-H4	handleSessionPayment	Gateway succeeds: closes session & sets table AVAILABLE	**PASS (Success)**

7. Conclusion

The application of **Basis Path Testing** to the Restaurant Management System has established complete structural verification of all main operational modules. By rigorously decomposing all boolean expressions and mapping each linearly independent path into automated unit tests:

- **100% Decision/Branch Coverage:** Every conditional outcome across order state transitions, role authorizations, reservation conflict detections, billing computations, and payment settlement workflows has been tested.
- **High Execution Velocity:** The entire basis path test suite of 51 tests executes in 44ms, enabling immediate feedback in CI/CD without database latency.
- **Architectural Integrity:** Critical system invariants (such as atomic table release, overlap prevention, and immutable historical menu pricing) are formally safeguarded against accidental regressions.