

iSend Global

Send Transaction API (REST) Specifications

Version 2.1

Revision History

Version	Date	Author	Description/Changes Made
2.0	06/24/2025	Manish Maharjan	Baselined version
2.1	06/08/2026	Manish Maharjan	Added sender/receiver's new fields to capture additional details. (corporate entity contact details, reference details, local collection amount field, native name fields)
			-

Contents

Process to send Transaction:	5
Communication Timeouts and Wait Periods	5
1. Get Authentication.....	6
Request Body	6
Response Body	6
2. Get Catalog.....	6
2.1 Request Param	6
2.2 Response:.....	7
3. Get Agent List.....	8
3.1 Request Param	8
3.2 Response:.....	8
4. Get Country Wise Rate.....	9
4.1 Request Param:.....	9
4.2 Response:.....	9
5. Get ExRate	10
5.1 Request param:.....	10
5.2 Response:.....	11
6. Check Balance	11
6.1 Response:.....	11
7. Send Transaction.....	12
7.1 Request Body	12
7.2 Field Details.....	16
7.3 Response:.....	21
8. Authorized Confirm.....	22
8.1 Request Body:	22
8.2 Field Details.....	22
8.3 Response:.....	22
9. Cancel Transaction	23
9.1 Request Body:	23
9.2 Field Detail:	23
9.3 Response:.....	23
10. Query Transaction.....	24

10.1 Request Param:.....	24
10.2 Response	24
11. Account Validation	25
11.1 Request Body	25
11.2 Field Details.....	26
11.3 Response	26
Appendix – Response Codes	27

Process to send Transaction:

1. Call **GetAuthentication** to receive token ID, Bearer Token Authentication is used in all other API.
2. Call **GetCatalogue** to fetch catalogue data. Static data that can be used in respective APIs
3. Call **GetAgentList** to get all the active payout location details.
4. Call **GetCountryWiseRate** to get the latest exchange rate.
*For multiple currency payout for same corridor please proceed with **GetExRate** method*
5. Call **GetEXRate** method to make enquiry on finding forex rates, service charge and amount details of that particular corridor as respective to locationIds.
6. **CheckBalance** method to check the available balance in the system.
7. Call **SendTransaction** to send transaction with the relevant parameters.
8. **Authorized Confirm** and **Cancel Transaction** APIs comes in play as per the API consumption process configured for sending partners. If Sending partners are configured as two step process required to confirm transaction then in that scenario, after calling **SendTransaction** API, partner needs to call **Authorized Confirm** API mandatorily to confirm the transaction in our system. Or if partner wants to terminate the transaction, then partner can call **Cancel Transaction**. Cancel Transaction only works for pending transaction that required auth confirm waiting status.
If two step process is not configured (not enabled) at our end then in single step by calling SendTransaction API, transaction is marked ready for payout at our end.
9. **QueryTXNStatus** method to check transaction status.

Partner need to check QueryTXN status after success response received from SendTransaction (iPay pin number generated in response). Transaction may take couple seconds to process at our end so please use QueryTXN API to identify the proper transaction status.

Communication Timeouts and Wait Periods

The timeout period for each unique transaction is 180 seconds. If a transaction request to web services is aborted or closed as part of network error detection and recovery before the timeout, Partner should query the transaction status using "**QueryTXNStatus**" before retry the same transaction.

S.N	Param Name	Mand - atory	Field Type / Length	Remarks and Description
1	CatalogueType	Y	String	Catalogue type and takes value as: "CTY": Get Available Country "PTY": Get Available Payment Mode "OCC": Get Occupation List "SOF": Get Source of Fund "REL": Get Relationship list "POR": Get Purpose of Remittance

				"DOC": Get Customer Document ID Type
2	AdditionalField1	N		Pass Country's ISO 3 alpha 3 code if Catalogue Type is "PTY"
3	AdditionalField2	N		Currently allocated for future use.
4	AdditionalField3	N		Currently allocated for future use.

2.2 Response:

For Country

```
{
  "responseCode": "0",
  "responseMessage": "",
  "agentSessionId": "72fa0fdc-7fd8-49d7-a320-794d51c56b0e",
  "data": [
    {
      "data": "AUS",
      "value": "Australia"
    },
    {
      "data": "BGD",
      "value": "BANGLADESH"
    }
  ]
}
```

For Payment Type

```
{
  "responseCode": "0",
  "responseMessage": "",
  "agentSessionId": "5baa7949-085f-466a-9aea-257f1ea06705",
  "data": [
    {
      "data": "D",
      "value": "Account Deposit to Other Bank"
    },
    {
      "data": "C",
      "value": "Cash Pay"
    },
    {
      "data": "W",
      "value": "Wallet"
    }
  ]
}
```

3. Get Agent List

Call *GetAgentList* to get the detailed location information of Payout location from API. Location ID must be passed to calculate *GetExRate* and to call *SendTransaction* method.

Method: GET

URL: <https://sendingmwdev.isendremit.com/api/v2/Agents>

3.1 Request Param

S.N	Param Name	Mand-atory	Field Type / Length	Remarks and Description
1	PaymentMode	Y	String	"D" or "C" or "W" or "O" D - Account Deposit C- Cash Pickup W- Wallet O- Other
2	PayoutCountry	Y	String /ISO3 Alpha 3 code / 3	
3	BankName	N		
4	BankBranchState	N		

3.2 Response:

```
{
  "responseCode": "0",
  "responseMessage": "",
  "agentSessionId": "",
  "data": [
    {
      "payoutAgentId": "AAA",
      "locationId": "BANKIND",
      "agent": "All Bank in India Route 1",
      "branch": "",
      "address": "",
      "city": "",
      "currency": "INR",
      "bankId": "BANKIND",
      "bankBranchId": "",
      "bankBranchState": "",
      "optionalField": ""
    },
    {
      "payoutAgentId": "BBB",
      "locationId": "BANKIND2",

```

```

    "agent": "All Bank in India Route 2",
    "branch": "",
    "address": "",
    "city": "",
    "currency": "INR",
    "bankId": "BANKIND2",
    "bankBranchId": "",
    "bankBranchState": "",
    "optionalField": ""
  }
]
}

```

4. Get Country Wise Rate

Partner call Get Country Wise Rate Command to get the latest country wise Exchange Rate and Service Charges. To get exchange rate of multi-currency for same payout country as per available agent list, partner can call [GET EXRATE API](#)

Method: Get

URL: <https://sendingmwdev.isendremit.com/api/v2/CountryWiseExchangeRate>

4.1 Request Param:

S.N	Param Name	Mand - atory	Field Type / Length	Remarks and Description
1	PayoutCountry	N	Iso3 alpha 3 code	When country code is passed, specific single country exRate response is received.

4.2 Response:

```

{
  "responseCode": "0",
  "responseMessage": "",
  "agentSessionId": "",
  "data": [
    {
      "destinationCountry": "ARMENIA",
      "exrate": "2.01",
      "payoutCurrency": "AMD",
      "lastUpdated": "8/30/2023 5:31:53 PM",
      "dollarRate": "",
      "agentSessionId": ""
    }
  ]
}

```

```

    },
    {
      "destinationCountry": "AUSTRALIA",
      "exrate": "1.037",
      "payoutCurrency": "AUD",
      "lastUpdated": "8/30/2023 5:31:53 PM",
      "dollarRate": "",
      "agentSessionId": ""
    },
    {
      "destinationCountry": "BANGLADESH",
      "exrate": "63.1111",
      "payoutCurrency": "BDT",
      "lastUpdated": "7/3/2024 4:35:27 PM",
      "dollarRate": "",
      "agentSessionId": ""
    }
  ]
}

```

5. Get ExRate

Partner call *GetEXRateCommand* to get the latest Exchange Rate and Service Charges.

Method: GET

URL: <https://sendingmwdev.isendremit.com/api/v2/ExchangeRates>

5.1 Request param:

S.N	Param Name	Mand - atory	Field Type / Length	Remarks and Description
1	TransferAmount	Y	String /	
2	PaymentMode	Y		Sample: "D" or "C" or "W" or "O" D - Account Deposit C- Cash Pickup W- Wallet O- Other
3	CalcBy	Y		"P" (can add static 'P') P as payout amount

4	PayoutCountry	Y	Iso3 alpha 3 code	
5	AdditionalField1	N		
6	LocationId	Y		Received from Get Agent List API

5.2 Response:

```
{
  "responseCode": "0",
  "responseMessage": "ISGHDFC",
  "agentSessionId": "47561ef7-2fa6-4875-9e7e-5d6b12b48444",
  "data": {
    "collectAmt": "1.1500",
    "collectCurrency": "USD",
    "serviceCharge": "0.0000",
    "exchangeRate": "86.9100",
    "payoutAmt": "100.0000",
    "payoutCurrency": "INR",
    "exrateSessionId": "14367979"
  }
}
```

6. Check Balance

Call this method to find your current account balance.

Method: GET

URL: <https://sendingmwdev.isendremit.com/api/v2/CheckBalance>

6.1 Response:

```
{
  "responseCode": "0",
  "responseMessage": "",
  "agentSessionId": "5836be73-25d6-4ef7-bc9b-a66f24052df5",
  "data": {
    "currentBalance": "24879586.8015",
    "currency": "SGD"
  }
}
```

7. Send Transaction

After Successful calling GetExRate method, call this function to send transactions.

Method: POST

URL: <https://sendingmwdev.isendremit.com/api/v2/Transactions>

7.1 Request Body

```
{
  "agentSessionId": "16a913830341",
  "transactionDetails": {
    "authorizedRequired": "N", // Y or N , in latest version it is not impacted from request body, it is configured from system portal
    "purposeOfRemittance": "Family maintenance / saving",
    "beneficiaryRelationship": "Colleague",
    "payoutCurrency": "INR",
    "payoutAmount": "290.00",
    "senderCurrency": "",
    "exRate": "",
    "collectAmount": "",
    "sourceOfFund": "testt",
    "agentTxnId": "SM20008160023",
    "locationRegulatoryId": "BANKIND",
    "regulatoryEntityId": "BANKIND",
    "transactionDate": "",
    "additionalField1": "",
    "additionalField2": "",
    "additionalField3": "",
    "reference": "",
    "localCollectAmount": ""
  },
  "senderDetails": {
    "senderType": "INDIVIDUAL",
    "senderIndividual": {
      "firstName": "Manish",
      "middleName": "",
      "lastName": "Test User",
      "nativeName": "",
      "gender": "Male",
      "nationality": "NPL",
      "birthCountry": "NPL",
      "idType": "passport",
      "idIssuedCountry": "NPL",
      "idNumber": "pa981231",
      "idIssueDate": "1963-08-07",
      "idExpiryDate": "2033-08-07",
      "dateOfBirth": "1963-08-07"
    },
    "senderCorporate": {
      "name": "",
      "nativeName": "",
      "registerCountry": ""
    }
  }
}
```

```

"businessType": "",
"idType": "",
"idNumber": "",
"idIssueDate": "",
"idExpiryDate": "",
"contactPerson": "",//
"contactPersonDesignation": "",//
"contactPersonIdType": "",//
"contactPersonIdNumber": "",//
"additionalIdNumber": ""//
},
"senderCountry": "SGP",
"senderAddress": "address",
"senderMobile": "9028668592",
"senderCity": "city",
"street": "street",
"streetNumber": "12",
"streetType": "",
"suburb": "",
"senderState": "state",
"senderZipcode": "47100",
"senderEmail": "test@gmail.com",
"occupation": "asda",
"reference": "",
},
"senderAgent": {
"country": "SGP",
"operatingCountry": "SGP",
"agentId": "",
"agentName": "",
"vAccount": "",
"reference": ""
},
"receiverDetails": {
"receiverType": "individual",
"receiverIndividual": {
"firstName": "Singham",
"middleName": "",
"lastName": "Shrivastav",
"nativeName": "",
"nationality": "IND",
"birthCountry": "IND",
"gender": "",
"occupation": "",
"idType": "",
"idIssuedCountry": "IND",
"idNumber": "",
"idIssueDate": "1903-08-07",
"idExpiryDate": "2026-08-07",
"dateOfBirth": "1903-08-07"
},
},
"receiverCorporate": {
"name": "",
"nativeName": "",
"registerCountry": "",
"idType": "",
"idNumber": "",
"idIssueDate": "",

```

```

    "idExpiryDate": "",
    "contactPerson": "",//
    "contactPersonDesignation": ""//
  },
  "receiverCountry": "IND",
  "receiverAddress": "Adress details",
  "receiverMobile": "919834565421",
  "receiverCity": "city",
  "street": "",
  "streetNumber": "",
  "streetType": "",
  "suburb": "",
  "receiverZipcode": "",
  "receiverState": "",
  "receiverEmail": "",
  "reference": ""
},
"receiverPayoutDetails": {
  "paymentType": "bank transfer",
  "bankDetails": {
    "bankAccountType": "SAVINGS",
    "bankName": "All Bank in India Route HDFC",
    "bankBranch": "",
    "bankAccountNo": "1010101010101",
    "bankCode": "",
    "bankBranchCode": "",
    "routeNo": "ROUTE001",
    "reference": ""
  },
  "walletDetails": {
    "walletEntityName": "",
    "walletAccountValue": "",
    "walletBranch": "",
    "walletCode": "",
    "walletBranchCode": "",
    "routeNo": "",
    "reference": ""
  },
  "cashPickupDetails": {
    "cashpointEntityName": "",
    "cashPickupReferenceValue": "",
    "cashpointBranch": "",
    "cashpointCode": "",
    "cashpointBranchCode": "",
    "routeNo": "",
    "reference": ""
  },
  "otherPayDetails": {
    "payingEntityName": "",
    "payoutAccountValue": "",
    "payoutBranch": "",
    "payoutCode": "",
    "payoutBranchCode": "",
    "routeNo": "",
    "reference": ""
  }
}
}

```

Note: "authorizedRequired": "N", // Y or N , in latest version it is not impacted from request body, it is configured from system portal. In previous version API, this field used to decide whether transactions require single step or multi step to confirm.

Following authorized confirm API or Cancel API to accept or reject transactions.

Note: Transaction confirmation by single step or multi step is configured by isend Head office team.

For single step transaction confirmation, no need to call other API

For multi-step, partner need to call AUTHORIZE CONFIRM API

7.2 Field Details

Mandatory fields which are marked 'Yes' remain the same whereas in future as per regulatory needs other fields may have conditional mandatory (CM) which will be updated to the partners.

Object	Fields	Man-datory	Remarks	Data type	Length	Format
main object						
	"agentSessionId"	No	Unique GUID for each request, session id is used in case of required transaction track via log check or internal check in case of failed request	String	50	
"transactionDetails"						
	"authorizedRequired"	No	Value taken as Either "N" or "Y" note applicable in new version, this setup is configured internally by iSendHUB admin team.			
	"purposeOfRemittance"	Yes				
	"beneficiaryRelationship"	Yes				
	"payoutCurrency"	Yes		String	50	ISO3 alpha-3
	"payoutAmount"	Yes		String	50	
	"senderCurrency"			String	50	ISO3 alpha-3
	"exRate"			String	50	
	"collectAmount"			String	50	
	"sourceOfFund"	Yes		String	256	static data
	"agentTxnId"	Yes	Partner's unique transaction ID which can be used to track the created transaction in the system, also can be used for query API	String	50	
	"locationRegulatoryId"	YES	for current HUB, received as "locationId" in getAgent API	String	50	
	"regulatoryEntityId"	YES	for current HUB, received as "bankId" in getAgent API	String	50	
	"transactionDate"			String	50	YYYY-MM-DD
	"additionalField1"			String	256	
	"additionalField2"			String	256	
	"additionalField3"			String	256	
	"reference"			String	256	
	"localCollectAmount"		Collection agent's collect amount as per their currency	String		
"senderDetails"						
	"senderType"	Yes	accepts as "INDIVIDUAL" or "CORPORATE"	String	50	static data
"senderDetails". "senderIndividual" (this object is active when sender is individual type)		CM	for this object If "sender_type" = "individual" then senderIndividual Object is mandatory			
	"firstName"	Yes		String	50	

	"middleName"			String	256	
	"lastName"	No		String	50	
	"nativeName"		Native name in native font	String	256	
	"gender"			String	50	
	"nationality"	Yes		String	50	
	"birthCountry"					ISO3 alpha-3
	"idType"	Yes		String	50	static data
	"idIssuedCountry"			String	50	ISO3 alpha-3
	"idNumber"	Yes		String	50	
	"idIssueDate"			String	50	YYYY-MM-DD
	"idExpiryDate"			String	50	YYYY-MM-DD
	"dateOfBirth"	Yes		String	50	YYYY-MM-DD
"senderDetails". "senderCorporate" (this object is active when sender is corporate type)		CM	for this object If "sender_type" = "corporate" then senderCorporate Object is mandatory			
	"name"	Yes		String	256	
	"nativeName"		Native name in native font	String	256	
	"registerCountry"	Yes		String	50	ISO3 alpha-3
	"businessType"					
	"idType"	Yes		String	50	static data
	"idNumber"	Yes		String	50	
	"idIssueDate"	CM		String	50	YYYY-MM-DD
	"idExpiryDate"	CM		String	50	YYYY-MM-DD
	"contactPerson"	CM	Contact person name for the sender business (should be head member)			
	"contactPersonDesignation"	CM	Contact persons designation			
	"contactPersonIdType"	CM	Contact persons id type			
	"contactPersonIdNumber"	CM	Contact Person id number			
	"additionalIdNumber"	CM	Business details, additional number incase of txn requirement			
"senderDetails".						
	"senderCountry"	Yes		String		ISO3 alpha-3
	"senderAddress"	Yes		String	256	
	"senderMobile"			String	50	
	"senderCity"	Yes		String	50	
	"street"			String	50	
	"streetNumber"			String	50	
	"streetType"			String	50	
	"suburb"			String	50	
	"senderState"	CM		String	50	
	"senderZipcode"	CM		String	50	

	"occupation"	CM		String	256	
	"senderEmail"	CM	As per payout corridor: ZAF	String	50	
	"reference"		Additional field incase of reference			
"senderAgent"						
	"country"			String	50	ISO3 alpha-3
	"operatingCountry"					ISO3 alpha-3
	"agentId"			String	50	
	"agentName"			String	256	
	"vAccount"			String	50	
	"reference"			String	50	
"receiverDetails"						
	"receiverType"	Yes	accepts as "INDIVIDUAL" or "CORPORATE"	String	50	
"receiverDetails". "receiverIndividual" (this object is active when receiver is individual type)		Yes	for this object If "receiver_type" = "individual" then receiverIndividual object is mandatory			
	"firstName"	Yes		String	50	
	"middleName"			String	256	
	"lastName"	CM		String	50	
	"nativeName"	CM	Native name in native font			
	"nationality"	CM		String	50	
	"birthCountry"					ISO3 alpha-3
	"gender"			String	50	
	"occupation"					
	"idType"			String	50	static data
	"idIssuedCountry"			String	50	ISO3 alpha-3
	"idNumber"	CM		String	50	
	"idIssueDate"			String	50	YYYY-MM-DD
	"idExpiryDate"			String	50	YYYY-MM-DD
	"dateOfBirth"	CM	As per payout corridor: SEPA countries	String	50	YYYY-MM-DD
"receiverDetails". "receiverCorporate" (this object is active when receiver is corporate type)		Yes	for this object If "receiver_type" = "corporate" then receiverCorporate object is mandatory			
	"name"	Yes		String	256	
	"nativeName"		Native name in native font			
	"registerCountry"			String	50	ISO3 alpha-3
	"idType"			String	50	static data

	"idNumber"	CM		String	50	
	"idIssueDate"			String	50	YYYY-MM-DD
	"idExpiryDate"			String	50	YYYY-MM-DD
	"contactPerson"	CM	Contact person name for the sender business (should be head member)			
	"contactPersonDesignation"	CM	Contact persons designation			
"receiverDetails"						
	"receiverCountry"	Yes		String	50	ISO3 alpha-3
	"receiverAddress"	Yes		String	256	
	"receiverMobile"			String	50	
	"receiverCity"	CM	As per payout corridor: AUS	String	50	
	"street"			String	50	
	"streetNumber"			String	50	
	"streetType"			String	50	
	"suburb"			String	50	
	"receiverZipcode"	CM	As per payout corridor: AUS	String	50	
	"receiverState"	CM	As per payout corridor: AUS	String	50	
	"occupation"			String	256	static data
	"receiverEmail"			String	50	
	"reference"		Additional field for reference details			
"receiverPayoutDetails"						
	"paymentType"	Yes	accepts as "D" for Account Deposit/Bank Transfer "C" for Cash Pay "W" for Wallet Pay for current HUB, we can receive available payment method from Get Catalog API			
"receiverPayoutDetails". "bankDetails" (If Payment Type is BankTransfer/ AccountDeposit then this object is active)		Yes	for this object If "paymentType" = "D" then BankDetails object is mandatory			
	"bankAccountType"	Yes	Accepted values as: "SAVINGS", "CURRENT", "NORMAL"	String	50	
	"bankName"	Yes	Received from the get agent list	String	256	
	"bankBranch"			String	50	
	"bankAccountNo"	Yes		String	50	
	"bankCode"			String	50	
	"bankBranchCode"			String	50	
	"routeNo"	conditional mandatory (CM)	For Payout corridors: AUS, IND, BGD, USA (may change as per regulatory)	String	50	
	"reference"			String	256	

"receiverPayoutDetails". "walletDetails" (If Payment Type is Wallet then this object is active)		Yes	for this object If "paymentType" = "W" then BankDetails object is mandatory			
	"walletEntityName"	Yes		String	256	
	"walletAccountValue"	Yes		String	50	
	"walletBranch"			String	50	
	"walletCode"			String	50	
	"walletBranchCode"			String	50	
	"routeNo"			String	50	
	"reference"			String	256	
"receiverPayoutDetails". "cashPickupDetails" (If Payment Type is Cash pay then this object is active)		Yes	for this object If "paymentType" = "C" then BankDetails object is mandatory			
	"cashpointEntityName"	Yes		String	256	
	"cashPickupReferenceValue"	Yes		String	50	
	"cashpointBranch"			String	50	
	"cashpointCode"			String	50	
	"cashpointCode"			String	50	
	"routeNo"			String	50	
	"reference"			String	256	
"receiverPayoutDetails". "otherPayDetails" (If Payment Type is Others then this object is active)		Yes	for this object If "paymentType" other than above then OtherPayDetails object is mandatory			
	"payingEntityName"	Yes		String	256	
	"payoutAccountValue"	Yes		String	50	
	"payoutBranch"			String	50	
	"payoutCode"			String	50	
	"payoutBranchCode"			String	50	
	"reference"			String	256	

7.3 Response:

```
{
  "responseCode": "0",
  "responseMessage": "Transaction saved successfully",
  "agentSessionId": "f6cd9286-e509-4fdd-8769-9f4778a00c1c",
  "data": {
    "pinNo": "IPAY213676932",
    "agentTxnId": "SM2000829CC02004",
    "collectAmt": "15.3500",
    "collectCurrency": "SGD",
    "exchangeRate": "54.1703",
    "serviceCharge": "10.0000",
    "payoutAmt": "290.0000",
    "payoutCurrency": "INR",
    "txnDate": "9/16/2024 7:04:00 PM",
    "partnerSettlement": "15.3500",
    "partnerCcyRate": ""
  }
}
```

Field for DATA response	Description
CODE	0 if Success otherwise Error Code
AGENT_SESSION_ID	Partner Session ID
MESSAGE	System Message
PINNO	Random Unique Transaction PINNO which is used for beneficiary to pick up cash
AGENT_TXNID	Partner Unique TXN ID for each transaction.
COLLECT_AMT	Total Amount to be collection from Customer including service fee
COLLECT_CURRENCY	Remit Currency e.g. MYR
SERVICE_CHARGE	Service Fee in Collect Currency
EXCHANGE_RATE	Exchange Rate
PAYOUT_AMT	Total Payout Amount to Payout Location
PAYOUTCURRENCY	Payout Currency
PARTNER_CCYRATE	Partner currency rate
TXN_DATE	Transaction Date and Time as recorded as of time
PARTNER_SETTLEMENT	Partner Settlement

8. Authorized Confirm

For Two step API configuration enabled partner for confirming transaction, Partner needs to call this API to approve from partner side.

If partner does not want to confirm the transaction, then partner can call Cancel Transaction API

Method POST

URL: <https://sendingmwdev.isendremit.com/api/v2/AuthorizedConfirm>

8.1 Request Body:

```
{
  "pinNo": "IPAY219284857"
}
```

8.2 Field Details

Field	Data Type	Max Length	Description	Required
"pinNo"	String	16	Pin no received from SendTransaction API when transaction is created.	Y

8.3 Response:

```
{
  "responseCode": "0",
  "responseMessage": "TXN Approved",
  "agentSessionId": "c138d057-a6f5-42f2-9df1-bc3e52a5545c",
  "data": {
    "pinNo": "IPAY223609395",
    "senderName": "MANISH TEST USER",
    "payoutAmt": "290.0000",
    "payoutCurrency": "INR"
  }
}
```

Field for Data response	Data Type	Max Length	Description
Code	string	4	if "0" Success, else Error
AGENT_SESSION_ID	String		Agent Session ID
MESSAGE	String	100	System Message
PINNO	String	16	Random Unique Transaction PINNO which is used for beneficiary to pick up cash.
SENDER_NAME	String	180	Full Sender Name

PAYOUTAMT	Money		Total Amount to be Paid to Beneficiary in Payout CCY
PAYOUTCURRENCY	String	3	Payout Currency
STATUS	String	30	Status of Transaction - HOLD (txn need to confirm by sender, auth confirm enabled) - COMPLIANCE (Txn is in compliance in HUB) - UN-PAID (TXN is initialized in HUB, no further status dertermined, wait for further status) - POST (TXN in in payout processing) - PAID (Txn successful in HUB, PAID) - CANCEL (TXN returned, failed, expired in HUB)

9. Cancel Transaction

For Two step API configuration enabled partner for confirming transaction, Partner needs to call this API to approve from partner side.

If partner does not want to confirm the transaction, then partner can call Cancel Transaction API

Method POST

URL: <https://sendingmwdev.isendremmit.com/api/v2/CancelTransaction>

9.1 Request Body:

```
{
  "pinNo": "IPAY00000001",
  "cancelReason": "Cancel"
}
```

9.2 Field Detail:

Field	Data Type	Max Length	Description	Required
"pinNo"	String	20	PinNo received in SendTransaction API	Y
"cancelReason"	string	50	Reason of cancel	Y

9.3 Response:

```
{
  "responseCode": "0",
  "responseMessage": "Transaction Cancelled Request Received ID:91",
  "agentSessionId": "a93c380b-a6f6-482b-90fb-ca7406b3b2fa",
  "data": {
    "pinNo": "IPAY218223826"
  }
}
```

10. Query Transaction

This method is called to get the status of the created transactions

Method GET

URL: <https://sendingmwdev.isendremit.com/api/v2/TransactionResponses/QueryTransactionStatus>

10.1 Request Param:

S.N	Param Name	Mand - atory	Field Type / Length	Remarks and Description
1	PinNo	Y if no Agent Txn Id is given	String	PinNo received in SendTransaction API response
2	AgentTxnId	Y If no PinNo is given	String	Value used in "transactionDetails"."agentTxnId" when SendTransaction API is called. This is not recommended which may have duplicate values as per multiple partners. USE PinNo for exact enquiry

10.2 Response

```
{
  "responseCode": "0",
  "responseMessage": "TXN Summary",
  "agentSessionId": "a8d43e41-1cef-4de5-bce0-771074d2ec7a",
  "data": {
    "pinNo": "IPAY218223826",
    "senderName": "MANISH TEST USER",
    "receiverName": "GHANENDRA BAHUBALI",
    "collectAmt": "15.35",
    "collectCurrency": "SGD",
    "exchangeRate": "54.1703",
    "serviceCharge": "10.00",
    "payoutAmt": "290.0000",
    "payoutCurrency": "INR",
    "partnerSettlement": "15.35",
    "partnerCcyRate": "1.35",
    "status": "CANCEL",
    "statusDate": "2024-09-16 18:20:42",
    "cancelWithCharge": ""
  }
}
```

STATUS	Status of Transaction - HOLD (txn need to confirm by sender, auth confirm enabled) - COMPLIANCE (Txn is in compliance in HUB) - UN-PAID (TXN is initialized in HUB, no further status determined, wait for further status) - POST (TXN in in payout processing) - PAID (Txn successful in HUB, PAID) - CANCEL (TXN returned, failed, expired in HUB)
--------	--

11. Account Validation

This method is called to check the payout account validation.

Note: This is a work-in-progress, currently available for limited corridors only.

Method GET

URL: <https://sendingmwdev.isendremmit.com/api/v2/accountValidation>

11.1 Request Body

```
{
  "paymentType": "D",
  "receiveCountryCode": "NPL",
  "receiveAmount": {
    "value": "5000",
    "currencyCode": "NPR"
  },
  "payoutChannelName": "Agriculture Development Bank",
  "payoutChannelCode": "BSBAUS",
  "accountCode": "012332",
  "accountNumber": "6792849152",
  "receiver": {
    "name": "Romman",
    "lastName": "Rai",
    "idType": "",
    "idNumber": ""
  },
  "sender": {
    "name": "Manish",
    "lastName": "Maharjan"
  }
}
```

11.2 Field Details

Account validation fields	Man - datory	Details	
paymentType	M	Accepts: D - Account Deposit W – Wallet Pay	
receiveCountryCode	M	Receiver/ Payout country in ISO 3 code format	
receiveAmount {}			
value	M	Payout amount	
currencyCode	M	Payout currency	
payoutChannelName	M	Payout channel name such as bank name or wallet name received from get Agent List	
payoutChannelCode	M	Payout channel code received from get Agent List	
accountCode	CM	Account code such as routing codes, BSB or IFSC as per payout corridors and accounts	
accountNumber	M	Payout Account detail / Account number	
receiver {}			
name	M	Receiver name	
lastName		Receiver last name	
idType		Receiver id type	
IdNumber		Received id number	
sender{}			
name		Sender Name	
lastName		Sender last name	

11.3 Response

Success Response

HTTP/1.1 200 OK

Content-Type: application/json

```
{
  "message": "Success"
}
```

Failed Response

```
{
  "error": {
    "code": "02",
    "message": " Invalid Account ",
    "target": "accountNumber"
  }
}
```

}

Response cases and error codes

Scenario	HTTP Status Code	"error.code"	Message	
Validation is Success	200		Success	
Account Number provided is not correct	400	02	Invalid Account Number	
Bad Syntax	400	22	Invalid Request	
Invalid Bank code	400	13	Invalid Bank/Routing code	
Invalid Access	401	27	Unauthorized	
Internal Error or not able to validate because of any reasons	500	10	Unable to verify account	

Appendix – Response Codes

ResponseCode	Code	Description
0	0	Success
1001	1001	Required Field is Empty
1004	1004	Invalid Parameter
1005	1005	Duplicate Agent TXN ID
2003	2003	Invalid Transaction
3001	3001	Invalid Payment Mode
3003	3003	Invalid Location ID
3006	3006	Agent TXN ID is missing
3008	3008	Select Country is not allowed
3009	3009	Sent Amount must be more than Service Charge
3012	3012	Partner Balance Exceed, Cannot Make a TXN
9001	9001	Technical Error
9002	9002	Server Busy
9999	999	invalid field value for <i>fieldname</i> , internal errors