RAJALAKSHMI ENGINEERING COLLEGE

Aashish Durai M 251801002-2025-AIDS

A2

Started on	Saturday, 12 September 2026, 2:00 PM
State	Finished
Completed on	Saturday, 12 September 2026, 2:23 PM
Time taken	23 mins 13 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive int and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 an any efficient algorithm to find the possible ways.

Example 1:

Input: *6*
Output:*6*
Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1
3+3
1+1+1+3
1+1+3+1
1+3+1+1
3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

long long countWays(int n) {
    if (n < 0) return 0;
    if (n == 0) return 1;

    long long *dp = (long long *)calloc(n + 1, sizeof(long long));
    if (dp == NULL) return 0;

    dp[0] = 1;

    for (int i = 1; i <= n; i++) {
        if (i >= 1) {
            dp[i] += dp[i - 1];
        }
        if (i >= 3) {
            dp[i] += dp[i - 3];
        }
    }

    long long result = dp[n];
    free(dp);
    return result;
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        printf("%lld\n", countWays(n));
    }
    return 0;
}
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Aashish Durai M 251801002-2025-AIDS

A2

Started on	Saturday, 3 October 2026, 4:20 PM
State	Finished
Completed on	Saturday, 3 October 2026, 4:25 PM
Time taken	4 mins 38 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to r position by traveling the maximum monetary path under the condition that he can only travel one step right or one step board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int board[n][n];
    int dp[n][n];


    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &board[i][j]);
        }
    }


    dp[0][0] = board[0][0];

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {

            if (i == 0 && j == 0)
                continue;

            if (i == 0) {
                dp[i][j] = dp[i][j - 1] + board[i][j];
            }
            else if (j == 0) {
                dp[i][j] = dp[i - 1][j] + board[i][j];
            }
            else {
                if (dp[i - 1][j] > dp[i][j - 1])
                    dp[i][j] = dp[i - 1][j] + board[i][j];
                else
                    dp[i][j] = dp[i][j - 1] + board[i][j];
```

```
            }
        }
    }

    printf("%d\n", dp[n - 1][n - 1]);

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 4 2 3 4 8 7 1	19	19	✔
✔	3 1 3 1 1 5 1 4 2 1	12	12	✔
✔	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Aashish Durai M 251801002-2025-AIDS

A2

Started on	Saturday, 3 October 2026, 4:26 PM
State	Finished
Completed on	Saturday, 3 October 2026, 4:30 PM
Time taken	3 mins 49 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	**g**	**t**	**a**	**b**
s2	**g**	x	**t**	**x**	**a**	**y**	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <string.h>

int main() {
    char s1[100], s2[100];

    scanf("%s", s1);
    scanf("%s", s2);

    int m = strlen(s1);
    int n = strlen(s2);

    int dp[m + 1][n + 1];

    // Initialize first row and first column
    for (int i = 0; i <= m; i++) {
        for (int j = 0; j <= n; j++) {
            if (i == 0 || j == 0) {
                dp[i][j] = 0;
            }
        }
    }

    // Fill DP table
    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {

            if (s1[i - 1] == s2[j - 1]) {
                dp[i][j] = dp[i - 1][j - 1] + 1;
            }
            else {
                if (dp[i - 1][j] > dp[i][j - 1])
                    dp[i][j] = dp[i - 1][j];
                else
                    dp[i][j] = dp[i][j - 1];
            }
        }
    }

    printf("%d", dp[m][n]);

    return 0;
}
```

	Input	Expected	Got	
✔	aab azb	2	2	✔
✔	ABCD ABCD	4	4	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Aashish Durai M 251801002-2025-AIDS

A2

Started on	Saturday, 3 October 2026, 4:31 PM
State	Finished
Completed on	Saturday, 3 October 2026, 4:34 PM
Time taken	3 mins 15 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[n];
    int dp[n];


    for (int i = 0; i < n; i++) {
        scanf("%d", &a[i]);
        dp[i] = 1;
    }

    int maxLength = 1;


    for (int i = 1; i < n; i++) {
        for (int j = 0; j < i; j++) {

            if (a[j] <= a[i]) {
                if (dp[j] + 1 > dp[i]) {
                    dp[i] = dp[j] + 1;
                }
            }
        }

        if (dp[i] > maxLength) {
            maxLength = dp[i];
        }
    }

    printf("%d", maxLength);

    return 0;
}
```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course