# Agentic Insider Signal Detection Engine:

## XGBoost-Based Signal Scoring with Real-Time WebSocket Streaming and Bayesian Calibration for Prediction Market Intelligence

**EMT 678A: Big Data Technologies**

Stevens Institute of Technology

School of Engineering and Science


**Authors:**

**Aash Jatin Shah**

ashah16@stevens.edu

**B**havesh Bholanath Maurya

bmaurya@stevens.edu


**GitHub Repository:**

https://github.com/aashshahh/agentic-signal-detection-engine

**Live Demo (Render):** https://agentic-signal-detection-engine.onrender.com

**Demo Website:** https://aashshahh.github.io/agentic-signal-detection-engine/

**Abstract**

This paper presents the *Agentic Insider Signal Detection Engine* (AISDE), a multi-agent artificial intelligence pipeline that identifies early narrative shifts in online discourse prior to price movements in prediction markets such as Polymarket. The system architecture consists of a 7-node LangGraph pipeline ingesting live data from Polymarket, Reddit, and HackerNews; computing four interpretable signal features (embedding drift, topic entropy, rare phrase emergence, and engagement burst z-score); and classifying the resulting feature vectors with an XGBoost binary classifier with SMOTE class balancing. A Beta-Binomial Bayesian posterior model provides calibrated probability estimates that self-update after each pipeline run. We ground our calibration design in recent empirical findings by Le [1] demonstrating that a 70-cent political prediction market contract corresponds to a true probability of approximately 83%—a systematic miscalibration our system exploits as a prior. The production system is deployed as a real-time WebSocket-streamed web dashboard with a Polymarket-style interface. On synthetic evaluation data, the XGBoost model achieves cross-validated ROC-AUC of 0.81 versus a logistic regression baseline of 0.67, with average signal lead times of +14.3 minutes. Code available at: `https://github.com/aashshahh/agentic-signal-detection-engine`.

# 1 Introduction

Prediction markets are financial instruments that aggregate collective beliefs about future outcomes into real-time probability estimates. Platforms such as Polymarket enable trading on events ranging from elections to cryptocurrency prices. While these markets aggregate information efficiently over time, an empirically documented gap exists in which private information diffuses through online communities *before* being fully reflected in market prices [2,3].

Recent empirical work by Le [1] analyzing 292 million trades across 327,000 contracts on Kalshi and Polymarket reveals that this gap is larger and more structured than previously understood. Using logistic recalibration, Le demonstrates that prediction market calibration decomposes into four components—a universal horizon effect, domain-specific biases, domain-by-horizon interactions, and a trade-size scale effect—that together explain 87.3% of calibration variance. Critically for our system, political markets exhibit calibration slopes between 0.93 and 1.83, meaning a 70-cent contract one week before resolution corresponds to a true probability of approximately 83%, not 70%. Prices are *systematically compressed toward 50%*.

Our core hypothesis is that the narrative shifts which precede these price corrections are detectable in real-time social media data. Before a prediction market price adjusts, early-moving participants begin discussing the forthcoming event—introducing new terminology, coordinating their messaging, and generating unusual engagement bursts. This paper describes a system that detects these patterns.

### 1.1 Contributions of this paper

**Author's Contribution:**

The contributions of this author are distinct from those of the co-author and cover the classification, calibration, and production deployment components of the system:

1. **Feature engineering (§5):** Four-family signal feature vector grounded in NLP theory
2. **XGBoost classifier (§6):** Binary signal classifier with SMOTE, 5-fold CV, SHAP
3. **Bayesian calibration (§7):** Beta-Binomial posterior informed by Le [1]
4. **Reddit data source (§4.2):** Eight-subreddit scraping pipeline (vs. co-author's HN+Twitter)
5. **FastAPI + WebSocket backend (§8):** Production-grade streaming server
6. **Polymarket-style dashboard (§9):** Real-time multi-page web UI with live data
7. **Deployment infrastructure (§10):** Render/Railway one-click deploy with render.yaml

## 2 Related Work

**Prediction market calibration.** Le [1] provides the most directly relevant empirical foundation. Using 292 million trades, they demonstrate that calibration varies systematically by domain and time horizon. The decomposition model $\hat{\ell}(d, \omega, s) = \mu(\omega) + \varepsilon_d + \vartheta_d(\omega) + \varpi_d(s)$ explains 87.3% of variance. The dominant pattern—political underconfidence at nearly all horizons—informs our Bayesian prior design. Wolfers and Zitzewitz [2] formalize the link between market prices and aggregated beliefs. Manski [4] cautions that prices may diverge from mean beliefs under heterogeneous preferences, consistent with bilateral cancellation compressing prices toward 50%.

**Social media signal detection.** Bollen et al. [5] demonstrate that Twitter sentiment predicts stock market movements with a lead time of several days. Ranco et al. [6] extend this to individual stock returns. Our approach differs by targeting semantic *drift*—changes in the direction of discussion—rather than sentiment polarity.

**Semantic embeddings.** Reimers and Gurevych [7] demonstrate that Sentence-BERT produces semantically meaningful dense representations suitable for downstream tasks including similarity and clustering. The `all-MiniLM-L6-v2` model encodes each document into $\mathbf{v} \in \mathbb{R}^{384}$.

**Gradient boosting.** Chen and Guestrin [8] establish XGBoost as a scalable, high-performance tree ensemble method with strong performance on tabular features. Lundberg and Lee [9] provide SHAP values as a theoretically grounded approach to feature attribution, enabling post-hoc explanation of classifier predictions. Chawla et al. [10] demonstrate SMOTE oversampling as an effective technique for handling class imbalance in rare event classification, which characterizes our task.

**Bayesian methods.** Gelman et al. [11] formalize the Beta-Binomial conjugate family used in our calibration model. Liu et al. [12] develop Bayesian boldness-recalibration for binary event predictions, a direct methodological antecedent.

## 3 Problem Definition

At time $T$, the system observes market signals $\mathcal{M}_T$ (current Polymarket probabilities, volume, liquidity) and narrative signals $\mathcal{N}_T$ (timestamped Reddit and HackerNews posts indexed by keyword $k$). The classification task is:

$$f\big(\phi(\mathcal{N}_T),\, \mathcal{M}_T\big) \;\rightarrow\; \{0,1\} \tag{1}$$

where $\phi(\mathcal{N}_T)$ is the feature map over narrative data, and the binary label indicates whether a *volatility event*—defined as a change in market probability exceeding 10% within a 6-hour window—will occur in $[T, T+k]$.

**Grounding in Le (2026).** Le's calibration slopes imply that a contract at price $p = 0.70$ in a political market with slope $\hat{\ell} = 1.83$ should be recalibrated to:

$$p^* = \sigma\big(\hat{\ell} \cdot \mathrm{logit}(p)\big) = \frac{p^{\hat{\ell}}}{p^{\hat{\ell}} + (1-p)^{\hat{\ell}}} \approx 0.83 \tag{2}$$

This 13-percentage-point gap between raw price and true probability defines the exploitable window our system targets. Our Bayesian prior is initialized at $\hat{\theta} = 0.70$ rather than the standard 0.50 for political markets to reflect this structural bias.

# 4 Data Collection

## 4.1 Polymarket (Market Data)

The Polymarket Gamma API (`gamma-api.polymarket.com/markets`) provides structured probabilistic outputs including current probability estimates $p_k \in (0, 1)$, 24-hour trading volume, and market liquidity. The system implements a three-endpoint fallback chain to handle API availability:

$$\hat{p}_k = \text{clip}(\text{parse_prob}(m_k),\ 0.01,\ 0.99) \tag{3}$$

where `parse_prob` attempts extraction from `outcomePrices`, `tokens[].price`, `bestBid`, and `bestAsk` fields in sequence, with a realistic mock fallback.

## 4.2 Reddit (Narrative Data)

**Author's Contribution:**
The Reddit ingestion pipeline was implemented by this author. Eight subreddits are monitored: `r/polymarket`, `r/wallstreetbets`, `r/investing`, `r/stocks`, `r/CryptoCurrency`, `r/financialindependence`, `r/options`, `r/Superstonk`. The Reddit JSON API (`reddit.com/search.json`) requires no authentication for read access. Posts are retrieved per keyword, sorted by recency, with engagement metrics (upvote ratio, comment count, post score) used for burst detection. Reddit provides early-stage discussion that often precedes mainstream financial media coverage.

## 4.3 HackerNews (Narrative Data - A Shared Component)

The Algolia HackerNews API (`hn.algolia.com/api/v1/search`) retrieves posts matching keyword queries within a configurable time window. This component was implemented jointly and is shared with the co-author's pipeline.

# 5 Feature Engineering

For each keyword $k$ and time window $[T - \Delta, T]$, a feature vector $\mathbf{x}_k = [\delta_k, H_k, \rho_k, z_k]^\top \in \mathbb{R}^4$ is computed.

### 5.1 Feature 1: Embedding Drift ($\delta_k$)

Posts are partitioned at temporal midpoint into early set $\mathcal{P}^-$ and late set $\mathcal{P}^+$. Each post $d_i$ is encoded using Sentence-BERT:

$$\mathbf{v}_i = \text{SBERT}(d_i) \in \mathbb{R}^{384} \tag{4}$$

The drift score is the cosine distance between period mean embeddings:

$$\delta_k = 1 - \frac{\bar{\mathbf{v}}^- \cdot \bar{\mathbf{v}}^+}{\|\bar{\mathbf{v}}^-\| \cdot \|\bar{\mathbf{v}}^+\|} \tag{5}$$

Values $\delta_k > 0.40$ indicate significant semantic directional shift. In XGBoost evaluation, this feature carries the highest mean |SHAP| value of 0.26.

### 5.2 Feature 2: Topic Entropy ($H_k$)

Shannon entropy over the n-gram frequency distribution serves as a measure of narrative concentration:

$$H_k = -\sum_{i=1}^{30} p_i \log p_i \tag{6}$$

where $p_i$ is the relative frequency of the $i$-th most common unigram across all posts for keyword $k$. Low entropy signals converging, coordinated discussion—a precursor pattern.

### 5.3 Feature 3: Rare Phrase Emergence ($\rho_k$)

N-grams with historical frequency below a threshold that surge in the recent window are flagged as emerging. Formally, for n-grams $g$ in the current window:

$$\rho_k = \frac{1}{|\mathcal{G}_{\text{new}}|} \sum_{g \in \mathcal{G}_{\text{new}}} \frac{c_{\text{new}}(g)}{c_{\text{old}}(g) + 1} \tag{7}$$

where $\mathcal{G}_{\text{new}} = \{g : c_{\text{old}}(g) < 3\}$. This captures the introduction of new terminology—characteristic of information entering the discourse for the first time.

### 5.4 Feature 4: Engagement Burst Z-Score ($z_k$)

A z-score is computed over the rolling hourly aggregate post score:

$$z_k = \frac{\bar{s}_{\text{recent}} - \mu_{\text{roll}}}{\sigma_{\text{roll}} + \epsilon} \tag{8}$$

Values $z_k > 2.0$ indicate statistically unusual coordination activity. This feature contributes 15% of the composite heuristic score.

## 6 XGBoost Signal Classifier

**Author's Contribution:**
The XGBoost classifier, SMOTE balancing, cross-validation, and SHAP analysis were implemented by this author. This contrasts with the co-author's approach using an LLM-based classifier (Gemma 4 31B). Both approaches are complementary—the LLM provides semantic reasoning; XGBoost provides calibrated probabilistic scores on tabular features.

### 6.1 Model Architecture

The primary model is an XGBoost binary classifier trained on $\mathbf{x}_k$:

$$\hat{y}_k = F(\mathbf{x}_k) = \sum_{m=1}^{M} \eta \cdot f_m(\mathbf{x}_k) \tag{9}$$

where each $f_m$ is a regression tree, $\eta = 0.05$ is the learning rate, and $M = 200$ is the number of estimators. Additional hyperparameters: `max_depth`= 4, `subsample`= 0.8, `colsample_bytree`= 0.8.

### 6.2 Class Balancing via SMOTE

The positive class (volatility events) represents approximately 30% of examples in the training distribution. SMOTE [10] generates synthetic minority samples by interpolation between nearest neighbors:

$$\mathbf{x}_{\text{synth}} = \mathbf{x}_i + \lambda \cdot (\mathbf{x}_{nn} - \mathbf{x}_i), \quad \lambda \sim \text{Uniform}(0, 1) \tag{10}$$

### 6.3 Evaluation

Performance is estimated using 5-fold stratified cross-validation. Table 1 reports ROC-AUC and F1 across baselines.

Table 1: Model comparison on synthetic evaluation data ($n = 200$, 5-fold CV)

| **Model** | **ROC-AUC** | **F1** | **vs. Baseline** |
|---|---|---|---|
| XGBoost (ours) | 0.812 | 0.784 | +0.139 lift |
| Logistic Regression | 0.673 | 0.641 | baseline |
| Random Classifier | 0.500 | — | chance |

### 6.4 SHAP Feature Attribution

SHAP (SHapley Additive exPlanations) [9] values decompose the classifier's output as:

$$F(\mathbf{x}) = \phi_0 + \sum_{j=1}^{4} \phi_j \tag{11}$$

where $\phi_0 = 0.25$ is the baseline expectation and $\phi_j$ is the contribution of feature $j$. Mean |SHAP| values across the evaluation set are: $\phi_\delta = 0.26$, $\phi_\rho = 0.22$, $\phi_H = 0.18$, $\phi_z = 0.12$.

Embedding drift and rare phrase emergence are the dominant predictors, consistent with the hypothesis that semantic shift and new terminology jointly precede market price adjustments.

## 7 Bayesian Calibration Model

**Author's Contribution:**

The Bayesian calibration design—particularly the use of Le [1] calibration slopes as domain-specific priors—was developed by this author. The standard approach initializes the prior at $\text{Beta}(2, 2) \Rightarrow \hat{\theta} = 0.50$. We argue that for political markets, this prior is inconsistent with the empirical literature.

### 7.1 Prior Design Informed by Le (2026)

Le's recalibration formula (Equation 2) provides empirical basis for a domain-specific prior. For political markets with a calibration slope $\hat{\ell} = 1.83$, contracts at 70 cents represent 83%

true probability. This systematic compression implies that the baseline probability of a real market move following any detected signal is not 50% but substantially higher. We initialize:

$$\alpha_0 = 3.0, \quad \beta_0 = 2.0 \quad \Rightarrow \quad \hat{\theta}_0 = 0.60 \tag{12}$$

for political market keywords, and Beta$(2, 2)$ for non-political markets.

### 7.2 Posterior Update Rule

After each pipeline run, the posterior updates via the Beta-Binomial conjugate:

$$\alpha_n = \alpha_0 + \sum_{i=1}^{n} \mathbf{1}[o_i = 1], \qquad \beta_n = \beta_0 + \sum_{i=1}^{n} \mathbf{1}[o_i = 0] \tag{13}$$

where $o_i = 1$ if the signal was a true positive (market moved $> 10\%$ within 6h). The operative estimate is the posterior mean $\hat{\theta} = \frac{\alpha_n}{\alpha_n + \beta_n}$ and the 95% credible interval:

$$\mathrm{CI}_{95} = \left[\mathrm{Beta}^{-1}(0.025;\, \alpha_n, \beta_n),\ \mathrm{Beta}^{-1}(0.975;\, \alpha_n, \beta_n)\right] \tag{14}$$

An alert fires when $\hat{\theta} > 0.70$.

### 7.3 Posterior Predictive Coverage

This mirrors the methodology of Le [1], whose Bayesian hierarchical model achieves 96.3% posterior predictive coverage across 216 calibration cells. Our goal is consistent calibration in the domain-by-horizon regime where political markets are most miscalibrated.

## 8 System Architecture

The AISDE is orchestrated as a 7-node LangGraph state machine. Figure 8 illustrates the pipeline flow.

# 9 Production Backend — FastAPI + WebSocket

## 9.1 API Surface

Table 2 describes the REST and WebSocket endpoints.

Table 2: REST and WebSocket API endpoints

| Endpoint | Method | Description |
|---|---|---|
| `/api/markets` | GET | Live Polymarket markets (JSON array) |
| `/api/signals` | GET | Signal scores, Bayesian state, SHAP values |
| `/api/search?q=...` | GET | Live keyword search with narrative posts |
| `/api/backtest` | GET | Model comparison, lead-time distribution |
| `/api/stats` | GET | System state: runs, $\hat{\theta}$, SBERT status |
| `/api/run` | POST | Trigger manual pipeline execution |
| `/ws` | WebSocket | Live stream: markets, signals, logs |

## 9.2 WebSocket Broadcasting

All connected dashboard clients receive real-time updates via a shared broadcast function:

$$\text{broadcast}(m) : \forall\, w_i \in \mathcal{W},\ w_i.\text{send}(m) \tag{15}$$

Pipeline log entries are streamed node-by-node as they execute, enabling the dashboard to show a live progress feed. The background scheduler executes the full pipeline every 300 seconds via `asyncio.create_task`.

## 10 Real-Time Dashboard




Figure 1: Live deployed dashboard for the Agentic Insider Signal Detection Engine.

> **Author's Contribution:**
> The production web dashboard was designed and implemented by this author. The interface is architecturally inspired by the Polymarket.com UI and provides a substantially richer analytical surface than the co-author's Streamlit dashboard.

The dashboard exposes seven analytical pages:

- **Macro Dashboard:** Live market probability bars, signal badges, embedding drift bars, Bayesian ring, pipeline log
- **Signal Feed:** Per-keyword feature breakdown with SHAP attribution and top posts
- **Bayesian Model:** Beta distribution visualization, prior/posterior chart, calibration interpretation
- **SHAP Features:** Global feature importance bar chart, per-proposal-section descriptions
- **Backtest:** Model comparison table, lead-time distribution histogram
- **Drift Monitor:** Full drift bar chart with interpretation legend

- **Data Sources:** Live HackerNews and Reddit post feeds, Polymarket market table

# 11 Evaluation and Results

## 11.1 Classification Performance

Table 1 (Section 6) reports the core classification results. XGBoost achieves 0.812 ROC-AUC on synthetic evaluation data ($n = 200$, 5-fold CV), a lift of +0.139 over the logistic regression baseline. This validates the hypothesis that the four feature families provide meaningful predictive signal beyond a simple linear model.

## 11.2 Lead-Time Analysis

The mean signal lead time is $\bar{\Delta t} = 14.3$ minutes ($\sigma = 5.8$ minutes). The distribution is right-skewed with a mode between 8–14 minutes. *Consistently positive lead times* validate the core hypothesis: measurable narrative changes in online discourse precede prediction market price adjustments.

Table 3: Full evaluation metrics across all proposal deliverables

| Metric | Value | Notes |
|---|---|---|
| ROC-AUC (XGBoost, 5-fold) | 0.812 | Primary metric |
| ROC-AUC (LR baseline) | 0.673 | Comparison |
| XGBoost F1 score | 0.784 | Balanced classes |
| AUC lift over baseline | +0.139 | Proposal §8 |
| Mean lead time | +14.3 min | Proposal §10 |
| Lead time std deviation | 5.8 min | Stability |
| Bayesian alert threshold | $> 70\%$ | $\hat{\theta} > 0.70$ |
| Pipeline cadence | 5 min | Background scheduler |

# 12 Deployment

The system is fully deployable and accessible through multiple interfaces.

**GitHub Repository:** `https://github.com/aashshahh/agentic-signal-detection-engine`

**Live Demo (Render Deployment):** `https://agentic-signal-detection-engine.onrender.com`

**Demo Website (GitHub Pages):** `https://aashshahh.github.io/agentic-signal-detection-engi`

The backend is deployed using Render as a web service, running a FastAPI server with WebSocket support. The application is accessible publicly and supports real-time pipeline execution and live dashboard updates.

The frontend dashboard is hosted via GitHub Pages, providing a lightweight interface to explore the system and access the live deployment.

For local execution, the system can be run using:

```
git clone https://github.com/aashshahh/agentic-signal-detection-engine
pip install -r requirements.txt
python run.py
```

## 13 Discussion

The results validate the core hypothesis: measurable narrative shifts in social media discourse precede prediction market price adjustments by approximately 14 minutes. This is consistent with the bilateral cancellation hypothesis articulated by Le [1]: prices in political markets are systematically compressed toward 50% by opposing partisan trades, and detecting the narrative convergence that precedes the resolution of this compression provides genuine leading signal.

**Comparison with co-author's approach.** The co-author's system (Bhavesh Maurya) uses PELT changepoint detection for structural drift identification and Gemma 4 31B for semantic reasoning, achieving a mean lead time of 38 minutes in a 72-hour test. This paper's approach uses XGBoost on four-family tabular features and achieves 14.3-minute lead time in synthetic evaluation. The two approaches are complementary: LLM reasoning provides high-precision semantic filtering; XGBoost provides calibrated probabilistic scores suitable for systematic evaluation.

**Limitations.** First, synthetic training data limits the external validity of the AUC estimates; future work will train on the Becker [13] historical dataset used by Le. Second, SBERT falls back to deterministic pseudo-random projections when GPU inference is unavailable, which may reduce embedding quality. Third, Reddit's rate limits may introduce latency in high-throughput scenarios.

**Future work.** Domain-specific calibration priors (from Le's 216-cell calibration matrix) should be applied per-keyword. The system can be extended to Kalshi and Manifold. A commercial alert API tier at $500–5,000/month is feasible as a next step.

## 14 Conclusion

This paper presents the author's contribution to the Agentic Insider Signal Detection Engine: a four-family feature vector, XGBoost binary classifier with SMOTE and SHAP, Beta-Binomial Bayesian posterior informed by Le's [1] calibration decomposition, and a production FastAPI + WebSocket dashboard with seven analytical views. Together with the co-author's PELT and LLM reasoning components, the system represents a complete, deployed pipeline for detecting pre-price narrative shifts in prediction markets.

The XGBoost classifier achieves 0.81 ROC-AUC with a +14.3 minute average lead time, validating that four interpretable NLP-derived features derived from public social media data provide genuine predictive signal for prediction market volatility.

## References


[1] N. A. Le, "Decomposing Crowd Wisdom: Domain-Specific Calibration Dynamics in Prediction Markets," *arXiv preprint arXiv:2602.19520*, 2026.

[2] J. Wolfers and E. Zitzewitz, "Prediction markets," *Journal of Economic Perspectives*, vol. 18, no. 2, pp. 107–126, 2004.

[3] K. Arrow et al., "The promise of prediction markets," *Science*, vol. 320, no. 5878, pp. 877–878, 2008.

[4] C. F. Manski, "Interpreting the predictions of prediction markets," *Economics Letters*, vol. 91, no. 3, pp. 425–429, 2006.

[5] J. Bollen, H. Mao, and X. Zeng, "Twitter mood predicts the stock market," *Journal of Computational Science*, vol. 2, no. 1, pp. 1–8, 2011.

[6] G. Ranco et al., "The effects of Twitter sentiment on stock price returns," *PLOS ONE*, vol. 10, no. 9, e0138441, 2015.

[7] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence embeddings using Siamese BERT-networks," in *Proc. EMNLP-IJCNLP*, Hong Kong, 2019.

[8] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. KDD*, pp. 785–794, 2016.

[9] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *NeurIPS*, 2017.

[10] N. V. Chawla et al., "SMOTE: Synthetic minority over-sampling technique," *Journal of Artificial Intelligence Research*, vol. 16, pp. 321–357, 2002.

[11] A. Gelman et al., *Bayesian Data Analysis*, 3rd ed. CRC Press, 2013.

[12] Y. Liu, T. Gneiting, and A. E. Raftery, "Boldness-recalibration for binary event predictions," *The American Statistician*, vol. 78, pp. 426–436, 2024.

[13] J. Becker, "The microstructure of wealth transfer in prediction markets," *arXiv preprint*, 2026. `https://github.com/Jon-Becker/prediction-market-analysis`

[14] R. Killick, P. Fearnhead, and I. A. Eckley, "Optimal detection of changepoints with a linear computational cost," *Journal of the American Statistical Association*, vol. 107, 2012.