Day 9 — APIs and Extensions

Cisco AppDynamics Professional Implementer (500-430 CAPI) · 10-day course · Blueprint 5.1–5.6 (Domain 5 = 20%)

Goal: authenticate to the Controller APIs, retrieve applications, tiers, nodes, BTs, metrics and health rule violations, create custom events, and build and install alerting and monitoring extensions.
Verification: every fact checked against the current Splunk AppDynamics docs (November 2026). Version note: the newest docs (25.10+) describe metric-data-v2; older Controllers and exam material use the classic metric-data — both are shown.

Block 1 — API basics and authentication

- Base path: https://<controller>/controller/rest/... · XML is the **default**, add **output=JSON** · URL-encode spaces and pipes in metric paths.
- **Basic auth:** username = <user>@<account> — on-prem single-tenant account **customer1**; SaaS = your account name.

```
curl --user admin@customer1:<password> "https://<ctrl>/controller/rest/applications?output=JSON"
```

API client + OAuth token (recommended for scripts)

1. **Administration → API Clients → + Create**: name, Generate Secret, token expiry, roles. Needs **Account Owner** (or Administer users, groups, roles).
2. Request a token (POST, form-encoded) — reply has access_token (JWT) and expires_in. **Default expiry: 5 minutes.**
3. Send Authorization: Bearer <token> on each call. Invalid/expired token → **HTTP 401**.

```
curl -X POST -H "Content-Type: application/x-www-form-urlencoded" \
  "https://<ctrl>/controller/api/oauth/access_token" \
  -d 'grant_type=client_credentials&client_id=<clientName>@<account>&client_secret=<secret>'

curl -H "Authorization: Bearer <access_token>" \
  "https://<ctrl>/controller/rest/applications?output=JSON"
```

Block 2 — Application Model API (5.5)

Retrieve	URI (GET)
Business applications	/controller/rest/applications
Business transactions	/controller/rest/applications/<app>/business-transactions
Tiers	/controller/rest/applications/<app>/tiers
Nodes in the application	/controller/rest/applications/<app>/nodes
Nodes in one tier	/controller/rest/applications/<app>/tiers/<tier>/nodes
Backends	/controller/rest/applications/<app>/backends

<app> can be the application **name or ID**.

Block 3 — Metric and Snapshot API (5.6)

- **Browse the tree:** GET /controller/rest/applications/<app>/metrics?metric-path=<path> → items are **folder** or **leaf**.

```
GET /controller/rest/applications/<app>/metric-data      <- classic (older Controllers / exam)
GET /controller/rest/applications/<app>/metric-data-v2   <- newest docs (25.10+)
    ?metric-path=Overall Application Performance|Average Response Time (ms)
    &time-range-type=BEFORE_NOW&duration-in-mins=60&rollup=false&output=JSON
```

Parameter	Rule
time-range-type	BEFORE_NOW (+ duration-in-mins), BEFORE_TIME, AFTER_TIME, BETWEEN_TIMES (+ start-time / end-time in **milliseconds**)
rollup	**Default true** = one combined value for the range; false = every data point
Wildcards	* in a path segment, e.g. Application Infrastructure Performance|*|Agent|App|Availability = every tier

- **Copy REST URL:** right-click a metric in the Metric Browser — exact path plus the selected time range.
- Granularity: 1-minute for ranges up to 24 h within the last 8 days; longer ranges hourly. On-prem retention defaults 4 h / 48 h / 365 days.
- **Snapshots:** GET .../request-snapshots — same time parameters, filters business-transaction-ids, user-experience, error-occurred, maximum-results (default **600**).

Block 4 — Alert and Respond API (5.2, 5.4)

```
GET /controller/rest/applications/<app>/problems/healthrule-violations
    ?time-range-type=BEFORE_NOW&duration-in-mins=60&output=JSON

GET /controller/rest/applications/<app>/events
    ?time-range-type=BEFORE_NOW&duration-in-mins=30
    &event-types=APPLICATION_ERROR,DIAGNOSTIC_SESSION&severities=INFO,WARN,ERROR
```

Events: at most **600** per call. **Create a custom event** (needs the Create Events permission):

```
curl -X POST --user admin@customer1:<pwd> \
 "https://<ctrl>/controller/rest/applications/PetClinic/events?severity=INFO\
&summary=Release%202.1%20deployed&eventtype=CUSTOM&customeventtype=deployment\
&propertynames=version&propertynames=team&propertyvalues=2.1&propertyvalues=web"
```

Parameter	Rule
summary, eventtype=CUSTOM, severity	**Required**; severity INFO, WARN or ERROR
customeventtype	Optional label (deployment, nagios ...)
node, tier, bt	Optional; **tier required** if node or bt is given
propertynames / propertyvalues	Paired **by position** — N names need N values; values up to 5,000 characters

Block 5 — Configuration Import and Export API

What	Export	Import	Format
Actions	GET /controller/actions/<app_id>	POST same path	JSON
Health rules	GET /controller/healthrules/<app_id>?name=<rule>	POST /controller/healthrules/<app_id>?overwrite=true|false	XML
Transaction detection	GET /controller/transactiondetection/<app_id>/...	POST with -F file=@rules.xml	XML

overwrite defaults to **false**. These paths are under /controller/, **not** /controller/rest/. The docs recommend the Health Rule API over XML import for health rules.

Block 6 — Alerting extensions: custom actions (5.1, 5.3)

On-prem only (SaaS: contact support).

1. Script in <controller_home>/custom/actions/<type>/ (.sh executable on Linux, .bat on Windows).
2. Describe it in <controller_home>/custom/actions/custom.xml.
3. **Restart the Controller.**
4. Controller UI: create a **Custom Action** and attach it to a **policy**.

```
<custom-actions>
  <action>
    <type>servicenow</type>            <!-- = subfolder name -->
    <executable>create-incident.sh</executable>
  </action>
</custom-actions>
```

- **Downloaded alerting extension (5.3):** unzip into custom/actions/<type>/, add the custom.xml entry, fill in its config, restart the Controller, create the action, attach to a policy.
- **Script input:** positional parameters. Health rule violation: $1 APP_NAME, $2 APP_ID, then PVN_ALERT_TIME, PRIORITY, SEVERITY, ACTION_NAME, HEALTH_RULE_NAME, HEALTH_RULE_ID ... ending with DEEP_LINK_URL. Other events use EN_TIME.
- **HTTP Request Actions:** template-based webhooks (ServiceNow, Slack) — no script, no Controller restart.

Block 7 — Monitoring extensions with scripts (Machine Agent)

1. Create <machine_agent_home>/monitors/<MyMonitor>/ (agent user needs read/write/execute).
2. Script prints one line per metric to STDOUT (format below).
3. monitor.xml: <type>managed</type>; execution-style **periodic** (every minute by default) or **continuous** (script loops); <executable-task> names the script per OS.
4. **Restart the Machine Agent**; the metric appears after about a minute.
5. Windows: use PowerShell or VBScript, not .bat (batch quotes metric names, so they're ignored).

```
name=Custom Metrics|Queue|Depth,value=42,aggregator=OBSERVATION,time-rollup=CURRENT,
     cluster-rollup=COLLECTIVE          (one line in real output)
```

Part	Options
value	**Long integer** (whole number)
aggregator (per minute)	**AVERAGE** (default), SUM, OBSERVATION (last value)
time-rollup	AVERAGE, SUM, CURRENT
cluster-rollup	INDIVIDUAL (average across nodes), COLLECTIVE (add across nodes)
Path prefix	Custom Metrics|... = all tiers · Server|Component:<tier>|... = one tier (Machine Agent associated with it)

Lab — SaaS + curl (~60 min)

1. **API client:** create one, request a token, call /controller/rest/applications?output=JSON.
2. **Application model:** PetClinic tiers, nodes, BTs and backends as JSON.

3. **Metrics:** browse /metrics; Copy REST URL for Average Response Time; run with rollup=true and rollup=false; wildcard Availability for every tier.
4. **Custom event:** post a deployment event with version=2.1 and team=web; find it in PetClinic's Events.
5. **Violations:** last 60 minutes of health rule violations from the Day 8 rule.
6. **Paper:** (a) custom.xml + script outline for an on-prem "servicenow" alerting extension; (b) a Linux monitoring script reporting Custom Metrics|Lab|TCP Connections.

Day 9 Quiz — with answer key

Cover the answer lines and test yourself first.

Q1. Basic-auth username format for a single-tenant on-prem Controller?

A. customer1/admin
B. admin@customer1
C. admin:customer1
D. root@system
Answer: B — <user>@<account>; on-prem account customer1.

Q2. Default lifetime of an API-client OAuth token?

A. 5 minutes
B. 1 hour
C. 24 hours
D. Never expires
Answer: A — expires_in 300; configurable per client.

Q3. URI listing all nodes in tier Web of PetClinic?

A. /controller/rest/nodes?tier=Web
B. /controller/rest/applications/PetClinic/tiers/Web/nodes
C. /controller/rest/applications/PetClinic/nodes/Web
D. /controller/api/tiers/Web
Answer: B — App by name or ID.

Q4. metric-data returns one value for 60 minutes — why?

A. No data
B. rollup defaults to true; use rollup=false
C. output=JSON missing
D. BEFORE_NOW returns latest only
Answer: B — rollup=true combines the range.

Q5. Easiest way to get a correct metric path?

A. Guess from dashboard
B. Metric Browser → Copy REST URL
C. agent.log
D. Health rule XML
Answer: B — Includes path and time range.

Q6. URI for health rule violations in the last hour?

A. .../problems/healthrule-violations?time-range-type=BEFORE_NOW&duration-in-mins=60
B. /controller/healthrules/<app_id>
C. .../events?eventtype=CUSTOM
D. /controller/api/violations
Answer: A — /controller/healthrules is the config export.

Q7. Custom event with node=web01 — which parameter becomes required?

A. bt
B. tier
C. comment
D. customeventtype
Answer: B — tier is required with node or bt.

Q8. New custom action script + custom.xml installed — next?

A. Restart Machine Agent
B. Restart Controller, create Custom Action, attach to policy
C. Nothing
D. Upload via REST
Answer: B — On-prem only.

Q9. Valid Machine Agent script output line?

A. Custom Metrics|Queue|Depth=42.5
B. name=Custom Metrics|Queue|Depth,value=42,aggregator=OBSERVATION
C. metric: Queue Depth 42
D. JSON object
Answer: B — Values are long integers.

Q10. Health rule import, existing same-name rule — default?

A. Replaced
B. Not overwritten (overwrite=false)
C. Both kept
D. Import fails
Answer: B — Set overwrite=true to replace.

Quick-review cheat sheet

Remember	Value
Auth	Basic user@account (on-prem customer1) · OAuth API client → Bearer token (5 min default)
Token URL	POST /controller/api/oauth/access_token · grant_type=client_credentials · client_id=name@account
Format	XML default · output=JSON
App model	/applications · /<app>/tiers · /nodes · /tiers/<tier>/nodes · /business-transactions · /backends
Metrics	/<app>/metrics (browse) · /metric-data (classic) or /metric-data-v2 · rollup default true · * wildcard
Time ranges	BEFORE_NOW · BEFORE_TIME · AFTER_TIME · BETWEEN_TIMES (ms)
Violations	/<app>/problems/healthrule-violations
Custom event	POST /<app>/events · summary + eventtype=CUSTOM + severity · tier if node/bt · names/values by position
Limits	600 events per call · 600 snapshots default
Config export	/controller/actions (JSON) · /controller/healthrules (XML, overwrite=false default)
Custom action	custom/actions/<type>/script + custom.xml · restart Controller · action → policy · on-prem only
Script args	$1 APP_NAME · $2 APP_ID · ... · DEEP_LINK_URL last
Script extension	monitors/<name>/ + monitor.xml · name=...,value=<long> · restart Machine Agent

Sources

- API Clients
- Using the Controller APIs
- Application Model API
- Metric and Snapshot API
- Events API (Alert and Respond)
- Configuration Import and Export API
- Create a Custom Action (on-prem)
- Contents of the custom.xml File
- Information Passed to the Custom Action Script
- Build a Monitoring Extension Using Scripts

Lab — model answers

What a correct result looks like for each Day 9 lab task. Replace <ctrl>, <account> and secrets with your own; use HTTPS on SaaS.

1. API client and token

```
TOKEN=$(curl -s -X POST -H "Content-Type: application/x-www-form-urlencoded" \
  "https://<ctrl>/controller/api/oauth/access_token" \
  -d 'grant_type=client_credentials&client_id=labclient@<account>&client_secret=<secret>' \
  | python3 -c 'import sys,json; print(json.load(sys.stdin)["access_token"])')
curl -s -H "Authorization: Bearer $TOKEN" \
  "https://<ctrl>/controller/rest/applications?output=JSON"
```

Expected: a JSON array of applications (name, id, description). After 5 minutes the same token returns HTTP 401 — request a new one.

2. Application model

```
B="https://<ctrl>/controller/rest/applications/PetClinic"
curl -s -H "Authorization: Bearer $TOKEN" "$B/tiers?output=JSON"
curl -s -H "Authorization: Bearer $TOKEN" "$B/nodes?output=JSON"
curl -s -H "Authorization: Bearer $TOKEN" "$B/tiers/Web/nodes?output=JSON"
curl -s -H "Authorization: Bearer $TOKEN" "$B/business-transactions?output=JSON"
curl -s -H "Authorization: Bearer $TOKEN" "$B/backends?output=JSON"
```

Expected: tier Web (and the .NET tier from Day 6), node web01, the PetClinic BTs, and backends such as the MySQL database.

3. Metrics

```
curl -s -H "Authorization: Bearer $TOKEN" "$B/metrics?output=JSON"     # top-level folders
curl -s -G -H "Authorization: Bearer $TOKEN" "$B/metric-data" \
  --data-urlencode "metric-path=Overall Application Performance|Average Response Time (ms)" \
  -d time-range-type=BEFORE_NOW -d duration-in-mins=60 -d rollup=false -d output=JSON
# wildcard: Availability for every tier
  --data-urlencode "metric-path=Application Infrastructure Performance|*|Agent|App|Availability"
```

- rollup=true → one entry in metricValues (the combined value for the hour). rollup=false → about 60 one-minute values.
- curl -G with --data-urlencode handles the spaces and pipes. On a newer Controller, metric-data-v2 accepts the same parameters.
- Copy REST URL from the Metric Browser gives a ready-made URL you can paste into curl.

4. Custom deployment event

```
curl -s -X POST -H "Authorization: Bearer $TOKEN" \
 "$B/events?severity=INFO&summary=Release%202.1%20deployed&eventtype=CUSTOM\
&customeventtype=deployment&propertynames=version&propertynames=team\
&propertyvalues=2.1&propertyvalues=web"
```

Expected: the reply confirms creation; PetClinic → Events (filter Custom) shows "Release 2.1 deployed" with properties version=2.1, team=web. The API client's role needs the Create Events permission.

5. Health rule violations

```
curl -s -H "Authorization: Bearer $TOKEN" \
 "$B/problems/healthrule-violations?time-range-type=BEFORE_NOW&duration-in-mins=60&output=JSON"
```

Expected: entries for the Day 8 rule (name, severity, start time, affected BT) if it fired; an empty array if not — generate slow requests and retry.

6a. On-prem "servicenow" alerting extension

```
<controller_home>/custom/actions/
├── custom.xml
└── servicenow/
    └── create-incident.sh        (chmod +x)

<custom-actions>
  <action>
    <type>servicenow</type>
    <executable>create-incident.sh</executable>
  </action>
</custom-actions>
```

```
#!/bin/bash
APP_NAME="$1"; APP_ID="$2"; ALERT_TIME="$3"; PRIORITY="$4"; SEVERITY="$5"
ACTION_NAME="$6"; RULE_NAME="$7"; RULE_ID="$8"
DEEP_LINK="${@: -1}"                  # DEEP_LINK_URL is the last argument
curl -s -u "$SN_USER:$SN_PASS" -H "Content-Type: application/json" \
  -X POST "https://bank.service-now.com/api/now/table/incident" \
  -d "{\"short_description\":\"AppD $SEVERITY: $RULE_NAME on $APP_NAME\",
       \"description\":\"$DEEP_LINK\"}"
```

Then **restart the Controller**, create a Custom Action of type servicenow, and attach it to a policy on health rule violations. On SaaS, use an HTTP Request Action template instead.

6b. Monitoring script: Custom Metrics|Lab|TCP Connections

```
#!/bin/bash                    # <MA_HOME>/monitors/TcpMonitor/tcp.sh
COUNT=$(ss -tan state established | tail -n +2 | wc -l)
echo "name=Custom Metrics|Lab|TCP Connections,value=${COUNT},aggregator=OBSERVATION,\
time-rollup=CURRENT,cluster-rollup=INDIVIDUAL"
```

```
<monitor>
  <name>TcpMonitor</name>
  <type>managed</type>
  <monitor-run-task>
    <execution-style>periodic</execution-style>
    <name>Run</name>
    <type>executable</type>
    <task-arguments></task-arguments>
    <executable-task>
      <type>file</type>
      <file os-type="linux">tcp.sh</file>
    </executable-task>
  </monitor-run-task>
</monitor>
```

The echo must print the whole line without a line break (the backslash above only wraps it for the page). chmod +x tcp.sh, restart the Machine Agent, and after about a minute the metric appears under Custom Metrics → Lab → TCP Connections.

Postman equivalents of every curl request

The same Day 9 requests (plus the Day 7 Machine Agent listener) set up in Postman. Import the two JSON files sent with these notes (**AppDynamics_Day9_Postman_Collection.json** and **AppDynamics_Lab_Postman_Environment.json**), or build them by hand from the tables below.

One-time setup

1. Postman → **Import** → select both JSON files.
2. Top-right environment selector → **AppDynamics Lab**; fill in the values below (Current value column).
3. The collection's Authorization tab is **Bearer Token = {{token}}**; every request inherits it unless shown otherwise.
4. Run **Get OAuth token** first — its Tests script saves the token into {{token}}. Re-run it after 5 minutes (HTTP 401 = expired).

Variable	Example value	Purpose
baseUrl	https://<your-account>.saas.appdynamics.com	Controller URL, no trailing slash (on-prem e.g. http://ctrl.bank.local:8090)
account	<your-account>	On-prem single-tenant: customer1
user	<username>	For Basic auth
password	<password>	For Basic auth (secret)
clientName	labclient	API client name
clientSecret	<secret>	API client secret (secret)
token		Filled automatically by 'Get OAuth token'
app	PetClinic	Application name or ID
appId	<numeric id>	Numeric ID for config export/import
tier	Web	Tier name
maListener	http://localhost:8293	Machine Agent HTTP listener

Tests script on **Get OAuth token**:

```
const j = pm.response.json();
pm.environment.set("token", j.access_token);
```

Authentication

Get OAuth token

Setting	Value
Method + URL	**POST** {{baseUrl}}/controller/api/oauth/access_token
Authorization	No Auth
Body	x-www-form-urlencoded: grant_type = client_credentials client_id = {{clientName}}@{{account}} client_secret = {{clientSecret}}
Note	Tests tab saves the token: pm.environment.set("token", pm.response.json().access_token). Token lasts 5 min by default.

List applications (Basic auth)

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications
Params tab	output = JSON
Authorization	Basic Auth — {{user}}@{{account}} / {{password}}
Note	Authorization tab → Basic Auth: Username {{user}}@{{account}}, Password {{password}}.

Application Model

List applications

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Tiers

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/tiers
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Nodes in application

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/nodes
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Nodes in tier

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/tiers/{{tier}}/nodes
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Business transactions

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/business-transactions
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Backends

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/backends
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Metrics and Snapshots

Browse metric tree

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/metrics
Params tab	output = JSON
Authorization	Inherit from collection (Bearer {{token}})
Note	Add metric-path (e.g. Overall Application Performance) to go one level deeper.

Metric data - all points (rollup=false)

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/metric-data
Params tab	metric-path = Overall Application Performance|Average Response Time (ms) time-range-type = BEFORE_NOW duration-in-mins = 60 rollup = false output = JSON
Authorization	Inherit from collection (Bearer {{token}})
Note	Postman encodes spaces and pipes in the Params tab. Newer Controllers (25.10+): metric-data-v2, same params.

Metric data - one value (rollup=true)

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/metric-data
Params tab	metric-path = Overall Application Performance|Average Response Time (ms) time-range-type = BEFORE_NOW duration-in-mins = 60 rollup = true output = JSON
Authorization	Inherit from collection (Bearer {{token}})
Note	rollup=true is the default.

Metric data - wildcard, every tier

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/metric-data
Params tab	metric-path = Application Infrastructure Performance|*|Agent|App|Availability time-range-type = BEFORE_NOW duration-in-mins = 60 output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Request snapshots

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/request-snapshots
Params tab	time-range-type = BEFORE_NOW duration-in-mins = 60 output = JSON
Authorization	Inherit from collection (Bearer {{token}})
Note	maximum-results defaults to 600.

Alert and Respond

Health rule violations

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/problems/healthrule-violations
Params tab	time-range-type = BEFORE_NOW duration-in-mins = 60 output = JSON
Authorization	Inherit from collection (Bearer {{token}})

Get events

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/rest/applications/{{app}}/events
Params tab	time-range-type = BEFORE_NOW duration-in-mins = 30 event-types = APPLICATION_ERROR,DIAGNOSTIC_SESSION,CUSTOM severities = INFO,WARN,ERROR output = JSON
Authorization	Inherit from collection (Bearer {{token}})
Note	Up to 600 events per call.

Create custom event

Setting	Value
Method + URL	**POST** {{baseUrl}}/controller/rest/applications/{{app}}/events
Params tab	severity = INFO summary = Release 2.1 deployed eventtype = CUSTOM customeventtype = deployment propertynames = version propertynames = team propertyvalues = 2.1 propertyvalues = web
Authorization	Inherit from collection (Bearer {{token}})
Note	Repeat propertynames/propertyvalues as separate rows, in matching order. Needs the Create Events permission.

Config Import Export

Export actions

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/actions/{{appId}}
Authorization	Inherit from collection (Bearer {{token}})
Note	Numeric application ID; JSON.

Export one health rule

Setting	Value
Method + URL	**GET** {{baseUrl}}/controller/healthrules/{{appId}}
Params tab	name = PetClinic Response Time
Authorization	Inherit from collection (Bearer {{token}})
Note	XML.

Import health rules

Setting	Value
Method + URL	**POST** {{baseUrl}}/controller/healthrules/{{appId}}
Params tab	overwrite = false
Authorization	Inherit from collection (Bearer {{token}})
Body	form-data: key **file** (type File) → the exported XML
Note	Body → form-data, key 'file' of type File. overwrite defaults to false.

Machine Agent listener (Day 7)

Post custom metric

Setting	Value
Method + URL	**POST** {{maListener}}/api/v1/metrics
Authorization	No Auth
Body	raw → JSON: [{"metricName":"Custom Metrics|Lab|Orders","aggregatorType":"SUM","value":10}]
Note	Full URL http://localhost:8293/api/v1/metrics; Header Content-Type: application/json. Run on the Machine Agent host (localhost only by default).