PIZZA

ORDER NOW

DISCOUNT · DISCOUNT · DISCOUNT · DISCOUNT

25%

RETRIEVE TOTAL NUMBER OF ORDER PLACED.

```
SELECT COUNT(ORDER_ID) FROM ORDERS;
```

Result Grid

	COUNT(ORDER_ID)
▸	21350

CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES.

```sql
SELECT
    ROUND(SUM(ORDER_DETAILS.QUANTITY * PIZZAS.PRICE),
            2)
FROM
    ORDER_DETAILS
        INNER JOIN
    PIZZAS ON PIZZAS.PIZZA_ID = ORDER_DETAILS.PIZZA_ID;
```

Result Grid | Filter Rows:

ROUND(SUM(ORDER_DETAILS.QUANTITY * PIZZAS.PRICE), 2)
817860.05

IDENTIFY THE HIGHEST PRICE PIZZA.

```sql
SELECT
    PIZZA_TYPES.NAME, PIZZAS.PRICE
FROM
    PIZZA_TYPES
        JOIN
    PIZZAS ON PIZZAS.PIZZA_TYPE_ID = PIZZA_TYPES.PIZZA_TYPE_ID
ORDER BY PIZZAS.PRICE DESC
LIMIT 1;
```

Result Grid | Filter Row

NAME	PRICE
The Greek Pizza	35.95

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED.

```sql
SELECT
    PIZZAS.SIZE,
    COUNT(ORDER_DETAILS.ORDER_DETAILS_ID) AS ORDER_COUNT
FROM
    PIZZAS
        INNER JOIN
    ORDER_DETAILS ON PIZZAS.PIZZA_ID = ORDER_DETAILS.PIZZA_ID
GROUP BY PIZZAS.SIZE
ORDER BY ORDER_COUNT DESC
LIMIT 1;
```

Result Grid | Filter Rows:

	SIZE	ORDER_COUNT
▶	L	18526

LIST TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITY.

```sql
SELECT
    PIZZA_TYPES.NAME, SUM(ORDER_DETAILS.QUANTITY) AS TOTAL_SALES
FROM
    PIZZA_TYPES
        JOIN
    PIZZAS ON PIZZA_TYPES.PIZZA_TYPE_ID = PIZZAS.PIZZA_TYPE_ID
        JOIN
    ORDER_DETAILS ON ORDER_DETAILS.PIZZA_ID = PIZZAS.PIZZA_ID
GROUP BY PIZZA_TYPES.NAME
ORDER BY TOTAL_SALES DESC
LIMIT 5;
```

Result Grid | Filter Rows:

NAME	TOTAL_SALES
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

JOIN THE NECESSARY TABLES TO FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED

```sql
SELECT
    PIZZA_TYPES.CATEGORY,
    SUM(ORDER_DETAILS.QUANTITY) AS TOTAL_SALES_CATEGORY
FROM
    PIZZA_TYPES
        JOIN
    PIZZAS ON PIZZA_TYPES.PIZZA_TYPE_ID = PIZZAS.PIZZA_TYPE_ID
        JOIN
    ORDER_DETAILS ON ORDER_DETAILS.PIZZA_ID = PIZZAS.PIZZA_ID
GROUP BY CATEGORY;
```

Result Grid Filter Rows:

CATEGORY	TOTAL_SALES_CATEGORY
Classic	14888
Veggie	11649
Supreme	11987
Chicken	11050

DETERMINE THE DISTRIBUTION OF ORDERS BY HOURS OF THE DAY

```sql
SELECT
    HOUR(ORDER_TIME) AS HOUR, COUNT(ORDER_ID)
FROM
    ORDERS
GROUP BY HOUR;
```

Result Grid | Filter Rows:

HOUR	COUNT(ORDER_ID)
15	1468
16	1920
17	2336
18	2399
19	2009
20	1642
21	1198

Result 1

Join Relevant Tables to Discover the Category-Wise Distribution of Pizza.

```
SELECT
    PIZZA_TYPES.CATEGORY, COUNT(NAME) AS PIZZA_COUNT
FROM
    PIZZA_TYPES
GROUP BY CATEGORY;
```

Result Grid | Filter Rows:

CATEGORY	PIZZA_COUNT
Chicken	6
Classic	8
Supreme	9
Veggie	9

GROUP THE ORDER BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY.

```sql
SELECT
    ROUND(AVG(SUM_SALES))
FROM
    (SELECT
        ORDERS.ORDER_DATE, SUM(ORDER_DETAILS.QUANTITY) AS SUM_SALES
    FROM
        ORDERS
    JOIN ORDER_DETAILS ON ORDERS.ORDER_ID = ORDER_DETAILS.ORDER_ID
    GROUP BY ORDER_DATE) AS AVG_SALES_PERDAY;
```

Result Grid | Filter Rows:

ROUND(AVG(SUM_SALES))
138

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPE BASED ON REVENUE.

```sql
SELECT
    PIZZA_TYPES.NAME,
    SUM(ORDER_DETAILS.QUANTITY * PIZZAS.PRICE) AS REVENUE
FROM
    PIZZA_TYPES
        JOIN
    PIZZAS ON PIZZA_TYPES.PIZZA_TYPE_ID = PIZZAS.PIZZA_TYPE_ID
        JOIN
    ORDER_DETAILS ON ORDER_DETAILS.PIZZA_ID = PIZZAS.PIZZA_ID
GROUP BY PIZZA_TYPES.NAME
ORDER BY REVENUE DESC
LIMIT 3;
```

Result Grid | Filter Rows:

NAME	REVENUE
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5