Conditioning, Guidance, and Memorization in Diffusion Image Generation

Aathi Muthu
DSC 180A, Domain D32

November 6, 2026

Abstract

Diffusion generators offer several ways to control an image, but stronger conditioning need not improve every measure of quality. This project studies class conditioning and classifier-free guidance using the design framework of Karras et al. We examine pretrained EDM models on CIFAR-10, investigate smaller conditional EDM networks on restricted training sets, and train a conditional U-Net from scratch on MNIST. Paired initial noise isolates the effects of class requests and guidance strength. Evaluation combines requested-class accuracy, feature-distribution distances, sampling trajectories, and comparisons with nearby training examples. In the completed MNIST experiment, increasing guidance from one to two raises requested-digit accuracy from 96.4% to 100%, while classifier-feature FID increases from 22.10 to 85.14. This illustrates a measurable tradeoff between class matching and agreement with the real feature distribution. Numerical findings are reported only for completed experiments in the preliminary-results section.

1 Introduction

1.1 Problem and motivation

Generating an image from noise requires both a learned description of the data and a procedure for turning that description into a sample. Class-conditional generation adds a request, such as "cat" or the digit seven. A useful generator should satisfy that request while retaining plausible variation within the class. These goals motivate three questions: how does a condition influence denoising over the sampling trajectory; how does guidance strength change class matching and the generated distribution; and how does the amount of training data affect similarity to the training set?

The central reference is *Elucidating the Design Space of Diffusion-Based Generative Models* (EDM) [1]. It separates choices in sampling, network preconditioning, and training, making these components easier to inspect and compare. This project applies that framework to controlled experiments with the supplied course labs. The pretrained CIFAR-10 experiments examine inference behavior, while the restricted-data runs and MNIST training examine how a network acquires conditional and unconditional estimates.

This separation matters because improvements to the sampling procedure can be studied with a pretrained model held fixed. For example, EDM's Heun sampler corrects an Euler proposal using a second slope evaluation and uses an Euler step when the next noise level is zero. Network preconditioning addresses a different issue: input and output scales vary strongly with noise. EDM represents the denoiser as a noise-dependent skip connection plus a scaled network prediction, and combines this parameterization with a weighted denoising loss and a log-normal distribution of training noise levels. Our sampling and training experiments keep these roles distinct.

1.2 Related work

Denoising diffusion probabilistic models connect image generation to iterative denoising and denoising score matching [2]. Song et al. [3] describe score-based generation through stochastic differential equations and an associated probability-flow ordinary differential equation. EDM builds on this line of work by organizing design choices and improving sampling and training [1].

Classifier-free guidance combines conditional and unconditional estimates to adjust the balance between sample fidelity and diversity without requiring a classifier gradient [4]. We use the course convention

$$D_w(x;\sigma,c) = D_u(x;\sigma) + w\big(D_c(x;\sigma,c) - D_u(x;\sigma)\big),$$

so $w = 0$ ignores the request and $w = 1$ uses the conditional estimate. The released conditional EDM checkpoint has no label dropout, so the pretrained experiments use separate conditional and unconditional networks. Our trained networks instead hide the label on 10% of training examples, allowing one network to supply both estimates. Classifiers are used only for evaluation.

1.3 Data

CIFAR-10 contains 32-by-32 RGB images in ten object classes, with 50,000 training images and 10,000 test images. The lab downloads a fixed Hugging Face copy and verifies checksums. Pretrained models and the all-class FID reference come from NVIDIA's EDM release. Small-data training uses balanced subsets of 100 and 1,000 training images, corresponding to 10 and 100 examples per class. Real test images provide a comparison group for nearest-training-image distances.

MNIST contains 28-by-28 grayscale digit images with 60,000 training images and 10,000 test images. All training digits are available to the new conditional U-Net; no supplied generator weights are loaded for this experiment. Images are scaled to $[-1, 1]$. The frozen course digit classifier supplies predicted labels and 128-dimensional features. We use the test split as the real reference for MNIST feature FID. Our present scope is digit and object-class control; no additional attribute dataset is used.

2 Experimental protocol

CIFAR-10 sampling uses the lab's deterministic 18-step Heun sampler. The pretrained guidance sweep uses $w \in \{0, 1, 1.5, 2, 3, 4\}$, with 1,000 generated images and balanced requests at each setting. Initial noise is paired across settings. We report all-class Inception FID and class-specific FID averaged across requested classes; each conditional class comparison has 100 generated images. FID values from different feature spaces or sample counts are not directly comparable.

The small CIFAR networks follow Part 6 of the lab: the approximately 7M-parameter EDM network, EDM loss, Adam with learning rate $2 \cdot 10^{-4}$, batch size 64, and exponential moving averages. The planned schedule is 20,000 updates with five evaluated snapshots per training subset. Training loss and snapshot FID are complemented by generated/training image pairs and pixel-distance comparisons against real test images. These measurements test for evidence of memorization rather than assuming it from the subset size alone.

MNIST training uses the lab U-Net with 64 base channels and 11 label embeddings, where label 10 denotes no request. Its cosine path is $x_t = \sin(\pi t/2)x_1 + \cos(\pi t/2)x_0$, with t sampled uniformly and x_0 standard Gaussian. We minimize clean-image mean squared error using Adam at $2 \cdot 10^{-4}$, batch size 128, and EMA weights. This training objective is an implementation choice consistent with the lab's clean-image predictor; it is distinct from EDM's weighted loss. The default budget

is 10,000 updates. Evaluation uses 32 deterministic DDIM steps, $w \in \{0, 1, 2, 4\}$, 1,000 balanced requests per setting, and paired noise. Actual completed updates accompany every training result.

3 Preliminary results

Evaluator checks. Before scoring generated samples, the frozen classifiers achieved 94.4% accuracy on all 10,000 real CIFAR-10 test images and 99.32% on all 10,000 real MNIST test images in local checks. These rates calibrate the evaluators; they are not generator accuracy results.

Unconditional trajectory. In the three displayed seed-0 examples, the denoiser estimate is a nearly uniform blur at $\sigma = 80$. Coarse structure emerges as noise decreases, and recognizable content appears between the displayed levels $\sigma \approx 3.3$ and $\sigma \approx 1.1$. Composition changes little from $\sigma \approx 0.3$ onward, although edges and texture continue to sharpen. This observation concerns these three trajectories, not a universal class-decision threshold.

Conditional trajectories. For the three cat requests at seed 2, recognizable cat structure is evident by $\sigma \approx 1.1$ for both $w = 1$ and $w = 4$. In the second example, the $w = 4$ estimate already has clearer ears and a face at $\sigma \approx 3.3$, while the $w = 1$ estimate remains more ambiguous. Thus stronger guidance can expose class structure earlier in these examples, but the displayed grid does not establish one threshold shared by all images. Composition is broadly stable by $\sigma \approx 0.3$. At low noise, $w = 4$ produces stronger contrast and more pronounced fur and facial features; it also changes pose and proportions relative to $w = 1$.

Guidance grid. At $w = 0$, the paired seeds produce several different object classes, while conditional and guided rows move toward cats. Strong guidance sharpens some faces but does not resolve every sample: the sixth column remains very dark even at $w = 4$, and the first column changes body shape substantially. These examples do not justify treating larger guidance as uniformly better. Selecting a preferred weight remains pending the quantitative sweep.

MNIST guidance. After 10,000 training updates, requested-digit accuracy rises from 10.4% at $w = 0$ to 96.4% at $w = 1$ and 100% at both $w = 2$ and $w = 4$. Classifier-feature FID is lowest at $w = 1$ (22.10), increasing to 85.14 at $w = 2$ and 182.57 at $w = 4$. Thus improved class matching does not imply a closer match to the real feature distribution. Mean within-class pixel variance also decreases from 0.196 at $w = 1$ to 0.173 at $w = 4$, consistent with reduced variation, though pixel variance alone does not establish perceptual quality. We would choose $w = 1$ for the best measured feature-distribution match, or $w = 2$ when class adherence takes priority. Increasing to $w = 4$ provides no measured accuracy gain over $w = 2$ and substantially worsens feature FID.

CIFAR-10 guidance. The required 1,000-image sweep has not yet been imported.

CIFAR-10 training: 100 images. Results have not yet been imported.

CIFAR-10 training: 1000 images. Results have not yet been imported.

3.1 MNIST guidance

The model was trained from scratch for 10,000 updates. Evaluation uses 1000 generated images per setting and 10000 real test images. FID is measured in the frozen digit classifier feature space.

w	Accuracy	Feature FID
0	0.104	106.40
1	0.964	22.10
2	1.000	85.14
4	1.000	182.57

Remaining work. Numerical tables are generated from saved experiment files. CIFAR-10 quantitative guidance comparisons and subset-training evidence remain pending where indicated. The MNIST training and evaluation are complete. Predictions are not presented as observed results.




Figure 1: Unconditional pretrained EDM samples.

Reproducibility

Code and commands: https://github.com/aathijmuthu/DSC-180A-Checkpoint. Scripts reuse the supplied course notebook implementations and the lab's pinned NVIDIA EDM revision. Dependencies, data access, seeds, checkpoints, and commands for each artifact are documented in the repository. The optional full-data EDM training experiment is outside the current completed scope.

The local MNIST run resumed at update 6,500. Its early checkpoint predated MPS random-state persistence, so the subsequent training-noise stream restarted; current checkpoints preserve CPU, CUDA, and MPS random states. All guidance comparisons nevertheless use the same final weights and paired evaluation noise. Exact historical weights are saved locally, and the repository documents the training protocol and this interruption.

References

[1] T. Karras, M. Aittala, T. Aila, and S. Laine. Elucidating the Design Space of Diffusion-Based Generative Models. NeurIPS, 2022. https://arxiv.org/abs/2206.00364.



Figure 2: Conditional samples, with the same initial noise in each column.




Figure 3: Guidance toward cat with paired noise: stronger guidance emphasizes cat features, while the dark sixth-column example remains ambiguous.




Figure 4: Unconditional noisy states and clean-image estimates: broad structure precedes recognizable content, and late steps mainly refine detail in these three examples.




Figure 5: Conditional cat trajectories at $w = 1$: class structure becomes recognizable at intermediate noise and late steps refine detail.




Figure 6: Paired cat trajectories at $w = 4$: the second image shows clearer class structure earlier, and low-noise predictions have stronger contrast.




Figure 7: Illustration of mean and covariance contributions to FID in two dimensions.




Figure 8: MNIST training loss using uniform cosine-time denoising MSE.




Figure 9: MNIST guidance samples from the newly trained network.




Figure 10: MNIST requested-digit accuracy and classifier-feature FID versus guidance strength.

[2] J. Ho, A. Jain, and P. Abbeel. Denoising Diffusion Probabilistic Models. NeurIPS, 2020. https://arxiv.org/abs/2006.11239.

[3] Y. Song, J. Sohl-Dickstein, D. P. Kingma, A. Kumar, S. Ermon, and B. Poole. Score-Based Generative Modeling through Stochastic Differential Equations. ICLR, 2021. https://arxiv.org/abs/2011.13456.

[4] J. Ho and T. Salimans. Classifier-Free Diffusion Guidance. arXiv:2207.12598, 2022. https://arxiv.org/abs/2207.12598.