Krishak Robot: An Autonomous Ground Vehicle for Herbicide-Free Weed Management

Technical Project Documentation

Project Overview

The Krishak Robot is a versatile and multifunctional robot designed for agricultural purposes. It has a modular structure that allows for easy addition or removal of attachments depending on the task at hand. In this implementation, we propose a six-wheeled differential drive rocker bogie robot equipped with IR sensor, proximity sensor, AHRS, encoders, and cameras for providing accurate feedback for path planning and weed uprooting tasks while making sure that we are traversing along a straight path regardless of the terrain using encoders and yaw heading. The Krishak robotic arm placed at the front end has a 6 DOF arm designed based on the workspace envelope, allowing it to cover its entire surrounding workspace. The camera module recognizes whether a plant placed in front of the robot is a weed or a normal crop.

It performs object recognition with the help of hardware implemented ML algorithms. On detecting a weed, it communicates its location to the main microcontroller which then commands the arm to move to that location using inverse kinematics and then uproot it. With the use of machine learning algorithms and April tags for localization, the Krishak Robot can navigate autonomously in farm lands, performing its task of uprooting unwanted plants effectively. The software implementation of the programming model is done using FSM (Finite state machine) and can be seen in the System design section. Keywords-AHRS, Robotic arm, April tags, Inverse kinematics, Finite State machine, robotics, computer vision, Machine learning, Husky lens, differential drive.

1. Background and Introduction

I. INTRODUCTION With the growing population and increasing demand for food, agriculture has become one of the most important sectors globally. However, agriculture is also one of the most labour- intensive industries, requiring significant manual effort for activities such as planting, harvesting, and weeding. With advancements in robotics and automation, there has been a push towards developing agricultural robots that can perform these tasks with high efficiency and accuracy, reducing the need for human labour. One such robot is our Krishak Robot, sixwheeled differential drive rocker bogie robot equipped with IR sensor, proximity sensor, AHRS, encoders, cameras and 6d of robotic arm. Modular robotics allows for versatility, as attachments can be added or removed depending on the task at hand.

The Krishak Robot is designed to traverse agricultural fields autonomously, uprooting weeds and unwanted plants with the robotic arm. In this paper, we propose the development of the Krishak bot, which utilizes a Raspberry Pi as its processor and an Arduino Uno as a slave device. The robot’s path planning and trajectory generation is controlled by the Raspberry Pi, which receives location information from April tags used for localization in the field.The camera module mounted on the robot arm uses hardware implemented machine learning algorithms to differentiate between crops and unwanted plants, providing the coordinates of the weeds to the Arduino Uno for uprooting. The robot’s differential drive is controlled by a set of differential equations, allowing it to navigate through the field with precision. Overall, the Krishak Robot aims to revolutionize the agriculture industry by providing an efficient and autonomous solution to weeding and plant uprooting.

Moreover, with its modularity the same mechanism and hardware can be used for different applications such as autonomous greenhouse maintenance, ripened and unripened fruit segregation.

2. Related Approaches and Existing Methods

The paper presents a weed detection system that uses a high-resolution 3D camera and deep learning techniques to identify weeds in soybean fields. The system achieved an overall accuracy of 97.5. The paper presents a robot system that can navigate autonomously in greenhouse rows for tomato plant inspection and harvesting. The system is equipped with a vision system that uses machine learning techniques to identify ripe toma- toes. The system achieved a tomato detection rate of 99.7.

The paper presents a real-time fruit detection and localization system that uses deep learning techniques and smartphone-based data acquisition. The system achieved an average detection rate of 88.1. The paper provides an overview of the current state of agricultural robotics and the challenges and opportunities in the field. The paper discusses various applications of agricultural robotics, including crop monitoring, weed control, and harvesting. The authors also highlight the potential benefits of agricultural robotics, such as improved crop yields, reduced labour costs, and decreased environmental impact.

Existing Weed Control Systems and Drawbacks

p • Various approaches are employed for weed control in agriculture at present. These encompass mechanical, chemical, and cultural methods. Mechanical techniques, such as hand-weeding, hoeing, and tilling, are known to be effective but require significant labor and time. Chemical methods utilize herbicides, offering costeffectiveness and efficiency, though they may pose environmental and human health risks. Cultural methods, including crop rotation, mulching, and cover crops, are employed to curb weed growth.. B.

Limitations of current methods and the need for autonomous weed killer agricultural bots: • There are various constraints associated with current weed control methods in agriculture. Mechanical approaches may demand significant labor and time, and chemical methods could adversely affect the environment and human health. Furthermore, these methods might not prove universally effective for all weed types or in every crop system. Autonomous weed killer agricultural bots can overcome these limitations by providing a cost-effective and efficient alter- native to current methods. These bots can operate 24/7, providing continuous weed control without the need for human intervention.

They can also be programmed to target specific types of weeds or crop systems, providing targeted and effective weed control. C. Examples of existing autonomous agricultural bots in the market: • There are several existing autonomous agricultural botsin the market, including the BoniRob, Blue River Technology's See Spray, and the Ecorobotix. The BoniRobis a multi-purpose field robot that can be used for weed control, phenotyping, and plant breeding. It uses machine learning to detect and remove weeds from crops. Blue River Technology's See Spray is a sprayer that uses computer vision and machine learning to detect and spray individual weeds.

The Ecorobotix is a solarpowered weeding robot that uses a camera and sensors to detect and remove weeds. These bots have been shown to be effective in weed control, providing a promising alternative to current methods. D. Historical Context of Weed Management in Agriculture: • The historical context of weed management in agriculture spans centuries, reflecting the intricate relationship between humans and the environment. In ancient agricultural practices, weed control primarily relied on manual labor, with farmers physically removing unwanted plants. This labor-intensive approach limited the scale of cultivation and hindered agricultural productivity.

During the Middle Ages, advancements in agricultural tools, such as the introduction of the plow, allowed for more efficient cultivation. However, weed control still heavily relied on manual labor and rudimentary tools. The understanding of weed ecology and the development of specific weed management strategies were limited during this era. The Renaissance marked a period of increased scientific inquiry, and agricultural practices began to incorporate a more systematic approach. The emergence of botanical knowledge during this time laid the foundation for a better understanding of weeds.

As exploration expanded and trade routes opened, plants from different regions were introduced to new ecosystems, unintentionally introducing invasive species that further complicated weed management. • The 19th century witnessed significant changes in agriculture with the advent of the Industrial Revolution. The introduction of machinery, such as the steam engine and mechanized plows, revolutionized farming practices, making it possible to cultivate larger areas.

However, the increased scale of cultivation also led to the spread of weeds, prompting the need for more effective weed control methods. The late 19th and early 20th centuries saw the development of chemical herbicides, marking a pivotal moment in the history of weed management. The discovery of synthetic herbicides like 2,4-D and atrazine provided farmers with powerful tools to control weeds on a large scale.

The widespread adoption of chemical herbicides contributed to the Green Revolution, a period of rapid agricultural development that significantly increased global food production. While chemical herbicides brought about unprecedented benefits in terms of weed control and increased crop yields, they also raised environmental and health concerns. The indiscriminate use of herbicides led to issues such as pesticide resistance, soil degradation, and water pollution. In response to these challenges, the latter half of the 20th century witnessed a growing awareness of sustainable and integrated weed management practices. • “Integrated Weed Management (IWM)” emerged as a holistic approach that combines various strategies, including cultural, “mechanical, biological, and chemical methods, to control weeds while minimizing environmental impact. This approach recognizes the complexity of weed-crop ecosystems and aims to create a balanced and sustainable agricultural system”.


In recent decades, advancements in biotechnology have introduced genetically modified (GM) crops with traits resistant to specific herbicides. While controversial, these crops have offered farmers additional tools for weed management. However, concerns about the environmental and economic impacts of GM crops persist, leading to ongoing debates about their role in sustainable agriculture. The historical context of weed management in agriculture reflects a dynamic interplay between human ingenuity, technological advancements, and environmental consequences. From manual labor in ancient times to the development of chemical herbicides in the 20th century and the contemporary emphasis on integrated and sustainable approaches, the quest for effective weed management continues to evolve in response to the changing needs and challenges of agriculture.

3. Development Methodology


A. The methodology for the development of the autonomous bot designed like a Mars rover for agricultural purposes involves the following steps: • Requirements gathering: The first step is to gather the requirements for the paper. This includes understanding the problem statement, identifying the goals of the paper, and determining the functional and non- functional requirements of the bot. • Design: The design phase involves creating the system architecture and designing the hardware and software components of the Robot. This includes selecting the appropriate sensors, cameras, and microcontrollers and designing the navigation and control systems. • Development: The development phase involves implementing the design by building the Robot and programming the software components. This includes assembling the hardware components and writing the code for navigation, holding angle, Weed detection and April tag detection. • Testing: The testing phase involves verifying that the Robot meets the functional and non-functional requirements.

This includes testing the navigation system, the robotic arm, and the Husky lens camera module • Deployment: The final phase involves deploying the Robot in a real-world agricultural environment and evaluating its performance. This includes monitoring the Robot’s navigation and control systems, its ability to differentiate between normal crops and weeds using the Husky lens camera module, and its ability to uproot unwanted plants using the robotic arm.

Prototype and Rover Design



Original prototype photograph or system rendering 3.1



Original prototype photograph or system rendering 3.2

System Overview and Hardware Architecture


arm • The system is an autonomous Robot designed like a Mars rover, specifically for agricultural purposes. The Robot navigates autonomously in the farm fields with the help of April tags, which are black and white markers that can be detected by the bot's camera. The navigation system is powered by an Arduino Uno microcontroller, which controls the Robot's movements and the robotic arm. • The Robot is equipped with a 6 degree of freedom robotic arm, which is controlled by the Arduino Uno microcontroller. The robotic arm is used to uproot unwanted plants from the field and put them in the basket. The coordinates of the unwanted plants are provided by an on-chip camera module called the Huskey lens camera, which has machine learning algorithms that help the robotic arm differentiate between normal crops and unwanted plants or weeds.

The Husky lens camera module communicates with the Arduino Uno microcontroller using serial communication. • The robotic arm's movements are based on the inverse matrix transformation which, on giving end effector coordinates, automatically finds the angles that each joint has to move in order to reach its destination. The Robot's movement is based on the differential drive system, which is a type of drive system that is commonly used in robotics. The differential drive system uses two arrays of wheels on either side of the Robot that can be independently controlled to change the Robot's heading and speed. The differential drive system's motion is based on a set of differential equations, which describe the Robot's position and orientation over time. • The system's overall design and operation have the potential to revolutionize the agriculture industry by improving crop yields while reducing labor costs. • The main design that we had in our mind was of a 6wheel differential drive rover having 6 DOF robotic arm. But we initially prototyped a 4-wheel differential drive robot having 4 DOF robotic arms and it was named Krishak Robot- SEED.

It can be seen in Figure 1. • The final model would be a 6-wheel differential drive robot having 6 DOF arms. It can be seen in figure 2a. • 6 wheeled Differential drive rocker bogie Robot. • Raspberry Pi as the main processor • April tags for localization • Huskey Lens • 6 degree of freedom robotic arm for uprooting unwanted plants • Arduino Uno microcontroller for controlling the robotic arm and receiving coordinates from the Husky Lens Camera • MDD3A motor

driver • L293D shield • SG90 Micro servos • Acrylic Robotic arm structure • 300 rpm BO Motors • 65 mm wheels • BN0O5 AHRS D. Design Overview: • We are using a new approach to extract global coordinates of the robot wrt its starting position in a GPS denied environment. For this we are using an April tagbased navigation algorithm. The krishak r o bot which we are aiming to develop has

Finite State Machine and Control Workflow



Original finite state machine diagram 4.1

Abbreviations: • Act- activation • Det- detected flag • D_ahead- detected ahead • Dis_trav- distance travelled • CS- crop spacing • US-uproot sequence

Design Overview and Modularity

many functionalities. One of the major ones being its modular structure. Due to this modularity depending on its task, the attachment can be added or removed thus making it a versatile and multi- functional robot. • For the first implementation we are proposing a sixwheeled differential drive robot equipped with sensors, on board machine learning, encoders, cameras for April tag detection etc for path planning and trajectory sequence generation and following. • At the front end of the robot, there would be a robot arm having 6 DOF arm which has its parameters designed based on the workspace, hence allowing it to cover its entire surrounding workspace. • Whenever a new weed would be detected by a camera module while traversing along the path, the arm would be directed to that particular direction, hence the weed would be uprooted. Although we are building a 6 DOF robotic arm considering its future applications, right now we are only using 4 DOF for the weed uprooting application. 3 DOF of which are three revolute joints and fourth being the end effector itself. Depending on what new task or operations it has to perform in its future updates, the remaining 2 DOF can be programmed accordingly for performing complex maneuverers.

This design can accommodate future changes or addition without requiring significant redesign or rework, thus making our design adaptable, flexible and future-proof. Below is the inverse kinematic equation for the 4 DOF robotic arm out of the total 6 DOF of which 2 is being unused for the weed uprooting application.

4. Robotic Arm Kinematics

Homogeneous Transformations and Coordinate Frames

i. Translation which focuses on Position ii. Rotation focuses on orientation iii. Change in size iv. Shape Solving for the above

Forward and Inverse Kinematics

By using “kinematic equations”, inverse kinematics can be used to predict how a robot will move in order to arrive at a specific place. Contrary to forward kinematics, inverse kinematics (generally) cannot be solved in a closed-form formula. We'll explore whether a problem has no solutions, some solutions, or even infinitely many solutions. The inverse kinematics are required to define the parameters of the actuators if the position and orientation of the tool tip are given and the inverse kinematic model is used in position control of the robot. In the top view, links a2 and a3 are not there, because ■2 and ■3 may move away or near to us.


Since the top view would give us X and Y position of the end effector and not the Z position, we will compute the other equations from the Side view of the Kinematic diagram.

Combining the above equations (A), (B) and (C) in equation (1), we get,


Figure 7. Side View of our Robot Similar to top view, in our side view there is no x3 due to the uncertainty of orientations of ■1. Figure 8. Side View1 Figure 9. Side View2 These both are the zoomed in versions of side view for easier calculations.

Applying Law of cosines we get,

Original Kinematic Figures and Equations




Original kinematics diagram or transformation equation 5.1



Original kinematics diagram or transformation equation 5.2

$$S_{new} = \left[\begin{array}{c|c} \begin{pmatrix}\text{Rotation}\\ \text{Matrix}\end{pmatrix}^{new}_{old} & \begin{pmatrix}\text{Location}\\ \text{of Old}\\ \text{Origin}\end{pmatrix}_{new} \\ \hline \begin{pmatrix}0 & 0 & 0\end{pmatrix} & 1 \end{array}\right] S_{old}$$

Original kinematics diagram or transformation equation 5.3



Original kinematics diagram or transformation equation 5.4

$$S_3^0 = S_1^0 * S_2^1 * S_3^2 \qquad -(1)$$

Solving for the above matrices

$$S_0^1 = \begin{bmatrix} \cos\theta_1 & 0 & \sin\theta_1 & 0 \\ \sin\theta_1 & 0 & -\cos\theta_1 & 0 \\ 0 & 1 & 0 & a_1 \\ 0 & 0 & 0 & 1 \end{bmatrix} \qquad -(A)$$

$$S_2^1 = \begin{bmatrix} \cos\theta_2 & \sin\theta_2 & 0 & a_2\cos\theta_2 \\ \sin\theta_1 & -\sin\theta_2 & 0 & a_2\sin\theta_2 \\ 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \qquad -(B)$$

$$S_3^2 = \begin{bmatrix} \cos\theta_3 & -\sin\theta_3 & 0 & a_3\cos\theta_3 \\ \sin\theta_3 & \cos\theta_3 & 0 & a_3\sin\theta_3 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \qquad -(C)$$

Original kinematics diagram or transformation equation 5.5

From the Top view we get, $\theta_1 = \tan^{-1}\left(\frac{Y_3^0}{X_3^0}\right)$ -(1)


By Pythagoras theorem: $r_1 = \sqrt{(X_3^0)^2 + (Y_3^0)^2}$ -(2)

Original kinematics diagram or transformation equation 5.6

$S_3^0 =$

$$\begin{bmatrix} (C\theta_1 C\theta_2 C\theta_3 + C\theta_1 S\theta_2 C\theta_3) & (C\theta_1 S\theta_2 C\theta_3 - C\theta_1 C\theta_2 S\theta_3) & (-S\theta_1) & (a_3 C\theta_1 C\theta_2 C\theta_3 + a_3 C\theta_1 S\theta_2 S\theta_3 + a_2 C\theta_1 C\theta_2) \\ (S\theta_1 C\theta_2 S\theta_3 + S\theta_1 S\theta_2 S\theta_3) & (S\theta_1 S\theta_2 C\theta_3 - S\theta_1 C\theta_2 S\theta_3) & (C\theta_1) & (a_3 S\theta_1 C\theta_3 - a_3 S\theta_1 S\theta_3 + a_1 + a_2 S\theta_2) \\ (S\theta_2 C\theta_3 - C\theta_2 S\theta_3) & (-S\theta_2 S\theta_3 - C\theta_2 C\theta_3) & 0 & (a_3 S\theta_2 C\theta_3 - a_3 S\theta_2 S\theta_3 + a_2 S\theta_2 + a_1) \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

Original kinematics diagram or transformation equation 5.7



Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.1

$$(a_3)^2 = (a_2)^2 + (r_3)^2 - 2a_2 r_3 \cos \boldsymbol{\phi}_1 \quad \text{-(6)}$$

So, $\boldsymbol{\phi}_1 = \cos^{-1}\left(\frac{(a_3)^2-(a_2)^2-(r_3)^2}{-2a_2 r_3}\right)$ -(7)

From Side View2 we get, $\theta_3 = 180 - \boldsymbol{\phi}_3$ -(8)

For $\boldsymbol{\phi}_3$ use of law of Cosines,

$(r_3)^2 = (a_2)^2 + (a_3)^2 - 2a_2 a_3 \cos \boldsymbol{\phi}_3$ -(9)

$\boldsymbol{\phi}_3 = \cos^{-1}\left(\frac{(r_3)^2-(a_2)^2-(a_3)^2}{-2a_2 a_3}\right)$ -(10)

By Pythagoras theorem $r_3 = \sqrt{(r_1)^2 + (r_2)^2}$ -(11)

On substituting equations (5) and (7) in equation (4), we get

$\theta_2 = \tan^{-1}\left(\frac{r_2}{r_1}\right) - \cos^{-1}\left(\frac{(a_3)^2-(a_2)^2-(r_3)^2}{-2a_2 r_3}\right)$ -(12)


Similarly substituting equation (10) in equation (8), we get,

$\theta_3 = 180 - \cos^{-1}\left(\frac{(r_3)^2-(a_2)^2-(a_3)^2}{-2a_2 a_3}\right)$ -(13)


Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.2

From Side view we get, $r_2 = Z_3^0 - a_1$ -(3)


Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.3



Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.4



Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.5



Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.6

wheels, V_L and V_R

$$V_R = \omega_R R \quad -(1)$$
$$V_L = \omega_L R \quad -(2)$$

Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.7

$$V = \frac{V_R + V_L}{2} \quad -(3)$$
$$V = \frac{(\omega_R + \omega_L)R}{2} \quad -(4)$$

Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.8

From Side View1 we get, $\theta_2 = \boldsymbol{\phi}_2 - \boldsymbol{\phi}_1$ -(4)

and $\boldsymbol{\phi}_2 = \tan^{-1}(\frac{r_2}{r_1})$ -(5)

Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.9

$$\dot{x} = v \sin\theta \quad -(5)$$
$$\dot{y} = v \cos\theta \quad -(6)$$

Original arm-geometry diagram, inverse-kinematics equation, or drive model 6.10

5. Differential-Drive Kinematics

The "two-wheel differential (TWD) drive mobile robot model" describes the mechanical structure and movement of the robot. Figure 10 illustrates the coordinate system of the mobile robot relative to the track line. The linear velocities of the rear driven wheels can be calculated using the wheel radius R" and the angular velocity of each wheel. A linear velocity for the mobile robot is determined by averaging the angular speeds of its right and left driving wheels. The x and y positions are the components of linear velocities that are generated from the coordinate system. Fig. 10 depicts the various robot positions in relation to the rail line.

Since the first mobile robot position's robot coordinates are [xMR1, yMR1] and the seconds are [xMR2, yMR2], the angle of the mobile robot's orientation is determined by the difference between yMR2 and yMR1. The robot's left arc (LL) and right arc (LR) determine the track curvature or length of the track line, respectively: The radius of movement RT divided by the angle of orientation was linear, but they can be expressed as: Both of left LL and right LR is obtained by the following equation The heading of the robot θ is deduced by the following equation: Hence by using the equations, and we can control the linear velocity and heading of our robot.

Additional Original Differential-Drive Equations

$$L_T = \frac{L_R + L_L}{2} \quad -(7)$$

Original differential-drive equation 7.1

$$\theta = \frac{L_T}{R_T} \quad -(8)$$

Original differential-drive equation 7.2

$$L_R = (R_T + \frac{L_{MR}}{2})\theta \quad -(9)$$

$$L_L = (R_T - \frac{L_{MR}}{2})\theta \quad -(10)$$

Original differential-drive equation 7.3

$$\theta = \frac{L_R - L_L}{L_{MR}} \quad -(11)$$

Original differential-drive equation 7.4

6. Discussion: Autonomous Ground Vehicles in Agriculture

Emergence of Autonomous Ground Vehicles in Agriculture The emergence of autonomous ground vehicles in agriculture marks a transformative shift in traditional farming practices, bringing cutting-edge technology to the fields. Over the past few decades, advancements in robotics, artificial intelligence, and sensor technology have converged to enable the development and deployment of autonomous vehicles in the agricultural sector. These vehicles, ranging from unmanned tractors to robotic harvesters, represent a paradigm shift in how farmers approach tasks such as planting, cultivation, and harvesting. Autonomous ground vehicles in agriculture leverage sophisticated sensor arrays, including GPS, LiDAR, cameras, and other sensors, to navigate and perform tasks with precision. This level of automation not only reduces the reliance on human labor but also enhances operational efficiency and resource utilization. GPS technology, in particular, plays a crucial role in guiding these vehicles, allowing for accurate and repeatable maneuvers in the field.

This precision agriculture approach minimizes the potential for overuse of inputs such as fertilizers and pesticides, contributing to more sustainable farming practices. One of the key advantages of autonomous vehicles in agriculture is their ability to operate continuously, day or night, without the constraints of human fatigue. This 24/7 operational capability allows for more timely and efficient execution of tasks, particularly during critical periods such as planting and harvest seasons. Additionally, autonomous vehicles can navigate challenging terrains and conditions, improving

accessibility to fields that may be difficult or unsafe for human operators. The introduction of autonomous technology in agriculture has also given rise to the concept of "smart farming." These autonomous systems are equipped with data analytics capabilities, enabling real-time monitoring and decision-making.

By collecting and analyzing data on soil conditions, crop health, and weather patterns, autonomous vehicles contribute to data-driven insights that empower farmers to make informed decisions about crop management. This data-centric approach facilitates precision agriculture, where inputs are tailored to the specific needs of individual crops, optimizing resource use and reducing environmental impact. The adoption of autonomous ground vehicles in agriculture is not without its challenges and considerations. High initial costs, technological complexity, and the need for infrastructure upgrades pose barriers to entry for some farmers. Moreover, concerns about data privacy and security have emerged as farmers increasingly rely on autonomous systems that generate and utilize large amounts of sensitive agricultural data.

Despite these challenges, the trend towards autonomous agriculture is gaining momentum. Major agricultural machinery manufacturers and technology companies are investing heavily in research and development to enhance the capabilities of autonomous vehicles. Pilot programs and field trials have demonstrated the feasibility and benefits of integrating autonomous technology into various aspects of farming, fostering increased confidence and acceptance within the agricultural community. As autonomous ground vehicles become more prevalent in agriculture, the industry is poised for a significant transformation. From increased operational efficiency and resource optimization to the potential for more sustainable farming practices, the impact of autonomous technology on agriculture extends beyond individual farm operations.

The ongoing evolution of these technologies will likely shape the future of farming, offering new possibilities for innovation and productivity in the everchanging landscape of agriculture.