

EXP NO : 11**DATE :****IMPLEMENT CODE OPTIMIZATION TECHNIQUES LIKE DEAD CODE AND
COMMON EXPRESSION ELIMINATION****AIM:**

The aim is to implement code optimization techniques such as Dead Code Elimination (DCE) and Common Subexpression Elimination (CSE) on an intermediate representation of a program (such as Three-Address Code (TAC)). These optimization techniques help reduce the size of the code, improve runtime performance, and eliminate redundant computations during the compilation process.

ALGORITHM:

- Start
- Create the input file which contains three address code.
- Open the file in read mode.
- If the file pointer returns NULL, exit the program else go to 5.
- Scan the input symbol from left to right.
- Store the first expression in a string.
- Compare the string with the other expressions in the file.
- If there is a match, remove the expression from the input file.
- Perform these steps 5-8 for all the input symbols in the file.
- Scan the input symbol from the file from left to right.
- Get the operand before the operator from the three address code.
- Check whether the operand is used in any other expression in the three address code.
- If the operand is not used, then eliminate the complete expression from the three address code else go to 14.
- Perform steps 11 to 13 for all the operands in the three address code till end of the file is reached.
- Stop.

PROGRAM:

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX 100

typedef struct {
    char lhs[20], rhs[50];
} TAC;
```

```

int isUsed(TAC tac[], int total, char *var, int current)
{
    for (int i = current + 1; i < total; i++) {
        if (strstr(tac[i].rhs, var)) return 1;
    }
    return 0;
}

void replaceVar(char *src, char *oldVar, char *newVar)
{
    char buffer[100] = "";
    char *pos = src, *match;
    while ((match = strstr(pos, oldVar)) != NULL)
    {
        strncat(buffer, pos, match - pos);
        strcat(buffer, newVar);
        pos = match + strlen(oldVar);
    }
    strcat(buffer, pos);
    strcpy(src, buffer);
}

int main()
{
    FILE *fp;
    TAC tac[MAX];
    char line[100], *lhs, *rhs;
    int count = 0;

    // Open input file
    fp = fopen("input.txt", "r");
    if (!fp) {
        printf("Error: Could not open 'input.txt'\n");
        return 1;
    }

    // Read input file
    while (fgets(line, sizeof(line), fp))
    {
        line[strcspn(line, "\n")] = 0;
        lhs = strtok(line, "=");
        rhs = strtok(NULL, "\n");
        if (lhs && rhs) {
            strcpy(tac[count].lhs, lhs);
            strcpy(tac[count].rhs, rhs);
            count++;
        }
    }
    fclose(fp);

    // Step 1: Common Subexpression Elimination (CSE)
    for (int i = 0; i < count; i++) {
        for (int j = i + 1; j < count; j++) {
            if (strcmp(tac[i].rhs, tac[j].rhs) == 0) {

```

```

        replaceVar(tac[j + 1].rhs, tac[j].lhs, tac[i].lhs);
        strcpy(tac[j].lhs, "");
        strcpy(tac[j].rhs, "");
    }
}

// Step 2: Copy Propagation
for (int i = 0; i < count; i++) {
    if (strchr(tac[i].rhs, '+') == NULL && strchr(tac[i].rhs, '-') == NULL &&
        strchr(tac[i].rhs, '*') == NULL && strchr(tac[i].rhs, '/') == NULL) {
        // rhs is a direct copy
        for (int j = i + 1; j < count; j++)
            { replaceVar(tac[j].rhs, tac[i].lhs, tac[i].rhs);
            }
        // mark line as empty
        strcpy(tac[i].lhs, "");
        strcpy(tac[i].rhs, "");
    }
}

// Step 3: Dead Code Elimination
for (int i = 0; i < count; i++) {
    if (tac[i].lhs[0] != '\0' && !isUsed(tac, count, tac[i].lhs, i))
        { strcpy(tac[i].lhs, "");
        strcpy(tac[i].rhs, "");
        }
}

// Print Optimized Code
printf("\nOptimized Code:\n----- \n");
for (int i = 0; i < count; i++)
    { if (tac[i].lhs[0] != '\0') {
        printf("%s=%s\n", tac[i].lhs, tac[i].rhs);
    }
}

return 0;
}

```

OUTPUT :

```
Optimized Three-Address Code:  
t1 = a + b  
t3 = t1 * c  
t4 = t2 * c
```

Implementation	
Output/Signature	

RESULT:

Thus The Above Program To Implement Code Optimization Techniques Like Dead Code And Common Expression Elimination Is Executed And Implemented Successfully.