

A400 | A300 | A200

Charging Made Seamless



Power Fit for Purpose

400 kW

Field-upgradable from 200 kW

Branded Experiences

32" HD

Award-winning UI/UX

Reliable Energy Delivery

99+ %

Success Rate*
*Operational target

Power Specification

Power Configuration:	A200: 200 kW A300: 300 kW A400: 400 kW Upgradable from 200 kW to 400 kW or from 300 kW to 400 kW
DC Output:	Output current: CCS/NACS (liquid-cooled): 600 A continuous CCS (phase-cooled): 600 A peak NACS (air-cooled): 375 A continuous Dynamic Power Sharing ¹ : 50 kW power granularity Output voltage: 150 - 980 V Number of outlets: dual outlet Power conversion efficiency: up to 97% Standby power: 156 W
AC Input:	Nominal voltage: (CE): 400 Vac ($\pm 10\%$) (NA): 480 Vac ($-7\%/+10\%$) Nominal input current (RMS): A200: (CE): 306 A (NA): 255 A A300: (CE): 460 A (NA): 383 A A400: (CE): 612 A (NA): 496 A Frequency: (CE): 50 - 60 Hz ($\pm 5\%$) (NA): 60 Hz ($\pm 5\%$) Earthing systems: (CE): TN-C, TN-C-S, TN-S, TT (NA): WYE Maximum temperature rating for AC inlet cables: 90°C (194°F) Inlet cable size per phase (no neutral): max. 2 x 300 mm ² (600 kcmil) Power factor: > 0.99 at full load Total Harmonic Distortion (THD): < 3% Overvoltage category: III SPD: (CE): Type 1 + 2 (NA): Type 1 SCCR: (CE): 50 kA (NA): 65 kA

Customer Interface

Display:	Type: 32" HD full-color anti-glare LCD; Brightness: 1300 nits; Contrast: 1000:1; Interface: 4 push buttons
HMI Configuration:	Info modules: pricing, payment method, help content, idle state info Branding modules: brand color, logo and messaging, app integration, rich media
Languages:	English, French, Spanish, German, Italian, Norwegian, Dutch, Swedish, Danish, Turkish, Portuguese, Slovenian, Bulgarian, Polish, Lithuanian, Czech
Connector Options:	CCS1/2 liquid-cooled, or phase-cooled NACS liquid-cooled, or air-cooled
Cable Management:	2 x integrated self-retracting swing arm
Cable Options:	Length: 4.8 m (15.7 ft); Reach: 3.5 m (11.4 ft) Length: 7 m (22.9 ft); Reach: 6.3 m (20.7 ft)
Lighting:	Roof: 360° dual RGBW LED strips; Gun holder: RGBW LEDs
Authentication Methods:	RFID, Autocharge, Plug & Charge, credit/debit card, mobile app
RFID System:	Mifare ISO 14443 A/B to part 4 and ISO 15693, ISO 18092/ECMA-340 (NFC), others available on request
Remote Management:	Access control, configuration, diagnostics, software updates ²

System Specification

Operating Conditions:	Operating from -30°C to 55°C (-22°F to 131°F) with derating Storage from 5°C to 40°C (41°F to 104°F), IEC 60721-3-2 Altitude: 2000 m (6562 ft) Humidity: up to 95%, non-condensing Impact resistance: IK10 IP rating: IP54, NEMA 3R (in development), indoor and outdoor rated Noise emission average within 1 m radius, at 25°C (77°F), full power: A200: 62 dB(A) A300: 64 dB(A) A400: 65 dB(A) Intended use: indoor and outdoor Mounting options: floor mounted Environment pollution degree: Class 3 (outside), Class 2 (inside)
Form Factor:	Dimensions of charger body (H x W x D): 2256 x 790 x 810 mm (88.8 x 31.1 x 31.9 in) Weight: A200: 560 kg (1235 lbs) A300: 645 kg (1422 lbs) A400: 730 kg (1610 lbs) Accessibility: meets ADA requirements for height, reach, and user interface Enclosure type: high-durability aluminum body Corrosion resistance: C5-H, ISO 12944

Standards & Compliance

Safety Standards:	(CE): IEC 61851-1, IEC 61851-23 (NA): UL 2202, UL 2231-1, UL 2231-2, CSA 22.2 No.346:22
Metering:	(CE): Eichrecht, MID, LNE (NA): CTEP/NTEP
EMC:	(CE): IEC 61851-21-2 (NA): FCC 47 CFR Part 15B (Class A)
Manufactured:	USA & Europe
Network Connections:	3G/4G/5G, Ethernet (10/100 Base-T), optional second modem
OCPP:	Open Charge Point Protocol (OCPP) 1.6J and 2.0.1
Vehicle Communication Protocol:	DIN SPEC 70121, ISO 15118-2, ISO 15118-3, Autocharge, Plug & Charge, ISO 15118-20 (in development)
RED Directive:	ETSI EN 300 330, ETSI EN 301 489-1, ETSI EN 301 489-3, ETSI 301 489-52, ETSI EN 301 908-13, EN 50364 (RFID), IEC 62311: 2019, EN IEC 62311: 2020 (4G test)
Sustainability:	ISO 14025 Environmental Product Declaration, A200 A300: ENERGY STAR
Additional Standards:	DC Vehicle connector compliant with IEC 62196-1, IEC 62196-3, Cabinet IP rating according to IEC 60529
Expected Lifespan:	10 years ³

¹ 50 kW granularity on A400 starts at 100 kW minimum output

² Subject to Service Package coverage

³ Expectation based on uninterrupted Service Package coverage, possible refurbishment based on use, and use in suitable environmental conditions including limited proximity to sea water, conductive dust, and condensing humidity

©Copyright ABB E-mobility 2026. All rights reserved to copyrights, registered trademarks, and trademarks reside with their respective owners. The information in this document is provided in good faith, is provided for information purposes only and is subject to contract. The information contained herein is subject to change without notice and should not be construed as any commitment by ABB E-mobility B.V. or its affiliates or holding companies (ABB E-mobility). ABB E-mobility assumes no responsibility for any errors that may appear in this document. We reserve all rights with respect to this document, its content and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB E-mobility. No representations are made, express or implied, with respect to the accuracy, reliability, availability or completeness of the information provided, and no liability is accepted for any damage or loss suffered as a result of reliance on any information provided herein.

ABB E-mobility B.V.

Heertjeslaan 6
2629 JG Delft
The Netherlands
Phone: +31 88 4404600
E-mail: info.evci@nl.abb.com
e-mobility.abb.com

ABB E-mobility Inc.

4601 Park Rd, Suite 600
Charlotte, NC 28209
United States
Phone: 1-706-344-2889
E-mail: US-evci@abb.com
e-mobility.abb.com

ABB E-mobility Inc.

800 Hymus Boulevard
Saint-Laurent, QC H4S 0B5
Canada
Phone: 1-800-435-7365
E-mail: CA-evci@abb.com
e-mobility.abb.com