

SDE: System Design and Engineering

Lecture – 01 (B)

Introduction to

Linux and Shell Scripting.

From Zero to Google: Architecting the Invisible Infrastructure

by

Aatiz Ghimire

Preface

- Focus on most important commands
- Additional content for advanced users
- Use this slide deck as lookup during course
- Available for download on course page:

<https://aatizghimire.com.np/sde-summer-2025>

- (✓) commands that you want to remember
- Other commands are nice to know
- Presentation accompanied by exercises

What is a Shell?

- A shell is a command line interpreter
- It takes commands entered via the keyboard to start programs
- **Bash** is the most widespread shell
- A **terminal** is an input/output environment for shells
- The mouse can still be used to select text for copy and paste
- The shell is only an interface through which other programs are started
- A shell can only show textual output

Open a shell:

- Windows: **WIN + r**, type `powershell` and press enter
- MacOS: Search for **Terminal** and open it

Table of contents

1.SSH

2. Syntax

3.Files & Folders

4. Shell Shortcuts and Help

5. Terminal Editor

6. Environments

7. Redirection and History

8. Permission

9. Processes

10. Shell Scripting

SSH Client

- **Windows 10/11:**
 - Use the **Powershell**
 - Confirm that it works with `ssh -V`
 - Alternatives: MobaXterm, putty
- **MacOS/Linux:**
 - Search for Terminal and open it
 - Check your ssh version `ssh -V`

Logging in

- *ssh -p 52000 uxxxxx@pluto.aatizghimire.com.np (✓)*

The uxxxxx is the username given to you.

-p is port, by default port is 22 and no need to specify, but for security reasons we kept at 52000.

Basic Command Syntax

- Common syntax for commands is

`COMMAND <-OPTIONS>` (✓)

- A command might take 0 or more options prefixed with a `-` and separated by spaces (long options use `--`) (✓)
- A command might take 0 or more arguments separated by spaces (✓)
- Arguments can be subcommands that also accept options (✓)
- Arguments including spaces must be put in quotes

`"my argument"` (✓)

- `" "` allow for variable expansion, `' '` do not

Syntax Example

- First command `echo` (✓)
- It prints whatever you type after it (✓)
- Try `echo hello world` (✓)
- It accepts the option `-e` to enable escape commands (✓)
- Try `echo -e "hello\nworld"` (try without `-e`) (✓)

Filesystem Hierarchy

- In Linux, everything is a file (✓)
- Directories are separated via `/` (Same for Mac, Windows has `\`) (✓)
- For example, `/path/to/my/folder` (directory and folder are used interchangeably) (✓)
- `/` is the root directory (✓)
- `.` indicates the current folder `./my/folder` (✓)
- A path can be absolute (starting with `/`)
or relative to the current directory (starting with `.`) (✓)
- Parent of current directory is `..` (✓)

Folder Navigation

- `pwd` Print current directory (✓)
- `ls` List files and folders in current directory (✓)
- `ls -a` Also list hidden files and folders (start with . marks as hidden) (✓)
- `ls -la` List all files and folders in long table format (✓)
- `ls -a DIR` List all files and folders in target directory (✓)
- `cd DIR` Change directory to target directory (✓)
- `cd ~` Change to HOME directory (✓)
- `cd ..` Change to parent folder (✓)
 - `~` Refers to your HOME folder (✓)
 - `.` Refers to the current folder (✓)
 - `..` Refers to parent of current folder (✓)
- A path including spaces `cd "path/with spaces/"` needs to be put in quotes (✓)

Create, Copy, Move, Delete

- `touch FILE` Update modification time of file or create empty file (✓)
- `rm -i FILE` Delete file with confirmation, confirm with y (✓)
- `mkdir DIR` Create directory (✓)
- `rmdir DIR` Delete directory (✓)
- `rm -rf DIR` Delete everything in folder (sub-folders, files, ...) (✓)

use with **great care**, there is **no undo**

- `cp SRC DEST` Copy a file from source to destination (✓)
- `cp -R SRC DEST` Copy folders including sub-folders (✓)
- `mv SRC DEST` Move a file or folder, also functions as rename (✓)

Read and Search Files

- `cat FILE` Print file content to shell (✓)
- `less FILE` Show file content with pager (✓)
- `find PATH -name '*.txt'` Find all txt files in path (✓)
- `locate NAME` Find files containing NAME in their filename (✓)
- `grep PATTERN FILE` Search for pattern in file (✓)
- `grep -R PATTERN PATH` Search for pattern in all files in path (✓)
- `head FILE` Show first 10 lines of file (✓)
- `tail FILE` Show last 10 lines of file (✓)
- `diff FILE1 FILE2` Compare files and list differences (✓)

Shell Shortcuts Basics

- `TAB` Auto-complete file/directory names and commands (✓)
- `TAB` + `TAB` Show all possibilities (✓)
- `CTRL` + `c` Abort current running process (✓)
- `ARROW UP/DOWN` Cycle through command history (✓)
- `clear` Clear screen (✓)
- `exit` Close current shell session (✓)

Getting help with a command

- `COMMAND --help` , `COMMAND -h` or `COMMAND help` commonly shows usage options (✓)
- `man COMMAND` Opens the manual for a command
 - Mouse wheel for scrolling
 - `d` / `w` For scrolling down/up
 - Mouse wheel sometimes does not work via SSH
 - `q` For quitting the manual
 - Try `man man`
- `whatis COMMAND` See what pages are available
- `man SECTION COMMAND` Open a specific page for a command
- Search for documentation and guides on the internet (✓)

Nano Basic Usage

- **Nano** is a text editor for the terminal (✓)
 - Relatively easy to use
 - Alternatives: **emacs**, **vi**, ...
 - Use your preferred editor
- **nano FILE** To start editing, if file does not exist, its created (✓)
- Navigate with ARROW -keys and type to edit (✓)
- **CTRL** + **o** To save as... (✓)
- **CTRL** + **s** To save (HPC machines have old nano, use **CTRL** + **o** instead) (✓)
- **CTRL** + **x** To exit (✓)

Nano Basic Usage 1/2

- **ESC** Can be used instead of **ALT**
- **CTRL** + **o** Open search
- **ALT** + **w** Continue search
- **CTRL** + **w** , **CTRL** + **R** Open search and replace
- **CTRL** + **c** Cancel command
- **CTRL** + **x** Set mark for selection
- **CTRL** + **6** Copy selected text (area between mark and cursor) to clipboard
- **CTRL** + **k** Cut current line or selected text to clipboard
- **CTRL** + **u** Paste clipboard at cursor

Nano Basic Usage 2/2

- **ALT** + **u/e** Undo/Redo
- **CTRL** + **a/e** jump to start/end
- **CTRL** + **y/v** Scroll page up/down
- **CTRL** + **g** Open help Window
- **CTRL** + **o** Save as ..
- **CTRL** + **c** Show cursor position
- **CTRL** + **7** Jump to line number
- **CTRL** + **o** Enable/Disable conversion of tabs to spaces

Environmental Variables

- Values can be stored in environmental variables (✓)
- Some are used for configurations (✓)
- `echo $HOME` To see the value of HOME (✓)
- `echo -e ${PATH//:/:\n}` To get a nice output for PATH
- `printenv` or `set` to see all current env vars
- `export NAME=Value` Set variable, no spaces before or after = (✓)
- `unset NAME` Unset variable
- Env vars are bound to your session and do not persist after session ends (✓)

Persistent settings

- When you login into a Bash shell, it reads `.bash_profile`
- When you open another Bash shell without login, it reads `.bashrc`
- `nano .bash_profile` Open bash profile and make it load `.bashrc`
- Add this line to it `[[-f ~/.bashrc]] && . ~/.bashrc` and save
- `nano .bashrc` To start editing
- Add `export HELLO=hi`
- `alias` Can be used to set command aliases
- Add `alias ll='ls -la'` and save
- `source .bashrc` To load the changes now

Custom Prompt

- By setting the env var `PS1` you can customize your prompt
- Try `export PS1='[\t] \u@\h:\w$'`
- `\t` Gives the current time
- `\u` Gives your username
- `\h` Gives the hostname
- `\w` Gives the current folder
- Search for **bash ps1 generator** on the internet

Redirect Command Outputs

- `COMMAND > FILE` Redirects the output of command into file (✓)
- `>` Creates or overwrites file, `>>` creates or appends file (✓)
- `|` A pipe that forwards inputs from one command into another (✓)
- `ps aux | grep PATTERN` Filter the output of a command using grep (✓)
- `COMMAND | sort -u` Sort and filter unique lines in output (✓)
- Only the output of the last command is shown in the shell (✓)

Bash History

- `history` List all previous commands (✓)
- `history -c` Clear history (in case you entered your password) (✓)
- `history | grep PATTERN` Look for a command you used before (✓)
- `!N` Expands to line n of your bash history
- `!!` Expands to previous command
- `!TEXT` Expands to last command starting with text
- `!?TEXT` Expands to last command containing text
- `!#:N` Expands to nth argument of current command, can be used like this:
 - `mkdir NEW_DIR && cd !#:1` to create and switch to new dir

File and Folder Permissions

- Files and folders each belong to a user (owner) and a group (✓)
- Read, write and execute permission can be set for owner, group and others (✓)
- `ls -l` shows these permissions d (✓)

d	rwX	- - -	- - -	2	linuxuser	Herald	1	Jan 1 14:00	test
-	rw-	- - -	- - -	1	linuxuser	Herald	15200	Jan 1 14:40	test.txt
type	User Perm	Group Perm	Other Perm	# of links	owner	group	size	Last modified	name

- Type **d** means directory, **-** means file (✓)
- Permission **-** means its not set, **r**, **w**, **x** means read, write or execute permission set (✓)

Modifying Permission

- `chmod` Command for changing permission (✓)
- `chmod (u|g|o|a)(+|-|=)(r|w|x|) TARGET` (✓)
- `chmod a+r test.txt` Gives everyone read permission (✓)
- `chmod g= test.txt` Removes all permission for group (✓)
- `chmod u+x test` Allows execution of test (✓)
- `chmod -R g+rwX test-dir` Makes test-dir and files and folders in it group readable and writable, -R flag makes it recursive (✓)

Changing ownership

- `chown NEW_OWNER TARGET` Change the ownership of target (✓)
- `chgrp NEW_GROUP TARGET` Change the group of target (✓)
- The admin or super-user on Linux systems is called root (✓)
- `sudo COMMAND` (super-user do) Execute command as admin (✓)
- `whoami` Show own username
- `who` Show logged in users
- `w` More information active users

Processes

- `top` or `htop` Show current resource usage by processes (✓)

Use `htop` over `top`, close with `q` or `CTRL` + `o`

- `ps` List all processes on current shell session
- `ps -u USER` List all processes by a specific user, try `ps -u root`
- `ps aux` or `ps -ef` List all processes by all users
- `kill PID` Stop process with process id
- `COMMAND1 && COMMAND2` Lets you chain multiple commands this will execute `COMMAND1` and then `COMMAND2` but only if `COMMAND1` succeeded (✓)

Jobs

- `COMMAND &` Let the command execute as a background job
- `CTRL` + `z` Stop and make the running command a background job
- `jobs` List your background jobs ■ Jobs are bound to your shell session, all jobs are killed when you close your shell
- `bg %JOB_NUM` Start a stopped background job
- `fg %JOB_NUM` Move a job into the foreground
- `disown %JOB_NUM` Disown a job from your shell, keeps it running after closing shell

Shell Scripting

- Bash commands can be used to program shell scripts (✓)
- Written in plain text and saved as `.sh` files (✓)
- Must have as first line `#!/usr/bin/bash` (✓)
- You can use loops, conditions and so on like a regular programming language (✓)
- Make it executable if it isn't `chmod u+x script.sh` (✓)
- Run a script using `./script.sh` (✓)
- First inspect a script `less script.sh` or `nano script.sh` before running it (✓)
- Commonly used to start jobs on supercomputers (✓)

Postface

- Linux networking was not covered
- Git for Windows comes with the Git Bash shell, which contains most Bash commands
<https://gitforwindows.org/>
- Terminal under MacOS uses either Bash or Zsh by default, check your shell with `echo $SHELL` and the version of Bash with `bash --version`
- Find more Bash tricks <https://github.com/dylananaraps/pure-bash-bible>
- Guide on Bash <https://learnxinyminutes.com/docs/bash>
- Detailed command lookup <https://explainshell.com/>

Conclusion

- The shell is really powerful
- It does not restrict you to the options of graphical programs
- You can combine outputs from multiple programs
- Automate your boring workflows
- With experience you can become very productive
- Further reading for the interested: <https://lwn.net/Articles/343828/>
<https://arcan-fe.com/2022/04/02/the-day-of-a-new-command-line-interface-shell/>