



NOTE:
1.Communication Mandatory Zone is From RFID Tag No.R-243 to RFID Tag No.R-333 in UP Direction.
2.Communication Mandatory Zone is From RFID Tag No.R-370 to RFID Tag No.R-224 in Down Direction.

2.0.0	INITIAL SUBMISSION (UPDATED ASPER LATEST TAN GUIDELINES & LIDAR SURVEY)	01/10/2026
REV. NO.	REVISION HISTORY	DATE

LEGEND

- N NORMAL TAG
- S SIGNAL FOOT TAG
- G GATE TAG
- X EXIT TAG
- D DEAD STOP TAG
- L ADJACENT LINE INFO. TAG
- A ADJUSTMENT/JUNCTION TAG
- T TURNOUT / TIN DISCRIMINATION TAG

STATION ID	STATION-C	STATION-B	STATION-A
09058	09059	09061	
RANGE	217-274	275-323,060-070	324-424
ALLOTTED	217-248,250 (USED 33/58)	275-316 (USED 42/60)	324-379,381 (USED 57/101)
SPARE	249,251-274	317-323,060-070	380,382-424
RANGE	109,240	179-204	111,242
ALLOTTED	109(UP),240(DN)	179-190	111(UP),242(DN)
SPARE	-----	191-204	-----
BOARDER LINE TAGS	243,224		333,370
TOTAL NO.OF TAGS-132			

