

OMSE 532 - Week 3 Architectural Qualities

Stuart Faulk
University of Oregon

Overview

- Categorizing architectural qualities
- Quality scenarios

© Stuart Faulk 2006

2

Expected Outcome

- Description of overall organizing principles
- Rationale
 - Connect design decisions to requirements/goals
 - Optional description of alternatives
- Components and relations
 - Including major interfaces
 - In (just) enough detail to serve as basis for feasibility and cost studies
- Focus on questions and Issues
 - What design issues emerge? Requirements questions?
 - What questions does the problem raise about developing an appropriate architecture?

© Stuart Faulk 2006

3

Spam Filter Design Process

Methodology independent view implied by purpose and context

1. Creating the business case for the system
 - Which business goals are affected by the architecture?
2. Understanding the requirements
 - What are the quality requirements?
 - Relation to: stakeholder, business goal, priority?
3. Designing the architecture
 - Which components, relations, and interfaces? Decomposition criteria?
 - Which tradeoffs maximize requirements/goals?
4. Representing and communicating the architecture
 - Audience of and purpose for each view?
 - What should be represented and how?
5. Analyzing or evaluating the architecture
 - What evaluation criteria should be used?
6. Implementing the system based on the architecture
7. Ensuring the implementation conforms to the architecture

© Stuart Faulk 2006

4

Evaluating Solutions

- Sufficient for purpose?
 - Basis for cost/feasibility estimate
 - Can we evaluate the schedule/cost consequences of architectural choices?
 - First step to product architecture
- Specific goals
 - Domain fit: standards-based email
 - Constraints: laptop / server / PDA / ...
 - Change/add filtering approaches on the fly
 - Customization and evolution of product line

© Stuart Faulk 2006

5

Placement Alternatives

A Major Issue





Fig. 1. Possible placements of filter.

© Stuart Faulk 2006

6



A Note on Views

- Architectural descriptions are models
 - They emphasize some characteristics and suppress others
- No single model is good for everything
 - An architectural sketch for cost/feasibility is unlikely to be sufficient for performance studies
- But models must be consistent
 - It is easy to end up with “views” that cannot be reconciled

© Stuart Faulk 2006

Architectural Qualities

Understanding Quality Attributes

- ABC: business considerations determine which qualities should be accommodated in a system's architecture
- Systems are frequently redesigned because they are difficult to maintain, port, or scale, or are too slow, or have been compromised by network hackers

© Stuart Faulk 2006

10

Effects of Architectural Decisions

- What kinds of system and development properties are affected by the system structure(s)?
- System run-time properties
 - Performance, Security, Availability, Usability
- System static properties
 - Modifiability, Portability, Reusability, Testability
- Production properties? (effects on project)
 - Work Breakdown Structure, Scheduling, time to market
- Business/Organizational properties?
 - Lifespan, Versioning, Interoperability, Target market
- Not affected: functionality

© S. Faulk 2010

11

Functionality, Architecture, and Quality Attributes

- Functionality and quality attributes are orthogonal
- Achieving quality attributes must be considered throughout design, implementation, and deployment
- Satisfactory results depends on:
 1. Getting the big picture (architecture) right
 2. Then getting the details (implementation) right

© Stuart Faulk 2006

12

Functionality, Architecture, and Quality Attributes

- Ex: Performance depends on
 - How much inter-component communication is necessary (Arch)
 - What functionality has been allocated to each component (Arch)
 - How shared resources are allocated (Arch)
 - The choice of algorithms to implement functionality (Non-arch)
 - How algorithms are coded (Non-arch)

© Stuart Faulk 2006

13

Terminology

- Avoid “functional” and non-functional” classification
- Behavioral Requirements - Any information necessary to determine if the run-time behavior of a given implementation constitutes an acceptable system
 - All quantitative constraints on the system’s run-time behavior
 - Other objective measures (safety, performance, etc)
 - *In theory* all can be validated by observing the running system and measuring the results
- Developmental Quality Attributes - Any constraints on the system’s static construction
 - Testability, ease of change (mutability), maintainability, reusability
 - Measures of these qualities are necessarily relativistic (I.e., in comparison to something else)

© Stuart Faulk 2006

14

Behavioral vs. Developmental

Behavioral (observable)

- Performance
- Security
- Availability (fault-tolerance)
- Security
- Usability

Properties resulting from the properties of components, connectors and interfaces that exist at run time.

Developmental Qualities

- Modifiability
- Portability
- Reusability
- Integrability
- Testability

Properties resulting from the properties components, connectors and interfaces that exist at design time *whether or not they have any distinct run-time manifestation.*

© Stuart Faulk 2006

15

Behavioral vs. Developmental (2)

Behavioral (observable)

- Performance
- Security
- Availability (fault-tolerance)
- Usability (responsiveness?)

Developmental Qualities

- Modifiability
- Portability
- Reusability
- Integrability
- Testability

- Usefully viewed as distinct concerns
 - Visible at different times
 - Can focus on one at a time
- Often not easy to separate in practice
 - Design time mechanisms often carried into run-time structures
 - Real separation requires careful engineering
 - Many mechanisms bind more than one attribute at a time or abstract from what we want to control. Examples?
- The "art" of design includes finding structures that:
 - Address multiple concerns concurrently and/or
 - Clearly separate design from run-time constraints

© Stuart Faulk 2006

16

Additional Properties

■ Business process qualities

- Properties of the system that
 - Are affected by architectural decisions
 - Reflect the business context (business goals, environment, constraints)
- Time to market, cost/benefit, projected life, target market, rollout schedule, legacy integration
- Observable by viewing the business process around the development

■ Design qualities

- Conceptual integrity, correctness, completeness, feasibility

© Stuart Faulk 2006

17

Architectural Design Process

Methodology independent view implied by *purpose* and *context*

1. Creating the business case for the system
2. Understanding the (quality) requirements
 1. Identify & prioritize behavioral and quality attributes
 2. Characterize and communicate to stakeholders
3. Creating or selecting the architecture
4. Representing and communicating the architecture
5. Analyzing or evaluating the architecture
6. Implementing the system based on the architecture
7. Ensuring the implementation conforms to the architecture

© Stuart Faulk 2006

18

Qualities - Questions

- Consider the spam filter exercise:
 - What qualities did we initially focus on?
 - How would (or did) this influence your architectural decisions?
 - What specific decisions were made to achieve particular architectural goals?
- How did the spam filter exercise differ from the A7 project in this regard?

© Stuart Faulk 2006

19

Quality Attribute Scenarios

A Tool for Capturing Quality Requirements


A QA-specific Requirement

- Source of stimulus - generating entity
- Stimulus - arriving condition needing consideration
- Environment - system condition
- Artifact - part of or entire system
- Response - activity caused by the stimulus
- Response measure - measurable results that tests the requirements

© Stuart Faulk 2006

21

Quality Scenarios



- Options (Chinese menu) for each type of quality attribute
- Used to “generate” general scenarios (must be edited)
- Focus on making sure all possibilities are considered

© Stuart Faulk 2009

22

Availability Table*

- Source: internal, external
- Stimulus: type of fault
- Artifact: processors, channels, storage, process
- Environment: normal, degraded
- Response: logging, notification, switching to backup, restart, shutdown
- Measure: availability, repair time, required uptime


**Have general scenario generation table for each quality*

Availability Table*

- Source: internal, external
- Stimulus: type of fault
- Artifact: processors, channels, storage, process
- Environment: normal, degraded
- Response: logging, notification, switching to backup, restart, shutdown, continue
- Measure: availability, repair time, required uptime

**General scenario from choosing parts*

Quality Scenarios - Concrete



- Must supply real values for each part
- Should be system specific
- Realistically, requires some rewriting of elements from "general" scenario to make sense

© Stuart Faulk 2006

25

Properties of Good QASs

- Values of each part are reasonable and useful
- The values must be consistent with one another
 - Values work together to describe a specific kind of quality requirement
 - E.g., for a performance requirement, all attributes address aspects related to same performance measure
- The set of choices actually specify a quality requirement
- The resulting scenario must specify a relevant system requirement
- To achieve this, need to be clear on what you are trying to specify

Applying Scenarios

Examples from A-7:
Modifiability
Extensibility/Portability
Performance

© Stuart Faulk 2010

27

Modifiability Example (A-7E)

9.2. COMPUTER CHANGES

- 9.2.1 The computer might be replaced by a TC-2A.
- 9.2.2 Additional channel hardware might be added to the TC-2.
- 9.2.3 Additional interlocks or improvements might be added to the present TC-2 channels.
- 9.2.4 A completely different computer might be substituted (very unlikely).
- 9.2.5 A register other than the A register might be used as an I/O buffer.
- 9.2.6 TC-2 Panel may be used for other parameters or pilot selectable switches.

9.3. INTERFACE CHANGES

9.3.1. General

- (a) Assignment of devices to channels may be changed.
- (b) Assignment of bits to discrete words may be changed.
- (c) All data representations may be changed.

A-7E Requirements Spec lists likely change
(View as QAS where only the "Stimulus"
changes)

© Stuart Faulk 2009

28

Map Changes to Modules

B-1.1 HARDWARE-HIDING MODULE DECOMPOSITION:



The Hardware-Hiding Module comprises two modules.

B-1.1.1 EXTENDED COMPUTER MODULE

The Extended Computer Module hides those characteristics of the hardware/software interface of the avionics computer that we consider likely to change if the computer is modified or replaced.

Avionics computers differ greatly in their hardware/software interfaces and in the capabilities that are implemented directly in the hardware. Some avionics computers include a hardware approximation of real numbers, while others perform approximate real number operations by a programmed sequence of fixed-point operations. Some avionics systems include a single processor, some systems provide several processors. The Extended Computer provides an instruction set that can be implemented efficiently on most avionics computers. This instruction set includes the operations on application-independent data types, sequence control operations, and general I/O operations. The Extended Computer is a multi-processor but may also serve as a single processor.

The primary secrets of the Extended Computer are: the number of processors, the instruction set of the computer, the processor state transitions, the processor addressing restrictions, and the processor's self-test capabilities.


The structure of the Extended Computer Module is given in section C.1.1. Specifications for Extended Computer submodules are given in [4].

Design of module structure (module
decomposition) allocates changes to modules

© Stuart Faulk 2009

29

A-7E Module Structure



© Stuart Faulk 2006

30

Define Interface for Leaf Modules

DETAILED RADAR ALTIMETER

1. Introduction
The Radar Altimeter is a sensor that measures the altitude of the aircraft above the local terrain, either land or water.

2. Interface overview

2.1. ACCESS PROGRAM TABLE

Program	Description	External event
0: RADAR_ALT	Get distance to ground	1: RADAR_ALT
1: RADAR_ALT	Get distance to ground	None

2.2. EVENTS/MESSAGES

0: GET_RADAR_ALT

1: RADAR_ALT

3. Local type definitions: None

4. Definitions

1: RADAR_ALT

2: RADAR_ALT

3: RADAR_ALT

4: RADAR_ALT

5. Unchecked error dictionary: None

6. Versioning parameters

7: RADAR_ALT

8: RADAR_ALT

9: RADAR_ALT

10: RADAR_ALT

11: RADAR_ALT

12: RADAR_ALT

13: RADAR_ALT

14: RADAR_ALT

15: RADAR_ALT

16: RADAR_ALT

17: RADAR_ALT

18: RADAR_ALT

19: RADAR_ALT

20: RADAR_ALT

21: RADAR_ALT

22: RADAR_ALT

23: RADAR_ALT

24: RADAR_ALT

25: RADAR_ALT

26: RADAR_ALT

27: RADAR_ALT

28: RADAR_ALT

29: RADAR_ALT

30: RADAR_ALT

31: RADAR_ALT

32: RADAR_ALT

33: RADAR_ALT

34: RADAR_ALT

35: RADAR_ALT

36: RADAR_ALT

37: RADAR_ALT

38: RADAR_ALT

39: RADAR_ALT

40: RADAR_ALT

41: RADAR_ALT

42: RADAR_ALT

43: RADAR_ALT

44: RADAR_ALT

45: RADAR_ALT

46: RADAR_ALT

47: RADAR_ALT

48: RADAR_ALT

49: RADAR_ALT

50: RADAR_ALT

51: RADAR_ALT

52: RADAR_ALT

53: RADAR_ALT

54: RADAR_ALT

55: RADAR_ALT

56: RADAR_ALT

57: RADAR_ALT

58: RADAR_ALT

59: RADAR_ALT

60: RADAR_ALT

61: RADAR_ALT

62: RADAR_ALT

63: RADAR_ALT

64: RADAR_ALT

65: RADAR_ALT

66: RADAR_ALT

67: RADAR_ALT

68: RADAR_ALT

69: RADAR_ALT

70: RADAR_ALT

71: RADAR_ALT

72: RADAR_ALT

73: RADAR_ALT

74: RADAR_ALT

75: RADAR_ALT

76: RADAR_ALT

77: RADAR_ALT

78: RADAR_ALT

79: RADAR_ALT

80: RADAR_ALT

81: RADAR_ALT

82: RADAR_ALT

83: RADAR_ALT

84: RADAR_ALT

85: RADAR_ALT

86: RADAR_ALT

87: RADAR_ALT

88: RADAR_ALT

89: RADAR_ALT

90: RADAR_ALT

91: RADAR_ALT

92: RADAR_ALT

93: RADAR_ALT

94: RADAR_ALT

95: RADAR_ALT

96: RADAR_ALT

97: RADAR_ALT

98: RADAR_ALT

99: RADAR_ALT

- Hides likely changes
- Defines everything necessary to implement the module
 - Services
 - Parameters
 - Timing constraints
 - Synchronization events
- Basis for
 - Abstract devices and abstract types
 - Work assignments
 - Understandability (study independently)
 - Unit testing

© Stuart Faulk 2006

31

Module Structure Evaluation Using Scenarios

- Procedure
 - “Play” each scenario against the module architecture
 - Review for understandability, etc.
- Completeness (internal)
 - Do the submodules of each module partition its secrets?
 - Is every change scenario the responsibility of some module?
- Modifiability
 - Is every likely change hidden by some module?
 - Are only aspects of the system that are very unlikely to change embedded in the module structure?
 - For each leaf module, are the module’s secrets revealed by its access programs?

© Stuart Faulk 2006

32

Performance

© Stuart Faulk 2006

33

Performance Table

- Source: external, internal
- Stimulus: event arrival pattern
 - periodic
 - stochastic
 - sporadic
- Artifact: system services
- Environment: normal, overload
- Response: change in mode?
- Measure: latency, deadline, throughput, jitter, miss rate, data loss

34

Required Demand Function

1. FUNCTION DESCRIPTION: Computer fail signal
 Function type: demand
 Result type: boolean
 Access program: +DEB_COMPUTER_FAIL_SIGNAL+

2. FUNCTION DEFINITION:

Table 3-a

MODES	EVENTS	
All modes	@T(*failed state+!)	@T(*Init complete+!)
Output value	true	false

- One for each system output
- Defines the arrival pattern and environment (system state)
- Defines the required response (output value)

© Stuart Faulk 2006

35

Timing Requirements

5.2. TIMING REQUIREMENTS FOR DEMAND FUNCTIONS

For all the demand functions, the rate of demand is so low that it will not constitute a significant CPU-load.


For the starred entries, the desired maximum delay is not known; the entry is the maximum delay in the current OFF, which we will use as an approximation. In one case, both the current and desired values are given. The current value would be good enough to satisfy requirements, but the desired rate would be preferred.

Function name	Maximum delay to completion
INB:	
Switch AUTOCAL light on/off	*200 ms
Switch computer control on/off	*200 ms
Issue computer failure	not significant
Change scale factor	*200 ms
Switch X slewing on/off	*200 ms
Switch Y slewing on/off	*200 ms
Switch Z slewing on/off	*200 ms
Change latitude-greater than 70-degrees	*200 ms
Switch INA light on/off	*200 ms
FLR:	
Enable radar cursor	200 ms
Slave or release slave	40 ms

© Stuart Faulk 2006


36

Data Flow View



Based on CMU/SEI tutorial for Software Architecture in Practice
© Stuart Faulk 2006

Consistent Design Pattern



© Stuart Faulk 2006

38

Evaluation

- Each process must meet its deadline
- Together, must be able to produce feasible schedule
 - Processes share common resources
 - Additional scenarios must account for requirements on the whole set

© Stuart Faulk 2006

39

Summary

- QAS provide a more-or-less standard format for specifying quality requirements
- Not always easy to formulate
 - Straight-forward for some kinds of qualities (e.g., ease of change for specific changes)
 - Inobvious for others
- Takes some experience and expertise in the quality attributes (e.g., security) to use effectively
 - The book's description is insufficient
- May be combined (as in the A-7) where the parts are similar

Questions?

© Stuart Faulk 2006

41
