

Contents

1 Combinatorial optimization

1.1	Dinic's	1
1.2	Min-cost Circulation	2
1.3	Edmonds Max Matching	3
1.4	Hungarian Min-cost	4
1.5	Konig's Theorem (Text)	4
1.6	Minimum Edge Cover (Text)	4

2 Geometry

2.1	Miscellaneous geometry	5
2.2	3D geometry	5
2.3	Convex hull	6
2.4	Min Enclosing Circle	7
2.5	Pick's Theorem (Text)	7
2.6	Slow Delaunay triangulation	7

3 Numerical algorithms

3.1	Pollard Rho	8
3.2	Simplex algorithm	8
3.3	Reduced row echelon form	9
3.4	Fast Fourier transform	10
3.5	Number Theoretic transform	10
3.6	Discrete Logarithm	11
3.7	Mobius Inversion (Text)	12
3.8	Burnside Lemma (Text)	12
3.9	Number Theory (Modular, CRT, Linear Diophantine)	12

4 Graph algorithms

4.1	Dynamic Connectivity	13
4.2	Bridges	13
4.3	Strongly connected components	14

5 String Stuff

5.1	Suffix Automaton	14
5.2	Suffix array	14
5.3	Z Algorithm	15
5.4	KMP	15
5.5	String Hashing	15
5.6	Palindrome DSU	16
5.7	Eertree	16

6 Data structures

6.1	BIT Range Queries	17
6.2	Treaps	17
6.3	Link-Cut Tree	17

7 Miscellaneous

7.1	2-SAT	19
7.2	Merge Insertion	20
7.3	DP Optimizations	20
7.4	Convex Hull Trick (Dynamic)	21
7.5	Convex Hull Trick (Static)	21
7.6	BigInt library	21
7.7	Manachers algorithm	23
7.8	Dates	23
7.9	Bitset (Text)	23
7.10	Template	23
7.11	Numerical Integration	24

1 Combinatorial optimization

1.1 Dinic's

```
struct Dinic {
    struct Edge {
        int u, v;
        long long cap, flow;
    };
    Edge() {}
    Edge(int u, int v, long long cap): u(u), v(v), cap(
        cap), flow(0) {}
};
int N;
vector<Edge> E;
vector<vector<int>> g;
vector<int> d, pt;

Dinic(int N): N(N), E(0), g(N), d(N), pt(N) {}

void AddEdge(int u, int v, long long cap) {
    if (u != v) {
        E.emplace_back(Edge(u, v, cap));
        g[u].emplace_back(E.size() - 1);
        E.emplace_back(Edge(v, u, 0));
        g[v].emplace_back(E.size() - 1);
    }
}

bool BFS(int S, int T) {
    queue<int> q({S});
    fill(d.begin(), d.end(), N + 1);
    d[S] = 0;
    while(!q.empty()) {
        int u = q.front(); q.pop();
        if (u == T) break;
        for (int k: g[u]) {
            Edge &e = E[k];
            if (e.flow < e.cap && d[e.v] > d[e.u] + 1) {
                d[e.v] = d[e.u] + 1;
                q.emplace(e.v);
            }
        }
    }
    return d[T] != N + 1;
}

long long DFS(int u, int T, long long flow = -1) {
    if (u == T || flow == 0) return flow;
```

```

for (int &i = pt[u]; i < g[u].size(); ++i) {
    Edge &e = E[g[u][i]];
    Edge &oe = E[g[u][i]^1];
    if (d[e.v] == d[e.u] + 1) {
        long long amt = e.cap - e.flow;
        if (flow != -1 && amt > flow) amt = flow;
        if (long long pushed = DFS(e.v, T, amt)) {
            e.flow += pushed;
            oe.flow -= pushed;
            return pushed;
        }
    }
}
return 0;
}
long long MaxFlow(int S, int T) {
    long long total = 0;
    while (BFS(S, T)) {
        fill(pt.begin(), pt.end(), 0);
        while (long long flow = DFS(S, T))
            total += flow;
    }
    return total;
}
};

```

1.2 Min-cost Circulation

*// Runs in $O(\text{max_flow} * \log(V * \text{max_edge_cost})) = O(V^3 * \log(V * C))$ Really fast in practice, $3e4$ edges are fine. Operates on integers, // costs are multiplied by $N!!$*

```

template<typename flow_t = int, typename cost_t = int>
struct mcSFlow{
    struct Edge{
        cost_t c;
        flow_t f;
        int to, rev;
        Edge(int _to, cost_t _c, flow_t _f, int _rev):c(_c),
            f(_f), to(_to), rev(_rev){}
    };
    static constexpr cost_t INFCOST = numeric_limits<
        cost_t>::max()/2;
    cost_t eps;
    int N, S, T;
    vector<vector<Edge>> G;
    vector<unsigned int> isq, cur;
    vector<flow_t> ex;
    vector<cost_t> h;
    mcSFlow(int _N, int _S, int _T):eps(0), N(_N), S(_S),
        T(_T), G(_N){}
    void add_edge(int a, int b, cost_t cost, flow_t cap){
        assert(cap>=0);
        assert(a>=0 && a<N && b>=0 && b<N);
        if(a==b){assert(cost>=0); return;}
        cost*=N;
        eps = max(eps, abs(cost));
        G[a].emplace_back(b, cost, cap, G[b].size());
        G[b].emplace_back(a, -cost, 0, G[a].size()-1);
    }
    void add_flow(Edge& e, flow_t f) {

```

```

        Edge &back = G[e.to][e.rev];
        if (!ex[e.to] && f)
            hs[h[e.to]].push_back(e.to);
        e.f -= f; ex[e.to] += f;
        back.f += f; ex[back.to] -= f;
    }
    vector<vector<int>> hs;
    vector<int> co;
    flow_t max_flow() {
        ex.assign(N, 0);
        h.assign(N, 0); hs.resize(2*N);
        co.assign(2*N, 0); cur.assign(N, 0);
        h[S] = N;
        ex[T] = 1;
        co[0] = N-1;
        for(auto &e:G[S]) add_flow(e, e.f);
        if(hs[0].size())
            for (int hi = 0; hi>=0;) {
                int u = hs[hi].back();
                hs[hi].pop_back();
                while (ex[u] > 0) { // discharge u
                    if (cur[u] == G[u].size()) {
                        h[u] = 1e9;
                        for(unsigned int i=0; i<G[u].size(); ++i) {
                            auto &e = G[u][i];
                            if (e.f && h[u] > h[e.to]+1) {
                                h[u] = h[e.to]+1, cur[u] = i;
                            }
                        }
                    }
                    if (++co[h[u]], !--co[hi] && hi < N)
                        for(int i=0; i<N; ++i)
                            if (hi < h[i] && h[i] < N) {
                                --co[h[i]];
                                h[i] = N + 1;
                            }
                    hi = h[u];
                } else if (G[u][cur[u]].f && h[u] == h[G[u][cur[u]]
                        .to]+1)
                    add_flow(G[u][cur[u]], min(ex[u], G[u][cur[u]]
                        .f));
                else ++cur[u];
            }
        while (hi>=0 && hs[hi].empty()) --hi;
        return -ex[S];
    }
    void push(Edge &e, flow_t amt){
        if(e.f < amt) amt=e.f;
        e.f-=amt; ex[e.to] += amt;
        G[e.to][e.rev].f += amt; ex[G[e.to][e.rev].to] -= amt;
    }
    void relabel(int vertex){
        cost_t newHeight = -INFCOST;
        for(unsigned int i=0; i<G[vertex].size(); ++i){
            Edge const&e = G[vertex][i];
            if(e.f && newHeight < h[e.to]-e.c){
                newHeight = h[e.to] - e.c;
                cur[vertex] = i;
            }
        }
        h[vertex] = newHeight - eps;

```

```

}
static constexpr int scale=2;
pair<flow_t, cost_t> minCostMaxFlow() {
    cost_t retCost = 0;
    for(int i=0; i<N; ++i)
        for(Edge &e:G[i])
            retCost += e.c*(e.f);
    //find max-flow
    flow_t retFlow = max_flow();
    h.assign(N, 0); ex.assign(N, 0);
    isq.assign(N, 0); cur.assign(N, 0);
    queue<int> q;
    for(; eps; eps>>=scale) {
        //refine
        fill(cur.begin(), cur.end(), 0);
        for(int i=0; i<N; ++i)
            for(auto &e:G[i])
                if(h[i] + e.c - h[e.to] < 0 && e.f) push(e, e.f);
        for(int i=0; i<N; ++i) {
            if(ex[i]>0) {
                q.push(i);
                isq[i]=1;
            }
        }
        // make flow feasible
        while(!q.empty()) {
            int u=q.front(); q.pop();
            isq[u]=0;
            while(ex[u]>0) {
                if(cur[u] == G[u].size())
                    relabel(u);
                for(unsigned int &i=cur[u], max_i = G[u].size()
                    (); i<max_i; ++i) {
                    Edge &e=G[u][i];
                    if(h[u] + e.c - h[e.to] < 0) {
                        push(e, ex[u]);
                        if(ex[e.to]>0 && isq[e.to]==0) {
                            q.push(e.to);
                            isq[e.to]=1;
                        }
                        if(ex[u]==0) break;
                    }
                }
            }
        }
        if(eps>1 && eps>>scale==0) {
            eps = 1<<scale;
        }
    }
    for(int i=0; i<N; ++i) {
        for(Edge &e:G[i]) {
            retCost -= e.c*(e.f);
        }
    }
    return make_pair(retFlow, retCost/2/N);
}
flow_t getFlow(Edge const &e) {
    return G[e.to][e.rev].f;
}
};

```

1.3 Edmonds Max Matching

```

#define MAXN 505
vector<int> g[MAXN];
int pa[MAXN], match[MAXN], st[MAXN], S[MAXN], v[MAXN];
int t, n;
inline int lca(int x, int y) {
    for(++t;; swap(x, y)) if(x) {
        if(v[x]==t) return x;
        v[x]=t, x=st[pa[match[x]]];
    }
}
#define qpush(x) q.push(x), S[x]=0
void flower(int x, int y, int l, queue<int> &q) {
    while(st[x]!=1) {
        pa[x]=y, y=match[x];
        if(S[y]==1) qpush(y);
        st[x]=st[y]=l, x=pa[y];
    }
}
bool bfs(int x) {
    for(int i=1; i<=n; ++i) st[i]=i;
    memset(S+1, -1, sizeof(int)*n);
    queue<int> q;
    qpush(x);
    while(q.size()) {
        x=q.front(), q.pop();
        for(size_t i=0; i<g[x].size(); ++i) {
            int y=g[x][i];
            if(S[y]==-1) {
                pa[y]=x, S[y]=1;
                if(!match[y]) {
                    for(int lst=x; y=lst, x=pa[y]) {
                        lst=match[x], match[x]=y, match[y]=x;
                    }
                    return 1;
                }
                qpush(match[y]);
            }
            else if(!S[y] && st[y]!=st[x]) {
                int l=lca(y, x);
                flower(y, x, l, q); flower(x, y, l, q);
            }
        }
    }
    return 0;
}
int blossom() {
    int ans=0;
    for(int i=1; i<=n; ++i)
        if(!match[i] && bfs(i)) ++ans;
    return ans;
}
int main() {
    while(m--) {
        g[x].push_back(y);
        g[y].push_back(x);
    }
    printf("%d\n", blossom());
    for(int i=1; i<=n; ++i) printf("%d ", match[i]);
}

```

1.4 Hungarian Min-cost

```
double MinCostMatching(const VVD &cost, VI &Lmate, VI &
    Rmate) {
    int n = int(cost.size());
    // construct dual feasible solution
    VD u(n);
    VD v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost[i]
            [j]);
    }
    for (int j = 0; j < n; j++) {
        v[j] = cost[0][j] - u[0];
        for (int i = 1; i < n; i++) v[j] = min(v[j], cost[i]
            [j] - u[i]);
    }
    // construct primal solution satisfying complementary
    // slackness
    Lmate = VI(n, -1);
    Rmate = VI(n, -1);
    int mated = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (Rmate[j] != -1) continue;
            if (fabs(cost[i][j] - u[i] - v[j]) < 1e-10) {
                Lmate[i] = j;
                Rmate[j] = i;
                mated++;
                break;
            }
        }
    }
    VD dist(n);
    VI dad(n);
    VI seen(n);
    // repeat until primal solution is feasible
    while (mated < n) {
        // find an unmatched left node
        int s = 0;
        while (Lmate[s] != -1) s++;
        // initialize Dijkstra
        fill(dad.begin(), dad.end(), -1);
        fill(seen.begin(), seen.end(), 0);
        for (int k = 0; k < n; k++)
            dist[k] = cost[s][k] - u[s] - v[k];
        int j = 0;
        while (true) {
            // find closest
            j = -1;
            for (int k = 0; k < n; k++) {
                if (seen[k]) continue;
                if (j == -1 || dist[k] < dist[j]) j = k;
            }
            seen[j] = 1;
            // termination condition
            if (Rmate[j] == -1) break;
            // relax neighbors
            const int i = Rmate[j];
```

```
            for (int k = 0; k < n; k++) {
                if (seen[k]) continue;
                const double new_dist = dist[j] + cost[i][k] - u
                    [i] - v[k];
                if (dist[k] > new_dist) {
                    dist[k] = new_dist;
                    dad[k] = j;
                }
            }
        }
        // update dual variables
        for (int k = 0; k < n; k++) {
            if (k == j || !seen[k]) continue;
            const int i = Rmate[k];
            v[k] += dist[k] - dist[j];
            u[i] -= dist[k] - dist[j];
        }
        u[s] += dist[j];
        // augment along path
        while (dad[j] >= 0) {
            const int d = dad[j];
            Rmate[j] = Rmate[d];
            Lmate[Rmate[j]] = j;
            j = d;
        }
        Rmate[j] = s;
        Lmate[s] = j;
        mated++;
    }
    double value = 0;
    for (int i = 0; i < n; i++)
        value += cost[i][Lmate[i]];
    return value;
}
```

1.5 Konig's Theorem (Text)

In any bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover. To exhibit the vertex cover:

1. Find a maximum matching
2. Change each edge **used** in the matching into a directed edge from **right to left**
3. Change each edge **not used** in the matching into a directed edge from **left to right**
4. Compute the set T of all vertices reachable from unmatched vertices on the left (including themselves)
5. The vertex cover consists of all vertices on the right that are **in** T , and all vertices on the left that are **not in** T

1.6 Minimum Edge Cover (Text)

If a minimum edge cover contains C edges, and a maximum matching contains M edges, then $C + M = |V|$. To obtain the edge cover, start with a maximum matching, and then, for every vertex not matched, just select some edge incident upon it and add it to the edge set.

2 Geometry

2.1 Miscellaneous geometry

```
double INF = 1e100, EPS = 1e-12;

struct PT {
    double x, y;
    PT() {}
    PT(double x, double y) : x(x), y(y) {}
    PT(const PT &p) : x(p.x), y(p.y) {}
    PT operator + (const PT &p) const { return PT(x+p.x,
        y+p.y); }
    PT operator - (const PT &p) const { return PT(x-p.x,
        y-p.y); }
    PT operator * (double c) const { return PT(x*c,
        y*c); }
    PT operator / (double c) const { return PT(x/c,
        y/c); }
};

double dot(PT p, PT q) { return p.x*q.x+p.y*q.y; }
double dist2(PT p, PT q) { return dot(p-q, p-q); }
double cross(PT p, PT q) { return p.x*q.y-p.y*q.x; }
ostream &operator<<(ostream &os, const PT &p) {
    os << "(" << p.x << ", " << p.y << ")";
}

// rotate a point CCW or CW around the origin
PT RotateCCW90(PT p) { return PT(-p.y, p.x); }
PT RotateCW90(PT p) { return PT(p.y, -p.x); }
PT RotateCCW(PT p, double t) {
    return PT(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos(t));
}

// project point c onto line through a and b
// assuming a != b
PT ProjectPointLine(PT a, PT b, PT c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);
}

// project point c onto line segment through a and b
PT ProjectPointSegment(PT a, PT b, PT c) {
    double r = dot(b-a, b-a);
    if (fabs(r) < EPS) return a;
    r = dot(c-a, b-a)/r;
    if (r < 0) return a;
    if (r > 1) return b;
    return a + (b-a)*r;
}

// compute distance from c to segment between a and b
double DistancePointSegment(PT a, PT b, PT c) {
    return sqrt(dist2(c, ProjectPointSegment(a, b, c)));
}

// compute distance between point (x,y,z) and plane ax+
// by+cz=d
double DistancePointPlane(double x, double y, double z,
    double a, double b, double c,
    double d)
{
    return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);
}
```

```
// determine if lines from a to b and c to d are
// parallel or collinear
bool LinesParallel(PT a, PT b, PT c, PT d) {
    return fabs(cross(b-a, c-d)) < EPS;
}

bool LinesCollinear(PT a, PT b, PT c, PT d) {
    return LinesParallel(a, b, c, d)
        && fabs(cross(a-b, a-c)) < EPS
        && fabs(cross(c-d, c-a)) < EPS;
}

// determine if line segment from a to b intersects with
// line segment from c to d
bool SegmentsIntersect(PT a, PT b, PT c, PT d) {
    if (LinesCollinear(a, b, c, d)) {
        if (dist2(a, c) < EPS || dist2(a, d) < EPS ||
            dist2(b, c) < EPS || dist2(b, d) < EPS) return
            true;
        if (dot(c-a, c-b) > 0 && dot(d-a, d-b) > 0 && dot(c-
            b, d-b) > 0)
            return false;
        return true;
    }
    if (cross(d-a, b-a) * cross(c-a, b-a) > 0) return
        false;
    if (cross(a-c, d-c) * cross(b-c, d-c) > 0) return
        false;
    return true;
}

// compute intersection of line passing through a and b
// with line passing through c and d, assuming that
// unique
// intersection exists; for segment intersection, check
// if
// segments intersect first
PT ComputeLineIntersection(PT a, PT b, PT c, PT d) {
    b=b-a; d=c-d; c=c-a;
    assert(dot(b, b) > EPS && dot(d, d) > EPS);
    return a + b*cross(c, d)/cross(b, d);
}

// compute center of circle given three points
PT ComputeCircleCenter(PT a, PT b, PT c) {
    b=(a+b)/2;
    c=(a+c)/2;
    return ComputeLineIntersection(b, b+RotateCW90(a-b), c,
        c+RotateCW90(a-c));
}

// determine if point is in a possibly non-convex
// polygon (by William
// Randolph Franklin); returns 1 for strictly interior
// points, 0 for
// strictly exterior points, and 0 or 1 for the
// remaining points.
// Note that it is possible to convert this into an *
// exact* test using
// integer arithmetic by taking care of the division
// appropriately
// (making sure to deal with signs properly) and then by
// writing exact
```

```

// tests for checking point on polygon boundary
bool PointInPolygon(const vector<PT> &p, PT q) {
    bool c = 0;
    for (int i = 0; i < p.size(); i++) {
        int j = (i+1)%p.size();
        if ((p[i].y <= q.y && q.y < p[j].y ||
            p[j].y <= q.y && q.y < p[i].y) &&
            q.x < p[i].x + (p[j].x - p[i].x) * (q.y - p[i].y) /
                (p[j].y - p[i].y))
            c = !c;
    }
    return c;
}

// determine if point is on the boundary of a polygon
bool PointOnPolygon(const vector<PT> &p, PT q) {
    for (int i = 0; i < p.size(); i++)
        if (dist2(ProjectPointSegment(p[i], p[(i+1)%p.size()],
            q), q) < EPS)
            return true;
    return false;
}

// compute intersection of line through points a and b
// with
// circle centered at c with radius r > 0
vector<PT> CircleLineIntersection(PT a, PT b, PT c,
    double r) {
    vector<PT> ret;
    b = b-a;
    a = a-c;
    double A = dot(b, b);
    double B = dot(a, b);
    double C = dot(a, a) - r*r;
    double D = B*B - A*C;
    if (D < -EPS) return ret;
    ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
    if (D > EPS)
        ret.push_back(c+a+b*(-B-sqrt(D))/A);
    return ret;
}

// compute intersection of circle centered at a with
// radius r
// with circle centered at b with radius R
vector<PT> CircleCircleIntersection(PT a, PT b, double r,
    double R) {
    vector<PT> ret;
    double d = sqrt(dist2(a, b));
    if (d > r+R || d+min(r, R) < max(r, R)) return ret;
    double x = (d*d-R*R+r*r)/(2*d);
    double y = sqrt(r*r-x*x);
    PT v = (b-a)/d;
    ret.push_back(a+v*x + RotateCCW90(v)*y);
    if (y > 0)
        ret.push_back(a+v*x - RotateCCW90(v)*y);
    return ret;
}

// This code computes the area or centroid of a (
// possibly nonconvex)
// polygon, assuming that the coordinates are listed in
// a clockwise or

```

```

// counterclockwise fashion. Note that the centroid is
// often known as
// the "center of gravity" or "center of mass".
double ComputeSignedArea(const vector<PT> &p) {
    double area = 0;
    for(int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        area += p[i].x*p[j].y - p[j].x*p[i].y;
    }
    return area / 2.0;
}

double ComputeArea(const vector<PT> &p) {
    return fabs(ComputeSignedArea(p));
}

PT ComputeCentroid(const vector<PT> &p) {
    PT c(0,0);
    double scale = 6.0 * ComputeSignedArea(p);
    for (int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*(p[i].x*p[j].y - p[j].x*p[i].y);
    }
    return c / scale;
}

// tests whether or not a given polygon (in CW or CCW
// order) is simple
bool IsSimple(const vector<PT> &p) {
    for (int i = 0; i < p.size(); i++) {
        for (int k = i+1; k < p.size(); k++) {
            int j = (i+1) % p.size();
            int l = (k+1) % p.size();
            if (i == l || j == k) continue;
            if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
                return false;
        }
    }
    return true;
}

```

2.2 3D geometry

```

public class Geom3D {
    // distance from point (x, y, z) to plane aX + bY + cZ
    // + d = 0
    public static double ptPlaneDist(double x, double y,
        double z,
        double a, double b, double c, double d) {
        return Math.abs(a*x + b*y + c*z + d) / Math.sqrt(a*a
            + b*b + c*c);
    }

    // distance between parallel planes aX + bY + cZ + d1
    // = 0 and
    // aX + bY + cZ + d2 = 0
    public static double planePlaneDist(double a, double b,
        double c,
        double d1, double d2) {
        return Math.abs(d1 - d2) / Math.sqrt(a*a + b*b + c*c);
    }
}

```



```

// distance from point (px, py, pz) to line (x1, y1,
// z1)-(x2, y2, z2)
// (or ray, or segment; in the case of the ray, the
// endpoint is the
// first point)
public static final int LINE = 0;
public static final int SEGMENT = 1;
public static final int RAY = 2;
public static double ptLineDistSq(double x1, double y1,
    double z1,
    double x2, double y2, double z2, double px, double
    py, double pz,
    int type) {
    double pd2 = (x1-x2)*(x1-x2) + (y1-y2)*(y1-y2) + (z1
        -z2)*(z1-z2);

    double x, y, z;
    if (pd2 == 0) {
        x = x1;
        y = y1;
        z = z1;
    } else {
        double u = ((px-x1)*(x2-x1) + (py-y1)*(y2-y1) + (
            pz-z1)*(z2-z1)) / pd2;
        x = x1 + u * (x2 - x1);
        y = y1 + u * (y2 - y1);
        z = z1 + u * (z2 - z1);
        if (type != LINE && u < 0) {
            x = x1;
            y = y1;
            z = z1;
        }
        if (type == SEGMENT && u > 1.0) {
            x = x2;
            y = y2;
            z = z2;
        }
    }

    return (x-px)*(x-px) + (y-py)*(y-py) + (z-pz)*(z-pz)
        ;
}

public static double ptLineDist(double x1, double y1,
    double z1,
    double x2, double y2, double z2, double px, double
    py, double pz,
    int type) {
    return Math.sqrt(ptLineDistSq(x1, y1, z1, x2, y2, z2
        , px, py, pz, type));
}

```

2.3 Convex hull

```

typedef pair<long long, long long> PT;
inline long long cross(PT o, PT a, PT b) {
    PT OA = {a.first-o.first, a.second-o.second};
    PT OB = {b.first-o.first, b.second-o.second};
    return OA.first*OB.second - OA.second*OB.first;
}
inline long double dist(PT a, PT b) {

```

```

    return sqrt(pow(a.first-b.first,2)+pow(a.second-b.
        second,2));
}
vector<PT> convexhull(vector<PT> a) {
    vector<PT> hull;
    sort(a.begin(), a.end(), [](PT i, PT j) {
        if(i.second!=j.second)
            return i.second < j.second;
        return i.first < j.first;
    });
    for(int i=0; i<a.size(); ++i) {
        while(hull.size()>1 && cross(hull[hull.size()-2],
            hull.back(), a[i]) <=0)
            hull.pop_back();
        hull.push_back(a[i]);
    }
    for(int i=a.size()-1, siz = hull.size(); i-->0) {
        while(hull.size()>siz && cross(hull[hull.size()-2],
            hull.back(), a[i]) <=0)
            hull.pop_back();
        hull.push_back(a[i]);
    }
    return hull;
}

```

2.4 Min Enclosing Circle

```

// Minimum enclosing circle, Welzl's algorithm
// Expected linear time.
// If there are any duplicate points in the input, be
// sure to remove them first.
struct point {
    double x;
    double y;
};
struct circle {
    double x;
    double y;
    double r;
    circle() {}
    circle(double x, double y, double r) : x(x), y(y)
        , r(r) {}
};
circle b_md(vector<point> R) {
    if (R.size() == 0) {
        return circle(0, 0, -1);
    } else if (R.size() == 1) {
        return circle(R[0].x, R[0].y, 0);
    } else if (R.size() == 2) {
        return circle((R[0].x+R[1].x)/2.0,
            (R[0].y+R[1].y)/2.0,
            hypot(R[0].x-R
                [1].x, R
                [0].y-R[1].
                y)/2.0);
    } else {
        double D = (R[0].x - R[2].x)*(R[1].y - R
            [2].y) - (R[1].x - R[2].x)*(R[0].y -
            R[2].y);
        double p0 = ((R[0].x - R[2].x)*(R[0].x
            + R[2].x) + (R[0].y - R[2].y)*(R[0].y

```

```

        + R[2].y)) / 2 * (R[1].y - R[2].y) -
        ((R[1].x - R[2].x)*(R[1].x + R[2].x)
        + (R[1].y - R[2].y)*(R[1].y + R[2].y
        )) / 2 * (R[0].y - R[2].y))/D;
    double p1 = (((R[1].x - R[2].x)*(R[1].x
    + R[2].x) + (R[1].y - R[2].y)*(R[1].y
    + R[2].y)) / 2 * (R[0].x - R[2].x) -
    ((R[0].x - R[2].x)*(R[0].x + R[2].x)
    + (R[0].y - R[2].y)*(R[0].y + R[2].y
    )) / 2 * (R[1].x - R[2].x))/D;
    return circle(p0, p1, hypot(R[0].x - p0,
    R[0].y - p1));
}
}
circle b_minidisk(vector<point>& P, int i, vector<point>
R) {
    if (i == P.size() || R.size() == 3) {
        return b_md(R);
    } else {
        circle D = b_minidisk(P, i+1, R);
        if (hypot(P[i].x-D.x, P[i].y-D.y) > D.r)
        {
            R.push_back(P[i]);
            D = b_minidisk(P, i+1, R);
        }
        return D;
    }
}
}
// Call this function.
circle minidisk(vector<point> P) {
    random_shuffle(P.begin(), P.end());
    return b_minidisk(P, 0, vector<point>());
}

```

2.5 Pick's Theorem (Text)

For a polygon with all vertices on lattice points, $A = i + b/2 - 1$, where A is the area, i is the number of lattice points strictly within the polygon, and b is the number of lattice points on the boundary of the polygon. (Note, there is no generalization to higher dimensions)

2.6 Slow Delaunay triangulation

```

// Slow but simple Delaunay triangulation. Does not
// handle degenerate cases (from O'Rourke)
//
// Running time: O(n^4)
// INPUT:      x[] = x-coordinates
//            y[] = y-coordinates
// OUTPUT:     triples = a vector containing m triples of
//            indices corresponding to triangle vertices
typedef double T;
struct triple {
    int i, j, k;
    triple() {}
    triple(int i, int j, int k) : i(i), j(j), k(k) {}
};

```

```

vector<triple> delaunayTriangulation(vector<T>& x,
vector<T>& y) {
    int n = x.size();
    vector<T> z(n);
    vector<triple> ret;
    for (int i = 0; i < n; i++)
        z[i] = x[i] * x[i] + y[i] * y[i];
    for (int i = 0; i < n-2; i++) {
        for (int j = i+1; j < n; j++) {
            for (int k = i+1; k < n; k++) {
                if (j == k) continue;
                double xn = (y[j]-y[i])*(z[k]-z[i]) - (y[k]-y[i]
                )*(z[j]-z[i]);
                double yn = (x[k]-x[i])*(z[j]-z[i]) - (x[j]-x[i]
                )*(z[k]-z[i]);
                double zn = (x[j]-x[i])*(y[k]-y[i]) - (x[k]-x[i]
                )*(y[j]-y[i]);
                bool flag = zn < 0;
                for (int m = 0; flag && m < n; m++)
                    flag = flag && ((x[m]-x[i])*xn + (y[m]-y[i])*
                    yn + (z[m]-z[i])*zn <= 0);
                if (flag) ret.push_back(triple(i, j, k));
            }
        }
    }
    return ret;
}

int main(){
    T xs[]={0, 0, 1, 0.9};
    T ys[]={0, 1, 0, 0.9};
    vector<T> x(&xs[0], &xs[4]), y(&ys[0], &ys[4]);
    vector<triple> tri = delaunayTriangulation(x, y);
    //expected: 0 1 3
    //           0 3 2
    for(int i = 0; i < tri.size(); i++)
        printf("%d %d %d\n", tri[i].i, tri[i].j, tri[i].k);
}

```

3 Numerical algorithms

3.1 Pollard Rho

```

typedef long long unsigned int llui;
typedef long long int lli;
typedef long double float64;
llui mul_mod(llui a, llui b, llui m){
    llui y = (llui) ((float64)a*(float64)b/m+(float64)1/2);
    y = y * m;
    llui x = a * b;
    llui r = x - y;
    if ( (lli)r < 0 ){
        r = r + m; y = y - 1;
    }
    return r;
}
llui C,a,b;
llui gcd(){
    llui c;
    if(a>b){
        c = a; a = b; b = c;
    }
}

```



```

    }
    while(1){
        if(a == 1LL) return 1LL;
        if(a == 0 || a == b) return b;
        c = a; a = b%a;
        b = c;
    }
}
llui f(llui a, llui b){
    llui tmp;
    tmp = mul_mod(a,a,b);
    tmp+=C; tmp%=b;
    return tmp;
}
llui pollard(llui n){
    if(!(n&1)) return 2;
    C=0;
    llui iteracoes = 0;
    while(iteracoes <= 1000){
        llui x,y,d;
        x = y = 2; d = 1;
        while(d == 1){
            x = f(x,n);
            y = f(f(y,n),n);
            llui m = (x>y)?(x-y):(y-x);
            a = m; b = n; d = gcd();
        }
        if(d != n)
            return d;
        iteracoes++; C = rand();
    }
    return 1;
}
llui pot(llui a, llui b, llui c){
    if(b == 0) return 1;
    if(b == 1) return a%c;
    llui resp = pot(a,b>>1,c);
    resp = mul_mod(resp,resp,c);
    if(b&1)
        resp = mul_mod(resp,a,c);
    return resp;
}
// Rabin-Miller primality testing algorithm
bool isPrime(llui n){
    llui d = n-1;
    llui s = 0;
    if(n <= 3 || n == 5) return true;
    if(!(n&1)) return false;
    while(!(d&1)){ s++; d>>=1; }
    for(llui i = 0; i<32; i++){
        llui a = rand();
        a <= 32;
        a+=rand();
        a%=(n-3); a+=2;
        llui x = pot(a,d,n);
        if(x == 1 || x == n-1) continue;
        for(llui j = 1; j<= s-1; j++){
            x = mul_mod(x,x,n);
            if(x == 1) return false;
            if(x == n-1) break;
        }
    }
}

```

```

        if(x != n-1) return false;
    }
    return true;
}
map<llui,int> factors;
// Precondition: factors is an empty map, n is a
// positive integer
// Postcondition: factors[p] is the exponent of p in
// prime factorization of n
void fact(llui n){
    if(!isPrime(n)){
        llui fac = pollard(n);
        fact(n/fac); fact(fac);
    }else{
        map<llui,int>::iterator it;
        it = factors.find(n);
        if(it != factors.end()){
            (*it).second++;
        }else{
            factors[n] = 1;
        }
    }
}
}

```

3.2 Simplex algorithm

```

// Two-phase simplex algorithm for solving linear
// programs of the form
//      maximize      c^T x
//      subject to    Ax <= b ; x >= 0
// INPUT: A -- an m x n matrix
//        b -- an m-dimensional vector
//        c -- an n-dimensional vector
//        x -- a vector where the optimal solution will
//        be stored
// OUTPUT: value of the optimal solution (infinity if
//         unbounded above, nan if infeasible)
// To use this code, create an LPsolver object with
// A, b, and c as arguments. Then, call Solve(x).
typedef long double DOUBLE;
typedef vector<DOUBLE> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;
const DOUBLE EPS = 1e-9;
struct LPsolver {
    int m, n;
    VI B, N;
    VVD D;
    LPsolver(const VVD &A, const VD &b, const VD &c) :
        m(b.size()), n(c.size()), N(n + 1), B(m), D(m + 2,
            VD(n + 2)) {
        for (int i = 0; i < m; i++) for (int j = 0; j < n; j++)
            D[i][j] = A[i][j];
        for (int i = 0; i < m; i++) { B[i] = n + i; D[i][n]
            = -1; D[i][n + 1] = b[i]; }
        for (int j = 0; j < n; j++) { N[j] = j; D[m][j] = -c
            [j]; }
        N[n] = -1; D[m + 1][n] = 1;
    }
    void Pivot(int r, int s) {
        double inv = 1.0 / D[r][s];
    }
}

```

```

for (int i = 0; i < m + 2; i++) if (i != r)
    for (int j = 0; j < n + 2; j++) if (j != s)
        D[i][j] -= D[r][j] * D[i][s] * inv;
for (int j = 0; j < n + 2; j++) if (j != s) D[r][j]
    *= inv;
for (int i = 0; i < m + 2; i++) if (i != r) D[i][s]
    *= -inv;
D[r][s] = inv;
swap(B[r], N[s]);
}
bool Simplex(int phase) {
    int x = phase == 1 ? m + 1 : m;
    while (true) {
        int s = -1;
        for (int j = 0; j <= n; j++) {
            if (phase == 2 && N[j] == -1) continue;
            if (s == -1 || D[x][j] < D[x][s] || D[x][j] == D
                [x][s] && N[j] < N[s]) s = j;
        }
        if (D[x][s] > -EPS) return true;
        int r = -1;
        for (int i = 0; i < m; i++) {
            if (D[i][s] < EPS) continue;
            if (r == -1 || D[i][n + 1] / D[i][s] < D[r][n +
                1] / D[r][s] ||
                (D[i][n + 1] / D[i][s]) == (D[r][n + 1] / D[r
                ][s]) && B[i] < B[r]) r = i;
        }
        if (r == -1) return false;
        Pivot(r, s);
    }
}
DOUBLE Solve(VD &x) {
    int r = 0;
    for (int i = 1; i < m; i++) if (D[i][n + 1] < D[r][n
        + 1]) r = i;
    if (D[r][n + 1] < -EPS) {
        Pivot(r, n);
        if (!Simplex(1) || D[m + 1][n + 1] < -EPS) return
            -numeric_limits<DOUBLE>::infinity();
        for (int i = 0; i < m; i++) if (B[i] == -1) {
            int s = -1;
            for (int j = 0; j <= n; j++)
                if (s == -1 || D[i][j] < D[i][s] || D[i][j] ==
                    D[i][s] && N[j] < N[s]) s = j;
            Pivot(i, s);
        }
    }
    if (!Simplex(2)) return numeric_limits<DOUBLE>::
        infinity();
    x = VD(n);
    for (int i = 0; i < m; i++) if (B[i] < n) x[B[i]] =
        D[i][n + 1];
    return D[m][n + 1];
}
}
int main() {
    const int m = 4, n = 3;
    DOUBLE _A[m][n] = {
        { 6, -1, 0 },

```

```

        { -1, -5, 0 },
        { 1, 5, 1 },
        { -1, -5, -1 }
    };
    DOUBLE _b[m] = { 10, -4, 5, -5 }, _c[n] = { 1, -1, 0
    };
    VVD A(m);
    VD b(_b, _b + m), c(_c, _c + n);
    for (int i = 0; i < m; i++) A[i] = VD(_A[i], _A[i] + n
    );
    LPSolver solver(A, b, c);
    VD x;
    DOUBLE value = solver.Solve(x);
    cerr << "VALUE: " << value << endl; // VALUE: 1.29032
    cerr << "SOLUTION:"; // SOLUTION: 1.74194 0.451613 1
    for (size_t i = 0; i < x.size(); i++) cerr << " " << x
        [i];
}

```

3.3 Reduced row echelon form

*// Reduced row echelon form via Gauss-Jordan elimination
 // with partial pivoting. This can be used for
 // computing the rank of a matrix.
 // Running time: $O(n^3)$
 // INPUT: $a[i][j]$ = an $n \times m$ matrix
 // OUTPUT: $rref[i][j]$ = an $n \times m$ matrix (stored in $a[i][j]$)
 // returns rank of $a[i][j]$*

```

const double EPSILON = 1e-10;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;
int rref(VVT &a) {
    int n = a.size(), m = a[0].size(), r = 0;
    for (int c = 0; c < m && r < n; c++) {
        int j = r;
        for (int i = r + 1; i < n; i++)
            if (fabs(a[i][c]) > fabs(a[j][c])) j = i;
        if (fabs(a[j][c]) < EPSILON) continue;
        swap(a[j], a[r]);
        T s = 1.0 / a[r][c];
        for (int j = 0; j < m; j++) a[r][j] *= s;
        for (int i = 0; i < n; i++) if (i != r) {
            T t = a[i][c];
            for (int j = 0; j < m; j++) a[i][j] -= t * a[r][j
            ];
        }
        r++;
    }
    return r;
}

```

3.4 Fast Fourier transform

```

template<typename fpt>
struct fft_wrap {
    using cpx_t = complex<fpt>;
    const fpt two_pi = 4 * acosl(0);
    vector<cpx_t> roots; //stores the N-th roots of unity.
    int N;
}

```

```

fft_wrap(int N) : roots(N), N(N) {
    for (int i = 0; i < N; ++i) {
        roots[i] = EXP(two_pi * i / fpt(N));
    }
}

cpx_t EXP(fpt theta) {
    return {cos(theta), sin(theta)};
}

void fft(cpx_t *in, cpx_t *out, int size, int dir) {
    bit_reverse(in, out, size);
    for (int s = 0; (1 << s) < size; ++s) {
        int s_ = s + 1;
        for (int k = 0; k < size; k += (1 << s_)) {
            for (int j = 0; j < (1 << s); ++j) {
                int id = (N + dir * (N >> s_) * j) & (N - 1);
                cpx_t w = roots[id];
                cpx_t t = w * out[k + j + (1 << s)];
                cpx_t u = out[k + j];
                out[k + j] = u + t;
                out[k + j + (1 << s)] = u - t;
            }
        }
    }

    void bit_reverse(cpx_t *in, cpx_t *out, int size) {
        for (int i = 0; i < size; ++i) {
            int rev = 0, i_copy = i;
            for (int j = 0; (1 << j) < size; ++j) {
                rev = (rev << 1) + (i_copy & 1);
                i_copy >>= 1;
            }
            out[rev] = in[i];
        }
    }
};

int main() {
    typedef complex<double> cpx_t;
    fft_wrap<double> fft_wrapper(2048);

    vector<cpx_t> in = {1.0, 1.0, 1.0, 1.0, 0.0, 0.0, 0.0,
        0.0}, out(8);

    fft_wrapper.fft(&in[0], &out[0], 8, 1);
    fft_wrapper.fft(&out[0], &in[0], 8, -1);
    for (int i = 0; i < 8; ++i) {
        cout << in[i].real() << ' ' << in[i].imag() << endl;
    }
}

```

3.5 Number Theoretic transform

```

// gen should be 5^((p - 1) / fft_wrapper_size)

template<int P>
struct field_t { ... };

template<typename fpt, int gen>
struct fft_wrap {
    vector<fpt> roots; //stores the N-th roots of unity.
    int N;

```

```

fft_wrap(int _N) : roots(_N), N(_N) {
    roots[0] = 1;
    for (int i = 1; i < N; ++i) {
        roots[i] = roots[i - 1] * gen;
        if (i != N - 1) {
            assert(roots[i].v != 1);
        }
    }
}

void fft(fpt *in, fpt *out, int size, int dir) {
    bit_reverse(in, out, size);
    for (int s = 0; (1 << s) < size; ++s) {
        int s_ = s + 1;
        for (int k = 0; k < size; k += (1 << s_)) {
            for (int j = 0; j < (1 << s); ++j) {
                int id = (N + dir * (N >> s_) * j) & (N - 1);
                fpt w = roots[id];
                fpt t = w * out[k + j + (1 << s)];
                fpt u = out[k + j];
                out[k + j] = u + t;
                out[k + j + (1 << s)] = u - t;
            }
        }
    }

    void bit_reverse(fpt *in, fpt *out, int size) {
        for (int i = 0; i < size; ++i) {
            int rev = 0, i_copy = i;
            for (int j = 0; (1 << j) < size; ++j) {
                rev = (rev << 1) + (i_copy & 1);
                i_copy >>= 1;
            }
            out[rev] = in[i];
        }
    }
};

using fpt = field_t<mod>;
fft_wrap<fpt, gen> fft_wrapper(1 << 18);

vector<fpt> polymul(vector<fpt> P1, vector<fpt> P2) {
    int fsize = P1.size() + P2.size() - 1;
    int N = max(P1.size(), P2.size());
    while(N & (N - 1)) {
        ++N;
    }
    N *= 2;
    P1.resize(N); P2.resize(N);
    vector<fpt> temp(N);
    fft_wrapper.fft(&P1[0], &temp[0], N, 1);
    fft_wrapper.fft(&P2[0], &P1[0], N, 1);
    for (int i = 0; i < N; ++i) {
        P1[i] *= temp[i];
    }
    fft_wrapper.fft(&P1[0], &temp[0], N, -1);
    field_t<mod> inv(N);
    inv = inv.modexp(mod - 2);
    for (int i = 0; i < N; ++i) {
        temp[i] *= inv;
    }
    temp.resize(fsize);
    return temp;
}

```

```
}
```

3.6 Discrete Logarithm

```
// Calculates x such that g^x % md == h
int baby_giant(int g, int h, int md) {
    unordered_map<int,int> mp;
    int sq = ceil(sqrt1(md));
    for(int i=0, now=1; i<sq; ++i)
        mp[now] = i, now = (long long) now*g % md;
    for(int i=0, jmp=power(g, md-1-sq); i<sq; ++i) {
        if(mp.find(h) != mp.end()) return i*sq+mp[h];
        h = (long long) h*jmp % md;
    }
    return -1;
}
```

3.7 Mobius Inversion (Text)

$$\mu(n) = \begin{cases} 0 & n \text{ not squarefree} \\ 1 & n \text{ squarefree w/ even no. of prime factors} \\ -1 & n \text{ squarefree w/ odd no. of prime factors} \end{cases}$$

Note that $\mu(a)\mu(b) = \mu(ab)$ for a, b relatively prime

$$\text{Also } \sum_{d|n} \mu(d) = \begin{cases} 1 & \text{if } n = 1 \\ 0 & \text{otherwise} \end{cases}$$

Möbius Inversion If $g(n) = \sum_{d|n} f(d)$ for all $n \geq 1$, then $f(n) = \sum_{d|n} \mu(d)g(n/d)$ for all $n \geq 1$.

3.8 Burnside Lemma (Text)

The number of orbits of a set X under the group action G equals the average number of elements of X fixed by the elements of G .

Here's an example. Consider a square of $2n$ times $2n$ cells. How many ways are there to color it into X colors, up to rotations and/or reflections? Here, the group has only 8 elements (rotations by 0, 90, 180 and 270 degrees, reflections over two diagonals, over a vertical line and over a horizontal line). Every coloring stays itself after rotating by 0 degrees, so that rotation has X^{4n^2} fixed points. Rotation by 180 degrees and reflections over a horizontal/vertical line split all cells in pairs that must be of the same color for a coloring to be unaffected by such rotation/reflection, thus there exist X^{2n^2} such colorings for each of them. Rotations by 90 and 270 degrees split cells in groups of four, thus yielding X^{n^2} fixed colorings. Reflections over diagonals split cells into $2n$ groups of 1 (the diagonal itself) and $2n^2 - n$ groups of 2 (all remaining cells), thus yielding $X^{2n^2-n+2n} = X^{2n^2+n}$ unaffected colorings. So, the answer is $(X^{4n^2} + 3X^{2n^2} + 2X^{n^2} + 2X^{2n^2+n})/8$.

3.9 Number Theory (Modular, CRT, Linear Diophantine)

```
// All algorithms described here work on nonnegative integers.
int mod(int a, int b) {
    return ((a%b) + b) % b;
}
int lcm(int a, int b) {
    return a / __gcd(a, b)*b;
}
int powermod(int a, int b, int m) {
    return b?powermod(a*a%m, b/2, m) * (b%2?a:1)%m:1;
}
// returns g = gcd(a, b); finds x, y such that d = ax + by
int extended_euclid(int a, int b, int &x, int &y) {
    int xx = y = 0;
    int yy = x = 1;
    while (b) {
        int q = a / b;
        int t = b; b = a%b; a = t;
        t = xx; xx = x - q*xx; x = t;
        t = yy; yy = y - q*yy; y = t;
    }
    return a;
}
// finds all solutions to ax = b (mod n)
VI modular_linear_equation_solver(int a, int b, int n) {
    int x, y;
    VI ret;
    int g = extended_euclid(a, n, x, y);
    if (!(b%g)) {
        x = mod(x*(b / g), n);
        for (int i = 0; i < g; i++)
            ret.push_back(mod(x + i*(n / g), n));
    }
    return ret;
}
// computes b such that ab = 1 (mod n), returns -1 on failure
int mod_inverse(int a, int n) {
    int x, y;
    int g = extended_euclid(a, n, x, y);
    if (g > 1) return -1;
    return mod(x, n);
}
// Chinese remainder theorem (special case): find z such
// that z % m1 = r1, z % m2 = r2.
// Here, z is unique modulo M = lcm(m1, m2).
// Return (z, M). On failure, M = -1.
PII chinese_remainder_theorem(int m1, int r1, int m2,
    int r2) {
    int s, t;
    int g = extended_euclid(m1, m2, s, t);
    if (r1%g != r2%g) return make_pair(0, -1);
    return make_pair(mod(s*r2*m1 + t*r1*m2, m1*m2) / g, m1
        *m2 / g);
}
// Find z such that z % m[i] = r[i] for all i.
// The solution is unique modulo M = lcm_i (m[i]).
// Return (z, M). On failure, M = -1.
// We don't require a[i]'s to be relatively prime.
PII chinese_remainder_theorem(const VI &m, const VI &r) {
```

```

PII ret = make_pair(r[0], m[0]);
for (int i = 1; i < m.size(); i++) {
    ret = chinese_remainder_theorem(ret.second, ret.first, m[i], r[i]);
    if (ret.second == -1) break;
}
return ret;
}
// computes x and y such that ax + by = c
// returns whether the solution exists
bool linear_diophantine(int a, int b, int c, int &x, int &y) {
    if (!a && !b) {
        if (c) return false;
        x = 0; y = 0;
        return true;
    }
    if (!a) {
        if (c % b) return false;
        x = 0; y = c / b;
        return true;
    }
    if (!b) {
        if (c % a) return false;
        x = c / a; y = 0;
        return true;
    }
    int g = __gcd(a, b);
    if (c % g) return false;
    x = c / g * mod_inverse(a / g, b / g);
    y = (c - a*x) / b;
    return true;
}

```

4 Graph algorithms

4.1 Dynamic Connectivity

```

struct UnionFind {
    int n, comp;
    vector<int> uf, si, c;
    UnionFind(int n=0) : n(n), comp(n), uf(n), si(n, 1) {
        for (int i=0; i<n; ++i)
            uf[i]=i;
    }
    int find(int x) {return x==uf[x]?x:find(uf[x]);}
    bool join(int x, int y) {
        if ((x=find(x))==(y=find(y))) return false;
        if (si[x]<si[y]) swap(x, y);
        si[x]+=si[y]; uf[y]=x; comp--;
        c.push_back(y);
        return true;
    }
    int snap() {return c.size();}
    void rollback(int snap) {
        while (c.size()>snap) {
            int x=c.back(); c.pop_back();
            si[uf[x]]-=si[x]; uf[x]=x; comp++;
        }
    }
};

```

```

enum {ADD, DEL, QUERY};
struct Query {int type, x, y;};
struct DynCon {
    vector<Query> q;
    UnionFind dsu;
    vector<int> mt;
    map<pair<int, int>, int> last;
    DynCon(int n) : dsu(n) {}
    void add(int x, int y) {
        if (x>y) swap(x, y);
        q.push_back((Query){ADD, x, y}); mt.push_back(-1);
        last[make_pair(x, y)] = q.size() - 1;
    }
    void remove(int x, int y) {
        if (x>y) swap(x, y);
        q.push_back((Query){DEL, x, y});
        int pr = last[make_pair(x, y)];
        mt[pr] = q.size() - 1;
        mt.push_back(pr);
    }
    void query(int x, int y) {
        q.push_back((Query){QUERY, x, y});
        mt.push_back(-1);
    }
    void process() { // answers all queries in order
        if (!q.size()) return;
        for (int i=0; i<q.size(); ++i)
            if (q[i].type==ADD && mt[i]<0)
                mt[i] = q.size();
        go(0, q.size());
    }
    void go(int l, int r) {
        if (l+1==r) {
            if (q[l].type==QUERY) // answer query using DSU
                puts(dsu.find(q[l].x)==dsu.find(q[l].y)? "YES":"NO");
            return;
        }
        int s=dsu.snap(), m=(l+r)/2;
        for (int i=r-1; i>=m; --i)
            if (mt[i]>=0 && mt[i]<l)
                dsu.join(q[i].x, q[i].y);
        go(l, m);
        dsu.rollback(s);
        for (int i=m-1; i>=l; --i) if (mt[i]>=r) dsu.join(q[i].x, q[i].y);
        go(m, r);
        dsu.rollback(s);
    }
};

```

4.2 Bridges

```

// Finds bridges and cut vertices
//
// Receives:
// N: number of vertices
// l: adjacency list
//
// Gives:
// vis, seen, par (used to find cut vertices)

```

```

// ap - 1 if it is a cut vertex, 0 otherwise
// brid - vector of pairs containing the bridges

typedef pair<int, int> PII;

int N;
vector<int> l[MAX];
vector<PII> brid;
int vis[MAX], seen[MAX], par[MAX], ap[MAX];
int cnt, root;

void dfs(int x) {
    if(vis[x] != -1)
        return;
    vis[x] = seen[x] = cnt++;

    int adj = 0;
    for(int i = 0; i < (int)l[x].size(); i++) {
        int v = l[x][i];
        if(par[x] == v)
            continue;
        if(vis[v] == -1) {
            adj++;
            par[v] = x;
            dfs(v);
            seen[x] = min(seen[x], seen[v]);
            if(seen[v] >= vis[x] && x != root)
                ap[x] = 1;
            if(seen[v] == vis[v])
                brid.push_back(make_pair(v, x));
        }
        else {
            seen[x] = min(seen[x], vis[v]);
            seen[v] = min(seen[x], seen[v]);
        }
    }
    if(x == root) ap[x] = (adj > 1);
}

void bridges() {
    brid.clear();
    for(int i = 0; i < N; i++) {
        vis[i] = seen[i] = par[i] = -1;
        ap[i] = 0;
    }
    cnt = 0;
    for(int i = 0; i < N; i++)
        if(vis[i] == -1) {
            root = i;
            dfs(i);
        }
}

```

4.3 Strongly connected components

```

struct SCC {
    int V, group_cnt;
    vector<vector<int>> adj, radj;
    vector<int> group_num, vis;
    stack<int> stk;
    // V = number of vertices
    SCC(int V): V(V), group_cnt(0), group_num(V), vis(V),
        adj(V), radj(V) {}
}

```

```

// Call this to add an edge (0-based)
void add_edge(int v1, int v2) {
    adj[v1].push_back(v2);
    radj[v2].push_back(v1);
}

void fill_forward(int x) {
    vis[x] = true;
    for(int i = 0; i < adj[x].size(); i++) {
        if(!vis[adj[x][i]]) {
            fill_forward(adj[x][i]);
        }
    }
    stk.push(x);
}

void fill_backward(int x) {
    vis[x] = false;
    group_num[x] = group_cnt;
    for(int i = 0; i < radj[x].size(); i++) {
        if(vis[radj[x][i]]) {
            fill_backward(radj[x][i]);
        }
    }
}

// Returns number of strongly connected components.
// After this is called, group_num contains component
// assignments (0-based)
int get_scc() {
    for(int i = 0; i < V; i++) {
        if(!vis[i]) fill_forward(i);
    }
    group_cnt = 0;
    while(!stk.empty()) {
        if(vis[stk.top()]) {
            fill_backward(stk.top());
            group_cnt++;
        }
        stk.pop();
    }
    return group_cnt;
}

```

5 String Stuff

5.1 Suffix Automaton

```

struct SuffixAutomaton {
    vector<map<char, int>> edges; // edges[i]: the labeled
    // edges from node i
    vector<int> link; // link[i] : the parent of i
    vector<int> length; // length[i]: length of longest
    // string in ith class
    vector<int> cnt; // No. of times substring occurs
    int last; // index of equivalence class of whole
    // string
    SuffixAutomaton(string const& s) {
        // add the initial node
        edges.push_back(map<char, int>());
        link.push_back(-1);
        length.push_back(0);
    }
}

```



```

cnt.push_back(0);
last = 0;
for(int i=0; i<s.size(); i++) {
    // construct r
    edges.push_back(map<char, int>());
    length.push_back(i+1);
    link.push_back(0);
    cnt.push_back(1);
    int r = edges.size() - 1;
    // add edges to r and find p with link to q
    int p = last;
    while(p >= 0 && !edges[p].count(s[i])) {
        edges[p][s[i]] = r;
        p = link[p];
    }
    if(p != -1) {
        int q = edges[p][s[i]];
        if(length[p] + 1 == length[q]) {
            // we do not have to split q, just set the
            // correct suffix link
            link[r] = q;
        } else {
            // we have to split, add q'
            edges.push_back(edges[q]); // copy edges of q
            length.push_back(length[q] + 1);
            link.push_back(link[q]); // copy parent of q
            cnt.push_back(0);
            int qq = edges.size()-1;
            // add qq as the new parent of q and r
            link[q] = link[r] = qq; cnt[r] = 1;
            // move short classes pointing to q to point
            // to q'
            while(p >= 0 && edges[p][s[i]] == q) {
                edges[p][s[i]] = qq;
                p = link[p];
            }
        }
    }
    last = r;
}

vector<int> ind(length.size());
iota(ind.begin(), ind.end(), 0);
sort(ind.begin(), ind.end(), [&](int i, int j){
    return length[i] > length[j];
});
for(auto i:ind) if(link[i] >= 0)
    cnt[link[i]] += cnt[i];
};

```

5.2 Suffix array

```

vector<int> suffix_array(string &A){
    int n=A.size(), i=n, *M=new int[5*n];
    int *B=M, *C=M+n, *F=M+2*n, *G=M+3*n, *S=M+4*n;
    for(; i-->0; S[i]=n-i-1) B[i]=A[i];
    stable_sort(S, S+n, [&](int i, int j){return A[i]<A[j];});
    for(int L=1, p; L<n; L*=2){
        for(++i<n; F[i]=B[S[i]], G[i]=B[S[i]+L/2]);
    }
}

```

```

for(--i; F[i]=F[i]==F[i-1]&&G[i]==G[i-1]&&S[i-1]<n-L);
for(p=B[*S]=0; ++i<n; B[S[i]]=p=F[i]?p:i);
for(fill_n(G, n, 0); i-->0; F[i]=S[i]<L?-1:B[S[i]-L]);
for(iota(C, C+n, 0); ++i<n; ~F[i]?G[i]=C[F[i]]++:0);
for(copy_n(S, n, F); i-->0; F[i]<L?0:S[G[i]]=F[i]-L);
}
vector<int> res(S, S+n);
delete[] M;
return res;
}

vector<int> kasai(string &s, vector<int> &sa){
    int n = s.size();
    vector<int> lcp(n), inv(n);
    for(int i=0; i<n; ++i) inv[sa[i]] = i;
    for(int i=0, k=0; i<n; ++i){
        if(k<0) k = 0;
        if(inv[i]==n-1){ k=0; continue; }
        for(int j=sa[inv[i]+1]; max(i, j)+k<n&&s[i+k]==s[j+k]; ++k);
        lcp[inv[i]] = k--;
    }
    return lcp;
}

```

5.3 Z Algorithm

```

vector<int> compute_Z(string s) {
    int n = s.length();
    vector<int> z(n, 0);
    z[0] = n;
    for (int i = 1, l = 0, r = 0; i < n; ++i) {
        if (r >= i) {
            z[i] = min(z[i - l], r - i + 1);
        }
        while (i+z[i] < n and s[i+z[i]] == s[z[i]]) {
            ++z[i];
        }
        if (i + z[i] - 1 > r) {
            r = i + z[i] - 1;
            l = i;
        }
    }
    return z;
}

```

5.4 KMP

```

vector<int> find_prefix(const vector<int> &P){
    int M = P.size();
    vector<int> pi(M);
    /* pi[i] <- largest prefix P[0..pi[i]] which is a
    suffix of P[0..i]
    * (but not equal to it) */
    pi[0] = -1;
    for (int i = 1, k = -1; i < M; ++i) {
        while(k > -1 && P[k + 1] != P[i])
            k = pi[k];
        if (P[k + 1] == P[i]) ++k;
        pi[i] = k;
    }
}

```

```

    return pi;
}
int kmp_matcher(const vector<int> &T, const vector<int>
    &P){
    int M = P.size(), N = T.size();
    vector<int> pi = find_prefix(P);
    int q = -1, matches = 0;
    for (int i = 0; i < N; ++i) {
        while(q > -1 && P[q + 1] != T[i])
            q = pi[q];
        if (P[q + 1] == T[i]) ++q;
        if (q == M - 1)
            ++matches, q = pi[q];
    }
    return matches;
}

```

5.5 String Hashing

```

struct hasher{
    int hashes[MAXN+5];
    int *pow, *inv;
    int mod;
    int n;
    void init(string &str, int *p, int *i, int m){
        pow = p;
        inv = i;
        mod = m;
        n = str.size();
        int last = 0;
        for (int i = 0; i < n; i++){
            int c = str[i] - 'a' + 1;
            last = (last + 1ll*c*pow[i]) % mod;
            hashes[i] = last;
        }
    }
    int getHash(int l, int r){
        if (r >= n || l < 0)
            return -1;
        int curr = hashes[r] - (l-1 >= 0 ? hashes[l-1] : 0);
        curr = ((curr % mod) + mod) % mod;
        curr = (1ll*curr*inv[l]) % mod;
        return curr;
    }
} A, B, C;

```

5.6 Palindrome DSU

```

// given an unknown string s and Q ranges that
// are known to be palindromes, this computes the
// characters
// that have to be equal in O(Q + n log n)
struct Palindrome{
    Palindrome(){}
    Palindrome(int n_):n(n_), m(3+__lg(n)), qs(m), p(2*n){
        iota(p.begin(), p.end(), 0);
    }
    int f(int i){
        return p[i] == i ? i : p[i] = f(p[i]);
    }
    void u(int a, int b){

```

```

        assert(0 <= a && a < 2*n);
        assert(0 <= b && b < 2*n);
        // union with splicing is a bit faster than
        // just path compression also guarantees p[i] <= i
        while(p[a] != p[b]){
            if(p[a] < p[b]) swap(a, b);
            if(p[a] == a){
                p[a] = b;
                return;
            }
            int tmp = p[a];
            p[a] = p[b];
            a = p[tmp];
        }
    }
    int components(){
        int ret = 0;
        for(int i=0; i<(int)p.size(); ++i)
            if(p[i] == i) ++ret;
        return ret;
    }
    // call this after adding all queries
    void compute(){
        vector<int> p2(2*n);
        for(int l=m-1; l>=0; --l){
            const int s = 1<<l;
            for(int i=0; i<2*n; ++i) p2[i] = f(i);
            for(int i=0; i+s<2*n; ++i){
                const int j = p2[i];
                if(j+s < 2*n) u(i+s, j+s);
            }
            for(auto const&e:qs[l])
                u(e.first, e.second);
        }
        // link point with mirror-image
        for(int i=0; i<n; ++i)
            u(i, 2*n-1-i);
    }
    // force [l, r] to be a palindrome
    void add_q(int l, int r){
        assert(0 <= l && l <= r && r < n);
        if(l==r) return;
        const int range = r-l+1;
        const int k = __lg(range);
        qs[k].emplace_back(l, 2*n-1-r);
    }
    int n, m;
    vector<vector<pair<int, int>>> qs;
    vector<int> p;
};

```

5.7 Eertree

```

/*
Palindrome tree. Useful structure to deal with
palindromes in strings. O(N)
This code counts no. of palindrome substrings of string.
Based on problem 1750 from informatics.mccme.ru:
http://informatics.mccme.ru/moodle/mod/statements/view.php?chapterid=1750
*/

```

```

const int MAXN = 105000;
struct node {
    int next[26];
    int len;
    int sufflink;
    int num;
};
int len;
char s[MAXN];
node tree[MAXN];
int num;           // node 1 - root with len -1, node 2
                  // - root with len 0
int suff;          // max suffix palindrome
long long ans;

bool addLetter(int pos) {
    int cur = suff, curlen = 0;
    int let = s[pos] - 'a';
    while (true) {
        curlen = tree[cur].len;
        if (pos - 1 - curlen >= 0 && s[pos - 1 - curlen]
            == s[pos])
            break;
        cur = tree[cur].sufflink;
    }
    if (tree[cur].next[let]) {
        suff = tree[cur].next[let];
        return false;
    }
    num++;
    suff = num;
    tree[num].len = tree[cur].len + 2;
    tree[cur].next[let] = num;
    if (tree[num].len == 1) {
        tree[num].sufflink = 2;
        tree[num].num = 1;
        return true;
    }
    while (true) {
        cur = tree[cur].sufflink;
        curlen = tree[cur].len;
        if (pos - 1 - curlen >= 0 && s[pos - 1 - curlen]
            == s[pos]) {
            tree[num].sufflink = tree[cur].next[let];
            break;
        }
    }
    tree[num].num = 1 + tree[tree[num].sufflink].num;
    return true;
}

void initTree() {
    num = 2; suff = 2;
    tree[1].len = -1; tree[1].sufflink = 1;
    tree[2].len = 0; tree[2].sufflink = 1;
}

int main() {
    gets(s);
    len = strlen(s);
    initTree();
    for (int i = 0; i < len; i++) {
        addLetter(i);

```

```

        ans += tree[suff].num;
    }
    cout << ans << endl;
}

```

6 Data structures

6.1 BIT Range Queries

```

struct BIT {
    int n;
    vector<int> slope;
    vector<int> intercept;

    // BIT can be thought of as having entries f[1], ...,
    // f[n] which are 0-initialized
    BIT(int n): n(n), slope(n+1), intercept(n+1) {}
    // returns f[1] + ... + f[idx-1]
    // precondition idx <= n+1

    int query(int idx) {
        int m = 0, b = 0;
        for (int i = idx-1; i > 0; i -= i&-i) {
            m += slope[i];
            b += intercept[i];
        }
        return m*idx + b;
    }

    // adds amt to f[i] for i in [idx1, idx2)
    // precondition 1 <= idx1 <= idx2 <= n+1 (you can't
    // update element 0)
    void update(int idx1, int idx2, int amt) {
        for (int i = idx1; i <= n; i += i&-i) {
            slope[i] += amt;
            intercept[i] -= idx1*amt;
        }
        for (int i = idx2; i <= n; i += i&-i) {
            slope[i] -= amt;
            intercept[i] += idx2*amt;
        }
    }
};

```

6.2 Treaps

```

typedef struct node{
    int prior, size;
    int val; //value stored in the array
    int sum; //whatever info you want to maintain in
             //segtree for each node
    int lazy; //whatever lazy update you want to do
    struct node *l, *r;
} node;

struct Treap {
    typedef node* pnode;
    int sz(pnode t) {
        return t?t->size:0;
    }
}

```

```

void upd_sz(pnode t){
    if(t)t->size=sz(t->l)+1+sz(t->r);
}
void lazy(pnode t){
    if(!t || !t->lazy) return;
    t->val+=t->lazy; //operation of lazy
    t->sum+=t->lazy*sz(t);
    if(t->l)t->l->lazy+=t->lazy; //propagate lazy
    if(t->r)t->r->lazy+=t->lazy;
    t->lazy=0;
}
void reset(pnode t){
    if(t)t->sum = t->val; //no need to reset lazy coz
    when we call this lazy would itself be propagated
}
void combine(pnode& t,pnode l,pnode r){ //combining two
    ranges of segtree
    if(!l || !r) return void(t = l?l:r);
    t->sum = l->sum + r->sum;
}
void operation(pnode t){ //operation of segtree
    if(!t) return;
    reset(t); //reset the value of current node assuming
    it now represents a single element of the array
    lazy(t->l); lazy(t->r); //imp: propagate lazy before
    combining t->l, t->r;
    combine(t, t->l, t);
    combine(t, t, t->r);
}
void split(pnode t, pnode &l, pnode &r, int pos, int add
    =0){
    if(!t) return void(l=r=NULL);
    lazy(t);
    int curr_pos = add + sz(t->l);
    if(curr_pos<=pos) //element at pos goes to left
        subtree(l)
        split(t->r, t->r, r, pos, curr_pos+1), l=t;
    else
        split(t->l, l, t->l, pos, add), r=t;
    upd_sz(t);
    operation(t);
}
void merge(pnode &t, pnode l, pnode r){ //l->leftarray, r
    ->rightarray, t->resulting array
    lazy(l); lazy(r);
    if(!l || !r) t = l?l:r;
    else if(l->prior>r->prior) merge(l->r, l->r, r), t=l;
    else merge(r->l, l, r->l), t=r;
    upd_sz(t);
    operation(t);
}
pnode init(int val){
    pnode ret = (pnode)malloc(sizeof(node));
    ret->prior=rand(); ret->size=1;
    ret->val=val;
    ret->sum=val; ret->lazy=0;
    return ret;
}
int range_query(pnode t, int l, int r){ //[l,r]
    pnode L, mid, R;

```

```

    split(t, L, mid, l-1);
    split(mid, t, R, r-1); //note: r-1!!
    int ans = t->sum;
    merge(mid, L, t);
    merge(t, mid, R);
    return ans;
}
void range_update(pnode t, int l, int r, int val){ //[l,r]
    pnode L, mid, R;
    split(t, L, mid, l-1);
    split(mid, t, R, r-1); //note: r-1!!
    t->lazy+=val; //lazy_update
    merge(mid, L, t);
    merge(t, mid, R);
}
};

```

6.3 Link-Cut Tree

```

const int MXN = 100005, MEM = 100005;
struct Splay {
    static Splay nil, mem[MEM], *pmem;
    Splay *ch[2], *f;
    int val, rev, size;
    Splay(int _val=-1) : val(_val), rev(0), size(1)
    { f = ch[0] = ch[1] = &nil; }
    bool isr()
    { return f->ch[0] != this && f->ch[1] != this; }
    int dir()
    { return f->ch[0] == this ? 0 : 1; }
    void setCh(Splay *c, int d) {
        ch[d] = c;
        if (c != &nil) c->f = this;
        pull();
    }
    void push() {
        if(!rev) return;
        swap(ch[0], ch[1]);
        if (ch[0] != &nil) ch[0]->rev ^= 1;
        if (ch[1] != &nil) ch[1]->rev ^= 1;
        rev=0;
    }
    void pull() {
        size = ch[0]->size + ch[1]->size + 1;
        if (ch[0] != &nil) ch[0]->f = this;
        if (ch[1] != &nil) ch[1]->f = this;
    }
} Splay::nil, Splay::mem[MEM], *Splay::pmem = Splay::mem;
Splay *nil = &Splay::nil;
void rotate(Splay *x) {
    Splay *p = x->f;
    int d = x->dir();
    if (!p->isr()) p->f->setCh(x, p->dir());
    else x->f = p->f;
    p->setCh(x->ch[!d], d); x->setCh(p, !d); p->pull();
    x->pull();
}
vector<Splay*> splayVec;
void splay(Splay *x) {
    splayVec.clear();
}

```

```

for(Splay *q=x;; q=q->f){
    splayVec.push_back(q);
    if (q->isr()) break;
}
reverse(begin(splayVec), end(splayVec));
for (auto it : splayVec) it->push();
while (!x->isr())
    if (x->f->isr()) rotate(x);
    else if (x->dir()==x->f->dir()) rotate(x->f), rotate(x);
    else rotate(x), rotate(x);
}
int id(Splay *x) { return x - Splay::mem + 1; }
Splay* access(Splay *x){
    Splay *q = nil;
    for (;x!=nil;x=x->f) {splay(x); x->setCh(q, 1); q = x;
    }
    return q;
}
void chroot(Splay *x){
    access(x); splay(x); x->rev ^= 1; x->push(); x->pull()
}
void link(Splay *x, Splay *y){
    access(x); splay(x);
    chroot(y); x->setCh(y, 1);
}
void cut_p(Splay *y) {
    access(y); splay(y); y->push(); y->ch[0] = y->ch[0]->f
    = nil;
}
void cut(Splay *x, Splay *y){
    chroot(x); cut_p(y);
}
Splay* get_root(Splay *x) {
    access(x); splay(x);
    for (; x->ch[0] != nil; x = x->ch[0]) x->push();
    splay(x); return x;
}
bool conn(Splay *x, Splay *y) {
    return (x = get_root(x)) == (y = get_root(y));
}
Splay* lca(Splay *x, Splay *y) {
    access(x); access(y); splay(x);
    if (x->f == nil) return x;
    else return x->f;
}

```

7 Miscellaneous

7.1 2-SAT

```

class Two_Sat {
    int N; // number of variables
    vector<int> val; // assignment of x is at val[2x] and
    -x at val[2x+1]
    vector<char> valid; // changes made at time i are kept
    iff valid[i]
    vector<vector<int>> G; // graph of implications G[x][
    i] = y means (x -> y)
}

```

```

Two_Sat(int N_) : N(N_) { // create a formula over N
    variables (numbered 1 to N)
    G.resize(2*N);
}
int add_variable() {
    G.emplace_back(); G.emplace_back();
    return N++;
}
private:
    // converts a signed variable index to its position in
    val[] and G[]
    int to_ind(int x) {
        return 2*(abs(x)-1) + (x<0);
    }
    // Add a directed edge to the graph.
    // You most likely do not want to call this yourself!
    void add_edge(int a, int b) {
        G[to_ind(a)].push_back(to_ind(b));
    }
    int time() {
        return valid.size()-1;
    }
    bool dfs(int x) {
        if(valid[abs(val[x])]) return val[x]>0;
        val[x] = time();
        val[x^1] = -time();
        for(int e:G[x])
            if(!dfs(e))
                return false;
        return true;
    }
public:
    // Add the or-clause: (a or b)
    void add_or(int a, int b) {
        add_edge(-a,b); add_edge(-b,a);
    }
    // Add the implication: a -> b
    void add_implication(int a, int b) {
        add_or(-a, b);
    }
    // Add condition: x is true
    void add_true(int x) {
        add_or(x,x);
    }
    // At most one with linear number of clauses
    template<typename T>
    void add_at_most_one(T vars) {
        if(vars.begin() == vars.end()) return;
        int last = *vars.begin(), cur = 0;
        for(int const&e:vars){
            if(e == last) continue;
            if(cur == 0) cur = e;
            else {
                add_or(-cur, -e);
                int new_cur = add_variable();
                cur = add_implication(cur, new_cur);
                add_implication(e, new_cur);
                cur = new_cur;
            }
        }
        if(cur != 0) add_or(-cur, -last);
    }
}

```

```

    }
    bool solve() {
        val.assign(2*n, 0); valid.assign(1, 0);
        for(int i=0; i<val.size(); i+=2) {
            if(!valid[abs(val[i])]) {
                valid.push_back(1);
                if(!dfs(i)) {
                    valid.back()=0;
                    valid.push_back(1);
                    if(!dfs(i+1)) return false;
                }
            }
        }
        return true;
    }
};

```

7.2 Merge Insertion

```

// Sorting in  $O(n^2)$  time with near-optimal number of
// comparisons
// Number of comparisons used is:  $n \lg n - 1.415 n$ 
// The lower bound is:  $\lg(n!) = n \lg n - 1.443 n$ 
// Binary search insertion sort would need:  $n \log n - n$ 
struct Merge_Insertion_Sort{
    template<typename F>
    static void apply_permutation(vector<int> const&p, F
        get){
        const int n = p.size();
        vector<int> q(n);
        for(int i=0; i<n; ++i) q[p[i]] = i;
        for(int i=0; i<n; ++i){
            while(q[i] != i){
                swap(get(i), get(q[i]));
                swap(q[i], q[q[i]]);
            }
        }
    }
    // ret.first is the sorted vector ret.second[i] is the
    // index of the i-th smallest element in the original
    // vector
    // i.e. ret.second is the permutation that was applied
    // to sort
    template<typename T, typename F>
    static pair<vector<T>, vector<int>> sort(vector<T> v,
        F comp){
        const int n = v.size();
        if(n <= 1) return {move(v), {{0}}};
        vector<int> preperm(n);
        iota(preperm.begin(), preperm.end(), 0);
        const int M = n-n/2;
        for(int i=0; i<n/2; ++i){
            if(comp(v[M+i], v[i])){
                swap(v[M+i], v[i]);
                swap(preperm[M+i], preperm[i]);
            }
        }
        auto ret=sort(vector<T>(v.begin(), v.begin()+n/2),
            comp);
        apply_permutation(ret.second, [&preperm, M](int const&
            i)->int&{return preperm[M+i];});
    }
};

```

```

    apply_permutation(ret.second, [&preperm](int const&i)
        ->int&{return preperm[i];});
    apply_permutation(ret.second, [&v, M](int const&i)->T
        &{return v[M+i];});
    iota(ret.second.begin(), ret.second.end(), 0);
    // insert one element without comparisons
    ret.first.push_back(v.back());
    ret.second.push_back(n-1);
    // now insert the rest in blocks that optimize the
    // binary search sizes
    for(int it=1, r=n-1, s=2; r>n/2; ++it, r-=s, s=(1<<it)
        -s){
        for(int i=r-s; i<r; ++i){
            if(i>=n/2){
                int a = find(ret.second.begin(), ret.second.
                    end(), i-M) - ret.second.begin();
                int b = ret.first.size();
                if(a==b) {
                    assert(i==M-1);
                    a = -1;
                }
                while(a+1 < b){
                    const int m = a+(b-a)/2;
                    if(comp(ret.first[m], v[i])) a = m;
                    else b = m;
                }
                ret.first.insert(ret.first.begin()+b, v[i]);
                ret.second.insert(ret.second.begin()+b, i);
            }
        }
    }
    // compose permutations
    apply_permutation(ret.second, [&preperm](int const&i)
        ->int&{return preperm[i];});
    ret.second.swap(preperm);
    return ret;
}

template<typename T>
static pair<vector<T>, vector<int>> sort(vector<T> v)
{
    return sort(move(v), std::less<T>{});
}
};

```

7.3 DP Optimizations

$A[i][j]$: The smallest k that gives optimal answer

Divide and Conquer:

$dp[i][j] = \min(k < j) \{dp[i-1][k] + C[k][j]\}$
 $O(kn^2) \rightarrow O(kn \log(n))$

Conditions:

$A[i][j] \leq A[i][j+1]$ OR
 $C[a][d] + C[b][c] \geq C[a][c] + C[b][d]$ where $a < b < c < d$

Short Description:

$A[i][1] \leq A[i][2] \leq \dots \leq A[i][n]$

Knuth Optimization:

$dp[i][j] = \min(i < k < j) \{dp[i][k] + dp[k][j]\} + C[i][j]$

$O(n^3) \rightarrow O(n^2)$

Conditions:

$A[i, j - 1] \leq A[i, j] \leq A[i + 1, j]$ OR
 $C[a][d] + C[b][c] \geq C[a][c] + C[b][d]$ AND
 $C[b][c] \leq C[a][d]$ where $a \leq b \leq c \leq d$

Short Description:

For $dp[i][j]$, loop k from $A[i][j - 1]$ to $A[i + 1][j]$

7.4 Convex Hull Trick (Dynamic)

```
struct Line {
    long long m, b;
    mutable function<const Line*> succ;
    bool operator<(const Line& rhs) const {
        if (rhs.b != -(1ll<<62)) return m > rhs.m; // < for max
        const Line* s = succ();
        if (!s) return 0;
        return b - s->b > (s->m - m) * rhs.m; // < for max
    }
};

struct HullDynamic : public multiset<Line> {
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y->m == z->m && y->b >= z->b; // <= for max
        }
        auto x = prev(y);
        if (z == end()) return y->m == x->m && y->b >= x->b;
        // <= for max
        return (x->b - y->b) * 1.0 * (z->m - y->m) >= (y->b - z->b) * 1.0 * (y->m - x->m);
    }

    void insert_line(long long m, long long b) {
        auto y = insert({ m, b });
        y->succ = [=] { return next(y) == end() ? 0 : *next(y); };
        if (bad(y)) { erase(y); return; }
        while (next(y) != end() && bad(next(y))) erase(next(y));
        while (y != begin() && bad(prev(y))) erase(prev(y));
    }

    long long eval(long long x) {
        auto l = *lower_bound((Line){ x, -(1ll<<62) });
        return l.m * x + l.b;
    }
};
```

7.5 Convex Hull Trick (Static)

```
struct ConvexHullTrick {
    typedef long long LL;
    vector<LL> M;
    vector<LL> B;
    vector<double> left;
    ConvexHullTrick() {}
    bool bad(LL m1, LL b1, LL m2, LL b2, LL m3, LL b3) {
        // Careful, this may overflow
        return (b3 - b1) * (m1 - m2) < (b2 - b1) * (m1 - m3);
    }
    // Add a new line to the structure, y = mx + b.
    // Lines must be added in decreasing order of slope.
```

```
void add(LL m, LL b) {
    while (M.size() >= 2 && bad(M[M.size()-2], B[B.size()-2], M.back(), B.back(), m, b)) {
        M.pop_back(); B.pop_back(); left.pop_back();
    }
    if (M.size() && M.back() == m) {
        if (B.back() > b) {
            M.pop_back(); B.pop_back(); left.pop_back();
        } else {
            return;
        }
    }
    if (M.size() == 0) {
        left.push_back(-numeric_limits<double>::infinity());
    }
    else {
        left.push_back((double) (b - B.back()) / (M.back() - m));
    }
    M.push_back(m);
    B.push_back(b);
}

// Get the minimum value of mx + b among all lines in the structure.
// There must be at least one line.
LL query(LL x) {
    int i = upper_bound(left.begin(), left.end(), x) - left.begin();
    return M[i-1]*x + B[i-1];
};
```

7.6 BigInt library

```
struct bignum {
    typedef unsigned int uint;
    vector<uint> digits;
    static const uint RADIX = 1000000000;
    bignum(): digits(1, 0) {}
    bignum(const bignum& x): digits(x.digits) {}
    bignum(unsigned long long x) { *this = x; }
    bignum(const char* x) { *this = x; }
    bignum(const string& s) { *this = s; }
    bignum& operator=(const bignum& y) {
        digits = y.digits; return *this;
    }
    bignum& operator=(unsigned long long x) {
        digits.assign(1, x % RADIX);
        if (x >= RADIX)
            digits.push_back(x / RADIX);
        return *this;
    }
    bignum& operator=(const char* s) {
        int slen = strlen(s), i, l;
        digits.resize((slen + 8) / 9);
        for (l = 0; slen > 0; l++, slen -= 9) {
            digits[l] = 0;
            for (i = slen > 9 ? slen - 9 : 0; i < slen; i++)
                digits[l] = 10 * digits[l] + s[i] - '0';
        }
        while (digits.size() > 1 && !digits.back()) digits.pop_back();
    }
};
```

```

    return *this;
}
bignum& operator=(const string& s)
{ return *this = s.c_str(); }
void add(const bignum& x) {
    int l = max(digits.size(), x.digits.size());
    digits.resize(l+1);
    for (int d=0, carry=0; d<=l; d++) {
        uint sum=carry;
        if (d<digits.size()) sum+=digits[d];
        if (d<x.digits.size()) sum+=x.digits[d];
        digits[d]=sum;
        if (digits[d]>=RADIX)
            digits[d]-=RADIX, carry=1;
        else
            carry=0;
    }
    if (!digits.back()) digits.pop_back();
}
void sub(const bignum& x) {
    // if ((*this)<x) throw; //negative numbers not yet
    // supported
    for (int d=0, borrow=0; d<digits.size(); d++) {
        digits[d]-=borrow;
        if (d<x.digits.size()) digits[d]-=x.digits[d];
        if (digits[d]>>31) { digits[d]+=RADIX; borrow=1; }
        else borrow=0;
    }
    while (digits.size() > 1 && !digits.back()) digits.
        pop_back();
}
void mult(const bignum& x) {
    vector<uint> res(digits.size() + x.digits.size());
    unsigned long long y,z;
    for (int i=0; i<digits.size(); i++) {
        for (int j=0; j<x.digits.size(); j++) {
            unsigned long long y=digits[i]; y*=x.digits[j];
            unsigned long long z=y/RADIX;
            res[i+j+1]+=z; res[i+j]+=y-RADIX*z; //mod is
            // slow
            if (res[i+j] >= RADIX) { res[i+j] -= RADIX; res[
                i+j+1]++; }
            for (int k = i+j+1; res[k] >= RADIX; res[k] -=
                RADIX, res[+k]++);
        }
    }
    digits = res;
    while (digits.size() > 1 && !digits.back()) digits.
        pop_back();
}
// returns the remainder
bignum div(const bignum& x) {
    bignum dividend(*this);
    bignum divisor(x);
    fill(digits.begin(), digits.end(), 0);
    // shift divisor up
    int pwr = dividend.digits.size() - divisor.digits.
        size();
    if (pwr > 0) {
        divisor.digits.insert(divisor.digits.begin(), pwr,

```

```

        0);
    }
    while (pwr >= 0) {
        if (dividend.digits.size() > divisor.digits.size()
        ) {
            unsigned long long q = dividend.digits.back();
            q *= RADIX; q += dividend.digits[dividend.digits
                .size()-2];
            q /= 1+divisor.digits.back();
            dividend -= divisor*q; digits[pwr] = q;
            if (dividend >= divisor) { digits[pwr]++;
                dividend -= divisor; }
            assert(dividend.digits.size() <= divisor.digits.
                size()); continue;
        }
        while (dividend.digits.size() == divisor.digits.
            size()) {
            uint q = dividend.digits.back() / (1+divisor.
                digits.back());
            if (q == 0) break;
            digits[pwr] += q; dividend -= divisor*q;
        }
        if (dividend >= divisor) { dividend -= divisor;
            digits[pwr]++; }
        pwr--; divisor.digits.erase(divisor.digits.begin()
            );
    }
    while (digits.size() > 1 && !digits.back()) digits.
        pop_back();
    return dividend;
}
string to_string() const {
    ostringstream oss;
    oss << digits.back();
    for (int i = digits.size() - 2; i >= 0; i--) {
        oss << setfill('0') << setw(9) << digits[i];
    }
    return oss.str();
}
bignum operator+(const bignum& y) const
{ bignum res(*this); res.add(y); return res; }
bignum operator-(const bignum& y) const
{ bignum res(*this); res.sub(y); return res; }
bignum operator*(const bignum& y) const
{ bignum res(*this); res.mult(y); return res; }
bignum operator/(const bignum& y) const
{ bignum res(*this); res.div(y); return res; }
bignum operator%(const bignum& y) const
{ bignum res(*this); return res.div(y); }
bignum& operator+=(const bignum& y)
{ add(y); return *this; }
bignum& operator-=(const bignum& y)
{ sub(y); return *this; }
bignum& operator*=(const bignum& y)
{ mult(y); return *this; }
bignum& operator/=(const bignum& y)
{ div(y); return *this; }
bignum& operator%=(const bignum& y)
{ *this = div(y); }
bool operator==(const bignum& y)

```

```

    {return digits == y.digits;}
    bool operator<(const bignum& y) const {
        if (digits.size() < y.digits.size()) return true;
        if (digits.size() > y.digits.size()) return false;
        for (int i = digits.size()-1; i >= 0; i--)
            if (digits[i] < y.digits[i])
                return true;
            else if (digits[i] > y.digits[i])
                return false;
            return false;
    }
    bool operator>(const bignum& y) const
    {return y<*this;}
    bool operator<=(const bignum& y) const
    {return !(y<*this);}
    bool operator>=(const bignum& y) const
    {return !(*this<y);}
};

```

7.7 Manachers algorithm

```

// Ex: "opposes" -> [0,1,0,1,4,1,0,1,0,1,0,3,0,1,0]
vector<int> fastLongestPalindromes(string str) {
    int i=0,j,d,s,e,lLen,palLen=0;
    vector<int> res;
    while (i < str.length()) {
        if (i > palLen && str[i-palLen-1] == str[i]) {
            palLen += 2; i++; continue;
        }
        res.push_back(palLen);
        s = res.size()-2;
        e = s-palLen;
        bool b = true;
        for (j=s; j>e; j--) {
            d = j-e-1;
            if (res[j] == d) { palLen = d; b = false; break; }
            res.push_back(min(d, res[j]));
        }
        if (b) { palLen = 1; i++; }
    }
    res.push_back(palLen);
    lLen = res.size();
    s = lLen-2;
    e = s-(2*str.length()+1-lLen);
    for (i=s; i>e; i--) { d = i-e-1; res.push_back(min(d,
        res[i])); }
    return res;
}

```

7.8 Dates

```

// Months are expressed as integers from 1 to 12, Days
// are expressed as integers from 1 to 31, and Years are
// expressed as 4-digit integers.
string dayOfWeek[] = {"Mon", "Tue", "Wed", "Thu", "Fri",
    "Sat", "Sun"};

//converts Gregorian date to integer(Julian day number)
int dateToInt (int m, int d, int y){
    return
        1461 * (y + 4800 + (m - 14) / 12) / 4 +

```

```

        367 * (m - 2 - (m - 14) / 12 * 12) / 12 -
        3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 +
        d - 32075;
}

```

// converts integer (Julian day number) to Gregorian date: month/day/year

```

void intToDate (int jd, int &m, int &d, int &y){
    int x, n, i, j;
    x = jd + 68569;
    n = 4 * x / 146097;
    x -= (146097 * n + 3) / 4;
    i = (4000 * (x + 1)) / 1461001;
    x -= 1461 * i / 4 - 31;
    j = 80 * x / 2447;
    d = x - 2447 * j / 80;
    x = j / 11;
    m = j + 2 - 12 * x;
    y = 100 * (n - 49) + i + x;
}

```

// converts integer (Julian day number) to day of week

```

string intToDay (int jd){
    return dayOfWeek[jd % 7];
}

```

7.9 Bitset (Text)

Remember `_Find_first()` and `_Find_next()` exist, and run in $O(N/W)$, where W is word size of machine.

7.10 Template

```

g++ -std=c++17 -DLOCAL -O2 -Wall -Wshadow -Wextra -
    pedantic -Wfloat-equal -Wlogical-op

#pragma comment(linker, "/stack:200000000")
#pragma GCC optimize("Ofast")
#pragma GCC optimize("unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,abm,
    mmx,avx,tune=native") // codeforces
//#pragma GCC target("avx,avx2,fma")
//#pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,
    abm,mmx,tune=native") // yandex

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <bits/stdc++.h>

using namespace __gnu_pbds;
using namespace std;

typedef long double ld;
typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;

mt19937 rng(std::chrono::duration_cast<std::chrono::
    nanoseconds>(chrono::high_resolution_clock::now() -
    time_since_epoch()).count());

template<typename has_less>
using ordered_set =
    tree<has_less,

```

```

    null_type,
    less<has_less>,
    rb_tree_tag,
    tree_order_statistics_node_update>;

//insert using pref_trie.insert
//get range for prefix using pref_trie.prefix_range
//use iterator from range.first until != range.second
typedef
trie<string,
    null_type,
    trie_string_access_traits<>,
    pat_trie_tag,
    trie_prefix_search_node_update>
    pref_trie;

struct chash {
    int operator()(int x) const { return x ^ RANDOM; }
};
gp_hash_table<key, int, chash> table;

int main() {}

```

7.11 Numerical Integration

```

// different schemes for numerical integration
// approximatively ordered by accuracy
// do NOT use integer types for integration range!
struct Integration_Midpoint{
    template<typename Func, typename S>
    static typename result_of<Func(S)>::type
        integrate_step(Func f, S l, S r){
        S m = (l+r)/2;
        return f(m) * (r-l);
    }
};

struct Integration_Simpson{
    template<typename Func, typename S>
    static typename result_of<Func(S)>::type
        integrate_step(Func f, S l, S r){
        S m = (l+r)/2;
        return (f(l) + 4*f(m) + f(r))/6 * (r-l);
    }
};

struct Integration_Gauss_2{
    static constexpr long double A = 1.01/sqrt(3)/2, x1
        =0.51-A, x2 = 0.51+A;
    template<typename Func, typename S>
    static typename result_of<Func(S)>::type
        integrate_step(Func f, S l, S r){
        return (f(l*x1 + r*x2) + f(l*x2+r*x1))/2 * (r-l);
    }
};

struct Integration_NCotes_Open_4{
    template<typename Func, typename S>
    static typename result_of<Func(S)>::type
        integrate_step(Func f, S l, S r){
        S h = (r-l)/5;
        return (11*f(l+h) + f(l+2*h) + f(r-2*h) + 11*f(r-h))
            /24 * (r-l);
    }
};

```

```

struct Integration_Gauss_3{
    static constexpr long double A = sqrt(3.01/5.01)/2,
        x1=0.5-A, x2 = 0.5+A;
    template<typename Func, typename S>
    static typename result_of<Func(S)>::type
        integrate_step(Func f, S l, S r){
        return (5*f(l*x1 + r*x2) + 8*f((l+r)/2) + 5*f(l*x2+r
            *x1))/18 * (r-l);
    }
};

template<typename Integration_Method>
struct Integrator_Fixedstep{
    template<typename Func, typename S>
    static typename result_of<Func(S)>::type integrate(
        Func f, S const l, S const r, size_t const steps){
        assert(steps>0);
        typename result_of<Func(S)>::type ret(0);
        S cur_l = l, cur_r;
        for(size_t i=0; i<steps; ++i){
            cur_r = (l*(steps-i-1) + r*(i+1))/steps;
            ret+=Integration_Method::integrate_step(f, cur_l,
                cur_r);
            cur_l = cur_r;
        }
        return ret;
    }
};

template<typename Integration_Method>
class Integrator_Adaptive{
private:
    template<size_t depth_limit, typename Func, typename S>
    static typename result_of<Func(S)>::type integrate(
        Func f, S const l, S const r, typename result_of<
        Func(S)>::type const val, typename result_of<Func(S)
        >::type const eps, const size_t depth){
        if(depth>=depth_limit){
            return val;
        }
        S const m = (l+r)/2;
        typename result_of<Func(S)>::type val_l =
            Integration_Method::integrate_step(f, l, m);
        typename result_of<Func(S)>::type val_r =
            Integration_Method::integrate_step(f, m, r);
        typename result_of<Func(S)>::type error = abs(val -
            val_l - val_r);
        if(error < eps){
            return val_l + val_r;
        }
        return integrate<depth_limit>(f, l, m, val_l, eps/2,
            depth+1)
            + integrate<depth_limit>(f, m, r, val_r, eps/2,
                depth+1);
    }
public:
    template<size_t depth_limit, typename Func, typename S>
    static typename result_of<Func(S)>::type integrate(
        Func f, S const l, S const r, typename result_of<
        Func(S)>::type const eps){
        return integrate<depth_limit>(f, l, r,

```

```
Integration_Method::integrate_step(f, l, r), eps, 0);  
}
```
