

# Contents

## 1 Combinatorial optimization

|     |                      |   |
|-----|----------------------|---|
| 1.1 | Dinic's              | 1 |
| 1.2 | Min-cost max-flow    | 2 |
| 1.3 | Edmonds Max Matching | 3 |
| 1.4 | Global min-cut       | 4 |

## 2 Geometry

|     |                             |   |
|-----|-----------------------------|---|
| 2.1 | Convex hull                 | 5 |
| 2.2 | Miscellaneous geometry      | 5 |
| 2.3 | 3D geometry                 | 7 |
| 2.4 | Slow Delaunay triangulation | 7 |

## 3 Numerical algorithms

|     |  |    |
|-----|--|----|
| 3.1 | Number theory (modular, Chinese remainder, linear Diophantine) | 8  |
| 3.2 | Systems of linear equations, matrix inverse, determinant       | 9  |
| 3.3 | Reduced row echelon form, matrix rank                          | 10 |
| 3.4 | Simplex algorithm  | 11 |
| 3.5 | Fast Fourier transform   | 12 |
| 3.6 | BigInt library   | 12 |

## 4 Graph algorithms

|     |  |    |
|-----|--|----|
| 4.1 | Bellman-Ford shortest paths with negative edge weights | 15 |
| 4.2 | Eulerian path  | 15 |
| 4.3 | Minimum spanning trees                                 | 15 |
| 4.4 | Centroid decomposition                                 | 16 |
| 4.5 | Heavy-Light decomposition                              | 17 |

## 5 Data structures

|     |              |    |
|-----|--------------|----|
| 5.1 | Suffix array | 18 |
| 5.2 | KD-tree      | 19 |
| 5.3 | Splay tree   | 20 |

## 6 Miscellaneous

|     |                                |    |
|-----|--------------------------------|----|
| 6.1 | Miller-Rabin Primality Test    | 22 |
| 6.2 | Pollard-Rho factorization      | 22 |
| 6.3 | Manachers algorithm            | 23 |
| 6.4 | Convex Hull Trick              | 23 |
| 6.5 | Dynamic Programming(DnC)       | 24 |
| 6.6 | Longest increasing subsequence | 24 |
| 6.7 | Dates                          | 24 |
| 6.8 | Knuth-Morris-Pratt             | 25 |
| 6.9 | 2-SAT                          | 25 |

# 1 Combinatorial optimization

## 1.1 Dinic's

|   |  |   |
|---|--|---|
| 1 |  | 1 |
| 2 | <code>struct Dinic {</code>  | 2 |
| 3 | <code>  struct Edge {</code>   | 3 |
| 4 | <code>    int u, v;</code>   | 4 |
|   | <code>    long long cap, flow;</code>  |   |
|   | <code>    Edge() {}</code>   |   |
|   | <code>    Edge(int u, int v, long long cap): u(u), v(v), cap(cap), flow(0) {}</code> | 5 |
|   | <code>  };</code>  | 5 |
|   | <code>  int N;</code>  | 5 |
|   | <code>  vector&lt;Edge&gt; E;</code>   | 7 |
|   | <code>  vector&lt;vector&lt;int&gt;&gt; g;</code>                                    | 7 |
|   | <code>  vector&lt;int&gt; d, pt;</code>  |   |
|   | <code>Dinic(int N): N(N), E(0), g(N), d(N), pt(N) {}</code>                          | 8 |
|   | <code>void AddEdge(int u, int v, long long cap) {</code>                             |   |
|   | <code>  if (u != v) {</code>   |   |
|   | <code>    E.emplace_back(Edge(u, v, cap));</code>                                    |   |
|   | <code>    g[u].emplace_back(E.size() - 1);</code>                                    |   |
|   | <code>    E.emplace_back(Edge(v, u, 0));</code>                                      |   |
|   | <code>    g[v].emplace_back(E.size() - 1);</code>                                    |   |
|   | <code>  }</code>   |   |
|   | <code>}</code>   |   |
|   | <code>bool BFS(int S, int T) {</code>  |   |
|   | <code>  queue&lt;int&gt; q({S});</code>  |   |
|   | <code>  fill(d.begin(), d.end(), N + 1);</code>                                      |   |
|   | <code>  d[S] = 0;</code>   |   |
|   | <code>  while(!q.empty()) {</code>   |   |
|   | <code>    int u = q.front(); q.pop();</code>   |   |
|   | <code>    if (u == T) break;</code>  |   |
|   | <code>    for (int k: g[u]) {</code>   |   |
|   | <code>      Edge &amp;e = E[k];</code>   |   |
|   | <code>      if (e.flow &lt; e.cap &amp;&amp; d[e.v] &gt; d[e.u] + 1) {</code>        |   |
|   | <code>        d[e.v] = d[e.u] + 1;</code>  |   |
|   | <code>        q.emplace(e.v);</code>   |   |
|   | <code>      }</code>   |   |
|   | <code>    }</code>   |   |
|   | <code>  return d[T] != N + 1;</code>   |   |
|   | <code>}</code>   |   |
|   | <code>long long DFS(int u, int T, long long flow = -1) {</code>                      |   |
|   | <code>  if (u == T    flow == 0) return flow;</code>                                 |   |
|   | <code>  for (int &amp;i = pt[u]; i &lt; g[u].size(); ++i) {</code>                   |   |
|   | <code>    Edge &amp;e = E[g[u][i]];</code>   |   |
|   | <code>    Edge &amp;oe = E[g[u][i]^1];</code>  |   |
|   | <code>    if (d[e.v] == d[e.u] + 1) {</code>   |   |
|   | <code>      long long amt = e.cap - e.flow;</code>                                   |   |
|   | <code>      if (flow != -1 &amp;&amp; amt &gt; flow) amt = flow;</code>              |   |
|   | <code>      if (long long pushed = DFS(e.v, T, amt)) {</code>                        |   |
|   | <code>        e.flow += pushed;</code>   |   |
|   | <code>        oe.flow -= pushed;</code>  |   |
|   | <code>        return pushed;</code>  |   |
|   | <code>      }</code>   |   |
|   | <code>    }</code>   |   |
|   | <code>  }</code>   |   |
|   | <code>}</code>   |   |

```

    return 0;
}
long long MaxFlow(int S, int T) {
    long long total = 0;
    while (BFS(S, T)) {
        fill(pt.begin(), pt.end(), 0);
        while (long long flow = DFS(S, T))
            total += flow;
    }
    return total;
};

```

## 1.2 Min-cost max-flow

```

// Implementation of min cost max flow algorithm using
// adjacency
// matrix (Edmonds and Karp 1972). This implementation
// keeps track of
// forward and reverse edges separately (so you can set
// cap[i][j] !=
// cap[j][i]). For a regular max flow, set all edge
// costs to 0.
//
// Running time,  $O(|V|^2)$  cost per augmentation
// max flow:  $O(|V|^3)$  augmentations
// min cost max flow:  $O(|V|^4 * \text{MAX\_EDGE\_COST})$ 
// augmentations
//
// INPUT:
// - graph, constructed using AddEdge()
// - source
// - sink
//
// OUTPUT:
// - (maximum flow value, minimum cost value)
// - To obtain the actual flow, look at positive
// values only.

#include <cmath>
#include <vector>
#include <iostream>
using namespace std;
typedef vector<int> VI;
typedef vector<VI> VVI;
typedef long long L;
typedef vector<L> VL;
typedef vector<VL> VVL;
typedef pair<int, int> PII;
typedef vector<PII> VPII;
const L INF = numeric_limits<L>::max() / 4;
struct MinCostMaxFlow {
    int N;
    VVL cap, flow, cost;
    VI found;
    VL dist, pi, width;
    VPII dad;

```

```

MinCostMaxFlow(int N) :
    N(N), cap(N, VL(N)), flow(N, VL(N)), cost(N, VL(N)),
    found(N), dist(N), pi(N), width(N), dad(N) {}
void AddEdge(int from, int to, L cap, L cost) {
    this->cap[from][to] = cap;
    this->cost[from][to] = cost;
}
void Relax(int s, int k, L cap, L cost, int dir) {
    L val = dist[s] + pi[s] - pi[k] + cost;
    if (cap && val < dist[k]) {
        dist[k] = val;
        dad[k] = make_pair(s, dir);
        width[k] = min(cap, width[s]);
    }
}
L Dijkstra(int s, int t) {
    fill(found.begin(), found.end(), false);
    fill(dist.begin(), dist.end(), INF);
    fill(width.begin(), width.end(), 0);
    dist[s] = 0;
    width[s] = INF;
    while (s != -1) {
        int best = -1;
        found[s] = true;
        for (int k = 0; k < N; k++) {
            if (found[k]) continue;
            Relax(s, k, cap[s][k] - flow[s][k], cost[s][k],
                1);
            Relax(s, k, flow[k][s], -cost[k][s], -1);
            if (best == -1 || dist[k] < dist[best]) best = k;
        }
        s = best;
    }
    for (int k = 0; k < N; k++)
        pi[k] = min(pi[k] + dist[k], INF);
    return width[t];
}
pair<L, L> GetMaxFlow(int s, int t) {
    L totflow = 0, totcost = 0;
    while (L amt = Dijkstra(s, t)) {
        totflow += amt;
        for (int x = t; x != s; x = dad[x].first) {
            if (dad[x].second == 1) {
                flow[dad[x].first][x] += amt;
                totcost += amt * cost[dad[x].first][x];
            } else {
                flow[x][dad[x].first] -= amt;
                totcost -= amt * cost[x][dad[x].first];
            }
        }
    }
    return make_pair(totflow, totcost);
};
// BEGIN CUT
// The following code solves UVA problem #10594: Data

```

```

Flow
int main() {
    int N, M;
    while (scanf("%d%d", &N, &M) == 2) {
        VVL v(M, VL(3));
        for (int i = 0; i < M; i++)
            scanf("%Ld%Ld%Ld", &v[i][0], &v[i][1], &v[i][2]);
        L D, K;
        scanf("%Ld%Ld", &D, &K);
        MinCostMaxFlow mcmf(N+1);
        for (int i = 0; i < M; i++) {
            mcmf.AddEdge(int(v[i][0]), int(v[i][1]), K, v[i][2]);
            mcmf.AddEdge(int(v[i][1]), int(v[i][0]), K, v[i][2]);
        }
        mcmf.AddEdge(0, 1, D, 0);
        pair<L, L> res = mcmf.GetMaxFlow(0, N);
        if (res.first == D) {
            printf("%Ld\n", res.second);
        } else {
            printf("Impossible.\n");
        }
    }
    return 0;
}
// END CUT

```

## 1.3 Edmonds Max Matching

```

/*
Input:
V->number of vertices
E->number of edges
pair of vertices as edges (vertices are 1..V)
Output:
output of edmonds() is the maximum matching
match[i] is matched pair of i (-1 if there isn't a
      matched pair)
*/
#include <bits/stdc++.h>
using namespace std;
const int M=505;
struct struct_edge{int v;struct_edge* n;};
typedef struct_edge* edge;
struct_edge pool[M*M*2];
edge top=pool,adj[M];
int V,E,match[M],qh,qt,q[M],father[M],base[M];
bool inq[M],inb[M],ed[M][M];
void add_edge(int u,int v)
{
    top->v=v,top->n=adj[u],adj[u]=top++;
    top->v=u,top->n=adj[v],adj[v]=top++;
}
int LCA(int root,int u,int v)

```

```

{
    static bool inp[M];
    memset(inp,0,sizeof(inp));
    while(1)
    {
        inp[u=base[u]]=true;
        if (u==root) break;
        u=father[match[u]];
    }
    while(1)
    {
        if (inp[v=base[v]]) return v;
        else v=father[match[v]];
    }
}
void mark_blossom(int lca,int u)
{
    while (base[u]!=lca)
    {
        int v=match[u];
        inb[base[u]]=inb[base[v]]=true;
        u=father[v];
        if (base[u]!=lca) father[u]=v;
    }
}
void blossom_contraction(int s,int u,int v)
{
    int lca=LCA(s,u,v);
    memset(inb,0,sizeof(inb));
    mark_blossom(lca,u);
    mark_blossom(lca,v);
    if (base[u]!=lca)
        father[u]=v;
    if (base[v]!=lca)
        father[v]=u;
    for (int u=0;u<V;u++)
        if (inb[base[u]])
        {
            base[u]=lca;
            if (!inq[u])
                inq[q[++qt]=u]=true;
        }
}
int find_augmenting_path(int s)
{
    memset(inq,0,sizeof(inq));
    memset(father,-1,sizeof(father));
    for (int i=0;i<V;i++) base[i]=i;
    inq[q[qh=qt=0]=s]=true;
    while (qh<=qt)
    {
        int u=q[qh++];
        for (edge e=adj[u];e;e=e->n)
        {
            int v=e->v;
            if (base[u]!=base[v]&&match[u]!=v)
            {
                if ((v==s)|| (match[v]==-1 && father[match[v]]!=-1))
                    blossom_contraction(s,u,v);
                else if (father[v]==-1)
                {

```

```

        father[v]=u;
        if (match[v]==-1)
            return v;
        else if (!inq[match[v]])
            inq[q[+qt]=match[v]]=true;
        }
    }
    return -1;
}
int augment_path(int s,int t)
{
    int u=t,v,w;
    while (u!=-1)
    {
        v=father[u];
        w=match[v];
        match[v]=u;
        match[u]=v;
        u=w;
    }
    return t!=-1;
}
int edmonds()
{
    int matchc=0;
    memset(match,-1,sizeof(match));
    for (int u=0;u<V;u++)
        if (match[u]==-1)
            matchc+=augment_path(u,find_augmenting_path(u));
    return matchc;
}
int main()
{
    int u,v;
    cin>>V>>E;
    while(E--)
    {
        cin>>u>>v;
        if (!ed[u-1][v-1])
        {
            add_edge(u-1,v-1);
            ed[u-1][v-1]=ed[v-1][u-1]=true;
        }
    }
    cout<<edmonds()<<endl;
    for (int i=0;i<V;i++)
        if (i<match[i])
            cout<<i+1<<" "<<match[i]+1<<endl;
}

```

## 1.4 Global min-cut

```

// Adjacency matrix implementation of Stoer-Wagner min
// cut algorithm.
//
// Running time:
//  $O(V^3)$ 
//
// INPUT:

```

```

// - graph, constructed using AddEdge()
//
// OUTPUT:
// - (min cut value, nodes in half of min cut)
#include <cmath>
#include <vector>
#include <iostream>
using namespace std;
typedef vector<int> VI;
typedef vector<VI> VVI;
const int INF = 1000000000;
pair<int, VI> GetMinCut(VVI &weights) {
    int N = weights.size();
    VI used(N), cut, best_cut;
    int best_weight = -1;
    for (int phase = N-1; phase >= 0; phase--) {
        VI w = weights[0];
        VI added = used;
        int prev, last = 0;
        for (int i = 0; i < phase; i++) {
            prev = last;
            last = -1;
            for (int j = 1; j < N; j++)
                if (!added[j] && (last == -1 || w[j] > w[last]))
                    last = j;
            if (i == phase-1) {
                for (int j = 0; j < N; j++) weights[prev][j] +=
                    weights[last][j];
                for (int j = 0; j < N; j++) weights[j][prev] =
                    weights[j][last];
                used[last] = true;
                cut.push_back(last);
                if (best_weight == -1 || w[last] < best_weight)
                {
                    best_cut = cut;
                    best_weight = w[last];
                }
            }
            else {
                for (int j = 0; j < N; j++)
                    w[j] += weights[last][j];
                added[last] = true;
            }
        }
    }
    return make_pair(best_weight, best_cut);
}
// BEGIN CUT
// The following code solves UVA problem #10989: Bomb,
// Divide and Conquer
int main() {
    int N;
    cin >> N;
    for (int i = 0; i < N; i++) {
        int n, m;
        cin >> n >> m;
        VVI weights(n, VI(n));
    }
}

```

```

    for (int j = 0; j < m; j++) {
        int a, b, c;
        cin >> a >> b >> c;
        weights[a-1][b-1] = weights[b-1][a-1] = c;
    }
    pair<int, VI> res = GetMinCut(weights);
    cout << "Case #" << i+1 << ": " << res.first << endl;
}
// END CUT

```

## 2 Geometry

### 2.1 Convex hull

```

typedef pair<long long, long long> PT;
long double dist (PT a, PT b) {
    return sqrt(pow(a.first-b.first,2)+pow(a.second-b.
        second,2));
}

long long cross (PT o, PT a, PT b) {
    PT OA = {a.first-o.first, a.second-o.second};
    PT OB = {b.first-o.first, b.second-o.second};
    return OA.first*OB.second - OA.second*OB.first;
}

vector<PT> convexhull () {
    vector<PT> hull;
    sort(a, a+n, [] (PT i, PT j) {
        if (i.second != j.second)
            return i.second < j.second;
        return i.first < j.first;
    });
    for (int i=0; i<n; ++i) {
        while (hull.size() > 1 && cross(hull[hull.size()-2],
            hull.back(), a[i]) <= 0)
            hull.pop_back();
        hull.push_back(a[i]);
    }
    for (int i=n-1, siz = hull.size(); i--;) {
        while (hull.size() > siz && cross(hull[hull.size()-2],
            hull.back(), a[i]) <= 0)
            hull.pop_back();
        hull.push_back(a[i]);
    }
    return hull;
}

```

### 2.2 Miscellaneous geometry

```

double INF = 1e100, EPS = 1e-12;
struct PT {
    double x, y;
    PT() {}
    PT(double x, double y) : x(x), y(y) {}
    PT(const PT &p) : x(p.x), y(p.y) {}
}

```

```

PT operator + (const PT &p) const { return PT(x+p.x,
    y+p.y); }
PT operator - (const PT &p) const { return PT(x-p.x,
    y-p.y); }
PT operator * (double c) const { return PT(x*c,
    y*c); }
PT operator / (double c) const { return PT(x/c,
    y/c); }

double dot (PT p, PT q) { return p.x*q.x+p.y*q.y; }
double dist2 (PT p, PT q) { return dot(p-q, p-q); }
double cross (PT p, PT q) { return p.x*q.y-p.y*q.x; }
ostream &operator<<(ostream &os, const PT &p) {
    os << "(" << p.x << ", " << p.y << ")";
}

// rotate a point CCW or CW around the origin
PT RotateCCW90 (PT p) { return PT(-p.y, p.x); }
PT RotateCW90 (PT p) { return PT(p.y, -p.x); }
PT RotateCCW (PT p, double t) {
    return PT(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos(t));
}

// project point c onto line through a and b
// assuming a != b
PT ProjectPointLine (PT a, PT b, PT c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);
}

// project point c onto line segment through a and b
PT ProjectPointSegment (PT a, PT b, PT c) {
    double r = dot(b-a, b-a);
    if (fabs(r) < EPS) return a;
    r = dot(c-a, b-a)/r;
    if (r < 0) return a;
    if (r > 1) return b;
    return a + (b-a)*r;
}

// compute distance from c to segment between a and b
double DistancePointSegment (PT a, PT b, PT c) {
    return sqrt(dist2(c, ProjectPointSegment(a, b, c)));
}

// compute distance between point (x,y,z) and plane ax+
// by+cz=d
double DistancePointPlane (double x, double y, double z,
    double a, double b, double c,
    double d)
{
    return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);
}

// determine if lines from a to b and c to d are
// parallel or collinear
bool LinesParallel (PT a, PT b, PT c, PT d) {
    return fabs(cross(b-a, c-d)) < EPS;
}

bool LinesCollinear (PT a, PT b, PT c, PT d) {
    return LinesParallel(a, b, c, d)
        && fabs(cross(a-b, a-c)) < EPS
        && fabs(cross(c-d, c-a)) < EPS;
}

```

```

}
// determine if line segment from a to b intersects with
// line segment from c to d
bool SegmentsIntersect(PT a, PT b, PT c, PT d) {
    if (LinesCollinear(a, b, c, d)) {
        if (dist2(a, c) < EPS || dist2(a, d) < EPS ||
            dist2(b, c) < EPS || dist2(b, d) < EPS) return
            true;
        if (dot(c-a, c-b) > 0 && dot(d-a, d-b) > 0 && dot(c-
            b, d-b) > 0)
            return false;
        return true;
    }
    if (cross(d-a, b-a) * cross(c-a, b-a) > 0) return
        false;
    if (cross(a-c, d-c) * cross(b-c, d-c) > 0) return
        false;
    return true;
}

// compute intersection of line passing through a and b
// with line passing through c and d, assuming that
// unique
// intersection exists; for segment intersection, check
// if
// segments intersect first
PT ComputeLineIntersection(PT a, PT b, PT c, PT d) {
    b=b-a; d=c-d; c=c-a;
    assert(dot(b, b) > EPS && dot(d, d) > EPS);
    return a + b*cross(c, d)/cross(b, d);
}

// compute center of circle given three points
PT ComputeCircleCenter(PT a, PT b, PT c) {
    b=(a+b)/2;
    c=(a+c)/2;
    return ComputeLineIntersection(b, b+RotateCW90(a-b), c
        , c+RotateCW90(a-c));
}

// determine if point is in a possibly non-convex
// polygon (by William
// Randolph Franklin); returns 1 for strictly interior
// points, 0 for
// strictly exterior points, and 0 or 1 for the
// remaining points.
// Note that it is possible to convert this into an *
// exact* test using
// integer arithmetic by taking care of the division
// appropriately
// (making sure to deal with signs properly) and then by
// writing exact
// tests for checking point on polygon boundary
bool PointInPolygon(const vector<PT> &p, PT q) {
    bool c = 0;
    for (int i = 0; i < p.size(); i++) {
        int j = (i+1)%p.size();
        if ((p[i].y <= q.y && q.y < p[j].y ||
            p[j].y <= q.y && q.y < p[i].y) &&
            q.x < p[i].x + (p[j].x - p[i].x) * (q.y - p[i].y)
                / (p[j].y - p[i].y))
            c = !c;
    }
}

```

```

}
return c;
}

// determine if point is on the boundary of a polygon
bool PointOnPolygon(const vector<PT> &p, PT q) {
    for (int i = 0; i < p.size(); i++)
        if (dist2(ProjectPointSegment(p[i], p[(i+1)%p.size()
            ], q), q) < EPS)
            return true;
    return false;
}

// compute intersection of line through points a and b
// with
// circle centered at c with radius r > 0
vector<PT> CircleLineIntersection(PT a, PT b, PT c,
    double r) {
    vector<PT> ret;
    b = b-a;
    a = a-c;
    double A = dot(b, b);
    double B = dot(a, b);
    double C = dot(a, a) - r*r;
    double D = B*B - A*C;
    if (D < -EPS) return ret;
    ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
    if (D > EPS)
        ret.push_back(c+a+b*(-B-sqrt(D))/A);
    return ret;
}

// compute intersection of circle centered at a with
// radius r
// with circle centered at b with radius R
vector<PT> CircleCircleIntersection(PT a, PT b, double r
    , double R) {
    vector<PT> ret;
    double d = sqrt(dist2(a, b));
    if (d > r+R || d+min(r, R) < max(r, R)) return ret;
    double x = (d*d-R*R+r*r)/(2*d);
    double y = sqrt(r*r-x*x);
    PT v = (b-a)/d;
    ret.push_back(a+v*x + RotateCCW90(v)*y);
    if (y > 0)
        ret.push_back(a+v*x - RotateCCW90(v)*y);
    return ret;
}

// This code computes the area or centroid of a (
// possibly nonconvex)
// polygon, assuming that the coordinates are listed in
// a clockwise or
// counterclockwise fashion. Note that the centroid is
// often known as
// the "center of gravity" or "center of mass".
double ComputeSignedArea(const vector<PT> &p) {
    double area = 0;
    for(int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        area += p[i].x*p[j].y - p[j].x*p[i].y;
    }
    return area / 2.0;
}

```

```

double ComputeArea(const vector<PT> &p) {
    return fabs(ComputeSignedArea(p));
}

PT ComputeCentroid(const vector<PT> &p) {
    PT c(0,0);
    double scale = 6.0 * ComputeSignedArea(p);
    for (int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*(p[i].x*p[j].y - p[j].x*p[i].y);
    }
    return c / scale;
}

// tests whether or not a given polygon (in CW or CCW
// order) is simple
bool IsSimple(const vector<PT> &p) {
    for (int i = 0; i < p.size(); i++) {
        for (int k = i+1; k < p.size(); k++) {
            int j = (i+1) % p.size();
            int l = (k+1) % p.size();
            if (i == l || j == k) continue;
            if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
                return false;
        }
    }
    return true;
}

```

## 2.3 3D geometry

```

public class Geom3D {
    // distance from point (x, y, z) to plane aX + bY + cZ
    // + d = 0
    public static double ptPlaneDist(double x, double y,
        double z,
        double a, double b, double c, double d) {
        return Math.abs(a*x + b*y + c*z + d) / Math.sqrt(a*a
            + b*b + c*c);
    }

    // distance between parallel planes aX + bY + cZ + d1
    // = 0 and
    // aX + bY + cZ + d2 = 0
    public static double planePlaneDist(double a, double b
        , double c,
        double d1, double d2) {
        return Math.abs(d1 - d2) / Math.sqrt(a*a + b*b + c*c
            );
    }

    // distance from point (px, py, pz) to line (x1, y1,
    // z1)-(x2, y2, z2)
    // (or ray, or segment; in the case of the ray, the
    // endpoint is the
    // first point)
    public static final int LINE = 0;
    public static final int SEGMENT = 1;
    public static final int RAY = 2;
    public static double ptLineDistSq(double x1, double y1
        , double z1,

```

```

        double x2, double y2, double z2, double px, double
        py, double pz,
        int type) {
        double pd2 = (x1-x2)*(x1-x2) + (y1-y2)*(y1-y2) + (z1
            -z2)*(z1-z2);

        double x, y, z;
        if (pd2 == 0) {
            x = x1;
            y = y1;
            z = z1;
        } else {
            double u = ((px-x1)*(x2-x1) + (py-y1)*(y2-y1) + (
                pz-z1)*(z2-z1)) / pd2;
            x = x1 + u * (x2 - x1);
            y = y1 + u * (y2 - y1);
            z = z1 + u * (z2 - z1);
            if (type != LINE && u < 0) {
                x = x1;
                y = y1;
                z = z1;
            }
            if (type == SEGMENT && u > 1.0) {
                x = x2;
                y = y2;
                z = z2;
            }
        }

        return (x-px)*(x-px) + (y-py)*(y-py) + (z-pz)*(z-pz)
            ;
    }

    public static double ptLineDist(double x1, double y1,
        double z1,
        double x2, double y2, double z2, double px, double
        py, double pz,
        int type) {
        return Math.sqrt(ptLineDistSq(x1, y1, z1, x2, y2, z2
            , px, py, pz, type));
    }
}

```

## 2.4 Slow Delaunay triangulation

```

// Slow but simple Delaunay triangulation. Does not
// handle
// degenerate cases (from O'Rourke, Computational
// Geometry in C)
//
// Running time: O(n^4)
//
// INPUT:      x[] = x-coordinates
//             y[] = y-coordinates
//
// OUTPUT:      triples = a vector containing m triples of
//             indices
//             corresponding to triangle
//             vertices
#include<vector>
using namespace std;

```



```

typedef double T;
struct triple {
    int i, j, k;
    triple() {}
    triple(int i, int j, int k) : i(i), j(j), k(k) {}
};

vector<triple> delaunayTriangulation(vector<T>& x,
    vector<T>& y) {
    int n = x.size();
    vector<T> z(n);
    vector<triple> ret;

    for (int i = 0; i < n; i++)
        z[i] = x[i] * x[i] + y[i] * y[i];

    for (int i = 0; i < n-2; i++) {
        for (int j = i+1; j < n; j++) {
            for (int k = i+1; k < n; k++) {
                if (j == k) continue;
                double xn = (y[j]-y[i])*(z[k]-z[i])
                    - (y[k]-y[i])*(z[j]-z[i]);
                double yn = (x[k]-x[i])*(z[j]-z[i])
                    - (x[j]-x[i])*(z[k]-z[i]);
                double zn = (x[j]-x[i])*(y[k]-y[i])
                    - (x[k]-x[i])*(y[j]-y[i]);
                bool flag = zn < 0;
                for (int m = 0; flag && m < n; m++)
                    flag = flag && ((x[m]-x[i])*xn +
                        (y[m]-y[i])*yn +
                        (z[m]-z[i])*zn
                            <= 0);
                if (flag) ret.push_back(triple(i, j,
                    k));
            }
        }
    }
    return ret;
}

int main()
{
    T xs[]={0, 0, 1, 0.9};
    T ys[]={0, 1, 0, 0.9};
    vector<T> x(&xs[0], &xs[4]), y(&ys[0], &ys[4]);
    vector<triple> tri = delaunayTriangulation(x, y);

    //expected: 0 1 3
    //           0 3 2

    int i;
    for(i = 0; i < tri.size(); i++)
        printf("%d %d %d\n", tri[i].i, tri[i].j, tri[i].
            k);
    return 0;
}

```

## 3 Numerical algorithms

### 3.1 Number theory (modular, Chinese remainder, linear Diophantine)

```

// All algorithms described here work on nonnegative
// integers.

// return a % b (positive value)
int mod(int a, int b) {
    return ((a%b) + b) % b;
}

// computes lcm(a,b)
int lcm(int a, int b) {
    return a / __gcd(a, b)*b;
}

// (a^b) mod m via successive squaring
int powermod(int a, int b, int m) {
    return b?powermod(a*a%m,b/2,m)*(b%2?a:1)%m:1;
}

// returns g = gcd(a, b); finds x, y such that d = ax +
// by
int extended_euclid(int a, int b, int &x, int &y) {
    int xx = y = 0;
    int yy = x = 1;
    while (b) {
        int q = a / b;
        int t = b; b = a%b; a = t;
        t = xx; xx = x - q*xx; x = t;
        t = yy; yy = y - q*yy; y = t;
    }
    return a;
}

// finds all solutions to ax = b (mod n)
VI modular_linear_equation_solver(int a, int b, int n) {
    int x, y;
    VI ret;
    int g = extended_euclid(a, n, x, y);
    if (!(b%g)) {
        x = mod(x*(b / g), n);
        for (int i = 0; i < g; i++)
            ret.push_back(mod(x + i*(n / g),
                n));
    }
    return ret;
}

// computes b such that ab = 1 (mod n), returns -1 on
// failure
int mod_inverse(int a, int n) {
    int x, y;
    int g = extended_euclid(a, n, x, y);
    if (g > 1) return -1;
    return mod(x, n);
}

// Chinese remainder theorem (special case): find z such

```



```

    that
    // z % m1 = r1, z % m2 = r2. Here, z is unique modulo M
    // = lcm(m1, m2).
    // Return (z, M). On failure, M = -1.
    PII chinese_remainder_theorem(int m1, int r1, int m2,
    int r2) {
        int s, t;
        int g = extended_euclid(m1, m2, s, t);
        if (r1%g != r2%g) return make_pair(0, -1);
        return make_pair(mod(s*r2*m1 + t*r1*m2, m1*m2) /
        g, m1*m2 / g);
    }

    // Chinese remainder theorem: find z such that
    // z % m[i] = r[i] for all i. Note that the solution is
    // unique modulo M = lcm_i (m[i]). Return (z, M). On
    // failure, M = -1. Note that we do not require the a[i]
    // 's
    // to be relatively prime.
    PII chinese_remainder_theorem(const VI &m, const VI &r)
    {
        PII ret = make_pair(r[0], m[0]);
        for (int i = 1; i < m.size(); i++) {
            ret = chinese_remainder_theorem(ret,
            second, ret.first, m[i], r[i]);
            if (ret.second == -1) break;
        }
        return ret;
    }

    // computes x and y such that ax + by = c
    // returns whether the solution exists
    bool linear_diophantine(int a, int b, int c, int &x, int
    &y) {
        if (!a && !b) {
            if (c) return false;
            x = 0; y = 0;
            return true;
        }
        if (!a) {
            if (c % b) return false;
            x = 0; y = c / b;
            return true;
        }
        if (!b) {
            if (c % a) return false;
            x = c / a; y = 0;
            return true;
        }
        int g = __gcd(a, b);
        if (c % g) return false;
        x = c / g * mod_inverse(a / g, b / g);
        y = (c - a*x) / b;
        return true;
    }

```

### 3.2 Systems of linear equations, matrix inverse, determinant

```

// Uses:
// (1) solving systems of linear equations (AX=B)
// (2) inverting matrices (AX=I)
// (3) computing determinants of square matrices
//
// Running time: O(n^3)
//
// INPUT:      a[][] = an nxn matrix
//             b[][] = an nxm matrix
//
// OUTPUT:     X      = an nxm matrix (stored in b[][])
//             A^{-1} = an nxn matrix (stored in a[][])
//             returns determinant of a[][]

#include <iostream>
#include <vector>
#include <cmath>

using namespace std;

const double EPS = 1e-10;

typedef vector<int> VI;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

T GaussJordan(VVT &a, VVT &b) {
    const int n = a.size();
    const int m = b[0].size();
    VI irow(n), icol(n), ipiv(n);
    T det = 1;

    for (int i = 0; i < n; i++) {
        int pj = -1, pk = -1;
        for (int j = 0; j < n; j++) if (!ipiv[j])
            for (int k = 0; k < n; k++) if (!ipiv[k])
                if (pj == -1 || fabs(a[j][k]) > fabs(a[pj][pk]))
                    { pj = j; pk = k; }
        if (fabs(a[pj][pk]) < EPS) { cerr << "Matrix is
        singular." << endl; exit(0); }
        ipiv[pj]++;
        swap(a[pj], a[pk]);
        swap(b[pj], b[pk]);
        if (pj != pk) det *= -1;
        irow[i] = pj;
        icol[i] = pk;

        T c = 1.0 / a[pk][pk];
        det *= a[pk][pk];
        a[pk][pk] = 1.0;
        for (int p = 0; p < n; p++) a[pk][p] *= c;
        for (int p = 0; p < m; p++) b[pk][p] *= c;
        for (int p = 0; p < n; p++) if (p != pk) {
            c = a[p][pk];
            a[p][pk] = 0;
            for (int q = 0; q < n; q++) a[p][q] -= a[pk][q] *
            c;
            for (int q = 0; q < m; q++) b[p][q] -= b[pk][q] *
            c;
        }
    }

    for (int p = n-1; p >= 0; p--) if (irow[p] != icol[p])
    {

```

```

// Gauss-Jordan elimination with full pivoting.
//

```

```

    for (int k = 0; k < n; k++) swap(a[k][irow[p]], a[k][icol[p]]);
}
return det;
}

int main() {
    const int n = 4;
    const int m = 2;
    double A[n][n] = {
        {1, 2, 3, 4}, {1, 0, 1, 0}, {5, 3, 2, 4}, {6, 1, 4, 6} };
    double B[n][m] = { {1, 2}, {4, 3}, {5, 6}, {8, 7} };
    VVT a(n), b(m);
    for (int i = 0; i < n; i++) {
        a[i] = VT(A[i], A[i] + n);
        b[i] = VT(B[i], B[i] + m);
    }

    double det = GaussJordan(a, b);
    // expected: 60
    cout << "Determinant: " << det << endl;

    // expected: -0.233333 0.166667 0.133333 0.0666667
    //              0.166667 0.166667 0.333333 -0.333333
    //              0.233333 0.833333 -0.133333 -0.0666667
    //              0.05 -0.75 -0.1 0.2
    cout << "Inverse: " << endl;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            cout << a[i][j] << ' ';
        }
        cout << endl;
    }

    // expected: 1.63333 1.3
    //              -0.166667 0.5
    //              2.36667 1.7
    //              -1.85 -1.35
    cout << "Solution: " << endl;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            cout << b[i][j] << ' ';
        }
        cout << endl;
    }
}

```

### 3.3 Reduced row echelon form, matrix rank

```

// Reduced row echelon form via Gauss-Jordan elimination
// with partial pivoting. This can be used for
// computing
// the rank of a matrix.
//
// Running time: O(n^3)
//
// INPUT:      a[][] = an nxm matrix
//
// OUTPUT:     rref[][] = an nxm matrix (stored in a[][])
//              returns rank of a[][]

#include <iostream>
#include <vector>

```

```

#include <cmath>
using namespace std;
const double EPSILON = 1e-10;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

int rref(VVT &a) {
    int n = a.size();
    int m = a[0].size();
    int r = 0;
    for (int c = 0; c < m && r < n; c++) {
        int j = r;
        for (int i = r + 1; i < n; i++)
            if (fabs(a[i][c]) > fabs(a[j][c])) j = i;
        if (fabs(a[j][c]) < EPSILON) continue;
        swap(a[j], a[r]);

        T s = 1.0 / a[r][c];
        for (int j = 0; j < m; j++) a[r][j] *= s;
        for (int i = 0; i < n; i++) if (i != r) {
            T t = a[i][c];
            for (int j = 0; j < m; j++) a[i][j] -= t * a[r][j];
        }
        r++;
    }
    return r;
}

int main() {
    const int n = 5, m = 4;
    double A[n][m] = {
        {16, 2, 3, 13},
        {5, 11, 10, 8},
        {9, 7, 6, 12},
        {4, 14, 15, 1},
        {13, 21, 21, 13}};
    VVT a(n);
    for (int i = 0; i < n; i++)
        a[i] = VT(A[i], A[i] + m);

    int rank = rref(a);

    // expected: 3
    cout << "Rank: " << rank << endl;

    // expected: 1 0 0 1
    //              0 1 0 3
    //              0 0 1 -3
    //              0 0 0 3.10862e-15
    //              0 0 0 2.22045e-15
    cout << "rref: " << endl;
    for (int i = 0; i < 5; i++) {
        for (int j = 0; j < 4; j++)
            cout << a[i][j] << ' ';
        cout << endl;
    }
}

```

## 3.4 Simplex algorithm

```
// Two-phase simplex algorithm for solving linear
// programs of the form
//
//      maximize      c^T x
//      subject to    Ax <= b
//                  x >= 0
//
// INPUT: A -- an m x n matrix
//        b -- an m-dimensional vector
//        c -- an n-dimensional vector
//        x -- a vector where the optimal solution will
//        be stored
//
// OUTPUT: value of the optimal solution (infinity if
//         unbounded
//         above, nan if infeasible)
//
// To use this code, create an LPSolver object with A, b
// , and c as
// arguments. Then, call Solve(x).

#include <iostream>
#include <iomanip>
#include <vector>
#include <cmath>
#include <limits>

using namespace std;

typedef long double DOUBLE;
typedef vector<DOUBLE> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;

const DOUBLE EPS = 1e-9;

struct LPSolver {
    int m, n;
    VI B, N;
    VVD D;

    LPSolver(const VVD &A, const VD &b, const VD &c) :
        m(b.size()), n(c.size()), N(n + 1), B(m), D(m + 2,
            VD(n + 2)) {
        for (int i = 0; i < m; i++) for (int j = 0; j < n; j++)
            D[i][j] = A[i][j];
        for (int i = 0; i < m; i++) { B[i] = n + i; D[i][n]
            = -1; D[i][n + 1] = b[i]; }
        for (int j = 0; j < n; j++) { N[j] = j; D[m][j] = -c[j]; }
        N[n] = -1; D[m + 1][n] = 1;
    }

    void Pivot(int r, int s) {
        double inv = 1.0 / D[r][s];
        for (int i = 0; i < m + 2; i++) if (i != r)
            for (int j = 0; j < n + 2; j++) if (j != s)
                D[i][j] -= D[r][j] * D[i][s] * inv;
        for (int j = 0; j < n + 2; j++) if (j != s) D[r][j]
            *= inv;
        for (int i = 0; i < m + 2; i++) if (i != r) D[i][s]

```

```
        *= -inv;
        D[r][s] = inv;
        swap(B[r], N[s]);
    }

    bool Simplex(int phase) {
        int x = phase == 1 ? m + 1 : m;
        while (true) {
            int s = -1;
            for (int j = 0; j <= n; j++) {
                if (phase == 2 && N[j] == -1) continue;
                if (s == -1 || D[x][j] < D[x][s] || D[x][j] == D
                    [x][s] && N[j] < N[s]) s = j;
            }
            if (D[x][s] > -EPS) return true;
            int r = -1;
            for (int i = 0; i < m; i++) {
                if (D[i][s] < EPS) continue;
                if (r == -1 || D[i][n + 1] / D[i][s] < D[r][n +
                    1] / D[r][s] ||
                    (D[i][n + 1] / D[i][s]) == (D[r][n + 1] / D[r
                        ][s]) && B[i] < B[r]) r = i;
            }
            if (r == -1) return false;
            Pivot(r, s);
        }
    }

    DOUBLE Solve(VD &x) {
        int r = 0;
        for (int i = 1; i < m; i++) if (D[i][n + 1] < D[r][n
            + 1]) r = i;
        if (D[r][n + 1] < -EPS) {
            Pivot(r, n);
            if (!Simplex(1) || D[m + 1][n + 1] < -EPS) return
                -numeric_limits<DOUBLE>::infinity();
            for (int i = 0; i < m; i++) if (B[i] == -1) {
                int s = -1;
                for (int j = 0; j <= n; j++)
                    if (s == -1 || D[i][j] < D[i][s] || D[i][j] ==
                        D[i][s] && N[j] < N[s]) s = j;
                Pivot(i, s);
            }
        }
        if (!Simplex(2)) return numeric_limits<DOUBLE>::
            infinity();
        x = VD(n);
        for (int i = 0; i < m; i++) if (B[i] < n) x[B[i]] =
            D[i][n + 1];
        return D[m][n + 1];
    }
};

int main() {
    const int m = 4;
    const int n = 3;
    DOUBLE _A[m][n] = {
        { 6, -1, 0 },
        { -1, -5, 0 },
        { 1, 5, 1 },
        { -1, -5, -1 }
    }

```

```

};
DOUBLE _b[m] = { 10, -4, 5, -5 };
DOUBLE _c[n] = { 1, -1, 0 };
VVD A(m);
VD b(_b, _b + m);
VD c(_c, _c + n);
for (int i = 0; i < m; i++) A[i] = VD(_A[i], _A[i] + n);

LPSolver solver(A, b, c);
VD x;
DOUBLE value = solver.Solve(x);
cerr << "VALUE: " << value << endl; // VALUE: 1.29032
cerr << "SOLUTION:"; // SOLUTION: 1.74194 0.451613 1
for (size_t i = 0; i < x.size(); i++) cerr << " " << x[i];
cerr << endl;
return 0;
}

```

### 3.5 Fast Fourier transform

```

auto FFT = [] (vector<long double>a, vector<long double>b)
{
    auto DFT = [] (vector<complex<long double>>&a, bool inv)
    {
        int L=31-__builtin_clz(a.size()), n=1<<L;
        vector<complex<long double>> A(n);
        for (int k=0, r=i, i<n; A[r]=a[k++])
            for (i=r=0; i<L; (r<<=1) |=(k>>i++) &1);
        complex<long double> w, wm, t;
        for (int m=2, j, k; m<=n; m<<=1)
            for (w={0, 2*acos(-1)/m}, wm=exp(inv?-w:w), k=0; k<n; k+=m)
                for (j=0, w=1; j<m/2; ++j, w*=wm)
                    t=w*A[k+j+m/2], A[k+j+m/2]=A[k+j]-t, A[k+j]+=t;
        return A;
    };
    int n=4<<31-__builtin_clz(max(a.size(), b.size()));
    vector<complex<long double>> A(n), B(n), CC(n);
    for (int i=0; i<n; ++i)
        A[i]=i<a.size()?a[i]:0, B[i]=i<b.size()?b[i]:0;
    vector<complex<long double>> AA=DFT(A, 0), BB=DFT(B, 0);
    for (int i=0; i<n; ++i) CC[i]=AA[i]*BB[i];
    vector<long double> c;
    for (auto i:DFT(CC, 1)) if (c.size()<a.size()+b.size()-1)
        c.push_back(i.real()/n+1e-5);
    return c;
};

```

### 3.6 BigInt library

```

struct bigint {
    const int base = 1000000000, base_digits = 9;
    vector<int> a;
    int sign;
    bigint() : sign(1) {}
    bigint(long long v) {

```

```

        *this = v;
    }
    bigint(const string &s) {
        read(s);
    }
    void operator=(const bigint &v) {
        sign = v.sign;
        a = v.a;
    }
    void operator=(long long v) {
        sign = 1;
        if (v < 0) sign = -1, v = -v;
        for (; v > 0; v = v / base)
            a.push_back(v % base);
    }
    bigint operator+(const bigint &v) const {
        if (sign == v.sign) {
            bigint res = v;
            for (int i = 0, carry = 0; i < (int) max(a.size(), v.a.size()) || carry; ++i) {
                if (i == (int) res.a.size())
                    res.a.push_back(0);
                res.a[i] += carry + (i < (int) a.size() ? a[i] : 0);
                carry = res.a[i] >= base;
                if (carry)
                    res.a[i] -= base;
            }
            return res;
        }
        return *this - (-v);
    }
    bigint operator-(const bigint &v) const {
        if (sign == v.sign) {
            if (abs() >= v.abs()) {
                bigint res = *this;
                for (int i = 0, carry = 0; i < (int) v.a.size() || carry; ++i) {
                    res.a[i] -= carry + (i < (int) v.a.size() ? v.a[i] : 0);
                    carry = res.a[i] < 0;
                    if (carry)
                        res.a[i] += base;
                }
                res.trim();
                return res;
            }
            return -(v - *this);
        }
        return *this + (-v);
    }
    void operator*=(int v) {
        if (v < 0)
            sign = -sign, v = -v;
        for (int i = 0, carry = 0; i < (int) a.size() || carry; ++i) {
            if (i == (int) a.size())
                a.push_back(0);
            long long cur = a[i] * (long long) v + carry;

```

```

        carry = (int) (cur / base);
        a[i] = (int) (cur % base);
        //asm("divl %%ecx" : "=a"(carry), "=d"(a[i])
        : "A"(cur), "C"(base));
    }
    trim();
}

bigint operator*(int v) const {
    bigint res = *this;
    res *= v;
    return res;
}

friend pair<bigint, bigint> divmod(const bigint &a1,
    const bigint &b1) {
    int norm = a1.base / (b1.a.back() + 1);
    bigint a = a1.abs() * norm;
    bigint b = b1.abs() * norm;
    bigint q, r;
    q.a.resize(a.a.size());
    for (int i = a.a.size() - 1; i >= 0; i--) {
        r *= a1.base;
        r += a.a[i];
        int s1 = r.a.size() <= b.a.size() ? 0 : r.a[
            b.a.size()];
        int s2 = r.a.size() <= b.a.size() - 1 ? 0 :
            r.a[b.a.size() - 1];
        int d = ((long long) a1.base * s1 + s2) / b.
            a.back();
        r -= b * d;
        while (r < 0)
            r += b, --d;
        q.a[i] = d;
    }
    q.sign = a1.sign * b1.sign;
    r.sign = a1.sign;
    q.trim();
    r.trim();
    return make_pair(q, r / norm);
}

bigint operator/(const bigint &v) const {
    return divmod(*this, v).first;
}

bigint operator%(const bigint &v) const {
    return divmod(*this, v).second;
}

void operator/=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = (int) a.size() - 1, rem = 0; i >=
        0; --i) {
        long long cur = a[i] + rem * (long long)
            base;
        a[i] = (int) (cur / v);
        rem = (int) (cur % v);
    }
    trim();
}

bigint operator/(int v) const {
    bigint res = *this;
    res /= v;
    return res;
}

```

```

int operator%(int v) const {
    if (v < 0)
        v = -v;
    int m = 0;
    for (int i = a.size() - 1; i >= 0; --i)
        m = (a[i] + m * (long long) base) % v;
    return m * sign;
}

void operator+=(const bigint &v) {
    *this = *this + v;
}

void operator-=(const bigint &v) {
    *this = *this - v;
}

void operator*=(const bigint &v) {
    *this = *this * v;
}

void operator/=(const bigint &v) {
    *this = *this / v;
}

bool operator<(const bigint &v) const {
    if (sign != v.sign)
        return sign < v.sign;
    if (a.size() != v.a.size())
        return a.size() * sign < v.a.size() * v.sign;
    for (int i = a.size() - 1; i >= 0; i--)
        if (a[i] != v.a[i])
            return a[i] * sign < v.a[i] * sign;
    return false;
}

bool operator>(const bigint &v) const {
    return v < *this;
}

bool operator<=(const bigint &v) const {
    return !(v < *this);
}

bool operator>=(const bigint &v) const {
    return !(*this < v);
}

bool operator==(const bigint &v) const {
    return !(*this < v) && !(v < *this);
}

bool operator!=(const bigint &v) const {
    return *this < v || v < *this;
}

void trim() {
    while (!a.empty() && !a.back())
        a.pop_back();
    if (a.empty())
        sign = 1;
}

bool isZero() const {
    return a.empty() || (a.size() == 1 && !a[0]);
}

bigint operator-() const {
    bigint res = *this;
    res.sign = -sign;
    return res;
}

bigint abs() const {

```

```

    bigint res = *this;
    res.sign *= res.sign;
    return res;
}

long long longValue() const {
    long long res = 0;
    for (int i = a.size() - 1; i >= 0; i--)
        res = res * base + a[i];
    return res * sign;
}

friend bigint gcd(const bigint &a, const bigint &b)
{
    return b.isZero() ? a : gcd(b, a % b);
}

friend bigint lcm(const bigint &a, const bigint &b)
{
    return a / gcd(a, b) * b;
}

void read(const string &s) {
    sign = 1;
    a.clear();
    int pos = 0;
    while (pos < (int) s.size() && (s[pos] == '-' ||
        s[pos] == '+')) {
        if (s[pos] == '-') sign = -sign;
        ++pos;
    }
    for (int i = s.size() - 1; i >= pos; i -=
        base_digits) {
        int x = 0;
        for (int j = max(pos, i - base_digits + 1);
            j <= i; j++)
            x = x * 10 + s[j] - '0';
        a.push_back(x);
    }
    trim();
}

friend istream& operator>>(istream &stream, bigint &
    v) {
    string s;
    stream >> s;
    v.read(s);
    return stream;
}

friend ostream& operator<<(ostream &stream, const
    bigint &v) {
    if (v.sign == -1) stream << '-';
    stream << (v.a.empty() ? 0 : v.a.back());
    for (int i = (int) v.a.size() - 2; i >= 0; --i)
        stream << setw(v.base_digits) << setfill('0'
            ) << v.a[i];
    return stream;
}

static vector<int> convert_base(const vector<int> &a
    , int old_digits, int new_digits) {
    vector<long long> p(max(old_digits, new_digits)
        + 1);
    p[0] = 1;
    for (int i = 1; i < (int) p.size(); i++)
        p[i] = p[i - 1] * 10;
    vector<int> res;

```

```

    long long cur = 0;
    int cur_digits = 0;
    for (int i = 0; i < (int) a.size(); i++) {
        cur += a[i] * p[cur_digits];
        cur_digits += old_digits;
        while (cur_digits >= new_digits) {
            res.push_back(int(cur % p[new_digits]));
            cur /= p[new_digits];
            cur_digits -= new_digits;
        }
    }
    res.push_back((int) cur);
    while (!res.empty() && !res.back())
        res.pop_back();
    return res;
}

typedef vector<long long> vll;
static vll karatsubaMultiply(const vll &a, const vll
    &b) {
    int n = a.size();
    vll res(n + n);
    if (n <= 32) {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                res[i + j] += a[i] * b[j];
        return res;
    }
    int k = n >> 1;
    vll a1(a.begin(), a.begin() + k);
    vll a2(a.begin() + k, a.end());
    vll b1(b.begin(), b.begin() + k);
    vll b2(b.begin() + k, b.end());
    vll alb1 = karatsubaMultiply(a1, b1);
    vll a2b2 = karatsubaMultiply(a2, b2);
    for (int i = 0; i < k; i++)
        a2[i] += a1[i];
    for (int i = 0; i < k; i++)
        b2[i] += b1[i];
    vll r = karatsubaMultiply(a2, b2);
    for (int i = 0; i < (int) alb1.size(); i++)
        r[i] -= alb1[i];
    for (int i = 0; i < (int) a2b2.size(); i++)
        r[i] -= a2b2[i];
    for (int i = 0; i < (int) r.size(); i++)
        res[i + k] += r[i];
    for (int i = 0; i < (int) alb1.size(); i++)
        res[i] += alb1[i];
    for (int i = 0; i < (int) a2b2.size(); i++)
        res[i + n] += a2b2[i];
    return res;
}

bigint operator*(const bigint &v) const {
    vector<int> a6 = convert_base(this->a,
        base_digits, 6);
    vector<int> b6 = convert_base(v.a, base_digits,
        6);
    vll a(a6.begin(), a6.end());
    vll b(b6.begin(), b6.end());
    while (a.size() < b.size())
        a.push_back(0);
    while (b.size() < a.size())

```

```

        b.push_back(0);
    while (a.size() & (a.size() - 1))
        a.push_back(0), b.push_back(0);
    vll c = karatsubaMultiply(a, b);
    bigint res;
    res.sign = sign * v.sign;
    for (int i = 0, carry = 0; i < (int) c.size(); i++) {
        long long cur = c[i] + carry;
        res.a.push_back((int) (cur % 1000000));
        carry = (int) (cur / 1000000);
    }
    res.a = convert_base(res.a, 6, base_digits);
    res.trim();
    return res;
};

```

## 4 Graph algorithms

### 4.1 Bellman-Ford shortest paths with negative edge weights

```

// Single source shortest paths with negative edge weights.
// Returns false if a negative weight cycle is detected.
// Running time:  $O(|V|^3)$ 
// INPUT: start, w[i][j] = cost of edge from i to j
// OUTPUT: dist[i] = min weight path from start to i
//         dad[i] = prevector<int>ous node on the
//         best path from the start node
vector<int> dad;
vector<double> dist;
bool BellmanFord(int start, vector<vector<double>> &w) {
    int n = w.size();
    dad = vector<int>(n, -1);
    dist = vector<double>(n, 1000000000);
    dist[start] = 0;
    for (int k = 0; k < n; k++)
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                if (dist[j] > dist[i] + w[i][j]) {
                    if (k == n-1) return false;
                    else dist[j] = dist[i] + w[i][j], dad[j] = i;
                }
    return true;
}
int main() {}

```

### 4.2 Eulerian path

```

struct Edge;
typedef list<Edge>::iterator iter;
struct Edge
{

```

```

    int next_vertex;
    iter reverse_edge;
    Edge(int next_vertex)
        : next_vertex(next_vertex)
    { }
};

const int max_vertices = ;
int num_vertices;
list<Edge> adj[max_vertices]; // adjacency list
vector<int> path;
void find_path(int v)
{
    while (adj[v].size() > 0)
    {
        int vn = adj[v].front().next_vertex;
        adj[vn].erase(adj[v].front().reverse_edge);
        adj[v].pop_front();
        find_path(vn);
    }
    path.push_back(v);
}

void add_edge(int a, int b)
{
    adj[a].push_front(Edge(b));
    iter ita = adj[a].begin();
    adj[b].push_front(Edge(a));
    iter itb = adj[b].begin();
    ita->reverse_edge = itb;
    itb->reverse_edge = ita;
}

```

### 4.3 Minimum spanning trees

```

// This function runs Prim's algorithm for constructing
// minimum weight spanning trees.
// Running time:  $O(|V|^2)$ 
// INPUT: w[i][j] = cost of edge from i to j
// NOTE: Make sure that w[i][j] is
// nonnegative and symmetric. Missing edges should be given
// -1 weight.
// OUTPUT: edges = list of pair<int,int> in minimum
// spanning tree
// return total weight of tree

```

```

#include <iostream>
#include <queue>
#include <cmath>
#include <vector>

```



```

using namespace std;
typedef double T;
typedef vector<T> VT;
typedef vector<VT> VVT;

typedef vector<int> VI;
typedef vector<VI> VVI;
typedef pair<int,int> PII;
typedef vector<PII> VPPII;

T Prim (const VVT &w, VPPII &edges){
    int n = w.size();
    VI found (n);
    VI prev (n, -1);
    VT dist (n, 1000000000);
    int here = 0;
    dist[here] = 0;
    while (here != -1){
        found[here] = true;
        int best = -1;
        for (int k = 0; k < n; k++) if (!found[k]){
            if (w[here][k] != -1 && dist[k] > w[here][k]){
                dist[k] = w[here][k];
                prev[k] = here;
            }
            if (best == -1 || dist[k] < dist[best]) best = k;
        }
        here = best;
    }
    T tot_weight = 0;
    for (int i = 0; i < n; i++) if (prev[i] != -1){
        edges.push_back (make_pair (prev[i], i));
        tot_weight += w[prev[i]][i];
    }
    return tot_weight;
}

int main(){
    int ww[5][5] = {
        {0, 400, 400, 300, 600},
        {400, 0, 3, -1, 7},
        {400, 3, 0, 2, 0},
        {300, -1, 2, 0, 5},
        {600, 7, 0, 5, 0}
    };
    VVT w(5, VT(5));
    for (int i = 0; i < 5; i++)
        for (int j = 0; j < 5; j++)
            w[i][j] = ww[i][j];

    // expected: 305
    //          2 1
    //          3 2
    //          0 3
    //          2 4

    VPPII edges;
    cout << Prim (w, edges) << endl;
    for (int i = 0; i < edges.size(); i++)
        cout << edges[i].first << " " << edges[i].second <<
            endl;
}

```

## 4.4 Centroid decomposition

```

set<int> v[100005];
map<int,int> mp[100005];
int n, up[100005][17], lvl[100005], par[100005], CNT, siz
[100005], tin[100005], tout[100005];
void dfspre(int u, int dad=1, int depth = 0){
    static int clk = 0;
    tin[u]=clk++;
    up[u][0] = dad;
    lvl[u] = depth;
    for(int i=1; i<17; ++i)
        up[u][i] = up[up[u][i-1]][i-1];
    for(int i:v[u]) if(i!=dad)
        dfspre(i, u, depth+1);
    tout[u]=clk++;
}
int dfs(int u, int dad){
    siz[u] = 1;
    for(int i:v[u]) if(i!=dad)
        siz[u] += dfs(i, u);
    return siz[u];
}
int centroid(int u, int dad){
    for(int i:v[u]) if(i!=dad && siz[i]>CNT)
        return centroid(i, u);
    return u;
}
void decompose(int u, int dad){
    CNT = dfs(u, dad)/2;
    int centre = centroid(u, dad);
    par[centre] = dad;
    for(int i:v[centre]) if(i!=dad){
        v[i].erase(centre);
        decompose(i, centre);
    }
    v[centre].clear();
}
int lca(int u, int v){
    if(lvl[u]>lvl[v]) swap(u, v);
    if(tin[u]<=tin[v] && tout[v]<=tout[u]) return u;
    for(int i=17; i--;)
        if(!(tin[up[u][i]]<=tin[v] && tout[v]<=tout[up[u]
            ][i]]))
            u = up[u][i];
    return up[u][0];
}
void update(int u){
    for(int node = u; u; u = par[u])
        ++mp[u][lvl[node]+lvl[u] - 2*lvl[lca(u, node)]];
}
int get(int u){
    int ans = INT_MAX;
    for(int node = u; u; u = par[u])
        ans = min(ans, lvl[u]+lvl[node]-2*lvl[lca(u, node)
            ]+(*mp[u].begin()).first);
    return ans;
}

```

## 4.5 Heavy-Light decomposition

```
#include <bits/stdc++.h>
using namespace std;
int a[100005], sz[100005], lvl[100005];
int seg_id[100005], pos_id[100005], parent[100005];
int CNT;
int e_to_v[100005];
vector<pair<int, int>> edges(100005);
vector<pair<int, int>> v[100005];
vector<int> chain[100005];
template <typename T>
class SegmentTree{
    vector<T> segtree, lazy;
public:
    SegmentTree(int size){
        segtree.resize(4*size, 0);
        lazy.resize(4*size, 0);
    }
    void update(int u, int a, int b, int i, int j, T x){
        if(lazy[u]){
            segtree[u] += (b-a+1)*lazy[u];
            if(a!=b)
                lazy[u*2] += lazy[u], lazy[2*u+1] += lazy[u];
            lazy[u] = 0;
        }
        if(j<a || i>b || a>b) return;
        if(j>=b && i<=a){
            segtree[u] = x;
            if(a!=b) lazy[u*2] += x, lazy[2*u+1] += x;
            return;
        }
        update(u*2, a, (a+b)/2, i, j, x); update(u*2+1, (a+b)/2+1,
            b, i, j, x);
        segtree[u] = max(segtree[u*2], segtree[u*2+1]);
    }
    void update(int i, T x){
        update(1, 0, segtree.size()/4-1, i, i, x);
    }
    void update(int i, int j, T x){
        update(1, 0, segtree.size()/4-1, i, j, x);
    }
    T query(int u, int a, int b, int i, int j){
        if(j<a || i>b || a>b) return 0;
        if(lazy[u]){
            segtree[u] += (b-a+1)*lazy[u];
            if(a!=b)
                lazy[u*2] += lazy[u], lazy[2*u+1] += lazy[u];
            lazy[u] = 0;
        }
        if(j>=b && i<=a) return segtree[u];
        return max(query(u*2, a, (a+b)/2, i, j), query(u*2+1, 1+(a
            +b)/2, b, i, j));
    }
    T query(int i, int j){
        return query(1, 0, segtree.size()/4-1, i, j);
    }
};
int dfs(int u, int dad=1, int depth=1){
```

```
    lvl[u] = depth;
    sz[u] = 1;
    for(auto i:v[u]) if(i.first!=dad)
        sz[u] += dfs(i.first, u, depth+1);
    return sz[u];
}
void hld(int u, int dad = 1, int chain_no = 0, int
    chain_parent = 0){
    seg_id[u] = chain_no;
    pos_id[u] = chain[chain_no].size();
    parent[u] = chain_parent;
    chain[chain_no].push_back(u);
    int max_sz = 0, heavy_child = -1;
    for(auto i:v[u]) if(i.first!=dad){
        a[i.first] = i.second;
        if(max_sz < sz[i.first])
            max_sz = sz[i.first], heavy_child = i.first;
    }
    if(heavy_child!=-1)
        hld(heavy_child, u, chain_no, chain_parent);
    for(auto i:v[u]) if(i.first!=dad && i.first!=
        heavy_child)
        hld(i.first, u, ++CNT, u);
}
int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0); cout.tie(0);
    int T, n, x, y;
    for(cin>>T; T-- && cin>>n;){
        CNT = 0;
        for(int i=0; i<100005; chain[i].clear(), v[i].clear(),
            i++){
            for(int i=1, c; i<n; ++i){
                cin>>x>>y>>c;
                edges[i] = {x, y};
                v[x].push_back({y, c});
                v[y].push_back({x, c});
            }
            dfs(1);
            for(int i=1; i<n; ++i){
                int u = edges[i].first, v = edges[i].second;
                e_to_v[i] = (lvl[u]<lvl[v]?v:u);
            }
            hld(1);
            vector<SegmentTree<int>> ST;
            for(int i=0; i<=CNT; ++i){
                ST.push_back(SegmentTree<int>(chain[i].size()));
                for(auto u:chain[i])
                    ST[i].update(pos_id[u], a[u]);
            }
            for(string type; cin>>type && type!="DONE";){
                cin>>x>>y;
                if(type=="QUERY"){
                    int res = 0;
                    while(x!=y){
                        if(seg_id[x]>seg_id[y]) swap(x, y);
                        else if(seg_id[x] == seg_id[y]){
```

```

        if(pos_id[x]>pos_id[y]) swap(x,y);
        res = max(res, ST[seg_id[y]].query(pos_id[x]
            ]+1, pos_id[y]));
        break;
    }
    res = max(res, ST[seg_id[y]].query(0, pos_id[y]
        ));
    y = parent[y];
}
cout<<res<<'\\n';
}
else if(type == "CHANGE"){
    int u = e_to_v[x];
    ST[seg_id[u]].update(pos_id[u], y);
}
}
}
}
}

```

## 5 Data structures

### 5.1 Suffix array

```

// Suffix array construction in  $O(L \log^2 L)$  time.
// Routine for
// computing the length of the longest common prefix of
// any two
// suffixes in  $O(\log L)$  time.
//
// INPUT:  string s
//
// OUTPUT: array suffix[] such that suffix[i] = index (
//         from 0 to L-1)
//         of substring s[i...L-1] in the list of
//         sorted suffixes.
//         That is, if we take the inverse of the
//         permutation suffix[],
//         we get the actual suffix array.

#include <vector>
#include <iostream>
#include <string>

using namespace std;

struct SuffixArray {
    const int L;
    string s;
    vector<vector<int>> > P;
    vector<pair<pair<int,int>,int>> > M;

    SuffixArray(const string &s) : L(s.length()), s(s), P
        (1, vector<int>(L, 0)), M(L) {
        for (int i = 0; i < L; i++) P[0][i] = int(s[i]);
        for (int skip = 1, level = 1; skip < L; skip *= 2,
            level++) {
            P.push_back(vector<int>(L, 0));
            for (int i = 0; i < L; i++)
                M[i] = make_pair(make_pair(P[level-1][i], i +
                    skip < L ? P[level-1][i + skip] : -1000), i);
            sort(M.begin(), M.end());
        }
    }
}

```

```

        for (int i = 0; i < L; i++)
            P[level][M[i].second] = (i > 0 && M[i].first ==
                M[i-1].first) ? P[level][M[i-1].second] : i;
    }
}

vector<int> GetSuffixArray() { return P.back(); }

// returns the length of the longest common prefix of
// s[i...L-1] and s[j...L-1]
int LongestCommonPrefix(int i, int j) {
    int len = 0;
    if (i == j) return L - i;
    for (int k = P.size() - 1; k >= 0 && i < L && j < L;
        k--) {
        if (P[k][i] == P[k][j]) {
            i += 1 << k;
            j += 1 << k;
            len += 1 << k;
        }
    }
    return len;
}

};

// BEGIN CUT
// The following code solves UVA problem 11512: GATTACA.
#define TESTING
#ifdef TESTING
int main() {
    int T;
    cin >> T;
    for (int caseno = 0; caseno < T; caseno++) {
        string s;
        cin >> s;
        SuffixArray array(s);
        vector<int> v = array.GetSuffixArray();
        int bestlen = -1, bestpos = -1, bestcount = 0;
        for (int i = 0; i < s.length(); i++) {
            int len = 0, count = 0;
            for (int j = i+1; j < s.length(); j++) {
                int l = array.LongestCommonPrefix(i, j);
                if (l >= len) {
                    if (l > len) count = 2; else count++;
                    len = l;
                }
            }
            if (len > bestlen || len == bestlen && s.substr(
                bestpos, bestlen) > s.substr(i, len)) {
                bestlen = len;
                bestcount = count;
                bestpos = i;
            }
        }
        if (bestlen == 0) {
            cout << "No repetitions found!" << endl;
        } else {
            cout << s.substr(bestpos, bestlen) << " " <<
                bestcount << endl;
        }
    }
}

```

```

#else
// END CUT
int main() {
    SuffixArray suffix("bobocel");
    vector<int> v = suffix.GetSuffixArray();
    // Expected output: 0 5 1 6 2 3 4
    //
    for (int i = 0; i < v.size(); i++) cout << v[i] << " "
    ;
    cout << endl;
    cout << suffix.LongestCommonPrefix(0, 2) << endl;
}
// BEGIN CUT
#endif
// END CUT

```

## 5.2 KD-tree

```

// A straightforward, but probably sub-optimal KD-tree
// implmentation
// that's probably good enough for most things (current
// it's a
// 2D-tree)
//
// - constructs from n points in O(n lg^2 n) time
// - handles nearest-neighbor query in O(lg n) if
// points are well
// distributed
// - worst case for nearest-neighbor may be linear in
// pathological
// case
//
// Sonny Chan, Stanford University, April 2009
#include <iostream>
#include <vector>
#include <limits>
#include <cstdlib>
using namespace std;

// number type for coordinates, and its maximum value
typedef long long ntype;
const ntype sentry = numeric_limits<ntype>::max();

// point structure for 2D-tree, can be extended to 3D
struct point {
    ntype x, y;
    point(ntype xx = 0, ntype yy = 0) : x(xx), y(yy) {}
};

bool operator==(const point &a, const point &b) {
    return a.x == b.x && a.y == b.y;
}

// sorts points on x-coordinate
bool on_x(const point &a, const point &b) {
    return a.x < b.x;
}

// sorts points on y-coordinate
bool on_y(const point &a, const point &b) {
    return a.y < b.y;
}

```

```

}

// squared distance between points
ntype pdist2(const point &a, const point &b) {
    ntype dx = a.x-b.x, dy = a.y-b.y;
    return dx*dx + dy*dy;
}

// bounding box for a set of points
struct bbox {
    ntype x0, x1, y0, y1;
    bbox() : x0(sentry), x1(-sentry), y0(sentry), y1(-sentry) {}

    // computes bounding box from a bunch of points
    void compute(const vector<point> &v) {
        for (int i = 0; i < v.size(); ++i) {
            x0 = min(x0, v[i].x);    x1 = max(x1, v[i].x)
            ;
            y0 = min(y0, v[i].y);    y1 = max(y1, v[i].y)
            ;
        }
    }

    // squared distance between a point and this bbox, 0
    // if inside
    ntype distance(const point &p) {
        if (p.x < x0) {
            if (p.y < y0) return pdist2(point(x0,
            y0), p);
            else if (p.y > y1) return pdist2(point(x0,
            y1), p);
            else return pdist2(point(x0,
            p.y), p);
        }
        else if (p.x > x1) {
            if (p.y < y0) return pdist2(point(x1,
            y0), p);
            else if (p.y > y1) return pdist2(point(x1,
            y1), p);
            else return pdist2(point(x1,
            p.y), p);
        }
        else {
            if (p.y < y0) return pdist2(point(p.x,
            y0), p);
            else if (p.y > y1) return pdist2(point(p.x,
            y1), p);
            else return 0;
        }
    }
};

// stores a single node of the kd-tree, either internal
// or leaf
struct kndnode {
    bool leaf; // true if this is a leaf node (has
    one point)
    point pt; // the single point of this is a
    leaf
    bbox bound; // bounding box for set of points in
    children
    kndnode *first, *second; // two children of this kd-

```

```

    node
    kdnode() : leaf(false), first(0), second(0) {}
    ~kdnode() { if (first) delete first; if (second)
        delete second; }
    // intersect a point with this node (returns squared
    // distance)
    ntype intersect(const point &p) {
        return bound.distance(p);
    }
    // recursively builds a kd-tree from a given cloud
    // of points
    void construct(vector<point> &vp) {
        // compute bounding box for points at this node
        bound.compute(vp);
        // if we're down to one point, then we're a leaf
        // node
        if (vp.size() == 1) {
            leaf = true;
            pt = vp[0];
        }
        else {
            // split on x if the bbox is wider than high
            // (not best heuristic...)
            if (bound.x1-bound.x0 >= bound.y1-bound.y0)
                sort(vp.begin(), vp.end(), on_x);
            // otherwise split on y-coordinate
            else
                sort(vp.begin(), vp.end(), on_y);

            // divide by taking half the array for each
            // child
            // (not best performance if many duplicates
            // in the middle)
            int half = vp.size()/2;
            vector<point> vl(vp.begin(), vp.begin()+half
                );
            vector<point> vr(vp.begin()+half, vp.end());
            first = new kdnode(); first->construct(vl);
            second = new kdnode(); second->construct(vr);
        }
    }
};

// simple kd-tree class to hold the tree and handle
// queries
struct kdtree {
    kdnode *root;
    // constructs a kd-tree from a points (copied here,
    // as it sorts them)
    kdtree(const vector<point> &vp) {
        vector<point> v(vp.begin(), vp.end());
        root = new kdnode();
        root->construct(v);
    }
    ~kdtree() { delete root; }
    // recursive search method returns squared distance
    // to nearest point

```

```

    ntype search(kdnode *node, const point &p)
    {
        if (node->leaf) {
            // commented special case tells a point not
            // to find itself
            if (p == node->pt) return sentry;
            else
                return pdist2(p, node->pt);
        }
        ntype bfirst = node->first->intersect(p);
        ntype bsecond = node->second->intersect(p);
        // choose the side with the closest bounding box
        // to search first
        // (note that the other side is also searched if
        // needed)
        if (bfirst < bsecond) {
            ntype best = search(node->first, p);
            if (bsecond < best)
                best = min(best, search(node->second, p));
            return best;
        }
        else {
            ntype best = search(node->second, p);
            if (bfirst < best)
                best = min(best, search(node->first, p));
            return best;
        }
    }
    // squared distance to the nearest
    ntype nearest(const point &p) {
        return search(root, p);
    }
};

// some basic test code here
int main() {
    // generate some random points for a kd-tree
    vector<point> vp;
    for (int i = 0; i < 100000; ++i) {
        vp.push_back(point(rand()%100000, rand()%100000));
    }
    kdtree tree(vp);
    // query some points
    for (int i = 0; i < 10; ++i) {
        point q(rand()%100000, rand()%100000);
        cout << "Closest squared distance to (" << q.x
            << ", " << q.y << ")"
            << " is " << tree.nearest(q) << endl;
    }
}

```

## 5.3 Splay tree

```

#include <cstdio>
#include <algorithm>

```

```

using namespace std;
const int N_MAX = 130010;
const int oo = 0x3f3f3f3f;
struct Node
{
    Node *ch[2], *pre;
    int val, size;
    bool isTurned;
} nodePool[N_MAX], *null, *root;
Node *allocNode(int val)
{
    static int freePos = 0;
    Node *x = &nodePool[freePos++];
    x->val = val, x->isTurned = false;
    x->ch[0] = x->ch[1] = x->pre = null;
    x->size = 1;
    return x;
}
inline void update(Node *x)
{
    x->size = x->ch[0]->size + x->ch[1]->size + 1;
}
inline void makeTurned(Node *x)
{
    if(x == null)
        return;
    swap(x->ch[0], x->ch[1]);
    x->isTurned ^= 1;
}
inline void pushDown(Node *x)
{
    if(x->isTurned)
    {
        makeTurned(x->ch[0]);
        makeTurned(x->ch[1]);
        x->isTurned ^= 1;
    }
}
inline void rotate(Node *x, int c)
{
    Node *y = x->pre;
    x->pre = y->pre;
    if(y->pre != null)
        y->pre->ch[y == y->pre->ch[1]] = x;
    y->ch[!c] = x->ch[c];
    if(x->ch[c] != null)
        x->ch[c]->pre = y;
    x->ch[c] = y, y->pre = x;
    update(y);
    if(y == root)
        root = x;
}
void splay(Node *x, Node *p)
{
    while(x->pre != p)
    {
        if(x->pre->pre == p)
            rotate(x, x == x->pre->ch[0]);
    }
}

```

```

    else
    {
        Node *y = x->pre, *z = y->pre;
        if(y == z->ch[0])
        {
            if(x == y->ch[0])
                rotate(y, 1), rotate(x, 1);
            else
                rotate(x, 0), rotate(x, 1);
        }
        else
        {
            if(x == y->ch[1])
                rotate(y, 0), rotate(x, 0);
            else
                rotate(x, 1), rotate(x, 0);
        }
    }
    update(x);
}
void select(int k, Node *fa)
{
    Node *now = root;
    while(1)
    {
        pushDown(now);
        int tmp = now->ch[0]->size + 1;
        if(tmp == k)
            break;
        else if(tmp < k)
            now = now->ch[1], k -= tmp;
        else
            now = now->ch[0];
    }
    splay(now, fa);
}
Node *makeTree(Node *p, int l, int r)
{
    if(l > r)
        return null;
    int mid = (l + r) / 2;
    Node *x = allocNode(mid);
    x->pre = p;
    x->ch[0] = makeTree(x, l, mid - 1);
    x->ch[1] = makeTree(x, mid + 1, r);
    update(x);
    return x;
}
int main()
{
    int n, m;
    null = allocNode(0);
    null->size = 0;
    root = allocNode(0);
    root->ch[1] = allocNode(oo);
    root->ch[1]->pre = root;
    update(root);
    scanf("%d%d", &n, &m);
}

```

```

root->ch[1]->ch[0] = makeTree(root->ch[1], 1, n);
splay(root->ch[1]->ch[0], null);

while(m --)
{
    int a, b;
    scanf("%d%d", &a, &b);
    a ++, b ++;
    select(a - 1, null);
    select(b + 1, root);
    makeTurned(root->ch[1]->ch[0]);
}

for(int i = 1; i <= n; i ++)
{
    select(i + 1, null);
    printf("%d ", root->val);
}
}

```

## 6 Miscellaneous

### 6.1 Miller-Rabin Primality Test

```

// Error rate: 2^(-TRIAL)
// Almost constant time. srand is needed
int64_t ModMul(int64_t a, int64_t b, int64_t m) {
    int64_t ret=0, c=a;
    for(;b;b>>=1, c=(c+c)%m)
        if(b&1) ret=(ret+c)%m;
    return ret;
}
int64_t ModExp(int64_t a, int64_t n, int64_t m) {
    return n?ModMul(ModExp(a, n/2, m), (n
        %2?a:1), m):1;
}
bool Witness(int64_t a, int64_t n) {
    int64_t u=n-1;
    int t=0;
    while(!(u&1)) {u>>=1; t++;}
    int64_t x0=ModExp(a, u, n), x1;
    for(int i=1; i<=t; i++) {
        x1=ModMul(x0, x0, n);
        if(x1==1&&x0!=1&&x0!=n-1) return true;
        x0=x1;
    }
    if(x0!=1) return true;
    return false;
}
bool IsPrimeFast(int64_t n, int TRIAL=15) {
    if(n<=2) return (n==2);
    static random_device rd;
    static mt19937_64 g(rd());
    while(TRIAL--)
        if(Witness(g()/2%(n-2)+1, n))
            return false;
    return true;
}

```

### 6.2 Pollard-Rho factorization

```

typedef long long unsigned int llui;
typedef long long int lli;
typedef long double float64;

llui mul_mod(llui a, llui b, llui m) {
    llui y = (llui)((float64)a*(float64)b/m+(float64)1/2);
    y = y * m;
    llui x = a * b;
    llui r = x - y;
    if ( (lli)r < 0 ) {
        r = r + m; y = y - 1;
    }
    return r;
}

llui C, a, b;
llui gcd() {
    llui c;
    if(a>b) {
        c = a; a = b; b = c;
    }
    while(1) {
        if(a == 1LL) return 1LL;
        if(a == 0 || a == b) return b;
        c = a; a = b%a;
        b = c;
    }
}

llui f(llui a, llui b) {
    llui tmp;
    tmp = mul_mod(a, a, b);
    tmp+=C; tmp%=b;
    return tmp;
}

llui pollard(llui n) {
    if(!(n&1)) return 2;
    C=0;
    llui iteracoes = 0;
    while(iteracoes <= 1000) {
        llui x, y, d;
        x = y = 2; d = 1;
        while(d == 1) {
            x = f(x, n);
            y = f(f(y, n), n);
            llui m = (x>y)?(x-y):(y-x);
            a = m; b = n; d = gcd();
        }
        if(d != n)
            return d;
        iteracoes++; C = rand();
    }
    return 1;
}

llui pot(llui a, llui b, llui c) {
    if(b == 0) return 1;
    if(b == 1) return a%c;
    llui resp = pot(a, b>>1, c);

```



```

    resp = mul_mod(resp, resp, c);
    if(b&1)
        resp = mul_mod(resp, a, c);
    return resp;
}

// Rabin-Miller primality testing algorithm
bool isPrime(llui n) {
    llui d = n-1;
    llui s = 0;
    if(n <= 3 || n == 5) return true;
    if(!(n&1)) return false;
    while(!(d&1)) { s++; d>>=1; }
    for(llui i = 0; i<32; i++) {
        llui a = rand();
        a <= 32;
        a += rand();
        a %= (n-3); a += 2;
        llui x = pot(a, d, n);
        if(x == 1 || x == n-1) continue;
        for(llui j = 1; j<= s-1; j++) {
            x = mul_mod(x, x, n);
            if(x == 1) return false;
            if(x == n-1) break;
        }
        if(x != n-1) return false;
    }
    return true;
}

map<llui, int> factors;
// Precondition: factors is an empty map, n is a
// positive integer
// Postcondition: factors[p] is the exponent of p in
// prime factorization of n
void fact(llui n) {
    if(!isPrime(n)) {
        llui fac = pollard(n);
        fact(n/fac); fact(fac);
    } else {
        map<llui, int>::iterator it;
        it = factors.find(n);
        if(it != factors.end()) {
            (*it).second++;
        } else {
            factors[n] = 1;
        }
    }
}
}

```

## 6.3 Manachers algorithm

```

// Maximal palindrome lengths centered around each
// position in a string (including positions between
// characters) and returns
// them in left-to-right order of centres. Linear time.
// Ex: "opposes" -> [0, 1, 0, 1, 4, 1, 0, 1, 0, 1, 0, 3,
// 0, 1, 0]
vector<int> fastLongestPalindromes(string str) {
    int i=0, j, d, s, e, lLen, palLen=0;
    vector<int> res;

```

```

    while (i < str.length()) {
        if (i > palLen && str[i-palLen-1] == str[i]) {
            palLen += 2; i++; continue;
        }
        res.push_back(palLen);
        s = res.size()-2;
        e = s-palLen;
        bool b = true;
        for (j=s; j>e; j--) {
            d = j-e-1;
            if (res[j] == d) { palLen = d; b = false;
                break; }
            res.push_back(min(d, res[j]));
        }
        if (b) { palLen = 1; i++; }
    }
    res.push_back(palLen);
    lLen = res.size();
    s = lLen-2;
    e = s-(2*str.length()+1-lLen);
    for (i=s; i>e; i--) { d = i-e-1; res.push_back(min(d
        , res[i])); }
    return res;
}

```

## 6.4 Convex Hull Trick

```

struct Line {
    long long m, b;
    mutable function<const Line*> succ;
    bool operator<(const Line& rhs) const {
        if (rhs.b != -(1ll<<62)) return m > rhs.m;
        // < for max
        const Line* s = succ();
        if (!s) return 0;
        return b-s->b > (s->m -m)*rhs.m; // <
        // for max
    }
};

struct HullDynamic : public multiset<Line> {
    bool bad(iterator y) {
        auto z = next(y);
        if(y==begin()) {
            if(z==end()) return 0;
            return y->m == z->m && y->b >= z->b; // <= for max
        }
        auto x = prev(y);
        if (z == end()) return y->m == x->m && y->b >= x->b; // <= for max
        return (x->b - y->b)*1.0*(z->m - y->m)
            >= (y->b - z->b)*1.0*(y->m - x->m);
    }
    void insert_line(long long m, long long b) {
        auto y = insert({ m, b });
        y->succ = [=] { return next(y) == end()
            ? 0 : &*next(y); };
        if (bad(y)) { erase(y); return; }
        while (next(y) != end() && bad(next(y)))
            erase(next(y));
    }
}

```

```

        while (y != begin() && bad(prev(y)))
            erase(prev(y));
    }
    long long eval(long long x) {
        auto l = *lower_bound((Line){x, -(1ll
            <<62)});
        return l.m * x + l.b;
    }
};

```

## 6.5 Dynamic Programming(DnC)

```

long long dp[21][100005];
void cost(int x, int y);
void computeDP(int idx, int jleft, int jright, int kleft,
    int kright) {
    if(jleft > jright) return;
    int jmid = (jleft + jright) / 2;
    int bestk = jmid;
    for(int k = kleft; k <= min(kright, jmid); ++k) {
        cost(k, jmid);
        if(dp[idx-1][k-1] + tot < dp[idx][jmid])
            dp[idx][jmid] = dp[idx-1][k-1] + tot,
            bestk = k;
    }
    computeDP(idx, jleft, jmid-1, kleft, bestk);
    computeDP(idx, jmid+1, jright, bestk, kright);
}
int main() {
    for(int i = 0; i <= k; ++i)
        for(int j = 0; j <= n; dp[i][j] = 1e17);
    dp[0][0] = 0;
    for(int i = 1; i <= k; ++i)
        computeDP(i, 1, n, 1, n);
    cout << dp[k][n];
}

```

## 6.6 Longest increasing subsequence

```

// Given a list of numbers of length n, this routine
// extracts a
// longest increasing subsequence.
//
// Running time: O(n log n)
//
// INPUT: a vector of integers
// OUTPUT: a vector containing the longest increasing
// subsequence

typedef vector<int> VI;
typedef pair<int, int> PII;
typedef vector<PII> VPII;
#define STRICTLY_INCREASNG
VI LongestIncreasingSubsequence(VI v) {
    VPII best;
    VI dad(v.size(), -1);
    for (int i = 0; i < v.size(); i++) {

```

```

#ifdef STRICTLY_INCREASNG
        PII item = make_pair(v[i], 0);
        VPII::iterator it = lower_bound(best.begin(), best.
            end(), item);
        item.second = i;
    #else
        PII item = make_pair(v[i], i);
        VPII::iterator it = upper_bound(best.begin(), best.
            end(), item);
    #endif
    if (it == best.end()) {
        dad[i] = (best.size() == 0 ? -1 : best.back().
            second);
        best.push_back(item);
    } else {
        dad[i] = it == best.begin() ? -1 : prev(it)->
            second;
        *it = item;
    }
}
VI ret;
for (int i = best.back().second; i >= 0; i = dad[i])
    ret.push_back(v[i]);
reverse(ret.begin(), ret.end());
return ret;
}

```

## 6.7 Dates

```

// Months are expressed as integers from 1 to 12, Days
// are expressed
// as integers from 1 to 31, and Years are expressed as
// 4-digit
// integers.
string dayOfWeek[] = {"Mon", "Tue", "Wed", "Thu", "Fri",
    "Sat", "Sun"};

// converts Gregorian date to integer (Julian day number
// )
int dateToInt (int m, int d, int y) {
    return
        1461 * (y + 4800 + (m - 14) / 12) / 4 +
        367 * (m - 2 - (m - 14) / 12 * 12) / 12 -
        3 * ((y + 4900 + (m - 14) / 12) / 100) / 4 +
        d - 32075;
}

// converts integer (Julian day number) to Gregorian
// date: month/day/year
void intToDate (int jd, int &m, int &d, int &y) {
    int x, n, i, j;
    x = jd + 68569;
    n = 4 * x / 146097;
    x -= (146097 * n + 3) / 4;
    i = (4000 * (x + 1)) / 1461001;
    x -= 1461 * i / 4 - 31;
    j = 80 * x / 2447;
    d = x - 2447 * j / 80;
    x = j / 11;
    m = j + 2 - 12 * x;
    y = 100 * (n - 49) + i + x;
}

```

```

}
// converts integer (Julian day number) to day of week
string intToDay (int jd){
    return dayOfWeek[jd % 7];
}

```

## 6.8 Knuth-Morris-Pratt

```

typedef vector<int> VI;
void buildPi(string& p, VI& pi){
    pi = VI(p.length());
    int k = -2;
    for(int i = 0; i < p.length(); i++) {
        while(k >= -1 && p[k+1] != p[i])
            k = (k == -1) ? -2 : pi[k];
        pi[i] = ++k;
    }
}
int KMP(string& t, string& p){
    VI pi;
    buildPi(p, pi);
    int k = -1;
    for(int i = 0; i < t.length(); i++) {
        while(k >= -1 && p[k+1] != t[i])
            k = (k == -1) ? -2 : pi[k];
        k++;
        if(k == p.length() - 1) {
            // p matches t[i-m+1, ..., i]
            cout << "matched at index " << i-k << ": ";
            cout << t.substr(i-k, p.length()) << endl;
            k = (k == -1) ? -2 : pi[k];
        }
    }
    return 0;
}
int main(){
    string a = "AABAACAADAABAABA", b = "AABA";
    KMP(a, b); // expected matches at: 0, 9, 12
}

```

## 6.9 2-SAT

```

struct TwoSat {
    int n;
    vector<vector<int>> adj, radj, scc;
    vector<int> sid, vis, val;
    stack<int> stk;
    int scnt;
    // n: number of variables, including negations

```

```

TwoSat(int n): n(n), adj(n), radj(n), sid(n), vis(n),
    val(n, -1) {}
// adds an implication
void impl(int x, int y) { adj[x].push_back(y); radj[y]
    .push_back(x); }
// adds a disjunction
void vee(int x, int y) { impl(x^1, y); impl(y^1, x); }
// forces variables to be equal
void eq(int x, int y) { impl(x, y); impl(y, x); impl(x
    ^1, y^1); impl(y^1, x^1); }
// forces variable to be true
void tru(int x) { impl(x^1, x); }

void dfs1(int x) {
    if (vis[x]++) return;
    for (int i = 0; i < adj[x].size(); i++)
        dfs1(adj[x][i]);
    stk.push(x);
}
void dfs2(int x) {
    if (!vis[x]) return; vis[x] = 0;
    sid[x] = scnt; scc.back().push_back(x);
    for (int i = 0; i < radj[x].size(); i++)
        dfs2(radj[x][i]);
}
// returns true if satisfiable, false otherwise
// on completion, val[x] is the assigned value of
// variable x
// note, val[x] = 0 implies val[x^1] = 1
bool two_sat() {
    scnt = 0;
    for (int i = 0; i < n; i += 2)
        if (sid[i] == sid[i+1]) return false;
    vector<int> must(scnt);
    for (int i = 0; i < scnt; i++)
        for (int j = 0; j < scc[i].size(); j++){
            val[scc[i][j]] = must[i];
            must[sid[scc[i][j]^1]] = !must[i];
        }
    return true;
}
};

```