

COL380

Introduction to  
Parallel & Distributed Programming

# Agenda

- Sample clock
- Basic synchronization primitives and their properties

# Synchronization

- Do Operation  $X$  at time  $T$

## Synchronization

- Do Operation  $X$  at time  $T$
- Do we need a precise notion of time to make progress?
  - ➔ Always increasing
  - ➔ Shared view or individual view?


## Synchronization

- Do Operation  $X$  at time  $T$
- Do we need a precise notion of time to make progress?
  - ➔ Always increasing
  - ➔ Shared view or individual view?
- Basic synchronization
  - ➔ Two (or a set of) events should happen together
  - ➔ Any two (from a set of) events should NOT happen together
  - ★ Event  $A$  should happen after event  $B$




## Synchronization

- Do Operation  $X$  at time  $T$
- Do we need a precise notion of time to make progress?
  - Always increasing
  - Shared view or individual view?
- Basic synchronization
  - Two (or a set of) events should happen together
  - Any two (from a set of) events should NOT happen together
  - ★ Event  $A$  should happen after event  $B$




## Synchronization

- Do Operation  $X$  at time  $T$
- Do we need a precise notion of time to make progress?
  - Always increasing
  - Shared view or individual view?
- Basic synchronization
  - Two (or a set of) events should happen together
  - Any two (from a set of) events should NOT happen together
  - ★ Event  $A$  should happen after event  $B$



## Synchronization


- Do Operation  $X$  at time  $T$
- Do we need a precise notion of time to make progress?
  - Always increasing
  - Shared view or individual view?
- Basic synchronization
  - Two (or a set of) events should happen together
  - Any two (from a set of) events should NOT happen together
  - ★ Event  $A$  should happen after event  $B$





## Synchronization

- Do Operation  $X$  at time  $T$
- Do we need a precise notion of time to make progress?
  - Always increasing
  - Shared view or individual view?
- Basic synchronization
  - Two (or a set of) events should happen together
  - Any two (from a set of) events should NOT happen together
  - ★ Event  $A$  should happen after event  $B$



Stop and Go

# Causal Ordering

- Define a partial order
  - Causality:  $A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$
  - Inverse is not required to be true

# Causal Ordering

- Define a partial order

→ Causality:  $A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$     Same as:  $\text{Time}(A) < \text{Time}(B) \Rightarrow B \nrightarrow A$

→ Inverse is not required to be true    Means they can be concurrent

# Causal Ordering

- Define a partial order

→ Causality:  $A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$     Same as:  $\text{Time}(A) < \text{Time}(B) \Rightarrow B \nrightarrow A$

→ Inverse is not required to be true    Means they can be concurrent

Strong causality:  $A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B) \ \&\& \ \text{Time}(A) < \text{Time}(B) \Rightarrow A \rightarrow B$



# Causal Ordering

- Define a partial order

- Causality:  $A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$     Same as:  $\text{Time}(A) < \text{Time}(B) \Rightarrow B \nrightarrow A$

- Inverse is not required to be true    Means they can be concurrent

Strong causality:  $A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B) \ \&\& \ \text{Time}(A) < \text{Time}(B) \Rightarrow A \rightarrow B$

- Clocks at least must support partial ordering of events

- Can construct total ordering (e.g., by using Process-ID to break tie)

- Possible to build “counters” that can support total order (strong causality)

## Logical-Clock

- Each entity (process) maintains a counter
  - ➔ increments every 'event,' at its own pace

$$A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$$

## Logical-Clock

- Each entity (process) maintains a counter
  - ➔ increments every 'event,' at its own pace
- Interaction between entities is through messages
  - ➔ Data + counter

$$A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$$

# Logical-Clock

- Each entity (process) maintains a counter
  - ➔ increments every 'event,' at its own pace
- Interaction between entities is through messages
  - ➔ Data + counter
- On message receipt:
  - ➔ If recipient counter < received counter
    - ▶ Increase local counter to received counter
    - ▶ Receive is an event, so increment by one

$$A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$$



## Logical-Clock [Lamport's Timestamp algorithm]

- Each entity (process) maintains a counter
  - ➔ increments every 'event,' at its own pace
- Interaction between entities is through messages
  - ➔ Data + counter
- On message receipt:
  - ➔ If recipient counter < received counter
    - ▶ Increase local counter to received counter
    - ▶ Receive is an event, so increment by one

$$A \rightarrow B \Rightarrow \text{Time}(A) < \text{Time}(B)$$

# Synchronization Concepts

- Synchronization primitives
  - ➔ Lock/Mutex, Condition variables, Monitor
  - ➔ Atomics, Critical section, Barrier, Wait, Order
- Properties of Synchronization
  - ➔ Safety, Liveness
  - ➔ Blocking, Starvation-free, Deadlock-free, Lockfree, Waitfree
- Central authority?
  - ➔ OS scheduler, Runtime

- Object: lock
- Actions: Lock and Unlock

# Lock

```
omp_lock_t *lockA;  
omp_init_lock (lockA);  
...  
omp_destroy_lock (lockA);
```

Critical Section

- Object: lock
- Actions: Lock and Unlock

```
OperateA(object *A)  
{  
    omp_set_lock(lockA);  
    Operate_Exclusively(A)  
    omp_unset_lock (lockA);  
}
```



# Lock

```
omp_lock_t *lockA;  
omp_init_lock (lockA);  
...  
omp_destroy_lock (lockA);
```

Critical Section

```
OperateA(object *A)  
{  
    omp_set_lock(lockA);  
    Operate_Exclusively(A)  
    omp_unset_lock (lockA);  
}
```

- Object: lock
- Actions: Lock and Unlock

- ➔ Reentrant
- ➔ Recursive
- ➔ Timed
- ➔ Exclusive
- ➔ Shared

```
OperatePlus(object *A)  
{  
    omp_set_lock(lockA);  
    if(! A->initalized())  
        OperateA(A);  
    omp_unset_lock(lockA)  
}
```

# Lock

```
omp_lock_t *lockA;  
omp_init_lock (lockA);  
...  
omp_destroy_lock (lockA);
```

Critical Section

- Object: lock
- Actions: Lock and Unlock

```
OperateA(object *A)  
{  
    omp_set_lock(lockA);  
    Operate_Exclusively(A)  
    omp_unset_lock (lockA);  
}
```

- ➔ Reentrant
- ➔ Recursive
- ➔ Timed
- ➔ Exclusive
- ➔ Shared

```
OperatePlus(object *A)  
{  
    omp_set_lock(lockA);  
    if(! A->initalized())  
        OperateA(A);  
    omp_unset_lock(lockA)  
}
```

See

omp\_test\_lock\_t  
omp\_init\_test\_lock  
omp\_set\_test\_lock  
omp\_unset\_test\_lock

# Lock

See:

```
int omp_test_lock (omp_lock_t *);
```

```
omp_lock_t *lockA;
```

```
_lock (lockA);
```

```
omp_destroy_lock (lockA);
```

Critical Section

- Object: lock
- Actions: Lock and Unlock

```
OperateA(object *A)
```

```
{
```

```
    omp_set_lock(lockA);
```

```
    Operate_Exclusively(A)
```

```
    omp_unset_lock (lockA);
```

➔ Reentrant

➔ Recursive

➔ Timed

➔ Exclusive

➔ Shared

```
OperatePlus(object *A)
```

```
{
```

```
    omp_set_lock(lockA);
```

```
    if(! A->initalized())
```

```
        OperateA(A);
```

```
    omp_unset_lock(lockA)
```

```
}
```

See

omp\_test\_lock\_t

omp\_init\_test\_lock

omp\_set\_test\_lock

omp\_unset\_test\_lock



- Block of code
- Criticality context



# Critical Section

- Block of code
- Criticality context

```
#pragma omp critical (a_name)
{
    mutually_excluded_code();
}
```

# Condition Variable

- Raise the condition
- Wait for a condition to 'hold'

```
Produce();  
acv.notify_one();
```

```
std::condition_variable acv;  
...  
  
std::unique_lock<std::mutex> alock(amutex);  
acv.wait(alock);  
.. Condition Holds Now ..  
Consume();
```

- A group of entities
- Wait for all

```
ParallelInput();  
#pragma omp barrier  
ParallelProcess();  
#pragma omp barrier  
ParallelOutput();
```

- Logical clocks
  - ➔ Implementation
- Synchronization primitives
  - ➔ Lock, Critical section, Condition variables, Barrier