Aayush Kumar

From 21M to 68M ops/s: two changes to a C++ order book


29 October 2026. Numbers from lob-engine at 2178cef (https://github.com/aayxshkumar/lob-engine/tree/2178cef).

I'm building lob-engine (https://github.com/aayxshkumar/lob-engine), a limit order book in C++20, to learn how matching engines are made fast. This is a log of the first two optimisations, with the numbers at each step, the step that made things slower, the benchmark that turned out to be too kind, and a replay of 20 minutes of real exchange data.

Version	Change	Mixed workload M ops/s	Add + cancel ns
v0	`std::map` price levels	21.2	32.6
v1	flat arrays + a bitset	34.3	28.5
v2	open-addressing id table	**67.5**	**8.6**

3.2× on the mixed workload, 3.8× on add + cancel. 1M seeded operations: 55% limit orders near the mid, 40% cancels, 5% market orders. Apple M4, Apple clang 17, −O3, median of 3. v1 at ffe9956 (https://github.com/aayxshkumar/lob-engine/tree/ffe9956), book sized for 1M; v0 and v2 for 262,144. Receipts: claims ledger.

Sections: v0, v1, v2, real data, what went wrong, reproduce it, what I can't measure yet, revisions.



v2 is 3.2× v0 with sequential ids, and 3.0× with random-looking ones. Filled bars: ids 1, 2, 3…; outlined: the same ids scrambled. Same runs as the table. Drawn by `tools/plot_steps.py` from the README at 2178cef.

v0: the baseline, and how I know it's right

An order book keeps resting buy and sell orders sorted by price, and orders at the same price in arrival order. An incoming order that crosses the spread trades against the best opposite price first, oldest order first.

v0 is the textbook version. Each side is a `std::map` from price to a level. Orders come from a pre-allocated pool, and each level chains its orders in an intrusive doubly linked list, so resting an order never allocates and a cancel is O(1) once the order is found. Finding it is a `std::unordered_map` from order id to pool slot.

Before optimising anything I wanted a way to tell whether a faster version was still correct. The test suite includes a deliberately naive reference book (plain vectors, linear scans), and a differential test pushes 20,000 random operations through both, comparing every trade and the whole book after every step.

My first version of that test passed with a bug planted in it. The random orders crossed the spread so often that queues never formed, so time-priority bugs had nothing to break. Biasing the flow towards passive orders and adding explicit "increase size at the same price" modifies fixed it. Since then I plant bugs by hand to check the tests catch them; it's 16 so far, and the tests catch all of them. You can step through five of them on the home page.

v1: flat arrays, which made it slower first

Exchanges limit how far prices can move, so the price levels can live in a flat array indexed by tick: finding a level becomes one subtraction instead of a tree walk. I gave each side an array covering 65,536 ticks and cached the index of the best level.

The cost moves to the moment the best level empties, when the next one has to be found. I added a benchmark for the case that should hurt: 50 asks spaced far apart, cleared one at a time by market orders.

Sweep of 50 levels, μs	v0 `std::map`	v1 linear scan	v1 + bitset
1-tick gaps	2.0	22.5	1.5
100-tick gaps	2.0	3.0	1.6
1,000-tick gaps	2.0	14.8	**1.85**

The 22.5μs was a bug, not the gap. `BM_SparseSweep`: 50 asks, cleared one level at a time by market orders. v2 takes 1.28μs at 1,000-tick gaps. Apple M4, Apple clang 17, `-O3`, median of 3 runs. README at 2178cef (https://github.com/aayxshkumar/lob-engine/tree/2178cef).

The array was slower than the map, but the first row didn't make sense: with 1-tick gaps there's almost nothing to scan, yet it was the slowest. The cost didn't depend on the gap at all. When the last ask was cleared, the scan walked the whole 65,536-tick band looking for an ask that didn't exist. The book already counted its levels, so it now checks the count and skips the scan when a side is empty.

That left real gaps. The fix is one bit per price level, set while the level has orders. Finding the next non-empty level then checks 64 levels per step with `std::countr_zero`, which beats following `std::map` pointers even with 1,000 empty ticks between levels.

v2: the benchmark was flattering `std::unordered_map`

After v1, the largest cost left was looking orders up by id. Every add checks for a duplicate, every cancel looks the order up, and every fill removes one. `std::unordered_map` allocates a node per order, and each lookup follows a bucket pointer and then a node pointer.

Before replacing it I looked at what the benchmark fed it. The generator numbered orders 1, 2, 3 and so on. That's unusually kind to `unordered_map`: with libc++, consecutive ids land in consecutive buckets, and

nodes allocated one after another tend to sit close together in memory. Real venues send ids that look random. Scrambling the same ids with a bijective mixer (the splitmix64 finaliser, so they stay unique) cost v1 a quarter of its throughput, from 34.4M to 25.7M ops/s.

> The finaliser is a bijection on 64-bit integers, so every id maps to a different id: the scrambled run has the same orders, prices and sizes, and only the id bits change.

The replacement, `IdTable` (https://github.com/aayxshkumar/lob-engine/blob/9d18ba6/include/lob/id_table.hpp), is about 100 lines:

A flat array of 16-byte entries, each an order id and a pool slot.

Linear probing, kept at most half full, so a lookup usually touches one or two neighbouring entries.

Fibonacci hashing: multiply the id by $2^{64}/\varphi$ and keep the top bits. One multiply, and sequential ids still spread out.

> $2^{64}/\varphi$ rounded down is 0x9E3779B97F4A7C15. Keeping the top bits of the product, not the bottom, is what spreads consecutive ids apart.

Backward-shift deletion instead of tombstones. When an entry is removed, later entries in the same run move back to fill the hole, so a book that runs all day doesn't fill up with dead entries.

A fixed capacity, taken from the order pool, so it never rehashes.

`include/lob/id_table.hpp` at 9d18ba6 (https://github.com/aayxshkumar/lob-engine/blob/9d18ba6/include/lob/id_table.hpp#L62-L83), lines 62–83

```
bool erase(OrderId id) {
    std::size_t i = home(id);
    for (;; i = (i + 1) & mask_) {
        if (entries_[i].value == kEmpty) return false;
        if (entries_[i].key == id) break;
    }
    // Backward shift: walk the rest of the run and pull back any entry
    // whose home position is not strictly between the hole and itself
    // (cyclically), i.e. any entry the hole would cut off from its home.
    std::size_t hole = i;
    for (std::size_t j = (i + 1) & mask_; entries_[j].value != kEmpty; j = (j + 1) & mask_) {
        const std::size_t h = home(entries_[j].key);
        const bool reachable = hole <= j ? (hole < h && h <= j) : (hole < h || h <= j);
        if (!reachable) {
            entries_[hole] = entries_[j];
            hole = j;
        }
    }
    entries_[hole].value = kEmpty;
    --size_;
    return true;
}
```

Backward shift is easy to get subtly wrong when a run wraps past the end of the array, so the table has its own differential test against `std::unordered_map`: 20 seeds of 20,000 inserts and erases in a 16-slot table, where nearly every run is long and many wrap. I planted four bugs in the deletion code and it caught all four. A fifth survived, and it took me a minute to see why: it swapped two checks in a way that can't change the result. That's an equivalent mutant, not a gap in the tests.

The first v2 result was confusing. With sequential ids it was no faster than v1: 34.4M against 34.4M ops/s. The benchmark sized the book for one million orders, so the id table had 2^{21} slots, 32 MB, far bigger than the cache, and almost every lookup missed. The workload never has more than about 109,000 live orders. Sized for 262,144, the table has 2^{19} slots, 8 MB, and v2 is about twice as fast as v1 with either kind of id.

Book sized for	Id-table slots	Memory	v2 against v1
1,000,000 orders	2^{21}	32 MB	no faster with sequential ids
262,144 orders	2^{19}	8 MB	about 2×, with either kind of id

The table's memory follows the configured capacity, not the live orders. Slots are twice the capacity, rounded up to a power of two (`id_table.hpp` line 34 (https://github.com/aayxshkumar/lob-engine/blob/9d18ba6/include/lob/id_table.hpp#L34)). Sizes and speeds from the README at 2178cef.

So the honest version of the result comes with a condition: a fixed table's memory follows the capacity you configure, not the orders you have. Size it for the peak you expect, not the biggest number you can think of.

On real data

A seeded generator is easy to fool yourself with, as the ids showed. So I recorded 20 minutes of Binance's public BTCUSDT feed (11,992 depth updates and 71,328 trades) with a small recorder (https://github.com/aayxshkumar/lob-engine/blob/9014c87/tools/record_binance.py) that uses only Python's standard library. It follows Binance's procedure for keeping a local book and stops at the first sequence gap.

Binance publishes price levels, not individual orders, so the replay has to invent orders that explain each change. A level that grows gets a new order for the difference. A level that shrinks loses size from its newest orders. A trade becomes an incoming order at the trade price, which fills the oldest orders there. After every update, the replay checks the book's top 10 levels on each side against the exchange's.

> This is level-2 data: one total per price, no orders. Queue positions in the replay are inferred from size changes, so they are a model of the queue, not the exchange's.

The first version of that check found a bug in my translation. A single update can clear an ask and place a bid at the same price. Applying the bid first crosses the stale ask and invents a trade that never happened, so each update now applies its reductions before its additions.

20 minutes of BTCUSDT	v0 `std::map`	v2 + id table
Throughput, M ops/s	15.9	**81.9**

v2 replays the recording 5.2× as fast as v0. 562,850 order operations: 53.5% adds, 40.3% cancels, 6.2% size reductions. Median of 5 runs of `lob_replay`, Apple M4, Apple clang 17. Recorded 29 October 2026, 02:30–02:50 UTC; the recording isn't published. Commit 9014c87 (https://github.com/aayxshkumar/lob-engine/tree/9014c87).

That's 5.2×, more than on the synthetic workload, though I wouldn't read much into the difference: at most 4,203 orders were resting at once, so the whole book fits in cache. The mix was close to what the

generator produces.

The top of book matched the exchange after 99.93% of updates. The other 0.07% come from the feed, not the book. Binance doesn't sequence trades against depth updates, so a trade sometimes arrives after the update that already includes it, and the replay removes that size twice until the next update for the level corrects it. Replaying the same recording without trades matches after every update.

What went wrong, and what caught it

What went wrong	What caught it
A scan of the full 65,536-tick band	The sparse-book benchmark
Sequential ids flattering `unordered_map`	The same ids, scrambled
A 32 MB id table	v2 not speeding up with sequential ids
A bid applied before the ask it replaced	The top-10 check in the replay
The first differential test passing with a bug	Planting bugs on purpose

Reproduce it

The four commands from the README. The last two need your own recording, since recordings aren't committed.

`README.md` at 2178cef (https://github.com/aayxshkumar/lob-engine/blob/2178cef/README.md)

Copy

```
cmake -S . -B build -DCMAKE_BUILD_TYPE=Release && cmake --build build -j
./build/lob_tests && ./build/lob_bench && ./build/lob_latency
python3 tools/record_binance.py BTCUSDT 1200 data/btcusdt.lobrec
./build/lob_replay data/btcusdt.lobrec
```

Per-number commands, at pinned commits, are in the claims ledger.


If your numbers differ from mine, I'd like to see them, with the machine and compiler: aayushkumr25@gmail.com (mailto:aayushkumr25@gmail.com).

What I can't measure yet

These are throughput numbers. Latency percentiles are harder on this machine: on Apple Silicon `steady_clock` ticks every 41.7 ns, so the fastest operations measure as zero or one tick.

> `sysctl hw.tbfrequency` prints 24000000 on this M4: one tick is 1/24,000,000 of a second. Victor Zverovich (https://vitaut.net/posts/2023/measuring-clock-precision/) measured about 41 ns on an M1.

My latency tool measures the clock first and warns when it's too coarse, and it reports tick counts rather than pretending to have nanoseconds.



v2 finishes 55.5% of adds within the first clock tick; v0, 16.4%. Share of 1M `add_limit` calls that read at most k ticks. p99 is 2 ticks for both; p99.9 is 14 ticks for v0 and 3 for v2. Data: m4-quantiles.csv at 9d18ba6, binned by `round(ns / 41.67)` in `tools/plot_cdf.py`.

`add_limit` readings at or under	v0, %	v2, %
0 ticks	16.4	55.5
1 tick	91.6	95.9
2 ticks	99.0	99.7
3 ticks	99.7	99.9

Every reading is a whole number of ticks; an earlier version of this chart drew two steps per tick (see Revisions).

Next I'm running on Linux with a TSC-based timer and `perf stat`, to get real percentiles and cache-miss counts for each version.

The code, the benchmarks and the recorder are at github.com/aayxshkumar/lob-engine (https://github.com/aayxshkumar/lob-engine). If you see something I've measured wrong, I'd like to hear about it.

Revisions

2026-10-29. First version.

2026-10-29. The latency chart now bins readings by clock tick. The first plot drew two steps per tick, because `m4-quantiles.csv` writes one tick as 41 or 42 ns. It now bins by `round(ns / 41.67)` and labels the axis in ticks.

2026-10-29. Removed a sentence that put v2's gain with random ids, while the table was oversized, at 40%. No committed run gives that figure; the paragraph now uses the README's numbers.

2026-10-29. Corrected the sizing note. v1's 34.3M was measured at ffe9956 (https://github.com/aayxshkumar/lob-engine/commit/ffe9956), whose benchmark sizes the book for all 1M operations; v0 and v2 are sized

for 262,144.

2026-10-29. The commit message of 0a8bdc2 (https://github.com/aayxshkumar/lob-engine/commit/0a8bdc2) says 20.1M → 34.0M ops/s. Those were the README's v0 and v1 medians until 9d18ba6 (https://github.com/aayxshkumar/lob-engine/commit/9d18ba6), which gives 21.2M and 34.3M. The numbers here are the later ones.