

IdealBase™

Style	IdealBase™ (.080")	IdealBase™ (.100")	IdealBase™ (.118")
Construction	Thermoplastic Rubber - TP	Thermoplastic Rubber - TP	Thermoplastic Rubber - TP
Classification	ASTM F1861, Type TP, Group 1	ASTM F1861, Type TP, Group 1	ASTM F1861, Type TP, Group 1
Wallbase Thickness	.125 inches (3.2 mm)	.125 inches (3.2 mm)	.125 inches (3.2 mm)
Wallbase Height	6.25 inches (159 mm)	6.25 inches (159 mm)	6.25 inches (159 mm)
Toe Thickness	.080 inches (2.03 mm)	.100 inches (2.54 mm)	.118 inches (3.00 mm)
Toe Length	2.00 inches	2.00 inches	2.00 inches
Sizes	8' lengths (2.43 m)	8' lengths (2.43 m)	8' lengths (2.43 m)
Packaging	6 pieces per carton in 8' lengths	6 pieces per carton in 8' lengths	6 pieces per carton in 8' lengths
Colors	10	10	10
Adhesive	MR-101, Double-sided Tape	MR-101, Double-sided Tape	MR-101, Double-sided Tape
Seam Method	Heat weld to vinyl and rubber, direct bond to Legato flooring Mannington Cold Weld for IdealBase seams on wall	Heat weld to vinyl and rubber, direct bond to Legato flooring Mannington Cold Weld for IdealBase seams on wall	Heat weld to vinyl and rubber, direct bond to Legato flooring Mannington Cold Weld for IdealBase seams on wall
Color Application - Seams	Quantum Guard Elite® Colored/Clear Pen	Quantum Guard Elite® Colored/Clear Pen	Quantum Guard Elite® Colored/Clear Pen
Testing			
HUD/FHA	Meets / Exceeds		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm2		
Smoke Density (ASTM E662)	Passes - < 450		
Environmental Data			
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010		
Product Declaration	HPD		
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
Manufacturing	Eustis, FL (USA)		
Warranty			
	Limited 5-Year Commercial Warranty		