

# Subqueries

## TABLE OF CONTENTS

1. Subqueries
2. Subqueries in IN clause
3. Subqueries in Where clause
4. All and Any
5. Co-related Subqueries
6. Subqueries in from clause
7. Exists



Notes

14<sup>th</sup> Hard day challenge :

1. Assignments + Revision
2. Backlog (Assignments of prev. session)
3. Additional Questions



# Subqueries

- This is very intuitive way of writing queries.
- Breakdown bigger problems into smaller ones.
- Will use result of smaller problems to get final answer.

## Students

id	name	b_id	psp
1	John	Null	80
2	Jane	1	90
3	Jim	2	85
4	Jenny	3	95
5	Jack	2	78

→ psp of s\_id = 90

**< Question > :** Find all the students having psp > (psp of s\_id\_2).

Step-1 : Find psp of student with s\_id = 2 → (x) → 90

Step-2 : Find all students with psp > x



**Query-1** : Code for x

```
select psp  
from students  
where s-rid = 2 ;
```

→ x

**Query-2** : Main query

```
select *  
from students  
where psp > (select psp  
              from students  
              where s-rid = 2 ) ;
```



## Students

id	name	b_id	psp
1	John	Null	80
2	Jane	1	90
3	Jim	2	85
4	Jenny	3	95
5	Jack	2	78

$\min(\text{psp}) \rightarrow 2 \rightarrow \underline{78} \rightarrow x$

**< Question > :** Find data of all the students having psp > (min psp of b\_id\_2).

Step-1 : Find min psp of b\_id = 2  $\rightarrow (x)$

Step-2 : Find all students having psp > x




**Query-1 :** Query to find x

```
select min(psp)
from students
where bnd = 2 ;
```

→ x

**Query-2 :** Final query

```
select *
from students
where psp > (select min(psp)
from students
where bnd = 2 ) ;
```



  
Films

name	release_year	rental_rate
Hera Pheri	2008	250
Robot	2009	300
Welcome	2011	420
Bahubali	2016	250

  
Films

name	release_year	rental_rate
Hera Pheri	2008	250
Robot	2009	300
Welcome	2011	420
Bahubali	2016	250

**< Question > :** Find all years where average rental\_rate > (The global average rental rate).



# Subqueries and IN Clause

Rows	Column	Output
1	1	Single value
1	m	Single row
m	1	Single col
m	m	Table

id	Name	is_student	is_TA
1	Gaurav	1	1
2	Rohit	1	0
3	Pravallika	1	0
4	Krish Na	1	1
5	Nandini	1	0
6	Rohit	0	1

Users →

```
select name
from users
where is_student = 1
and is_TA = 1;
```

**< Question > :** Get names of all the students who are ( names of TA as well )

Step-1 : Get names of all TA. ( Gaurav, Krishna, Rohit ) → x

Step-2 : Check whether name of a student is a name of TA as well.



&lt;/&gt; Code -1

```
select distinct name  
from users  
where is_TA = 1 ;
```



&lt;/&gt; Code -2

```
select name  
from users  
where is_student = 1 and  
name IN (select distinct name  
from users  
where is_TA = 1) ;
```





## Subqueries inside from clause

< **Question** > : Find data of all the students where  $psp > (\min(psp) \text{ among } avg(psp) \text{ of every batch})$ .

### Students

id	name	b_id	psp
1	John	<del>Null</del> 1	80
2	Jane	1	90
3	Jim	2	85
4	Jenny	3	95
5	Jack	2	78

$$1. \text{ avg}(psp) = 85$$

$$2. \text{ avg}(psp) = 81.5 \rightarrow y$$

$$3. \text{ avg}(psp) = 95$$

### Explanation :

1. Find  $\text{avg}(psp)$  of every batch.  $\rightarrow x$

2. Find  $\min(psp)$  among  $x \rightarrow y$

3. Find all students with  $psp > y$

Note : Whenever we use subquery inside from clause, always use aliasing.



# All and Any

Note: In operator is just to check membership.

**< Question > :** Find data of all the students where psp  $\geq$  (min(psp) of student in every batch).

## Students

id	name	b_id	psp
1	John	<del>Null</del> 1	80
2	Jane	1	90
3	Jim	2	85
4	Jenny	3	95
5	Jack	2	78

$$1. \min(\text{psp}) = 80$$

$$2. \min(\text{psp}) = 78$$

$$3. \min(\text{psp}) = 95$$

Comparing...



1. All

Comparing...



2. Any



## Co-related Subqueries

**< Question > :** Find data of all the students where psp > (avg(bsp) of their batch).

### Students

id	name	b_id	bsp
1	John	1	80
2	Jane	1	90
3	Jim	2	85
4	Jenny	3	95
5	Jack	2	78

' For Jane we need avg bsp of batch 1. For Jim batch 2..... '



**Conclusion :** For every batch\_id we need avg bsp of that batch to compare the value.



# Exists

**Students**

id	name	psp
1	Rahul	98
2	Rohit	95
3	Tarun	88

**Tas**

id	Name	student_id
1	Rahul	1
2	Mohit	Null
3	Sameer	Null

**< Question > :** Find all the students who are also TAs

**Example**

1. ' Does **RED** ball exists here? '



2. ' And here ? '



3. ' And what about in this one? '





- **Exist is used when output depends on just having > 0 values.**
- **Exist gives us faster results than IN clause.**

Now, we will write query using exist.