

rcclone does not ship a closed list of “all export variables.” Almost every long flag becomes an env var, plus a few special names that are not flags. Official rule: take `--long-option`, drop `--`, turn `-` into `_`, uppercase, prepend `RCLONE_`. Command-line flags override env vars; env vars override defaults. Confirm what was applied with `rcclone version -vv` or any command plus `-vv`.

Naming rules

Source	Env var
<code>--stats 5s</code>	<code>RCLONE_STATS=5s</code>
<code>--fast-list</code>	<code>RCLONE_FAST_LIST=true</code>
<code>--drive-use-trash</code>	<code>RCLONE_DRIVE_USE_TRASH=true</code>
<code>-v / --verbose</code>	<code>RCLONE_VERBOSE=1</code>
<code>-vv</code>	<code>RCLONE_VERBOSE=2</code>
config option on remote <code>secret</code>	<code>RCLONE_CONFIG_SECRET_<OPTION></code>
backend-wide crypt option	<code>RCLONE_CRYPT_PASSWORD</code>

Repeatable flags (`--exclude`, `--filter`, `--include`, ...) are CSV in one variable:

Bash
<pre>export RCLONE_EXCLUDE='*.tmp,*.bak' export RCLONE_FILTER='- *.iso,+ *'</pre>

Remote names used in `RCLONE_CONFIG_<NAME>_...` should be letters, digits, `_` only. `secret` works; `my-crypt / test.enc` do not map cleanly in a normal shell. Env-defined remotes are case-insensitive. You must set `RCLONE_CONFIG_<NAME>_TYPE`.

Special variables (not just flag aliases)

These are the ones people usually mean by “rcclone export variables.”

Variable	Purpose
RCLONE_CONFIG	Path to <code>rcclone.conf</code>
RCLONE_CONFIG_PASS	Password to decrypt an encrypted config (plaintext)
RCLONE_PASSWORD_COMMAND	Program that prints the config password
RCLONE_PASSWORD_CHANGE	Set to <code>1</code> by <code>rcclone</code> while changing the config password
RCLONE_CONFIG_DIR	Set by <code>rcclone</code> to the directory of the config file (usable in paths as <code>\${RCLONE_CONFIG_DIR}</code>)
_RCLONE_CONFIG_KEY_FILE	Internal; temp file for daemonized config key
HTTP_PROXY / HTTPS_PROXY / NO_PROXY	Standard proxy vars (lowercase also work)
USER / LOGNAME	Username fallbacks
TMPDIR / TMP / TEMP	Temp dirs; <code>--temp-dir</code> also writes these
AWS_ACCESS_KEY_ID / AWS_SECRET_ACCESS_KEY / AWS_SESSION_TOKEN / AWS_PROFILE	S3 when <code>env_auth=true</code>
AWS_ACCESS_KEY / AWS_SECRET_KEY	Older S3 aliases

Define a remote entirely from env

Bash

```
export RCLONE_CONFIG_SECRET_TYPE=crypt
export RCLONE_CONFIG_SECRET_REMOTE='/path/to/cipher'
export RCLONE_CONFIG_SECRET_FILENAME_ENCRYPTION=standard
export RCLONE_CONFIG_SECRET_DIRECTORY_NAME_ENCRYPTION=true
export RCLONE_CONFIG_SECRET_PASSWORD='<obscured>'
export RCLONE_CONFIG_SECRET_PASSWORD2='<obscured>'
rcclone ls secret:
```

Pattern: `RCLONE_CONFIG_ + remote name + _ + option`, all uppercase. Only options of that **immediate** backend apply. Nested credentials belong on the

options of that immediate backend apply. Nested credentials belong on the inner remote (RCLONE_CONFIG_GDRIVE_...) or on the backend-wide prefix (RCLONE_DRIVE_... , RCLONE_S3_...).

Common global flags as env vars

Performance / listing

- RCLONE_TRANSFERS
- RCLONE_CHECKERS
- RCLONE_FAST_LIST
- RCLONE_CHECK_FIRST
- RCLONE_TPSLIMIT
- RCLONE_TPSLIMIT_BURST
- RCLONE_MULTI_THREAD_STREAMS
- RCLONE_MULTI_THREAD_CUTOFF
- RCLONE_BUFFER_SIZE
- RCLONE_USE_MMAP
- RCLONE_TRACK_RENAMES
- RCLONE_TRACK_RENAMES_STRATEGY

Filters / size / age

- RCLONE_EXCLUDE , RCLONE_INCLUDE , RCLONE_FILTER
- RCLONE_EXCLUDE_FROM , RCLONE_INCLUDE_FROM , RCLONE_FILTER_FROM
- RCLONE_MAX_AGE , RCLONE_MIN_AGE
- RCLONE_MAX_SIZE , RCLONE_MIN_SIZE
- RCLONE_MAX_DEPTH
- RCLONE_IGNORE_CASE
- RCLONE_DELETE_EXCLUDED

Sync / copy behavior

- RCLONE_DRY_RUN
- RCLONE_INTERACTIVE

- RCLONE_IGNORE_EXISTING
- RCLONE_IGNORE_TIMES
- RCLONE_IGNORE_SIZE
- RCLONE_CHECKSUM
- RCLONE_SIZE_ONLY
- RCLONE_UPDATE
- RCLONE_BACKUP_DIR
- RCLONE_SUFFIX
- RCLONE_IMMUTABLE
- RCLONE_COMPARE_DEST
- RCLONE_COPY_DEST
- RCLONE_DELETE_BEFORE / RCLONE_DELETE_DURING / RCLONE_DELETE_AFTER
- RCLONE_MAX_DELETE , RCLONE_MAX_DELETE_SIZE
- RCLONE_MAX_TRANSFER , RCLONE_MAX_DURATION
- RCLONE_CUTOFF_MODE

Logging / UI

- RCLONE_VERBOSE (1 or 2)
- RCLONE_LOG_LEVEL (DEBUG , INFO , NOTICE , ERROR)
- RCLONE_LOG_FILE
- RCLONE_STATS , RCLONE_STATS_ONE_LINE , RCLONE_STATS_LOG_LEVEL
- RCLONE_PROGRESS , RCLONE_PROGRESS_WINDOW
- RCLONE_QUIET
- RCLONE_DUMP (e.g. headers)

Paths / config / cache

- RCLONE_CONFIG
- RCLONE_CACHE_DIR
- RCLONE_TEMP_DIR
- RCLONE_ASK_PASSWORD
- RCLONE_AUTO_CONFIRM

- RCLONE_PASSWORD_COMMAND

Network

- RCLONE_BIND
- RCLONE_TIMEOUT , RCLONE_CONTIMEOUT
- RCLONE_RETRIES , RCLONE_RETRIES_SLEEP
- RCLONE_LOW_LEVEL_RETRIES
- RCLONE_DISABLE_HTTP2
- RCLONE_CA_CERT , RCLONE_CLIENT_CERT , RCLONE_CLIENT_KEY
- RCLONE_NO_CHECK_CERTIFICATE
- RCLONE_USER_AGENT
- RCLONE_HEADER (CSV for repeats)

VFS / mount (when using `rcclone mount`)

- RCLONE_VFS_CACHE_MODE
- RCLONE_VFS_CACHE_MAX_AGE
- RCLONE_VFS_CACHE_MAX_SIZE
- RCLONE_VFS_CACHE_POLL_INTERVAL
- RCLONE_VFS_READ_CHUNK_SIZE
- RCLONE_VFS_WRITE_BACK
- RCLONE_DIR_CACHE_TIME
- RCLONE_ATTR_TIMEOUT
- RCLONE_UID , RCLONE_GID , RCLONE_UMASK
- RCLONE_ALLOW_OTHER , RCLONE_ALLOW_NON_EMPTY
- RCLONE_DAEMON

Serve (same rule as flags: `--user` → `RCLONE_USER` , `--pass` → `RCLONE_PASS` , `--addr` → `RCLONE_ADDR` , `--auth-key` → `RCLONE_AUTH_KEY` , ...)

Backend-wide families (apply to every remote of that type)

Form: RCLONE_<BACKEND>_<OPTION> .

Crypt (from the previous thread):

- RCLONE_CRYPT_REMOTE
- RCLONE_CRYPT_FILENAME_ENCRYPTION
- RCLONE_CRYPT_DIRECTORY_NAME_ENCRYPTION
- RCLONE_CRYPT_PASSWORD (obscured)
- RCLONE_CRYPT_PASSWORD2 (obscured)
- RCLONE_CRYPT_SHOW_MAPPING
- RCLONE_CRYPT_FILENAME_ENCODING
- RCLONE_CRYPT_SUFFIX
- RCLONE_CRYPT_NO_DATA_ENCRYPTION
- RCLONE_CRYPT_STRICT_NAMES

S3:

- RCLONE_S3_ACCESS_KEY_ID
- RCLONE_S3_SECRET_ACCESS_KEY
- RCLONE_S3_SESSION_TOKEN
- RCLONE_S3_REGION
- RCLONE_S3_ENDPOINT
- RCLONE_S3_PROVIDER
- RCLONE_S3_ENV_AUTH
- RCLONE_S3_ACL , RCLONE_S3_STORAGE_CLASS , RCLONE_S3_BUCKET_ACL
- RCLONE_S3_LOCATION_CONSTRAINT
- RCLONE_S3_SERVER_SIDE_ENCRYPTION , RCLONE_S3_SSE_KMS_KEY_ID

Drive:

- RCLONE_DRIVE_CLIENT_ID
- RCLONE_DRIVE_CLIENT_SECRET
- RCLONE_DRIVE_TOKEN
- RCLONE_DRIVE_SCOPE
- RCLONE_DRIVE_ROOT_FOLDER_ID

- RCLONE_DRIVE_TEAM_DRIVE
- RCLONE_DRIVE_USE_TRASH
- RCLONE_DRIVE_SHARED_WITH_ME

Local / SFTP / FTP / HTTP examples:

- RCLONE_LOCAL_ENCODING , RCLONE_LOCAL_NOUNC
- RCLONE_SFTP_HOST , RCLONE_SFTP_USER , RCLONE_SFTP_PORT , RCLONE_SFTP_PASS , RCLONE_SFTP_KEY_FILE , RCLONE_SFTP_KEY_PEM
- RCLONE_FTP_HOST , RCLONE_FTP_USER , RCLONE_FTP_PORT , RCLONE_FTP_PASS , RCLONE_FTP_TLS
- RCLONE_HTTP_URL

Every backend page on rclone.org lists Env Var: next to each option. There are dozens of backends and hundreds of options; listing every RCLONE_AZUREBLOB_... / RCLONE_B2_... / RCLONE_DROPBOX_... name here would just duplicate those pages.

How to dump “everything this build knows”

Bash

```
# all global + backend flags (then apply the RCLONE_ transform)
rclone help flags
rclone help flags crypt
rclone help flags s3

# see env vars actually applied
rclone version -vv
rclone listremotes --long --json    # includes source=environment
```

Example transform in a shell:

Bash

```
rclone help flags 2>/dev/null | grep -oE -- '--[a-z0-9-]+' | sort -u | \
sed 's/^/--//; s/-/_/g; s/./RCLONE_\U&/'
```

That is the complete set for **your** rclone version: one RCLONE * name per long option. plus

...the complete server, you have to enter the ... the specials in the table above. Passwords for crypt/FTP/SFTP in those vars must be **obscured** (`rclone obscure 'plaintext'`), except `RCLONE_CONFIG_PASS` , which is the raw config-file password