

Usually **no** — if you only set up OpenPGP / GPG. MFA you already use is almost always a **different applet** on the same stick.

Isolated vs shared

What you change	Affects web/GitHub/Google MFA (FIDO2/U2F)?	Affects Authenticator TOTP?	Affects Yubico OTP?
Generate GPG keys, keytocard	No	No	No
OpenPGP User/Admin PIN	No	No	No
ykman openpgp keys set-touch ...	No	No	No
ykman openpgp reset / GPG factory-reset	No	No	No
Enable OpenPGP in Authenticator	No	No	No
FIDO PIN change	Same passkeys; you just use the new PIN	No	No
ykman fido reset	Yes — wipes all passkeys	No	No
ykman oath reset	No	Yes — wipes TOTP	No
Overwrite OTP slot 1 / 2	No	No	Yes
ykman config usb - -disable FIDO	Yes — sites cannot see the key	No	No
Full device reset / all apps reset	Yes	Yes	Yes

FIDO2, OATH, OTP, PIV, and OpenPGP each have their own PINs and storage. GPG work does not rewrite FIDO credentials.

What *will* break MFA

- ykman fido reset

- Disabling the FIDO USB (or NFC) interface
- Resetting the whole YubiKey
- Reprogramming slot 1 if a site still uses Yubico OTP (touch-and-paste codes), not WebAuthn
- Resetting OATH if your “MFA” is TOTP codes in Yubico Authenticator

Safe sequence on a key that already does MFA

Bash

```
ykman info                # note which USB apps are on
ykman config usb --list    # do not disable FIDO or OTP
gpg --card-status
# then only: change OpenPGP PINs, generate/move GPG keys, set-touch on
openpgp
```

Leave FIDO enabled. Do not run any `fido reset`, `oath reset`, or `config usb -disable`.

Small side effects (not broken MFA)

- `pcscd` + GPG fighting over CCID can make **Authenticator TOTP** or `ykman` flaky until you set `disable-ccid` / `pcsc-shared` in `scdaemon.conf`. FIDO MFA in the browser uses HID, not CCID, so it still works.
- A short CCID glitch does not delete passkeys.
- Changing the **FIDO** PIN is unrelated to GPG; only change it if you intend to.

If you say how MFA is set up (browser passkey, Yubico OTP blink-paste, or Authenticator TOTP) we can mark the exact commands that are off-limits