

The preset menu, dry-run prompt, confirm step, and dtach handoff are unchanged. What changed is the rclone setup those steps were feeding.



rcloneAutomationv5.sh
Shell Script · 8.66 KB

 Download

- Bandwidth, transfer count, cutoff, and logging were set as `RCLONE_S3_*`. rclone does not read those. They are now `RCLONE_BWLIMIT`, `RCLONE_TRANSFERS`, `RCLONE_CUTOFF_MODE`, `RCLONE_MAX_TRANSFER`, `RCLONE_LOG_LEVEL`, and `RCLONE_LOG_FILE`.
- The computed log path is actually exported. The old `RCLONE_S3_LOG_FILE` value was ignored, and the `logfile` variable was never used.
- `RCLONE_S3_STORAGE_CLASS` is still set from the selected preset, after the choice. A `DEEP_ARCHIVE` preset uploads as Deep Archive. A `STANDARD` preset sets `STANDARD`, so it does not keep a leftover class.
- Crypt obscure now uses `--`, and the plaintext password and salt are unset afterward. The wipe list names matched the crypt variables (`RCLONE_CONFIG_S3CRYPT_PASSWORD` / `PASSWORD2`); the old names were typos and were never cleared.
- Loopback gpg falls back to the desktop pinentry, same as the mount script.
`RCLONE_S3_TYPE=s3` was removed because the remotes are already `:s3:` and `S3CRYPT:`.

`S3CRYPT:` copies stay on `encrypted-standard-storage` and should keep the `STANDARD` presets. Deep Archive copies still cannot be read back until a restore finishes.