

rclone only treats `RCLONE_S3_` as a prefix for S3 backend flags. `MAX_TRANSFER` , `BWLIMIT` , `TRANSFERS` , `CUTOFF_MODE` , `LOG_LEVEL` , and `LOG_FILE` are global flags, so that prefix never reaches them.

A global flag maps to `RCLONE_` plus the flag name. `--bwlimit` becomes `RCLONE_BWLIMIT` , `--transfers` becomes `RCLONE_TRANSFERS` , and `--log-file` becomes `RCLONE_LOG_FILE` . A backend flag keeps the backend name: `--s3-storage-class` becomes `RCLONE_S3_STORAGE_CLASS` , and `--s3-chunk-size` becomes `RCLONE_S3_CHUNK_SIZE` . A named-remote setting is a third form, `RCLONE_CONFIG_S3CRYPT_PASSWORD` .

`RCLONE_S3_MAX_TRANSFER` is therefore read as an S3 option called `max_transfer` . The S3 backend has no such option, so the value is discarded. It is not applied to the global `--max-transfer` limit. The same drop happens for `RCLONE_S3_BWLIMIT` , `RCLONE_S3_TRANSFERS` , `RCLONE_S3_CUTOFF_MODE` , `RCLONE_S3_LOG_LEVEL` , and `RCLONE_S3_LOG_FILE` .

These are valid `RCLONE_S3_` names because they match real S3 flags: `RCLONE_S3_REGION` , `RCLONE_S3_CHUNK_SIZE` , `RCLONE_S3_UPLOAD_CONCURRENCY` , `RCLONE_S3_ACL` , `RCLONE_S3_ACCESS_KEY_ID` . and `RCLONE_S3_STORAGE_CLASS` .