

`RCLONE_CONFIG_S3CRYPT_PASSWORD` is valid. It is a remote-config variable, not a global flag and not an S3 backend flag. The names that were invalid were the old typos `CLONE_CONFIG_SECRET_PASSWORD` and `RCLONE_CONFIG_SECRET_PASSWORD2`.

`rcclone` has three separate namespaces:

- `RCLONE_TRANSFERS` sets the global flag `--transfers`.
- `RCLONE_S3_STORAGE_CLASS` sets the S3 backend flag `--s3-storage-class`.
- `RCLONE_CONFIG_S3CRYPT_PASSWORD` sets the `password` option on a remote whose name is `S3CRYPT`.

The middle piece must be the remote name. `RCLONE_CONFIG_S3CRYPT_TYPE=crypt` creates that remote, so the password variable has to use `S3CRYPT` too. `SECRET` does not match any remote this script defines, and `CLONE_CONFIG_...` is missing the `R` in `RCLONE`, so nothing reads it and the exit trap cannot unset it.

The value still has to be obscured. The crypt backend will not accept the raw password or salt in config or in this environment variable. That is why the script runs `rcclone obscure -`
- `"$RCLONE_PASSWORD"` and exports the result. A plaintext assignment is rejected even though the variable name is correct. `RCLONE_CONFIG_S3CRYPT_PASSWORD2` is the same rule for the salt.