

Models of Computation: DFAs & NFAs

Deterministic/Nondeterministic Finite Automata

Dr Kamal Bentahar

School of Engineering, Environment and Computing
Coventry University

10/10/2016

Mindmap

Search problems

Models of
Computation

Languages


Language
recognition

Language
Recognition

The DFA model

JFLAP

The NFA model



Mindmap

Search problems

Models of
Computation

Languages

Language
recognition

Language
Recognition

The DFA model

JFLAP

The NFA model

A needle in haystack

Given any (finite) haystack, decide whether it contains a needle or not.



- ▶ Tedious but doable: simply search every location within the haystack in some order and terminate with **yes** if we find a needle. If we complete the search and no needle was found then terminate with **no**.
- ▶ → **decision problem**: given data, decide if it has a certain property.
- ▶ We may divide all possible instances of the problem into **yes instances** and **no instances** using our process.

[Mindmap](#)[Search problems](#)[Models of
Computation](#)[Languages](#)[Language
recognition](#)[Language
Recognition](#)[The DFA model](#)[JFLAP](#)[The NFA model](#)

- ▶ Simplify the way we describe the problems that machines will solve.
 - ▶ Turn *search* problems into *decision* problems
 - ▶ Problems with a **yes/no** answer.
- ▶ **Language recognition:**
 - ▶ Think about the English language:
 - ▶ Alphabet: a, b, c, \dots, x, y, z (plus spaces, punctuation, etc.)
 - ▶ However, not all strings over this alphabet are members of the language.
 - English is a subset of all possible strings over its alphabet.
 - ▶ A problem *instance* can be represented as a string of symbols.
 - ▶ Instances which yield **yes** are said to *belong* to the corresponding **language** for the problem.
 - ▶ Instances which yield **no** (including invalid strings) do not belong to the language.

Mindmap

Search problems

Models of
Computation

Languages

Language
recognition

Language
Recognition

The DFA model

JFLAP

The NFA model

Decision problems can be encoded as problems of *language recognition*.

Example (Subset sum problem)

- ▶ **Instance:** A set of natural numbers, and a target value.
- ▶ **Question:** Is there a subset whose sum equals the target?
- ▶ For example, given the set $\{7, 3, 2, 5, 8\}$ and target 10, the answer is **yes** because the subset $\{7, 3\}$ sums to 10.
- ▶ This can be represented using the symbols $-, \{, \}, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9$ and **comma**: $\{7, 3, 2, 5, 8\}10$.
- ▶ Given a string using these symbols, we could write a decision procedure to decide if this string belongs to the language of **yes** instances.

Mindmap

Search problems

Models of
Computation

Languages

Language
recognition

Language
Recognition

The DFA model

JFLAP


The NFA model

- ▶ Languages are defined over an **alphabet**, denoted by Σ
 Σ is the set of allowable symbols for the language (*"Sigma"*)
- ▶ Σ^* denotes the set of all possible strings, over Σ , whose length is finite
(*"Sigma star"*)
- ▶ A language can be regarded as a subset of Σ^*

The **Deterministic Finite Automaton** (DFA) model

Models of
Computation:
DFAs & NFAs

Example (Is a given binary number even?)



Mindmap

Search problems

Models of
Computation

Languages

Language
recognition

Language
Recognition

The DFA model

JFLAP

The NFA model

The **Deterministic Finite Automaton** (DFA) model

Conceptually, it is a directed, labelled graph which describes how a sequence of symbols from an alphabet will be processed.

- ▶ Each node of the graph is called a **state**.
- ▶ Each arc of the graph is called a **transition**.
 - ▶ The arcs are labelled with symbols from the alphabet.
- ▶ We need to designate a *single* **start state**.
- ▶ We also need to designate a *set* of **accept states**, which will indicate whether or not the string is accepted after processing.
- ▶ Each state must have **exactly one** transition defined for **every** symbol of the alphabet.

Mindmap

Search problems

Models of
Computation

Languages

Language
recognition

Language
Recognition

The DFA model

JFLAP

The NFA model

Example

Let us build DFAs over the alphabet $\{a, b\}$ to recognize strings that:

- ▶ begin with a
- ▶ end with b
- ▶ either begin or end with b .
- ▶ begin with a and contain at least one b

Definition of a DFA

A *Deterministic Finite Automaton* (DFA) is defined by the 5-tuple $(Q, \Sigma, \delta, q_{\text{start}}, F)$ where

- ▶ Q is a finite set called the **set of states**
- ▶ Σ is a finite set called the **alphabet**
- ▶ $\delta: Q \times \Sigma \rightarrow Q$ is a total function called the **transition function**
- ▶ q_{start} is the unique **start state** ($q_{\text{start}} \in Q$)
- ▶ F is the set of accepting states ($F \subseteq Q$).

Mindmap

Search problems

Models of
Computation

Languages


Language
recognitionLanguage
Recognition

The DFA model

JFLAP

The NFA model

Example (DFAs)



This DFA is defined by the 5-tuple $(Q, \Sigma, \delta, q_{start}, F)$ where

► $Q = \{q_0, q_1\}$

► $\delta(state, symbol)$ is given by the table:

	a	b
$\rightarrow q_0$	q_0	q_1
$*q_1$	q_0	q_1

► $q_{start} = q_0$

► $F = \{q_1\}$

Notation

$\delta: Q \times \Sigma \rightarrow Q$ means that the function *delta* “sends” pairs (q, σ) from $Q \times \Sigma$, made of a *state* q and an *alphabet symbol* σ , to a state in Q .

This is usually given as a table, e.g.

	a	b
$\rightarrow q_0$	q_0	q_1
$*q_1$	q_0	q_2
\vdots	\vdots	\vdots

This means that

$$\delta(q_0, a) = q_0$$

$$\delta(q_0, b) = q_1$$

$$\vdots = \vdots$$

We put “ \rightarrow ” next to the start state, and “ $*$ ” next to the accept states.

[Mindmap](#)
[Search problems](#)
[Models of
Computation](#)
[Languages](#)
[Language
recognition](#)
[Language
Recognition](#)
[The DFA model](#)
[JFLAP](#)
[The NFA model](#)

2^Q is the “set of subsets of Q ”, also called the “power set of Q .”

Example

$Q = \{A, B, C\}$

Then

$$2^Q = \{ \underbrace{\emptyset}_{\text{Empty set}}, \{A\}, \{B\}, \{C\}, \{A, B\}, \{A, C\}, \{B, C\}, \underbrace{\{A, B, C\}}_Q \}.$$

It has $2^{\text{cardinality of } Q} = 2^{|Q|} = 2^3$ elements.

Mindmap

Search problems

Models of
Computation

Languages

Language
recognition

Language
Recognition

The DFA model

JFLAP

The NFA model

The Nondeterministic Finite Automaton (NFA) model

From the design point of view: NFAs are almost the same as DFAs.
Only, instead of every state having **one and only one outward transition** defined **for each symbol**, we may define **zero or more transitions for the same symbol**.

What if δ is not a total function? \rightarrow NFA


DFA: $\delta: Q \times \Sigma \rightarrow Q$ is a **total** function

1. δ is defined for *every* pair (q, σ) from $Q \times \Sigma$
2. δ sends (q, σ) to a **state** from Q (exactly one state, no more, no less)

NFA: $\delta: Q \times \Sigma \rightarrow 2^Q$ *may be* a **partial** function


1. δ is *not necessarily* defined for every pair (q, σ) from $Q \times \Sigma$
2. δ sends (q, σ) to a **subset of** Q (many, one, or no states)

NFA example



Q	a	b
$\rightarrow q_0$	$\{q_0, q_1\}$	$\{q_0\}$
q_1	\emptyset	$\{q_2\}$
$*q_2$	$\{q_2\}$	$\{q_2\}$

NFA example



Q	a	b
$\rightarrow q_0$	$\{q_1, q_2\}$	\emptyset
q_1	$\{q_3\}$	\emptyset
q_2	\emptyset	$\{q_5\}$
q_3	\emptyset	$\{q_4\}$
$*q_4$	$\{q_4\}$	$\{q_4\}$
q_5	$\{q_6\}$	\emptyset
$*q_6$	$\{q_6\}$	$\{q_6\}$

Example

Let us build NFAs over the alphabet $\{a, b\}$ to recognize strings that:

- ▶ begin with a
- ▶ end with b
- ▶ either begin or end with b .
- ▶ begin with a and contain at least one b

Definition of an NFA

A *Nondeterministic Finite Automaton* (NFA) is defined by the 5-tuple $(Q, \Sigma, \delta, q_0, F)$ where

- ▶ Q is a finite set called the **set of states**
- ▶ Σ is a finite set called the **alphabet**
- ▶ $\delta: Q \times \Sigma \rightarrow 2^Q$ is a partial function called the **transition function**
- ▶ q_0 is the unique **start state** ($q_0 \in Q$)
- ▶ F is the set of accepting states ($F \subseteq Q$).

Surprise: NFAs recognize exactly the same language as DFAs!

[Mindmap](#)[Search problems](#)[Models of
Computation](#)[Languages](#)[Language
recognition](#)[Language
Recognition](#)[The DFA model](#)[JFLAP](#)[The NFA model](#)