

Subgroups Chapter 8

Nick Lauerman

Contents

Libraries and data used	1
Libraries	1
Data	1
Social Cohesion	2
Cliques	2
k-Cores	5
Community Detection	9
Modularity	9

Libraries and data used

Libraries

```
library(UserNetR)
library(igraph)

##
## Attaching package: 'igraph'

## The following objects are masked from 'package:stats':
##
##   decompose, spectrum

## The following object is masked from 'package:base':
##
##   union

library(intergraph)
```


Data

```
data("DHHS")
data("Moreno")
data("Facebook")
```

Social Cohesion

Cliques

```
clqexmp <- graph.formula(A:B:C:D--A:B:C:D,D-E,E-F-G-E)
plot(clqexmp,
     layout = layout_with_fr)
```



```
clique.number(clqexmp)
```

```
## [1] 4
```

```
cliques(clqexmp,
        min = 3)
```

```
## [[1]]
## + 3/7 vertices, named, from 573a2b9:
## [1] B C D
##
## [[2]]
## + 3/7 vertices, named, from 573a2b9:
## [1] E F G
##
## [[3]]
## + 3/7 vertices, named, from 573a2b9:
## [1] A B C
##
## [[4]]
## + 4/7 vertices, named, from 573a2b9:
## [1] A B C D
##
## [[5]]
## + 3/7 vertices, named, from 573a2b9:
## [1] A B D
##
## [[6]]
## + 3/7 vertices, named, from 573a2b9:
## [1] A C D
```

```
maximal.cliques(clqexmp,
                min = 3)
```

```
## [[1]]
## + 3/7 vertices, named, from 573a2b9:
## [1] E F G
##
## [[2]]
## + 4/7 vertices, named, from 573a2b9:
## [1] A B D C
```

```
largest.cliques(clqexmp)
```

```
## [[1]]
## + 4/7 vertices, named, from 573a2b9:
## [1] D A B C
```

```
V(clqexmp)[unlist(largest.cliques(clqexmp))]
```

```
## + 4/7 vertices, named, from 573a2b9:
## [1] D A B C
```

```
g25 <- erdos.renyi.game(25,
                        75,
                        type = "gnm")
g50 <- erdos.renyi.game(50,
                        150,
                        type = "gnm")
g100 <- erdos.renyi.game(100,
```

```

      300,
      type = "gnm")
g500 <- erdos.renyi.game(500,
      1500,
      type = "gnm")
g1000 <- erdos.renyi.game(1000,
      3000,
      type = "gnm")
g5000 <- erdos.renyi.game(5000,
      15000,
      type = "gnm")
g10000 <- erdos.renyi.game(10000,
      30000,
      type = "gnm")
nodes <- c(25,
  50,
  100,
  500,
  1000,
  5000,
  10000)
lrgclg <- c(clique.number(g25),
  clique.number(g50),
  clique.number(g100),
  clique.number(g500),
  clique.number(g1000),
  clique.number(g5000),
  clique.number(g10000))
numclq <- c(length(cliques(g25,
  min = 3)),
  length(cliques(g50,
  min = 3)),
  length(cliques(g100,
  min = 3)),
  length(cliques(g500,
  min = 3)),
  length(cliques(g1000,
  min = 3)),
  length(cliques(g5000,
  min = 3)),
  length(cliques(g10000,
  min = 3)))
clqinfo <- data.frame(
  Nodes = nodes,
  Largest = lrgclg,
  number = numclq)
clqinfo

```

```

##   Nodes Largest number
## 1    25      4      37
## 2    50      3      26
## 3   100      3      40
## 4   500      3      36
## 5  1000      3      47

```

```
## 6 5000      3      29
## 7 10000     3      39
```

k-Cores

```
data(DHHS)
iDHHS <- asIgraph(DHHS)
graph.density(iDHHS)

## [1] 0.312369

iDHHS <- subgraph.edges(iDHHS,
                        E(iDHHS)[collab > 2])
graph.density(iDHHS)

## [1] 0.1533688

coreness <- graph.coreness(iDHHS)
table(coreness)


## coreness
##  1  2  3  4  5  6
##  7  6  2  5  2 26

maxCoreness <- max(coreness)
maxCoreness

## [1] 6

Vname <- get.vertex.attribute(iDHHS,
                              name = "vertex.names",
                              index = V(iDHHS))


V(iDHHS)$name <- Vname
V(iDHHS)$color <- coreness + 1
op <- par(mar = rep(0,4))
plot(iDHHS,
     vertex.label.cex = 0.8)
```



```

par(op)
colors <- rainbow(maxCoreness)
op <- par(mar = rep(0,4))
plot(idHHS,
     vertex.label = coreness,
     vertex.color = colors[coreness])

```









```
par(op)

V(iDHHS)$name <- coreness
V(iDHHS)$color <- colors[coreness]
iDHHS1_6 <- iDHHS
iDHHS2_6 <- induced.subgraph(iDHHS,
                             vids = which(coreness > 1))
iDHHS3_6 <- induced.subgraph(iDHHS,
                             vids = which(coreness > 2))
iDHHS4_6 <- induced.subgraph(iDHHS,
                             vids = which(coreness > 3))
iDHHS5_6 <- induced.subgraph(iDHHS,
                             vids = which(coreness > 4))
iDHHS6_6 <- induced.subgraph(iDHHS,
```

```

                                vids = which(coreness > 5))
lay <- layout.fruchterman.reingold(iDHHS)
op <- par(mfrow = c(3,2),
          mar = c(3, 0, 2, 0))
plot(iDHHS1_6,
      layout = lay,
      main = "All k-cores")
plot(iDHHS2_6,
      layout = lay[which(coreness > 1), ],
      main = "k-cores 2-6")
plot(iDHHS3_6,
      layout = lay[which(coreness > 2), ],
      main = "k-cores 3-6")
plot(iDHHS4_6,
      layout = lay[which(coreness > 3), ],
      main = "k-cores 4-6")
plot(iDHHS5_6,
      layout = lay[which(coreness > 4), ],
      main = "k-cores 5-6")
plot(iDHHS6_6,
      layout = lay[which(coreness > 5), ],
      main = "k-cores 6-6")

```

```
par(op)
```

Community Detection

Modularity


```
g1 <- graph.formula(A-B-C-A,
                    D-E-F-D,
                    G-H-I-G,
                    A-D-G-A)
V(g1)$grp_good <- c(1,1,1,2,2,2,3,3,3)
V(g1)$grp_bad  <- c(1,2,3,2,3,1,3,1,2)
op <- par(mfrow = c(1,2))
```

```


plot(g1,
     vertex.color = (V(g1)$grp_good),
     vertex.size = 20,
     main = "Good Grouping")
plot(g1,
     vertex.color = (V(g1)$grp_bad),
     vertex.size = 20,
     main = "Bad Grouping")

```

Good Grouping



Bad Grouping



```

par(op)
modularity(g1,
           V(g1)$grp_good)

```

```
## [1] 0.4166667
```

```

modularity(g1,
            V(g1)$grp_bad)

## [1] -0.3333333

data(DHHS)
iDHHS <- asIgraph(DHHS)
table(V(iDHHS)$agency)

##
##  0  1  2  3  4  5  6  7  8  9 10
##  2  4 12  2  2  3  2 16  3  5  3

V(iDHHS)[1:10]$agency

## [1] 0 0 1 1 1 1 2 2 2 2

modularity(iDHHS,
            (V(iDHHS)$agency + 1))

## [1] 0.1402264

data("Moreno")
iMoreno <- asIgraph(Moreno)
table(V(iMoreno)$gender)

##
##  1  2
## 16 17

modularity(iMoreno,
            V(iMoreno)$gender)

## [1] 0.4761342

data("Facebook")
levels(factor(V(Facebook)$group))

## [1] "B" "C" "F" "G" "H" "M" "S" "W"

grp_mun <- as.numeric(factor(V(Facebook)$group))
modularity(Facebook, grp_mun)

## [1] 0.6145798

```