

## I. Introduction

- A. Purpose of the work: investigate the effect of deploying HALEU-fueled advanced reactors on the nuclear fuel cycle in the US
- B. Scope:
  - 1. US facilities
  - 2. select advanced reactors: USNC MMR, X-energy Xe-100, NuScale VOYGR
  - 3. Front-end and back-end of the fuel cycle
- C. Motivations
  - 1. U.S. wants to develop a supply chain of HALEU
  - 2. HALEU has broad uses outside of reactors [1]
  - 3. Benefits of using HALEU in reactors
    - a. higher burnups
    - b. reduced LCOE
  - 4. Changing the fuel form affects fuel cycle dynamics
- D. Goals
  - 1. understand how deploying HALEU reactors affects resource demand
  - 2. understand which components of the fuel cycle are most sensitive to HALEU deployments
  - 3. understand how implementing recycling with HALEU reactors affects the fuel cycle
  - 4. understand how possible avenues to obtain fuel for HALEU reactors can affect neutronics
    - a. neutron flux
    - b. k-eff
    - c.  $\beta$ -eff
    - d. feedback coefficients,
    - e. lifetimes
    - f. uranium utilization in general
    - g. breeding ratio

## II. Lit Review

- A. The nuclear fuel cycle
  - 1. Once-through vs recycle [2]
  - 2. Enrichment facility/SWU calculations [2]
  - 3. Recycling processes [2]
    - a. overview of aqueous reprocessing
    - b. Known changes to LWR fuel cycle by recycling
- B. Fuel Cycle simulators
  - 1. Why we use them, their benefits
  - 2. why multiples have been created
  - 3. ideal functionalities and capabilities [3, 4]
  - 4. uses of fuel cycle simulators
    - a. Department of Energy (DOE) Evaluation & screening [5]
      - (1) Differences in EG 01 and EG 02
    - b. EG29 analysis [6]
    - c. verification [7]
  - 5. CYCLUS [8]

- a. basic fundamentals
    - b. CYCAMORE [9]
    - c. addresses many of the things brought up by [3]
    - d. comparison to other codes [10]
    - e. verification [11]
  - C. sensitivity analysis and optimization
    - 1. Dakota [12]
  - D. HALEU
    - 1. production methods
    - 2. fuel forms (ceramic vs metallic vs TRISO)
    - 3. expected demand [13]
    - 4. Reactors with HALEU
      - a. Effects of changing from 5% to 7% for PWR [14]
      - b. Effects on NuScale SMR [15]
      - c. Effects of impurities [16]
- III. Transition modeling methodology
- A. Reactors, including serpent models
    - 1. USNC MMR [17]
    - 2. X-energy Xe-100 [18]
    - 3. NuScale VOYGR [19, 20]
  - B. material flow in fuel cycles
    - 1. Once-through
      - a. once-through flow figure
      - b. scenario definitions
    - 2. recycle
      - a. recycle-flow figure
      - b. scenario definitions
- IV. Material requirements – Once through fuel cycles
- A. Results
    - 1. Scenario 1 – current fleet
      - a. reactor deployment – compare to actual data??
      - b. uranium resources
      - c. SWU capacity
      - d. Waste
    - 2. Reactor deployment
      - a. No growth scenarios
      - b. 1% growth scenarios
    - 3. Uranium resources
      - a. No growth scenarios
      - b. 1% growth scenarios
    - 4. SWU capacity
      - a. No growth scenarios
      - b. 1% growth scenarios
    - 5. Waste

- a. No growth scenarios
- b. 1% growth scenarios

## V. Model fuel cycle with recycle

### A. Results

- 1. Reactor deployment
  - a. No growth scenarios
  - b. 1% growth scenarios
- 2. Uranium resources
  - a. No growth scenarios
  - b. 1% growth scenarios
- 3. SWU capacity
  - a. No growth scenarios
  - b. 1% growth scenarios
- 4. Waste
  - a. No growth scenarios
  - b. 1% growth scenarios

## VI. Sensitivity analysis and optimization

- A. Methodology
- B. Results

## VII. Effects on neutronics

- A. Methodology
- B. Models
- C. Results

## VIII. Conclusions

# Bibliography

- [1] S. Nagley, “HA-LEU Supply (Enrichment, De-conversion, Fuel Fab & Transportation),” Apr. 2020.
- [2] N. Tsoulfanidis, *The Nuclear Fuel Cycle*. La Grange Park, Illinois, USA: American Nuclear Society, 2013. 00177.
- [3] K. Huff and B. Dixon, “Next Generation Fuel Cycle Simulator Functions and Requirements Document,” Tech. Rep. fcrd-sysa-2010-000110, Idaho National Laboratory, July 2010.
- [4] N. R. Brown, B. W. Carlsen, B. W. Dixon, B. Feng, H. R. Greenberg, R. D. Hays, S. Passerini, M. Todosow, and A. Worrall, “Identification of fuel cycle simulator functionalities for analysis of transition to a new fuel cycle,” *Annals of Nuclear Energy*, vol. 96, pp. 88–95, Oct. 2016.
- [5] R. Wigeland, T. Taiwo, H. Ludewig, M. Todosow, W. Halsey, J. Gehin, R. Jubin, J. Buelt, S. Stockinger, and K. Jenni, “Nuclear Fuel Cycle Evaluation and Screening Final Report,” *Final Report*, p. 51, 2014.
- [6] E. Sunny, A. Worrall, J. Peterson, J. Powers, J. Gehin, and R. Gregg, “Transition Analysis of Promising U.S. Future Fuel Cycles Using ORION,” p. 10, 2015.
- [7] B. Feng, B. Dixon, E. Sunny, A. Cuadra, J. Jacobson, N. R. Brown, J. Powers, A. Worrall, S. Passerini, and R. Gregg, “Standardized verification of fuel cycle modeling,” *Annals of Nuclear Energy*, vol. 94, pp. 300–312, Aug. 2016.
- [8] K. D. Huff, M. J. Gidden, R. W. Carlsen, R. R. Flanagan, M. B. McGarry, A. C. Opotowsky, E. A. Schneider, A. M. Scopatz, and P. P. H. Wilson, “Fundamental concepts in the Cyclus nuclear fuel cycle simulation framework,” *Advances in Engineering Software*, vol. 94, pp. 46–59, Apr. 2016. arXiv: 1509.03604.
- [9] A. M. Scopatz, K. D. Huff, M. J. Gidden, R. W. Carlsen, R. R. Flanagan, M. B. McGarry, A. C. Opotowsky, E. A. Schneider, and P. P. Wilson, “Cyclus Archetypes,” *Submitted*, 2015.
- [10] D. Djokic, A. M. Scopatz, H. R. Greenberg, K. D. Huff, R. P. Nibbelink, and M. Fratoni, “The Application of CYCLUS to Fuel Cycle Transition Analysis,” in *Proceedings of Global 2015*, LLNL-CONF-669315, (Paris, France), p. 5061, Sept. 2015.
- [11] J. W. Bae, J. L. Peterson-Droogh, and K. D. Huff, “Standardized verification of the Cyclus fuel cycle simulator,” *Annals of Nuclear Energy*, vol. 128, pp. 288–291, June 2019.
- [12] B. M. Adams, M. S. Eldred, G. Geraci, and W. J. Bohnhoff, “Dakota, A Multilevel Parallel Object-Oriented Framework for Design Optimization, Parameter Estimation, Uncertainty Quantification, and Sensitivity Analysis: Version 6.11 Users Manual,” Nov. 2019.
- [13] M. Korsnick, “Need for High-Assay Low Enriched Uranium,” July 2018.
- [14] J. R. Burns, R. Hernandez, K. A. Terrani, A. T. Nelson, and N. R. Brown, “Reactor and fuel cycle performance of light water reactor fuel with 235U enrichments above 5%,” *Annals of Nuclear Energy*, vol. 142, p. 107423, July 2020. JC0008.

- [15] L. Carlson, J. Miller, and Z. Wu, “Implications of HALEU fuel on the design of SMRs and micro-reactors,” *Nuclear Engineering and Design*, vol. 389, p. 111648, Apr. 2022.
- [16] O. S. Celikten and D. Sahin, “The Effects of Impurities in Down-Blending Highly Enriched Uranium on the Reactor Neutronics and Cycle Length,” in *Transactions of the American Nuclear Society Winter Meeting*, vol. 125, (Washington D.C.), pp. 165–167, Dec. 2021.
- [17] M. Hussain, F. Reitsma, M. Subki, and H. Kiuchi, “Advances in Small Modular Reactor Technology Developments,” a Supplement to: IAEA Advanced Reactors Information System (ARIS), Nuclear Power Technology Development Section, Division of Nuclear Power of the IAEA Department of Nuclear Energy, Vienna, Austria, Sept. 2018.
- [18] B. Harlan, “X-energy Xe-100 Reactor initial NRC meeting,” Sept. 2018.
- [19] NuScale, “Chapter Four Reactor,” July 2020. Rev. 5.
- [20] P. Suk, O. Chvla, G. I. Maldonado, and J. Frbort, “Simulation of a NuScale core design with the CASL VERA code,” *Nuclear Engineering and Design*, vol. 371, p. 110956, Jan. 2021.