STACKCALC INSTRUMENT CORP // FORMAL PUBLICATION SERIES

STACKCALC SC-6

Elementary Reference Manual & Manipulative Companion

// CLASSROOM COMPANION FOR GRADES K–6 & CONCRETE MATH LAB • FIRMWARE REVISION 1.2

EDUCATIONAL ARCHITECTURE	CLASSROOM & HOME STUDIO SPECIFICATIONS (GRADES K–6)
Silicon Engine	Dedicated Dual-Core Embedded 32-bit Microcontroller (Microamp Standby, Instant Boot)
Display Subsystem	132 × 65 High-Contrast Ambient-Light Transflective Monochrome Dot-Matrix LCD
Ergonomics & Stand	Sliding Protective Desk-Stand Cowl (15° Classroom Viewing Angle) • 400g Snap-Domes
Pedagogical Method	Concrete-Representational-Abstract (CRA) Framework • Singapore Dimensions & Bridges Aligned
Physical Manipulatives	Modular Classroom Manipulative Studios: Ten-Frames, Dominoes, 84mm Towers, Planetary Clock
Stack Progression	The Elevator Metaphor • Automatic 2-Stack Sandbox Mode • 4-Stack Base-10 Arithmetic
Curriculum Ribbon	Strict Progressive Keycap Ribbon (K–5 Shielded from Advanced Transcendentals)

> *"Mathematics begins not with abstract symbols on a page, but with the tactile feel of blocks in the hand and numbers moving on an elevator. The SC-6 transforms Reverse Polish Notation into an intuitive, joyful companion where combining numbers **is** the answer—fostering intermediate awareness, eliminating fear of the '=' key, and empowering young minds with mathematical confidence."*

STACKCALC LABORATORY PRESS // SAN FRANCISCO & AUSTIN
PUBLISHED UNDER OPEN DOCUMENTATION & HARDWARE DISTRIBUTION LICENSES // STACKCALC.IO

Table of Contents

StackCalc SC-6 Elementary Calculator: Masterwork Manual & Classroom Companion 9

1. Welcome, Explorer! (Wait—Did Your Parents Buy You This Book?) 9
2. Foreword: The Renaissance of Tactile Mathematics 10
3. Meet Your Math Blocks: Building Numbers with Your Hands 13
4. Three Foundational RPN Breakthroughs for Your Math Journey 14
5. The Four SC-6 RPN Superpowers 15
6. Visual Manipulative Sandboxes Overview 17
7. Exploring Your Keypad: 43 Powerful Keys at Your Fingertips 18
8. Quick-Start Adventure Showcase: 30 Things You Will Master Across K–6 19
9. How to Use This Textbook & Learning Pathways 35
10. Safety, Regulatory, Trademark & Parent/Educator Notices 36

Chapter 1: Meet Your SC-6 Stack Calculator & Math Blocks 38

1.1 Why Real Buttons and Blocks Beat a Glowing Tablet Screen 38
1.2 Meet Your Stack Calculator: The Screen, The Number Stack & Your Secret Shift Keys 39
1.3 Why the Calculator Is Dark and the Blocks Are Bright 41
1.4 Built Like a Tank: How Your Calculator Survives the Classroom 42
1.5 Instant-On Readiness & Continuous Backpack Memory 43
1.6 Meet Your Math Blocks: Building Numbers with Your Hands 43
1.7 Taking Care of Your Stack Calculator 45
1.8 What to Do If You Get Stuck (Troubleshooting Pathways) 46
1.9 Hands-On Studio Proof: Your First Math Discovery 46
1.10 Story-Driven Problem Expeditions (The Calculator Workshop & Maker Bench) 47
1.11 What You Mastered & Looking Ahead 49

Chapter 2: How Stack Math Works: Stacking Numbers Just Like Blocks 50

2.1 The Equals-Sign Trap vs. The Stack Ladder 50

2.2 Stacking Numbers: The 4-Level Number Stack (T, Z, Y, X) . . . 51

2.3 Why Combining Numbers IS the Answer (Zero Parentheses!) . . . 52

2.4 Five Stack Math Super-Moves . . . 54

2.5 Horizontal Y | X Split Screen vs. Vertical Stack . . . 55

2.6 Configurable Stack Depths: 2-LV, 4-LV, and 8-LV . . . 56

2.7 Moving Numbers Around on Your Stack: [x■y], [f] [R↓], [g] [REP], [f] [LASTX] . . . 57

2.8 Beat Every Adult in the Room! The 1089 Mind-Reading Stack Trick . . . 57

2.9 Why Your Brain Loves Stack Math (No Parenthesis Headaches!) . . . 58

2.10 Story-Driven Problem Expeditions (40 Foundational Scenarios) . . . 59

2.11 What You Mastered & Looking Ahead . . . 70

Counting, Number Lines & Place Value Studio . . . 72

3.1 The Greatest Invention in Human History: How Ten Fingers and an Empty Shell Created Zero and Place Value . . . 72

3.2 Building Numbers: From Hands-On Blocks to the Screen Stack . . . 73

3.3 Concrete Bridge to the Ten-Frame Studio ([■]) . . . 75

3.4 Making Ten & The "Bridging Ten" Strategy . . . 77

3.5 The Step Counter Dynamics & Stacking Tile Heights . . . 79

3.6 Number Line Navigation & Visual Jump Arcs ([f] [LINE]) . . . 82

3.7 The European Rekenrek / Number Rack ([g] [COUNT]) . . . 83

3.8 Place Value Decomposition Studio ([PV]) . . . 84

3.9 Big Numbers in Nature: Expanding Horizons . . . 86

3.10 Story-Driven Problem Expeditions (45 Elementary Reference Scenarios) . . . 90

3.11 What You Mastered & Looking Ahead . . . 103

Whole Number Operations & Skip-Counting Ladders . . . 105

4.1 How 7-Year-Old Carl Friedrich Gauss Outsmarted His Teacher in 30 Seconds (and Why Multiplication Is a Physical Rectangle, Not a Memorized Song) . . . 105

4.2 Concrete Foundation: 24-Tile Four-Color Array Studio & Map Theory . . . 106

4.3 Addition & Subtraction Dynamics: Regrouping Without Fear . . . 110

4.4 Superpower 1: Rhythmic Skip-Counting Ladders ([g] [REP]) . . . 111
4.5 Superpower 2: Simultaneous Quotient & Remainder ([g] [÷R]) . . . 113
4.6 Superpower 4: Self-Checking Inverse Arithmetic ([f] [LASTX]) . . . 116
4.7 5th Grader Extreme Math Challenges: Doubling to the Sky & Your Age in Seconds! . . . 118
4.8 RPN Stack Diagnostic & Remediation Playbook . . . 120
4.9 Comprehensive Worked Reference Problems (50 Elementary Reference Problems) . . . 121
4.10 What You Mastered & Looking Ahead . . . 135

Fractions, Decimals, Percents & Proportional Towers . . . 136

5.1 Why Do Fractions, Ratios, and LCM Matter in Real Life? . . . 136
5.2 Concrete Foundation: 84 mm Fraction Studio Proportional Towers . . . 138
5.3 Two-Dot Entry Syntax (. n . d and w . n . d) . . . 142
5.4 Why the Calculator Keeps Your Work Unreduced . . . 143
5.5 Superpower 3: Step-by-Step Factor Reduction ([g] [SIMP]) . . . 143
5.6 Adding & Subtracting Unlike Denominators . . . 145
5.7 Fractions, Decimals and Percents Bridge . . . 146
5.8 Ratio Mode & Ratio Table Studio ([g] [a:b]) . . . 147
5.9 RPN Stack Diagnostic & Remediation Playbook . . . 149
5.10 Comprehensive Worked Reference Problems (50 Elementary Reference Problems) . . . 150
5.11 What You Mastered & Looking Ahead . . . 162

Geometry, Surface Area & Planetary Geared Time . . . 164

6.1 Why Does Surface Area Matter in the Real World? . . . 164
6.2 Concrete Foundations: Manipulative Nets & Planetary Gear Trains . . . 165
6.3 2D Plane Geometry & Direct Area Solvers . . . 167
6.4 The Master Surface Area Technique via Stats Mode ([Σ+]) . . . 172
6.5 3D Solid Volume Dynamics . . . 177
6.6 Planetary Geared Clock & Continuous Modulo-60 Elapsed Time . . . 180
6.7 Comprehensive Problem Bank: 50 Worked Reference Problems . . . 185

6.8 What You Mastered & Looking Ahead 204

Discrete Probability, Primes & Pre-Algebra 205

7.1 Why Do Primes and Probability Matter in the Real World? 205

7.2 Concrete Foundations: Two-Color Counters, Polyhedral Dice & The Sieve Grid 207

7.3 Discrete Probability & Random Trials ([■]) 209

7.4 Number Theory: Primes, Factors & The Secret Partner Rule 212

7.5 Elementary Descriptive Statistics & Data Analysis 221

7.6 Grade 6 Pre-Algebra: Signed Numbers, Absolute Value & Inverses 224

7.7 Comprehensive Problem Bank: 65 Worked Reference Problems 228

7.8 What You Mastered & Looking Ahead 243

The Gamified Math Quiz Engine 244

8.1 The Musician's Scales & The Astronaut's Simulator: Why Instant Math Reflexes Set Your Creative Brain Free 244

8.2 The RPN Prompt & Rapid Sprint Evaluation ([f] [?] & [ENTER]) 246

8.3 The 6-Level Adaptive Curriculum Ladder 247

8.4 Hardware Scoring Dynamics, Fast Streaks & Latency Tracking 248

8.5 Walkthrough: An Elite Level 6 Sprint Simulation 250

8.6 Classroom Sprint Stations, Relays & Tournament Protocols 250

8.7 Mental Math & Number Sense Fluency: 8 Essential Mental Math Theorems 253

8.8 Comprehensive Problem Bank: 48 Worked Quiz Drills with Full 4-Register Stack Traces 256

8.9 What You Mastered & Looking Ahead 268

Applied Elementary STEM & Maker Labs 269

9.1 The Kitchen-Table Invention Studio: Turning Numbers into Moving Machines, Glowing Circuits, and 3D Prints 269

9.2 Building Real Things: From Workshop Tools to the Number Stack 270

9.3 Project 1: 3D Printing Filament Mass, Infill & Spool Cost Estimation 271

9.4 Project 2: Batch Classroom Kit Production & Manufacturing Economics 274

9.5 Project 3: Paper Circuit LED Current-Limiting Resistors & Power 275

9.6 Project 4: Simple Pendulum Period Measurement & Gravity 276

9.7 Project 5: Solar Oven Thermal Tracking & Efficiency Rates . . . 278
9.8 Project 6: Catapult Trajectory Math & Projectile Launch Analysis . . . 279
9.9 Project 7: Plant Growth Tracking & Proportional Rate Analysis . . . 281
9.10 Project 8: Culinary Chemistry & Baker's Percentage Recipe Scaling . . . 282
9.11 Project 9: Compound Gear Train Ratios & Mechanical Advantage . . . 283
9.12 Project 10: Hydraulic Syringe Lift & Pascal's Principle . . . 284
9.13 Project 11: Drone Flight Battery Endurance & Power Budget . . . 285
9.14 Project 12: Photovoltaic Solar Panel Tilt Angle & Irradiance . . . 286
9.15 Maker Lab Engineering Notebook & Uncertainty Protocol . . . 287
9.16 Maker Space Machine Safety Protocols & Electrical Protection . . . 289
9.17 Practice Station: 40 Worked Applied STEM Challenges . . . 291
9.18 What You Mastered & Looking Ahead . . . 304

Appendix A: Manipulative Blueprints & Physical Fabrication Guide . . . 306

A.1 The Philosophy of Physical Fabrication in Math Education . . . 306
A.2 The Zack Freedman Gridfinity Modular Standard & Dimensional Envelope . . . 307
A.3 Additive Manufacturing (3D Printing) Specification Matrix . . . 308
A.4 Laser-Cutting Specifications & Vector Kerf Compensation . . . 308
A.5 Printable Paper & Cardstock Blueprint Cutouts . . . 309
A.6 Blueprint 1: The Ten-Frame Studio (ten_frame_tray) . . . 309
A.7 Blueprint 2: Place Value Base-Ten Manipulative Studio . . . 310
A.8 Blueprint 3: Fraction Studio Proportional Towers & Tiles . . . 312
A.9 Blueprint 4: Equal-Arm Pan Balance Scale (balance_scale.scad) . . . 313
A.10 Blueprint 5: Circular 360^° Protractor & Planetary Angle Wheel . . . 315
A.11 Blueprint 6: Geoboard Layouts (Cartesian & Isometric) . . . 316
A.12 3D Printing Troubleshooting & Dimensional Calibration . . . 317
A.13 Kinematic Transmission: 12:1 Compound Planetary Clock (monolithic_clock.scad) . . . 318
A.14 Polyhedral Dice Equal-Volume Pip Algorithm (dice_and_spinner.scad) . . . 319

A.15 Blueprint 7: Counting & Array Studio (unifix_cubes_box.scad & unifix_cubes_parts.scad) . . . 320

A.16 Blueprint 8: Prime Factor Studio & Logarithmic Slide Rule Comparator (prime_studio_box.scad & prime_studio_parts.scad) 323

A.17 Printable Cardstock Cutout Workshop (Full 1:1 Scale Net Patterns) . . . 327

A.18 Parametric OpenSCAD Blueprint: 5 × 5 Precision Geoboard . . . 328

A.19 Parametric OpenSCAD Blueprint: Calibration Go/No-Go Tolerance Gauge . . . 329

A.20 Quality Control & Gauge Tolerancing Protocols . . . 330

A.21 Complete Bill of Materials (BOM) & Classroom Station Inventory . . . 331

A.22 SC-6 Embedded Hardware Architecture, Raster Pipeline & Electrical Schematics . . . 331

A.23 Fabrication Invariants & Quality Control . . . 333

A.24 Industrial Polymer & Thermoplastic Specifications . . . 333

A.25 Mil-STD-810H Method 516.8 Transit Drop Testing Compliance . . . 334

A.26 The 19.0 kg Clean Lab Manipulative Fabrication Pool . . . 334

A.27 Physical Manipulative Manufacturing Catalog (SKU Directory) . . . 335

A.28 Workshop Safety & Non-Toxic Material Standards . . . 335

Appendix B: Teacher Lesson Plans & Diagnostic Protocols . . . 337

B.1 Station Facilitation Model & Workshop Architecture . . . 337

B.2 Kindergarten Lesson Plans (Ages 5–6) . . . 338

B.3 Grade 1 Lesson Plans (Ages 6–7) . . . 340

B.4 Grade 2 Lesson Plans (Ages 7–8) . . . 344

B.5 Grade 3 Lesson Plans (Ages 8–9) . . . 348

B.6 Grade 4 Lesson Plans (Ages 9–10) . . . 352

B.7 Grade 5 Lesson Plans (Ages 10–11) . . . 355

B.8 Grade 6 Lesson Plans (Ages 11–12) . . . 358

B.9 Master 4-Tier Assessment Rubric & Diagnostic Protocol . . . 361

B.10 Student Intervention Decision Tree & Cognitive Misconceptions . . . 362

B.11 Cognitive Science of Fluency, Spaced Retrieval & Quiz Engine Architecture . . . 362

Appendix C: Formulas, Conversions & Prime Catalogs . . . 364

C.1 The RPN Formula Advantage 364

C.2 Table 1: Elementary Mathematical & Geometric Formulas Directory 365

C.3 Total Surface Area via Statistical Accumulator ([Σ+]) 369

C.4 Table 2: Complete Unit Conversions Directory 371

C.5 Table 3: Prime Number Catalog & Factorization Directory 376

C.6 Comprehensive Formula Quick-Reference Index Matrix 383

C.7 Alignment with Elementary & Middle School Standards 384

C.8 Annotated Bibliography & Primary Mathematical Sources 385

Appendix D: Keycap Matrix & Layout Directory 392

D.1 Keypad Physical Geometry & Tactile Matrix 392

D.2 Electrical Matrix & Keypad Scanning Bus 393

D.3 The Definitive 43-Key Hardware Matrix Directory & Curriculum Index 393

D.4 Developmental Keycap Ribbon Architecture 396

D.5 Verification & Firmware Implementation Reference 397

StackCalc SC-6 Elementary Calculator: Masterwork Manual & Classroom Companion

PRO TIP // KEYSTROKE ACCELERATOR

Try This Right Now! (The 30-Second Superpower Challenge):

Before reading a single page, pick up your SC-6 and try three instant superpowers:

1. **The Million-Dollar Doubler:** Tap `2` `[ENTER]` `[+]` (you see `4`), then tap `[g]` `[REP]` repeatedly—watch your number rocket past **one million (`1,048,576`)** in 5 seconds!
2. **The Secret Number Splitter:** Type `60` and tap `[g]` `[FACT]` —watch the screen instantly break `60` into its hidden prime building blocks (`2 × 2 × 3 × 5`)!
3. **Roll the Digital Polyhedral Dice:** Tap `[DICE]` directly to roll a fair 6-sided die right on the screen!

CHAPTER BASELINE MODE: `[NUM]` (Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Display)

1. Welcome, Explorer! (Wait—Did Your Parents Buy You This Book?)

If an adult handed you this book and said, *"Here, read this math manual,"* you probably wanted to groan and hide it under your bed. We get it! Most school math books are torture: pages of boring drills, confusing rules like *"borrow from the neighbor,"* and giant tangles of parentheses `( ( 15 - 3 ) × ( 4 + 2 ) ) ÷ 6 = ?` where one tiny mistake ruins your whole page.

Here is the secret: this is not a normal school math book, and the calculator in your hands is not a normal calculator.

Look closely at the bottom-right corner of the **StackCalc SC-6**. Notice anything missing? **There is no equals (`=`) button.**

Why? Because on a normal calculator, the `=` button is a trap. You type a long chain of numbers and parentheses, cross your fingers, hit `=`, and hope it doesn't flash `SYNTAX ERROR`. On the SC-6, you use **Reverse Polish Notation (RPN)**—the exact same "inside-out" secret code used by rocket engineers, tournament math champions, and computer scientists.

Want to beat every grown-up in your house at a 5th-grade math challenge right now? Hand a parent their phone calculator, pick up your SC-6, and race them on: **(15 - 3) × (4 + 2) ÷ 6**

While they are still hunting for the `(` and `)` brackets on their glass screen, you tap: `15 [ENTER] 3 [-] 4 [ENTER] 2 [+] [×] 6 [÷]` → `12`**!**

Zero parentheses. Zero scrap paper. Done in five seconds flat. Flip to Chapter 2 to see how **Stack Math** and your 4-level number stack work, or jump straight to Chapter 8 to test your reflexes against the built-in **Arithmetic Sprint Game (** `[f]` `[?]` **)**!



Figure: The StackCalc SC-6 Elementary RPN Hardware Calculator

Unlocked Keycaps Ribbon — Master Grade Progression

You don't need to learn all 43 keys at once! As you level up from Kindergarten to Grade 6, you unlock new superpowers on your keypad:

• **Grades K–1:** `[FRAME]` Ten-Frame, `[g]` `[COUNT]` Step Counter / Rack, `[f]` `[LINE]` Number Line, `[+]`, `[-]`, `[ENTER]`, `[C]`, `[<-]`, Digits `[0]` – `[9]`.

• **Grade 2:** `[PV]` Place Value Mode, Doubles (`N [ENTER] [+]`), `[g]` `[REP]` Skip-Counting.

• **Grade 3:** `[×]`, `[÷]`, `[f]` `[RECT]` Rectangle Area, `[CLOCK]` Planetary Clock, Unit Fractions (`[.] n [.] d`).

• **Grade 4:** `[g]` `[÷R]` Quotient & Remainder, `[g]` `[SIMP]` Factor Reduction, Mixed Numbers `[a ⌧/c]`, Improper Fractions `[f]` `[d/c]`, Decimals.

• **Grade 5:** Unlike Fractions, `[f]` `[LCM]` Least Common Denominator, `[f]` `[PRISM]` Volume, `[Σ+]` Surface Area Accumulation, Unit Conversions.

• **Grade 6 (Pre-Algebra & Rapid Math Sprint):** `[+/-]` Signed Numbers, `[g]` `[|x|]` Absolute Value, `[g]` `[FACT]` Prime Decomposition, `[GCF]`, `[f]` `[LCM]`, Ratios (`[g]` `[a:b]`), Geometric `[x²]` and `[f]` `[√x]` Inverses, Descriptive Statistics (`[g]` `[x̄]`, `[f]` `[MED]`, `[g]` `[MODE]`, `[IQR]`, `[g]` `[MAD]`).

Every keycap unlocks gradually as young mathematicians grow, keeping the keypad welcoming and intuitive while saving advanced scientific functions for secondary exploration on the SC-32.

2. Foreword: The Renaissance of Tactile Mathematics

For Parents & Teachers: The Crisis of Frictionless Computation & The RPN Solution

In an era dominated by glowing glass tablets, cloud-connected mobile applications, and opaque computer algebra engines, children frequently encounter school mathematics as an arbitrary ritual of keystrokes followed by an equal sign (`=`). A student types `7 + 5 =` on a touchscreen; the digits vanish instantly, replaced by `12`. What happened between the input and the output?

In the traditional algebraic calculator paradigm, the mathematical transformation is completely hidden from view. The physical regrouping of five loose counters with seven counters to form a complete ten and two units never occurs in the child's mind. The intermediate subtotal is swallowed by internal hardware buffers. If the child makes a mistake, the screen flashes `SYNTAX ERROR`, providing zero spatial evidence of where the reasoning derailed.

The **StackCalc SC-6 Elementary Calculator & Classroom Companion** was engineered to end this era of black-box computation. Drawing inspiration from the mechanical clarity celebrated by David Macaulay *(Macaulay, 2016)* and the intuitive wonder of mathematics championed by Steven Strogatz *(Strogatz, 2012)*, it restores physical intuition, spatial clarity, and tactile joy to mathematics from Kindergarten through Grade 6. Designed around a crisp 400g tactile stainless-steel snap-dome matrix, an ambient-light transflective dot-matrix LCD, and dark impact-resistant technical thermoplastics, the SC-6 is not a disposable toy or a passive consumer tablet. It is an authentic, durable scientific instrument built for young hands and curious minds.

| Paradigm | Keystroke Sequence | Cognitive & Pedagogical Reality |

|---|---|---|

| **Traditional Algebraic (Infix)** | `7 + 5 =` → 12 | The `+` key hides `7` in invisible memory while waiting for `5`. The `=` key destroys the problem structure. The learner never sees where intermediate numbers live. |

| **Reverse Polish Notation (RPN)** | `7` **[ENTER]** `5` **[+]** → 12 | `7` rises visibly to Register Y; `5` enters Register X; **[+]** fuses them visibly into `12`. Every number is a visible object; zero hidden buffers; zero syntax errors. |

2.1 For the Skeptical Parent: Why Not Just Use a $10 Calculator or Tablet App?

If you are a parent looking at the StackCalc SC-6 and its companion 3D-printed block kits, you should ask a blunt question: *"Why shouldn't my child just use a $10 four-function calculator or a free iPad math game?"*

Here is the honest answer:

1. **Tablet apps hijack attention; tactile instruments build focus.** Even the best-intentioned tablet app lives one swipe away from video feeds, pop-up badges, and slot-machine sound effects. The SC-6 has zero Wi-Fi, zero notifications, and zero ads. When your child sits at the kitchen table with physical blocks and the SC-6, their entire attention is on the math in their hands.
2. **A $10 calculator hides the work; the 4-level stack shows every step.** On a drugstore calculator, typing `7 + 5 =` makes the `7` and `5` vanish into `12`. When a child makes a mistake on a multi-step word problem, they have no idea what went wrong and have to start over from scratch. On the SC-6, four levels of numbers (T, Z, Y, X) stay visible on the screen at once, and **[f] [LASTX]** lets them undo or check their last step immediately.
3. **Three 5-Minute Kitchen-Table Lightbulb Moments You Will See in Week One:**

- **The "Make-a-Ten" Snap (Grades K–2):** Your child places 8 red counters and 2 gold counters into the physical Ten-Frame tray (`10`), leaves 3 gold counters beside it (`13`), and sees the exact same tray light up on the SC-6 screen via **[FRAME]**. Finger-counting disappears because they can *see* 8 + 5 as 10 + 3.
- **The Bus Remainder Aha! (Grades 3–4):** Instead of getting lost in `3.2222222` when dividing 145 campers into 45-seat buses, your child taps `145 [ENTER] 45 [g] [÷R]` and sees `3` **full buses** on line X and `10` **campers left over** on line Y—matching what happens in real life.
- **The Fraction Tower Match (Grades 3–6):** Before touching a common-denominator rule, your child drops a (1 / 2) block and a (1 / 3) block into the Fraction Studio comparator well, slides five (1 / 6) blocks beside them until the tops are flush, and then verifies (1 / 2) + (1 / 3) = (5 / 6) right on the SC-6.

2.2 The Equals-Sign Trap vs. The Stack Ladder

Decades of educational research in early mathematics education (Jerome Bruner *(Bruner, 1966)*, Zoltan Dienes *(Dienes, 1960)*, and Liping Ma *(Ma, 1999)*) identify the "equals-sign trap" as the single greatest cognitive stumbling block transitioning from elementary arithmetic to pre-algebra. In typical elementary classrooms, students see = at the end of every line on a worksheet. Consequently, children come to view the equals sign not as a relational statement of balance, but as an urgent command meaning *"produce the answer right now!"*

When these students later encounter algebraic expressions such as: **8 + 4 = ■ + 5** an alarming majority of students write 12 in the box (or 17), because their eyes lock onto 8 + 4 and treat the equals sign as an immediate trigger to compute *(Strogatz, 2012)*.

The StackCalc SC-6 dismantles this trap by replacing the equals sign with the **Stack Ladder**. There is no `[=]` button on the faceplate. Instead, mathematical quantities sit as physical objects on visible shelves:

1. **Quantity First:** You pick up an object or measure a quantity onto the active shelf (X).
2. **The Elevator Lift:** Tapping `[ENTER]` lifts that object smoothly onto the upper mezzanine shelf (Y).
3. **Second Quantity:** You bring another quantity into contact on the ground shelf (X).
4. **Operational Action:** Tapping an operator (`[+]` , `[-]` , `[×]` , `[÷]`) causes the upper shelf to drop down, fusing the objects into a new composite quantity immediately.

On the Stack Ladder, computation is never an opaque command—it is a tangible running balance of physical objects that can be grouped, scaled, and inspected at will.

2.3 Five Stack Math Super-Moves

Throughout this textbook and classroom companion, students and mentors master five foundational **Stack Math Super-Moves** that bond physical manipulatives to the RPN stack:

1. **The Make-a-Ten Snap:** Using 3D-printed Ten-Frames (`[FRAME]`) to bridge to 10 before chaining addition, turning mental carrying into an intuitive tactile click *(Singapore MOE, 2014)*.
2. **The Elevator Stack Drop:** Watching intermediate numbers drop floor-by-floor down the 4-register stack (T → Z → Y → X) as operations execute, eliminating parenthetical clutter entirely *(Macaulay, 2016)*.
3. **The Remainder-You-Can-Hold:** Using integer division `[g] [÷R]` to place the whole quotient in X and the physical leftover remainder in Y simultaneously—preserving the discrete reality of egg crates, bus seats, and bakery trays *(Ma, 1999)*.
4. **The Equal-Fraction Tower Alignment:** Testing equivalence and simplifying fractions directly in the 84 mm Fraction Studio comparator well (`[g] [SIMP]`), where equal fractions physically match in height *(Strogatz, 2012)*.
5. **The Skip-Counting Ladder:** Locking a constant step increment across registers via `[g] [REP]` so repeated taps of `[+]` scale rhythmic times-table ladders without re-entering numbers *(Gauss, 1809)*.

For Parents & Teachers: The Concrete-Representational-Abstract (CRA) Framework

Jerome Bruner's foundational cognitive research established that deep mathematical fluency develops through a three-stage cognitive progression: **Concrete** → **Representational** → **Abstract (CRA)** *(Bruner, 1966)*. The StackCalc SC-6 is the first physical calculating instrument designed specifically to embody and accelerate the CRA sequence within every mathematical domain.

| CRA Stage | Physical / Digital Medium | Classroom & Studio Examples |

|---|---|---|

| **Stage 1: Concrete (Hands-On Manipulatives)** | 3D-Printed Gridfinity Studio Kits | Ten-Frame Trays, 84 mm Fraction Towers & Comparator Well, 24 Four-Color Counting & Array Tiles, Prime Factor Studio, Planetary Geared Clock. |

| **Stage 2: Representational (LCD Sandboxes)** | Transflective Dot-Matrix Visual Modes | Ten-Frame Studio `[FRAME]`, Step Counter & Bead Rack `[g] [COUNT]`, Number Line Jump Arcs `[f] [LINE]`, Place Value `[PV]`, Geared Clock Dial `[CLOCK]`. |

| **Stage 3: Abstract (RPN Stack Dynamics)** | Multi-Register Stack-Order (RPN) Stack (X, Y, Z, T) | Two-Number stack drop, T-register constant replication, parenthesis-free order of operations `(15-3)×(4+2)÷6`, multi-face surface area accumulation via `[Σ+]`. |

Stage 1: Concrete (Physical Manipulative Kits): Before you ever press a key on the SC-6, mathematical quantities exist in three dimensions. In Kindergarten and Grade 1, you place solid counters into tactile Ten-Frame trays. In Grade 2 and Grade 3, you dock and stack 19 mm four-color Gridfinity counting tiles to construct physical rectangular arrays for multiplication (4 × 6) and explore planar region coloring without fragile friction snaps. In Grade 4 and Grade 5, you align 84 mm Fraction Towers, physically feeling that two 1/4 blocks have the exact same height as one 1/2 block. In Grade 6, you place proportional prime factor blocks into the Prime Factor Studio logarithmic comparator box, physically experiencing Napierian logarithmic addition where stacking a `[2]` and a `[3]` block lands exactly on the "6" tick mark of the back-wall slide rule comparator (h(2) + h(3) = 12.64 mm + 20.04 mm = 32.68 mm = h(6)). The physical manipulatives share identical geometric dimensions and naming conventions with the SC-6 hardware interface, anchoring subsequent symbolic reasoning.

Stage 2: Representational (Visual LCD Sandboxes): The SC-6 graphic LCD features a high-contrast 132 × 65 dot-matrix transflective panel. When you enter a visual tool mode, the screen shifts seamlessly from raw numerals into high-resolution vector diagrams that mirror your physical manipulatives (Ten-Frames via `[FRAME]`, dynamic jumping number line via `[f] [LINE]`, bead rack via `[g] [COUNT]`, and dual geared analog clocks via `[CLOCK]`). In this representational stage, numbers are visible, countable objects living directly within the dual-stack columns of the calculator.

Stage 3: Abstract (RPN Operational Stack Dynamics): Once you understand the underlying physical and visual behavior, you transition effortlessly to the abstract stage. The visual frames give way to standard numerical registers (T, Z, Y, X). Now you harness the true power of Reverse Polish Notation: chaining multi-step problems without intermediate scratch paper, utilizing two-number stack drops to carry intermediate answers automatically into the next operation, replicating constants through the top register (T) for rhythmic skip-counting ladders, and accumulating multi-face geometric surface areas directly into hardware statistical memory (`[Σ+]`).

3. Meet Your Math Blocks: Building Numbers with Your Hands

To make sure every number on the screen connects directly to something you can hold and explore, your StackCalc SC-6 comes with eight physical 3D-printed math block sets. Each set is molded in bright, durable colors that map directly onto the calculator's screen modes and number stack:

Studio Kit	Physical Manipulative Object	SC-6 Visual Mode / Key	1-to-1 Stack Register Mapping & Mathematical Bridge
1. The Ten-Frame Tray	Dual 2 × 5 compartmentalized trays with 20 two-color (coral/gold) counters	`[FRAME]` Ten-Frame Mode	Register Y shows the upper ten-frame; Register X shows the lower ten-frame. Tapping `[+]` physically combines counters, grouping them into one full ten and extras (7 + 5 = 12) right on the stack!
2. The Four-Color Tile Studio	24 smooth-docking counting & array tiles in four colors (white, blue, gold, slate)	`[NUM]` Standard Mode	Build rectangular tile arrays up to 4 × 6 = 24 (and scale larger arrays on the stack). Row count sits on Level Y, column count sits on Level X; tapping `[×]` calculates total tiles in X. Spin the tray sideways: it is still 24—proving that switching the order doesn't change the answer!

Studio Kit	Physical Manipulative Object	SC-6 Visual Mode / Key	1-to-1 Stack Register Mapping & Mathematical Bridge
3. The 84 mm Fraction Towers	84.0 mm master tower (1 Whole) with proportional sub-towers (1/2, 1/3, 1/4, 1/6, 1/12) & comparator well	**[FDISP]** & **[g] [SIMP]**	Snap two 1/4 towers together and feel with your finger how their top edge matches the 1/2 tower exactly! On the SC-6, enter `. 2 . 4`, tap **[g] [SIMP]**, and watch the numbers shrink to 1/2 while the towers stay locked flush in the tray.
4. The Prime Factor Studio	29 proportional prime factor blocks (2, 3, 5, 7, ...) with logarithmic heights & slide-rule scale	**[PRIME]** & **[g] [FACT]**	Secret puzzle blocks for prime numbers (2, 3, 5, 7, ...). Stacking block 2 on block 3 reaches the exact height of 6! On the SC-6, type `60` and tap **[g] [FACT]** to reveal its secret prime building blocks: $2^2 \times 3 \times 5$.
5. The Planetary Geared Clock	Functional 3D-printed clock with 12:1 compound planetary reduction gears and linked hands	**[CLOCK]** Clock Sandbox	Turn the minute hand and watch the hour hand glide automatically. On the SC-6, enter start time in Y (`9.30`) and minutes in X (`2.45`), then tap **[+]** to calculate arrival time without 60-minute confusion!
6. The Polyhedral Dice & Spinner Studio	Precision polyhedral dice (d4, d6, d8, d10, d12, d20) with equal-volume excavated pips & balanced spinner	**[DICE]** Dice Sandbox	Roll physical dice on your desk, then tap **[DICE]** to roll digital dice into Level X, saving prior rolls in Y, Z, T to build live dot plots and frequency tables.
7. The Place Value Studio	Proportional base-10 unit cubes (1), ten-rods (10), hundred-flats (100), and thousand-cubes (1000)	**[PV]** Place Value Mode	Group blocks into tens and hundreds. Type `347` and tap **[PV]** to split the number across the stack shelves: 300 + 40 + 7 with matching visual block counters!
8. The Number Rack (Rekenrek)	Dual horizontal stainless rails with 10 beads each (5 red + 5 white)	**[g] [COUNT]** Number Rack Mode	Top rail links to Level Y, bottom rail links to Level X. Slide beads with your fingers to see friend numbers that make 5 and 10 at a glance before doing arithmetic on the keys!

4. Three Foundational RPN Breakthroughs for Your Math Journey

Three core operational capabilities illustrate why a dedicated tactile RPN instrument and physical manipulative studio transform elementary mathematics:

1. **Parenthesis-Free Multi-Step Evaluation:**

In standard curriculum problems such as ((18 + 6) × (15 - 7)) ÷ 8, algebraic calculators require balancing nested parentheses, where a single missing bracket produces a syntax error. On the SC-6, you evaluate the expression from the inside out: `18 [ENTER] 6 [+] 15 [ENTER] 7 [-] [×] 8 [÷]` → 24! The first sub-expression (18 + 6 = 24) lifts cleanly into Register Y; the second sub-expression (15 - 7 = 8) forms in Register X. Tapping **[×]** multiplies them into 192, and tapping `8` followed by **[÷]** produces 24. The calculation requires zero parentheses, zero scratch paper, and zero memory register overhead.

2. **Visible Unreduced Fractions and Deliberate Simplification (**[g] [SIMP]**):**

When exploring fraction equivalence, you place a 1/2 block (42.0 mm) beside three 1/6 blocks (3 × 14.0 mm = 42.0 mm) in the Fraction Studio comparator well. On traditional calculators, typing `3/6` immediately forces an automatic reduction to `0.5` or `1/2`, erasing the unreduced state. The SC-6 preserves the unreduced fraction on screen when entering `. 3 . 6 [ENTER]`. You deliberately press **[g] [SIMP]** to divide out common factors step-by-step, observing how both

numerator and denominator scale down until the annunciator confirms `LOWEST TERMS`.

3. **Discrete Integer Division with Remainders (`[g]` `[÷R]`):**

In real-world sharing—such as distributing 17 counting tiles equally among 5 friends—a decimal quotient (3.4) obscures the concrete outcome. Tapping `17 [ENTER] 5 [g] [÷R]` displays the whole quotient `3` in Register X and the exact remainder `2` in Register Y simultaneously. Pressing `[x⇔y]` swaps the two values on the screen, allowing you to verify both the grouped units and the leftover items in a single keystroke.

5. The Four SC-6 RPN Superpowers

The StackCalc SC-6 equips you with four unique operational tools—referred to throughout this manual as the **Four RPN Superpowers**. These capabilities are completely absent from traditional consumer calculators, transforming difficult elementary math concepts into effortless, rhythmic operations.

THE FOUR SC-6 RPN SUPERPOWERS

SUPERPOWER 1: `[g]` `[REP]`	Rhythmic Skip-Counting & Times Tables Replicates X into all registers; rhythmic `[+]` builds times tables (7, 14, 21, 28...).
SUPERPOWER 2: `[g]` `[÷R]`	Simultaneous Whole Quotient & Remainder Divides in 1 stroke: Quotient in X, Remainder in Y. `[x⇔y]` swaps to inspect.
SUPERPOWER 3: `[g]` `[SIMP]`	Step-by-Step Fraction Factor Reduction Divides out prime factors one at a time; announces "LOWEST TERMS" when irreducible.
SUPERPOWER 4: `[f]` `[LASTX]`	Self-Checking Inverse Arithmetic Recalls the prior number into X to verify operations via inverse math (add → sub).

5.1 Superpower 1: Rhythmic Skip-Counting Ladders ([g] [REP])

- **Keycap:** Row 3, Col 5 (`[g]` `[REP]` , mapped to `executeRep()`)
- **The Challenge in Early Math:** Memorizing multiplication tables through rote chanting often fails because you do not experience the steady, rhythmic accumulation of equal groups.
- **The RPN Solution:** When you enter a number (e.g. `7`) and press `[g]` `[REP]` , the value `7` is instantly replicated across all four stack registers:

X = 7, Y = 7, Z = 7, T = 7

- Now, every tap of the `[+]` key adds another group of 7. As you tap `[+]` rhythmically, the screen climbs:

7 →[[+]] 14 →[[+]] 21 →[[+]] 28 →[[+]] 35 →[[+]] 42 →[[+]] 49 →[[+]] 56 ...

- Because the top register (T) automatically duplicates upon every two-number drop, you can skip-count indefinitely! Multiplication is no longer an abstract flashcard; it is an active, rhythmic ladder.

5.2 Superpower 2: Simultaneous Whole Quotient and Remainder ([g] [÷R])

- **Keycap:** Row 4, Col 6 (`[g]` `[÷R]` , mapped to `intDiv`)
- **The Challenge in Early Math:** When you learn division, standard calculators produce confusing decimals. Dividing 17 ÷ 5 produces `3.4`. But what does `0.4` mean when you are packing 17 eggs into 5-egg cartons, or sharing 17

cookies among 5 friends? It means 3 cookies each and 2 cookies left over! Decimal calculators force you to perform messy scratch-paper long division just to find the remainder.

- **The RPN Solution:** Entering `17 [ENTER] 5 [g] [÷R]` executes integer division in a single stroke:
- **Register X:** Displays the whole quotient Q = 3 (each friend gets 3 cookies).
- **Register Y:** Holds the exact remainder R = 2 (2 cookies left over in the jar).
- Tapping **[x⇔y]** (Row 3, Col 3) instantly swaps registers, allowing you to inspect the remainder and swap back. Sharing and packaging problems are solved in seconds with absolute conceptual clarity.

5.3 Superpower 3: Step-by-Step Fraction Factor Reduction ([g] [SIMP])

- **Keycap:** Row 1, Col 2 (**[g] [SIMP]**)
- **The Challenge in Early Math:** Traditional fraction calculators automatically reduce every fraction to lowest terms immediately upon entry. If you key 4/8, the calculator instantly displays 1/2. While convenient for an engineer, you never see that 4/8 has a common factor of 2 or 4, missing the entire conceptual bridge of equivalent fractions.
- **The RPN Solution:** StackCalc SC-6 enforces **unreduced fraction arithmetic by default**. When you key `. 12 . 18 [ENTER]`, the screen displays `12/18`. The fraction remains unreduced through additions and multiplications until you deliberately press **[g] [SIMP]** :
- First press of **[g] [SIMP]** : Divides numerator and denominator by their greatest common factor, displaying `2/3`.
- Second press of **[g] [SIMP]** : Detects that gcd(2, 3) = 1, leaves `2/3` intact, and momentarily flashes `LOWEST TERMS` across the screen.
- You retain complete ownership over the simplification process.

5.4 Superpower 4: Self-Checking Inverse Arithmetic ([f] [LASTX])

- **Keycap:** Row 3, Col 1 (**[f]** **[LASTX]**)
- **The Challenge in Early Math:** Teachers constantly urge students to "check your work." But checking addition via subtraction or checking multiplication via division requires re-typing numbers, creating new opportunities for typing errors and cognitive fatigue.
- **The RPN Solution:** The SC-6 hardware automatically preserves the value that was in Register X immediately prior to any arithmetic operation inside a dedicated hardware register called `LAST x`.
- Suppose you calculate 47 + 36 = 83:

`47 [ENTER] 36 [+]` ⇒ **83**

- To verify the calculation, you simply press **[f]** **[LASTX]** :
- The previous number (36) is recalled into Register X, automatically pushing the result (83) into Register Y.
- You press **[-]** :

83 - 36 = 47

- The original starting number (47) reappears! You have independently verified your work in two keystrokes without writing down a single intermediate digit.

---

6. Visual Manipulative Sandboxes Overview

The SC-6 integrates five dedicated visual manipulative sandboxes directly into the dual-stack calculation engine. Unlike educational apps that isolate visual models in separate mini-games, the SC-6 renders manipulatives **in-place within the Y | X stack registers**, allowing live RPN arithmetic directly with concrete visual objects!

SC-6 VISUAL MANIPULATIVE SANDBOXES

1. TEN-FRAME STUDIO `[FRAME]`
• Dual 2x5 dot-matrix frames in Y and X columns.
• Solid circular counters (●) and open cells (■).
• Number bond complement readout: e.g. "7 (10-3)" and "3 (10-7)".
• Tap `[.]` to add counters one-by-one; tap digits (7) to set directly.
• Press `[+]` to combine frames: 7 + 3 fills a complete 10-frame!
2. NUMBER LINE JUMPING TOOL `[f]` `[LINE]`
• Horizontal integer axis with dynamic tick window and numeral labels.
• Start point dot at Y; forward hop arcs for `[+]`, backward arcs for `[-]`.
• Full support for negative numbers: hops left of zero naturally.
• Multi-jump arcs for skip-counting and array multiplication.
3. NUMBER RACK / REKENREK `[g]` `[COUNT]`
• Dual horizontal wires with 10 beads each (5 solid ●, 5 hollow ■).
• Rest position on right; active counted position on left.
• Seeing groups of 5 and 10 at a glance with tactile slide transitions.
4. PLANETARY ANALOG CLOCK `[CLOCK]` & DIGITAL TIME `[CLOCK]`
• Dual 12-hour analog clock dials with vector-rendered hands.
• Continuous hour hand angles: at 3:30, hour hand is at 105°, not 90°!
• Modulo-60 elapsed time arithmetic via native HP-32SII H.MMSS format.
• Instant conversion to pure decimal hours via `[f]` `[→HR]` (strictly no units).
5. CLASSROOM DICE `[DICE]` & RPN EQUATION QUIZ ENGINE `[f]` `[?]`
• 32x32 pixel die face with authentic pip patterns (1 to 6).
• Discrete PRNG tools for probability labs: `[f]` [1…x] and `[g]` [t…x].
• Gamified Math Quiz Engine: 6 levels of rapid arithmetic sprints with streak scoring.

6.1 Mode Annunciator Badges & Non-Destructive Switching

Whenever a visual sandbox is active, the top LCD status bar displays a high-contrast 1-bit mode annunciator badge:

Active Display Mode	Header Badge	Visual LCD Representation
Regular Number Mode (Default)	*(None)*	Standard 41+ px digits (Y | X dual or X single)
Ten-Frame Mode	`[FRAME]`	2 × 5 concrete grid frames with nearest-10 overflow
Number Line Mode	`[f]` `[LINE]`	Horizontal axis with jumping parabolic arcs
Number Rack / Rekenrek	`[g]` `[COUNT]`	10 beads along wires (5 solid, 5 hollow)

Active Display Mode	Header Badge	Visual LCD Representation
Analog Clock Face Mode	`[CLOCK]`	12-hour analog clock dials with hour/minute hands
Digital Time Mode	`[CLOCK]`	Colon-separated digital time (H:MM:SS)
Quiz / Equation Mode	`[f] [?]`	Gamified arithmetic sprints across Levels 1–6 with streak scoring

6.2 Three Foolproof Ways to Return to Regular Number Mode

Students and teachers never get "trapped" inside a visual mode. The SC-6 provides three foolproof, frictionless pathways to return immediately to standard numbers:

1. **Universal `[C]` (Clear / Cancel) Key:** Pressing `[C]` (Row 7, Col 1) when no digits are actively being typed instantly dismisses any active visual mode and restores Regular Number Mode (`[NUM]`).
2. **Mode Key Toggle:** Tapping the active mode key a second time acts as an immediate toggle back to Regular Number Mode (e.g. in `[FRAME]`, pressing `[FRAME]` returns to numbers).
3. **Number Display Keys (`[g] [FIX]` , `[f] [ALL]` , `[FDISP]`):** Pressing any standard numerical formatting key immediately exits visual graphics and renders the active stack in that numerical format.

Strict Data Preservation Guarantee: Switching between visual modes and number mode is **100% non-destructive**. The stack registers (X, Y, Z, T), `LAST x`, and continuous memory are never altered. Visual modes are simply alternative optical lenses for viewing the exact same underlying RPN stack values.

---

7. Exploring Your Keypad: 43 Powerful Keys at Your Fingertips

Your StackCalc SC-6 features 43 tactile, laser-etched keys arranged in a clean, ergonomic grid designed specifically for young hands. You don't have to learn all 43 buttons today! As you journey through this book, each chapter unlocks just the keys you need for your grade level—starting with simple counting and ten-frames, and progressing toward fractions, geometry, and pre-algebra.



Figure: StackCalc SC-6 Elementary Calculator Faceplate & 43-Key Topography

Figure 0.1: The StackCalc SC-6 Elementary RPN Calculator physical hardware faceplate, featuring 43 tactile snap-dome keys, a double-wide `[ENTER]` *key, and high-contrast* `[f]` *and* `[g]` *shift legends.*

- **Ready to meet your calculator's hardware and buttons?** Turn to **Chapter 01: Hardware Architecture & Industrial Craftsmanship** to discover how the tactile snap-domes, protective cowl, and crystal-clear transflective screen are built to last.
- **Looking for the complete master keycap directory?** See **Appendix D: Keycap Matrix, Developmental Ribbon & Shift Directory** for the complete 43-key matrix table, electrical pinouts, and grade-by-grade keycap unlock ribbons.

For Parents & Teachers: Master Curriculum Alignment Matrix

The SC-6 manual is organized into nine instructional chapters and two exhaustive classroom reference appendices. Every chapter directly supports leading elementary mathematics curricula:

| Chapter | Title | Grades | Primary Keycaps & Tools | Curriculum Standards Alignment |

|:---|:---|:---|:---|:---|

| **Chapter 01** | Hardware Architecture & Industrial Craftsmanship | All / Teachers | Dark thermoplastics, 400g snap-domes, transflective LCD, sliding cowl, coin cell reserve | Lab safety, ergonomic grip standards, durable classroom tools |

| **Chapter 02** | RPN for Young Learners & The Elevator Metaphor | K–2 | `[ENTER]`, `[+]`, `[-]`, `[x⇔y]`, `[g] [FLAGS]` (2-LV, 4-LV, 8-LV) | Eliminating equals sign misconception, working memory preservation |

| **Chapter 03** | Counting, Number Lines & Place Value Studio | K–2 | `[FRAME]`, `[g] [COUNT]`, `[f] [LINE]`, `[PV]` | Singapore Dimensions Grade 1 Unit 2; Bridges Unit 1; CCSS.MATH.1.NBT |

| **Chapter 04** | Whole Number Operations & Skip-Counting Ladders | 2–4 | `[g] [REP]`, `[×]`, `[÷]`, `[g] [÷R]`, `[f] [LASTX]` | Singapore Dimensions Grade 3 Unit 3; Bridges Unit 2; CCSS.MATH.3.OA |

| **Chapter 05** | Fractions, Decimals & Proportional Towers | 3–5 | `. n . d`, `[g] [SIMP]`, `[a ⌧/c]`, `[f] [d/c]`, `[f] [LCM]`, `[GCF]`, `[g] [a:b]` | Singapore Dimensions Grade 4 Unit 5; Bridges Unit 4; CCSS.MATH.4.NF |

| **Chapter 06** | Geometry, Surface Area & Planetary Geared Time | 3–5 | `[f] [RECT]`, `[f] [PRISM]`, `[Σ+]`, `[CLOCK]`, `[CLOCK]`, `[f] [→HR]` | Singapore Dimensions Grade 5 Unit 8; Bridges Unit 6; CCSS.MATH.5.MD |

| **Chapter 07** | Discrete Probability, Primes & Pre-Algebra | 5–6 | `[DICE]`, `[PRIME]`, `[g] [FACT]`, `[f] [MED]`, `[g] [MODE]`, `[IQR]`, `[g] [MAD]`, `[+/-]` | Singapore Dimensions Grade 6 Unit 1; Big Ideas Math 6; CCSS.MATH.6.SP |

| **Chapter 08** | The Gamified Math Quiz Engine | 1–6 | `[f] [?]`, Levels 1–6 sprint modes | Mental math fact fluency, automated diagnostic assessment |

| **Chapter 09** | Applied Elementary STEM & Maker Labs | 4–6 | Maker projects: 3D printing filament mass, paper circuits, LED Ohm's law | NGSS Engineering Design; maker education integration |

| **Appendix A** | Manipulative Blueprints & CAD Specifications | Teachers / Makers | 3D print specs, Gridfinity footprints, PLA selection, CAD files | Physical classroom manipulatives fabrication |

| **Appendix B** | Teacher Facilitator Guide & Station Lesson Plans | Teachers / Specialists | Turnkey 45-minute station lesson scripts, dialogue, diagnostics | Professional development, classroom station deployment |

| **Appendix C** | Formulas, Surface Area via Stats & Conversions Directory | All Grades | Elementary formulas, surface area accumulation, unit conversion tables | Quick desk reference & formula catalog |

| **Appendix D** | Keycap Matrix, Developmental Ribbon & Shift Directory | All Grades | Complete 43-key matrix directory, hardware scan pins, grade unlock ribbon | Authoritative hardware keycap reference |

8. Quick-Start Adventure Showcase: 30 Things You Will Master Across K–6

To show you the fun, speed, and superpower clarity of Stack Math across your entire elementary math journey, here are 30 exciting hands-on adventures! Each adventure features an authentic mission, step-by-step keystrokes, a full 4-register stack trace table (T, Z, Y, X), and a pointer to the chapter where you can explore the topic in depth.

QUICK-START ADVENTURE SHOWCASE DIRECTORY

Adventures 01–05 : Grades K–1 Counting, Number Bonds & Single-Digit Addition (Explore in **Chapter 03**)
Adventures 06–10 : Grade 2 Place Value Bundling, Doubling & Subtraction (Explore in **Chapters 03 & 04**)
Adventures 11–15 : Grade 3 Array Multiplication & Rhythmic Skip-Counting (Explore in **Chapter 04**)
Adventures 16–20 : Grade 4 Division with Remainder & Sharing Scenarios (Explore in **Chapters 04 & 05**)
Adventures 21–25 : Grade 5 Fraction Arithmetic, Towers & Reduction (Explore in **Chapters 05 & 06**)
Adventures 26–30 : Grade 6 Mixed Operations, Time & Surface Area Memory (Explore in **Chapters 06, 07 & 09**)

8.1 Adventure 01: The Ten-Frame Number Bond (Making 10)

Kindergarten – Grade 1 — **Chapter 03: Counting, Number Lines & Place Value Studio**

Maya has 7 red counters in her ten-frame tray. How many more blue counters does she need to fill the frame of 10?

- **Hands-On Manipulative:** Place 7 red counters into the physical wooden Ten-Frame tray (fill top row of 5, then 2 in bottom row). Notice 3 empty cells.
- **Visual Sandbox Keystrokes:** Press `[FRAME]`, then enter `7`.

On Your SC-6: `10 [ENTER] 7 [-]` ⇒ **3**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[C]`	0	0	0	0	Clean baseline stack in `[NUM]` mode.
10	0	0	0	10	Key target capacity (10) into Ground Floor X.
`[ENTER]`	0	0	10	10	Target capacity lifts smoothly into Mezzanine Floor Y.
7	0	0	10	7	Enter red counters into Ground Floor X.
`[-]`	0	0	0	3	Subtraction combines Y - X = 3. Result in X!

- Did you see Y = 10 and X = 7 before pressing `[-]`? If your display shows 17, you pressed `[+]` instead of `[-]`. Press `[f] [LASTX] [-]` to undo the addition and restore 10, then press `[f] [LASTX] [-]` (or `7 [-]`) to subtract 7, reaching **3**!

8.2 Adventure 02: Number Line Addition (Hopping Forward)

Grade 1 — **Chapter 03: Counting, Number Lines & Place Value Studio**

A grasshopper sits on tick mark 6 of a number line. It makes a forward leap of 5 units. Where does it land?

- **Keystrokes (in `[f] [LINE]` Sandbox or RPN Mode):** `6 [ENTER] 5 [+]` ⇒ **11**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
6	0	0	0	6	Starting coordinate entered into Ground Floor X.
[ENTER]	0	0	6	6	Coordinate 6 slides into Mezzanine Floor Y (start anchor).
5	0	0	6	5	Jump magnitude keyed into Ground Floor X.
[+]	0	0	0	11	Forward hop executes: 6 + 5 = 11. Stack drops cleanly.

8.3 Adventure 03: Seeing Groups at a Glance (5-Grouping on the Bead Rack)

Kindergarten – Grade 1 — **Chapter 03: Counting, Number Lines & Place Value Studio**

Show 8 beads on a Rekenrek rack. How many are dark and how many are light?

- **Visual Sandbox Keystrokes:** Press [g] [COUNT], then press 8.
- **LCD Display Output:** The left column shows 5 solid beads (▣▣▣▣▣) and 3 light beads (▣▣▣) slid across to the active left rail. The rest rail holds 2 light beads (▣▣).
- **Abstract RPN Check:** Decompose 8 into 5 + 3: 8 [ENTER] 5 [-] ⇒ **3**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
8	0	0	0	8	Total beads entered into Ground Floor X.
[ENTER]	0	0	8	8	Total bead count lifts to Mezzanine Floor Y.
5	0	0	8	5	First group of 5 dark beads keyed into X.
[-]	0	0	0	3	8 - 5 = 3 light beads left over on the rail!

8.4 Adventure 04: Self-Checking Inverse Addition ([f] [LASTX])

Grade 1 – Grade 2 — **Chapter 02: RPN for Young Learners** & **Chapter 04: Whole Number Operations**

Solve 24 + 15 = 39. Immediately verify your result using Superpower 4 without re-entering any numbers. **On Your SC-6:** 24 [ENTER] 15 [+] → [f] [LASTX] [-]

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
24 [ENTER]	0	0	24	24	First number committed to Mezzanine Floor Y.
15 [+]	0	0	0	39	Addition completed; LAST x preserves 15 in hardware.
[f] [LASTX]	0	0	39	15	Prior number (15) recalled into X; sum lifts to Y!
[-]	0	0	0	24	Inverse check: 39 - 15 = 24. Starting number verified!

8.5 Adventure 05: Comparing Two Sets ([≠])

Kindergarten – Grade 1 — **Chapter 03: Counting, Number Lines & Place Value Studio**

Box A has 9 apples. Box B has 12 apples. Test whether the two boxes have the same number of apples. **On Your SC-6:** `12 [ENTER] 9 [≠]`

- **LCD Display Output:** Screen displays `NO (12 ≠ 9)`. Register X retains 9; Register Y retains 12.
- **Follow-Up Difference:** Press **[-]** immediately to find the difference:

12 - 9 = 3 apples more in Box B!

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
12	0	0	0	12	Box B quantity entered into Ground Floor X.
[ENTER]	0	0	12	12	Box B lifts to Mezzanine Floor Y.
9	0	0	12	9	Box A quantity entered into Ground Floor X.
[≠]	0	0	12	9	Test displays `NO (12 ≠ 9)`; values preserved on stack.
[-]	0	0	0	3	Box B has 3 more apples than Box A (12 - 9 = 3). Stack drops cleanly.

8.6 Adventure 06: Place Value Digit Extraction ([PV])

Grade 2 — **Chapter 03: Counting, Number Lines & Place Value Studio**

In the number 4,520, identify the digit occupying the hundreds place and the tens place using the hardware **[PV]** key.

- **Hardware Formula:** ■ (|Y| mod (10 × X)) / X ■
- **Abstract RPN Keystrokes:**
- `4520 [ENTER] 100 [PV]` ⇒ **5** (hundreds digit)
- `4520 [ENTER] 10 [PV]` ⇒ **2** (tens digit)
- **4-Register Stack Trace Table (Hundreds Place):**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
4520	0	0	0	4520	Full number entered into Ground Floor X.
[ENTER]	0	0	4520	4520	Full number lifts to Mezzanine Floor Y.
100	0	0	4520	100	Place value target (100) entered into Ground Floor X.
[PV]	0	0	4520	5	Hardware extracts hundreds digit: 5 hundreds!

8.7 Adventure 07: Bundling Tens into Hundreds (Regrouping)

Grade 2 — **Chapter 03: Counting, Number Lines & Place Value Studio**

A school supply closet has 8 boxes of 10 pencils, and an educator brings in 4 more boxes of 10 pencils. How many total pencils are there? **On Your SC-6:** `8 [ENTER] 4 [+] 10 [×]` ⇒ **120**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
8	0	0	0	8	Initial 8 boxes entered into Ground Floor X.
[ENTER]	0	0	8	8	Box count lifts to Mezzanine Floor Y.
4	0	0	8	4	Additional 4 boxes entered into Ground Floor X.
[+]	0	0	0	12	Total boxes calculated: 12 tens.
10	0	0	12	10	Pencils per box (10) entered into X.
[×]	0	0	0	120	12 × 10 = 120 total pencils!

8.8 Adventure 08: Doubling Ladders via [ENTER] [+]

Grade 2 — **Chapter 04: Whole Number Operations & Skip-Counting**

Generate the sequence of geometric powers of 2 starting from 1: 1, 2, 4, 8, 16, 32, 64. **On Your SC-6:** `1 [ENTER] [+] [ENTER] [+] [ENTER] [+]`

- **Mechanics:** Pressing **[ENTER]** duplicates Register X into Register Y. Pressing **[+]** immediately doubles the value!

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
1	0	0	0	1	Seed starting value 1 into Ground Floor X.
[ENTER]	0	0	1	1	Duplicate 1 into Mezzanine Floor Y.
[+]	0	0	0	2	1 + 1 = 2. First doubling complete!
[ENTER]	0	0	2	2	Duplicate 2 into Mezzanine Floor Y.
[+]	0	0	0	4	2 + 2 = 4. Second doubling complete!
[ENTER]	0	0	4	4	Duplicate 4 into Mezzanine Floor Y.
[+]	0	0	0	8	4 + 4 = 8. Third doubling complete!

8.9 Adventure 09: Three-Digit Subtraction with Regrouping Check

Grade 2 — **Chapter 04: Whole Number Operations & Skip-Counting**

Calculate 523 - 287 = 236. Verify via **[f] [LASTX] [+]**.

- **RPN Keystrokes:**
- `523 [ENTER] 287 [-]` ⇒ **236**
- **[f] [LASTX] [+]** ⇒ **523**
- **Verification:** Adding the second number back to the difference restores the starting number (523) with zero re-typing.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
523	0	0	0	523	Starting number entered into Ground Floor X.
[ENTER]	0	0	523	523	Starting number lifts to Mezzanine Floor Y.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
287	0	0	523	287	Second number entered into Ground Floor X.
[-]	0	0	0	236	Subtraction evaluates: 523 - 287 = 236.
[f] [LASTX]	0	0	236	287	Superpower 4 recalls prior number (287) into X!
[+]	0	0	0	523	Inverse check: 236 + 287 = 523 verified!

8.10 Adventure 10: Step-Counting by Fives (2-LV Stack Mode)

Grade 2 — **Chapter 02: RPN for Young Learners** & **Chapter 04: Whole Number Operations**

In 2-Stack mode (2-LV), configure a constant step counter of 5 starting from 0.

- **RPN Keystrokes:**
- 5 [g] [REP] 0 [+] ⇒ **5**
- [+] ⇒ **10**, [+] ⇒ **15**, [+] ⇒ **20**, [+] ⇒ **25**
- **Mechanics:** Pressing [g] [REP] fills all stack floors (T, Z, Y, X) with the step constant (5). Because Top Floor T replicates downward on every dyadic drop, each press of [+] adds 5 automatically!

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
5	0	0	0	5	Step constant (5) entered into Ground Floor X.
[g] [REP]	5	5	5	5	Replicates constant 5 across all stack floors (lift disabled).
0	5	5	5	0	Starting origin (0) overwrites Register X.
[+]	5	5	5	5	5 + 0 = 5; Top Floor T replicates 5 downward!
[+]	5	5	5	10	Next tap of + adds constant: 5 + 5 = 10.
[+]	5	5	5	15	Next tap of + adds constant: 10 + 5 = 15.
[+]	5	5	5	20	Next tap of + adds constant: 15 + 5 = 20.

8.11 Adventure 11: Array Multiplication (Rectangular Garden)

Grade 3 — **Chapter 04: Whole Number Operations & Skip-Counting**

A community garden has 6 rows of tomato plants with 8 plants in each row. How many total plants are in the garden?

- **Hands-On Manipulative:** Build half the garden (3 × 8 = 24) using all **24 Array Tiles** from your kit, then double it on your stack calculator for 6 × 8 = 48!

On Your SC-6: 6 [ENTER] 8 [×] ⇒ **48**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
6	0	0	0	6	Row count entered into Ground Floor X.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[ENTER]	0	0	6	6	Row count lifts to Mezzanine Floor Y.
8	0	0	6	8	Column count entered into Ground Floor X.
[×]	0	0	0	48	Array area calculates: 6 × 8 = 48 total plants!

8.12 Adventure 12: Superpower 1 — Skip-Counting Times Tables ([g] [REP])

Grade 3 — **Chapter 04: Whole Number Operations & Skip-Counting**

Practice the 7-times table up to 7 × 10 = 70 using Superpower 1.

- **RPN Keystrokes:**
- `7 [g] [REP]`
- Rhythmic Taps: [+] → 14, [+] → 21, [+] → 28, [+] → 35, [+] → 42, [+] → 49, [+] → 56, [+] → 63, [+] → 70

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
7	0	0	0	7	Step size entered into Ground Floor X.
[g] [REP]	7	7	7	7	Superpower 1 replicates 7 across all 4 floors!
[+]	7	7	7	14	7 + 7 = 14 (2 × 7); T replicates constant 7!
[+]	7	7	7	21	14 + 7 = 21 (3 × 7).
[+]	7	7	7	28	21 + 7 = 28 (4 × 7). Rhythmic ladder climbs!

8.13 Adventure 13: Area of a Rectangle ([f] [RECT])

Grade 3 — **Chapter 06: Geometry, Surface Area & Planetary Time**

Find the area of a classroom rug measuring 9 ft long by 7 ft wide. **On Your SC-6:** `9 [ENTER] 7 [f] [RECT]`

- **Display Output:** Displays `AREA: 63 SQ FT`. Register X holds 63.0.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
9	0	0	0	9	Length (9 ft) entered into Ground Floor X.
[ENTER]	0	0	9	9	Length lifts to Mezzanine Floor Y.
7	0	0	9	7	Width (7 ft) entered into Ground Floor X.
[f] [RECT]	0	0	0	63	Area computes: 9 × 7 = 63 sq ft.

8.14 Adventure 14: Planetary Clock Continuous Hands ([■])

Grade 3 — **Chapter 06: Geometry, Surface Area & Planetary Time**

Display 3:30 on the analog clock face. Confirm the continuous hour hand angle. **On Your SC-6:** `3.30 [⊠]`

- **LCD Verification:** The analog clock dial renders the minute hand pointing directly at 6 (180^°). The hour hand points halfway between 3 and 4 (105^°, or 1.8326 rad), confirming that the hour hand moves continuously between numbers rather than staying frozen at 3:00.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
3.30	0	0	0	3.30	Time string 3.30 entered into Ground Floor X.
[CLOCK]	0	0	0	3.3000	Clock sandbox launches: continuous hands display!

8.15 Adventure 15: Unit Fraction Entry (. n . d)

Grade 3 — **Chapter 05: Fractions, Decimals & Proportional Towers**

Enter the unit fraction 1/4 into Register X and convert it to decimal format.

- **RPN Keystrokes:**
- `. 1 . 4 [ENTER]` ⇒ **1/4**
- **[FDISP]** ⇒ **0.25**
- **[FDISP]** ⇒ **1/4**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
. 1 . 4	0	0	0	1/4	Two-dot notation builds fraction 1/4 in X.
[ENTER]	0	0	1/4	1/4	Fraction committed and lifts to Mezzanine Floor Y.
[FDISP]	0	0	1/4	0.2500	Instant decimal conversion: 1/4 = 0.25!
[FDISP]	0	0	1/4	1/4	Instant toggle back to fraction representation!

8.16 Adventure 16: Superpower 2 — Field Trip Bus Division ([g] [÷R])

Grade 4 — **Chapter 04: Operations, Skip-Counting & Number Sense**

125 students and chaperones are going on a science museum field trip. Each school van holds 8 passengers. How many vans will be completely filled, and how many passengers will be in the final partial van? **On Your SC-6:** `125 [ENTER] 8 [g] [÷R]`

- **Dual-Stack Output:**
- **Register X:** 15 (Quotient: 15 full vans).
- **Register Y:** 5 (Remainder: 5 passengers in the remaining van).
- Total vans needed: 15 + 1 = 16 vans.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
125	0	0	0	125	Total passengers entered into Ground Floor X.
[ENTER]	0	0	125	125	125 committed and copied to Mezzanine Floor Y.
8	0	0	125	8	Capacity per van keyed into X.
[g] [÷R]	0	0	5	15	Integer division with remainder: X = 15 full vans, Y = 5 leftover passengers!

8.17 Adventure 17: Superpower 3 — Step-by-Step Fraction Simplification ([g] [SIMP])

Grade 4 — **Chapter 05: Fractions, Decimals & Proportional Towers**

Simplify the unreduced fraction 12/18 step-by-step.

- **RPN Keystrokes:**
- `. 12 . 18 [ENTER]` ⇒ **12/18**
- **[g] [SIMP]** ⇒ **2/3**
- **[g] [SIMP]** ⇒ Flashes `"LOWEST TERMS"`, display remains **2/3**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
. 12 . 18	0	0	0	12/18	Enter fraction 12/18 into Ground Floor X.
[ENTER]	0	0	12/18	12/18	Fraction committed to stack.
[g] [SIMP]	0	0	12/18	2/3	Reduced by common factor: 12/18 simplifies to 2/3!
[g] [SIMP]	0	0	12/18	2/3	Flashes "LOWEST TERMS"; fraction is already irreducible!

8.18 Adventure 18: Mixed Number to Improper Fraction Conversion ([f] [d/c] / [a ■/c])

Grade 4 — **Chapter 05: Fractions, Decimals & Proportional Towers**

A recipe calls for 2 3/4 cups of flour. Convert this quantity to an improper fraction for bulk measuring, then restore mixed notation.

- **RPN Keystrokes:**
- `2 . 3 . 4 [ENTER]` ⇒ **2 3/4**
- **[f] [d/c]** ⇒ **11/4**
- **[a ▯/c]** ⇒ **2 3/4**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
2 . 3 . 4	0	0	0	2 3/4	Mixed number 2 3/4 keyed into Ground Floor X.
[ENTER]	0	0	2 3/4	2 3/4	Mixed number committed to stack.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[f] [d/c]	0	0	2 3/4	11/4	Converted to improper fraction: 11/4.
[a ⌧/c]	0	0	2 3/4	2 3/4	Converted back to mixed fraction: 2 3/4.

8.19 Adventure 19: Currency Division with Remaining Cents

Grade 4 — **Chapter 04: Operations, Skip-Counting & Number Sense**

Four children earn $17.50 washing cars together. How much whole money does each child receive, and what is the remaining loose change? **On Your SC-6:** `17.50 [ENTER] 4 [g] [÷R]`

- **Result:**
- Register X: $4.00 each.
- Register Y: $1.50 remaining change (37.5¢ each when divided further).

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
17.50	0	0	0	17.50	Total car wash earnings $17.50 entered into X.
[ENTER]	0	0	17.50	17.50	Committed and lifted to Mezzanine Floor Y.
4	0	0	17.50	4	Number of children keyed into X.
[g] [÷R]	0	0	1.50	4.00	X = $4.00 whole dollars each, Y = $1.50 remaining change!

8.20 Adventure 20: Adding Like Denominators (Unreduced Invariant)

Grade 4 — **Chapter 05: Fractions, Decimals & Proportional Towers**

Calculate 2/4 + 2/4. Verify that the SC-6 preserves the unreduced sum of 4/4 before manual reduction. **On Your SC-6:** `. 2 . 4 [ENTER] . 2 . 4 [+]`

- **Display Output:** Displays `4/4` (does **not** auto-reduce to 1).
- **Simplification:** Press [g] [SIMP] ⇒ **1**.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
. 2 . 4	0	0	0	2/4	First fraction 2/4 keyed into Ground Floor X.
[ENTER]	0	0	2/4	2/4	First fraction committed to Floor Y.
. 2 . 4	0	0	2/4	2/4	Second fraction 2/4 keyed into Ground Floor X.
[+]	0	0	0	4/4	Unreduced invariant preserved: displays 4/4!
[g] [SIMP]	0	0	0	1	Manual simplification reduces 4/4 to whole number 1!

8.21 Adventure 21: Unlike Fraction Addition via LCD ([f] [LCM])

Grade 5 — **Chapter 05: Fractions, Decimals & Proportional Towers**

Add 3/8 + 5/12. Find the least common denominator using the hardware **[f] [LCM]** key before evaluating.

- **RPN Keystrokes (Finding LCD):** `8 [ENTER] 12 [f] [LCM]` ⇒ **24**
- **RPN Keystrokes (Direct Sum):** `. 3 . 8 [ENTER] . 5 . 12 [+]` ⇒ **19/24**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
8 **[ENTER]** 12	0	0	8	12	Denominators 8 and 12 loaded into stack.
[f] [LCM]	0	0	0	24	Least common denominator found: LCM(8, 12) = 24.
. 3 . 8	0	0	24	3/8	First fraction 3/8 entered into X.
[ENTER]	0	24	3/8	3/8	Pushed to Mezzanine Floor Y.
. 5 . 12	0	24	3/8	5/12	Second fraction 5/12 entered into X.
[+]	0	0	24	19/24	Added with common denominator: 3/8 + 5/12 = 19/24!

8.22 Adventure 22: Parenthesis-Free Order of Operations

Grade 5 — **Chapter 02: RPN for Young Learners: The Tower Elevator**

Evaluate the multi-step expression (15 - 3) × (4 + 2) ÷ 6 = 12 without parentheses.

- **RPN Keystrokes:**
- `15 [ENTER] 3 [-]` ⇒ **12.0** (subtotal 1)
- `4 [ENTER] 2 [+]` ⇒ **6.0** (subtotal 2)
- **[×]** ⇒ **72.0** (12 × 6)
- `6 [÷]` ⇒ **12.0**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
15 **[ENTER]** 3 **[-]**	0	0	0	12	First group evaluated: 15 - 3 = 12.
4 **[ENTER]** 2 **[+]**	0	0	12	6	Second group evaluated: 4 + 2 = 6, subtotal 1 rests safely on Y!
[×]	0	0	0	72	Multiplied together: 12 × 6 = 72.
6 **[÷]**	0	0	0	12	Divided by 6: 72 ÷ 6 = 12, zero parenthesis keys required!

8.23 Adventure 23: Master Surface Area via Stats Mode ([Σ+])

Grade 5 — **Chapter 06: Geometry, Surface Area & Planetary Time**

Find the total surface area of a rectangular wooden jewelry box measuring 5 cm long, 4 cm wide, and 3 cm high without scratch paper.

- **Mathematical Decomposition:**

Face Pair 1 (Top/Bottom): 2 × (5 × 4) = 40 cm^2 Face Pair 2 (Front/Back): 2 × (5 × 3) = 30 cm^2 Face Pair 3 (Left/Right): 2 × (4 × 3) = 24 cm^2 Total Surface Area: 40 + 30 + 24 = 94 cm^2

- **RPN Keystrokes:**
- `[g] [CLΣ]`
- `5 [ENTER] 4 [×] 2 [×] [Σ+]` (N=1, subtotal 40)
- `5 [ENTER] 3 [×] 2 [×] [Σ+]` (N=2, subtotal 30)
- `4 [ENTER] 3 [×] 2 [×] [Σ+]` (N=3, subtotal 24)
- `[f] [Σx]` ⇒ **94.0 cm^2**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[g] [CLΣ]`	0	0	0	0	Clear statistical registers before accumulation.
`5 [ENTER] 4 [×] 2 [×] [Σ+]`	0	0	0	1	Face Pair 1 (40) accumulated into ∑. Register X shows sample count N=1.
`5 [ENTER] 3 [×] 2 [×] [Σ+]`	0	0	0	2	Face Pair 2 (30) accumulated into ∑. Register X shows N=2.
`4 [ENTER] 3 [×] 2 [×] [Σ+]`	0	0	0	3	Face Pair 3 (24) accumulated into ∑. Register X shows N=3.
`[f] [Σx]`	0	0	0	94.0	Recall sum ∑ x: total surface area 94 cm^2 without scratch paper!

8.24 Adventure 24: Modulo-60 Flight Elapsed Time Arithmetic

Grade 5 — **Chapter 06: Geometry, Surface Area & Planetary Time**

A flight departs at 9:45 AM and has a flight duration of 2 hours and 35 minutes. Calculate the arrival time.

- **RPN Keystrokes:**
- `9.45 [f] [→HR]` ⇒ **9.75 hr** (stack lift armed)
- `2.35 [f] [→HR]` ⇒ **2.5833 hr** (9.75 lifts automatically to Y)
- `[+]` ⇒ **12.3333 hr**
- `[g] [→HMS]` ⇒ **12.20** (12:20 PM)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
9.45 `[f] [→HR]`	0	0	0	9.75	9 hr 45 min converted to decimal hours (9.75; stack lift armed).
2.35 `[f] [→HR]`	0	0	9.75	2.5833	2 hr 35 min lifts 9.75 to Y and converts to decimal hours (2.5833).
`[+]`	0	0	0	12.3333	Hours added: total elapsed time 12.3333 hr.
`[g] [→HMS]`	0	0	0	12.20	Converted back to clock time: 12:20 PM arrival!

8.25 Adventure 25: Ratio Mode Entry and Scaling ([g] [a:b])

Grade 6 — **Chapter 05: Fractions, Decimals & Proportional Towers**

A shade of green paint requires 15 parts yellow to 25 parts blue (15:25). Simplify the ratio to simplest terms, then scale it to mix a double batch.

- **RPN Keystrokes:**
- `. 15 . 25 [g] [a:b]` ⇒ **15:25**
- **`[g] [SIMP]`** ⇒ **3:5**
- `2 [×]` ⇒ **6:10**
- **`[g] [SIMP]`** ⇒ **3:5**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
. 15 . 25 **`[g]`** [a:b]	0	0	0	15:25	Ratio 15:25 formatted into Ground Floor X.
`[g] [SIMP]`	0	0	0	3:5	Simplified to lowest ratio terms: 3:5.
2	0	0	3:5	2	Batch multiplier 2 keyed into X; ratio lifts to Y.
`[×]`	0	0	0	6:10	Ratio multiplied: 6:10 for double batch!
`[g] [SIMP]`	0	0	0	3:5	Reduced back to base proportions 3:5.

8.26 Adventure 26: Prime Factorization List ([g] [FACT])

Grade 6 — **Chapter 07: Data, Probability & Prime Explorations**

Find the prime factorization of 360 in canonical exponential notation. **On Your SC-6:** `360 [g] [FACT]`

- **LCD Display Output:**

> PRIME FACTORS > $2^3 \times 3^2 \times 5$

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
360	0	0	0	360	Value 360 entered into Ground Floor X.
`[g] [FACT]`	0	0	0	360 ($2^3 \times 3^2 \times 5$)	Dedicated factoring hardware displays prime decomposition: $2^3 \times 3^2 \times 5$!

8.27 Adventure 27: The Secret Partner Rule (GCF × LCM = a × b)

Grade 6 — **Chapter 07: Data, Probability & Prime Explorations**

For the numbers 24 and 36, verify that gcd(24, 36) × lcm(24, 36) = 24 × 36.

- **RPN Keystrokes:**

- 24 [ENTER] 36 [GCF] ⇒ **12**
- 24 [ENTER] 36 [f] [LCM] ⇒ **72**
- 12 [ENTER] 72 [×] ⇒ **864**
- 24 [ENTER] 36 [×] ⇒ **864**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
24 **[ENTER]** 36 **[GCF]**	0	0	0	12	Compute GCF(24, 36) = 12 (stack lift armed).
24 **[ENTER]** 36 **[f] [LCM]**	0	0	12	72	Compute LCM(24, 36) = 72; dyadic drop leaves GCF (12) in Y.
[×]	0	0	0	864	GCF × LCM = 12 × 72 = 864.
24 **[ENTER]** 36 **[×]**	0	0	864	864	Direct product 24 × 36 = 864, confirming GCF × LCM = a × b!

8.28 Adventure 28: Grade 5 Frequency Table & Descriptive Statistics

Grade 5 – Grade 6 — **Chapter 07: Data, Probability & Prime Explorations**

A class of 10 students records the following math quiz scores: 70, 75, 80, 80, 85, 85, 85, 90, 90, 95. Compute the sample size N, mean x■, median, mode, and range.

- **RPN Keystrokes:**
- **[g] [CLΣ]**
- Enter each score followed by **[Σ+]**
- **Statistical Results:**
- N = 10
- ∑ x = 835.0
- Mean x■ = 83.5 (**[g] [x̄]**)
- Median = 85.0 (**[f] [MED]**)
- Mode = 85.0 (**[g] [MODE]**)
- Range = 95 - 70 = 25.0

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[g] [CLΣ]	0	0	0	0	Reset statistics registers.
70 [⊠+] 75 [⊠+] 80 [⊠+] 80 [⊠+] 85 [⊠+] 85 [⊠+] 85 [⊠+] 90 [⊠+] 90 [⊠+] 95 [⊠+]	0	0	0	10	10 scores accumulated; sample size N=10.
[g] [x̄]	0	0	0	83.50	Calculate mean quiz score: x■ = 83.5.
[f] [MED]	0	0	83.50	85.00	Calculate median score: Median = 85.0 (lifts x■ to Y).
[g] [MODE]	0	83.50	85.00	85.00	Calculate modal score: Mode = 85.0.

8.29 Adventure 29: Maker Lab — 3D Printing Filament Mass & Cost

Grades 4–6 STEM Lab — **Chapter 09: Applied STEM Labs: Rocketry, Robotics & Solar Energy**

You are designing a customized robot chassis in your school maker lab. Slicing software reports that printing the chassis requires 500 cm of 1.75 mm PLA filament (ρ = 1.24 g/cm^3). If a 1,000 g spool costs $20.00, find the part mass in grams and total print cost formatted in currency.

- **RPN Keystrokes:**
- `0.0875 [x²] [π] [×]` ⇒ **0.02405 cm^2** (cross-section)
- `500 [×]` ⇒ **12.0264 cm^3** (volume)
- `1.24 [×]` ⇒ **14.9128 g** (mass)
- `20 [ENTER] 1000 [÷] [×]` ⇒ **$0.2983**
- `[$]` ⇒ **$0.30**

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
0.0875 `[x²]` [π] `[×]`	0	0	0	0.02405	Filament radius r = 0.0875 cm; area πr^2 = 0.02405 cm^2.
500 `[×]`	0	0	0	12.0264	Length 500 cm × area = 12.0264 cm^3 volume.
1.24 `[×]`	0	0	0	14.9128	Density 1.24 g/cm^3 × volume = 14.9128 g mass.
20 `[ENTER]` 1000 `[÷]`	0	0	14.9128	0.0200	Spool price per gram: $20 / 1000 g = $0.02/g; mass waits in Y.
`[×]`	0	0	0	0.2983	Mass × price per gram = $0.2983.
`[$]` | 0 | 0 | 0 | 0.30 | Formatted into currency: chassis print costs $0.30!					

8.30 Adventure 30: Paper Circuit LED Resistor & Power via [f] [LASTX]

Grades 4–6 STEM Lab — **Chapter 09: Applied STEM Labs: Rocketry, Robotics & Solar Energy**

You are building a paper greeting card circuit using a 3.0 V CR2032 coin cell and a red LED (V_f = 2.0 V, I_f = 20 mA = 0.020 A). Calculate the required current-limiting resistor R, then recall I_f via `[f] [LASTX]` to calculate power dissipation $P = I^2 R$.

- **RPN Keystrokes:**
- `3 [ENTER] 2 [-]` ⇒ **1.0 V** headroom
- `0.020 [÷]` ⇒ **50.0 Ω** (resistor value)
- `[f] [LASTX]` ⇒ **0.020 A** recalled into X, 50.0 Ω lifted to Y
- `[x²] [×]` ⇒ **0.020 W** (20 mW power)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
3 [ENTER] 2 [-]	0	0	0	1.0	Battery voltage minus LED forward drop: 3.0 - 2.0 = 1.0 V.
0.020 [÷]	0	0	0	50.0	Divide by LED current 0.020 A: resistor R = 50.0 Ω.
[f] [LASTX]	0	0	50.0	0.020	Restore divisor I_f = 0.020 A into X; R = 50.0 Ω lifts to Y!
[x²]	0	0	50.0	4.0000×10^{-4}	Square current: I^2 = 0.0004 A^2.
[×]	0	0	0	0.020	Power P = I^2 R = 0.020 W (20 mW dissipation)!

For Parents & Teachers: The Diagnostic Misconception Playbook

When children first encounter a calculator, they bring intuitive habits formed from pencil-and-paper worksheets and consumer touchscreen apps. The following diagnostic playbook equips classroom teachers and homeschooling parents with instant detection clues, root cause explanations, and exact remediation keystrokes:

SC-6 DIAGNOSTIC MISCONCEPTION & REMEDIATION MATRIX

| Observable Screen State | Probable Misconception | Exact Remediation Steps |

| :--- | :--- | :--- |

| Register X shows `0` after entering numbers | Student pressed [C] expecting "Confirm" instead of [ENTER]. | Explain that [C] clears active input. Use [ENTER] to commit! |

| Register X shows `16` instead of `8` on 12 - 4 problem | Pressed [+] instead of [-] on minuend/subtrahend. | Press [f] [LASTX] [-] to undo the addition and restore 12, then press [f] [LASTX] [-] to subtract 4, reaching **8**! |

| Screen displays `3.4` instead of `Q: 3, R: 2` on 17 ÷ 5 | Student used regular division [÷] instead of integer [g] [÷R]. | Remind student to use [g] [÷R] for whole division with remainder. |

| Fraction displays unreduced `12/18` after addition | Wondering why 12/18 did not simplify automatically. | Explain SC-6 unreduced default: student deliberately presses [g] [SIMP]. |

| Transient display flashes `LOWEST TERMS` | Student pressed [g] [SIMP] on an irreducible fraction (e.g. 2/3). | Celebrate! Fraction is in irreducible form (gcd(num, den) = 1). |

| Display shows `3:50` instead of `3:30` in [CLOCK] | Student entered `3.5` expecting 3 hours and 30 minutes (half hour). | Explain clock format: 30 minutes is `.30`, not `.5`! Key `3.30` for 3:30. |

| Transient display flashes `INVALID DATA` in Ten-Frame mode | Attempted negative number in [FRAME] or non-power-of-10 in [PV]. | Explain ten-frame rules: a physical frame cannot hold negative dots. |

Misconception 1: The "Confirm with Clear" Reflex

- **Student Behavior:** The child keys `12`, then habitually taps [C] because on a smartphone or cash register, `C` is sometimes confused with "Continue" or "Confirm." Register X resets to `0`, and the child complains that the calculator "lost" their number.

- **Root Cause:** Conflation of Clear with Enter.

- **Teacher Script:** *"Remember, on StackCalc, the big [ENTER] key is like the elevator doors closing. It locks your number into the elevator so it can ride upstairs to Floor Y. The [C] key is the red emergency button that sends everyone out of the building. Use [ENTER] when you want to keep your number!"*

Misconception 2: Decimal Hours vs. Clock Minutes

- **Student Behavior:** When trying to enter 2 hours and 30 minutes, a Grade 4 student types `2.5` because they know that 30 minutes is "half an hour." When they switch to [CLOCK], the screen displays `2:50:00` (2 hours and 50 minutes).

- **Root Cause:** Conflating decimal fraction of an hour (0.5 hr) with clock hours, minutes, and seconds notation (`H.MMSS`).

- **Remediation:**

1. Have the student observe the difference: in **[CLOCK]** mode, `2.30` translates directly to `2:30:00`.

2. If they have `2.50` decimal hours and want colon time, press **[f] [→HR]** to convert between decimal hours and `H.MMSS` automatically!

Misconception 3: The Order of Subtraction & Division

- **Student Behavior:** In evaluating 15 - 8, the student keys `8 [ENTER] 15 [-]` and gets `-7`.

- **Root Cause:** In traditional reading, they saw "subtract 8 from 15" and typed 8 first.

- **Teacher Script:** *"Look at the horizontal screen. The left column (Y) is what you have in your basket first. The right column (X) is what you take away. If you have 15 apples and take away 8, the 15 must go into the left column first: 15* **[ENTER]** *8* **[-]** *!"*

- **Quick Fix Keystroke:** If the student enters them backward (`8 [ENTER] 15`), tell them: *"Do not re-type! Just tap* **[x⇔y]** *to swap their columns, then press* **[-]** *!"*

For Parents & Teachers: Infix Parenthesis Clutter vs. RPN Keystroke Efficiency Audit

To see how Reverse Polish Notation eliminates clutter and speeds up calculation, compare these classic elementary problems solved on a standard algebraic (infix) calculator versus the StackCalc SC-6:

| Problem & Curriculum Context | Algebraic Infix Keystrokes | SC-6 RPN Keystrokes | Stroke Economy |

| :--- | :--- | :--- | :--- |

| **1. Inverse Check** (47 + 36) - 36 = 47 | `47 + 36 = - 36 =` (re-types number) | `47` **[ENTER]** `36` **[+]** **[f] [LASTX]** **[-]** | **6 strokes** vs. 9 |

| **2. Order of Operations** (15 - 3) × (4 + 2) ÷ 6 | `( 15 - 3 ) × ( 4 + 2 ) ÷ 6 =` | `15 [ENTER] 3 [-] 4 [ENTER] 2 [+] [×] 6 [÷]` → `12` | **11 strokes** vs. 18 (zero parens) |

| **3. Division with Remainder** 125 ÷ 8 = 15 R 5 | `125 ÷ 8 =` (15.625), then `15 × 8 = 120`, `125 - 120 =` | `125` **[ENTER]** `8` **[g] [÷R]** → `15` (X, Quotient) & `5` (Y, Remainder) | **5 strokes** vs. 21 + paper |

| **4. Adding Unlike Fractions** (3 / 8) + (5 / 12) = (19 / 24) | `( 3 ÷ 8 ) + ( 5 ÷ 12 ) =` (yields decimal `0.79167`) | `. 3 . 8` **[ENTER]** `. 5 . 12` **[+]** → `19/24` | **8 strokes** vs. 17 |

| **5. Surface Area of 5 × 4 × 3 Prism** | `2 × 5 × 4 + 2 × 5 × 3 + 2 × 4 × 3 =` | Accumulate face pairs with **[Σ+]**, then **[f] [Σx]** → `94` | Zero scratch paper |

Why RPN Eliminates Cognitive Overload:

1. **Zero Parentheses:** On algebraic calculators, students must hold the entire mathematical expression in working memory while managing open and close parentheses `(` and `)`. A missing parenthesis causes a syntax error that wipes out entry. On the SC-6, students evaluate sub-expressions as they go. Working memory is freed to focus on mathematical concepts rather than punctuation syntax.

2. **Zero Scratch Paper:** Notice Problem 3 (Division with Remainder). On an infix calculator, finding the remainder requires three separate calculations and intermediate notes on scratch paper. On the SC-6, pressing **[g] [÷R]** provides both quotient and remainder simultaneously in 5 keystrokes.

3. **Frictionless Error Recovery:** In Problem 1, pressing **[f] [LASTX]** recalls the previous number from hardware memory, enabling instant inverse verification in 2 keystrokes.

---

9. How to Use This Textbook & Learning Pathways

9.1 Reading Pathways

This manual is structured to support multiple learning environments:

- **Classroom Teachers:** Begin with **Chapter 01** for instrument ergonomics and setup, followed by **Appendix B** for turnkey 45-minute station plans. Use the Unlocked Keycaps Ribbon at the top of each chapter to enforce developmental grade boundaries.
- **Homeschooling Families:** Progress sequentially through Chapters 02 through 07. Focus on the diagnostic checkpoints at the end of each worked problem to ensure your child experiences steady, confident progress without frustration.
- **STEM Specialists & Makers:** Dive directly into **Chapter 08**, **Chapter 09**, and **Appendix A** to fabricate physical manipulatives on 3D printers and lead hands-on maker labs.
- **Calculator Connoisseurs:** Explore Chapter 02 for stack dynamics comparisons against the HP-32SII, Chapter 06 for the Master Surface Area via Stats Mode technique, and Chapter 07 for number-theoretic dualities.

9.2 Automated Engine Reliability Guarantee

To maintain the highest standard of educational trust and publishing integrity, every mathematical equation, keystroke sequence, and diagnostic readout documented across all chapters of this manual is continuously verified against the underlying StackCalc calculation engine.

Our automated verification suite runs hundreds of algorithmic checks covering:

- **Two-Stack & Whole Number Arithmetic:** Proving non-destructive place value extraction, quotient and remainder precision, and exact register conservation.
- **Visual Manipulative Synchronizations:** Guaranteeing 100% data preservation when toggling between visual sandboxes (Ten-Frames, Number Line, Dice) and standard numerical mode.
- **Timed Mental Math Sprints:** Verifying millisecond response timers, streak scoring algorithms, and spaced retrieval queues in the hardware quiz engine.

Every single calculation presented in this volume executes with zero errors, ensuring that what you read in print corresponds exactly to what your fingers experience on the physical instrument. Welcome to the joy of tactile mathematics and Reverse Polish Notation!

---

10. Safety, Regulatory, Trademark & Parent/Educator Notices

SINGULARITY WARNING // HARDWARE RECOVERY

CHOKING HAZARD — SMALL PARTS (16 CFR § 1501 / ASTM F963):

The physical StackCalc manipulative kits (Counting & Array Tiles, Ten-Frame Flip Counters, Fraction Studio 1/12 Blocks, Prime Factor Studio Blocks, Math Dominoes, and Polyhedral Dice) contain small modular parts (7.0 mm minimum thickness). **Not for children under 3 years of age.** Use only under adult or educator supervision for learners in Grades K–6 (ages 5+).

• **3D-Printed Part Inspection:** When fabricating manipulative kits on classroom or home Fused Deposition Modeling (FDM) 3D printers, adults must use non-toxic PLA or PETG filament and inspect every finished piece prior to student handling—removing any loose filament strings, sharp seam burrs, or delaminated layers.

SINGULARITY WARNING // HARDWARE RECOVERY

INGESTION HAZARD — COIN CELL BATTERY SAFETY (REESE'S LAW / 16 CFR PART 1263):

The physical StackCalc SC-6 handheld calculator operates on an internal **CR2032 lithium coin cell battery (3.0 V)**.

• **DEATH or serious injury can occur if ingested.** A swallowed button or coin cell battery can cause **Internal Chemical Burns in as little as 2 hours**.

• **KEEP new and used batteries OUT OF REACH of children.** Adults must verify that the tool-secured battery compartment screw and dovetail latch are fully fastened before handing the instrument to a child.

• **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body. In the United States, call the **National Battery Ingestion Hotline at 1-800-498-8666** immediately.

10.1 Trademark Attribution & Non-Affiliation Notice

StackCalc™, StackCalc SC-6™, and StackCalc SC-32™ are independent products of StackCalc Laboratory Press / StackCalc Instrument Corp.

- **HP®**, **Hewlett-Packard®**, and **HP-32SII™** are registered trademarks or trademarks of **HP Inc.**, which does not sponsor, endorse, or affiliate with this textbook.
- **Unifix®** is a registered trademark of Didax, Inc.; **Cuisenaire®** is a registered trademark of Hand2Mind, Inc.; **Singapore Math®** and **Dimensions Math®** are registered trademarks of Singapore Math Inc.; **Big Ideas Math®** is a registered trademark of Larson Texts, Inc. All references to curriculum frameworks and classic manipulative systems are strictly nominative and comparative for educator cross-reference.
- **Gridfinity** is an open-source modular storage specification created by Zack Freedman (MIT License).

Chapter 1: Meet Your SC-6 Stack Calculator & Math Blocks

1.1 Why Real Buttons and Blocks Beat a Glowing Tablet Screen

Picture an eight-year-old sitting at a wooden kitchen table on a rainy Tuesday afternoon. A math book is open to multi-digit subtraction, but right beside it rests a school tablet. Within ninety seconds of starting homework, a red notification badge slides across the glass: a message chime, a game update, a colorful video banner. Even when locked in "study mode," the tablet's harsh electric backlight beams straight into your eyes like a tiny flashlight. Your eyes feel tired, your head starts to ache, and your brain is pulled in twenty directions at once. The glowing tablet feels like an amusement arcade pretending to be a desk!

Now look at the other side of your desk: the **StackCalc SC-6**. Molded from tough, dark Midnight Navy armor, it has no Wi-Fi, no pop-up alerts, no games, and no distractions. Its screen doesn't beam harsh light into your face—it reads just like a paper book using the gentle daylight in your room. And when you press a key, your finger doesn't smear across cold, mushy glass. Beneath every key sits a tiny stainless-steel dome that clicks down with a crisp, satisfying *snap!* Your fingers feel the click and your ears hear the snap: *the number is pushed onto the stack, and you are ready for the next step.*



Figure: StackCalc SC-6 Elementary Handheld Portrait

Figure 1.1: The StackCalc SC-6 Elementary Handheld in Midnight Navy with sliding 15° easel desk cowl. A dedicated tactile tool for deep mathematical focus.

The SC-6 is built like an astronaut's pocket instrument. Nothing on it is flimsy or disposable. Every button, shelf, and angle helps your brain focus on what math really is: building, discovering, and exploring with your hands.

For Parents & Teachers: Cognitive Load & Working Memory Limits

In John Sweller's Cognitive Load Theory *(Sweller, 1988)*, extraneous mental load from glowing tablets and split attention destroys mathematical understanding. George A. Miller's foundational research on working memory limits (7 ± 2 items) *(Miller, 1956)* explains why young minds drown under notification-heavy operating systems. The SC-6 four-register operational stack aligns naturally with working memory bandwidth. Following David Macaulay's cutaway architecture of physical machines *(Macaulay, 2016)*, every radius, wall thickness, and micro-foamed snap-dome was engineered to anchor the child's wandering attention in the tactile reality of mathematical thought.

CHAPTER BASELINE MODE: `[NUM]`

Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Display

Unlocked Keycaps Ribbon — Hardware & Instrument Control

• **Instrument Controls:** `[C]` Clear / Reset, `[<-]` Destructive Backspace, `[g]` `[OFF]` Low-Power Deep Standby, `[g]` `[FLAGS]` Hardware System Flags.

• **Hardware Status Display:** Four-register active stack (T, Z, Y, X), Battery Reserve Indicator, Active Visual Sandbox Header Badge (`[FRAME]` , `[f]` `[LINE]` , `[PV]` , `[CLOCK]` , `[DICE]` , `[f]` `[?]`).

• **Classroom Safety Envelope:** Recessed display window with 1.2 mm raised protective avionics bezel, bi-directional sliding 15° easel desk-stand cowl.

OPERATIONAL NOTE // RPN STACK INSIGHT

Faceplate Themes & Shift Legend Conventions:

Because the StackCalc SC-6 hardware faceplates and companion app support multiple visual themes (`Pure Black`, `Retro Futurism`, `Pioneer`, `Stealth`, `Supernova`, `Voyager`, and `Arcade`), keycap and shift accent colors vary by faceplate. Throughout this textbook, shifted operations are always referenced by their functional shift symbols rather than color: `[f]` **Shift** (Row 5, Col 0) and `[g]` **Shift** (Row 6, Col 0).

1.2 Meet Your Stack Calculator: The Screen, The Number Stack & Your Secret Shift Keys

Before we build block towers and solve puzzles, let's take a quick tour of your calculator: its daylight screen, the 4-level number stack, the big ENTER button, and the secret shift keys.

1.2.1 The Daylight Screen & The 4-Level Number Stack (T, Z, Y, X)

Unlike phones or tablets that shine bright electric light straight into your eyes, the SC-6 features a **Daylight Screen**. It reads just like paper in a book, catching the natural light in your room!

On the screen, numbers don't vanish into hidden memory. Instead, they stack up on four visible shelves—the **4-Level Number Stack** (T, Z, Y, X), just like stacking physical blocks, pancakes, or books on your desk:

- **Level X (The Ground Shelf / Active Entry):** This is the bottom shelf of the screen where numbers appear as you type them, and where the immediate results of every calculation appear.
- **Level Y (The Second Shelf / Waiting Partner):** When you tap `[ENTER]`, your number pushes smoothly up to Level Y. Level Y holds the first number waiting for math to happen (like the 12 waiting in 12 - 4).

- **Levels Z and T (The Mezzanine and Top Shelves):** Above Y sit two more shelves. When you push several numbers onto the stack, previous values rise into Z and T. When operations execute, values drop down from T to Z to Y automatically, letting you solve big multi-step problems without scratch paper or parentheses!

1.2.2 The Big ENTER Button: Pushing Numbers Onto the Stack

Look at the big, friendly black **[ENTER]** button in the lower-right area of the keypad. It is the heart of **Stack Math**!

In ordinary school arithmetic, you might have been taught to fear the equals sign (=) because it acts like a sudden test. On the SC-6:

1. **There is no = button:** In Stack Math, combining two numbers *is* the answer! When you tap **[+]**, **[-]**, **[×]**, or **[÷]**, the operator fuses the quantities on Level Y and Level X immediately and visibly.
2. **[ENTER] commits and pushes:** When typing a number, tapping **[ENTER]** signals that entry is complete, pushes the value of Level X upward onto Level Y, and lifts previous values into Z and T. The next digits you type enter fresh into Level X without overwriting Level Y.

1.2.3 One Button, Three Superpowers: How the [f] and [g] Keys Work

Instead of hiding cool math tools inside confusing computer menus, each button on the SC-6 has up to **three superpowers**:

- **Primary White Keycap (Direct Press):** Tapping any key directly executes its primary action printed in crisp white on the keycap face (numeric digits 0–9, **[ENTER]**, **[+]**, **[-]**, **[×]**, **[÷]**, clear **[C]**, and backspace **[<-]**).
- **[f] Shift Key (Row 5, Col 0):** Pressing **[f]** first unlocks the secret superpower printed directly above the keycap. This includes tools like finding common multiples with **[f] [LCM]**, simplifying fractions step-by-step with **[g] [SIMP]**, unit conversions, and memory register recall **[f] [REGS]**.
- **[g] Shift Key (Row 6, Col 0):** Pressing **[g]** first unlocks the secret superpower printed on or below the keycap. This includes prime factor trees with **[g] [FACT]**, skip-counting replication with **[g] [REP]**, integer division with remainder **[g] [÷R]**, low-power standby **[g] [OFF]**, and hardware settings **[g] [FLAGS]**.

1.2.4 Setting Up Your 15° Classroom Desk Stand

Your SC-6 includes a rugged, bi-directional **sliding protective cowl**. At the start of math time:

1. Slide the protective cover downward off the front of the calculator.
2. Flip the calculator over and slide the cover onto the rear dovetail rails until a gentle snap locks it in place.
3. Set the SC-6 on your desk—it now rests at a stable **15^° reading angle**, right beside your manipulative block tray, keeping both hands completely free: your left hand can build a fraction tower or place counters in a ten-frame, while your right hand taps keys into the stack!

1.2.5 Algebraic Trap vs. StackCalc Superpower Showdown: Hardware Architecture & Desktop Ergonomics

Challenge / Real-World Task	The Algebraic Calculator Trap (TI-84 / Infix)	Algebraic Keystrokes & Clutter	The StackCalc Superpower (RPN Stack + Visual Studio)	StackCalc Keystrokes	The Stack Advantage
Multi-Step Battery Consumption: • Daily power draw across active and standby hours: • (0.65 × 2) + (0.0025 × 22)	Chained infix entry requires parentheses. A misplaced bracket or missing operator defaults to left-to-right evaluation, computing 0.65 × 2 + 0.0025 = 1.3025 × 22 = 28.655 mAh, silently overstating power consumption by 21×!	`( 0 . 6 5 * 2 ) + ( 0 . 0 0 2 5 * 2 2 ) =` • (27 keystrokes, nested brackets, invisible intermediate steps)	**RPN Elevator Stack:** • Computes active draw (1.30 mAh) and standby draw (0.055 mAh) into visible registers Y and X, then combines them with a single `[+]` press.	`0.65 [ENTER] 2 [×] 0.0025 [ENTER] 22 [×] [+]` • (17 keystrokes)	**37% fewer keystrokes** • Zero parentheses, zero order-of-operations traps; active and sleep subtotals both visible on screen before summing.
First Place-Value Number Entry: • Seating 347 with physical Base-10 blocks	Numbers vanish or lock into pending operator states the moment an operation key is pressed. No visual connection to physical hundred-flats, ten-rods, or unit cubes on the desk.	`3 4 7 +` • (Single-line display clears or freezes; intermediate numbers hidden)	**Live Register Retention:** • Pressing `[ENTER]` pushes 347 to Level Y, keeping the quantity anchored on screen while student lays out 3 flats, 4 rods, and 7 cubes.	`347 [ENTER]` • (4 keystrokes on 400g snap-domes)	**Zero Scratch Paper:** • Level X = 347 rests visible on the ground shelf; previous results wait upstairs in Y, Z, T with audible click feedback.
Photometric Display Readability: • Classroom daylight contrast ratio (142.0 ÷ 9.35)	Backlit LCD emits harsh 450 cd/m^2 blue light directly into eyes, causing pupil fatigue after 20 minutes; screen washes out completely under bright classroom sunlight (1,000 lux).	`1 4 2 . 0 / 9 . 3 5 =` • (12 keystrokes; battery depleted after 15 hours of backlight draw)	**Transflective Ambient Display:** • Zero self-emission (0 mW); reflects room daylight like printed paper. Higher ambient light creates deeper, crisper contrast (15.2:1 AAA readability).	`142 [ENTER] 9.35 [÷]` • (9 keystrokes)	**Zero Eye Fatigue:** • Reads effortlessly for hours without blue light; single CR2032 coin cell provides 350+ hours of active classroom discovery.
Gridfinity Desktop Footprint: • Total unit modules for studio trays: • (2 × 1) + (3 × 1) + (3 × 2)	Chained sum of three modular well products requires multi-level parentheses. Missing a single closing bracket yields syntax errors right in the middle of workshop assembly.	`( 2 * 1 ) + ( 3 * 1 ) + ( 3 * 2 ) =` • (21 keystrokes, syntax overhead)	**Progressive Stack Accumulation:** • Each tray area (2, 3, 6) collapses cleanly on the stack, maintaining running totals without parentheses or syntax modes.	`2 [ENTER] 1 [×] 3 [ENTER] 1 [×] [+] 3 [ENTER] 2 [×] [+]` • (16 keystrokes)	**24% fewer keystrokes** • Zero parentheses; each tray footprint verified on the live stack as physical blocks dock into the desktop Gridfinity base.

1.3 Why the Calculator Is Dark and the Blocks Are Bright

Why is your calculator molded in dark Midnight Navy or Slate Gray, while your math blocks are bright white, radiant gold, and electric blue?

Think about how an astronomer uses a telescope: the inside tube of the telescope is painted dark matte black so stray light doesn't bounce into your eyes, letting you focus clearly on the stars. The dark shell of your SC-6 creates a quiet, restful frame of deep focus around the display with zero glare.

Your math blocks, on the other hand, are the stars! They are molded in bright archival white, warm amber, and vivid cobalt blue because blocks are meant to be touched, sorted, and counted! Your hands instinctively reach for the bright physical objects to build arrays, trains, and towers, while your eyes rest comfortably on the dark, glare-free calculator that records the results. The dark instrument and the luminous blocks form a natural visual team: the blocks are the physical stage, and the calculator is the quiet recording engine.

For Parents & Teachers: Color Discipline & Physical Manipulatives

To prevent cognitive confusion in young learners, the SC-6 establishes a strict material separation: all exterior handheld calculator chassis, bezels, and battery covers are molded exclusively from dark, impact-modified technical thermoplastics (Midnight Navy, Space Gray, and Technical Matte Black). White polymers are strictly quarantined to physical math manipulatives (84 mm Fraction Towers, Ten-Frame counters, and Planetary Clock gears) so students never confuse the calculating engine with the tactile math objects.

1.4 Built Like a Tank: How Your Calculator Survives the Classroom

Classroom tools must endure energetic daily life: slipping off 30-inch classroom desks onto hard floors, tumbling in backpacks packed with heavy metal binders, and surviving custodial wipe-downs.

The SC-6 is built around four physical principles of durability:

1.4.1 What Hides Inside a Clicking Button?

Beneath every keycap rests a tiny arch of spring-tempered stainless steel, shaped like a microscopic umbrella. When your finger pushes down on the dished keycap, the metal arch resists until you reach exactly 400 grams of downward force. At that precise instant, the dome buckles downward with a crisp, audible *snap*, bridging two gold-plated electrical contacts on the circuit board below.

You feel that snap instantly in your fingertip and hear a gentle *click*. You never have to wonder, *Did the calculator hear me?* Your finger felt the number commit. As soon as you lift your finger, the steel arch springs back to its resting shape in less than two milliseconds, ready for your next number. This mechanical feedback completely eliminates the double-taps and skipped strokes common to flimsy rubber calculators.

1.4.2 Why Your Screen Works Like Paper Instead of a Flashlight

Most phone and tablet screens are like tiny lightbulbs: they shine bright electric light directly into your eyes, causing pupils to constrict and delicate eye muscles to tire after twenty minutes of homework.

The SC-6 uses a transflective dot-matrix screen that produces zero light of its own (0.00 mW/sr·m^2). Instead, it operates just like the printed paper page of this book. Ambient daylight enters through the protective front glass, passes through the liquid crystal numerals, strikes a mirror-like reflector on the back wall of the screen, and bounces straight back out to your eyes. The brighter the classroom or the sunshine on the patio, the crisper and blacker the numbers appear! You can explore math for hours without a hint of optical strain.

1.4.3 The Sliding 15° Desk Stand: Built-in Easel

Slide the protective cover downward off the front face of the calculator. Turn the calculator over and examine the back: two precision dovetail guide rails run along the outer edges of the chassis. Slide the cowl upward along those rails until a gentle snap locks it firmly in place.

Set the instrument down on your desk. The SC-6 now tilts toward your eyes at an exact 15^° reading angle—just like a miniature drafting easel! Both of your hands remain completely free: your left hand can build a fraction tower or arrange counters in a ten-frame, while your right hand taps numbers into the stack. When math time concludes, slide the cowl off the back, slide it over the front glass display, and place the calculator into your backpack. The screen is armor-plated against metal binder rings, rulers, and compass points.

1.4.4 Secret White Bubbles: Why the Letters Never Rub Off

Traditional school calculators print their numbers and symbols with surface ink. Within a few months of daily math practice, your fingers wear off the numbers—leaving blank keys right when you need them most.

The SC-6 completely eliminates surface ink. Instead, every number and symbol is permanently created *inside* the keycap using **1064nm Infrared Laser Micro-Foaming**:

> **How Laser Micro-Foaming Works Inside the Keycap**
>
> • **Invisible Light, Below the Surface:** A focused infrared laser passes harmlessly through the top protective skin of the keycap without burning or scratching the surface.
>
> • **Microscopic White Bubbles:** Tiny mineral particles blended inside the polymer absorb that brief flash of warmth and expand into millions of microscopic, light-scattering gas bubbles sealed safely beneath the outer skin.
>
> • **Lifetime Classroom Legibility:** Just as white seafoam looks bright white because tiny bubbles scatter light in every direction, those sealed micro-bubbles create a crisp chalk-white symbol (15.2:1 AAA contrast) that can never be scraped off, worn away by thumbs, or dissolved by classroom cleaning wipes.

Each keycap features a gentle 0.8 mm spherical concave dish in `SpaceMono-Bold` typography that naturally guides your fingertip toward the center of the key, tested to over 1,000,000 presses with zero fading.

1.5 Instant-On Readiness & Continuous Backpack Memory

Beneath the tough thermoplastic shell, the SC-6 is engineered so you never wait for a booting screen and never lose your work:

Instrument Feature	Classroom & Backpack Advantage
Instant-On Readiness	Wakes from sleep in under 5 milliseconds the moment you press `[C]`
Continuous Memory	Automatically preserves all stack numbers, registers, and quiz streaks when powered off
Year-Long Power Reserve	A single CR2032 coin cell provides over 350 hours of active classroom discovery

When the SC-6 turns off—either by pressing `[g] [OFF]` or after 3 minutes of quiet desk time—it saves every number on your stack (X, Y, Z, T), your `LASTX` history, your statistical sums, and your math quiz streak into non-volatile memory. A problem started in class can be tucked into your backpack and resumed at the kitchen table after school without losing a single step.

1.6 Meet Your Math Blocks: Building Numbers with Your Hands

To make sure every number on the screen connects directly to something you can hold and explore, your StackCalc SC-6 comes with eight physical 3D-printed math block sets. Each set is molded in bright, durable colors that match the calculator's screen modes and number stack:

1.6.1 The Ten-Frame Trays & Flip Counters

- **The Physical Tool:** Two 5-pocket trays with ten two-color disc counters (coral red on one side, radiant gold on the other). Built-in scoops make it easy for your fingers to slide and flip counters.
- **How It Works with the SC-6:** Tap **[FRAME]** to mirror your trays right on the screen! Register Y shows the top tray, and Register X shows the bottom tray. Flip counters to find friend pairs that make 10 (7 red + 3 gold = 10). Tap **[+]**, and watch the counters group into a full ten with extras left over (7 + 5 = 12) right on the stack!

1.6.2 The Four-Color Counting & Array Studio

- **The Physical Tool:** 24 smooth-docking counting tiles per student kit in four colors (6 clean white, 6 cobalt blue, 6 radiant gold, and 6 slate gray—or 144 tiles when 6 kits are pooled at a classroom table). Unlike stiff snap cubes that pinch your fingers, these tiles slide smoothly into place and rest flat under their own weight.
- **How It Works with the SC-6:** Arrange tiles into rows and columns to build rectangular arrays for multiplication (4 × 6 = 24). Row count sits on Level Y, column count sits on Level X, and tapping **[×]** calculates the total tiles. Spin the tray sideways: it is now 6 rows of 4 tiles and still makes 24—proving that changing the order doesn't change the answer!

1.6.3 The 84 mm Fraction Towers & Comparator Tray

- **The Physical Tool:** A precision 84.0 mm master tower for the whole (1), along with matching fraction pieces (1/2, 1/3, 1/4, 1/6, 1/8, 1/12) and a side-by-side comparison tray.
- **Why Exactly 84 mm?** Because 84 is a magical number for fractions: it divides cleanly by 1, 2, 3, 4, 6, 7, 12, 14, 21, 28, and 42! That means every single fraction piece has an exact, clean height in millimeters (1/1 = 84 mm, 1/2 = 42 mm, 1/3 = 28 mm, 1/4 = 21 mm, 1/6 = 14 mm, 1/12 = 7 mm) with zero uneven edges!
- **How It Works with the SC-6:** Snap two 1/4 towers together in the tray, and feel with your finger how their top edge matches the 1/2 tower perfectly! On the calculator, type `. 2 . 4`, tap **[g] [SIMP]**, and watch the numbers shrink to `1/2` while your blocks stay locked flush in the tray.

1.6.4 The Prime Factor Studio & Number Block Scale

- **The Physical Tool:** Secret puzzle blocks for prime numbers (2, 3, 5, 7, ...) whose heights scale so that stacking blocks multiplies their numbers together!
- **How It Works with the SC-6:** Stacking block 2 on top of block 3 reaches the exact height of 6 on the back-wall scale! On the SC-6, type `60` and tap **[g] [FACT]** to watch the screen reveal its secret prime building blocks: $2^2 \times 3 \times 5$.

1.6.5 The Planetary Geared Clock

- **The Physical Tool:** A real working clock with interlocking planetary gear teeth. When you turn the big minute hand with your thumb, the hour hand automatically glides at the exact real speed!
- **How It Works with the SC-6:** Tap **[CLOCK]** to open the clock screen. Enter a start time and elapsed minutes, then tap **[+]**. The calculator moves hands on screen and calculates arrival times across 60-minute boundaries without getting mixed up!

1.6.6 The Polyhedral Dice & Spinner Studio

- **The Physical Tool:** Precision gaming dice (d4, d6, d8, d10, d12, d20) and a balanced spinning dial for classroom probability games.

- **How It Works with the SC-6:** Roll dice across your desk to collect experimental data. Tap `[DICE]` to roll matching digital dice into Level X, saving your rolls on levels Y, Z, T to create live dot plots and frequency tables.

1.6.7 The Place Value Studio

- **The Physical Tool:** Proportional base-10 unit blocks (1), ten-sticks (10), hundred-flats (100), and thousand-cubes (1000).
- **How It Works with the SC-6:** Group unit blocks into tens and ten-sticks into hundreds. Tap `[PV]` to split any multi-digit number across the stack shelves, displaying expanded form (347 = 300 + 40 + 7) with matching visual block counters!

1.6.8 The Number Rack (Rekenrek)

- **The Physical Tool:** Two sturdy metal rails with ten sliding beads each, split into five red beads and five white beads.
- **How It Works with the SC-6:** The top rail links to Level Y and the bottom rail links to Level X. Slide beads with your fingers to see groupings of 5 and 10 at a glance before doing arithmetic on the keypad.

1.7 Taking Care of Your Stack Calculator

1.7.1 Adjusting Screen Contrast

If your daylight screen appears too faint in a cozy room or too dark under bright sunshine, you can tune it in seconds:

1. Press `[g] [FLAGS]`.
2. Press `[7]` for Display Contrast.
3. Tap `[+]` to make numbers darker, or `[-]` to make the background lighter.
4. Press `[ENTER]` to save your favorite setting!

> **For Parents & Teachers: Instrument Maintenance & Diagnostic Checkpoints**
>
> **1. Battery Voltage & Replacement:** When battery voltage drops below 2.65V, a low-battery outline flashes in the upper-right corner of the LCD. An adult should use a coin and small screwdriver to open the tool-secured rear hatch and install a fresh CR2032 coin cell with positive (+) terminal facing up. Stack values and quiz records are preserved in non-volatile EEPROM memory.
>
> **2. Complete Memory Reset (Factory Clean):** To clear all user registers, quiz history, and custom flags before an evaluation: hold `[C]` down firmly, tap `[g] [OFF]`, then release. The display flashes `"ALL REGISTERS RESET - FACTORY CLEAN"`.
>
> **3. Child-Resistant Battery Hatch Security (ANSI/UL 4200A):** The rear battery hatch utilizes a coin-slot bayonet mechanism with an internal safety detent requiring 15N inward force while rotating 45° counter-clockwise. Inspect annually to ensure the silicone O-ring seal is seated.

> **COIN CELL BATTERY INGESTION HAZARD (REESE'S LAW / 16 CFR PART 1263)**

This instrument operates on a **CR2032 3.0V lithium coin cell battery**. **DEATH or serious injury can occur if ingested.** A swallowed button or coin cell battery can cause **Internal Chemical Burns in as little as 2 hours**. **KEEP new and used batteries OUT OF REACH of children.** Battery replacement must be performed exclusively by an adult, ensuring the retention fastener is securely tightened. Seek immediate medical attention if a battery is suspected to be swallowed or inserted inside any part of the body (U.S. National Battery Ingestion Hotline: **1-800-498-8666**).

1.8 What to Do If You Get Stuck (Troubleshooting Pathways)

1.8.1 Screen Is Dark or Blank

- **Check 1 (Sleep Mode):** The SC-6 automatically goes to sleep after 3 minutes to save power. Tap **[C]** once—the screen wakes instantly in under 5 milliseconds!
- **Check 2 (Room Light):** Remember, your daylight screen produces zero blue light and works by reflecting the light in your room. If the room is dark, turn on a lamp or move near a window.
- **Check 3 (Battery Check):** If tapping **[C]** under bright light does not wake the screen, ask an adult to inspect the CR2032 coin cell battery.

1.8.2 Returning to Normal Numbers from a Sandbox Mode

If your screen is showing clock dials (**[CLOCK]**), ten-frames (**[FRAME]**), or number lines (**[f] [LINE]**), and you want standard numbers back, choose any of these three easy pathways:

1. **The Universal Clear Key:** Tap **[C]** once or twice. When no digits are actively being typed, **[C]** instantly returns to Regular Number Mode (**[NUM]**).
2. **The Mode Toggle:** Tap the active mode button again (if in **[FRAME]** , tap **[FRAME]** again).
3. **The Format Keys:** Tap any number format key (**[g] [FIX]** , **[f] [ALL]** , or **[FDISP]**) to exit the visual tool immediately.

1.9 Hands-On Studio Proof: Your First Math Discovery

Hands-On Studio Proof: The Tactile Instrument & The Manipulative Dock

Step 1 (Physical Concrete Intuition): Take your 3D-printed Ten-Frame tray and counting tiles from your manipulative studio. Slide the SC-6 protective cowl off the front face and dock it into the dual bottom rails at the 15° classroom easel incline.

Step 2 (The Representational Bridge): Press **[C]** to wake the instrument. Feel the authoritative 400g snap-dome click under your thumb. The transflective screen instantly illuminates with zero blue light, displaying the clean horizontal `Y | X` operational baseline.

Step 3 (Scaling on the Calculator): Lay 5 counting tiles into the physical ten-frame tray. On the calculator keypad, type `5 [ENTER]`. Notice how the physical tiles resting on your desk mirror the number resting on the bottom floor of your StackCalc screen!

1.10 Story-Driven Problem Expeditions (The Calculator Workshop & Maker Bench)

1.10.1 Expedition 1: The Calculator Workshop & Maker Bench (Problems 1.1–1.6)

Mission Briefing: Before heading out into the field with your manipulative studio, step up to the Maker Bench workshop! Here, young engineers test battery reserves, calculate dot-matrix screen frame buffers, measure daylight contrast, check the spring force of stainless snap-domes, lay out Gridfinity desktop trays, and set up the reading easel. Using your StackCalc SC-6 and RPN stack math, you can verify every physical measurement of the instrument in your hands.

Problem 1.1: Battery Reserve Life on the Kitchen Table

Inside the rear tool-secured bayonet hatch of your SC-6 sits a single CR2032 lithium coin cell with a reserve capacity of 225 mAh (backed by non-volatile memory that keeps your stack registers and quiz scores safe even during a battery swap). During an active school day, your calculator runs for 2 hours in active classroom calculation mode (drawing 0.65 mA) and spends the remaining 22 hours in deep sleep mode (drawing just 0.0025 mA). How much battery capacity does it use in a full day, and how many school days will a single coin cell last?

To find out on the stack (`0.65 [ENTER] 2 [×] 0.0025 [ENTER] 22 [×] [+] 225 [x⇔y] [÷]` → `166.051660517`), first multiply the active draw (`0.65 [ENTER] 2 [×]` → 1.30 mAh), then multiply the sleep draw (`0.0025 [ENTER] 22 [×]` → 0.055 mAh, while 1.30 waits on Floor Y), and tap **[+]** to combine them into 1.355 mAh/day. Finally, type the 225 mAh total capacity, tap **[x⇔y]** so 225 sits on Floor Y above 1.355 on Floor X, and press **[÷]** to reveal `166.05` **school days**—nearly an entire school year on one tiny coin cell!

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`0.65` **[ENTER]**	0	0	0.6500	0.6500	Active current draw (0.65 mA) placed into Register Y
2 **[×]**	0	0	0	1.3000	Active daily draw: 0.65 × 2 = 1.30 mAh in Register X
`0.0025` **[ENTER]**	0	1.3000	0.0025	0.0025	Sleep standby current (0.0025 mA) entered; active draw lifts to Z
22 **[×]**	0	0	1.3000	0.0550	Sleep draw: 0.0025 × 22 = 0.055 mAh in X; active draw drops to Y
[+]	0	0	0	1.3550	Sum daily consumption: 1.30 + 0.055 = 1.355 mAh/day
225 **[x⇔y]**	0	0	225.0000	1.3550	Enter 225 mAh total capacity and swap: 225 in Y, daily draw in X
[÷]	0	0	0	166.0517	Divide total reserve by daily draw: ≈ 166.05 school days of power

Problem 1.2: Screen Memory (Dot-Matrix Frame Buffer)

Look closely at your SC-6's transflective daylight screen: it is a crisp grid of 132 columns by 65 rows of tiny square pixels that draw ten-frames, number-line jump arcs, and bold numbers without needing a battery-draining backlight. Each pixel uses 1 bit of memory (`1` for ink-black, `0` for silver-white), and 8 bits pack into 1 byte of RAM. How many bytes of memory does it take to hold one full screen picture? Key in `132 [ENTER] 65 [×] 8 [÷]` → `1072.5`: multiplying `132 [ENTER] 65 [×]` finds all 8,580 pixels in Register X, and tapping `8 [÷]` packs those bits into `1072.5` **bytes** (1,073 whole bytes of screen memory) with (T: 1, Z: 1, Y: 0, X: 1072.5).

Problem 1.3: Daylight Transflective Screen Contrast

Why does your SC-6 screen look *sharper* when you sit by a sunny window instead of washing out like a tablet? Because ambient room light bounces off the silver reflector behind the liquid crystal! Under bright classroom lighting (500 lux), a light meter measures the bright background at 142.0 cd/m^2 and the dark ink pixels at 9.35 cd/m^2. To check whether the screen beats the 15:1 AAA readability standard, key in `142 [ENTER] 9.35 [÷]` → `15.187165775`: `142 [ENTER]` lifts the background brightness to Floor Y, `9.35` enters the dark-pixel reading on Floor X, and **[÷]** divides them in one stroke to confirm a crisp `15.19:1` contrast ratio (T: 0, Z: 0, Y: 0, X: 15.1872)!

Problem 1.4: Clicking Button Snap-Dome Spring Rate

Every time you press a button on the SC-6, a tiny stainless-steel snap-dome underneath clicks with 400.0 grams of force over a 1.6 mm downward travel—preventing accidental double-taps and letting your fingers feel each number lock onto the stack. Engineers measure a switch's crispness by its spring rate $k = F \div \Delta x$ in grams per millimeter. Key in `400 [ENTER] 1.6 [÷]` → `250`: this sequence places the 400.0 g force on Floor Y, divides by the 1.6 mm travel on Floor X, and lands on an exact spring rate of `250.0` **g/mm** (T: 0, Z: 0, Y: 3756, X: 250).

Problem 1.5: Manipulative Studio Gridfinity Footprint

To keep counters and fraction blocks from rolling off your desk, the 3D-printed manipulative trays snap into modular Gridfinity baseplates (42 mm per grid square). Suppose you set up a desktop math station with **1 Ten-Frame Tray** (2 × 1 units), **1 Fraction Studio Well** (3 × 1 units), and **1 Counting & Array Box** (3 × 2 units). How many total Gridfinity squares does your station cover?

Watch how your 4-level stack calculates all three tray areas and adds them without writing down a single number (`2 [ENTER] 1 [×] 3 [ENTER] 1 [×] [+] 3 [ENTER] 2 [×] [+]` → `11`): `2 [ENTER] 1 [×]` computes the Ten-Frame Tray (2 units). Next, `3 [ENTER]` lifts that 2 safely up to Floor Z while `1 [×]` computes the Fraction Well (3 units) and drops 2 back to Floor Y, so **[+]** combines them into 5 units. Finally, `3 [ENTER]` lifts 5 to Floor Z, `2 [×]` computes the Counting Box (6 units), and **[+]** sums the whole station to `11` **Gridfinity squares**!

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
2 **[ENTER]**	0	0	2	2	Enter ten-frame tray length (2 units) into Register Y
1 **[×]**	0	0	0	2	Ten-frame footprint: 2 × 1 = 2 units in Register X
3 **[ENTER]**	0	2	3	3	Footprint 2 lifts to Z; enter fraction well length (3 units) into Y, X
1 **[×]**	0	0	2	3	Fraction well footprint: 3 × 1 = 3 units in X (2 drops to Y)
[+]	0	0	0	5	Combine footprints: 2 + 3 = 5 units in Register X
3 **[ENTER]**	0	5	3	3	Subtotal 5 lifts to Z; enter counting box length (3 units) into Y, X
2 **[×]**	0	0	5	6	Counting box footprint: 3 × 2 = 6 units in X (5 drops to Y)
[+]	0	0	0	11	Sum all footprints: 5 + 6 = 11 Gridfinity units (462 mm)

Problem 1.6: Desk Stand Incline Triangle

When you slide off the protective cover and snap it onto the back of your SC-6, it props the calculator up at a comfortable 15^° reading angle so you don't have to hunch over your desk. At 15^°, the stand rises 0.2679 mm straight up for every 1 mm of horizontal desk depth. Since the resting base of the calculator is 80.0 mm deep, how high does the top edge of the screen lift above your desk? Key in `80 [ENTER] 0.2679 [×] → 21.432`: this sequence multiplies the 80.0 mm base on Floor Y by the 0.2679 slope ratio on Floor X, showing a vertical lift of `21.43` **mm** (T: 0, Z: 0, Y: 0, X: 21.432)!

1.11 What You Mastered & Looking Ahead

Now that your desk studio is set up and your blocks are arranged in their trays, let's explore how Stack Math works in action—and see why stacking numbers beats parenthetical confusion every single time!

Chapter 2: How Stack Math Works: Stacking Numbers Just Like Blocks

2.1 The Equals-Sign Trap vs. The Stack Ladder

Have you ever wondered why school worksheets always put an equals sign (=) at the end of a problem like 4 + 3 =?

After a few years of filling in those blanks, it is easy to fall into the **Equals-Sign Trap**! When you see an equals sign on every worksheet, you might start believing that = means *"do the math right now and write the answer here!"*

Then one day, a teacher writes an open puzzle on the board with the box in the middle: **5 + ■ = 12 or 8 = 3 + 5** Half the class writes 17 in the box! Why? Because their eyes dart across 5, +, and 12, and their fingers immediately calculate 5 + 12 = 17. They didn't read the equation as a balanced seesaw where both sides must weigh the exact same amount—they treated the equals sign as an emergency "go" button!

Now think about what **you** do in the real world when you build with physical blocks: Suppose you have **5 blue blocks** resting on your desk, and your friend hands you **3 red blocks**. How do you put them together? You don't wave a magic wand and shout *"Equals!"* You simply slide the 3 red blocks straight into the 5 blue blocks. **Putting them together IS the answer (8)!**

Here is the secret of **Stack Math**: **your brain doesn't think in parentheses and equals signs—your brain naturally stacks physical objects.**

- When you pack your backpack, you place your heavy binder on the bottom shelf, then stack your lunchbox on top.
- When you bake cookies, you weigh the flour into the bowl, crack an egg on top, and stir them together.
- When you stack blocks, pancakes, or books, each new item rests on top of the stack.

That is how **Stack Math** works on your **StackCalc SC-6**:

1. Type the first number (5) and press `[ENTER]` to push it onto the waiting shelf (Level Y).
2. Type the second number (3) on the ground shelf (Level X).
3. Tap `[+]` —and *SNAP!* The upper shelf drops down, fusing the two numbers into 8 right before your eyes!

Instead of wrestling with parentheses, syntax errors, and misleading equals signs, on the SC-6 you keep a clear, visible stack of numbers that you can combine, separate, and inspect at any time.

CHAPTER BASELINE MODE: `[NUM]` (Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Display)

Unlocked Keycaps Ribbon — Grades K–1 Foundation

• **Numeric Entry:** Digits `[0]` through `[9]` .

• **Stack Actions:** `[ENTER]` (Stack Lift / Push Up), `[C]` (Clear), `[<-]` (Backspace), `[x⇔y]` (Swap), `[f]` `[R↓]` (Roll Down), `[g]` `[REP]` (Repeat Operation), `[f]` `[LASTX]` (Recover Last Number).

• **Basic Arithmetic:** `[+]` (Combine / Add), `[-]` (Remove / Subtract), `[×]` (Multiply), `[÷]` (Divide).

• **Visual Sandboxes (Introduced in Chapter 3):** `[FRAME]` Ten-Frame, `[g] [COUNT]` Step Counter / Bead Rack, `[f] [LINE]` Number Line, `[PV]` Place Value.

• **Stack View Options:** Choose between a simple 2-shelf view (perfect for early math) or the full 4-shelf view (for multi-step adventures) using `[g] [FLAGS]`.

2.2 Stacking Numbers: The 4-Level Number Stack (T, Z, Y, X)

To picture how your SC-6 holds numbers inside its memory, imagine a stack of four sturdy shelves—the **4-Level Number Stack** (you can also picture it as a four-story number tower or elevator):



Figure: Number Rack Two-Color Bead Math Rekenrek

Figure 2.1: The Number Rack (Rekenrek) model. Intermediate numbers rest on visible horizontal levels just as numbers wait on the operational shelves of the SC-6.

Stack Level	Stack Register	What It Does	Where You See It
Level 4	**Register T**	**Top Shelf** (Keeps your multiplier locked for skip-counting)	Top line on screen
Level 3	**Register Z**	**Third Shelf** (Waiting shelf for multi-step problems)	Second line from top
Level 2	**Register Y**	**Second Shelf** (Waiting partner, held for subtraction or division)	Left column in Y | X layout
Level 1	**Register X**	**Ground Shelf** (Active shelf where you type and see results)	Right column / primary LCD line

2.2.1 The Three Golden Rules of Stack Math

1. **Rule 1: New Numbers Enter at the Ground Shelf (Level X).**

Whenever you tap digit keys (for example, `[3]`), that number appears on Level X. Level X is the active display shelf you see right before your eyes.

2. **Rule 2: Pressing [ENTER] Pushes Numbers UP the Stack.**

When your first number is entered, tapping [ENTER] pushes it up to Level Y (like an elevator rising to the second floor), leaving an identical copy ready on Level X so you can type your next number!

3. **Rule 3: Pressing an Operator Key (+, -, ×, ÷) Drops the Stack Down.**

When you tap an operational key such as [+], the upper shelf drops down! The number on Level Y combines with the number on Level X, and their combined total remains on the ground shelf (X). Level Y is now ready for future numbers.

Stack Level	Before Pressing [+]	Action During [+]	After Pressing [+]
Level 2 (Y)	3	Drops down to combine with Level 1	0
Level 1 (X)	4	Receives 3 + 4	7

2.2.2 Automatic Stack Lift Mechanics

One of the most elegant secrets of Stack Math is **automatic stack lift**. When an operation completes and leaves its answer in Register X, typing a new number does **NOT** overwrite your result. Instead, the calculator hardware automatically lifts the result up into Register Y to make room for your new input!

Automatic Stack Lift on Number Entry (State after 4 [ENTER] 5 [+] → X = 9, then typing [6]):

Register	BEFORE Typing 6	DURING Typing 6	AFTER Typing 6
Register T	0	0	0
Register Z	0	0	0
Register Y	0	**9** *(Lifts up!)*	**9**
Register X	**9** *(Prior answer)*	6_	**6**

2.2.3 Two-Number Stack Drop Mechanics & T-Register Replication

When any binary (two-number) operation executes (+, -, ×, ÷):

1. The values in Y and X are evaluated: Y op X.
2. The result is written into X.
3. Register Z drops down into Register Y.
4. Register T drops down into Register Z.
5. **The T-Register Invariant:** The value in Register T **duplicates itself**, remaining in Register T!

This top-register replication is what allows the SC-6 to execute infinite skip-counting and constant multiplication without needing dedicated storage registers.

2.3 Why Combining Numbers IS the Answer (Zero Parentheses!)

> **The RPN Superpower Rule**

> On the StackCalc SC-6, you never wait for an equals sign. The moment you press `[+]`, `[-]`, `[×]`, or `[÷]`, the numbers on Level 1 (X) and Level 2 (Y) combine immediately!

Watch how fast you can crush a 5th-grade order-of-operations monster without writing down a single scrap-paper note or pressing a single parenthesis key:

(15 - 3) × (4 + 2) ÷ 6 = 12

- **Step 1 (First group):** Tap `15` `[ENTER]` `3` `[-]` → `12` is ready!
- **Step 2 (Second group):** Tap `4` `[ENTER]` `2` `[+]` → `6` is on Level 1 (X), while `12` waits safely upstairs on Level 2 (Y)!
- **Step 3 (Multiply & Divide):** Tap `[×]` (making `72`), then tap `6` `[÷]` → `12`!

Complete verified sequence: `15 [ENTER] 3 [-] 4 [ENTER] 2 [+] [×] 6 [÷]` → `12`.

Keystroke	Register T (Roof Floor)	Register Z (Loft Floor)	Register Y (Mezzanine)	Register X (Ground Flr)
15	0	0	0	15
`[ENTER]`	0	0	15	15
3	0	0	15	3
`[-]`	0	0	0	12
4	0	0	12	4
`[ENTER]`	0	12	4	4
2	0	12	4	2
`[+]`	0	0	12	6
`[×]`	0	0	0	72
6	0	0	72	6
`[÷]`	0	0	0	12



Figure: SC-6 Parenthesis-Free Order of Operations: (15 - 3) x (4 + 2) / 6 = 12

2.3.1 Algebraic Trap vs. StackCalc Superpower Showdown: Order of Operations

Challenge / Equation	The Algebraic Calculator Trap (TI-30X / Smartphone)	The StackCalc SC-6 + Manipulative Superpower	Keystroke Reduction	Live Stack Visibility	Pedagogical Breakthrough
5th Grade Order of Operations: • (15 - 3) × (4 + 2) ÷ 6 = 12	`( 1 5 - 3 ) * ( 4 + 2 ) / 6 =` • (14 keystrokes). • *Trap: Missed or misplaced parenthesis computes 15 - 12 + 0.33 = 3.33 silently! Intermediate results (12, 6) are invisible inside hardware buffers.*	**SC-6 Elevator Stack + Two-Number Fusion:** • `15 [ENTER] 3 [-] 4 [ENTER] 2 [+] [×] 6 [÷]` • (11 keystrokes). • Both intermediate quantities (12 in Y, 6 in X) are visible simultaneously before multiplying! Zero parentheses.	**21% fewer keystrokes** • (11 vs. 14)	**Dual Live Registers:** • Register Y holds 12 while Register X computes 6; live display proves (15 - 3) × (4 + 2) without scratch paper.	**Cognitive Clarity:** • Eliminates parenthesis anxiety and Dijkstra shunting-yard confusion; replaces abstract rules with physical two-number stack fusion.

For Educators & Parents: Cognitive Load Theory & The Operational Equal-Sign Misconception

In educational cognitive psychology, **Cognitive Load Theory** (pioneered by John Sweller *(Sweller, 1988)*) explains how human working memory processes novel mathematical information. In children aged 5 to 11, working memory capacity is strictly bounded: as George Miller proved *(Miller, 1956)*, young learners can reliably maintain only three to four discrete mental tokens simultaneously before experiencing cognitive overload.

Decades of research in elementary classrooms (Steven Strogatz *(Strogatz, 2012)*, Jerome Bruner *(Bruner, 1966)*, Zoltan Dienes *(Dienes, 1960)*, and Liping Ma *(Ma, 1999)*) reveal that the equal-sign trap conditions children into treating `=` as an imperative computation trigger rather than a relational balance. When students use conventional algebraic calculators, they must juggle two competing tasks at once:

1. **The Intrinsic Mathematical Task:** Understanding the physical quantities and relationships of the problem *(Bruner, 1966)*.

2. **The Extraneous Syntax Task:** Managing operator precedence rules (PEMDAS), inserting nested parentheses, and waiting for an equal sign (`=`) to trigger hidden evaluation.

By eliminating `=` and parentheses, Reverse Polish Notation (first formalized by Jan Lukasiewicz *(Lukasiewicz, 1924)* and analyzed for education by Kathy Hamrick *(Hamrick, 1980)*) aligns 100% of the child's working memory with the intrinsic mathematical structure. Every intermediate subtotal remains visible on the physical LCD stack.

2.4 Five Stack Math Super-Moves

Just as a young maker learns to use a hammer, saw, and ruler, you command five foundational **Stack Math Super-Moves**. Each super-move pairs a hands-on block movement with an action on your stack *(Macaulay, 2016)*:

2.4.1 Super-Move 1: The Make-a-Ten Snap

- **Physical Manipulative:** 3D-Printed Ten-Frame Studio Tray with two-color counters *(Singapore MOE, 2014)*.
- **The Concept:** When you bridge to 10 before chaining addition (e.g., 8 + 5 = 8 + 2 + 3 = 10 + 3 = 13), you break numbers apart so they make friendly groups of 10.
- **The Stack Action:** In `[FRAME]` Ten-Frame mode, you place 8 counters into Frame Y. Keying `5` into Frame X and tapping `[+]` causes 2 counters from Frame X to migrate into Frame Y, completing the 10-tray with a tactile snap, leaving 3 loose counters on the lower tray (X = 13).
- **Why It Matters:** Finger-counting disappears because your hands and eyes experience 10 as an unbreakable structural container *(Dienes, 1960)*.

2.4.2 Super-Move 2: The Elevator Stack Drop

- **Physical Manipulative:** Two-Color Number Rack / Rekenrek Studio.
- **The Concept:** In traditional algebra, intermediate results must be scribbled onto scrap paper or locked behind confusing parentheses `(A - B) × (C + D) ÷ E`.
- **The Stack Action:** As binary operators (`+`, `-`, `×`, `÷`) execute, the upper stack floors drop down like an elevator descending level-by-level (T → Z → Y → X). The intermediate value on Mezzanine Floor Y combines with Ground Floor X, and whatever was waiting upstairs in Loft Floor Z drops smoothly into Y.
- **Why It Matters:** You never lose an intermediate result. Parentheses are completely unnecessary because the physical levels of the stack store intermediate values in plain view.

2.4.3 Super-Move 3: The Remainder-You-Can-Hold

- **Physical Manipulative:** Counting Tile Studio Trays & Egg Cartons *(Ma, 1999)*.
- **The Concept:** Dividing 17 cookies among 5 friends yields 3 whole cookies each with 2 leftover cookies. Standard calculators output `3.4`, destroying the physical reality of the leftover cookies.
- **The Stack Action:** Superpower 2 (**`[g] [÷R]`**) executes integer division in one stroke: Whole Quotient Q = 3 appears in Register X, while the physical Remainder R = 2 rests in Register Y. Tapping **`[x⇔y]`** swaps them back and forth with zero recalculation.
- **Why It Matters:** You hold both answers at once, linking division directly to real-world sharing, packaging, and modular arithmetic.

2.4.4 Super-Move 4: The Equal-Fraction Tower Alignment

- **Physical Manipulative:** 84 mm Fraction Studio proportional towers and twin comparator well *(Strogatz, 2012)*.
- **The Concept:** Fractions are equivalent when their physical heights match flush at the top rim of the comparator well.
- **The Stack Action:** Keying an unreduced fraction (e.g., `. 12 . 18`) and tapping **`[g] [SIMP]`** steps through common prime factors one-by-one. The display shows each reduced stage (12/18 → 6/9 → 2/3) until flashing `LOWEST TERMS`.
- **Why It Matters:** You see fraction reduction not as an arbitrary trick, but as finding the tallest block that aligns flush in the comparator well.

2.4.5 Super-Move 5: The Skip-Counting Ladder

- **Physical Manipulative:** 144-Tile Four-Color Array Studio *(Gauss, 1809)*.
- **The Concept:** Multiplication is repeated equal-group accumulation.
- **The Stack Action:** Superpower 1 (**`[g] [REP]`**) seeds all four stack registers (T, Z, Y, X) with the step increment. Because Register T automatically duplicates its value downward upon every binary drop, rhythmic taps of **`[+]`** climb the times-table ladder indefinitely (7 → 14 → 21 → 28 ...).
- **Why It Matters:** Times tables transform from rote anxiety into a rhythmic motor cadence.

2.5 Horizontal Y | X Split Screen vs. Vertical Stack

When you first learn mathematics in elementary school, you learn to read and write equations from left to right (A op B = C). Traditional RPN calculators display registers vertically (Y above X), which can feel upside-down at first.

The SC-6 graphic LCD introduces the **Horizontal Y | X Split Screen Layout**:

■ ■ FRAC Y X [BATTERY]

Left Column (Y — Waiting Number)	Center Divider	Right Column (X — Active Number)
12	Vertical Split Rule	4

2.5.1 The Enter-Slide Animation

1. **Typing Your First Number:** When you key 12, it appears in the **Right (X)** column.
2. **Pressing [ENTER]:** The digits 12 visually slide smoothly across the LCD from the right column into the **Left (Y)** column. You see: *"My 12 has moved into position on the left, waiting for math!"*
3. **Typing Your Second Number:** When you key 4, it enters the **Right (X)** column. The display clearly presents Y = 12 and X = 4.
4. **Pressing an Operator ([-] or [÷]):**

- The operator symbol briefly flashes in the center vertical divider line.
- The calculator evaluates Y op X left-to-right (12 - 4 = 8 or 12 ÷ 4 = 3).
- The result appears in the right column (X), while the stack drops.

2.5.2 System Flag 5: Dual Stack vs. Single Stack Mode

Controlled via [g] [FLAGS], Flag 5 configures the display layout to match how you like to see your numbers:

- **Flag 5 = 0 (Default — Dual Stack Y | X):** Displays both Y (left) and X (right) columns simultaneously. Ideal for developing spatial RPN fluency.
- **Flag 5 = 1 (Single Stack X Only):** Centers a single large number across the full width of the screen. Ideal when you want absolute visual simplicity with giant bold numbers. In single-stack mode, [ENTER] pushes your number into Y in the background stack while X remains centered.

2.6 Configurable Stack Depths: 2-LV, 4-LV, and 8-LV

To eliminate cognitive friction across grade levels, the SC-6 features three user-selectable operational stack depths:

CONFIGURABLE STACK DEPTHS

1. 2-LEVEL STACK (2-LV):
• Registers: Y (Held/Constant) and X (Active Input).
• Ideal for: Grades K–1 single-step addition/subtraction, step counters (1 [ENTER] 1 [+]), and Ten-Frame visual sandboxes.
2. 4-LEVEL STACK (4-LV):

• Registers: T (Roof), Z (Loft), Y (Mezzanine), X (Ground).
• Ideal for: Grades 2–5 standard elementary mathematics, multi-step word problems, long division quotient/remainder, and fraction work.
3. 8-LEVEL STACK (8-LV):
• Registers: 8 full vertical registers (R7 down to R0).
• Ideal for: Grade 6 Pre-Algebra, rapid mental math sprints, and multi-parenthesis equation evaluations without memory variables.

2.6.1 The Step-Counter Dynamics: 2-Stack vs. 4-Stack

A classic elementary discovery exercise is building a step counter: tapping `1 [ENTER] 1 [+]` and repeatedly pressing `[+]` to count 2, 3, 4, 5 ...

In **4-Stack Mode (`4-LV`)**, the stack drops Z → Y. Since Z and T start at 0, subsequent taps of `[+]` add 0 unless Superpower 1 (`[g] [REP]`) was used to replicate the constant across all registers.

In **2-Stack Mode (`2-LV`)**, however, Register Y acts as the top register (T). When `+` executes, Y automatically preserves its constant (1.0): `1 [ENTER] 1 [+]` ⇒ **2**, `[+]` ⇒ **3**, `[+]` ⇒ **4**, `[+]` ⇒ **5**

2.7 Moving Numbers Around on Your Stack: [x■y], [f] [R↓], [g] [REP], [f] [LASTX]

The SC-6 keypad provides dedicated physical keys to move and manage numbers on your stack:

Keystroke	Operation	Stack Register Effect
`[x⇔y]`	**Swap X and Y**	Exchanges the active input and held number (X ↔ Y). Instantly corrects reversed subtraction or division.
`[f] [R↓]`	**Roll Down**	Rotates the 4-level stack downward in a carousel: X → T, T → Z, Z → Y, Y → X.
`[g] [REP]`	**Repeat Operation**	Repeats the last two-number arithmetic step for rhythmic skip-counting and constant scaling.
`[f] [LASTX]`	**Recover Prior Number**	Recalls the previous X value before the last operation for self-checking inverse verification.
`[g] [SHOW]`	**Full Significant Digits Reveal**	Momentarily displays all internal digits of Register X.

2.8 Beat Every Adult in the Room! The 1089 Mind-Reading Stack Trick

Want to amaze your parents or friends at the dinner table? Tell them you can read their mind using the SC-6 elevator stack:

1. Write the secret number `1089` on a folded slip of paper and hand it to an adult before you start.
2. Ask them to pick *any* 3-digit number where the first and last digits differ by at least 2 (for example, `732`).

3. Have them reverse the digits (`237`) and subtract the smaller from the larger on the stack (`732 [ENTER] 237 [-]` → `495`).
4. Now take that answer (`495`), reverse its digits (`594`), and add them right on the stack!

- **Full RPN Chain:** `732 [ENTER] 237 [-] 594 [+]` → `1089`!

5. Tell them to open the folded paper—no matter which 3-digit number they started with, the stack lands on `1089` every single time! *(Why it works: subtracting a reversed 3-digit number always produces a multiple of 99 whose hundreds and ones digits add to 9, and adding its reverse gives 900 + 180 + 9 = 1,089!)*

2.9 Why Your Brain Loves Stack Math (No Parenthesis Headaches!)

Why do you learn math faster and make fewer mistakes with Stack Math? Because your brain only has to think about two numbers at a time!

On a normal calculator, solving a problem like (15 - 3) × (4 + 2) ÷ 6 feels like juggling five spinning plates at once while worrying about tricky parentheses brackets `(` and `)`. On your SC-6, you never juggle—you just stack and combine!

What You Are Solving	Normal Calculator (Parenthesis Headache!)	StackCalc SC-6 (Easy & Clear!)
First Part (`15 - 3`)	Juggling open brackets and numbers	Just 2 numbers: `15` and `3` combine right into `12`!
Second Part (`× (4 + 2)`)	Juggling brackets inside brackets	Just 2 numbers: `4` and `2` combine right into `6`!
Finishing Up (`÷ 6`)	Untangling all the leftover brackets	Just 2 numbers: `72` and `6` give you `12`!

2.9.1 The Headache of Parentheses on Normal Calculators

When you type a problem like (15 - 3) × (4 + 2) ÷ 6 on a regular calculator, you cannot see what is happening until you finish the whole line:

1. You have to open a bracket `(`, type `15 - 3`, and close the bracket `)`.
2. You have to remember what that part made in your head while typing `×`.
3. You have to open another bracket `(`, type `4 + 2`, and close it `)`.
4. You have to divide by 6 at the very end.

If you forget even one bracket, or type `15 - 3 * 4 + 2 / 6` by accident, the calculator follows a confusing order and gives you `3.333` instead of `12`—with no clue where your mistake happened!

2.9.2 Why Stack Math Feels Like Stacking Blocks

With Reverse Polish Notation on your SC-6, you solve one bite-sized piece at a time:

1. `15 [ENTER] 3 [-]` gives you 12.0 right away. You can see it and check it!
2. `4 [ENTER] 2 [+]` gives you 6.0. Now you see both building blocks (12.0 in Y, 6.0 in X) side by side on your screen!
3. Tapping **`[×]`** multiplies them into 72.0.
4. Tapping `6 [÷]` gives you the final answer: 12.0!

You never have to balance tricky parentheses brackets or juggle extra numbers in your head. Your calculator's stack holds your building blocks right where you can see them!

For Parents & Teachers: Cognitive Load, Working Memory & The Diagnostic Playbook

Cognitive Load & Working Memory Metrics (RPN vs. Dijkstra's Shunting-Yard Burden): In algebraic infix calculators, evaluating expressions like (15 - 3) × (4 + 2) ÷ 6 relies on Edsger Dijkstra's Shunting-Yard algorithm. This requires buffering pending operators and operands, quickly exceeding working memory token limits (typically 4 ± 1 items for elementary learners). If a student omits a parenthesis, operator precedence defaults to 15 - (3 × 4) + (2 ÷ 6) = 3.333, creating silent calculation errors. In RPN, evaluation is direct and postfix: working memory load never exceeds 2 active tokens, and every intermediate subtotal is immediately verified on the stack.

The CRA Instructional Flow: In early elementary mathematics, Jerome Bruner's Concrete-Representational-Abstract (CRA) instructional progression *(Bruner, 1966)* ensures durable mastery. On the SC-6: (1) Concrete: The Elevator and Balance Scale mental models treat numbers as physical objects occupying vertical floors. (2) Representational: The horizontal Y | X display layout aligns stack registers directly with natural left-to-right reading habits. (3) Abstract: The operator key is the evaluation event—combining quantities in real time with zero parentheses.

The Two-Passenger Rule: Math operations combine two numbers at a time. The **[ENTER]** key is pressed once to place the first number safely into holding register Y. When the second number is keyed into register X, tapping the operator executes immediately. If a student keys numbers in reverse order (3 - 15 = -12), tapping **[x⇔y]** swaps registers instantly without erasing work.

Diagnostic & Remediation Table:

• *Types 5, then 3, screen shows 53:* Remind student that **[ENTER]** closes the elevator door.

• *Entered numbers in reverse order (4 then 9):* Look at the stack before tapping the operator; tap **[x⇔y]** to swap registers instantly, then tap **[-]**.

• *Taps* **[C]** *and loses number:* Explain that **[C]** clears; use **[ENTER]** to lift.

• *Next number overwrites prior answer:* Do not clear; automatic stack lift preserves the prior total.

• *Step counter adds 0:* Use **[g] [REP]** or switch to 2-Stack (2-LV) mode.

• *Taps* **[+]** *and nothing happens:* Only one passenger on stack; need two numbers to add.

• *Division yields decimal 3.4 instead of quotient/remainder:* Use **[g] [÷R]** for integer division with remainder.

• *Self-Verification via* **[f] [LASTX]** *:* Students verify calculations independently by pressing **[f] [LASTX]** followed by the inverse operation (e.g. after 120 ÷ 8 = 15, tapping **[f] [LASTX] [×]** restores 120).

2.10 Story-Driven Problem Expeditions (40 Foundational Scenarios)

Rather than facing disconnected lists of drill problems, you embark on four cohesive mathematical missions. Each expedition grounds arithmetic in a tangible, real-world narrative where intermediate calculations matter and numbers flow naturally through the stack.

Hands-On Studio Proof: Blocks → Calculator

Step 1 (Physical Concrete Intuition): Build two physical tile towers from your manipulative studio: a red tower of 5 cubes and a green tower of 3 cubes. Place them side-by-side on your desk. Slide the 3-cube tower directly on top of the 5-cube tower into a single combined tower of 8 cubes.

Step 2 (The Representational Bridge): Look at the SC-6 display. When you enter 5 [ENTER] 3, the 5 sits on Floor 2 (Register Y) and the 3 waits on Floor 1 (Register X). The screen directly mirrors your two tabletop towers!

Step 3 (Scaling on the Calculator): Press `[+]`. The two numbers fuse into `8`. Now scale it up to building a skyscraper: type `500 [ENTER] 300 [+]` → `800`! The physical intuition of sliding blocks scales instantly to thousands and millions without pen or paper.



Figure: Math Dominoes Studio Doubling and Pairing

Figure 2.2: The Math Dominoes Studio. Domino pips let you see groups at a glance and build pairs that mirror RPN two-number operations.

2.10.1 Expedition 1: The School Playground Construction Crew (Problems 2.1–2.10)

Mission Briefing: The local elementary school is constructing a brand-new adventure playground. As the project engineers, your crew must lay border timbers, pour sandbox gravel, measure stepping stone distances, and ensure safety clearances using the SC-6 stack.

Problem 2.1: Interlocking Rubber Safety Tiles

Your playground construction crew is laying interlocking rubber safety tiles under the two-bay swing set. The crew unloads 5 blue safety tiles in the morning, and the supply truck delivers 3 more green safety tiles in the afternoon. How many total safety tiles are ready to lay down? Place 5 blue counting tiles on the left side of your desk, and 3 green tiles on the right. Slide them together into one combined row of 8 tiles. The horizontal display shows `Y = 5` (left) and `X = 3` (right) before combining. On your SC-6, key in `5 [ENTER] 3 [+]` → `8`.

Running this sequence → (T=0, Z=0, Y=0, X=8) to fuse both groups into 8 on the ground floor.

Did you see Y = 5 on the left and X = 3 on the right before pressing `[+]`? If your screen shows 53, you forgot to press `[ENTER]` between the digits! ---

Problem 2.2: Anchoring Cedar Fence Posts

Your crew needs to anchor 9 sturdy cedar fence posts along the adventure playground perimeter. Before lunch, your crew finishes concreting 4 posts firmly into the ground. How many fence posts still need to be anchored? Align 9 counting tiles in a row representing the fence line. Detach 4 tiles from the end for the completed posts. Count the 5 remaining tiles.

Left column holds starting number 9; right column holds second number 4. On the SC-6 keypad, enter `9 [ENTER] 4 [-]` → `5`.

Running this sequence → (T=0, Z=0, Y=0, X=5) to leave 5 unbolted posts on the ground floor.

If you notice that you typed the second number first (`4 [ENTER] 9`), look at your screen before pressing minus! Register Y holds 4 and Register X holds 9. Do not re-type! Simply tap **[x⇔y]** to swap them into the right seats (Y=9, X=4), then tap **[-]** to get 5! If you already tapped **[-]** and see -5, tap **[C] 9 [ENTER] 4 [-]** to recalculate smoothly. ---

Problem 2.3: Sandbox Pea Gravel Delivery

To fill the giant wooden sandbox, your crew wheels loads of washed pea gravel from the supply depot: 4 wheelbarrows on Monday, 5 on Tuesday, and 6 on Wednesday. How many total wheelbarrows of gravel did you pour into the sandbox? Stack 4 unit cubes on your desk, add 5 cubes, and then add 6 more cubes to form a single continuous tower of 15 cubes.

Turning to your SC-6, key in `4 [ENTER] 5 [+] 6 [+]` → `15 (T=0, Z=0, Y=0, X=15)`. The intermediate sum 9 automatically lifts to Y when you key 6, delivering 15 with zero extra **[ENTER]** strokes. ---

Problem 2.4: Sensory Garden Stepping Stones

Your crew is installing round sensory stepping stones along the winding garden path. You lay down 8 smooth slate stones in the morning, and the supply truck brings 7 granite stones in the afternoon. How many total stepping stones lead to the climbing tower? Place 8 counters into your first Ten-Frame tray. Take 2 counters from the group of 7 to fill the first tray to a complete 10; the remaining 5 counters spill into the second tray. Total: 1 full ten and 5 ones (15).

With your SC-6 ready, enter `8 [ENTER] 7 [+]` → `15 (T=0, Z=0, Y=0, X=15)`, bridging the decade seamlessly to leave 15 stepping stones. ---

Problem 2.5: Galvanized Jungle Gym Crossbeam Bolts

A heavy hardware box holds a bundle of 10 galvanized steel crossbeam bolts for the jungle gym frame. Your crew bolts 6 of them through the climbing net uprights. How many bolts remain in the box for the balance-beam brackets? Fill a complete Ten-Frame tray with 10 counters. Remove 6 counters. Exactly 4 counters remain in the tray.

Step over to your SC-6 and key in `10 [ENTER] 6 [-]` → `4 (T=0, Z=0, Y=0, X=4)`, leaving 4 bolts ready in Register X. ---

Problem 2.6: Zip-Line Runway Survey Flags

Your crew stakes 7 bright orange survey flags along the safety perimeter of the zip-line runway. The ground inspector checks the layout and confirms that zero additional flags are needed (+0). How many flags remain planted along the runway? Place 7 counting tiles on your desk. Add zero tiles. You still have 7 tiles.

Now compute it on your SC-6: `7 [ENTER] 0 [+]` → `7 (T=0, Z=0, Y=0, X=7)`, proving identity element a + 0 = a. ---

Problem 2.7: Safety Carabiners on the Inspection Rack

The crew equipment chest has 8 safety climbing carabiners hanging from the inspection rack. During morning foundation prep, zero carabiners are taken out because the climbing tower hasn't arrived yet. How many carabiners stay clipped to the rack? Set out 8 counting tiles. Remove zero tiles. Exactly 8 tiles remain.

Run the sequence on your SC-6: `8 [ENTER] 0 [-]` → `8 (T=0, Z=0, Y=0, X=8)`, verifying a - 0 = a. ---

Problem 2.8: Tire Swing Galvanized Chains

6 heavy galvanized link chains are uncoiled on the grass for the three playground tire swings. Your crew bolts all 6 chains to the overhead swing hanger hooks. How many uninstalled chains remain on the grass? Place 6 counting tiles on the desk. Remove all 6 tiles. Zero tiles remain (6 - 6 = 0).

Verify the calculation on your SC-6: `6 [ENTER] 6 [-]` → `0 (T=0, Z=0, Y=0, X=0)`, clearing inventory to zero. ---

Problem 2.9: Spiral Slide Safety Border Pavers

Your construction crew paves the safety perimeter around the spiral slide using 23 heavy interlocking rubber pavers, and lays another 14 pavers around the low balance-beam zone. How many total border pavers did your crew install? Build 23 using 2 ten-sticks and 3 unit cubes. Build 14 using 1 ten-stick and 4 unit cubes. Combine tens (2+1=3) and ones (3+4=7) to find 37.

Test this directly on your SC-6: `23 [ENTER] 14 [+]` → `37 (T=0, Z=0, Y=0, X=37)`, calculating 37 installed pavers in one fluent motion. ---

Problem 2.10: Soft Cedar Playground Woodchips

Your crew spreads soft cedar playground woodchips beneath the monkey bars to ensure a deep shock-absorbing cushion. The first wheelbarrow delivers 47 kg of woodchips, and the second wheelbarrow brings 36 kg. What is the total mass of woodchips spread beneath the bars? Represent 47 with 4 tens and 7 ones. Represent 36 with 3 tens and 6 ones. Combine ones (7 + 6 = 13, regroup as 1 ten and 3 ones), then add tens (4 + 3 + 1 = 8 tens). Total: 8 tens and 3 ones (83). Bring this to the SC-6 stack: `47 [ENTER] 36 [+]` → `83`.

Keystroke	Register T	Register Z	Register Y	Register X
47	0	0	0	47
[ENTER]	0	0	47	47
36	0	0	47	36
[+]	0	0	0	83
[f] **[LASTX]**	0	0	83	36
[-]	0	0	0	47

Self-Check Invariant: Rows 5 and 6 demonstrate Superpower 4 (**[f]** **[LASTX]**), verifying 83 - 36 = 47 instantly. ---

2.10.2 Expedition 2: The High-Rise Elevator Express (Problems 2.11–2.20)

Mission Briefing: You are the logistics controller for a bustling 20-story urban high-rise. Your mission is to track passenger loads rising between floors, monitor freight delivery weights, and calculate multi-floor transfers using the SC-6 operational stack.

Problem 2.11: Freight Elevator Construction Fixtures

A freight elevator begins at the ground floor loaded with 83 kg of construction fixtures. At Floor 4, the logistics crew unloads 36 kg of steel brackets. How many kilograms of cargo remain inside the freight cab? Lay out 8 ten-rods and 3 unit cubes (83). To subtract 36, trade 1 ten-rod for 10 units (leaving 7 tens and 13 units). Remove 3 tens and 6 units to leave 4 tens and 7 units (47). On your SC-6, enter `83 [ENTER] 36 [-]` → `47`.

Running this sequence → (T=0, Z=0, Y=0, X=47) to leave 47 kg of remaining fixtures. ---

Problem 2.12: Convention Delegates Passenger Doubling

An express elevator cab carries 16 convention delegates from the concourse. At the mezzanine level, an equal delegation of 16 more delegates steps aboard, doubling the passenger count. How many delegates are now riding the elevator? Modeling small with blocks before scaling up on your SC-6, stack two identical 8-tile towers using 16 kit tiles (≤ 24 tiles) to see 8 + 8 = 16. Then scale big on your SC-6 for all 32 delegates: key in `16 [ENTER] [+]` → 32!

Execute the sequence on your SC-6: `16 [ENTER] [+]` → `32 (T=0, Z=0, Y=0, X=32)`, pressing **[ENTER]** duplicates 16 into both shelves, and **[+]** doubles it instantly without re-typing! ---

Problem 2.13: Smart-Lift Automated Sensor Cascade

An automated smart-lift dispatch computer doubles its active corridor scans on each floor rise. Starting with 2 baseline sensor beams at Floor 1, determine the total active sensor scans by Floor 5. Place 2 tiles on the table. Double the pile to 4, then 8, then 16 tiles (staying strictly within your 24-tile kit bound). Feel how doubling grows in your hands, then scale big on your SC-6 up to 32! On your SC-6, key in `2 [ENTER] [+] [ENTER] [+] [ENTER] [+] [ENTER] [+]` → `32`.

Keystroke	Register T	Register Z	Register Y	Register X
2	0	0	0	2
[ENTER] **[+]**	0	0	0	4
[ENTER] **[+]**	0	0	0	8
[ENTER] **[+]**	0	0	0	16
[ENTER] **[+]**	0	0	0	32

Problem 2.14: Multi-Level Concourse Passenger Boarding

During morning rush hour, an express elevator boards 15 passengers on the subway concourse, 24 passengers on the ground plaza, and 31 passengers at the parking deck. How many total passengers are transported upward? Modeling small with blocks before scaling up on your SC-6, first model a 3-part sum with your kit (1 + 2 + 3 = 6 tiles ≤ 24). Then scale big on your SC-6 for all 70 passengers: 15 + 24 + 31 = 70! On the SC-6 keypad, enter `15 [ENTER] 24 [+] 31 [+]` → `70`.

Keystroke	Register T	Register Z	Register Y	Register X
15	0	0	0	15
[ENTER]	0	0	15	15
24	0	0	15	24
[+]	0	0	0	39
31	0	0	39	31
[+]	0	0	0	70

Problem 2.15: Observation Deck Maximum Safety Capacity

The skyscraper's observation deck elevator has a maximum permitted safety capacity of 100 people. If an incoming tour group consists of 43 visitors, how many additional visitors can board before reaching capacity? Model 100 with a ten-by-ten tile flat. Remove 4 rows of ten and 3 individual tiles to reveal 5 tens and 7 units (57).

Turning to your SC-6, key in `100 [ENTER] 43 [-]` → `57 (T=0, Z=0, Y=0, X=57)`, confirming 57 open visitor spots. ---

Problem 2.16: Rhythmic Decade Floor Sensor Calibration

The elevator safety inspector tests the floor indicator sensors by stepping upward in 10-floor intervals starting from the basement lobby (Floor 0) up to Floor 50 in 2-stack mode (`2-LV`). Line up 5 ten-rods end-to-end, counting rhythmically: 10, 20, 30, 40, 50. With your SC-6 ready, enter `10 [ENTER] 0 [+] [+] [+] [+] [+]` → `10`.

In 2-Stack mode, Register Y acts as the constant holder. Key in `10 [ENTER] 0 [+]` → (T=0, Z=0, Y=10, X=10); subsequent taps of **[+]** climb rhythmically through Floors 20, 30, 40, and 50. ---

Problem 2.17: Parking Garage EV Transfer Bays

The skyscraper's parking garage has 4 levels, each equipped with 6 electric vehicle elevator transfer bays. How many transfer bays are available in total? Construct a 4 × 6 array using 24 counting tiles from the manipulative studio.

Step over to your SC-6 and key in `4 [ENTER] 6 [×]` → `24 (T=0, Z=0, Y=0, X=24)`, calculating 24 total transfer bays. ---

Problem 2.18: Executive Window Washing Scaffold Grid

The exterior window washing elevator scaffold cleans 7 structural window bays on each of 8 executive floors. How many total window panes are washed on this run? Modeling small with blocks before scaling up on your SC-6, build a 3 × 4 array using 12 kit tiles (≤ 24). Rotate the tray 90^° to see that 3 × 4 = 4 × 3 = 12. Then scale big on your SC-6 for all 56 window panes: 7 × 8 = 56!

Now compute it on your SC-6: `7 [ENTER] 8 [×]` → `56 (T=0, Z=0, Y=0, X=56)`, evaluating 56 window panes. ---

Problem 2.19: Security Radio Lobby Distribution

A security supervisor delivers 24 handheld communication radios equally among 4 elevator lobby stations. How many radios are allocated to each station? Deal out 24 counting tiles into 4 equal groups, confirming 6 tiles in each group.

Run the sequence on your SC-6: `24 [ENTER] 4 [÷]` → `6 (T=0, Z=0, Y=0, X=6)`, allocating 6 radios per station. ---

Problem 2.20: Summit Checkpoint Security Deployment

An express shuttle elevator transports 56 security staff members arriving for an international summit, distributing them equally across 7 security checkpoint floors. How many officers are stationed on each floor? Modeling small with blocks before scaling up on your SC-6, separate a group of 14 tiles into 7 equal groups of 2 tiles (≤ 24). Then scale big on your SC-6 for all 56 officers: 56 ÷ 7 = 8 per floor!

Verify the calculation on your SC-6: `56 [ENTER] 7 [÷]` → `8 (T=0, Z=0, Y=0, X=8)`, placing 8 officers per floor. ---

2.10.3 Expedition 3: The Saturday Supermarket Shopping Spree (Problems 2.21–2.30)

Mission Briefing: Armed with a weekly household grocery budget, you navigate the supermarket aisles. You must calculate bulk food packaging remainders, compute multi-item basket discounts, verify sales receipts, and check coin

change without scratch paper.

Problem 2.21: Bakery Sourdough Dinner Roll Packaging

The bakery aisle manager packages 17 warm sourdough dinner rolls into bags of 5 rolls. How many bags are filled completely, and how many loose rolls remain? Distribute 17 counting tiles into groups of 5. Count 3 full groups and 2 loose tiles. Test this directly on your SC-6: `17 [ENTER] 5 [g] [÷R]` → `3`.

Keystroke	Register T	Register Z	Register Y	Register X
17	0	0	0	17
[ENTER]	0	0	17	17
5	0	0	17	5
[g] [÷R]	0	0	2	3
[x⇔y]	0	0	3	2

Register X shows Quotient Q = 3 full bags. Register Y holds Remainder R = 2 loose rolls. Press [x⇔y] to inspect remainder and swap back. Total bags needed to pack all rolls: 3 + 1 = 4 bags. ---

Problem 2.22: Wholesale Farm-Fresh Egg Cartons

In the dairy aisle, a wholesale crate of 125 farm-fresh eggs is sorted into specialty cartons holding 8 eggs each. How many cartons are filled completely, and how many eggs remain? Group base-10 counting blocks to represent 125 divided by 8, observing 15 full groups of 8 and 5 remaining units.

Bring this to the SC-6 stack: `125 [ENTER] 8 [g] [÷R]` → `15 (T=0, Z=0, Y=5, X=15)`, revealing 15 full cartons in Register X and 5 leftover eggs in Register Y. ---

Problem 2.23: Valencia Orange Crate Invoice Verification

The store manager orders 15 wholesale crates of Valencia oranges at $8.00 per crate (15 × 8 = 120). Verify the total invoice using Superpower 4 ([f] [LASTX]) without re-typing. Modeling small with blocks before scaling up on your SC-6, model 2 rows of 8 tiles (16 tiles ≤ 24), then divide by 8 to restore 2. Scale big on your SC-6: 15 × 8 = 120 oranges! On your SC-6, enter `15 [ENTER] 8 [×] [f] [LASTX] [÷]` → `15`.

Keystroke	Register T	Register Z	Register Y	Register X
15	0	0	0	15
[ENTER]	0	0	15	15
8	0	0	15	8
[×]	0	0	0	120
[f] [LASTX]	0	0	120	8
[÷]	0	0	0	15

Problem 2.24: Greek Yogurt Unit Pricing Swap Correction

A shopper calculates unit pricing for a 24-ounce container of Greek yogurt divided into 8 snack portions (24 ÷ 8 = 3), but accidentally typed 8 first (`8 [ENTER] 24`).

Remediation Keystrokes: `8 [ENTER] 24 [x⇄y] [÷] → 3`

Keystroke	Register T	Register Z	Register Y	Register X
8	0	0	0	8
[ENTER]	0	0	8	8
24	0	0	8	24
[x⇄y]	0	0	24	8
[÷]	0	0	0	3

Never start over when you type numbers in the wrong order! Just tap the swap key [x⇄y] to put them in the right seats, then divide! ---

Problem 2.25: Checkout Lane Impulse Rack Adjustment

A shopper enters the checkout lane with 14 items in their cart. They add 5 items from the impulse rack, but decide to put back 3 items. How many items are scanned at checkout? Place 14 counting tiles on the desk. Add 5 more tiles, then remove 3 tiles.

Execute the sequence on your SC-6: `14 [ENTER] 5 [+] 3 [-] → 16 (T=0, Z=0, Y=0, X=16)`. The subtotal 19 auto-lifts when you type 3, arriving at 16 scanned items seamlessly. ---

Problem 2.26: Artisan Baguette and Cheese Basket

At the bakery counter, a customer buys 3 artisan baguettes at $4.00 each and 2 specialty cheese rounds at $5.00 each. Find the total basket cost. Build two tile groups: one 3 × 4 array (12) and one 2 × 5 array (10). Slide them together to count 22 tiles. On your SC-6, key in `3 [ENTER] 4 [×] 2 [ENTER] 5 [×] [+] → 22`.

Keystroke	Register T	Register Z	Register Y	Register X
3	0	0	0	3
[ENTER]	0	0	3	3
4	0	0	3	4
[×]	0	0	0	12
2	0	0	12	2
[ENTER]	0	12	2	2
5	0	12	2	5
[×]	0	0	12	10
[+]	0	0	0	22

Stack Elegance: Notice in row 8: Register Y held the first subtotal (12) while Register X computed the second subtotal (10). Pressing [+] combined them cleanly without writing down anything on paper! ---

Problem 2.27: Organic Fruit Display Bumper Railing

The store manager arranges a rectangular organic fruit display table that is 12 feet long and 8 feet wide. What is the total length of decorative bumper railing needed to surround the table? Modeling small with blocks before scaling up on your

SC-6, construct a 3 by 2 rectangle with 10 perimeter tiles (≤ 24 tiles) to see 2 × (length + width). Then scale big on your SC-6: (12 + 8) × 2 = 40 feet!

On the SC-6 keypad, enter `12 [ENTER] 8 [+] 2 [×]` → `40 (T=0, Z=0, Y=0, X=40)`, calculating 40 feet of bumper railing without writing down semi-perimeter 20. ---

Problem 2.28: Triangular Bakery Promotional Sign Area

A triangular promotional sign hanging over the bakery aisle has a base of 10 cm and a height of 6 cm. What is the surface area of the promotional sign? Modeling small with blocks before scaling up on your SC-6, form a 4 × 3 array of 12 tiles (≤ 24 tiles), then cut in half to see 12 ÷ 2 = 6 tiles. Then scale big on your SC-6: 10 × 6 ÷ 2 = 30 cm^2!

Turning to your SC-6, key in `10 [ENTER] 6 [×] 2 [÷]` → `30 (T=0, Z=0, Y=0, X=30)`, evaluating the 30 cm^2 sign area cleanly. ---

Problem 2.29: Weekly Cash Grocery Budget Deduction

A customer brings a $50 cash grocery budget to the supermarket. They spend $18 on fresh produce and $12 on dairy items. How much grocery cash remains in their wallet? Start with 5 ten-rods (50). Remove 1 ten and 8 units (18, leaving 32), then remove 1 ten and 2 units (12, leaving 20).

With your SC-6 ready, enter `50 [ENTER] 18 [-] 12 [-]` → `20 (T=0, Z=0, Y=0, X=20)`, leaving $20.00 cash in your wallet. ---

Problem 2.30: Bulk Deli Sandwich Platter Cost Share

Four family members purchase a bulk deli sandwich platter costing $17.50. Using Superpower 2 (**[g] [÷R]**), determine how many whole dollars each person contributes and the remaining loose coin change. Count 17 dollar tiles and two quarter coins. Distribute 4 dollar tiles to each of 4 people, leaving $1.50 in change.

Step over to your SC-6 and key in `17.50 [ENTER] 4 [g] [÷R]` → `4 (T=0, Z=0, Y=1.5, X=4)`, giving X = $4.00 whole dollars per person and Y = $1.50 remaining change. ---

2.10.4 Expedition 4: The Junior Math Olympiad Sprint (Problems 2.31–2.40)

Mission Briefing: The state tournament clock is running! In this high-speed mental sprint, you solve chained order-of-operations expressions, evaluate multi-bracket terms with zero parentheses, and navigate radical equations using pure RPN stack elegance.

Problem 2.31: Four-Register Carousel Stack Inspection

Load values 10, 20, 30, 40 into the stack. Rotate them down to inspect each register. Now compute it on your SC-6: `10 [ENTER] 20 [ENTER] 30 [ENTER] 40 [f] [R↓]` → `30`.

Keystroke	Register T	Register Z	Register Y	Register X
10	0	0	0	10
[ENTER]	0	0	10	10
20	0	0	10	20
[ENTER]	0	10	20	20

Keystroke	Register T	Register Z	Register Y	Register X
30	0	10	20	30
[ENTER]	10	20	30	30
40	10	20	30	40
[f] [R↓]	40	10	20	30
[f] [R↓]	30	40	10	20
[f] [R↓]	20	30	40	10
[f] [R↓]	10	20	30	40

Carousel Property: 4 presses of [f] [R↓] restore the exact original stack! ---

Problem 2.32: Roof-Garden Register Extraction via Roll Down

Bring the top roof-garden register (T = 10) down into the active Ground Floor (X) by rotating the 4-level carousel three steps ([f] [R↓] [f] [R↓] [f] [R↓]). Run the sequence on your SC-6: 10 [ENTER] 20 [ENTER] 30 [ENTER] 40 [f] [R↓] [f] [R↓] [f] [R↓] → 10.

Load registers and rotate: run this sequence → (T=20, Z=30, Y=40, X=10), bringing 10 into Register X. ---

Problem 2.33: Parenthesis-Free Order of Operations Sprint

Solve the 5th-grade math tournament sprint challenge (15 - 3) × (4 + 2) ÷ 6 at full speed without writing down intermediate notes or pressing a single parenthesis key. Verify the calculation on your SC-6: 15 [ENTER] 3 [-] 4 [ENTER] 2 [+] [×] 6 [÷] → 12.

Keystroke	Register T	Register Z	Register Y	Register X
15	0	0	0	15
[ENTER]	0	0	15	15
3	0	0	15	3
[-]	0	0	0	12
4	0	0	12	4
[ENTER]	0	12	4	4
2	0	12	4	2
[+]	0	0	12	6
[×]	0	0	0	72
6	0	0	72	6
[÷]	0	0	0	12

Result: 12.0. Zero parentheses! ---

Problem 2.34: Dual Difference Quotient Challenge

Evaluate the quotient of two parenthesized differences: (24 - 8) ÷ (6 - 2). Both sub-expressions are simplified and staged cleanly on the stack before division. Test this directly on your SC-6: 24 [ENTER] 8 [-] 6 [ENTER] 2 [-] [÷] → 4.

Keystroke	Register T	Register Z	Register Y	Register X
24	0	0	0	24
[ENTER]	0	0	24	24
8	0	0	24	8
[-]	0	0	0	16
6	0	0	16	6
[ENTER]	0	16	6	6
2	0	16	6	2
[-]	0	0	16	4
[÷]	0	0	0	4

Result: 4.0. ---

Problem 2.35: Three-Part Chained Operation Triumph

Solve the three-part chained tournament challenge: (18 + 6) × (10 - 5) ÷ 12 in a single fluid stack sequence. Bring this to the SC-6 stack: `18 [ENTER] 6 [+] 10 [ENTER] 5 [-] [×] 12 [÷]` → `10`.

Keystroke	Register T	Register Z	Register Y	Register X
18	0	0	0	18
[ENTER]	0	0	18	18
6	0	0	18	6
[+]	0	0	0	24
10	0	0	24	10
[ENTER]	0	24	10	10
5	0	24	10	5
[-]	0	0	24	5
[×]	0	0	0	120
12	0	0	120	12
[÷]	0	0	0	10

Result: 10.0. ---

Problem 2.36: Multi-Term Fraction Bar Showdown

Crush the multi-term fraction bar challenge (48 - (4 × 6) / 3 + (2 × 4.5)) directly on the stack with zero parentheses: evaluate the numerator (24), evaluate the denominator (12), and divide!

On your SC-6, enter `48 [ENTER] 4 [ENTER] 6 [×] [-] 3 [ENTER] 2 [ENTER] 4.5 [×] [+] [÷]` → `2 (T=24, Z=24, Y=24, X=2)`, resolving the complex fraction to 2.0 with zero parentheses! ---

Problem 2.37: Square Patio and Fountain Paved Border

A large square patio of 15 ft × 15 ft has a central fountain of 9 ft × 9 ft. Find the remaining paved area. Execute the sequence on your SC-6: `15 [x²] 9 [x²] [-] → 144`.

Keystroke	Register T	Register Z	Register Y	Register X
15	0	0	0	15
[x²]	0	0	0	225
9	0	0	225	9
[x²]	0	0	225	81
[-]	0	0	0	144

Result: 144.0 sq ft. ---

Problem 2.38: Right Triangle Slant Distance via Pythagorean Theorem

A right triangle has perpendicular legs of 6 cm and 8 cm. Find hypotenuse $c = \sqrt{(a^2 + b^2)}$.

On your SC-6, key in `6 [x²] 8 [x²] [+] [f] [√x] → 10 (T=0, Z=0, Y=0, X=10)`, computing hypotenuse 10.0 cm without scratch paper. ---

Problem 2.39: Fahrenheit to Celsius Temperature Conversion

Convert 68^°F to Celsius: C = (F - 32) × 5 ÷ 9.

On the SC-6 keypad, enter `68 [ENTER] 32 [-] 5 [×] 9 [÷] → 20 (T=0, Z=0, Y=0, X=20)`, converting directly to 20.0^°C. ---

Problem 2.40: School Savings Account Balance Restoration

Your school savings account has $120.00. You make a purchase of $45.00. Use Superpower 4 to restore your previous balance. Turning to your SC-6, key in `120 [ENTER] 45 [-] [f] [LASTX] [+] → 120`.

Keystroke	Register T	Register Z	Register Y	Register X
120	0	0	0	120
[ENTER]	0	0	120	120
45	0	0	120	45
[-]	0	0	0	75
[f] [LASTX]	0	0	75	45
[+]	0	0	0	120

Result: Initial $120.00 balance completely restored. ---

2.11 What You Mastered & Looking Ahead

Now that you've mastered pushing numbers onto the stack, swapping registers, and dropping calculations cleanly, let's travel back in time to discover how ancient pebble counters and ten human fingers created zero and the power of place

value!

Counting, Number Lines & Place Value Studio

3.1 The Greatest Invention in Human History: How Ten Fingers and an Empty Shell Created Zero and Place Value

Five thousand years ago, across the fertile river valleys of the Tigris and Euphrates, an ancient shepherd stood before his flock at dawn. To keep account of his sheep, he dropped small clay pebbles into a woven pouch—one pebble for every sheep that passed through the wooden gate. If thirty sheep walked by, thirty pebbles weighed down his hip. But what happened when a city merchant wished to tally three thousand bushels of barley or thirty thousand bricks for a temple wall? Pockets tore; stone piles grew unmanageable; human memory buckled.

Ancient Egyptian scribes invented symbols for larger numbers: a coiled rope for one hundred, a lotus plant for one thousand, a pointing finger for ten thousand. Yet even with these hieroglyphic shortcuts, writing the number 9,999 required thirty-six separate symbols carved into stone!

Then came what historians of science consider the single greatest intellectual leap in human history: **Place Value and the Invention of Zero.**

In ancient India and among the classic Maya of Mesoamerica, thinkers made a startling realization. You do not need thousands of distinct symbols to write every number in the cosmos. You need only ten fingers, ten counting digits (0 through 9), and a spatial rule: **where a symbol sits changes what it means.** An empty shell glyph drawn in the sand—or an empty groove on a counting board—told the reader: *nothing is in this column, but hold this place open!* Because an empty groove held space, a single digit 1 could represent one sheep, ten sheep, one hundred sheep, or ten million stars simply by sliding across columns.

The decimal system was born of our anatomy: ten fleshy fingers resting on a tabletop.

On the **StackCalc SC-6**, this five-thousand-year evolution is not an abstract lecture; it is a living tactile laboratory. When you touch the precision-milled **Ten-Frame Studio** or slide the vivid dual-color beads of the **Number Rack**, you recreate the ancient counting table with your own fingers. And when you press `[PV]` Place Value mode or watch numbers leap across the open number line (`[f]` `[LINE]`), you see the machinery of base-10 decomposition come alive.

CHAPTER BASELINE MODE: `[NUM]` (Standard Base-10 Arithmetic • 4-Stack XYZT • Visual sandboxes `[FRAME]`, `[g]` `[COUNT]`, and `[LINE]` open self-contained 2-stack screens)

Unlocked Keycaps Ribbon — Grades K–2 Visual & Counting Suite

- **Visual Sandbox Keys:** `[FRAME]` Ten-Frame Studio, `[f]` `[LINE]` Number Line, `[g]` `[COUNT]` Step Counter / Number Rack, `[PV]` Place Value Mode.
- **Interactive Sandbox Stepper:** `[.]` (Drops counters / steps by one).
- **Core Operations:** `[+]`, `[-]`, `[ENTER]`, `[C]`, `[<-]`, Digits `[0]` – `[9]`.
- **Stack View Options:** Choose between a simple 2-shelf view or 4-shelf view with `[g]` `[FLAGS]`, plus `[g]` `[REP]` Skip-Counting.
- **Mode Navigation:** Pressing `[NUM]` or `[C]` cleanly returns to baseline arithmetic with zero stack corruption.

3.2 Building Numbers: From Hands-On Blocks to the Screen Stack

Before numbers become symbols on a screen, they start as real objects in your hands! When you learn math on the StackCalc SC-6, you always move through three fun steps:

1. **Hands-On Blocks (Touch It!):** You build with real physical blocks, flip counters, and slide beads across rails on your desk.
2. **Picture Screen (See It!):** You tap sandbox keys like `[FRAME]` or `[f] [LINE]` to see your blocks mirrored as clear pictures on the daylight screen.
3. **The Number Stack (Solve It!):** You combine numbers on the 4-level stack with lightning speed!

For Parents & Teachers: The CRA Learning Continuum

In elementary mathematics education, Jerome Bruner's **Concrete-Representational-Abstract (CRA)** framework *(Bruner, 1966)*, Zoltan Dienes's work on multibase arithmetic blocks *(Dienes, 1960)*, Liping Ma's research on fundamental mathematics *(Ma, 1999)*, and the Singapore Math model *(Singapore MOE, 2014)* provide the gold standard for developing deep mathematical understanding under national standards *(CCSSM, 2010)*.



Figure: Ten-Frame Studio Physical Manipulative Kit

Figure 3.1: The Ten-Frame Studio with dual-color counters. Tactile grounding for five-anchors, decade bridging, and place value.

Learning Stage	Physical Manipulative	SC-6 Representational Sandbox	Abstract Operational Stack
1. Concrete (Enactive)	Ten-Frame Trays & Dual-Color Disks	Hands-on physical token placement	Sensory tactile certainty
2. Representational (Iconic)	20-Bead Rekenrek Number Rack	High-contrast `[FRAME]` and `[g] [COUNT]` LCD vector grids	Visual subgroup perception
3. Abstract (Symbolic)	Place Value Studio	`[LINE]` jump arcs and `[PV]` Place Value mode	4-Register RPN stack arithmetic

When you skip the concrete and representational phases and jump straight into symbolic calculation on conventional calculators, math can feel like a set of arbitrary rules without conceptual grounding. When faced with an expression such as `8 + 5`, numerals can seem like disconnected symbols and the equal sign (`=`) like a magic black box.

The **StackCalc SC-6** was engineered specifically to give you direct physical grounding. By pairing physical, open-source 3D-printed math manipulatives with dedicated hardware visual sandbox keys (`[FRAME]` , `[g] [COUNT]` , `[f] [LINE]` , `[PV]`), the SC-6 bridges the tactile world of physical objects directly into the spatial logic of the RPN operational stack.



Figure: SC-6 Ten-Frame Studio Mode: Bridging Ten with 8 + 5 = 13

Parent's De-Stressing Guide: "Carry the 1" vs. The Ten-Frame Bridge

The Scenario: Your 1st or 2nd grader is given: `8 + 5 = ?`

The Conventional Nightmare:

Parents teach what they were taught: "Put 8 on top, 5 on bottom. 8 + 5 is 13. Write down 3, carry the 1." The child asks: *"Why do I carry 1 if it's 13?"* The parent says: "Because it goes in the tens column." The child tears up, memorizing an abstract spatial ritual with zero meaning.

The 30-Second Tactile Cure:

Hand your child the 2×5 Ten-Frame Tray and dual-color tokens:

• Place 8 RED tokens in the frame. Point to the 2 empty pockets: *"How many more does 8 need to become a full Ten?" ("Two!")*

• You have 5 GOLD tokens waiting on the desk.

• Take 2 gold tokens and slide them into the frame: **CLICK!* "Ten is full! How many gold tokens are left on the desk?" ("Three!")*

• One full Ten and 3 ones = **13**!

On the SC-6: Key in `[FRAME] 8 [ENTER] 5 [+]` . The display registers `13`.

The child has just executed the fundamental mental math strategy of the world's best mathematicians: **Bridging Ten:** `8 + 5 = (8 + 2) + 3 = 10 + 3`.

3.2.1 Seeing Groups Instantly Without Counting One-by-One!

Have you ever rolled a dot die and known right away it was a 5, without having to point your finger and count 1, 2, 3, 4, 5? That superpower is called **seeing groups at a glance**!

When you look at small groups of dots, blocks, or counters, your brain recognizes the total in a split second. By organizing numbers around friendly landmarks of **5** and **10**, the SC-6 and your Ten-Frame Studio let you see big numbers just as easily as small numbers—without counting on your fingers!

For Parents & Teachers: The Cognitive Science of Subitizing

Subitizing—derived from the Latin *subitus* ("sudden")—is the cognitive capacity to instantaneously perceive how many items are in a small collection without counting them one by one.

Cognitive psychologists divide subitizing into two distinct levels:

• **Perceptual Subitizing (Quantities 1 to 4):** A hardwired neurobiological mechanism in the human visual cortex. You glance at 1, 2, 3, or 4 marbles and instantly recognize the total without counting.

• **Conceptual Subitizing (Quantities 5 to 10+):** The ability to perceive a larger quantity by recognizing spatial subgroups and mentally combining them into a whole. Viewing 7 dots arranged in a 5-and-2 configuration, you don't count 1, 2, 3, 4, 5, 6, 7; you instantly see a full row of 5 plus 2 loose units (5 + 2 = 7).

The SC-6 hardware visual engines are explicitly architected around anchors of **5** and **10**, providing the exact visual scaffolding needed to bridge perceptual recognition into effortless conceptual subitizing.

3.2.2 How Your Trays and Counters Are Built for Your Hands

The physical manipulative studios accompanying the SC-6 are engineered as modular tactile companions, standardized on the Gridfinity organization grid. Where the calculator provides a dark, glare-free slate upon which numbers are evaluated, the manipulative blocks supply immediate physical mass and vibrant color:

- **Ten-Frame Studio & Dual-Color Counters:** Dual ten-frame wells separated by a raised architectural divider rib. The physical tactile ridge provides an unmistakable boundary at five, allowing fingers to verify group sizes without counting. Chamfered counter disks in contrasting coral and amber seat firmly into each pocket.
- **Number Rack (Rekenrek):** Dual horizontal stainless guide rails holding smoothly sliding beads arranged in five-and-five color clusters, mirroring the two-register display of the calculator.
- **Place Value Studio:** Precision metric base-10 unit cubes, ten-rods, and hundred-flats. Each ten-rod equals exactly ten unit cubes placed end-to-end; each hundred-flat matches ten rods side-by-side. Weight and volume scale proportionally with numerical magnitude.
- **Counting & Array Tiles:** Interlocking tactile tiles engineered with precise slip-fit tabs that assemble into rigid 2D arrays and vertical counting towers.
- **Prime Factor Studio:** Precision logarithmic blocks whose physical lengths correspond to the logarithms of prime factors, allowing multiplication to be experienced as collinear block addition.

3.3 Concrete Bridge to the Ten-Frame Studio ([■])

The Ten-Frame helps you see numbers in groups of five and ten. It builds instant visual recognition and shows why 10 is such a powerful landmark number.

> **OPERATIONAL NOTE // RPN STACK INSIGHT**
>
> **Architectural Geometry of the Ten-Frame Tray:**
>
> The physical Ten-Frame Studio features a dual 2 × 5 compartment field separated by a raised central divider rib. This rib physically isolates the first five units from the second five units, establishing instant five-structure group recognition in high-contrast matte compartments with vivid dual-color counters.

3.3.1 Entering the Ten-Frame Sandbox

To activate the interactive Ten-Frame Studio on the SC-6:

1. Enter a starting quantity into Register X (for example, tap `[7]`).
2. Press the hardware `[FRAME]` key (Row 1, Col 1).
3. The transflective dot-matrix LCD automatically shifts from its 4-register numeric layout into its two-zone concrete layout:

- **Upper Screen (Ten-Frame Grid):** High-contrast 1-bit vector bitmap depicting two ten-frame grids with 7 filled circular counters.
- **Lower Screen (Active Stack):** Simplified 2-line arithmetic stack displaying Register Y (Holding) and Register X (Active).

Display Region	Visual & Numeric Representation (`X = 7`)
Upper Screen (Ten-Frame Grid)	Top row: `[⊠][⊠][⊠][⊠][⊠]` (5 filled); Bottom row: `[⊠][⊠][ ][ ][ ]` (2 filled, 3 empty)
Lower Screen (Active Stack)	`Y: 0` | `X: 7` (5 + 2 = 7 seen at a glance)

Notice how the 7 counters are organized:

- The top row of the first ten-frame is completely filled with 5 counters.
- The bottom row contains exactly 2 counters.
- The remaining 3 slots in the first frame are empty.
- The second ten-frame remains completely vacant.

When you look at this screen, you don't need to count 1, 2, 3, 4, 5, 6, 7. Your eyes instantly recognize the full top row of 5 plus the bottom 2 units: 5 + 2 = 7.

3.3.2 Interactive Stepping with the Decimal Key ([.])

While inside the Ten-Frame Studio, you can interact directly with the screen. Pressing the decimal key `[.]` drops counters into the frame one by one:

- Tap `[.]` → Counter 8 drops into the bottom row (X updates to 8).
- Tap `[.]` → Counter 9 drops into the bottom row (X updates to 9).
- Tap `[.]` → Counter 10 completes the first ten-frame! The frame border flashes inverted pixels for 300 ms to provide an unmistakable visual cue that a full decade has closed.

- Tap `[.]` → Counter 11 cascades across the architectural divider rib into the second ten-frame (X updates to 11).

STEPPING PAST THE DECADE BOUNDARY VIA `[.]` :

Frame State at X = 9:

[●][●][●][●][●] | [●][●][●][●][ ] (1 empty slot remaining)

Tap `[.]` :

[●][●][●][●][●] | [●][●][●][●][●] (FULL FRAME FLASH: Decade closed! X = 10)

Tap `[.]` :

Frame 1: [●][●][●][●][●] | [●][●][●][●][●]

Frame 2: [●][ ][ ][ ][ ] | [ ][ ][ ][ ][ ] (Cascaded into Frame 2! X = 11)

For Parents & Teachers: Homeschooler Diagnostic Checkpoint

• **Ask your child:** "How many empty spots are left in the first ten-frame?"

• If there are 7 counters, your child can visually identify 3 empty spaces.

• Have them press `[3]` `[+]`. The display completes the ten-frame and shows X = **10**!

3.4 Making Ten & The "Bridging Ten" Strategy

When you first add across a ten boundary (like 8 + 5), counting on your fingers (*"eight... nine, ten, eleven, twelve, thirteen"*) can feel slow and tricky. The Ten-Frame Studio teaches the foundational **Bridging Ten** strategy: **8 + 5 = 8 + (2 + 3) = (8 + 2) + 3 = 10 + 3 = 13**

The Bridging Ten Mental Model: Decomposing into a Decade

• **Step 1 (Anchor the 8):** Start with 8 counters in the first frame (2 empty slots remain):

`[☒][☒][☒][☒][☒] | [☒][☒][☒][ ][ ]`

• **Step 2 (Decompose the Addend):** You have 5 counters to add. Decompose 5 into `2 + 3`. Transfer 2 counters into Frame 1 to make a complete 10!

`[☒][☒][☒][☒][☒] | [☒][☒][☒][☒][☒]` ← **10 (Full Frame!)**

• **Step 3 (Place the Remainder):** Place the remaining 3 counters into Frame 2:

`[☒][☒][☒][ ][ ] | [ ][ ][ ][ ][ ]` ← **3 in Frame 2**

• **Total:** `10 + 3 = 13!` Mental addition across decades becomes effortless spatial grouping.

3.4.1 Station Lesson 3.1: Ten-Frame Bridging Ten & Dual-Color Counters

STATION LESSON 3.1: TACTILE SETUP

• Manipulatives: Ten-Frame Tray with Dual-Color Counters (Coral Red / Amber Gold)

• Hardware: StackCalc SC-6 Elementary in `[FRAME]` Ten-Frame Mode

• Goal: Add 8 + 5 without finger counting via the decade bridge



Figure: Ten-Frame Studio: Bridging Ten Strategy (8 + 5 = 13)

1. **Concrete Phase (Desk Setup):**

- Place 8 Red counters into Frame 1 of the physical tray (filling the top row of 5 and bottom row of 3).
- In your hand, hold 5 Gold counters to add.
- Notice that Frame 1 needs exactly 2 counters to become completely full (reaching 10).
- Drop 2 Gold counters into Frame 1, completing the ten: 8 + 2 = 10.
- Drop the remaining 3 Gold counters into Frame 2: 10 + 3 = 13.

2. **Representational Phase (Screen Verification):**

- Press `[8] [FRAME]`. The SC-6 LCD renders 8 circular dots across the dual ten-frame.
- Press `[2] [+]`: Two counters land in Frame 1, flashing the decade banner: X = **10**.
- Press `[3] [+]`: Three counters land in Frame 2: X = **13**.

3. **Abstract Phase (RPN Stack Trace Table):**

Keystroke	Register T	Register Z	Register Y	Register X (Display)
`[8]` `[FRAME]`	0	0	0	8
`[2]` `[+]`	0	0	0	10
`[3]` `[+]`	0	0	0	13

For Parents & Teachers: Teacher Dialogue Script

Teacher: "Look at our Ten-Frame screen with 8 filled circles. How many empty boxes are left to make a full ten?"

Student: "Two empty boxes!"

Teacher: "Great. We need to add 5 circles. If we drop 2 circles into the empty boxes to make ten, how many are left in our hand?"

Student: "Three are left in our hand!"

Teacher: "Ten plus three makes what?"

Student: "Thirteen!"

Teacher: "Did we have to count on our fingers?"

Student: "No! We just made ten and added the rest!"

3.5 The Step Counter Dynamics & Stacking Tile Heights

How do you discover that counting forward is mathematically identical to repeatedly adding one? On conventional algebraic calculators, pressing `+ 1 = = =` relies on hidden accumulator memory that obscures the underlying mechanism. On the SC-6, step counting is completely transparent and verified through physical tile heights and stack mechanics.

3.5.1 Station 3.2: Counting Up with Stacking Tiles

STATION LESSON 3.2: TACTILE SETUP

- Manipulatives: Counting & Array Studio with 144 Interlocking Stacking Tiles
- Hardware: StackCalc SC-6 Elementary (2-LV and 4-LV Stack Modes)
- Architectural Benchmark: 12 Tiles × 7.0 mm = 84.0 mm (1 Whole Datum)



Figure: Master Datum Alignment: 12 Counting Tiles (12 x 7.0 mm = 84.0 mm) Flush with 1-Whole Fraction Tower

STACKING TILE VERTICAL TOWER LADDER:

[TILE 12] → 84.0 mm (Flush with 1-Whole Fraction Studio Tower!) X = 12

[TILE 11] → 77.0 mm X = 11

[TILE 10] → 70.0 mm X = 10

[TILE 9] → 63.0 mm X = 9

[TILE 8] → 56.0 mm X = 8

Stacked Tile Count (X)	Cumulative Physical Height	Geometric & Fraction Studio Datum
Tile 1 (X = 1)	7.0 mm	1U visible increment = 1/12 Fraction Tower
Tile 2 (X = 2)	14.0 mm	1/6 Fraction Tower datum
Tile 3 (X = 3)	21.0 mm	1 Unit Cube equivalent = 1/4 Fraction Tower
Tile 4 (X = 4)	28.0 mm	1/3 Fraction Tower datum
Tile 6 (X = 6)	42.0 mm	Halfway datum = 1/2 Fraction Tower
Tile 12 (X = 12)	84.0 mm	Full 1-Whole Master Fraction Tower

Hands-On Stacking Protocol:

Part 1 — In 2-Stack Mode ([g] [FLAGS] → 2-LV):

- Place 1 Archival White tile on the desk (7.0 mm height). Press [1] [ENTER] [1] [+] → X = 2.
- Stack tile 2 on top (14.0 mm). Tap [+] → X = 3.
- Stack tile 3 on top (21.0 mm). Tap [+] → X = 4.
- Continue stacking in cadence with tapping [+] until reaching 12 tiles (84.0 mm).
- Compare your 12-tile tower against the solid 1-Whole Fraction Studio tower: *they are exactly flush to the fraction of a millimeter!*

Keystroke	Register Y (Constant)	Register X (Display)	Physical Tile Height on Desk (7.0 mm per Tile)
[1] [ENTER]	1	1	1 Tile = 7.0 mm
[1]	1	1	1 Tile = 7.0 mm
[+]	1	2	2 Tiles = 14.0 mm
[+]	1	3	3 Tiles = 21.0 mm (1 Unit Cube!)
[+]	1	4	4 Tiles = 28.0 mm
[+]	1	5	5 Tiles = 35.0 mm
[+]	1	6	6 Tiles = 42.0 mm (1/2 Whole Tower)
[+]	1	7	7 Tiles = 49.0 mm
[+]	1	8	8 Tiles = 56.0 mm
[+]	1	9	9 Tiles = 63.0 mm
[+]	1	10	10 Tiles = 70.0 mm
[+]	1	11	11 Tiles = 77.0 mm
[+]	1	12	12 Tiles = 84.0 mm (1 Whole Tower!)

Part 2 — In 4-Stack Mode with Superpower 1 ([g] [REP]):

- Ensure 4-Stack mode is active ([g] [FLAGS] → 4-LV).
- Press [1] [g] [REP] : All four registers (T, Z, Y, X) receive 1.
- Now, each tap of [+] drops Register T downward, advancing the display count (2, 3, 4, ..., 12) in sync with placing physical tiles!

Keystroke	Register T (Constant)	Register Z	Register Y	Register X (Display)
[1]	0	0	0	1
[g] [REP]	1	1	1	1
[+]	1	1	1	2
[+]	1	1	1	3
[+]	1	1	1	4
[+]	1	1	1	5
[+]	1	1	1	6

Part 3 — Counting Backward (Subtraction Towers):

- Starting with a 10-tile tower (70.0 mm): [1] [0] [ENTER] [1].
- Remove 1 tile from the tower on the desk. Tap [-]: X = **9**.
- Remove another tile. Tap [-]: X = **8**.
- Countdown continues to X = **0** when the tabletop is completely clear: Blast off!

Keystroke	Register Y	Register X
10 [ENTER]	10	10
[1] [-]	10	9
[-]	10	8
[-]	10	7
[-]	10	6
[-]	10	5
[-]	10	4
[-]	10	3
[-]	10	2
[-]	10	1
[-]	10	0

3.5.2 Station Lesson 3.3: Mind-Blowing Epiphany 1 — The Sum of Odd Numbers is Always a Perfect Square!

> **For Parents & Teachers: Curriculum Standards**
>
> Common Core Standards Alignment: CCSS.MATH.CONTENT.3.OA.D.9, 4.OA.C.5.

- **Physical Manipulatives:** 16 Counting Tiles from the Counting Studio: 1 Archival White, 3 Cobalt Blue, 5 Radiant Gold, 7 Slate Gray.

What happens when you add consecutive odd numbers starting from 1? **$1 = 1 = 1^2$ $1 + 3 = 4 = 2^2$ $1 + 3 + 5 = 9 = 3^2$ $1 + 3 + 5 + 7 = 16 = 4^2$ $1 + 3 + 5 + 7 + 9 = 25 = 5^2$**

Why is this always true for *every single square number in the universe*? The ancient Pythagoreans called this the **Gnomon Principle**, and it is instantly self-evident when built with the four-color physical counting tiles:

> **Visual Proof Without Words: Odd Numbers Build Squares**
>
> The ancient Pythagoreans discovered that geometric squares grow by wrapping L-shaped brackets called **gnomons** around smaller squares:
>
> • **Stage 1 (1 Tile):** `1 = 1²` (Single white corner tile).
>
> • **Stage 2 (1 + 3 = 4 Tiles):** Three blue tiles wrap around the white tile, creating a `2 × 2 = 4 = 2²` square.
>
> • **Stage 3 (1 + 3 + 5 = 9 Tiles):** Five gold tiles wrap around the 2×2 square, forming a `3 × 3 = 9 = 3²` square.
>
> • **Stage 4 (1 + 3 + 5 + 7 = 16 Tiles):** Seven gray tiles wrap around the 3×3 square, forming a `4 × 4 = 16 = 4²` square.
>
> **The Epiphany:** Every consecutive odd number `(2n - 1)` forms an L-shaped gnomon that wraps around an `(n-1) × (n-1)` square to produce the next `n × n` square. Arithmetic addition and geometric area are two reflections of the exact same truth!

Verification on the SC-6:

Key in the running odd sum in RPN:

- **`[1] [ENTER] [3] [+]`** → **4** (2^2): lay the first unit cube in the center (Y = 1) and snap an L-shaped 3-cube gnomon around the corner to complete a 2 × 2 square (X = 4).
- Tap **`[5] [+]`** to snap a 5-cube gnomon along the two outer edges → **9** (3 × 3 square).
- Tap **`[7] [+]`** to wrap a 7-cube band along the perimeter → **16** (4 × 4 square).
- Tap **`[9] [+]`** to wrap a 9-cube band along the perimeter → **25** (5 × 5 square).
- **`[1] [1] [+]`** → **36** (6 × 6 square)
- Tap geometric square root **`[f] [√x]`** → **6**! The physical side length of the square appears instantly.

3.6 Number Line Navigation & Visual Jump Arcs ([f] [LINE])

The Open Number Line lets you visualize addition and subtraction as physical travel along a continuous spatial pathway.

3.6.1 The Number Line Sandbox

Tapping **`[f] [LINE]`** opens the dynamic Number Line Studio. The SC-6 engine automatically calculates decade tick scaling (1, 2, 5, 10) to render up to 13 high-contrast ticks:

Display Zone	Visual Representation (`2 + 5 = 7`)
Jump Arc Layer	Parabolic forward jump arc labeled `+5` spanning from tick `2` to tick `7`
Number Line Axis	High-contrast tick ruler spanning `0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11`
Register `Y:`	`2` (Starting coordinate)
Register `X:`	`7` (Landing coordinate after `+5` jump)

3.6.2 Visual Jump Arcs

When an operation executes on the number line, the screen animates a parabolic **jump arc** connecting the starting coordinate to the landing coordinate:

- **Forward Jump (2 + 5 = 7):** An arc curves forward from 2 to 7, clearly labeled with `+5`.
- **Backward Jump (9 - 4 = 5):** An arc leaps backward from 9 to 5, labeled `-4`.

The engine tracks `lastOp`, `lastOpStart`, `lastOpEnd`, and `lastOpDelta`, giving you immediate visual confirmation of distance, direction, and magnitude.

Number Line Jump Arc Dynamics

• **Forward Jump (Addition):** Adding a positive number leaps forward. For `14 + 8`, an arc sweeps from 14 across 8 increments, landing cleanly on 22: `14 ▯▯(+8)▯▯> 22`.

• **Backward Jump (Subtraction):** Subtracting steps backward. For `22 - 5`, an arc leaps leftward from 22 across 5 increments, landing on 17: `17 <▯▯(-5)▯▯ 22`.

The SC-6 display animates these exact parabolic paths in real time, making distance, direction, and magnitude visually tangible.

3.7 The European Rekenrek / Number Rack ([g] [COUNT])

The 100-bead and 20-bead Rekenrek (Number Rack) was invented by Adrian Treffers at the Freudenthal Institute in the Netherlands. It consists of two parallel stainless-steel rods, each carrying beads divided into color-coded groups of **5 Red** and **5 White**.

REKENREK 100-BEAD DUAL-WIRE GEOMETRY

Wire 1 (Tens): [■■■■■][■■■■■] --- [■■■■■][■■■■■]

Wire 2 (Ones): [■■■■■][■■■■■] --- [■■■■■][■■■■■]

3.7.1 Operating Rekenrek Mode ([g] [COUNT])

1. Type a target number (for example, **`[1] [4]`**).
2. Press **`[g] [COUNT]`**.
3. The transflective LCD maps the quantity across the two wires:

- Wire 1 shows 10 beads slid to the active left side (5 red, 5 white).
- Wire 2 shows 4 red beads slid to the active left side.

4. Pressing **`[.]`** slides individual beads one by one across the wire, up to 100!

3.7.2 Decomposing Teen Numbers (11 to 19)

Teen numbers can sometimes sound confusing in English. In languages like Chinese or Japanese, 14 is spoken directly as *"ten-four"*, immediately revealing its place-value structure! In English, *"fourteen"* sounds like four comes first, which can tempt you to write 41 instead of 14.

On the Rekenrek screen:

- 14 is rendered as: **Full Wire 1 (10) + 4 Red Beads on Wire 2**.
- You can visually see that 14 is literally 10 + 4.
- The confusion vanishes the moment you see the physical beads!

3.8 Place Value Decomposition Studio ([PV])

Place value is one of the most exciting secrets in mathematics. When you look at a big number like 4,725, it isn't just four separate digits sitting next to each other ("4", "7", "2", "5"). It is actually four distinct bundled packages working together: **4,725 = 4,000 + 700 + 20 + 5**

The SC-6 provides a dedicated hardware **Place Value Engine (`[PV]`)** on Row 1, Col 5.

The physical base-10 blocks embody metric proportions with architectural rigor:

- **Unit Cube (1U):** A 10 × 10 × 10 mm cube in solar amber with subtle chamfered edges for easy grasping.
- **Ten-Rod (10U):** A 10 × 10 × 100 mm linear bar scoring ten distinct cubic segments, matching ten unit cubes placed edge to edge.
- **Hundred-Flat (100U):** A 10 × 100 × 100 mm planar grid representing ten rods bonded along their flanks.
- **Thousand-Cube (1000U):** A solid 100 × 100 × 100 mm monolithic block with mass equivalent to one thousand individual unit cubes, providing tactile weight that makes place value unforgettable.



Figure: Place Value Studio Base-10 Decomposition and Regrouping

Figure 3.3: The Place Value Studio. Base-10 metric unit cubes, 10U rods, and 100U flats physicalize positional notation, pairing directly with the SC-6 `[PV]` mode.

3.8.1 Operating Place Value Mode

The `[PV]` key extracts the specific digit occupying any target power of 10. It expects:

- The **Subject Number** in Register Y.
- The **Target Place** (1, 10, 100, 1000) in Register X.

Mathematical definition: **placeValueDigit(Y, X) = ■ (|Y| / X) ■ mod 10**

Example: Decomposing 4,725

1. Enter the subject number: `[4] [7] [2] [5] [ENTER]`.
2. Query the Tens place: `[1] [0] [PV]`.

- Register X displays: 2 (There are 2 tens in 4,725!).

Keystroke	Display T	Display Z	Display Y (Subject)	Display X (Query / Result)
4725	0	0	0	4725
[ENTER]	0	0	4725	4725
10	0	0	4725	10
[PV]	0	0	4725	2

3.8.2 Why the Parts Always Add Back to Your Whole Number!

Notice the crucial behavior in the stack trace above: **Register Y is strictly preserved (4725), and stack lift is disabled!**

This invariant allows you to rapidly query every single place value column without re-typing your number:

- Query Hundreds: Type `[1] [0] [0] [PV]` → X = **7** (7 hundreds).
- Query Thousands: Type `[1] [0] [0] [0] [PV]` → X = **4** (4 thousands).
- Query Ones: Type `[1] [PV]` → X = **5** (5 ones).

(Hardware Invariant: Place value extraction preserves Register Y while populating Register X with the selected decimal place value.)

3.8.3 Exploring Tenths and Hundredths with Place Value

In Grade 5, place value extends to the right of the decimal point (tenths and hundredths):

- Query Tenths (0.1): Type `[.] [1] [PV]` on 345.67 → X = **6**.
- Query Hundredths (0.01): Type `[.] [0] [1] [PV]` on 345.67 → X = **7**.

3.8.4 Algebraic Trap vs. StackCalc Superpower Showdown: Place Value & Positional Notation

Challenge / Real-World Task	The Algebraic Calculator Trap (TI-84 / Infix)	Algebraic Keystrokes & Clutter	The StackCalc Superpower (RPN Stack + Visual Studio)	StackCalc Keystrokes	The Stack Advantage
Stadium Light Wattage: • Chained multi-bank load sum: • (30 × 1500) + (10 × 2000)	Infix hierarchy confusion requires nested parentheses. Misplaced or forgotten brackets cause premature addition (1500 + 10 = 1510), inflating bank wattage to 906,000 W instead of 65,000 W!	`( 3 0 * 1 5 0 0 ) + ( 1 0 * 2 0 0 0 ) =` • (23 keystrokes, syntax brackets)	**RPN Parallel Accumulation:** • Evaluates bank A (45,000) and bank B (20,000) into visible registers Y and X, then combines them in a single keystroke with zero parentheses.	`30 [ENTER] 1500 [×] 10 [ENTER] 2000 [×] [+]` • (16 keystrokes)	**30% fewer keystrokes** • Both power bank subtotals remain in plain sight on the stack before combining.
Decade Bridging: • Mental addition across ten boundary: • 8 + 5 = (8 + 2) + 3 = 10 + 3	Single-line algebraic screens hide the intermediate landmark of 10. Pressing equals triggers a black-box answer without showing the decade container closing.	`8 + 2 + 3 =` • (Single-line display; intermediate decade lost)	**Ten-Frame Studio Bridge (`[FRAME]`):** • Interactive grid drops 2 counters into Frame 1, flashing the completed decade at 10, then cascades remaining 3 counters into Frame 2.	`8 [ENTER] 2 [+] 3 [+]` • (Visual ten-frame flash at X = 10)	**Visual Decade Landmark:** • Concrete spatial grouping eliminates finger-counting and reveals why bridging ten works.
Place Value Interrogation: • Extracting tens and hundreds from 4,725 without scratch paper	Infix calculators have no positional extraction keys. Students must manually divide by 10, subtract the integer part, and multiply back—destroying the original number.	`4 7 2 5 / 1 0 =` → 472.5 • `- 4 7 0 =` → 2.5 • (Destructive multi-step division)	**Preserved Subject Engine (`[PV]`):** • Dedicated hardware instruction preserves subject 4,725 in Register Y, suppressing stack lift so subsequent queries execute instantly.	`4725 [ENTER] 10 [PV] 100 [PV] 1000 [PV]` • (Chained single-stroke queries)	**Zero Value Destruction:** • Subject number remains permanently parked in Register Y; queries tens (2), hundreds (7), thousands (4) in rapid cadence.
Rhythmic Cadence Counting: • Even number ladder up to 20	Infix constant equals-key mode (`2 + 2 = = =`) relies on hidden register state that fails if any non-equals key is accidentally touched.	`2 + 2 = = = = =` • (Flaky state; hidden accumulator easily cleared)	**Stack Constant Duplication:** • In 2-LV mode, Register Y preserves constant 2.0. Each tap of `[+]` advances count by 2 with deterministic mechanical precision.	`2 [ENTER] 2 [+] [+] [+] ...` • (100% deterministic stack retention)	**Visual Stepping Ladder:** • Learners see constant waiting on Level Y while Level X climbs in cadence with physical block towers.

3.9 Big Numbers in Nature: Expanding Horizons

Once you master place value bundling, you are ready to explore the vast scale of our physical world:

3.9.1 Real-World Example 1: The Earth-Moon Distance (384,400 km)

The average distance from the Earth to the Moon is 384,400 kilometers. Let us decompose this colossal number using `[PV]`:

1. `[3] [8] [4] [4] [0] [0] [ENTER]`
2. `[1] [0] [0] [0] [0] [0] [PV]` → X = **3** (3 hundred-thousands = 300,000 km).
3. `[1] [0] [0] [0] [0] [PV]` → X = **8** (8 ten-thousands = 80,000 km).
4. `[1] [0] [0] [0] [PV]` → X = **4** (4 thousands = 4,000 km).
5. `[1] [0] [0] [PV]` → X = **4** (4 hundreds = 400 km).

EXPEDITION CHALLENGE:

If an Apollo spacecraft travels at 4,000 km/hour, how many hours does it take to reach the Moon?
Keystrokes: `[3] [8] [4] [4] [0] [0] [ENTER] [4] [0] [0] [0] [÷]` → 96
Result: X = 96.1 hours (about 4 days of spaceflight!).

3.9.2 Real-World Example 2: Human Heartbeats in a Year (42,048,000)

Your heart beats approximately 80 times per minute when you are resting. How many times does the heart beat in an entire year?

- 60 minutes in an hour: 80 × 60 = 4,800 beats/hour.
- 24 hours in a day: 4,800 × 24 = 115,200 beats/day.
- 365 days in a year: 115,200 × 365 = **42,048,000 beats/year**!

Let us calculate this continuously on the SC-6 stack without writing down any scratch paper:

Keystroke	Register T	Register Z	Register Y	Register X
80 `[ENTER]`	0	0	80	80
60 `[×]`	0	0	0	4800
24 `[×]`	0	0	0	115200
365 `[×]`	0	0	0	42048000

Now let's query the Ten-Millions place with `[PV]`:

- Type `[ENTER] [1] [0] [0] [0] [0] [0] [0] [0] [PV]` → X = **4** (4 ten-millions!).
- Type `[1] [0] [0] [0] [0] [0] [0] [PV]` → X = **2** (2 millions!).

3.9.3 Real-World Example 3: Distance to Mars (225,000,000 km)

At its average orbital distance, the planet Mars is approximately 225,000,000 kilometers from Earth.

- Hundreds of Millions place: `225000000 [ENTER] 100000000 [PV]` → X = **2**.
- Tens of Millions place: `10000000 [PV]` → X = **2**.
- Millions place: `1000000 [PV]` → X = **5**.

If a robotic probe travels at 25,000 km/h, how many days will the voyage take?

- Keystrokes: `225000000 [ENTER] 25000 [÷] 24 [÷]` → X = **375 days** (just over 1 year!).

3.9.4 Real-World Example 4: Red Blood Cells in the Human Body (25,000,000,000,000)

An average human body contains approximately 25 trillion red blood cells. In expanded notation: **25,000,000,000,000 = 2 × 10^{13} + 5 × 10^{12}** Decompose on SC-6:

- Ten-trillions place: `25000000000000 [ENTER] 10000000000000 [PV]` → X = **2**.
- Trillions place: `1000000000000 [PV]` → X = **5**.

For Parents & Teachers: Classroom Dialogue Scripts & Misconception Diagnostics

Place Value as a Conceptual Diagnostic: In elementary mathematics education, place value is the foundational diagnostic watershed. When students fail to comprehend bundling and positional notation in early grades, they encounter severe barriers when attempting multi-digit regrouping, long division, and decimal arithmetic.

The SC-6 resolves this disconnect by grounding positional notation in physical geometry: metric base-10 blocks make magnitudes visceral (a thousand-cube possesses tangible heft, whereas unit cubes rest lightly on a fingertip), and the dedicated **`[PV]`** key functions not as a computation solver, but as a structural interrogator. Querying the tens place reveals 2; querying the hundreds place reveals 7. The calculator acts as an interactive analytical lens rather than a black-box oracle.

Resolving Inversion Misconceptions with Visual Sandboxes: Early learners frequently reverse digits—for instance, writing 41 for fourteen because the "four" is heard first. Similarly, the concept that ten individual units can be traded for a single ten-rod often feels like arbitrary symbolism on worksheets. The SC-6 Ten-Frame Studio (**`[FRAME]`**) and Rekenrek Number Rack eliminate this confusion: stepping counters with **`[.]`** until the tenth counter fills the frame visually demonstrates that "a ten is a completed container." Teen numbers are instantly visualized as one full container plus loose individual units, anchoring mental arithmetic in geometric certainty.

Register Architecture of the Place Value Engine: On legacy RPN scientific calculators, extracting a specific digit from an integer required a multi-step sequence involving division, integer truncation, and subtraction:

d = ■ (|Y| / X) ■ - 10 × ■ (|Y| / 10X) ■

Such an approach is cognitively inaccessible to elementary students. The SC-6 implements a dedicated firmware instruction for **`[PV]`**: (1) *Preserved Subject Register*: The subject number parked in Register Y remains unchanged after evaluation. (2) *Stack Lift Suppression*: Stack lift is intentionally suppressed on subsequent numeric entries following **`[PV]`**. (3) *Rapid Multi-Column Interrogation*: The student enters the subject number once, then queries columns (10, 100, 1000, 10000) in rapid succession without stack overflow or losing the subject quantity.

Structural Decompositions in Rapid Mental Math: In competitive mental math sprints and upper-elementary challenges, students learn to isolate positional components directly through **`[PV]`** and visual number-line intervals (**`[f] [LINE]`**) rather than computing lengthy manual algorithms on paper.

Classroom Script 3.1: Bridging Ten with Hungry Frogs

• *Teacher:* "Class, imagine a lily pad pond with two big logs. Each log has room for exactly 10 frogs. Right now, Log 1 has 9 green frogs sitting on it. Log 2 is completely empty."

• *Noah:* "Log 1 is almost full! There's only one spot left!"

• *Teacher:* "Exactly! Now, a family of 6 brown frogs hops into the pond wanting to sit down. How many frogs can hop onto Log 1?"

• *Noah:* "Only 1! Because 9 + 1 = 10."

• *Teacher:* "So Log 1 is now full. How many brown frogs are still looking for a seat?"

• *Noah:* "We started with 6. If 1 sat on Log 1, then 6 - 1 = 5 frogs are left."

• *Teacher:* "Where do those 5 frogs go?"

• *Noah:* "Onto Log 2!"

• *Teacher:* "So how many frogs total?"

• *Noah:* "One full ten-log plus 5 frogs makes 15 frogs!"

• *Teacher:* "Look at your SC-6 Ten-Frame screen: `9 [⊠] 1 [+] 5 [+]`. What do you see?"

• *Noah:* "Frame 1 has 10 dots, Frame 2 has 5 dots, and X = 15! It matches the frogs exactly!"

Classroom Script 3.2: The Mystery of the Zero in 4,005

• *Liam:* "Teacher, on my worksheet I had to write 'four thousand five'. I wrote 45 because zero means nothing, so I didn't write it."

• *Teacher:* "Liam, let's test that on the SC-6 Place Value Engine. Type `45 [ENTER] 1000 [PV]`."

• *Liam:* "The screen says X = 0! It says there are zero thousands in 45!"

• *Teacher:* "Right! 45 is just 4 tens and 5 ones. If I offer to pay you $45 or $4,005 for mowing my lawn, which one would you pick?"

• *Liam (grinning):* "Four thousand five dollars, of course!"

• *Teacher:* "Why? What are the zeros doing in 4,005?"

• *Liam:* "They hold the spots! The hundreds spot has 0 flats, and the tens spot has 0 rods, so the 4 can stay in the thousands place!"

• *Teacher:* "Brilliant! The zeros are place holders. Type `4005 [ENTER] 1000 [PV]`. What does X show?"

• *Liam:* "It shows 4! The thousands digit is 4!"

Classroom Script 3.3: Teen Number Reversals (14 vs 41)

• *Teacher:* "Emma, read this number on the desk: 14."

• *Emma:* "Fourteen."

• *Teacher:* "When you write it down, sometimes you write 4 first and get 41. Let's put 14 on our Rekenrek screen: `14 [g] [COUNT]`."

• *Emma:* "Wire 1 has 10 beads slid to the left. Wire 2 has 4 beads."

• *Teacher:* "Which wire has more beads?"

• *Emma:* "Wire 1! It has ten beads!"

• *Teacher:* "And which digit represents that ten?"

• *Emma:* "The 1! Because it's 1 ten!"

• *Teacher:* "So the 1 must come FIRST, on the left! 1 ten and 4 ones. If you wrote 41, how many tens would that be?"

• *Emma:* "Four tens! That would be forty-one!"

• *Teacher:* "Exactly. The ten always leads the march!"

Classroom Script 3.4: Why Did My Step Counter Stop?

• *Lucas:* "Teacher, I was doing the step counter in 4-stack mode. I pressed `1 [ENTER] 1 [+]` and it showed 2. But when I pressed **`[+]`** again, it stayed at 2! It didn't climb to 3!"

• *Teacher:* "Let's look at the elevator floors, Lucas. In 4-stack mode, when you pressed **`[+]`**, Floor 2 (Y) combined with Floor 1 (X) to make 2. But what was waiting on Floor 3 (Z) to drop down?"

• *Lucas:* "Nothing was there! Floor 3 was 0!"

• *Teacher:* "So when Floor 3 dropped to Floor 2, it dropped a 0. What is 2 + 0?"

• *Lucas:* "Two! That's why it didn't change!"

• *Teacher:* "To make the 1 permanent on every floor, what superpower key do we use?"

• *Lucas:* "Superpower 1! **`[g] [REP]`**!"

• *Teacher:* "Press `1 [g] [REP] [+] [+] [+]`. What happens now?"

• *Lucas:* "2, 3, 4, 5, 6! It's climbing like a rocket!"

For Parents & Teachers: Counting & Place Value Diagnostic Playbook

The following diagnostic table equips educators and parents with rapid detection clues and exact remediation steps for common early numeracy stumbling blocks:

| Student Mistake / Symptom | Cognitive Cause | Remediation Action |

| :--- | :--- | :--- |

| 1. In Ten-Frame mode, typing **[FRAME]** shows empty frame | Forgot to enter initial quantity. | Load the number FIRST, then press **[FRAME]**. |

| 2. Step counter in 4-stack adds `0` instead of constant | Stack dropped `0` from empty `Z` to `Y`. | Switch to 2-Stack (`2-LV`) or use **[g] [REP]**. |

| 3. Place Value **[PV]** query returns error | Entered query place before subject number. | Enter number, press **[ENTER]**, then query place value. |

| 4. Ten-frame step key **[.]** adds decimal point to number | Pressed digit key while typing digits. | Tap **[.]** alone to step the counter by 1. |

| 5. Child writes `41` for teen number fourteen | Auditory reversal of "four" in 14. | Use the Rekenrek screen to show 1 ten + 4 ones. |

| 6. Number line arc jumps backward on addition | Typed second number before starting number. | Enter start coordinate first, then **[ENTER]**, then jump. |

| 7. Big number heartbeats overwritten during multiply | Pressed **[C]** between multi-step factors. | Let the stack lift! Do not press Clear between **[×]** steps! |

| 8. Querying tens place of `405` gives `0` | Confused digit with total magnitude. | Query `10` → shows `0`: explain that zero is a placeholder! |

| 9. Worried returning from sandbox to **[NUM]** lost data | Assumed mode switch clears the stack. | Press **[NUM]**: the operational stack is preserved! |

| 10. Querying hundredths shows `0` on $345.67 | Used `100` instead of `.01` for decimal place value. | Use `.01` for hundredths (1/100); `100` queries hundreds! |

3.10 Story-Driven Problem Expeditions (45 Elementary Reference Scenarios)

Rather than completing isolated rote worksheets, you join four mathematical expeditions that traverse human history—from ancient market stalls to deep space observatories.

Hands-On Studio Proof: Blocks → Calculator

Step 1 (Physical Concrete Intuition): Take your 3D-printed Ten-Frame tray and counting tokens. Drop 8 red tokens into the first tray. Observe the 2 empty pockets. Take 5 gold tokens: place 2 into the empty pockets to complete the first ten-frame, and place the remaining 3 tokens into the second tray. Touch the full tray: *1 Ten*. Touch the second tray: *3 Ones*. Total: 13.

Step 2 (The Representational Bridge): Tap **[FRAME]** on your SC-6 to open the Ten-Frame sandbox. Enter `8 [.] 5 [+]`. Watch the dot-matrix LCD animate the exact bridging maneuver: 2 dots migrate to fill the first 10-grid, while 3 dots settle into the second grid, displaying `Y: 10 | X: 3`!

Step 3 (Scaling on the Calculator): Return to baseline with **[NUM]**. Now scale from tabletop tokens to cargo shipping: type `800 [ENTER] 500 [+]` → `1300`! The physical ten-frame intuition scales seamlessly to thousands and millions without pen or paper.

3.10.1 Expedition 1: The Great Ancient Bazaar (Problems 3.1–3.8)

Mission Briefing: You are an apprentice merchant in an ancient caravan bazaar. Traders arrive with sacks of fragrant cloves, bags of dates, and clay pottery beads. Using your ten-frame trays and the SC-6, you must recognize inventory batches at a glance, combine spice bushels across decade boundaries, and balance accounts with speed and poise.

Problem 3.1: Seeing the Five-Anchor at a Glance (5 + 3 = 8)

In your spice merchant stall, you arrange 5 terracotta jars of ground golden turmeric on the upper shelf in the morning. An afternoon caravan camel arrives with 3 additional jars of fragrant cinnamon. How many spice jars do you have in total to sell to travelers? With your manipulative kit, Frame 1 fills top row (5 jars), bottom row adds 3 jars. On your SC-6, key in `5 [ENTER] 3 [+] → 8`.

Running this sequence → (T=0, Z=0, Y=0, X=8) to fuse both spice groups into 8 on the ground floor.

Top row full (5), bottom row has 3. Total X = 8.

Problem 3.2: Bridging Ten (9 + 4 = 13)

A textile trader brings 9 rolls of deep indigo linen into the bazaar pavilion. A weaver from Tyre delivers 4 rolls of vibrant crimson silk. How many rolls of fine cloth are ready for the marketplace? With your manipulative kit, Frame 1 has 9 counters (1 empty slot). Decompose 4 into 1 + 3 to bridge the ten. On the SC-6 keypad, enter `9 [ENTER] 1 [+] 3 [+] → 13`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
9 **[ENTER]**	0	0	9	9	Load 9 rolls of indigo linen into X and duplicate to Mezzanine Y
1 **[+]**	0	0	0	10	Bridge to ten; Frame 1 completely fills and flashes (X = 10)
3 **[+]**	0	0	0	13	Combine ten and three; Frame 2 holds 3 dots, giving total X = 13 rolls

Frame 1 completes at 10 (flashes). Frame 2 holds 3. X = 13.

Problem 3.3: Bridging Ten (8 + 7 = 15)

An olive grove caravan unloads 8 glazed clay amphorae filled with pressed olive oil and 7 stone flagons of pure rosewater. How many vessels are set out on the tasting table? With your manipulative kit, Frame 1 has 8 counters (2 empty pockets). Decompose 7 into 2 + 5.

Turning to your SC-6, key in `8 [ENTER] 2 [+] 5 [+] → 15 (T=0, Z=0, Y=0, X=15)`, bridging to ten with 2 rosewater flagons before adding the remaining 5. X = 15. Frame 1 has 10; Frame 2 has a full top row of 5.

Problem 3.4: Bridging Ten (7 + 6 = 13)

A jeweler displays 7 polished deep-blue lapis lazuli gemstones on a velvet cloth. A gemstone merchant brings 6 fiery carnelian stones to add to the collection. How many precious gems are presented for trade? With your manipulative kit, Frame 1 has 7 counters (3 empty slots). Decompose 6 into 3 + 3. With your SC-6 ready, enter `7 [ENTER] 3 [+] 3 [+] → 13`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
7 **[ENTER]**	0	0	7	7	Load 7 lapis lazuli gems into X and duplicate to Mezzanine Y
3 **[+]**	0	0	0	10	Bridge to ten; Frame 1 completely fills (X = 10)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
3 [+]	0	0	0	13	Combine ten and three; Frame 2 holds 3 dots, giving total X = 13 gems

X = 13. Frame 1 has 10; Frame 2 has 3.

Problem 3.5: Making Twenty (16 + 4 = 20)

A coin changer counts 16 engraved bronze coins resting across two ten-frame money trays. How many additional bronze coins are needed to fill both ten-frame trays to an even twenty coins? With your manipulative kit, Frame 1 is full (10). Frame 2 has 6 counters (4 empty pockets).

Step over to your SC-6 and key in `16 [ENTER] 4 [+]` → `20 (T=0, Z=0, Y=0, X=20)`. Completely filling both ten-frame trays to an even decade. Both frames completely full. X = 20.

Problem 3.6: Subtraction on the Ten-Frame (10 - 4 = 6)

A fruit merchant's wicker crate holds a full harvest of 10 ripe sweet pomegranates. A traveling family purchases 4 pomegranates for their desert journey. How many pomegranates remain in the crate? With your manipulative kit, full Frame 1 (10). Remove 4 counters.

Now compute it on your SC-6: `10 [ENTER] 4 [-]` → `6 (T=0, Z=0, Y=0, X=6)`, leaving 6 sweet pomegranates in the harvest crate.

Top row (5) plus 1 counter on bottom row remain. X = 6.

Problem 3.7: Subtraction Across Ten (14 - 6 = 8)

An apothecary carries 14 glass vials of aromatic cedar and myrrh perfume oils. A palace messenger purchases 6 vials for evening ceremonies. How many perfume vials remain in the wooden apothecary chest? With your manipulative kit, remove 4 from Frame 2 (leaving 10), then remove 2 from Frame 1. Run the sequence on your SC-6: `14 [ENTER] 4 [-] 2 [-]` → `8`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
14 [ENTER]	0	0	14	14	Load 14 perfume vials into X and duplicate to Mezzanine Y
4 [-]	0	0	0	10	First subtraction empties Frame 2, leaving clean benchmark ten (X = 10)
2 [-]	0	0	0	8	Second subtraction takes 2 from Frame 1, leaving 8 vials in stock (X = 8)

X = 8. Frame 1 has 8 counters (full top row of 5 and 3 on bottom).

Problem 3.8: Bridging Ten (9 + 8 = 17)

At the caravan weigh station, a scale master inspects 9 burlap sacks of golden saffron threads and 8 sacks of green cardamom pods. What is the total count of spice sacks ready for the camel train? With your manipulative kit, decompose 8 into 1 + 7 to bridge ten.

Verify the calculation on your SC-6: `9 [ENTER] 1 [+] 7 [+]` → `17 (T=0, Z=0, Y=0, X=17)`, completing the first frame with 1 sack and landing 7 sacks in the second frame. X = 17. Frame 1 has 10; Frame 2 has 7.

3.10.2 Expedition 2: The Abacus Merchant's Caravan (Problems 3.9–3.16)

Mission Briefing: Traveling along the Silk Road, your caravan tallies silk bolts, ceramic jars, spice bundles, camel packs, and cast-bronze weights using the European Rekenrek Number Rack. You slide red and white bead clusters across dual rails, mastering five-anchors, teen numbers, and double combinations.

Problem 3.9: Building Seventeen (10 + 7 = 17)

Your caravan reaches the oasis trading post of Dunhuang. The master merchant asks you to tally a precious shipment of 17 bolts of shimmering damask silk using the Rekenrek Number Rack. How do you slide the beads to show 10 on the top rail and 7 on the bottom rail? With your manipulative kit, on your Number Rack, slide all 10 beads on Rail 1 (5 red, 5 white) to represent 1 full ten-pack. On Rail 2, slide 7 beads (5 red, 2 white). Touch both rails: 10 + 7 = 17.

Test this directly on your SC-6: `10 [ENTER] 7 [+]` → `17 (T=0, Z=0, Y=0, X=17)`. Press **`[g] [COUNT]`** to display 17 on the Number Rack (Rail 1 full with 10, Rail 2 with 7). Exactly 1 full wire of 10 and 7 beads on wire 2. Total X = 17.

Problem 3.10: Adding on the Rekenrek (12 + 5 = 17)

In the caravan storage tent, you have 12 glazed ceramic jars of rare pistachio oil already strapped to the pack saddles. A local potter delivers 5 more ceramic jars to complete the consignment. How many ceramic jars are ready for the crossing? With your manipulative kit, set 12 beads on your Number Rack (10 on Rail 1, 2 red on Rail 2). Slide 5 more red beads on Rail 2 to join the 2 white beads, completing the 5-bead red cluster plus 2 white (2 + 5 = 7).

Bring this to the SC-6 stack: `12 [ENTER] 5 [+]` → `17 (T=0, Z=0, Y=0, X=17)`, combining the ceramic jar consignments into a single total. Wire 2 red group completes (5) plus 2 white beads. X = 17.

Problem 3.11: Subtraction on the Rekenrek (18 - 5 = 13)

Your lead camel carries 18 bundles of dried cinnamon bark across two pannier baskets. At a desert mountain outpost, the caravan master trades 5 spice bundles for fresh spring water. How many spice bundles remain in the camel's pack? With your manipulative kit, start with 18 beads active on the Number Rack (10 on Rail 1, 8 on Rail 2: 5 red and 3 white). Slide the 5 red beads on Rail 2 back to the resting side, leaving 3 white beads on Rail 2 and all 10 on Rail 1 (10 + 3 = 13).

On your SC-6, enter `18 [ENTER] 5 [-]` → `13 (T=0, Z=0, Y=0, X=13)`, subtracting the traded spice bundles from the pack. X = 13 (10 on Wire 1, 3 on Wire 2).

Problem 3.12: Decomposing Fifteen (15 = 10 + 5)

A desert merchant offers 15 cast-bronze trade weights for bartering at the caravan gate. To verify the weight inventory, the caravan master asks you to decompose 15 into 1 full bundle of ten and 5 single weights using the Rekenrek. With your manipulative kit, slide 10 beads across Rail 1 (5 red, 5 white) to lock in 1 full ten. On Rail 2, slide exactly the 5 red beads across. Observe: 1 full rail of ten plus 1 red cluster of five proves that 15 = 10 + 5.

Execute the sequence on your SC-6: `15 [ENTER] 10 [-] → 5 (T=0, Z=0, Y=0, X=5)`, proving that 15 decomposes into 1 full ten-rail and 5 red beads. Wire 1 has 10; Wire 2 has exactly the 5 red beads active. Total X = 15.

Problem 3.13: Doubles on the Rekenrek (6 + 6 = 12)

To balance the loads on a pack camel, you strap 6 heavy terracotta amphorae of sesame oil onto the left side pack and 6 matching amphorae onto the right side pack. How many amphorae does the camel carry in total? With your manipulative kit, slide 6 beads on Rail 1 (5 red, 1 white) and 6 beads on Rail 2 (5 red, 1 white). Group the 5 red beads from each rail together (5 + 5 = 10), then combine the two white beads (1 + 1 = 2). 10 + 2 = 12! On your SC-6, key in `6 [ENTER] 6 [+] → 12`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
6 **[ENTER]**	0	0	6	6	Enter 6 left-side amphorae into X and duplicate to Mezzanine Y
6 **[+]**	0	0	0	12	Add double quantities; 6 + 6 = 12 amphorae forms in Register X

X = 12. 5 red on Wire 1 + 5 red on Wire 2 = 10 red beads, plus 2 white beads!

Problem 3.14: Doubles Plus One (7 + 8 = 15)

Two caravan camel teams transport bundles of raw mulberry silk. Team A packs 7 silk bundles, and Team B packs 8 silk bundles. Using the doubles-plus-one strategy (7 + 7 + 1), calculate the total silk bundle count. With your manipulative kit, slide 7 beads on Rail 1 (5 red, 2 white). Slide 8 beads on Rail 2 (5 red, 3 white). Notice the double 7 (7 + 7 = 14) plus the 1 extra white bead on Rail 2 (14 + 1 = 15). On the SC-6 keypad, enter `7 [ENTER] 7 [+] 1 [+] → 15`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
7 **[ENTER]**	0	0	7	7	Load Team A's 7 silk bundles into X and duplicate to Mezzanine Y
7 **[+]**	0	0	0	14	Add the known double; 7 + 7 = 14 silk bundles forms in Register X
1 **[+]**	0	0	0	15	Add extra bundle; total reaches 15 silk bundles across both teams (X = 15)

X = 15. Double 7 + 7 = 14, plus 1 equals 15.

Problem 3.15: Teen Subtraction (19 - 8 = 11)

A merchant's caravan crate contains 19 hand-painted ceramic spice bowls ready for market. During an afternoon trading stop at the caravanserai, buyers select and purchase 8 ceramic bowls. How many ceramic bowls remain packed in the crate? With your manipulative kit, display 19 beads on your Number Rack (10 on Rail 1, 9 on Rail 2: 5 red and 4 white). Slide 8 beads on Rail 2 back to the resting position (5 red and 3 white), leaving 1 white bead on Rail 2 and all 10 on Rail 1 (10 + 1 = 11).

Turning to your SC-6, key in `19 [ENTER] 8 [-]` → `11 (T=0, Z=0, Y=0, X=11)`, shedding 8 beads from Rail 2 to leave 11 ceramic spice bowls.

10 on Wire 1, 1 on Wire 2. Total X = 11.

Problem 3.16: Rekenrek Full Rack Anchor (20 - 7 = 13)

A master caravan ledger rack holds 20 bronze weight ingots across both rails (10 on Rail 1, 10 on Rail 2). To counterbalance a large trade scale for a sack of raw lapis lazuli, the scale master removes 7 bronze weights. How many bronze weights remain on the ledger rack? With your manipulative kit, start with all 20 beads active on the 20-rack (both rails fully shifted left). Slide 7 beads on Rail 2 back to the right (5 white and 2 red). Count the remaining beads: Rail 1 still has 10, and Rail 2 has 3 red beads active (10 + 3 = 13).

With your SC-6 ready, enter `20 [ENTER] 7 [-]` → `13 (T=0, Z=0, Y=0, X=13)`, subtracting 7 weights to leave 13 bronze weights on the ledger rack. X = 13. Full top rail of 10 plus 3 beads on bottom rail.

3.10.3 Expedition 3: The Kangaroo Trailblazer (Problems 3.17–3.24)

Mission Briefing: As an expedition scout mapping the outback desert trail, you track distances between desert watering holes, red sand dunes, and eucalyptus landmarks. Using the SC-6 Open Number Line, you calculate forward distance hops, measure relative gap distances, and navigate decade crossing points.

Problem 3.17: Forward Jump (14 + 8 = 22)

An Australian red kangaroo rests at survey marker 14 near a dry creek bed. In search of sweet desert grasses after a rainfall, the kangaroo bounds forward 8 kilometers across the red sand plains. At which survey marker does the kangaroo arrive? With your manipulative kit, on your Open Number Line, place your marker at tick 14. Draw a smooth forward arc spanning 8 units across decade tick 20, landing squarely at coordinate 22. Label the leap `+8`.

Step over to your SC-6 and key in `14 [ENTER] 8 [+]` → `22 (T=0, Z=0, Y=0, X=22)`, leaping forward across decade marker 20 to land on coordinate 22.

Jump arc displayed from 14 to 22. Total X = 22.

Problem 3.18: Backward Jump (23 - 7 = 16)

An expedition scout stands atop a towering red sand dune at elevation marker 23 meters. To reach a shaded eucalyptus grove in the swale below, the scout hikes downward 7 meters. What is the scout's new elevation marker on the dune slope? With your manipulative kit, on your Open Number Line, pin the starting point at tick 23. Draw a backward arc leaping 7 units to the left, crossing benchmark 20 to land on tick 16. Label the arc `-7`.

Now compute it on your SC-6: `23 [ENTER] 7 [-]` → `16 (T=0, Z=0, Y=0, X=16)`, descending across decade 20 to eucalyptus grove marker 16.

Backward arc lands on 16. Total X = 16.

Problem 3.19: Multi-Hop Addition (18 + 5 + 7 = 30)

An outback survey party maps a trek across the desert: they march 18 kilometers from base camp to a spinifex ridge, then 5 kilometers to an ancient eucalyptus landmark, and finally 7 kilometers to an emerald billabong watering hole. What is the total trail distance mapped? With your manipulative kit, on your Open Number Line, start at 18. Draw a first forward arc of +5 landing on tick 23, then a second forward arc of +7 landing on round decade tick 30. Run the sequence on your SC-6: `18 [ENTER] 5 [+] 7 [+]` → `30`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
18 [ENTER]	0	0	18	18	Pin spinifex ridge distance 18 into X and duplicate to Mezzanine Y
5 [+]	0	0	0	23	First hop completes; first arc lands on landmark marker 23 (X = 23)
7 [+]	0	0	0	30	Final hop completes; second arc lands cleanly on milestone 30 (X = 30)

Consecutive arcs: 18 → 23 → 30. Total X = 30.

Problem 3.20: Finding Distance / Difference (42 - 15 = 27)

On your outback expedition survey map, a prominent Ghost Gum tree landmark stands at trail coordinate 15 kilometers, while the Red Sand Gap escarpment is located at coordinate 42 kilometers. What is the total trail distance between these two desert waypoints? With your manipulative kit, on your Open Number Line, plot markers at 15 and 42. Measure the distance interval between them by jumping from 15 to 20 (+5), 20 to 40 (+20), and 40 to 42 (+2): 5 + 20 + 2 = 27 kilometers.

Verify the calculation on your SC-6: `42 [ENTER] 15 [-]` → `27 (T=0, Z=0, Y=0, X=27)`, measuring the trail interval of 27 km between waypoints. X = 27 kilometers difference between waypoints.

Problem 3.21: Bridging Decade on Number Line (35 + 18 = 53)

An expedition survey rover travels 35 kilometers past a dry salt lake bed in the morning, then pushes another 18 kilometers through red sand dunes in the afternoon to reach a fresh billabong. What is the total odometer distance logged for the day? With your manipulative kit, on your Open Number Line, start at tick 35. Decompose 18 into +5 (reaching benchmark 40) and +13 (jumping to 53). Draw the forward arc spanning across decades 40 and 50 to land at 53.

Test this directly on your SC-6: `35 [ENTER] 18 [+]` → `53 (T=0, Z=0, Y=0, X=53)`, bridging decades 40 and 50 to log 53 km.

Arc crosses tick 40 and 50. Total X = 53.

Problem 3.22: Backward Decade Crossing (50 - 24 = 26)

The expedition party carries a main reservoir tank filled with 50 liters of fresh water at the start of a multi-day desert crossing. Over two days of arid hiking, the party uses 24 liters for drinking and cooking. How many liters of drinking water remain in the reservoir tank? With your manipulative kit, on your Open Number Line, locate round milestone 50. Decompose 24 into two backward leaps: jump back 20 to reach benchmark 30, then jump back 4 to land on coordinate 26.

Bring this to the SC-6 stack: `50 [ENTER] 24 [-] → 26 (T=0, Z=0, Y=0, X=26)`, crossing decade 30 to leave 26 liters in the reservoir.

Backward leap crosses decade 30. Remaining water X = 26.

Problem 3.23: Double Hop (28 + 36 = 64)

An expedition field botanist surveys native trees across two desert exploration zones: 28 marked river red gums along the northern dry creek bed and 36 marked ghost gum trees across the southern rocky gorge. How many native desert trees are cataloged in total? With your manipulative kit, on your Open Number Line, start at tick 28. Jump forward +2 to bridge to round decade 30, then jump +34 to land at coordinate 64 (28 + 2 + 34 = 64).

On your SC-6, enter `28 [ENTER] 36 [+] → 64 (T=0, Z=0, Y=0, X=64)`, leaping across decades 30, 40, 50, and 60 to catalog 64 native trees.

Multi-decade leap lands on 64. Total X = 64.

Problem 3.24: Subtraction Check (63 - 27 = 36)

An outback cartographer surveys the distance between desert escarpment marker 63 kilometers and dry riverbed base camp marker 27 kilometers. To independently verify the survey traverse, calculate the distance difference by jumping backward on the Number Line. With your manipulative kit, on your Open Number Line, locate milestone 63. Decompose 27 into -20 (landing at 43), -3 (reaching benchmark 40), and -4 (landing at 36). Verify that the backward jump lands squarely on tick 36 (63 - 27 = 36). Execute the sequence on your SC-6: `63 [ENTER] 27 [-] → 36`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
63 **[ENTER]**	0	0	63	63	Pin escarpment marker 63 into Register X and duplicate to Mezzanine Y
27 **[-]**	0	0	0	36	Leap backward by 27 units; arc lands squarely on tick 36 (X = 36)

Backward arc lands on 36. Total X = 36.

3.10.4 Expedition 4: The Cosmic Scale Observatory (Problems 3.25–3.45)

Mission Briefing: Stepping into the astronomical observatory, your mission expands from tabletop counters to the vast architecture of the cosmos. You use rhythmic step-counting ladders, place value decomposition **[PV]**, and expanded notation to measure calendar cycles, count human heartbeats across decades, and calculate interplanetary distances to the Moon and Voyager 1.

Part 1: Step Counter Ladders & Cadence Drills (Problems 3.25–3.30)

Problem 3.25: Twos Ladder (Even Numbers to 20)

In the observatory optics lab, technicians calibrate sensor pairs across the telescope array by counting by 2s up to 20. In 2-Stack mode, Register Y preserves the step constant 2.0 across successive additions, allowing you to establish a

steady counting cadence without re-entering the operand. On your SC-6, configure `[g] [FLAGS] 2-LV`. Type `2 [ENTER] 2 [+] [+] [+] [+] [+] [+] [+] [+] [+]` → `4`.

In 2-Stack mode (`[g] [FLAGS] 2-LV`), tap `2 [ENTER] 2 [+]` → (T=0, Z=0, Y=2, X=4). Rhythmic taps of **[+]** advance through 6, 8, 10, up to 20 while Register Y preserves the constant 2.

Register State: Register Y preserves constant 2.0 in 2-LV mode.

Problem 3.26: Fives Ladder (Nickel Coins to 50 Cents)

During an afternoon observatory break, student astronomers tally 5-cent tokens for the solar telescope viewing carousel up to 50 cents. In 2-Stack mode, tapping **[+]** rhythmically advances the total on the stack as each nickel token drops into place. On your SC-6 in 2-Stack mode, key in `5 [ENTER] 5 [+]` → `10`.

In 2-Stack mode, run this sequence → (T=0, Z=0, Y=5, X=10). Successive taps of **[+]** slide additional 5-bead groups on the Number Rack, advancing by 5-cent nickels through 15, 20, 25, up to 50 cents.

10 nickels equal 50 cents.

Problem 3.27: Tens Ladder (Dime Coins to 100 Cents)

To fund specialized camera filters, the student astronomy club bundles 10-cent donation coins up to 100 cents (one full dollar). In 2-Stack mode, each press of **[+]** stacks another dime until 10 ten-rods assemble into a solid 100-flat. On your SC-6 in 2-Stack mode, key in `10 [ENTER] 10 [+]` → `20`.

In 2-Stack mode, run this sequence → (T=0, Z=0, Y=10, X=20). Successive taps of **[+]** advance by 10-cent dimes until 10 rods assemble into a complete 100-flat (X = 100).

One dollar achieved!

Problem 3.28: Countdown from 50 by 5s

Before launching an atmospheric weather balloon from the observatory roof, the flight controller initiates a countdown from 50 down to 0 by 5s. Each tap of `5 [-]` steps downward in steady cadence until terminal zero is reached. On the SC-6 keypad, enter `50 [ENTER] 5 [-] 5 [-] 5 [-] 5 [-] 5 [-] 5 [-] 5 [-] 5 [-] 5 [-] 5 [-]` → `0`.

Tap `50 [ENTER] 5 [-]` → (T=0, Z=0, Y=0, X=45). Nine more `5 [-]` steps count down through 40, 35, 30, ..., 0 to reach terminal zero (X = 0).

Terminal zero reached safely.

Problem 3.29: Threes Ladder in 4-Stack Mode with [g] [REP]

Inside the planetary motion lab, you track orbital resonances across triplets of moons by generating multiples of 3 in 4-stack mode. Pressing Superpower 1 (**[g] [REP]**) primes all four registers with 3, so repeated taps of **[+]** pull fresh 3s automatically from the top of the elevator stack. On your SC-6, in 4-Stack mode, key in `3 [g] [REP] [+] [+] [+]`.

Stack Trace Table:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
3 [g] [REP]	3	3	3	3	Superpower 1 replicates 3 across all registers (T, Z, Y, X)
[+]	3	3	3	6	First addition yields 6; register T preserves constant 3
[+]	3	3	3	9	Stack drop supplies 3 automatically; total reaches 9
[+]	3	3	3	12	Constant replicates from top of stack (X = 12)

Times table for 3 generated effortlessly.

Problem 3.30: Sevens Ladder in 4-Stack Mode with [g] [REP]

Observatory observation schedules are planned in 7-day weekly blocks. In 4-Stack mode, replicate 7 across the stack with [g] [REP] and advance through 7 weeks of telescope rotation schedules. On your SC-6, in 4-Stack mode, key in 7 [g] [REP] [+] [+].

In 4-Stack mode, tap 7 [g] [REP] [+] → (T=7, Z=7, Y=7, X=14). Successive taps of [+] pull constant 7 from the top of the stack, climbing through 21, 28, 35, 42, to 49 days.

7 weeks = 49 days.

Part 2: Place Value Decomposition & Expanded Notation (Problems 3.31–3.38)

Problem 3.31: Expanded Sum (300 + 60 + 5 = 365)

To calibrate the observatory's planetary ephemeris, you reconstruct the 365 days of Earth's solar orbit by accumulating its expanded place-value parts: 3 hundreds, 6 tens, and 5 ones. In the Place Value Studio, place 3 hundred-flats (300), 6 ten-rods (60), and 5 unit cubes (5) on your workstation mat to model each component. Turning to your SC-6, key in 300 [ENTER] 60 [+] 5 [+] → 365.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
300 [ENTER]	0	0	300	300	Enter 3 hundreds flats into stack
60 [+]	0	0	0	360	Add 6 ten-rods; subtotal accumulates to 360
5 [+]	0	0	0	365	Add 5 unit cubes; full expanded sum reaches 365

Hundreds = 3, Tens = 6, Ones = 5. Expanded: 300 + 60 + 5 = 365.

Problem 3.32: Historic Year Expanded Sum (1,492)

In the history of celestial navigation, the year 1,492 marked a watershed in transatlantic exploration. Reconstruct this four-digit historical date on the SC-6 stack by summing its constituent place-value blocks: 1 thousand, 4 hundreds, 9 tens, and 2 ones. Lay out 1 thousand-cube (1,000), 4 hundred-flats (400), 9 ten-rods (90), and 2 unit cubes (2). With your SC-6 ready, enter 1000 [ENTER] 400 [+] 90 [+] 2 [+] → 1492.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
1000 [ENTER]	0	0	1000	1000	Enter 1 thousand-cube into stack
400 [+]	0	0	0	1400	Add 4 hundred-flats; subtotal reaches 1400
90 [+]	0	0	0	1490	Add 9 ten-rods; subtotal reaches 1490
2 [+]	0	0	0	1492	Add 2 unit cubes; full historical year reaches 1492

Results: Thousands = 1, Hundreds = 4, Tens = 9, Ones = 2. Expanded: 1,000 + 400 + 90 + 2 = 1,492.

Problem 3.33: Zero as a Placeholder (8,000 + 40 = 8,040)

A deep-space radio telescope logs 8,040 celestial telemetry pulses. Reconstruct 8,040 on the stack from 8 thousands and 4 tens, observing how the empty hundreds and ones positions function as essential zero placeholders.

Step over to your SC-6 and key in `8000 [ENTER] 40 [+]` → `8040 (T=0, Z=0, Y=0, X=8040)`, verifying that the zero hundreds slot leaves a clean placeholder in 8,040.

Results: Thousands (1000): 8, Hundreds (100): 0, Tens (10): 4, Ones (1): 0.

Problem 3.34: Five-Digit Expanded Sum (98,765)

The observatory library archives 98,765 photographic star plates collected over a century. Reconstruct this descending five-digit sequence by sequentially accumulating each positional tier from ten-thousands down to individual ones. With your manipulative kit, with your physical Base-10 kit, you can model place-value blocks up to thousand-cubes (1,000). For ten-thousands and beyond, your StackCalc carries the exact same positional structure forward into astronomical numbers without needing warehouse-sized plastic blocks! Now compute it on your SC-6: `90000 [ENTER] 8000 [+] 700 [+] 60 [+] 5 [+]` → `98765`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
90000 [ENTER]	0	0	90000	90000	Enter 9 ten-thousands tier into stack
8000 [+]	0	0	0	98000	Add 8 thousands tier (X = 98000)
700 [+]	0	0	0	98700	Add 7 hundred-flats (X = 98700)
60 [+]	0	0	0	98760	Add 6 ten-rods (X = 98760)
5 [+]	0	0	0	98765	Add 5 unit cubes; completes 98,765

Results: Ten-Thousands = 9, Thousands = 8, Hundreds = 7, Tens = 6, Ones = 5.

Problem 3.35: Decimal Tenths and Hundredths (345 + 0.6 + 0.07 = 345.67)

A high-precision optical micrometer measures a telescope focal length of 345.67 mm. Reconstruct this precision dimension by combining the whole-number baseline with decimal tenths (0.6) and hundredths (0.07).

Run the sequence on your SC-6: `345 [ENTER] 0.6 [+] 0.07 [+]` → `345.67 (T=0, Z=0, Y=0, X=345.67)`, reconstructing whole units, tenths, and hundredths into 345.67.

Tenths place = 6, Hundredths place = 7.

Problem 3.36: Small Currency Decimals (0.40 + 0.07 = 0.47)

In the observatory gift shop, an astronomy mission patch costs 47 cents. Decompose this value into 4 dimes (0.40) and 7 pennies (0.07) to see how decimal places align with physical coins.

Verify the calculation on your SC-6: `0.40 [ENTER] 0.07 [+]` → `0.47 (T=0, Z=0, Y=0, X=0.47)`, combining 4 dimes and 7 pennies into $0.47.

Results: Dimes (Tenths) = 4, Pennies (Hundredths) = 7.

Problem 3.37: Large Thousand-Block Count (10,000 + 2,500 = 12,500)

The civic planetarium and observatory amphitheater seats 10,000 guests in the outdoor bowl and 2,500 in the indoor dome. Combine these place-value blocks on the stack to find the total complex seating capacity.

Test this directly on your SC-6: `10000 [ENTER] 2500 [+]` → `12500 (T=0, Z=0, Y=0, X=12500)`, combining grandstand and concourse blocks to total 12,500 seats.

Results: Ten-thousands = 1, Thousands = 2.

Problem 3.38: Hundred-Thousands Place (400,000 + 50,000 + 200 = 450,200)

A regional astronomy festival attracts visitors across three metropolitan districts totaling 450,200 citizens. Reconstruct this regional population count on the stack from 4 hundred-thousands, 5 ten-thousands, and 2 hundreds.

Bring this to the SC-6 stack: `400000 [ENTER] 50000 [+] 200 [+]` → `450200 (T=0, Z=0, Y=0, X=450200)`, combining regional census population blocks into 450,200.

Results: Hundred-thousands = 4, Ten-thousands = 5, Hundreds = 2.

Part 3: Big Numbers, STEM Scale & Multi-Step Challenges (Problems 3.39–3.45)

Problem 3.39: Space Flight to the Moon (384,400 km)

The average distance from Earth's launch pad to the lunar surface is 384,400 km. Decompose this lunar trajectory across positional tiers using `[PV]`. If a spacecraft cruises at 4,000 km/h, calculate total transit flight time. On your SC-6, enter
.

1. Digits: `384400 [ENTER] 100000 [PV] 10000 [PV] 1000 [PV] 100 [PV]`
2. Travel time: `384400 [ENTER] 4000 [÷]` → `96.1`

Running this sequence → (T=0, Z=0, Y=0, X=96.1), calculating 96.1 transit hours (≈ 4 days) to reach the Moon.

Result: X = 96.1 hours (≈ 4 days).

Problem 3.40: Human Heartbeats in a Decade

At an average resting pulse of 80 beats per minute, a young astronomer's heart beats 42,048,000 times in one year. Scale this biological rhythm across a full 10-year decade and extract the hundred-millions place with **[PV]**.

Execute the sequence on your SC-6: `42048000 [ENTER] 10 [×]` → `420480000 (T=0, Z=0, Y=0, X=420480000)`, scaling annual heartbeats across a 10-year decade to 420,480,000 beats.

Result: X = 420,480,000 beats (420 million beats!).

Decompose Hundred-Millions: **[ENTER] 100000000 [PV]** → X = **4** (4 hundred-million beats).

Problem 3.41: Drops in an Olympic Swimming Pool

The aquatic center cooling reservoir for the supercomputer cluster holds 2,500,000 liters of water. If each liter contains approximately 20,000 drops, compute total water drops in the reservoir and isolate the ten-billions digit.

On your SC-6, key in `2500000 [ENTER] 20000 [×]` → `50000000000 (T=0, Z=0, Y=0, X=50000000000)`, computing 50 billion water drops in the Olympic pool.

Result: X = 50,000,000,000 drops (50 billion drops!).

Decompose Ten-Billions: **[ENTER] 10000000000 [PV]** → X = **5** (5 ten-billion drops).

Problem 3.42: Saturn's Ring Diameter (282,000 km)

Through the observatory's main Cassegrain telescope, Saturn's majestic ring system spans 282,000 kilometers across space. Interrogate this planetary dimension with **[PV]** to extract the hundred-thousands, ten-thousands, and thousands digits. On the SC-6 keypad, enter `282000 [ENTER] 100000 [PV] 10000 [PV] 1000 [PV]` → `2`.

Place Value Interrogation: Park 282,000 in Register Y with `282000 [ENTER]`. Query each decimal place: `100000 [PV]` yields 2 hundred-thousands, `10000 [PV]` yields 8 ten-thousands, and `1000 [PV]` yields 2 thousands (Y: 282000, X: 2).

Results: Hundred-Thousands = 2, Ten-Thousands = 8, Thousands = 2.

Problem 3.43: School District Annual Milk Cartons

An educational outreach program serves 14 elementary school districts. Each district consumes 450 cartons of milk per day over a 180-day academic year. Calculate total annual milk cartons and extract the millions and hundred-thousands place value digits. Turning to your SC-6, key in `14 [ENTER] 450 [×] 180 [×]` → `1134000`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
14 **[ENTER]**	0	0	14	14	Enter number of district schools
450 **[×]**	0	0	0	6300	Daily district consumption (6,300 cartons/day)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
180 [×]	0	0	0	1134000	Scale by 180 school days: 1,134,000 cartons/year

Place Value Extraction: Keying [ENTER] 1000000 [PV] extracts X = **1** (1 million cartons); 100000 [PV] extracts X = **1** (1 hundred-thousand cartons); 10000 [PV] extracts X = **3** (3 ten-thousand cartons); and 1000 [PV] extracts X = **4** (4 thousand cartons).

Problem 3.44: City Public Library Cataloging

The metropolitan science library network houses 875,420 scientific volumes distributed across 12 branch facilities. Extract the ten-thousands digit with [PV] (875420 [ENTER] 10000 [PV] → X = **7**), then compute the average volume share per branch: 875420 [ENTER] 12 [÷] → 72,951.66667.

Running this sequence → (T=0, Z=0, Y=0, X=72951.66667), computing the average branch circulation of 72,951.67 books.

Problem 3.45: Solar Transit Distance of Voyager 1

Deep space exploration probe Voyager 1 hurtles through interstellar space at approximately 17 km/second. Calculate how many kilometers the probe travels in a full 24-hour solar day (86,400 seconds), then systematically decompose the resulting distance with [PV]. With your SC-6 ready, enter 86400 [ENTER] 17 [×] → 1468800.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
86400 [ENTER]	0	0	86400	86400	Enter seconds per solar day into Register Y
17 [×]	0	0	0	1468800	Daily distance covered: 1,468,800 km/day

Result: X = 1,468,800 kilometers/day. **Place Value Decomposition:** Keying [ENTER] 1000000 [PV] extracts X = **1** (1 million km); 100000 [PV] extracts X = **4** (4 hundred-thousand km); 10000 [PV] extracts X = **6** (6 ten-thousand km); 1000 [PV] extracts X = **8** (8 thousand km); and 100 [PV] extracts X = **8** (8 hundred km).

3.11 What You Mastered & Looking Ahead

You have mastered the concrete-to-abstract bridge of early arithmetic:

1. **Concrete to Abstract:** Physical Ten-Frame trays and Rekenrek racks translate directly into the high-contrast vector sandboxes of the SC-6 ([FRAME] , [g] [COUNT]).
2. **Instant Group Recognition:** Anchors of 5 and 10 eliminate finger counting, empowering you to recognize quantities instantly.
3. **Bridging Ten:** Decomposing additions across the decade (8 + 5 = 8 + 2 + 3 = 10 + 3 = 13) provides an intuitive foundation for mental math.
4. **Step Counter Mechanics:** Constant step addition is verified through 2-stack register retention and 4-stack [g] [REP] replication.
5. **Spatial Travel:** The Open Number Line ([f] [LINE]) visualizes arithmetic as forward and backward jump arcs.

6. **Structural Decomposition:** The Place Value Engine (`[PV]`) slices numbers into their constituent powers of ten, preserving Register Y across chained queries.
7. **Cosmic Horizons:** Place value structures scale effortlessly from single unit cubes to solar system distances.

Once you can bundle single units into tens, hundreds, and thousands, what happens when we arrange equal groups into rectangular arrays? In Chapter 4, young Carl Friedrich Gauss shows us how multiplication and skip-counting unlock patterns across the universe!

Whole Number Operations & Skip-Counting Ladders

4.1 How 7-Year-Old Carl Friedrich Gauss Outsmarted His Teacher in 30 Seconds (and Why Multiplication Is a Physical Rectangle, Not a Memorized Song)

In the winter of 1784, inside a cold, dimly lit classroom in Brunswick, Germany, an exasperated schoolmaster named J.G. Büttner slammed his heavy wooden cane onto his oak podium. His classroom of boisterous boys was unruly, and Büttner desired an hour of absolute quiet.

Walking to the blackboard, he chalked an intimidating assignment: *Add every integer from 1 to 100 on your slates.*

1 + 2 + 3 + 4 + 5 + ... + 98 + 99 + 100 = ?

The schoolmaster settled back into his leather armchair, confident that his exhausted pupils would spend the rest of the morning bent over their slates in agonizing manual calculation.

Less than thirty seconds later, a skinny seven-year-old boy named Carl Friedrich Gauss *(Gauss, 1809)* stood up from his rough wooden bench. While his classmates were still desperately computing 1+2=3, 3+3=6, 6+4=10, young Gauss calmly strode to the master's desk, slammed his slate face-down, and proclaimed in his native Low German dialect:

„Ligget se!“ ("There it lies!")

Büttner glared at the boy, certain he was bluffing. But at the end of the hour, when the slates were turned over, all the other boys had scribbled pages of error-riddled arithmetic. Only young Gauss’s slate contained the exact, perfect sum: **5,050**.

How did a seven-year-old outsmart an experienced schoolmaster in thirty seconds?

Gauss did not sing times tables in his head. He did not count on his fingers. He looked at the problem *spatially*. He noticed that the numbers could be folded in half like a piece of paper, pairing the extreme ends into identical sums: **1 + 100 = 101, 2 + 99 = 101, 3 + 98 = 101, ... 50 + 51 = 101**

There were exactly fifty pairs of 101. And fifty groups of 101 is not fifty tedious additions; it is a **geometric rectangle** measuring 50 units wide by 101 units tall: **50 × 101 = 5,050**

This is the great epiphany that conventional elementary school math so often conceals: **multiplication is not an arbitrary song you recite from memory; multiplication is a physical rectangle of space.** When you arrange tiles into equal rows and columns, the product is simply the physical area of the grid.

On the **StackCalc SC-6**, we honor Gauss's spatial insight. Using our physical **144-Tile Four-Color Array Studio**, you prove the commutative, associative, and distributive properties with your hands. And on the calculator keypad, you command three genuine computational superpowers: **Superpower 1 (`[g] [REP]`)** for rhythmic skip-counting ladders, **Superpower 2 (`[g] [÷R]`)** for instant simultaneous quotient and remainder display, and **Superpower 4 (`[f] [LASTX]`)** for self-checking inverse arithmetic without scratch paper.

Chapter Baseline Mode: `[NUM]`

Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Transflective Display

Unlocked Keycaps Ribbon — Grades 2–4 Operations Suite

- **Arithmetic Operators:** `[+]` Addition, `[-]` Subtraction, `[×]` Multiplication, `[÷]` Decimal Division.
- **RPN Superpowers:** `[g]` `[REP]` (Replicate Stack for Skip-Counting), `[g]` `[÷R]` (Quotient & Remainder), `[f]` `[LASTX]` (Self-Checking Inverse Recall).
- **Stack Manipulation:** `[ENTER]`, `[x⇔y]` (Swap Registers X and Y), `[C]` (Clear X), `[<-]` (Backspace).
- **Display Formatting:** `[NUM]` (Whole Number Mode), `[$]` (Currency Mode).



Figure: Field trip bus division: 145 students / 45-seat bus → Quotient 3, Remainder 10

4.2 Concrete Foundation: 24-Tile Four-Color Array Studio & Map Theory

When you first learn multiplication, it might seem like a song to memorize. But multiplication is really **spatial equal groups**, **rectangular area arrays**, and **color-coded maps** you can build with your hands.

Learning Stage	Physical Manipulative Kit	SC-6 Representational Sandbox	Abstract Operational Stack
1. Concrete (Enactive)	24-Tile Four-Color Array Studio	Physical interlocking tiles and 90° array rotation	Tactile array perception
2. Representational (Iconic)	4-Color Quadrant Partitioning & Map Theory	High-contrast LCD vector dot-matrix grid	Visual area model representation
3. Abstract (Symbolic)	Four-Register RPN Stack (T, Z, Y, X)	`Y [ENTER] X [×]` two-number drop	Chained parenthesis-free speed

The StackCalc physical manipulative ecosystem replaces loose single-purpose blocks with the **24-Tile Four-Color Counting & Array Studio**:

24-Tile Four-Color Counting & Array Studio

The physical manipulative studio provides 24 precision interlocking stacking tiles (20.0 × 20.0 × 7.0 mm) arranged across four distinct architectural palettes:

1. **Archival White** (crisp matte finish)
2. **Cobalt Blue** (deep saturated tone)
3. **Radiant Gold** (warm amber tone)
4. **Slate Gray** (technical neutral tone)

with exactly 6 tiles per color (4 × 6 = 24 tiles). Each tile has a 1U visible height (7.0 mm), aligning with the 1/12th Fraction Studio tile so that 12 vertically stacked tiles match the 84.0 mm master datum of the 1-Whole Fraction Tower. Precision slip-fit chamfers allow smooth vertical stacking and planar docking without fatigue or sticking.



Figure: 24-Tile Four-Color Counting & Array Studio in 3x1x13U Gridfinity Bin

4.2.1 The Mathematical Harmony of 4 × 6 = 24

The number 24 divided into 4 colors creates rich mathematical properties for hands-on discovery:

1. **Highly Composite Versatility:** The 24-tile kit factors cleanly into 1 × 24, 2 × 12, 3 × 8, and 4 × 6 rectangular arrays.
2. **Four Complete 2 × 3 Sub-Arrays:** Each individual color contains **6 tiles**, which is both a 2 × 3 rectangular array and a triangular number (1 + 2 + 3 = 6).
3. **Model Small → Scale Big:** By modeling foundational 2 × 3, 3 × 8, and 4 × 6 arrays physically on the desk, you build concrete intuition before scaling up to large multi-digit arrays on the SC-6 stack!

Array Orientation	Grid Dimensions	Row Breakdown	Total Area
Array A	3 Rows × 8 Columns	3 rows of 8 tiles (8 + 8 + 8)	**3 × 8 = 24 tiles**
Array B	4 Rows × 6 Columns	4 rows of 6 tiles (6 + 6 + 6 + 6)	**4 × 6 = 24 tiles**

4.2.2 Station Lesson 4.1: The 24-Tile Rectangular Array Studio & Multiplication Properties

Station Lesson 4.1: Tactile Setup

- **Manipulatives:** Counting & Array Studio with 24 Precision Interlocking Tiles (4 colors × 6 tiles)
- **Hardware:** StackCalc SC-6 Elementary Calculator
- **Core Goals:** Tactile proof of Commutative, Associative, and Distributive properties with 4-register stack traces



Figure: Commutative Property of Multiplication: 3x8 Array Rotated to 8x3 on Tabletop

1. Commutative Property (A × B = B × A)

Build a solid rectangular mat of 3 rows of 8 tiles (3 × 8). Now, physically pick up the mat and rotate it by 90^° on the tabletop. You now see 8 rows of 3 tiles (8 × 3). Did the number of tiles change? Not a single tile was added or removed!

On the SC-6 stack:

- Sequence 1: `3 [ENTER] 8 [×]` → X = **24**.
- Sequence 2: `8 [ENTER] 3 [×]` → X = **24**.

Keystroke	Register T	Register Z	Register Y	Register X (Display)
[3] [ENTER]	0	0	3	3
[8] [×]	0	0	0	24
[8] [ENTER]	0	24	8	8
[3] [×]	0	0	24	24

You see with your own eyes and feel with your own hands that spatial orientation does not alter the product.

2. Associative Property ((A × B) × C = A × (B × C))

Model small on your desk with two layers of 3 × 4 tiles (12 tiles per layer, 24 tiles total), then scale big on your SC-6 to a three-layer block prism (3 × 4 × 3 = 36). Because each tile is 7.0 mm tall, 3 stacked tiles equal 21.0 mm (approximating 1 cubic unit):

- Method A: Multiply length by width first (3 × 4 = 12), then multiply by height (12 × 3 = 36).
- Method B: Multiply width by height first (4 × 3 = 12), then multiply by length (3 × 12 = 36).

On the SC-6:

- Keystrokes: `[3] [ENTER] [4] [×] [3] [×]` → X = **36**.

Keystroke	Register T	Register Z	Register Y	Register X (Display)
`[3]` `[ENTER]`	0	0	3	3
`[4]` `[×]`	0	0	0	12
`[3]` `[×]`	0	0	0	36

The operational stack handles continuous chained multiplication without requiring parentheses.

3. Distributive Property & 4-Quadrant Area Models ((a+b)(c+d))

Model small on your desk by arranging a 4 × 4 = (2 + 2) × (2 + 2) = 16-tile square using four 2 × 2 color quadrants (4 + 4 + 4 + 4 = 16 tiles). Now scale big on your SC-6 to decompose (10 + 2) × (10 + 2) into four partial products across four quadrants: **(10 + 2) × (10 + 2) = (10 × 10) + (10 × 2) + (2 × 10) + (2 × 2) = 100 + 20 + 20 + 4 = 144**

Partial Product Quadrant	Dimensions	Area Value
Upper-Left (10 × 10)	10 rows × 10 columns	100 square units
Upper-Right (10 × 2)	10 rows × 2 columns	20 square units
Lower-Left (2 × 10)	2 rows × 10 columns	20 square units
Lower-Right (2 × 2)	2 rows × 2 columns	4 square units
Total Distributive Area	(10 + 2) × (10 + 2) = 12 × 12	**144 square units**



Figure: Four-Color Distributive Area: (10 + 2) x (10 + 2) = 144 Square Units across 4 Quadrants

On the SC-6:

- Keystrokes: `[1][0] [ENTER] [2] [+] [1][0] [ENTER] [2] [+] [×]` → X = **144**.

Keystroke	Register T	Register Z	Register Y	Register X (Display)
`10` `[ENTER]`	0	0	10	10
`[2]` `[+]`	0	0	0	12
`10` `[ENTER]`	0	12	10	10
`[2]` `[+]`	0	0	12	12
`[×]`	0	0	0	144

The four colors turn an abstract polynomial identity into an intuitive spatial puzzle.

4.2.3 The Four-Color Map Theorem Station Game

In 1976, Kenneth Appel and Wolfgang Haken proved that **no more than four colors are required** to color any planar map so that no two adjacent regions share a color.

Station Game: "Planar Map Showdown"

- **Players:** 2 to 4 players.
- **Rules:** Players take turns placing a counting tile onto the table grid to expand a contiguous "country". A placed tile may **never share a side edge** with a tile of the same color (diagonal corners are allowed).
- **The Challenge:** You discover that no matter how winding or complex the border network becomes, you **never need a 5th color**! If a player cannot legally place their color, they must skip their turn. The player with the most legal placements wins.

4.3 Addition & Subtraction Dynamics: Regrouping Without Fear

4.3.1 The Crisis of the Standard "Borrowing" Algorithm

In traditional arithmetic instruction, multi-digit subtraction (92 - 38) is taught through mechanical column borrowing:

1. "Look at the ones column: 2 - 8. You can't take 8 from 2."
2. "Cross out the 9, make it an 8."
3. "Put a little 1 next to the 2 to make it 12."
4. "12 - 8 = 4."
5. "8 - 3 = 5."
6. "Answer: 54."

When you learn traditional column borrowing, it's easy to fall into two confusing habits:

- Seeing the "little 1" as an arbitrary mark rather than a physical bundle of **10 units** transferred from the tens column.
- Feeling anxious when crossing out numbers, treating it like an error rather than keeping the total quantity invariant.

4.3.2 Mental Math Regrouping Strategies

With the SC-6, you can explore flexible mental math strategies that build true intermediate number awareness:

Strategy 1: The Compensation Method (92 - 38)

Instead of subtracting 38, subtract the friendly landmark number 40, and then compensate by adding 2 back: **92 - 38 = (92 - 40) + 2 = 52 + 2 = 54** On the SC-6 stack:

- `92 [ENTER] 40 [-] 2 [+]` → X = **54**.

Strategy 2: Bridging Tens (47 + 38)

Decompose 38 into 30 + 3 + 5: **47 + 30 = 77** → **77 + 3 = 80** → **80 + 5 = 85** On the SC-6:

- `47 [ENTER] 30 [+] 3 [+] 5 [+]` → X = **85**.

Every step is evaluated in real time, giving immediate diagnostic confirmation.

4.4 Superpower 1: Rhythmic Skip-Counting Ladders ([g] [REP])

In math class, times tables are mastered through **rhythmic skip-counting**. On conventional algebraic calculators, doing this requires repeatedly typing `+ 7 = = =`, which is easily disrupted if you pause, clear, or double-tap.

On classic scientific RPN calculators like the HP-32SII, loading a constant multiplier into Register T required pressing **`[ENTER]`** three times (**`[7] [ENTER] [ENTER] [ENTER]`**). That is cumbersome and easy to forget.

The SC-6 introduces **Superpower 1 (`[g] [REP]`)** on Row 3, Col 4. In a single click, **`[g] [REP]`** replicates the contents of Register X across all four registers (T, Z, Y, X).

Superpower 1: Stack Replication `[g] [REP]`

• **Enter Step Constant:** Type **`[7]`** .

• **Press `[g] [REP]` :** Replicates the constant across every level: Register T = 7 (Top Floor Permanent Constant), Register Z = 7, Register Y = 7, Register X = 7.

• **The Ladder Invariant:** Each time you tap **`[+]`** , Register T drops downward to replenish the stack, maintaining the constant step indefinitely without re-typing!

4.4.1 Station Lesson 4.2: Skip-Counting Ladders with Superpower 1 ([g] [REP])

Station Lesson 4.2: Tactile Setup

• **Manipulatives:** Counting & Array Studio, Batches of Stacking Tiles arranged in equal groups

• **Hardware:** StackCalc SC-6 in 4-Stack Mode with **`[g] [REP]`** key

• **Cadence:** Physical group addition paired with RPN stack collapse

1. Skip-Counting by Sevens: The 7s Ladder

Let us generate the multiples of 7:

1. Type `[7]`.
2. Press `[g]` `[REP]` (Row 3, Col 4). Every register (T, Z, Y, X) now holds 7!
3. Now simply tap `[+]` rhythmically as you place each physical 7-tile bar onto the table:

Keystroke	Register T (Constant)	Register Z	Register Y	Register X (Ladder)
`[7]`	0	0	0	7
`[g]` `[REP]`	7	7	7	7
`[+]`	7	7	7	14
`[+]`	7	7	7	21
`[+]`	7	7	7	28
`[+]`	7	7	7	35
`[+]`	7	7	7	42
`[+]`	7	7	7	49
`[+]`	7	7	7	56
`[+]`	7	7	7	63
`[+]`	7	7	7	70

Because Register T constantly duplicates its value down during two-number stack drop, you can march through the entire times table (7, 14, 21, 28 ... 70) in cadence with clapping drills or physical stepping.

2. Skip-Counting by Twelves (Dozens Ladder)

The number 12 is fundamental to everyday life (dozens of eggs, hours on a clock, inches in a foot, months in a year).

1. Type `12`.
2. Press `[g]` `[REP]`. All registers hold 12!
3. Tap `[+]` rhythmically to climb:

24, 36, 48, 60, 72, 84, 96, 108, 120

Dozens (1–4)	Dozens (5–8)	Dozens (9–12)
1 Dozen = 12 eggs	5 Dozen = 60 eggs	9 Dozen = 108 eggs
2 Dozen = 24 eggs	6 Dozen = 72 eggs	10 Dozen = 120 eggs
3 Dozen = 36 eggs	7 Dozen = 84 eggs	11 Dozen = 132 eggs
4 Dozen = 48 eggs	8 Dozen = 96 eggs	12 Dozen = **144** (1 Gross!)

3. The Doubling Ladder: Geometric Powers

Doubling is one of the most powerful mental math strategies in Grade 2 and 3. How do living cells divide, or how do digital computer memory chips scale?

1. Enter `[2]` `[ENTER]`.

2. Press `[ENTER]` `[+]`: 2 + 2 = **4**.
3. Press `[ENTER]` `[+]`: 4 + 4 = **8**.
4. Press `[ENTER]` `[+]`: 8 + 8 = **16**.
5. Press `[ENTER]` `[+]`: 16 + 16 = **32**.
6. Continue climbing: **64, 128, 256, 512, 1024**!

YOUR STACK SUPERPOWER CHECKPOINT:

- Pressing `[ENTER]` duplicates the number in Register X into Register Y.
- Pressing `[+]` immediately combines them into double their value!
- This two-key rhythm (`[ENTER]` `[+]`) lets you double any number instantly.

4.5 Superpower 2: Simultaneous Quotient & Remainder ([g] [÷R])

Why Long Division Causes Tears vs `[g]` `[÷R]`

The Scenario: You face: *"Divide 43 by 6."*

The Traditional Homework Trap:

You are taught to divide, multiply, subtract, and bring down. If you type it into a standard smartphone calculator, the screen displays: `7.16666666667`.

You wonder: *"Where did 0.1666 come from? My teacher wants a remainder!"* How do you convert decimals back to leftovers?

The 10-Second RPN Superpower:

On your SC-6, press: `43 [ENTER] 6 [g] [÷R]`.

The transflective LCD splits instantly:

- **Register X displays:** `7` (The whole Quotient)
- **Register Y displays:** `1` (The exact Remainder!)

To inspect the remainder, simply tap `[x⇔y]`!

To check your work with Superpower 4: `[f] [LASTX] [×] [+]` → `43`! Instant self-proof! Zero decimals. Zero tears. Total mathematical confidence.

In elementary school math, long division produces a **whole quotient** and a **remainder**. Traditional calculators display unwieldy decimals (17 ÷ 5 = 3.4), completely obscuring the physical meaning of equal groups and leftovers.

The SC-6 introduces **Superpower 2: Integer Division with Remainder (`[g]` `[÷R]`)** on Row 2, Col 5:

Superpower 2: Integer Division with Remainder (`[g]` `[÷R]`)

Given Dividend Y and Divisor X:

- **Register X** receives the whole integer Quotient: Q = trunc(Y / X)
- **Register Y** receives the whole integer Remainder: R = Y mod X
- Tapping `[x⇔y]` instantly swaps registers to inspect the Remainder!

4.5.1 Algebraic Trap vs. StackCalc Superpower Showdown: Division with Remainder

Challenge / Equation	The Algebraic Calculator Trap (TI-30X / Smartphone)	The StackCalc SC-6 + Manipulative Superpower	Keystroke Reduction	Live Stack Visibility	Pedagogical Breakthrough
Integer Division with Remainder: • 185 ÷ 12	1 8 5 / 1 2 = • → 15.41666667. • To extract integer remainder: • - 15 = * 12 = • (18 keystrokes). • Self-check requires retyping: • 15 * 12 + 5 = • (28 total keystrokes). • *Trap: Decimals obscure discrete items; scratch paper required.*	**SC-6 + 24-Cube Array Studio & Egg Cartons:** • 185 [ENTER] 12 [g] [÷R] • (7 keystrokes). • Simultaneously displays Quotient Q = 15 in Register X and Remainder R = 5 in Register Y! • Tap [x⇔y] to swap. • Self-check in 3 keys: • [f] [LASTX] [×] [+] • → 185!	**75% fewer keystrokes** • (7 vs. 28)	**Dual Live Registers:** • Quotient Q and Remainder R visible simultaneously on the transflective screen; zero scratch paper.	**Discrete Math Alignment:** • Eliminates decimal confusion in discrete sharing problems; transforms long division into an intuitive physical packaging and self-checking workflow.

4.5.2 Station Lesson 4.3: Equal Group Packaging & Remainder Sorting with Superpower 2 ([g] [÷R])

Station Lesson 4.3: Tactile Setup

- **Manipulatives:** Counting & Array Studio, 23 Stacking Tiles on desk
- **Hardware:** StackCalc SC-6 Elementary with [g] [÷R] integer division
- **Physical Goal:** Deal 23 tiles into equal groups of 5; isolate remainders

DESK DEALING LAYOUT (23 TILES DIVIDED BY 5):

GROUP 1: [■][■][■][■][■] (5 Tiles)

GROUP 2: [■][■][■][■][■] (5 Tiles)

GROUP 3: [■][■][■][■][■] (5 Tiles)

GROUP 4: [■][■][■][■][■] (5 Tiles)

REMAINDER: [■][■][■] (3 Loose Leftover Tiles!)

Total: 4 Groups × 5 Tiles + 3 Remainder = 23 Tiles!

Step-by-Step Hands-On Protocol:

1. **Concrete Dealing:** Count out 23 tiles and divide them into piles of 5. You find you can make exactly 4 complete piles, but 3 tiles remain loose on your desk.
2. **RPN Execution:**

- Type 23 [ENTER] [5] [g] [÷R].
- Register X displays: **4** (The 4 full equal groups!).
- Register Y holds: **3** (The 3 loose leftover tiles!).

3. **Register Swap:**

- Tap [x⇔y]: The active display shifts to **3**, bringing the remainder directly to your eyes.
- Tap [x⇔y] again: Returns to quotient **4**.

Keystroke	Register T	Register Z	Register Y	Register X (Display)
23 [ENTER]	0	0	23	23

Keystroke	Register T	Register Z	Register Y	Register X (Display)
[5]	0	0	23	5
[g] [÷R]	0	0	3	4
[x⇔y]	0	0	4	3

4.5.3 Real-World Problem 1: Egg Carton Packaging (12 Eggs per Carton)

A farm gathers 147 fresh eggs in the morning. Each carton holds exactly 12 eggs. How many full cartons can be packed for the farmer's market, and how many loose eggs are left over?

Keystroke	Register T	Register Z	Register Y	Register X
147	0	0	0	147
[ENTER]	0	0	147	147
12	0	0	147	12
[g] [÷R]	0	0	3	12
[x⇔y]	0	0	12	3

DIAGNOSTIC VERIFICATION:

- Register X = 12 (There are 12 full cartons of eggs!).
- Press [x⇔y] → Register X = 3 (There are 3 loose eggs left over!).
- Mathematical proof: (12 cartons × 12 eggs) + 3 remainder = 144 + 3 = 147!

4.5.4 Real-World Problem 2: Bakery Muffin Trays (6 Muffins per Tray)

A bakery oven bakes 86 apple cinnamon muffins. Each baking tray holds 6 muffins. How many full trays are filled, and how many extra muffins remain?

1. Type `86 [ENTER] [6] [g] [÷R]`.

- Register X displays: **14** (14 full trays!).
- Register Y holds: **2** (2 leftover muffins).

2. Tap [x⇔y] to inspect the remainder: Register X = **2**.

4.5.5 Real-World Problem 3: School Field Trip Buses (54 Passengers per Bus)

An elementary school is taking 380 students and chaperones on a science museum field trip. Each chartered bus has 54 seats. How many full buses are needed, and how many people must ride on an additional bus?

1. Type `380 [ENTER] 54 [g] [÷R]`.

- Register X displays: **7** (7 full buses carrying 7 × 54 = 378 people).

- Register Y holds: **2** (2 people left over).

2. **Think About It:** *"Can we order 7 buses?"*

- No! Those 2 people cannot be left behind at school. The school must order **8 buses** in total! (Ceiling division: if remainder > 0, add 1 bus!).

4.5.6 Real-World Problem 4: Dividing Classroom Chore Earnings

Four siblings earn $17.50 raking autumn leaves. How much whole dollar money does each sibling receive, and what remainder must be shared in pennies?

1. Type `17.50 [ENTER] [4] [g] [÷R]`.

- Register X displays: **4.00** (Each sibling receives $4.00).
- Register Y holds: **1.50** (Remainder of $1.50 left over).

2. Tap **[x⇔y]** to verify the $1.50 remainder.

4.5.7 The Euclidean Algorithm for Greatest Common Divisor via [g] [÷R]

As you advance in math, you will discover Euclid's timeless algorithm for finding the Greatest Common Factor (GCF) of two large numbers: **gcd(a, b) = gcd(b, a mod b)**

On the SC-6, Superpower 2 executes this algorithm with breathtaking elegance: Find gcd(252, 105):

1. `252 [ENTER] 105 [g] [÷R]` → Q = 2, R = **42** in Register Y.
2. Tap **[x⇔y]** to bring remainder 42 to X.
3. We divide prior divisor 105 by 42: `105 [x⇔y] [g] [÷R]` → Q = 2, R = **21** in Register Y.
4. Tap **[x⇔y]** to bring remainder 21 to X.
5. We divide 42 by 21: `42 [x⇔y] [g] [÷R]` → Q = 2, R = **0**!
6. The last non-zero remainder is **21**! Therefore, gcd(252, 105) = **21**!

4.6 Superpower 4: Self-Checking Inverse Arithmetic ([f] [LASTX])

A great mathematician never simply accepts an answer—they prove it using **inverse operations**.

On conventional calculators, self-checking requires clearing the screen and re-typing the entire calculation backwards. On the SC-6, **Superpower 4 ([f] [LASTX])** preserves the prior number before the operation executed:

> **Superpower 4: Self-Checking Inverse ([f] [LASTX])**
> • Whenever an operation executes, Register X's prior value is saved in the hardware `LASTX` register.

• Tapping **[f] [LASTX]** pushes that number back into Register X, while automatically lifting the calculated result into Register Y!

• You can immediately execute the inverse operation with **zero re-typing**!

4.6.1 Inverse Verification 1: Checking Addition with Subtraction

Let us verify 47 + 36 = 83:

1. Add the numbers: `47 [ENTER] 36 [+]` → X = **83**.
2. Press **[f]** **[LASTX]** (Row 2, Col 3):

- 36 is recalled into Register X.
- 83 is automatically lifted into Register Y.

3. Press **[-]** to execute the inverse check:

- 83 - 36 = **47**!
- We have restored our starting quantity with 100% mathematical certainty!

Keystroke	Register T	Register Z	Register Y	Register X
47	0	0	0	47
[ENTER]	0	0	47	47
36	0	0	47	36
[+]	0	0	0	83
[f] **[LASTX]**	0	0	83	36
[-]	0	0	0	47

4.6.2 Inverse Verification 2: Checking Multiplication with Division

Let us verify 15 × 8 = 120:

1. Multiply: `15 [ENTER] 8 [×]` → X = **120**.
2. Press **[f]** **[LASTX]**:

- 8 is recalled into Register X.
- 120 is lifted into Register Y.

3. Press **[÷]**:

- 120 ÷ 8 = **15**!

4.6.3 Inverse Verification 3: Checking Subtraction with Addition

Let us verify 95 - 38 = 57:

1. Subtract: `95 [ENTER] 38 [-]` → X = **57**.
2. Press **[f]** **[LASTX]**:

- 38 is pushed into Register X.
- 57 is lifted into Register Y.

3. Press **[+]**:

- 57 + 38 = **95**! Original starting value confirmed!

4.6.4 Inverse Verification 4: Checking Division with Multiplication

Let us verify 84 ÷ 7 = 12:

1. Divide: `84 [ENTER] 7 [÷]` → X = **12**.
2. Press **[f]** **[LASTX]**:

- 7 is recalled into Register X.
- 12 is lifted into Register Y.

3. Press **[×]**:

- 12 × 7 = **84**! Original dividend restored!

4.7 5th Grader Extreme Math Challenges: Doubling to the Sky & Your Age in Seconds!

Think multiplication is just boring times tables? Try these two extreme challenges on your SC-6 and test them on your family:

4.7.1 Challenge 1: What Happens If You Fold a Piece of Paper 10 Times with [g] [REP]?

A sheet of notebook paper is only 1 layer thick. Every time you fold it in half, the number of layers **doubles** (× 2). Can you fold a piece of paper 10 times with your bare hands? Almost nobody can—and Superpower 1 (**[g] [REP]**) shows why!

- Seed the stack with `2` and tap **[×]** nine times to see 10 doublings (2^{10}):

`2 [g] [REP] [×] [×] [×] [×] [×] [×] [×] [×] [×]` → `1024` **layers** (thicker than a 1,000-page dictionary!).

1. Tap `2` **[g] [REP]** to lock constant factor 2 into every stack floor (T = Z = Y = X = 2), priming the physical doubling mechanism *(Parker, 2019)*.
2. Tap **[×]** for the 1st fold: 2 layers double to 4 (X = 4), while constant 2 drops down from Floor T to wait on Floor Y.

3. Tap `[×]` for the 2nd fold: 4 layers double to 8 (X = 8), already thicker than standard cardstock.
4. Tap `[×]` for the 3rd fold: 8 layers double to 16 (X = 16), resisting thumb pressure.
5. Tap `[×]` for the 4th fold: 16 layers double to 32 (X = 32), thick like a deck of index cards.
6. Tap `[×]` for the 5th fold: 32 layers double to 64 (X = 64), stiff like a wooden slat.
7. Tap `[×]` for the 6th fold: 64 layers double to 128 (X = 128), impossible to crease with bare fingers.
8. Tap `[×]` for the 7th fold: 128 layers double to 256 (X = 256), thick like a textbook.
9. Tap `[×]` for the 8th fold: 256 layers double to 512 (X = 512), a full 500-sheet ream of copy paper.
10. Tap `[×]` for the 9th fold: 512 layers double to 1,024 (X = 1024), towering like a colossal phone directory!

- If you keep tapping `[×]` 10 more times (20 folds = 1,048,576 layers), that single sheet of paper would be taller than the Empire State Building!

4.7.2 Challenge 2: How Many Seconds Old Are You Right Now?

If you are **11 years old** in 5th grade, have you lived for a million seconds yet? What about a *billion* seconds? Let's chain the multiplication right on the stack (11 years × 365 days × 24 hours × 60 minutes × 60 seconds): **Keystrokes:** `11 [ENTER] 365 [×] 24 [×] 60 [×] 60 [×]` → `346,896,000` **seconds**!

1. Tap `11` `[ENTER]` to set your 11-year age baseline onto the upper mezzanine shelf (Y = 11).
2. Tap `365` `[×]` to fold in days per year: 11 × 365 = 4,015 days of sunrise and sunset resting on the active floor (X = 4015).
3. Tap `24` `[×]` to fold in hours per day: 4,015 × 24 = 96,360 hours lived (X = 96360).
4. Tap `60` `[×]` to convert hours to minutes: 96,360 × 60 = 5,781,600 minutes (X = 5781600).
5. Tap `60` `[×]` to convert minutes to seconds: 5,781,600 × 60 = 346,896,000 seconds ticking past on the LCD screen!

- You blew past 1,000,000 seconds when you were only 11.5 days old—and at 11 years old, you are already more than **one-third of the way to 1 Billion seconds**!

For Parents & Teachers: Division as Partitioning & Inverse Verification

Division as Partitioning vs. Decimal Abstraction: In elementary classrooms, long division often presents a severe pedagogical hurdle *(Ma, 1999)*. Traditional calculators compound this difficulty by outputting continuous decimal quotients: 17 ÷ 5 = 3.4. In concrete situations involving discrete objects—such as packing egg cartons, grouping students, or cutting materials—a fractional decimal fails to match physical intuition *(Singapore MOE, 2014)*.

Superpower 2 (`[g] [÷R]`) aligns calculator output directly with discrete partitioning. By placing the whole-number quotient Q in Register X and the integer remainder R in Register Y, the SC-6 mirrors physical manipulation: 17 units divide into 3 complete groups of 5 with 2 loose units remaining. Tapping `[x⇔y]` swaps registers instantaneously, enabling inspection of both components without recalculation.

Self-Checking and the Inverse Verification Strategy: Developing mathematical autonomy requires moving learners away from external answer validation toward internal verification. Superpower 4 (`[f] [LASTX]`) provides direct support for George Pólya's classic "look back" problem-solving strategy *(Pólya, 1945)*.

By preserving the argument of the most recent operation in the non-volatile `LASTX` register, the SC-6 allows students to verify results using inverse operations without re-entering values:

after addition (47 + 36 = 83.0), tapping [f] [LASTX] [-] immediately returns to 47.0; after division (120 ÷ 8 = 15.0), executing [f] [LASTX] [×] multiplies back to 120.0.

Stack Constant Seeding & Fluency: Superpower 1 ([g] [REP]) populates all four stack registers (T, Z, Y, X) with the entered step value in a single instruction *(Macaulay, 2016)*, powering rhythmic skip-counting ladders and building structural number sense.

For Parents & Teachers: Classroom Dialogue Scripts & Misconception Diagnostics

Script 4.1: The Field Trip Bus Ceiling Trap: When dividing 145 students across 40-seat buses (`145 [ENTER] 40 [g] [÷R]` → X=3, Y=25), remind students that 25 people cannot be left behind. Any remainder greater than zero requires ordering an additional bus (3 + 1 = 4 buses!).

Script 4.2: Array Rotation & The Commutative Miracle: Rotating a 3 × 8 counting tile array into an 8 × 3 array proves that A × B = B × A without altering the physical tile count (both evaluate to 24).

Script 4.3: The Magic Mirror of LASTX: If a student multiplies 18 × 7 = 126, pressing [f] [LASTX] [÷] restores the starting 18, proving the answer without scratch paper.

Script 4.4: Leftovers vs. Decimals in Pizza Sharing: Four friends sharing 15 pizza slices (`15 [ENTER] 4 [g] [÷R]`) receive 3 slices each with 3 whole slices left in the box for tomorrow, avoiding awkward decimal cuts (3.75).

4.8 RPN Stack Diagnostic & Remediation Playbook

The following diagnostic table addresses the ten most common beginner stumbling blocks encountered during operations, skip-counting, and remainder division:

Common Mistake / What You See	Why It Happened	How to Fix It on the Stack
1. In skip-counting, [g] [REP] was not pressed; [+] adds 0	Forgot to seed all registers with REP.	Type step constant, press [g] [REP] !
2. In division, expected remainder but got decimal	Pressed [÷] instead of integer division.	Use [g] [÷R] for whole quotient & remainder!
3. Cannot see remainder after pressing [g] [÷R]	Remainder is in Register Y; Register X holds quotient.	Tap [x⇔y] to swap and inspect remainder!
4. Self-check inverse gave wrong answer	Pressed wrong inverse operator.	Addition pairs with -; multiplication pairs with ÷!
5. Doubling ladder did not double	Did not press [ENTER] before [+] .	Press [ENTER] [+] to duplicate and add!
6. Multiplication product was too small	Pressed [+] instead of [×] .	[×] multiplies; [+] only adds.
7. Subtraction gave negative number (e.g., -54)	Entered second number before starting number.	Enter starting number, [ENTER], then subtract.
8. Pressed [C] after first product in chained sum	Believed screen had to be cleared.	Do not clear! Stack lifts automatically!
9. Field trip bus answer was short by one bus	Forgot that any leftover requires an additional bus.	If remainder > 0, round up by 1 whole bus!
10. LASTX recalled unexpected number	Executed another operation after error.	LASTX updates on **every** operation!

4.9 Comprehensive Worked Reference Problems (50 Elementary Reference Problems)

Hands-On Studio Proof: Blocks → Calculator

Step 1 (Physical Concrete Intuition): Take 24 precision stacking tiles from your 24-Tile Array Studio. Build a solid rectangular array of 3 rows with 8 tiles each (3 × 8). Count the rows and columns: 24 total tiles. Now physically rotate the entire tile tray 90^° on the tabletop. You now see 8 rows of 3 tiles (8 × 3). Not a single tile was added or lost: the physical area is invariant.

Step 2 (The Representational Bridge): Enter the calculation on your SC-6: `3 [ENTER] 8 [×]` → `24`. Now verify the rotated physical array: `8 [ENTER] 3 [×]` → `24`. Tap **`[f] [LASTX] [÷]`** to execute the inverse check: `24 ÷ 3 = 8`! Every physical manipulation maps directly to a stack operation.

Step 3 (Scaling on the Calculator): Now scale beyond the physical tabletop limits. You cannot easily lay out an orchard of 48 rows with 36 apple trees each on your desk—but your SC-6 evaluates `48 [ENTER] 36 [×]` → `1,728` trees in a fraction of a second, with the exact same spatial truth!

4.9.1 Expedition 1: The Saturday Morning Bakehouse & Master Orchard (Problems 4.1–4.8)

Mission Briefing: You are the head baker and master orchardist preparing goods for the weekend market. You must calculate baking tray capacities, arrange fruit crate matrices, and rotate cookie cooling grids—verifying that commutativity and spatial area always protect your production counts.

Problem 4.1: Four-Color Counting Tile Array (3 × 8 = 24)

At dawn in the Saturday morning bakehouse, the pastry chef prepares a rectangular baking sheet by snapping together 3 rows of 8 Archival White counting tiles on the workstation desk to model fresh sugar cookies. Rather than counting individual cookies one by one, multiplication treats the tray as a single cohesive rectangle of space (3 × 8 = 24).

On your SC-6, key in `3 [ENTER] 8 [×]` → `24`. Keying `3 [ENTER]` lifts the row dimension into Register Y, and tapping `8 [×]` multiplies on the ground floor to display 24 cookies in active Register X.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[3]`	0	0	0	3	Key in row count; value enters active Register X
`[ENTER]`	0	0	3	3	Lift row dimension to holding Register Y
`[8]`	0	0	3	8	Key in tiles per row into Register X
`[×]`	0	0	0	24	Multiply dimensions; stack drops to display total area (X = 24)

With Register X displaying 24, the chef verifies that all 24 cookie spaces are accounted for before sliding the tray into the brick oven.

Problem 4.2: Rotated Array Commutative Proof (8 × 3 = 24)

While inspecting the cooling racks, the baker grips the assembled 3 × 8 cookie mat from Problem 4.1 and rotates it by 90^° on the tabletop. Where there were previously 3 rows of 8 cookies, there are now 8 rows of 3 cookies (8 × 3). Without adding or discarding a single tile, the physical area remains identical at 24 cookies—demonstrating the commutative property (A × B = B × A) through direct tactile manipulation.

To verify this transformation on your SC-6, key in `8 [ENTER] 3 [×] → 24`. This sequence parks 8 into Register Y, multiplies by 3 on the ground floor, and leaves (T: 0, Z: 0, Y: 0, X: 24) glowing on the transflective screen (X = 24 cookies), confirming that spatial orientation never alters the underlying mathematical product.

Problem 4.3: Bakehouse Seating Grid (4 × 6 = 24)

As the morning café opens for brunch, the dining room supervisor arranges 4 rows of 6 Cobalt Blue counting tiles on the desk mat to model the café table seating grid. Calculating the total guest table capacity requires finding the area of this 4-by-6 matrix.

On the SC-6 keypad, enter `4 [ENTER] 6 [×] → 24`. This sequence lifts the 4 rows into Register Y, multiplies by 6 tables per row, and displays (T: 0, Z: 0, Y: 0, X: 24) tables across the dining room (X = 24 tables).

Problem 4.4: Orchard Tree Matrix (7 × 5 = 35)

Across the valley at the heirloom apple orchard, the arborist plants 7 parallel rows with 5 Radiant Gold Honeycrisp apple trees per row. Laying out 7 vertical strips of 5 gold tiles side-by-side models the geometric orchard grid on the planning table.

Turning to your SC-6, key in `7 [ENTER] 5 [×] → 35`. This sequence holds the 7 rows in Register Y, multiplies by 5 trees per row, and evaluates directly to (T: 0, Z: 0, Y: 0, X: 35) trees across the orchard (X = 35 trees).

Problem 4.5: Orchard Heirloom Apple Gift Crate (6 × 9 = 54)

To prepare for the harvest festival showcase, the master orchardist packs a wooden presentation crate with 6 rows of 9 prize-winning dessert apples. Modeling small with blocks, you can build a compact 2 × 9 = 18 tile sample boundary (≤ 24 tiles) on the desk mat to see how 9-compartment rows stack.

On your SC-6, scale the calculation to the full presentation crate by keying in `6 [ENTER] 9 [×] → 54`. This sequence loads 6 rows into Register Y and multiplies by 9 apples, yielding (T: 0, Z: 0, Y: 0, X: 54) apples packaged for delivery (X = 54 apples).

Problem 4.6: Bakehouse Pastry Cooling Grid (8 × 8 = 64)

The bakehouse pastry station features an 8 × 8 checkerboard cooling grid of alternating marble squares for tartlets. Model small with blocks by constructing a 4 × 4 checkerboard quadrant using 16 alternating white and slate tiles (≤ 24 tiles) on your desk mat, noting how equal rows and columns form a balanced geometric square.

Scale Big on StackCalc to compute the complete commercial grid: key in `8 [ENTER] 8 [×] → 64`. This sequence lifts the base dimension into Register Y and multiplies by height to drop the stack to (T: 0, Z: 0, Y: 0, X: 64) cooling squares (X = 64 squares).

Problem 4.7: Orchard Seedling Flat (12 × 4 = 48)

In the greenhouse nursery, an orchard seedling propagation flat contains 12 columns with 4 apple rootstock pots in each column. Model small with blocks by snapping together 3 columns of 4 tiles (12 tiles ≤ 24) to observe the repeating

modular structure of the planting flat.

Scale Big on StackCalc by keying in `12 [ENTER] 4 [×]` → `48`. This sequence parks the 12 columns in Register Y and combines them with 4 pots per column, leaving (T: 0, Z: 0, Y: 0, X: 48) healthy seedlings on the nursery bench (X = 48 seedlings).

Problem 4.8: Muffin Tin Array (9 × 7 = 63)

The commercial bakery rolls out a high-capacity sheet pan featuring 9 rows of 7 blueberry muffin wells. Model small with blocks by placing 3 rows of 7 counting tiles (21 tiles ≤ 24) on your workstation mat to visualize the column alignment.

Scale Big on StackCalc across the entire sheet pan: key in `9 [ENTER] 7 [×]` → `63`. This sequence lifts 9 rows into Register Y and multiplies by 7 wells per row, evaluating to (T: 0, Z: 0, Y: 0, X: 63) golden blueberry muffins fresh from the oven (X = 63 muffins).

4.9.2 Expedition 2: The Mountain Rescue Rhythmic Ladder (Problems 4.9–4.16)

Mission Briefing: You are part of an alpine search-and-rescue team ascending steep mountain ridges. Each elevation waypoint requires rhythmic stepping, skip-counting ropes, and rapid doubling ladders to track your climbing party's altitude, emergency radio beacon intervals, and supply drops.

Problem 4.9: Threes Ladder Alpine Trail Checkpoints (3 ... 27)

As an alpine search-and-rescue team ascends a steep mountain ridge, the lead mountaineer plants an emergency trail marker every 3 vertical meters of elevation gain. Rather than performing 9 separate additions, Superpower 1 (**[g] [REP]**) seeds the constant step across all four registers to create an effortless skip-counting ladder.

Model small with blocks by snapping together 3 rungs of 3 counting tiles (9 tiles ≤ 24) on your desk mat. Chant the climbing cadence: 3, 6, 9 meters! With your SC-6 ready, enter `3 [g] [REP] [+] [+] [+] [+] [+] [+] [+] [+]` → `27`. Keying `3 [g] [REP]` locks 3 into every register (T, Z, Y, X); each subsequent press of **[+]** pulls constant 3 downward from Register T to climb smoothly up the ridge.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[3] [g] [REP]	3	3	3	3	Load constant 3 into all 4 registers to seed the rhythmic ladder
[+]	3	3	3	6	1st step: 3 + 3 = 6 m; Register T preserves constant 3
[+]	3	3	3	9	2nd step: 6 + 3 = 9 m; constant 3 drops from T
[+]	3	3	3	12	3rd step: 9 + 3 = 12 m; rhythmically advancing up the ridge
[+]	3	3	3	15	4th step: 12 + 3 = 15 m; halfway station reached
[+]	3	3	3	18	5th step: 15 + 3 = 18 m; constant 3 preserved continuously
[+]	3	3	3	21	6th step: 18 + 3 = 21 m elevation waypoint
[+]	3	3	3	24	7th step: 21 + 3 = 24 m elevation waypoint
[+]	3	3	3	27	8th step: 24 + 3 = 27 m; 9th multiple reached

With Register X holding 27 meters, the team confirms they have secured the 9th checkpoint with zero re-entry.

Problem 4.10: Fours Ladder Granite Cliff Anchor Rops (4 ... 36)

To reach a stranded hiker on a sheer granite cliff, a rescue climber drives a solid steel safety piton every 4 vertical meters. Model small with blocks by building a vertical strip of 4 four-tile rungs (16 tiles ≤ 24) on your workstation mat, sliding your finger upward to count by fours: 4, 8, 12, 16 meters.

Scale Big on StackCalc to determine the total rope height secured after 9 safety anchors: key in `4 [g] [REP] [+] [+] [+] [+] [+] [+] [+] [+] → 36`. Pressing `4 [g] [REP]` loads the 4-meter interval across the entire stack; 8 rhythmic taps of `[+]` advance the climbing ladder up to (T: 4, Z: 4, Y: 4, X: 36) meters (X = 36 meters), securing the anchor line at the 9th piton.

Problem 4.11: Sixes Ladder Alpine Shelter Rations (6 ... 48)

Emergency ration packs are stocked across 8 high-altitude mountain shelters, with each shelter receiving 6 freeze-dried ration packs (6 × 8). Model small with blocks on your 2-wire Number Rack: slide 6 beads across Rail 1 and 6 beads across Rail 2 (6 × 2 = 12 rations ≤ 24), feeling the steady rhythm of equal groups.

Scale Big on StackCalc across all 8 shelters: key in `6 [g] [REP] [+] [+] [+] [+] [+] [+] [+] → 48`. Seeding the stack with `6 [g] [REP]` holds the 6-pack ration constant in Register T; 7 steady taps of `[+]` climb the supply ladder to (T: 6, Z: 6, Y: 6, X: 48) packs (X = 48 ration packs), completely provisioning all 8 stations without scratch paper.

Problem 4.12: Eights Ladder Glacier Traverse Carabiners (8 ... 64)

To cross a hazardous glacial icefield, the rescue team rigs 8 consecutive safety guide-rope spans, with each span requiring 8 heavy-duty locking carabiners (8 × 8). Model small with blocks by assembling 2 rows of 8 counting tiles (16 tiles ≤ 24) on your desk mat to visualize the 8-carabiner span increment.

Scale Big on StackCalc using Superpower 1: key in `8 [g] [REP] [+] [+] [+] [+] [+] [+] [+] → 64`. Replicating 8 with `8 [g] [REP]` locks the span requirement in Register T; 7 rhythmic taps of `[+]` march through the 8s table to (T: 8, Z: 8, Y: 8, X: 64) carabiners (X = 64 carabiners), verifying the complete rigging manifest for the crossing.

Problem 4.13: Nines Ladder Peak Radio Beacons (9 ... 81)

Emergency radio transceiver beacons are positioned across 9 surrounding mountain peaks, broadcasting 9 synchronized audio pulses during each transmission cycle (9 × 9 = 81). Model small with blocks using two Ten-Frames: place 9 counters on Frame 1 and 9 counters on Frame 2 (18 counters ≤ 24), observing how 9 + 9 = 18.

Scale Big on StackCalc to compute the total audio pulses transmitted per cycle: key in `9 [g] [REP] [+] [+] [+] [+] [+] [+] [+] [+] → 81`. Priming all four registers with `9 [g] [REP]` allows 8 taps of `[+]` to reach (T: 9, Z: 9, Y: 9, X: 81) pulses (X = 81), where the digital root property (8 + 1 = 9) confirms the product with instant certainty.

Problem 4.14: Twelves Ladder Alpine Supply Crates (Dozens to 144)

A supply helicopter delivers an alpine emergency crate packed with 12 cartons of chemical hand-warmers, each carton containing 12 individual warming packets (1 gross). Model small with blocks by taking a single 12-tile strip (12 tiles ≤ 24) from your Array Studio to ground the physical unit of one dozen.

Scale Big on StackCalc through all twelve cartons: key in `12 [g] [REP]` to seed all four registers (T: 12, Z: 12, Y: 12, X: 12), followed by 11 rhythmic taps of **[+]**. The stack advances through each dozen (24, 36, 48 ... 132) until reaching **144 warming packets** (X = 144), accounting for the entire gross of emergency heaters.

Problem 4.15: Geometric Doubling: Alpine Search Grid Expansion (1 → 64)

At nightfall in the mountains, a search-and-rescue coordinator initiates an expanding grid search. Beginning with an initial core sector of 1 square kilometer, the search perimeter doubles each hour as additional volunteer alpine teams arrive (1 → 2 → 4 → 8 → 16 → 32 → 64 km^2).

Modeling small with blocks, place 1 counting tile on your desk mat. Double it to 2 tiles, double the pair to 4, then 8, and 16 tiles (using only 16 tiles ≤ 24 tiles). Feel how geometric doubling grows explosively on the tabletop.

Scale Big on StackCalc: Now let your SC-6 doubling cadence (**[ENTER] [+]**) scale smoothly beyond physical block limits: key in `1 [ENTER] [+] [ENTER] [+] [ENTER] [+] [ENTER] [+] [ENTER] [+] [ENTER] [+]` → 64.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[1] **[ENTER]**	0	0	1	1	Enter starting search area of 1 km^2; duplicate into Y
[+]	0	0	0	2	Hour 1: 1 + 1 = 2 km^2 searched
[ENTER] **[+]**	0	0	0	4	Hour 2: Duplicate 2 and sum: 2 + 2 = 4 km^2
[ENTER] **[+]**	0	0	0	8	Hour 3: Duplicate 4 and sum: 4 + 4 = 8 km^2
[ENTER] **[+]**	0	0	0	16	Hour 4: Duplicate 8 and sum: 8 + 8 = 16 km^2
[ENTER] **[+]**	0	0	0	32	Hour 5: Duplicate 16 and sum: 16 + 16 = 32 km^2
[ENTER] **[+]**	0	0	0	64	Hour 6: Duplicate 32 and sum: 32 + 32 = 64 km^2

With Register X displaying 64, the coordinator verifies that 64 km^2 ($2^6 = 64$) have been comprehensively searched by the 6th hour.

Problem 4.16: Doubling Triples: High-Angle Hauling Rig Load (3 → 96)

The alpine rescue crew rigs a heavy-duty mechanical advantage pulley system to haul a rescue stretcher up a vertical cliff. The initial pilot rope holds a 3 kN test load. As successive double-pulley stages are coupled, the system's mechanical load rating doubles through 5 consecutive stages (3 → 6 → 12 → 24 → 48 → 96 kN).

Modeling small with blocks, place 3 counting tiles on your desk mat. Snap 3 more to double to 6 tiles, then double to 12 and 24 tiles (staying strictly within the 24-tile studio bound).

Scale Big on StackCalc: Let your SC-6 continue the geometric doubling ladder (**[ENTER] [+]**) to scale from 24 through 48 up to 96 kN without needing 96 physical tiles on your workstation mat! Key in `3 [ENTER] [+] [ENTER] [+] [ENTER] [+] [ENTER] [+] [ENTER] [+]` → 96. Tapping **[ENTER] [+]** five consecutive times duplicates and combines each stage (6 → 12 → 24 → 48 → 96), leaving (T: 48, Z: 48, Y: 96, X: 96) kN on the LCD screen (X = 96 kN), confirming

full rated hauling capacity.

4.9.3 Expedition 3: The Farm Stand Harvest & Egg Packaging Depot (Problems 4.17–4.26)

Mission Briefing: You are directing logistics at a bustling farm co-op. Baskets of fresh eggs, crates of apples, and batches of bakery muffins arrive by the truckload. Using Superpower 2 (**[g] [÷R]**), you must determine how many standard containers can be filled completely and sort leftover units without touching scratch paper or dealing with fractions.

Problem 4.17: Farm Egg Cartons (185 Eggs)

The farm hen house collects 185 fresh pasture-raised eggs this morning, and the packing crew must package them into standard 12-egg dozen cartons for the farm stand market. Superpower 2 (**[g] [÷R]**) determines both the complete carton count and the remaining loose eggs simultaneously without generating awkward decimals.

Model small with blocks using two Ten-Frames: place 14 counters into your frames, partitioning into a single dozen carton of 12 (one full frame plus 2 counters), leaving exactly 2 loose counters (14 ÷ 12 = 1 R 2). Feel how remainders separate cleanly from full cartons. Scale Big on StackCalc to process all 185 eggs in one stroke: key in `185 [ENTER] 12 [g] [÷R]` → 15.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
185 **[ENTER]**	0	0	185	185	Load 185 total harvested eggs into holding Register Y
12	0	0	185	12	Enter carton capacity 12 into active Register X
[g] **[÷R]**	0	0	5	15	Integer divide: X = 15 full cartons, Y = 5 leftover eggs
[x⇔y]	0	0	15	5	Swap registers to inspect remainder in active display (X = 5)

The LCD display cleanly splits the answer: Register X shows 15 full market cartons, and tapping **[x⇔y]** reveals the remainder of 5 loose eggs set aside for the farm kitchen (Q = 15 cartons, R = 5 eggs).

Problem 4.18: Dinner Roll Bakery Bags (75 Rolls)

The farm stand bakery pulls 75 warm honey-wheat dinner rolls fresh from the brick oven, packing them into kraft bakery bags holding 8 rolls each. Model small with blocks by taking 19 counting tiles from your studio tray (≤ 24 tiles). Bundling them into groups of 8 yields 2 complete bags (16 tiles) with 3 loose rolls left over (19 ÷ 8 = 2 R 3).

Scale Big on StackCalc across all 75 rolls: key in `75 [ENTER] 8 [g] [÷R]` → 9. Integer division with remainder simultaneously loads quotient 9 into Register X and leaves remainder 3 in Register Y with inline trace (T: 0, Z: 75, Y: 3, X: 9), separating 9 complete market bags from 3 warm rolls for the customer tasting basket (Q = 9 bags, R = 3 rolls).

Problem 4.19: Harvest Volunteer Camp Tents (29 Volunteers)

A crew of 29 harvest volunteers stays overnight at the farm camp, with each canvas orchard tent sleeping 4 workers. Model small with blocks by placing 17 counting tiles on your desk mat (≤ 24 tiles). Partitioning into groups of 4 yields 4 complete tents (16 workers) plus 1 volunteer remaining (17 ÷ 4 = 4 R 1).

Scale Big on StackCalc to shelter the full team: key in `29 [ENTER] 4 [g] [÷R]` → `7`. The stack drops into (T: 0, Z: 0, Y: 1, X: 7) tents; because remainder Y=1 person cannot sleep outside in the orchard, ceiling division dictates that the farm must erect 7 + 1 = 8 total tents (Q = 7 full tents, R = 1 volunteer, total = 8 tents).

Problem 4.20: Apple Orchard Gift Baskets (140 Apples)

The farm orchard harvests 140 crisp Honeycrisp apples, and the farm stand crew packages them into decorative woven gift baskets containing 6 apples each. Model small with blocks by taking 20 counting tiles (≤ 24 tiles) and grouping them into bundles of 6, creating 3 full baskets (18 tiles) with 2 leftover apples (20 ÷ 6 = 3 R 2).

Scale Big on StackCalc to package the entire harvest: key in `140 [ENTER] 6 [g] [÷R]` → `23`. Superpower 2 evaluates 140 ÷ 6 in a single stroke, leaving (T: 0, Z: 0, Y: 2, X: 23) on the display: 23 full gift baskets ready for shipment and 2 dessert apples left over (Q = 23 baskets, R = 2 apples).

Problem 4.21: Farm Floral Bouquet Twine Ties (250 cm Spool)

At the farm stand floral counter, a 250 cm spool of natural jute twine is cut into 35 cm ties for bundling freshly picked wildflower bouquets. Model small with blocks by taking 20 counting tiles from your Array Studio (≤ 24 tiles) and grouping them into bundles of 7, making 2 complete bundles (14 tiles) with 6 loose tiles remaining (20 ÷ 7 = 2 R 6).

Scale Big on StackCalc to divide the entire spool: key in `250 [ENTER] 35 [g] [÷R]` → `7`. Tapping **`[g] [÷R]`** yields (T: 0, Z: 0, Y: 5, X: 7), confirming that the florist cuts 7 full bouquet ties with an exact 5 cm twine remnant remaining on the wooden spool (Q = 7 ties, R = 5 cm leftover).

Problem 4.22: Farm Kitchen Chocolate Truffles (115 Truffles)

The farm confectionery kitchen dips 115 dark chocolate maple truffles, packaging them into artisan gold boxes holding 9 truffles each. Model small with blocks by counting out 24 counting tiles (≤ 24 tiles) and grouping them into 3 × 3 boxes of 9 tiles, making 2 complete boxes (18) with 6 loose truffles left over (24 ÷ 9 = 2 R 6).

Scale Big on StackCalc to package all 115 artisan delicacies: key in `115 [ENTER] 9 [g] [÷R]` → `12`. The display resolves instantly into (T: 0, Z: 115, Y: 7, X: 12), proving that 12 complete boxes can be sealed for the boutique with 7 truffles saved for the customer tasting dish (Q = 12 boxes, R = 7 truffles).

Problem 4.23: Pumpkin Patch Hayride Wagons (46 Visitors)

A farm tour group of 46 pumpkin patch visitors arrives to pick autumn pumpkins. The farm operates 7-passenger tractor hayride wagons to transport guests across the fields. Model small with blocks using two Ten-Frames: place 18 counters into your frames and group into sets of 7, filling 2 complete wagons (14) with 4 visitors waiting for the next wagon (18 ÷ 7 = 2 R 4).

Scale Big on StackCalc to transport the entire crowd: key in `46 [ENTER] 7 [g] [÷R]` → `6`. Integer division drops the registers to (T: 0, Z: 0, Y: 4, X: 6); since 4 pumpkin patch visitors cannot be left behind, the farm dispatches 6 + 1 = 7 total hayride wagons (Q = 6 full wagons, R = 4 visitors, total = 7 wagons).

Problem 4.24: Farm Harvest Garden Carts (78 Wheels)

The farm equipment shed has 78 pneumatic replacement wheels to service 4-wheeled harvesting garden carts. Model small with blocks by taking 18 counting tiles from your tray (≤ 24 tiles) and clustering them into groups of 4: you assemble 4 complete 4-wheel sets (16 tiles) with 2 spare wheels remaining (18 ÷ 4 = 4 R 2).

Scale Big on StackCalc to inventory all 78 replacement wheels: key in `78 [ENTER] 4 [g] [÷R]` → `19`. The operational stack drops into (T: 0, Z: 78, Y: 2, X: 19), confirming that 19 complete garden carts can be fully refitted with 2 spare wheels remaining in the maintenance bin (Q = 19 carts, R = 2 spare wheels).

Problem 4.25: Greenhouse Soil Sensor Battery Packs (42 Batteries)

The farm greenhouse operates automated irrigation soil-moisture sensors powered by 4-battery packs. The maintenance manager has 42 fresh AA batteries. Model small with blocks by taking 14 counting tiles (≤ 24 tiles) and partitioning into clusters of 4, building 3 complete 4-battery packs (12 tiles) with 2 spare batteries left over (14 ÷ 4 = 3 R 2).

Scale Big on StackCalc to evaluate the entire stock of 42 batteries: key in `42 [ENTER] 4 [g] [÷R]` → `10`. Integer division leaves (T: 0, Z: 42, Y: 2, X: 10) on the screen: 10 automated soil sensor packs are powered for deployment, leaving 2 reserve batteries in the charging dock (Q = 10 packs, R = 2 batteries).

Problem 4.26: Farm Stand Beeswax Candle Gift Boxes (175 Candles)

The farm apiary dips 175 handcrafted beeswax taper candles, and the farm stand packages them into gift boxes of 8 candles each. Model small with blocks by counting out 20 counting tiles (≤ 24 tiles) and grouping by 8, assembling 2 complete 8-candle boxes (16 tiles) with 4 loose candles remaining (20 ÷ 8 = 2 R 4).

Scale Big on StackCalc to package all 175 tapers: key in `175 [ENTER] 8 [g] [÷R]` → `21`. The operational stack cleanly separates 175 ÷ 8 into (T: 0, Z: 175, Y: 7, X: 21), delivering 21 boxed gift sets ready for sale and 7 display candles for the showroom counter (Q = 21 boxes, R = 7 candles).

4.9.4 Expedition 4: The Master Auditor's Inspection (Problems 4.27–4.34)

Mission Briefing: You are the chief quality inspector reviewing financial statements, warehouse balances, and shipping manifests. An auditor never assumes an arithmetic calculation is correct—they prove it through rigorous inverse operations. Using Superpower 4 (**`[f] [LASTX]`**), you will verify sums, differences, products, and quotients in reverse with zero re-entry.

Problem 4.27: Addition Check: Silver & Copper Bullion Invoices (68 + 27 = 95)

As chief auditor at the precious metals mint, you inspect a shipping ledger listing 68 silver bullion bars and 27 copper bullion bars for a total consignment of 95 bars (68 + 27 = 95). Rather than re-entering the entire manifest from scratch, Superpower 4 (**`[f] [LASTX]`**) executes an immediate inverse subtraction check (95 - 27) with zero scratch paper.

Modeling small with blocks, lay out 8 counting tiles on your desk mat, and place 7 tiles beside them to form 15 tiles (8 + 7 = 15). Pulling the 7 tiles away leaves exactly 8 tiles. Scale Big on StackCalc to audit the entire 95-bar consignment: key in `68 [ENTER] 27 [+] [f] [LASTX] [-]` → `68`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
68 [ENTER]	0	0	68	68	Load 68 silver bars into X and duplicate into Register Y
27 [+]	0	0	0	95	Add 27 copper bars; sum 95 displays in active Register X
[f] [LASTX]	0	0	95	27	Superpower 4: Recall last number 27 into X; sum lifts to Y
[-]	0	0	0	68	Inverse subtraction: 95 - 27 = 68; original addend restored

When Register X returns to 68, the auditor confirms with absolute mathematical certainty that the original silver bar allocation was intact.

Problem 4.28: Multiplication Check: Precision Aerospace Valves Manifest (18 × 6 = 108)

The auditor reviews a precision machining shipment of 18 crates holding 6 titanium shut-off valves each, billed as 108 valves total (18 × 6 = 108). Model small with blocks by building a small 3 × 6 array of 18 counting tiles (≤ 24 tiles) and dividing the array back into 6 equal rows (18 ÷ 6 = 3).

Scale Big on StackCalc to audit the bill of lading with Superpower 4: key in `18 [ENTER] 6 [×] [f] [LASTX] [÷]` → `18`. Keying `18 [ENTER] 6 [×]` evaluates 108 in Register X. Tapping **[f] [LASTX] [÷]** instantly recalls crate multiplier 6 into Register X, lifts total 108 into Register Y, and divides to return (T: 0, Z: 0, Y: 0, X: 18) crates (X = 18), verifying the manifest without touching scratch paper.

Problem 4.29: Subtraction Check: Central Bank Gold Vault Reserves (92 - 35 = 57)

A central bank vault transfer log records that from an opening vault reserve of 92 gold bricks, 35 bricks were dispatched to a regional branch, leaving an audited closing balance of 57 bricks (92 - 35 = 57). Model small with blocks on your 20-bead Number Rack: slide 18 beads across Rail 1, slide 5 beads away to model dispatching supplies (18 - 5 = 13), and then slide the same 5 beads back to restore 18 beads (≤ 24).

Scale Big on StackCalc to validate the vault ledger: key in `92 [ENTER] 35 [-] [f] [LASTX] [+]` → `92`. Deducting 35 from 92 leaves 57 in Register X; tapping **[f] [LASTX] [+]** immediately recalls 35 and adds it back, restoring the opening reserve (T: 0, Z: 0, Y: 0, X: 92) without re-entering a single digit (X = 92 bricks).

Problem 4.30: Division Check: Titanium Airframe Fasteners Cargo (156 ÷ 12 = 13)

A customs inspection officer audits a shipping container of 156 high-strength aerospace bolts distributed into sealed structural kits of 12 bolts each, calculating 13 full kits (156 ÷ 12 = 13). Model small with blocks using 24 counting tiles (≤ 24 tiles): bundle into 2 kits of 12 tiles (24 ÷ 12 = 2) and recombine them (2 × 12 = 24).

Scale Big on StackCalc to verify the full shipment: key in `156 [ENTER] 12 [÷] [f] [LASTX] [×]` → `156`. After dividing 156 by 12 to find 13 kits, tapping **[f] [LASTX] [×]** recalls divisor 12 into Register X and multiplies in place, restoring (T: 0, Z: 0, Y: 0, X: 156) fasteners (X = 156), proving that all 156 bolts are accounted for across the 13 kits.

Problem 4.31: Large Addition Check: Treasury Capital Reserve Consolidation (348 + 185 = 533)

During a municipal budget audit, an auditor reviews the merger of two civic development funds: $348k in municipal bonds and $185k in utility reserves, yielding a consolidated fund of $533k (348 + 185 = 533). Model small with blocks using your Place Value blocks: combine 3 ten-bars and 4 unit cubes with 1 ten-bar and 8 unit cubes (16 blocks total ≤ 24), regrouping ten cubes into a ten-bar (52), then remove 18 to return to 34.

Scale Big on StackCalc across the multi-digit treasury accounts: key in `348 [ENTER] 185 [+] [f] [LASTX] [-]` → `348`. Adding 348 and 185 produces 533; executing **`[f] [LASTX] [-]`** recalls 185 and subtracts it in one motion, leaving (T: 0, Z: 0, Y: 0, X: 348) verified on the screen (X = 348).

Problem 4.32: Multi-Digit Product Check: Solar Array Photovoltaic Lot (24 × 16 = 384)

A green-energy auditor inspects a commercial solar farm installation featuring 24 photovoltaic panel rows with 16 monocrystalline cells per row, reported as 384 active cells (24 × 16 = 384). Model small with blocks by building a 4 × 4 array using 16 counting tiles (≤ 24 tiles), and divide by 4 to return to 4.

Scale Big on StackCalc to audit the solar array: key in `24 [ENTER] 16 [×] [f] [LASTX] [÷]` → `24`. Multiplying 24 × 16 gives 384 cells; tapping **`[f] [LASTX] [÷]`** divides product 384 by 16 in one keystroke, returning (T: 0, Z: 0, Y: 0, X: 24) rows (X = 24) with zero manual division steps.

Problem 4.33: Large Subtraction Check: Industrial Fuel Storage Tank (500 - 187 = 313)

An environmental compliance auditor inspects an industrial fuel depot with a 500-liter storage reservoir. After dispensing 187 liters of diesel fuel to a municipal service fleet, the calibrated flow meter reads 313 liters remaining (500 - 187 = 313). Model small with blocks using Place Value blocks: start with 1 hundred-flat, remove 3 ten-bars and 7 unit cubes (37, using 11 blocks ≤ 24), leaving 63, then add the 37 blocks back to reconstruct the 100-flat.

Scale Big on StackCalc to validate meter calibration: key in `500 [ENTER] 187 [-] [f] [LASTX] [+]` → `500`. Dispensing leaves 313 liters in Register X; tapping **`[f] [LASTX] [+]`** recalls 187 liters and adds it back, restoring full reservoir capacity (T: 0, Z: 0, Y: 0, X: 500) (X = 500 liters).

Problem 4.34: Long Division Check: Architectural Stone Tile Quarry (225 ÷ 15 = 15)

A quarry auditor reviews an architectural stone supply order supplying 225 square meters of honed granite pavers packed into modular pallets of 15 square meters each, billed as 15 complete pallets (225 ÷ 15 = 15). Model small with blocks by assembling a 4 × 4 square array using 16 counting tiles (≤ 24 tiles) to see how equal rows and columns form a geometric square.

Scale Big on StackCalc to confirm the quarrying delivery manifest: key in `225 [ENTER] 15 [÷] [f] [LASTX] [×]` → `225`. Dividing 225 by 15 leaves 15 pallets in Register X; tapping **`[f] [LASTX] [×]`** multiplies quotient by pallet size to restore (T: 0, Z: 0, Y: 0, X: 225) square meters (X = 225 m^2), matching the delivery bill to the quarry plan.

4.9.5 Expedition 5: The Junior Engineering Workshop (Problems 4.35–4.42)

Mission Briefing: You are an apprentice systems engineer designing robotics assemblies, purchasing supplies, and managing material budgets. Real engineering problems never come in neat single-step packages; they require combining multiple products, sums, and differences seamlessly on the operational stack without intermediate scratch

notes.

Problem 4.35: Robotics Frame Motor Mounts & Bearing Blocks

An apprentice systems engineer designs a robot drive chassis on the workshop bench using 3 aluminum motor brackets at $4 each and 2 linear bearing blocks at $5 each. Calculating the total bill ((3 × 4) + (2 × 5)) demonstrates how the RPN stack automatically preserves intermediate values in higher registers without requiring parentheses.

Model small with blocks by laying out 3 rows of 4 blue counting tiles for the $12 bracket cost, and 2 rows of 5 gold counting tiles for the $10 bearing cost (22 tiles total ≤ 24). Pushing the two arrays together visually combines the subtotals. Step over to your SC-6 and key in `3 [ENTER] 4 [×] 2 [ENTER] 5 [×] [+]` → 22.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[3] [ENTER] 4	0	0	3	4	Place 3 brackets in Y, key in $4 unit cost in X
[×]	0	0	0	12	Evaluate motor bracket subtotal: 3 × 4 = $12
[2] [ENTER] 5	0	12	2	5	Stack lifts $12 to Z; load 2 bearing blocks at $5
[×]	0	0	12	10	Evaluate bearing subtotal: 2 × 5 = $10; subtotal 1 in Y
[+]	0	0	0	22	Combine both hardware subtotals: $12 + $10 = $22

With Register X reading 22, the engineer confirms that total component cost is **$22** with zero intermediate notes scribbled on paper.

Problem 4.36: Stepper Motor Drivers & Limit Switches

An automation workcell requires 5 high-torque stepper motor drivers at $12 each and 4 optical limit switches at $8 each. Model small with blocks by placing 2 groups of 5 tiles (10) and 2 groups of 4 tiles (8) on your mat (18 tiles total ≤ 24).

Scale Big on StackCalc to compute the total electronics order: key in `5 [ENTER] 12 [×] 4 [ENTER] 8 [×] [+]` → 92. Multiplying 5 × 12 stores $60 in Register Y while 4 × 8 = $32 evaluates in Register X; tapping [+] fuses both subtotals into (T: 0, Z: 0, Y: 0, X: 92), evaluating the complete workcell bill to **$92** (X = 92).

Problem 4.37: Custom Servo Bracket 3D Print Batch

Your engineering team 3D prints 45 custom servo brackets valued at $2 each (45 × 2 = $90), incurring raw filament and brass threaded insert expenses of $28. Model small with blocks using 18 Place Value units (≤ 24 tiles): model 9 units, remove 3 units to simulate expenses, leaving 6 units.

Scale Big on StackCalc to find the net project yield: key in `45 [ENTER] 2 [×] 28 [-]` → 62. Evaluating gross production value 45 × 2 = $90 and immediately deducting $28 leaves (T: 0, Z: 0, Y: 0, X: 62), confirming a net project yield of **$62** (X = 62).

Problem 4.38: Test Bench Frame Extrusion & Gusset Packs

A structural test frame requires 40 meters of T-slot aluminum extrusion at $6 per meter (40 × 6 = $240), plus 5 heavy-duty cast corner gusset packs at $14 each (5 × 14 = $70). Model small with blocks using Place Value blocks: 4 ten-bars (40) and 1 ten-bar plus 4 units (14), staying strictly within 9 blocks (≤ 24).

Scale Big on StackCalc to determine total framing investment: key in `40 [ENTER] 6 [×] 5 [ENTER] 14 [×] [+]` → `310`. Multiplying 40 × 6 = $240 lifts to Register Z when loading the gussets, and the final sum drops the stack into (T: 0, Z: 0, Y: 0, X: 310) framing expense (X = 310).

Problem 4.39: Fastener Inventory Reconciliation

A hardware workshop inventory bin starts Monday with 850 socket-head cap screws. During chassis assembly, 145 screws are driven into frame joints, and 88 unused screws from a disassembled prototype are returned to stock. Model small with blocks using Place Value blocks: represent 85 with 8 ten-bars and 5 unit cubes (13 blocks ≤ 24).

Scale Big on StackCalc to reconcile fastener stock: key in `850 [ENTER] 145 [-] 88 [+]` → `793`. Deducting 145 leaves 705 screws, and adding the 88 reclaimed units leaves (T: 0, Z: 0, Y: 0, X: 793) screws on the active display (X = 793).

Problem 4.40: Robotics Wiring Harness Assembly

A production run assembles wiring harnesses: 120 sensor ribbon cables at $3 each, 85 heat-shrink sleeve bundles at $2 each, and 40 flexible cable-drag chains at $4 each. Model small with blocks by taking 16 counting tiles (≤ 24 tiles) and grouping them into small representative bundles of 3 and 2.

Scale Big on StackCalc through all three material lines: key in `120 [ENTER] 3 [×] 85 [ENTER] 2 [×] [+] 40 [ENTER] 4 [×] [+]` → `690`. The stack evaluates ribbon cables (120 × 3 = $360), lifts to add sleeves (85 × 2 = $170 → $530), and adds drag chains (40 × 4 = $160) to finish at (T: 0, Z: 0, Y: 0, X: 690) total material cost (X = 690).

Problem 4.41: Hex Standoff Packaging for Sensor Modules

Four automated workstations assemble 24 sensor modules each (4 × 24 = 96 modules), and each module requires 2 threaded hex standoff posts (96 × 2 = 192 standoffs). Standoffs are packaged in bags of 15. Model small with blocks by taking 16 counting tiles (≤ 24 tiles) and partitioning into clusters of 5 (16 ÷ 5 = 3 R 1).

Scale Big on StackCalc to determine total bags consumed: key in `4 [ENTER] 24 [×] 2 [×] 15 [g] [÷R]` → `12`. Chaining 4 × 24 × 2 produces 192 standoffs, and tapping `15 [g] [÷R]` drops the stack into (T: 0, Z: 0, Y: 12, X: 12): 12 full bags are emptied, with 12 additional standoffs required from a 13th bag (Q = 12 bags, R = 12 loose, total bags = 13).

Problem 4.42: Conveyor Pallet Roller Bearings

Three automated conveyor loops have 12 carrier pallets each (3 × 12 = 36 pallets), with each pallet requiring 3 precision roller bearings (36 × 3 = 108 bearings). Bearings are packaged in protective tubes of 8. Model small with blocks by grouping 18 counting tiles (≤ 24 tiles) into sets of 8: you get 2 complete tubes (16) with 2 loose bearings (18 ÷ 8 = 2 R 2).

Scale Big on StackCalc to determine the stockroom pull: key in `3 [ENTER] 12 [×] 3 [×] 8 [g] [÷R]` → `13`. Chaining 3 × 12 × 3 yields 108 bearings, and tapping `8 [g] [÷R]` yields (T: 0, Z: 0, Y: 4, X: 13): 13 complete tubes are emptied, and 4 bearings are taken from a 14th tube (Q = 13 tubes, R = 4 loose, pull 14 tubes).

4.9.6 Expedition 6: Mental Math & Rapid Arithmetic Shortcuts (Problems 4.43–4.50)

Mission Briefing: You are stepping into the High-Speed Math Discovery Studio. In rapid problem-solving sprints, speed and poise are everything: solving challenging arithmetic sequences under timed conditions without scratch paper. Use these championship-grade shortcuts, factoring tricks, and modular checks to solve high-pressure challenges in seconds.

Problem 4.43: Rapid Mental Multiplication by 25 (36 × 25)

In the High-Speed Math Discovery Studio sprint round, the coach challenges you to calculate 36 × 25 mentally in under two seconds. Because 25 = (100 / 4), multiplying by 25 is mathematically identical to dividing by 4 and scaling by 100 (36 ÷ 4 = 9 → 9 × 100 = 900). To anchor the factoring shortcut concretely, count out a small test set of 24 counting tiles and partition them into 4 equal quarters of 6 tiles each (24 ÷ 4 = 6). Treating each quarter as 25 gives 6 × 25 = 150, which matches 6 × 100 ÷ 4 = 150.

Scale Big on StackCalc to execute the tournament sprint: key in `36 [ENTER] 4 [÷] 100 [×]` → `900`. The stack evaluates the division and hundred-fold multiplication cleanly: `36` **[ENTER]** `4` **[÷]** sets Register X to 9, and `100` **[×]** instantly evaluates to (T: 0, Z: 0, Y: 0, X: 900)—conquering the calculation in two swift keystrokes.

Problem 4.44: Mental Multiplication by 99 (45 × 99)

During the rapid sprint challenge, the scoreboard flashes 45 × 99 without scratch paper allowed. Instead of tedious long multiplication, apply the distributive shortcut: multiplying by 99 is identical to scaling by 100 and subtracting exactly one single group of 45 (45 × 100 - 45 = 4,500 - 45 = 4,455). Build a tactile model on your desk using 10 unit cubes arranged in a single row to represent a strip of tens. Removing 1 unit cube leaves 9 units (10 - 1 = 9); scaling each unit by 45 confirms that subtracting one group from ten groups mirrors subtracting one group from one hundred groups.

Scale Big on StackCalc to confirm the distributive trick: key in `45 [ENTER] 100 [×] 45 [-]` → `4455`. Keying `45` **[ENTER]** `100` **[×]** establishes the baseline product of 4,500, and typing `45` **[-]** immediately yields (T: 0, Z: 0, Y: 0, X: 4455).

Problem 4.45: Consecutive Integers Sum Trick (1 + 2 + ... + 20)

The sprint prompt demands the sum of all consecutive integers from 1 to 20 (1 + 2 + 3 + ... + 20). Rather than adding twenty numbers sequentially, apply young Carl Friedrich Gauss's pairing formula: S = (n(n+1) / 2) = (20 × 21 / 2) = 210. Prove this geometrically on your desk by assembling a 4-rung stepped staircase using 10 counting tiles (1 + 2 + 3 + 4 = 10). Assemble an identical 10-tile twin staircase, rotate it 180^°, and interlock them into a solid 4 × 5 rectangle of 20 tiles (≤ 24 tiles). Halving the rectangular area gives (20 / 2) = 10 tiles.

Scale Big on StackCalc to compute the 20-integer sum: key in `20 [ENTER] 21 [×] 2 [÷]` → `210`. Entering `20` **[ENTER]** `21` **[×]** builds the paired rectangle of 420 in Register X, and pressing `2` **[÷]** halves the area to (T: 0, Z: 0, Y: 0, X: 210) without a single parenthesis.

Problem 4.46: Rapid Remainder Sprint (3,458 ÷ 11)

The discovery studio timer drops to 3 seconds: extract both the whole quotient and integer remainder of 3,458 ÷ 11. While a standard calculator yields an unhelpful repeating decimal (314.3636...), your SC-6 evaluates both exact integer parts simultaneously. Model the division small with 20 counters placed on two Ten-Frames: dividing 20 by 11 yields 1 full

bundle of 11 counters with 9 loose remnants left over ($20 = 1 \times 11 + 9$).

Scale Big on StackCalc for the four-digit sprint: key in `3458 [ENTER] 11 [g] [÷R]` → `314`. Pressing `3458` **[ENTER]** `11` **[g]** **[÷R]** instantly deposits the quotient 314 into Register X and the integer remainder 4 into Register Y ((T: 0, Z: 0, Y: 4, X: 314)). Tapping **[x⇔y]** swaps the display to verify the 4 loose remainder items, confirming $3{,}458 = 314 \times 11 + 4$.

Problem 4.47: Chained Multi-Step Arithmetic Sprint (15 × 12 - 18 × 6)

The final team sprint round challenges you to evaluate $(15 \times 12) - (18 \times 6)$ without scratch notes or parentheses. Watch how the RPN 4-register stack acts as an automatic holding buffer: it evaluates the first product (180), lifts it automatically into Register Z when the second factor pair is loaded, holds the first product safely in Register Y while computing the second product (108), and subtracts them with a single stroke.

Model the subtraction small on your desk using counting tiles: build a 3×4 array (12 tiles) and a 2×3 array (6 tiles). Removing the 6 tiles from the 12 tiles leaves 6 tiles ($12 - 6 = 6$).

Scale Big on StackCalc to execute the dual-product tournament sequence: key in `15 [ENTER] 12 [×] 18 [ENTER] 6 [×] [-]` → `72`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`15` **[ENTER]** `12`	0	0	15	12	Enter first factor pair: 15 into Y, 12 into X
[×]	0	0	0	180	Evaluate product 1: $15 \times 12 = 180$ in Register X
`18` **[ENTER]** `6`	0	180	18	6	Stack lifts 180 to Z; enter 18 into Y, 6 into X
[×]	0	0	180	108	Evaluate product 2: $18 \times 6 = 108$; product 1 in Y
[-]	0	0	0	72	Subtract products: $180 - 108 = 72$ in active display

The final display reads X = **72**, demonstrating how Register Z buffers intermediate sub-expressions seamlessly.

Problem 4.48: Rapid Mental Square of a Number Ending in 5 (35^2)

In the speed squaring sprint, compute 35^2 in under 2 seconds. Apply the mental squaring shortcut for numbers ending in 5: multiply the tens digit 3 by its consecutive successor $(3+1)=4$ to obtain 12, then append 25 to immediately produce 1,225! Model the geometric principle small using 16 counting tiles arranged as a 4×4 square. Decomposing the square into a 3×3 core (9 tiles), two 3×1 edge strips (6 tiles), and a 1×1 corner tile (1 tile) proves how tens and units interact symmetrically ($9 + 6 + 1 = 16$).

Scale Big on StackCalc to verify the speed square: key in `35 [ENTER] 35 [×]` → `1225`. Keying `35` **[ENTER]** `35` **[×]** yields (T: 0, Z: 0, Y: 0, X: 1225), verifying the mental calculation $35^2 = 1{,}225$.

Problem 4.49: Sum of First 10 Odd Integers (1 + 3 + 5 + ... + 19)

In the studio pattern sprint, find the sum of the first 10 odd numbers ($1 + 3 + 5 + 7 + 9 + 11 + 13 + 15 + 17 + 19$). The ancient Pythagorean theorem reveals that the sum of the first n odd integers is always a perfect square: $S_n = n^2 = 10^2 =$

100! Build this physically on your desk using counting tiles: start with 1 tile, wrap an L-shaped border of 3 tiles around it to form a 2 × 2 square (4 tiles), then wrap 5 tiles around that to form a 3 × 3 square (9 tiles), and finally 7 tiles to make a 4 × 4 square (16 tiles ≤ 24 tiles). Each odd layer expands the square by exactly one unit along each axis.

Scale Big on StackCalc for the 10-odd-integer sprint: key in `10 [ENTER] 10 [×]` → `100`. Keying `10` **[ENTER]** `10` **[×]** squares the count n=10, yielding (T: 0, Z: 0, Y: 0, X: 100) and confirming the geometric square sum.

Problem 4.50: Chained Divisibility & Modulo Sprint (4,896 ÷ 16)

The final tournament sprint challenge tests rapid divisibility: is 4,896 evenly divisible by 16? Tap **[g] [÷R]** on your SC-6: if the integer remainder in Register Y equals 0, the number divides cleanly with zero remainder! Model divisibility small with 16 counting tiles: arranging all 16 tiles into a single bundle of 16 leaves exactly 0 loose remnants (16 ÷ 16 = 1 R 0).

Scale Big on StackCalc to test the large dividend: key in `4896 [ENTER] 16 [g] [÷R]` → `306`. Keying `4896` **[ENTER]** `16` **[g] [÷R]** immediately sets Register X to 306 and Register Y to 0 ((T: 0, Z: 0, Y: 0, X: 306)). The zero remainder proves that 4,896 is evenly divisible by 16 with a clean quotient of 306.

4.10 What You Mastered & Looking Ahead

In this chapter, you transformed whole number operations into spatial, joyful superpowers! With the 24-Tile Four-Color Array Studio, you proved that multiplication is a physical rectangle of space. On your SC-6 Stack Calculator, you unlocked rhythmic skip-counting ladders with **Superpower 1 ([g] [REP])**, captured whole-number quotients and real remainders with **Superpower 2 ([g] [÷R])**, and commanded the self-checking magic mirror of **Superpower 4 ([f] [LASTX])** without ever needing scratch paper.

What happens when you have a remainder that cannot be left as a whole leftover—like slicing a single remaining pizza among four friends, or measuring a piece of lumber down to the exact fraction of an inch? In **Chapter 05: Fractions, Decimals, Percents & Proportional Towers**, you will dive into the 84 mm Fraction Studio, master single-key two-dot fraction entry, and discover how to reduce fractions step-by-step with **Superpower 3 ([g] [SIMP])**!

Fractions, Decimals, Percents & Proportional Towers

5.1 Why Do Fractions, Ratios, and LCM Matter in Real Life?

Fractions, decimals, and gear ratios aren't just symbols on paper. They are the hidden clockwork behind music, cooking recipes, bicycles, treehouses, and skateboards!

> **For Parents & Teachers: Historical Roots & Physical Mechanisms**
>
> Decimal fractions (formalized by John Napier *(Napier, 1614)*) and proportional ratios form the foundational mathematics of physical mechanisms and engineering, as celebrated by David Macaulay *(Macaulay, 2016)*.

5.1.1 Why Fractions & Equivalent Fractions (SIMP) Matter to You

Have you ever tried sharing a giant flatbread, pizza, or chocolate bar fairly among your friends? Or have you ever built a backyard treehouse where you measured a board with a tape measure and wondered why (4 / 8) inch is the exact same length as a (1 / 2) inch bolt?

When you lay four (1 / 8) blocks alongside one (1 / 2) block inside your **84 mm Fraction Studio Twin Comparator Well**, your fingers and eyes feel why (4 / 8) = (1 / 2) before you ever touch a pencil! On your SC-6, **Superpower 3 (`[g] [SIMP]`)** does the exact same thing: it peels away common factors one step at a time until your fraction reaches simplest terms.

5.1.2 The Backyard Barbecue Mystery: Why Hot Dogs and Buns Never Match (LCM)

Every kid who has ever helped plan a picnic or family birthday barbecue has faced the greatest commercial conspiracy in the grocery store:

- **Hot dogs** come in packs of **10**.
- **Hot dog buns** come in packs of **8**.

If you buy 1 pack of each, you have 2 extra wieners and zero buns! If you buy 2 packs of buns (16) and 2 packs of hot dogs (20), you now have 4 extra dogs. It feels like an endless trap!

How many packages must you buy so that **every single hot dog gets a bun with exactly zero waste**?

The Mathematical Rescue: Least Common Multiple (LCM)

You are searching for the smallest positive integer that is a simultaneous multiple of both 10 and 8:

Multiples of 10: 10, 20, 30, 40, 50, ... Multiples of 8: 8, 16, 24, 32, 40, 48, ...

The magic number is **40**!

- 40 ÷ 10 = **4** packs of hot dogs.
- 40 ÷ 8 = **5** packs of buns.

Four packs of dogs plus five packs of buns yields exactly 40 hot dogs tucked neatly into 40 buns.

> **On the SC-6: Instant Barbecue LCM Rescue**
>
> You don't need to guess multiples on scratch paper. On the keypad, press:
>
> `10 [ENTER] 8 [f] [LCM]` → `40`!
>
> Two seconds. Problem solved. The family barbecue is saved without a single leftover wiener!

Adding Different-Sized Slices with LCM

Least Common Multiple isn't just for hot dogs—it is your secret key to adding fractions! Suppose you are building a treehouse railing and need to join a (3 / 8)-foot piece of oak trim and a (5 / 12)-foot piece of pine trim. You can't just add 3 + 5, because an eighth-block and a twelfth-block are completely different sizes! You need the **smallest block size that fits evenly under both**: LCM(8, 12) = 24 (twenty-fourths). Once both pieces are measured in twenty-fourths, adding them is effortless!

5.1.3 The Drummer's Secret: Polyrhythms & Why Music Is Living Math

Ever listen to an irresistible Afro-Cuban groove, a jazz drum solo, or a modern hip-hop beat where the rhythm seems to float, dance, and pull against itself? That hypnotic feeling is powered directly by number theory!

Imagine a drummer playing a **"3-against-4" polyrhythm**:

- The right hand taps a steady pulse every 4 clock ticks: [4, 8, **12**, 16, 20, **24**, ...]
- The left hand plays a cross-pulse every 3 clock ticks: [3, 6, 9, **12**, 15, 18, 21, **24**, ...]

As the music plays, the two hands wander apart, creating electric musical tension. The listener's ear holds its breath. But then—**CRASH!** Both hands strike the cymbals at the exact same microsecond!

When does the pattern resolve? At tick **12**—the Least Common Multiple of 3 and 4 (LCM(3, 4) = 12). The entire universe of musical syncopation and harmonic acoustics is governed by common denominators.

5.1.4 The Bicycle Mechanic's Secret: The "Hunting Tooth" & Why Gears Survive (GCF)

Look closely at the steel chain and sprockets on a professional racing bicycle. Suppose the chainring at the crank has 34 teeth and the rear cog has 17 teeth.

Notice something dangerous? 34 = 2 × 17. Their **Greatest Common Factor is 17** (gcd(34, 17) = 17).

If a bicycle were built with that ratio, the exact same chain link would slam into the exact same cog tooth on every second pedal revolution! If that one link picks up a microscopic speck of diamond-hard road grit, it will hammer into that identical tooth thousands of times an hour, gouging a groove and destroying the drivetrain.

Master bicycle engineers avoid this disaster by using **coprime gear ratios**—meaning gear tooth counts that share no common factors other than 1 (gcd(A, B) = 1, a mathematical superpower we explore in depth in Chapter 7!). When the number of teeth share no common factor greater than 1, each link **"hunts"** around every single tooth on the entire sprocket before ever repeating. Wear is distributed with mathematically uniform perfection across all teeth, allowing the chain to last for thousands of miles. GCF is mechanical engineering!

Chapter Baseline Mode: `[NUM]`

Standard Base-10 Arithmetic • Transitioning to `[FDISP]` / `[g] [a:b]`

Unlocked Keycaps Ribbon — Grades 3–5 Fraction & Ratio Suite

- **Fraction Entry & Mode:** `[.]` (Two-dot syntax: `. n . d` and `w . n . d`), `[FDISP]` (Fraction/Decimal Display Mode).
- **Display Toggles:** `[a b/c]` Mixed Number Display, `[f] [d/c]` Improper Fraction Display, `[f] [0.3]` Repeating Decimal Display.
- **Superpower 3:** `[g] [SIMP]` (Step-by-Step Factor Reduction with Lowest Terms alert).
- **Number Theory Keys:** `[GCF]` (Greatest Common Factor), `[f] [LCM]` (Least Common Denominator finder).
- **Ratio Mode:** `[g] [a:b]` Ratio Mode & Ratio Table Studio (with pagination).
- **Percents & Core Operations:** `[%]` Percent Key, `[+]`, `[-]`, `[×]`, `[÷]`, `[ENTER]`, `[x⇔y]`, `[C]`.



Figure: Least Common Multiple of 12 and 18 → 36

5.2 Concrete Foundation: 84 mm Fraction Studio Proportional Towers

When you first see fractions written as flat numbers on paper ((3 / 4)), it can feel like looking at two disconnected numbers trapped in a box. But on your desk, **fractions are real physical heights and lengths** you can hold in your hand and stack side-by-side on a continuous number line!

For Parents & Teachers: Overcoming Fraction Phobia with Tactile Blocks

The Scenario: A learner is stuck on unlike denominators: 3/4 + 2/3 = ?

The Conventional Challenge:

"Find the Least Common Multiple of 4 and 3. It's 12. Now convert 3/4 to twelfths: multiply top and bottom by 3 to get 9/12. Now convert 2/3 to twelfths: multiply top and bottom by 4 to get 8/12. Now add 9 + 8 = 17/12. Now convert 17/12 to a mixed number: 1 and 5/12."

If a single factor is missed, the multi-step calculation easily breaks down.

The Tactile 84 mm Solution:

1. Drop the 3/4 tower (63.0 mm) and 2/3 tower (56.0 mm) into the Twin Comparator Well. Total height = 119.0 mm.

2. Next to it, place 1 Whole tower (84.0 mm). The stack is taller by exactly 35.0 mm—which fits **five 1/12th lilac tiles** (5 × 7.0 mm = 35.0 mm)!

3. You *see* the answer before touching a pencil: **1(5 / 12)**!

On the SC-6:

Key in: `. 3 . 4 [ENTER] . 2 . 3 [+]`.

The display instantly reads: `1_5/12` (or `17/12` in **`[f] [d/c]`** mode)!

Tap **`[g] [SIMP]`** → Already in lowest terms! Tap **`[FDISP]`** → `1.41666667`.

The mystery of fractions disappears into concrete certainty.

Concrete (Tactile Manipulation)	Representational (Dot-Matrix LCD)	Abstract (RPN Operational Stack)
84.0 mm Proportional Towers with zero-loss lap joints	**Transflective Dot-Matrix Grid** with Y ■ X split	**Hardware Stack Lift & Drop** without parenthesis clutter
Twin Comparator Well for immediate flush alignment checks	**3-Tier Linear Scaling Fonts** preventing digit truncation	**Intuitive Two-Dot Entry Syntax** (`. n . d` and `w . n . d`)
Calibrated Tri-Face Markings (Fraction / Decimal / Percent)	**Unreduced Default Mode** preserving your fractions	**Superpower 3 (`[g] [SIMP]`)** step-by-step reduction & LCM

The **StackCalc Fraction Studio** grounds rational numbers in physical height, tactile mass, and proportional geometry:



Figure: StackCalc Fraction Studio: 84mm Proportional Towers and Twin Comparator Well

Fraction Studio Proportional Towers (84.0 mm Standard)

Standardized on an 84.0 mm whole-unit tower standard:

• **1 WHOLE Tower:** 84.0 mm master architectural datum in matte technical white

• **1/2 Halves:** 42.0 mm each (vibrant scarlet red)

• **1/3 Thirds:** 28.0 mm each (bright solar yellow)

• **1/4 Fourths:** 21.0 mm each (cobalt blue)

• **1/6 Sixths:** 14.0 mm each (emerald green)

• **1/8 Eighths:** 10.5 mm each (cyan blue)

• **1/12 Twelfths:** 7.0 mm each (lilac purple)

Key Innovation: Precision interlocking joints ensure that two 1/2 towers exactly equal 84.0 mm! The Twin Comparator Well provides a precision side-by-side verification channel in a modular desk tray.

5.2.1 Tri-Face Laser-Marked Towers

Each physical fraction tower features three calibrated reference faces:

- **Front Face:** Standard common fraction ((1 / 4)).
- **Right Face:** Decimal equivalent (0.25).
- **Back Face:** Percentage equivalent (25%).

When you hold a fourths block, you simultaneously see all three mathematical representations in your hands, forming an unbreakable bond between fractions, decimals, and percents.

5.2.2 Station Lesson 5.1: Proportional Fraction Towers & The Twin Comparator Well

Station Lesson 5.1: Tactile Setup

• **Manipulatives:** Fraction Studio, Proportional Towers (84 mm standard: 1/2, 1/3, 1/4, 1/6), Twin Comparator Well (dual precision verification channel), 1 Counting Tile from the Counting Studio (7.0 mm 1U visible height)

• **Hardware:** StackCalc SC-6 Elementary with Two-Dot Syntax & `[g] [SIMP]`

• **Discovery:** Tactile height subtraction and the 1/12th tile bridge

The storage case for the Fraction Studio includes a precision channel called the **Twin Comparator Well**. When you place one Whole tower (84 mm) into Well A, and stack two Halves (42 mm + 42 mm) into Well B, your fingertips slide effortlessly across the flush top edge. The tactile sensation proves that (2 / 2) = 1 without writing a single line of equations.



Figure: Fraction Studio: Twin Comparator Well Equivalence Proof and Counting Tile Bridge

Twin Comparator Well Equivalence Proof

Proof 1: Two Halves Equal One Whole ((2 / 2) = 1)

• **Well A:** Drop one Whole tower (84.0 mm).

• **Well B:** Stack two Half towers (42.0 mm + 42.0 mm = 84.0 mm).

• **Result:** Flush top alignment (0.0 mm delta). Tactile proof that (2 / 2) = 1 Whole!

Proof 2: Comparing Unlike Denominators ((3 / 4) vs (4 / 6))

• **Well A:** Three (1 / 4) towers (21.0 × 3 = 63.0 mm).

• **Well B:** Four (1 / 6) towers (14.0 × 4 = 56.0 mm).

• **Result:** Well A protrudes above Well B by exactly 7.0 mm ((1 / 12)th of 84 mm). Tactile proof that (3 / 4) > (4 / 6)!

The Physical Bridge Action:

Insert one Counting Tile (7.0 mm visible 1U height) from the Counting Studio into Well B: 56.0 mm + 7.0 mm = 63.0 mm — *smooth, flush alignment with Well A!*

Hands-On Bridging Protocol:

1. **Physical Inspection:**

- Stack three 1/4 towers in Well A: 21 mm × 3 = 63.0 mm.
- Stack four 1/6 towers in Well B: 14 mm × 4 = 56.0 mm.
- Slide finger across: Well A sticks up above Well B by exactly 7.0 mm.
- Grab **1 Counting Tile** (7.0 mm visible height) from the Counting Studio and drop it into Well B.
- Run finger across: *Perfection! Completely flush!*
- Therefore: (4 / 6) + (1 / 12) = (3 / 4)!

2. **RPN Stack Verification:**

- Enter (4 / 6): `[.] 4 [.] 6 [ENTER]`.

- Enter (1 / 12): `[.] 1 [.] 12`.
- Add: **[+]** → X = **9/12**.
- Simplify: **[g]** **[SIMP]** → X = **3/4**!

Keystroke	Register T	Register Z	Register Y	Register X (Display)
`[.] 4 [.] 6`	0	0	0	4/6
[ENTER]	0	0	4/6	4/6
`[.] 1 [.] 12`	0	0	4/6	1/12
[+]	0	0	0	9/12
[g] **[SIMP]**	0	0	0	3/4

For Parents & Teachers: The Twin Comparator Dialogue

Guide: "Feel the top of the two wells. Is 3/4 bigger than 4/6?"

Student: "Yes! Well A is taller."

Guide: "How much taller is it? Try dropping one 7.0 mm counting tile into Well B."

Student: "It fits perfectly! They're totally smooth across now!"

Guide: "And what fraction is a 7.0 mm tile of our 84 mm Whole tower?"

Student: "One twelfth!"

Guide: "So four-sixths plus one-twelfth equals...?"

Student: "Three-fourths! Look, the calculator says 3/4 too!"

5.3 Two-Dot Entry Syntax (. n . d and w . n . d)

The SC-6 introduces an intuitive, single-key syntax for entering fractions without requiring a complicated menu or cumbersome fraction templates:

Two-Dot Fraction Syntax

1. Proper Fraction ((3 / 8)):

Press: `[.] 3 [.] 8` → Display shows: `3/8`

2. Mixed Number (2(3 / 4)):

Press: `[2] [.] 3 [.] 4` → Display shows: `2 3/4`

3. Improper Fraction ((11 / 4)):

Press: `[.] 11 [.] 4` → Display shows: `11/4`

The second decimal point automatically engages Fraction Mode!

When you type the second decimal point **[.]**, the calculator engine recognizes the fractional structure, configures internal numerator/denominator registers, and renders the fraction on the transflective dot-matrix display.

5.3.1 Split-Screen Display & Clear Reading

In the horizontal Y | X display layout, the screen splits into two clear columns. Register Y waits on the left, and your active number X sits on the right. The SC-6 automatically adjusts the text size so fractions remain bold, sharp, and easy to read from across your desk without ever cutting off numbers!

5.3.2 Display Formatting Toggles: Mixed vs. Improper

You can toggle how fractions appear on screen at any time:

- **Press `[a ⌧/c]`:** Formats as a mixed number (e.g., 11/4 → **2 3/4**).
- **Press `[f] [d/c]`:** Formats as an improper fraction (e.g., 2 3/4 → **11/4**).
- **Press `[FDISP]`:** Toggles instantaneously between fraction and decimal format (3/4 ↔ 0.75).

5.4 Why the Calculator Keeps Your Work Unreduced

On the SC-6, **arithmetic does not automatically reduce your fractions**:

- When you multiply (1 / 2) × (2 / 3), traditional calculators jump straight to (1 / 3). That skips the most important step: multiplying the numerators (1 × 2 = 2) and denominators (2 × 3 = 6) to get (2 / 6).
- The SC-6 proudly preserves your unreduced work on screen: **(2 / 6)**!
- You then choose when to simplify by pressing **Superpower 3 (`[g] [SIMP]`)**, watching common factors vanish step by step.

Operation	Unreduced Output	Next Step with `[g] [SIMP]`
Like Addition: 2/4 + 1/4	3/4	`LOWEST TERMS` alert
Like Addition: 2/4 + 2/4	4/4 (retains 4/4!)	`[g] [SIMP]` → 1
Like Subtraction: 3/4 - 1/4	2/4 (retains 2/4!)	`[g] [SIMP]` → 1/2
Unlike Addition: 1/2 + 1/4	3/4 (common denom 4)	`LOWEST TERMS` alert
Multiply: 2/3 × 3/4	6/12	`[g] [SIMP]` → 1/2
Divide: 2/3 ÷ 1/4	8/3 (2/3 × 4/1)	`[a ⌧/c]` → 2(2 / 3)

5.5 Superpower 3: Step-by-Step Factor Reduction ([g] [SIMP])

In 4th and 5th grade, simplifying fractions is a major superpower. Instead of guessing factors on scratch paper, you can see and feel how fractions shrink!

Superpower 3 (`[g] [SIMP]`) finds common factors and simplifies the fraction step-by-step:

- If the fraction can be reduced: Divides both the top and bottom numbers by common factors.
- If it is already in simplest form: The SC-6 flashes `"LOWEST TERMS"` across the screen!

5.5.1 Named Idiom: The Equal-Fraction Tower Alignment

When you drop two 1/4 blocks and one 1/2 block into the Fraction Studio comparison tray, their top edges match up completely flat and flush! When you tap `[g] [SIMP]` on the calculator, the screen does the exact same thing: it shrinks your numbers down step-by-step until your fraction is in its simplest, cleanest form.

For Parents & Teachers: Equivalence & Physical Height Alignment

Following Jerome Bruner's CRA framework *(Bruner, 1966)*, Zoltan Dienes's perceptual variability principle *(Dienes, 1960)*, Steven Strogatz's geometric insights *(Strogatz, 2012)*, and standard elementary curricula *(Singapore MOE, 2014)*, children master equivalent fractions through physical height matching. The SC-6 `[g] [SIMP]` key mirrors this tactile experience in the digital stack.



Figure: Fraction Studio Gauge Comparison: Visual and Tactile Height Verification

5.5.2 Station Lesson 5.2: Step-by-Step Reduction with Superpower 3 ([g] [SIMP])

Station Lesson 5.2: Tactile Setup

- **Manipulatives:** Fraction Studio Proportional Towers (84 mm standard), Twin Comparator Well
- **Hardware:** StackCalc SC-6 Elementary with `[g] [SIMP]` Key (Row 3, Col 2)
- **Problem:** Simplify 12/18 down to its irreducible lowest terms

Hands-On Simplification Protocol:

1. **Concrete Phase:**

- Assemble an unreduced model: stack twelve 1/18 unit slices (each 4.67 mm height, total 56.0 mm).
- In Well B, place two 1/3 towers (28.0 mm × 2 = 56.0 mm).
- Slide your finger across the tops: it proves that (12 / 18) = (2 / 3) exactly!

2. **RPN Execution:**

- Enter (12 / 18) using two-dot syntax: `[.] 12 [.] 18 [ENTER]`.
- Press `[g]` `[SIMP]` (Row 3, Col 2):

The engine factors out 6 (gcd(12, 18) = 6). Register X updates to: `2/3`.

- Press **[g]** **[SIMP]** a second time:

gcd(2, 3) = 1. The fraction cannot be reduced further. The status line flashes: `LOWEST TERMS`!

Keystroke	Register T	Register Z	Register Y	Register X (Display)
`[.] 12 [.] 18`	0	0	0	12/18
[ENTER]	0	0	12/18	12/18
[g] **[SIMP]**	0	0	12/18	2/3
[g] **[SIMP]**	0	0	12/18 [STATUS: LOWEST TERMS]	2/3

5.6 Adding & Subtracting Unlike Denominators

5.6.1 Station Lesson 5.3: Finding Common Denominators with Hardware [f] [LCM] and [GCF]

Station Lesson 5.3: Tactile Setup

- **Manipulatives:** Fraction Studio Towers (1/8, 1/12) + Prime Studio Blocks
- **Hardware:** StackCalc SC-6 with **[f]** **[LCM]** and **[GCF]** Keys (Row 1, Col 2)
- **Challenge:** Add 3/8 + 5/12 by finding the Least Common Multiple

When you need to find a **Least Common Denominator (LCD)** before adding unlike fractions, you do not have to guess multiples on scratch paper. On the SC-6, you use the hardware **[f]** **[LCM]** key (Row 1, Col 2) to find the common denominator instantly:

1. Finding Least Common Denominators (LCD)

Problem: Add (3 / 8) + (5 / 12).

1. Find the LCD of denominators 8 and 12:

`8 [ENTER] 12 [f] [LCM]` → X = **24**. The least common denominator is **24**!

2. Convert mentally or on paper: (3 / 8) = (9 / 24) and (5 / 12) = (10 / 24).
3. Verify on the SC-6:

[.] 3 [.] 8 [ENTER] [.] 5 [.] 12 [+] → X = **19/24**.

Keystroke	Register T	Register Z	Register Y	Register X
[8] **[ENTER]**	0	0	8	8
12	0	0	8	12
[f] **[LCM]**	0	0	0	24
`[.] 3 [.] 8`	0	0	24	3/8

Keystroke	Register T	Register Z	Register Y	Register X
[ENTER]	0	24	3/8	3/8
[.] 5 [.] 12	0	24	3/8	5/12
[+]	0	0	24	19/24

2. Single-Step Fraction Reduction with Hardware [GCF]

You can find the single greatest factor needed to reduce any fraction in one step using the primary [GCF] key (Row 1, Col 2):

- For the unreduced fraction (24 / 36), find the greatest common factor:

24 [ENTER] 36 [GCF] → X = **12**.

- Dividing both 24 and 36 by 12 yields the irreducible fraction: **(2 / 3)**!

3. The Secret Partner Rule: GCF × LCM = A × B

In number theory, the product of two positive integers equals the product of their Greatest Common Factor and their Least Common Multiple: **GCF(a, b) × LCM(a, b) = a × b**

On the SC-6: For a = 18 and b = 24:

- 18 [ENTER] 24 [GCF] → X = **6**.
- 18 [ENTER] 24 [f] [LCM] → X = **72**.
- Product: 6 [ENTER] 72 [×] → X = **432**.
- Direct multiplication: 18 [ENTER] 24 [×] → X = **432**!

The secret partner rule is proven live on the stack!

5.7 Fractions, Decimals and Percents Bridge

5.7.1 Terminating vs. Repeating Decimals

When converting fractions to decimals using [FDISP]:

- Terminating decimals terminate with finite digits: (1 / 4) = 0.25, (3 / 8) = 0.375.
- Repeating decimals loop indefinitely: (1 / 3) = 0.333333333333..., (2 / 3) = 0.666666666666..., (1 / 6) = 0.166666666666....

The SC-6 transflective dot-matrix LCD provides the **Repeating Bar ([f] [0.3])** indicator above the repeating period, honoring standard elementary mathematical typography.

5.7.2 Percentage Calculations on the Stack ([%])

A percentage is simply a ratio with a denominator of 100: **P% = (P / 100)**

On the SC-6:

- Finding 15% of $80.00:

`80 [ENTER] 15 [%]` → X = **12.00** (Register Y holds 80.00!).

- Adding 15% tip to $80.00:

[+] → X = **92.00**! Because Register Y retains the base amount (80.00), a single subsequent press of **[+]** computes the total with tip, or **[-]** computes the discounted sale price!

5.8 Ratio Mode & Ratio Table Studio ([g] [a:b])

Ratios represent proportional relationships — comparing ingredients in a recipe, gear teeth on a bicycle, or scale model dimensions to real buildings. You can use the SC-6 to explore scaling ratios and building **ratio tables** without getting tangled in fractions.

5.8.1 Entering Ratio Mode

1. Type a ratio using two-dot syntax (e.g. `[.] 15 [.] 25`).
2. Press **[g]** **[a:b]** (Row 1, Col 3).

- Display shows: `15:25`.

3. Press **[g]** **[SIMP]**:

- Ratio simplifies by its GCD (5): `3:5`!

4. Scale the ratio: Type **[2]** **[×]**:

- Ratio scales to: `6:10`.

5. Simplify back: Press **[g]** **[SIMP]**:

- Returns to: `3:5`.

Keystroke	Register T	Register Z	Register Y	Register X
`[.] 15 [.] 25`	0	0	0	15/25
[g] [a:b]	0	0	0	15:25
[g] **[SIMP]**	0	0	0	3:5
[2] **[×]**	0	0	0	6:10
[g] **[SIMP]**	0	0	0	3:5

5.8.2 Converting Fractions to Part-to-Part Ratios

If a committed fraction (15 / 25) is already on the stack (representing 15 parts out of a whole of 25), pressing **[g]** **[a:b]** converts it into a **part-to-part ratio** comparing the selected parts (15) to the remaining parts (25 - 15 = 10):

- Stack has (15 / 25). Press **[g]** **[a:b]** → Displays 15:10.
- Press **[g]** **[SIMP]** → Simplifies to 3:2!

For Parents & Teachers: Rational Number Foundations & Deliberate Reduction

The 84 mm Master Datum and Concrete Equivalence: In elementary mathematics education, mastery of fractions is the strongest empirical predictor of subsequent algebraic competence. Proportional Fraction Towers are standardized on an 84.0 mm master datum (divisible by 2, 3, 4, 6, 8, and 12), giving each fraction a tactile height directly proportional to its mathematical value. In the Twin Comparator Well, students evaluate sums like (1 / 2) + (1 / 4) by placing blocks side-by-side, verifying the 63.0 mm composite height against the 84.0 mm whole before symbolic computation begins.

Deliberate Unreduced Fraction Policy: Traditional calculators reduce fractions automatically, masking the product of numerators and denominators ((1 × 2 / 2 × 3) = (2 / 6)). The SC-6 retains unreduced intermediate results, allowing learners to actively extract common factors with **[g]** **[SIMP]** until reaching LOWEST TERMS.

Part-to-Part Ratio Bridge: Tapping **[g]** **[a:b]** on a committed fraction like (15 / 25) converts it into the part-to-part ratio 15:10, which simplifies via **[g]** **[SIMP]** to 3:2, cementing the distinction between part-to-part comparisons and part-to-whole fractions.

For Parents & Teachers: Classroom Dialogue Scripts & Misconception Diagnostics

Script 5.1: The Unreduced Fraction Revelation: When multiplying (1 / 2) × (2 / 3), the SC-6 shows 2/6, verifying 1 × 2 = 2 and 2 × 3 = 6. Pressing **[g]** **[SIMP]** reduces it to 1/3 and flashes LOWEST TERMS.

Script 5.2: Why We Don't Add Denominators: Stacking a (1 / 2) tower (42 mm) and (1 / 4) tower (21 mm) in Well A (63 mm) vs two (1 / 6) towers (28 mm) in Well B physically proves why (1 / 2) + (1 / 4) ≠ (2 / 6). Well B is far too short! Three (1 / 4) towers (63 mm) align perfectly flush.

Script 5.3: Lemonade Ratios (Parts vs. Whole): Mixing 2 cups lemon juice with 6 cups water gives a part-to-part ratio of 2:6 (1:3). But the total volume is 1 + 3 = 4 cups, meaning lemon juice represents (1 / 4) of the total pitcher.

5.8.3 Algebraic Trap vs. StackCalc Superpower Showdown: Fractions, Ratios & Rational Numbers

Challenge / Real-World Task	The Algebraic Calculator Trap (TI-84 / Infix)	Algebraic Keystrokes & Clutter	The StackCalc Superpower (RPN Stack + Visual Studio)	StackCalc Keystrokes	The Stack Advantage
Unlike Denominators Sum: • Rafter bolt spacing: • (3 / 8) + (5 / 12) = (19 / 24)	Infix fraction entry requires opening fraction templates or nested parentheses. Forgetting a parenthesis divides 8 by 5 prematurely, producing a misleading decimal. Common denominator (24) is hidden.	(3 / 8) + (5 / 12) = • (15 keystrokes, syntax brackets, invisible LCD)	**Hardware LCD via [f] [LCM] + Two-Dot Entry:** • Single-tap **[f]** **[LCM]** extracts LCD (24). Two-dot syntax . 3 . 8 [ENTER] . 5 . 12 [+] computes 19/24 directly with unreduced transparency.	. 3 . 8 [ENTER] . 5 . 12 [+] • (10 keystrokes)	**33% fewer keystrokes** • Zero parentheses, zero mode shifting; students see the exact common denominator and rational sum simultaneously.

Challenge / Real-World Task	The Algebraic Calculator Trap (TI-84 / Infix)	Algebraic Keystrokes & Clutter	The StackCalc Superpower (RPN Stack + Visual Studio)	StackCalc Keystrokes	The Stack Advantage
Step-by-Step Simplification: • Bulk syrup reduction: • (12 / 18) → (2 / 3)	Modern algebraic calculators automatically reduce fractions immediately, hiding numerator and denominator multiplication (1 × 2 = 2, 2 × 3 = 6). Students cannot see which common factor was divided out.	1 2 / 1 8 = → 2/3 • (Skips educational factoring; black-box reduction)	**Deliberate Unreduced Default + [g] [SIMP] :** • Preserves 12/18 on the stack. Pressing [g] [SIMP] factors out 6 to show 2/3, flashing LOWEST TERMS only when irreducible.	. 12 . 18 [g] [SIMP] • (7 keystrokes)	**Pedagogical Transparency:** • Honors student work; common factors are peeled away step-by-step matching physical Fraction Studio towers.
Chained Mixed-Number Evaluation: • Scale model ratio batching: • (3 (1 / 2) × 2 (2 / 3)) ÷ 1 (1 / 6)	Chained mixed numbers require massive nested parentheses (3 + 1 / 2) * (2 + 2 / 3) / (1 + 1 / 6) =. Forgetting an outer bracket divides prematurely, corrupting the calculation by orders of magnitude.	(3 + 1 / 2) * (2 + 2 / 3) / (1 + 1 / 6) = • (33 keystrokes, 6 parentheses)	**Natural Two-Dot RPN Stack Fusion:** • Two-dot syntax enters whole and fractional parts directly. The 4-register stack holds intermediate rational products with zero parentheses or scratch paper.	3 . 1 . 2 [ENTER] 2 . 2 . 3 [×] 1 . 1 . 6 [÷] • (17 keystrokes)	**48% fewer keystrokes** • Zero parentheses; stack resolves directly to exact integer 8 with intermediate rational verification on screen.
Part-to-Part Ratio Scaling: • Drawbridge gear ratio reduction & scale: • 15:25 → 3:5 → 6:10	Algebraic calculators treat ratios as division, converting 15:25 into decimal 0.6. The proportional relationship between parts is permanently lost.	1 5 / 2 5 = → 0.6 • (Ratios destroyed into decimal quotient; cannot scale terms)	**Dedicated Ratio Mode ([g] [a:b]):** • Retains antecedent and consequent. Pressing [g] [SIMP] reduces to 3:5; multiplying by 2 scales both parts simultaneously to 6:10.	. 15 . 25 [g] [a:b] [g] [SIMP] 2 [×] • (11 keystrokes)	**True Ratio Arithmetic:** • Scales recipes, gear teeth, and blueprints without converting to decimals or losing component parts.

5.9 RPN Stack Diagnostic & Remediation Playbook

The following diagnostic table addresses the ten most common beginner stumbling blocks encountered during fractions, decimals, and ratios:

Observed Symptom / Key Press	Cognitive Cause	Remediation Action
1. Entered 3.4 for 3/4	Used single dot (decimal syntax).	Use two dots! [.] 3 [.] 4 is 3/4.
2. Result of 1/2 × 2/3 shows 2/6 instead of 1/3	Confused unreduced default with error.	Calculator preserves your steps! Tap [g] [SIMP] !
3. [g] [SIMP] flashes LOWEST TERMS without changing digits	Fraction is already irreducible.	3/7 has no common factors; it is already in lowest terms.
4. Screen displays decimal 0.75 when fraction was wanted	In decimal display mode.	Tap [FDISP] to toggle display to fraction!
5. Added numerators & denoms: 1/2 + 1/4 = 2/6	Treating fractions as disconnected numbers.	Use Fraction Towers in the Twin Comparator Well!
6. Confused ratio 3:5 with fraction 3/5	Part-to-part vs. part-to-whole confusion.	3:5 has 8 total parts! The fraction of the whole is 3/8!
7. Wanted mixed number 2 3/4 but saw 11/4	Screen in improper fraction mode.	Tap [a ⌧/c] to toggle to mixed number display!
8. Percent tip calculated but total bill missing	Base in Register Y was lost by clearing screen.	Base stays in Register Y! Just tap [+] to add tip to bill!
9. Cannot find LCD of 8 and 12 on scratch paper	Manually guessing multiples.	Use hardware key: 8 [ENTER] 12 [f] [LCM] → 24!

Observed Symptom / Key Press	Cognitive Cause	Remediation Action
10. Saw `0.3333333333` without knowing if it repeats	Converting 1/3 to decimal display.	Notice the **`[f] [0.3]`** vinculum bar on the LCD showing repeating decimals!

5.10 Comprehensive Worked Reference Problems (50 Elementary Reference Problems)

Hands-On Studio Proof: Blocks → Calculator

Step 1 (Physical Concrete Intuition): Take your 84.0 mm Fraction Studio kit. Place three 1/4 towers (Cobalt Blue, 21.0 mm × 3 = 63.0 mm) into Well A of the Twin Comparator. In Well B, place two 1/3 towers (Solar Yellow, 28.0 mm × 2 = 56.0 mm). Run your index finger across the top: Well A protrudes above Well B by exactly 7.0 mm. Drop one Lilac 1/12th tile (7.0 mm) into Well B: the surface becomes perfectly, seamlessly smooth! Your fingertips have physically proven that (3 / 4) - (2 / 3) = (1 / 12).

Step 2 (The Representational Bridge): Enter the physical experiment into your SC-6 using two-dot syntax: `. 3 . 4 [ENTER] . 2 . 3 [-]`. The transflective dot-matrix LCD displays `1/12` instantly. Tap **`[FDISP]`** : the display shifts to `0.083`̄ with the repeating vinculum bar illuminated over the digit 3!

Step 3 (Scaling on the Calculator): Try this with fractional quantities that cannot fit on a desk—such as surveying an agricultural plot: `. 17 . 24 [ENTER] . 11 . 36 [-]` → `29/72`! The exact same proportional intuition protects your reasoning across any denominator.

5.10.1 Expedition 1: The Master Pastry Chef's Banquet (Problems 5.1–5.10)

Mission Briefing: You are the executive pastry chef designing artisanal cakes, tart glazes, and tiered wedding confections for a grand gala. Baking requires exacting precision: converting improper cups of flour into mixed numbers, reducing fractional vanilla extracts, and toggling between metric decimals and traditional baker's fractions without spilling a drop.

Foundational Keystroke Walkthroughs: Syntax & Screen Verification

Problem 5.1: Vanilla Glaze Cup Measurement (5/8 Cup)

As executive pastry chef preparing glaze for the grand gala, you need exactly (5 / 8) cup of Madagascar vanilla bean glaze. Before touching the keys, stack five 1/8 Fraction Studio blocks (5 × 10.5 mm = 52.5 mm) to verify the physical height against the 84 mm master whole. Then key in the proper fraction using two-dot syntax and verify its rational display on the screen. On your SC-6, key in **`[.] 5 [.] 8 [ENTER]`** → `5/8`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[.] 5 [.] 8`	0	0	0	5/8	Two-dot syntax parses numerator 5 and denominator 8 into active X
`[ENTER]`	0	0	5/8	5/8	Lift fraction to holding Register Y; verified as exact rational quantity

The transflective display confirms X = 5/8 cup in pristine rational notation without decimal approximation.

Problem 5.2: Scone Flour Batch Scaling (3 (2 / 5) Cups)

A catering banquet batch requires 3 (2 / 5) cups of sifted pastry flour for artisanal currant scones. Place 3 full 1-Whole towers (84 mm each) alongside two 1/5 fractional blocks to visualize the mixed quantity, then key in the mixed number using two-dot syntax and toggle to an improper fraction for bulk packaging. On the SC-6 keypad, enter **`[3] [.] 2 [.] 5 [ENTER] [f] [d/c]`** → 17/5.

Enter `3 . 2 . 5` (T: 0, Z: 0, Y: 0, X: 3 2/5), press **[ENTER]** (T: 0, Z: 0, Y: 3 2/5, X: 3 2/5), then tap **`[f] [d/c]`** to toggle to improper fraction form (T: 0, Z: 0, Y: 3 2/5, X: 17/5), confirming (3 × 5 + 2)/5 = 17/5 cups ready for bulk commissary packaging.

Problem 5.3: Bulk Sugar Syrup Reduction ((48 / 18) Pints)

A large copper kettle yields (48 / 18) pints of concentrated sugar syrup. Model small with your Fraction Studio kit by placing four 1/6 blocks (56.0 mm) beside two 1/3 blocks (56.0 mm) to see common-factor reduction physically, then scale up on your SC-6 to reduce (48 / 18) to lowest terms and display it as a mixed number. Turning to your SC-6, key in **`[.] 48 [.] 18 [ENTER] [g] [SIMP]`** → 8/3.

Enter `. 48 . 18` (T: 0, Z: 0, Y: 0, X: 48/18), press **[ENTER]** (T: 0, Z: 0, Y: 48/18, X: 48/18), tap **`[g] [SIMP]`** to extract common factor 6 leaving lowest terms (T: 0, Z: 0, Y: 48/18, X: 8/3), and press **`[a ⌧/c]`** to convert to mixed number (T: 0, Z: 0, Y: 48/18, X: 2 2/3 pints).

Problem 5.4: Almond Extract Baker's Decimal (5/8 oz → 0.625 oz)

A commercial digital kitchen scale registers in thousandths of an ounce. To calibrate the recipe's (5 / 8) ounce of almond extract, place five 1/8 towers in the comparator well (52.5 mm) to observe the 0.625 ratio against the 84.0 mm datum, then convert the recipe fraction directly on the stack. With your SC-6 ready, enter **`[.] 5 [.] 8 [ENTER] [FDISP]`** → 0.625.

Enter `. 5 . 8` followed by **[ENTER]** (T: 0, Z: 0, Y: 5/8, X: 5/8), then tap **`[FDISP]`** for an instant toggle to decimal readout (T: 0, Z: 0, Y: 5/8, X: 0.625), giving the digital scale equivalent of 0.625 oz.

Problem 5.5: Heavy Cream Decimal Conversion (0.375 Qt → 3/8 Qt)

An automated cream dispenser reports 0.375 quarts remaining in its refrigeration chamber. Align a 31.5 mm height with three 1/8 blocks in your comparator to verify 3/8 equivalence, then convert this decimal reading into an exact common fraction for the pastry chef's logbook. Step over to your SC-6 and key in **`[.] 375 [ENTER] [FDISP]`** → 3/8.

Key `.375` followed by **[ENTER]** (T: 0, Z: 0, Y: 0.375, X: 0.375), then tap **`[FDISP]`** to toggle the sensor reading into its exact rational equivalent (T: 0, Z: 0, Y: 0.375, X: 3/8 qt).

Problem 5.6: Butter Block Weight Conversion (2 (3 / 4) lbs → 2.75 lbs)

A grand brioche dough requires 2 (3 / 4) pounds of European churned butter. Assemble two full whole towers plus three 1/4 blocks (231 mm = 2.75 × 84 mm), then toggle the mixed fraction into decimal pounds for the automated commercial mixer. Now compute it on your SC-6: **`[2] [.] 3 [.] 4 [ENTER] [FDISP]`** → 2.75.

Key `2 . 3 . 4` followed by **[ENTER]** (T: 0, Z: 0, Y: 2 3/4, X: 2 3/4), then press **`[FDISP]`** to convert instantly to decimal (T: 0, Z: 0, Y: 2 3/4, X: 2.75 lbs).

Problem 5.7: Third-Batch Sourdough Starter (1/3 → 0.333...)

A sourdough brioche recipe divides a mature sourdough culture into 3 equal portions ((1 / 3) each). Place one 1/3 tower (28.0 mm) in the comparator well and observe that it cannot be formed by a finite sum of tenths or hundredths, then inspect the repeating decimal on the SC-6 display. Run the sequence on your SC-6: **[.] 1 [.] 3 [ENTER] [FDISP]** → `0.3333333333`.

Key `. 1 . 3` followed by **[ENTER]** (T: 0, Z: 0, Y: 1/3, X: 1/3), then press **[FDISP]** (T: 0, Z: 0, Y: 1/3, X: 0.3333333) to reveal the transflective display's active vinculum bar indicator illuminated over the repeating digit 3 (0.3■).

Problem 5.8: Brioche Egg Wash Fraction Simplification ((35 / 50) Batch)

An assistant pastry chef prepares (35 / 50) of a standard catering egg-wash batch. Place 7 tenth-bars (7 × 8.4 mm = 58.8 mm) in the comparator channel to visualize the simplified target, then scale to fifty-part batch units on your SC-6 and use hardware **[g] [SIMP]** to reduce (35 / 50) to tenths. Verify the calculation on your SC-6: **[.] 35 [.] 50 [ENTER] [g] [SIMP]** → `7/10`.

Key `. 35 . 50` followed by **[ENTER]** (T: 0, Z: 0, Y: 35/50, X: 35/50), then tap **[g] [SIMP]** (T: 0, Z: 0, Y: 35/50, X: 7/10) to extract common factor 5 in a single keystroke, recording 7/10 batch in the kitchen log.

Problem 5.9: Choux Pastry Bulk Inventory (23/6 Cups → 3 5/6 Cups)

An evening inventory tally reveals (23 / 6) cups of clarified butter used across all choux pastry batches. Model small with your kit by bundling 6 sixth-blocks (6 × 14.0 mm = 84.0 mm) against 1 Whole tower to see how every 6 sixths form a whole, then scale up on your SC-6 to convert (23 / 6) into a chef-friendly mixed number. Test this directly on your SC-6: **[.] 23 [.] 6 [ENTER] [a ⌧/c]** → `3 5/6`.

Key `. 23 . 6` followed by **[ENTER]** (T: 0, Z: 0, Y: 23/6, X: 23/6), then tap **[a ⌧/c]** (T: 0, Z: 0, Y: 23/6, X: 3 5/6) to decompose into whole and remainder parts: 3 (5 / 6) cups.

Problem 5.10: Single-Step Cocoa Glaze Fraction Reduction via [GCF] ((24 / 36) Liter)

A chocolate ganache glaze recipe uses (24 / 36) liter of warm cream. Using Prime Studio blocks, the largest single block unit that evenly measures both 24 and 36 units is the 12-unit block. Use hardware **[GCF]** to extract this common factor and simplify the recipe fraction in a single step. Bring this to the SC-6 stack: `24 [ENTER] 36 [GCF]` → `12`.

Running this sequence (T: 0, Z: 0, Y: 0, X: 12), extracting gcd(24, 36) = 12 directly, which instantly reduces 24/36 to the irreducible fraction 2/3 liter.

5.10.2 Expedition 2: The Backyard Treehouse Workshop (Problems 5.11–5.20)

Mission Briefing: You are framing beams, laying deck planks, and cutting roof rafters for an elevated treehouse fortress. Construction lumber is measured in fractional inches and yards: eighths, sixteenths, quarters, and twelfths. You must combine board lengths, subtract cutoffs, and reconcile unlike denominators with zero guesswork so every joint fits flush.

Problem 5.11: Like Denominator Deck Plank Addition ((2 / 5) + (1 / 5) = (3 / 5))

You are laying cedar deck planks across the elevated treehouse floor frame. You fasten a plank covering (2 / 5) yard of the deck opening in the morning, and another plank covering (1 / 5) yard after lunch. In your Fraction Studio Comparator Well, stack two 1/5 blocks with one 1/5 block to reach three 1/5 blocks ((3 / 5)), then combine the measurements on the stack. On your SC-6, enter **[.] 2 [.] 5 [ENTER] [.] 1 [.] 5 [+]** → 3/5.

Enter . 2 . 5 followed by **[ENTER]** (T: 0, Z: 0, Y: 2/5, X: 2/5), then add the afternoon plank with . 1 . 5 [+] (T: 0, Z: 0, Y: 0, X: 3/5), confirming a total covered span of 3/5 yard.

Problem 5.12: Like Denominator Window Trim Sum ((2 / 4) + (2 / 4) = (4 / 4))

Cutting window trim for the treehouse lookout openings requires two pieces of trim, each (2 / 4) foot long. Place two 2/4 block pairs side-by-side with the 84 mm whole unit block in the Comparator Well to see they match 1 whole, then combine them on the stack to experience the unreduced default policy. Execute the sequence on your SC-6: **[.] 2 [.] 4 [ENTER] [.] 2 [.] 4 [+]** → 4/4.

Enter . 2 . 4 followed by **[ENTER]** (T: 0, Z: 0, Y: 2/4, X: 2/4), press . 2 . 4 [+] (T: 0, Z: 0, Y: 0, X: 4/4) to preserve the unreduced sum (4 / 4), and tap **[g] [SIMP]** (T: 0, Z: 0, Y: 0, X: 1) to reduce to 1 whole foot.

Problem 5.13: Mixing Roof Weatherproofing Sealant ((3 / 4) + (2 / 5) = 1 (3 / 20))

Mixing weatherproofing roof sealant in your workshop bucket requires combining (3 / 4) gallon of natural pine resin with (2 / 5) gallon of boiled linseed oil. In the Comparator Well, a 3/4 tower (63 mm) and a 2/5 tower (33.6 mm) combine to exceed the 84 mm whole datum, demanding an improper or mixed representation. On your SC-6, key in **[.] 3 [.] 4 [ENTER] [.] 2 [.] 5 [+] [a b/c]** → 1 3/20.

Enter . 3 . 4 followed by **[ENTER]** (T: 0, Z: 0, Y: 3/4, X: 3/4), add . 2 . 5 [+] (T: 0, Z: 0, Y: 0, X: 23/20), and tap **[a b/c]** (T: 0, Z: 0, Y: 0, X: 1 3/20) to convert to 1 (3 / 20) gallons of sealant.

Problem 5.14: Rafter Bolt Hole Spacing via [f] [LCM] (LCM(8, 12) = 24)

You need to drill pilot holes for structural rafter bolts spaced every (1 / 8) foot along the ridge beam and every (1 / 12) foot along the ceiling brace. Comparing 8-unit and 12-unit rods reveals the shortest combined span where both line up flush is 24 units. Use hardware **[f] [LCM]** to find the exact common denominator distance. On the SC-6 keypad, enter **[8] [ENTER] 12 [f] [LCM]** → 24.

Running this sequence (T: 0, Z: 0, Y: 0, X: 24), confirming that alignment occurs at 24ths (LCD = 24).

Problem 5.15: Steel Gusset Bracket Alignment ((3 / 8) + (5 / 12) = (19 / 24))

You join two custom steel gusset plates measuring (3 / 8) inch and (5 / 12) inch thick to reinforce the treehouse corner post. In the Comparator Well, three 1/8 blocks (31.5 mm) and five 1/12 blocks (35.0 mm) stack to 66.5 mm (19 × 3.5 mm half-twelfth increments). Using your calculated common denominator of 24, add their thicknesses together. Turning to your SC-6, key in **[.] 3 [.] 8 [ENTER] [.] 5 [.] 12 [+]** → 19/24.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[.] 3 [.] 8 [ENTER]	0	0	3/8	3/8	Enter first bracket plate thickness (3 / 8) in
[.] 5 [.] 12 [+]	0	0	0	19/24	Add second bracket plate (5 / 12) in; stack finds 24ths LCD

The live stack transparently unites unlike denominators into the exact rational sum X = 19/24 inch.

Problem 5.16: Balcony Safety Post Assembly (1 (1 / 2) + 2 (1 / 3) = 3 (5 / 6))

Measuring support timbers for the lookout balcony railing involves joining a 1 (1 / 2)-foot base post with a 2 (1 / 3)-foot upper safety rail extension. Stack 1 whole block plus a 1/2 block alongside 2 whole blocks plus a 1/3 block in the wells to verify their combined height of 3 wholes plus five 1/6 blocks, then evaluate on the stack. With your SC-6 ready, enter **[1] [.] 1 [.] 2 [ENTER] [2] [.] 1 [.] 3 [+] [a b/c]** → 3 5/6.

Key 1 . 1 . 2 followed by **[ENTER]** (T: 0, Z: 0, Y: 1 1/2, X: 1 1/2), add 2 . 1 . 3 [+] (T: 0, Z: 0, Y: 0, X: 23/6), and convert with **[a b/c]** (T: 0, Z: 0, Y: 0, X: 3 5/6) to obtain the assembled post height of 3 (5 / 6) feet.

Problem 5.17: Pine Fascia Board Trim Cut ((3 / 4) - (1 / 4) = (2 / 4))

You have a (3 / 4)-foot pine fascia strip and trim off (1 / 4) foot to clear the tree's main trunk. In the Comparator Well, removing one 1/4 block leaves two 1/4 blocks (1/2 block). Compute the remaining strip on your stack to verify the unreduced fraction before simplifying. Step over to your SC-6 and key in **[.] 3 [.] 4 [ENTER] [.] 1 [.] 4 [-]** → 2/4.

Enter . 3 . 4 followed by **[ENTER]** (T: 0, Z: 0, Y: 3/4, X: 3/4), subtract . 1 . 4 [-] (T: 0, Z: 0, Y: 0, X: 2/4), and tap **[g] [SIMP]** (T: 0, Z: 0, Y: 0, X: 1/2) to reach the final clearance length of 1/2 foot.

Problem 5.18: Heavy Framing Stud Cutoff (5 (1 / 3) - 2 (3 / 4) = 2 (7 / 12))

From a 5 (1 / 3)-foot heavy framing stud, you saw off 2 (3 / 4) feet to construct a diagonal cross-brace. With unlike denominators 3 and 4, the subtraction requires twelfths: borrowing 1 whole transforms the fraction difference into 2 (7 / 12). Execute the mixed subtraction cleanly on the stack. Now compute it on your SC-6: **[5] [.] 1 [.] 3 [ENTER] [2] [.] 3 [.] 4 [-] [a b/c]** → 2 7/12.

Key 5 . 1 . 3 followed by **[ENTER]** (T: 0, Z: 0, Y: 5 1/3, X: 5 1/3), subtract 2 . 3 . 4 [-] (T: 0, Z: 0, Y: 0, X: 31/12), and press **[a b/c]** (T: 0, Z: 0, Y: 0, X: 2 7/12) to determine the remaining board length of 2 (7 / 12) feet.

Problem 5.19: Doorway Weather-Stripping Cutout (1 - (3 / 8) = (5 / 8))

You have 1 full roll of heavy canvas weather-stripping for the treehouse doorway. You cut off (3 / 8) of the roll to seal the upper sill. Place one whole 84 mm datum block in the well and remove a 3/8 block (31.5 mm); the remaining gap is filled precisely by a 5/8 block (52.5 mm). Verify the subtraction on the stack. Run the sequence on your SC-6: **[1] [ENTER] [.] 3 [.] 8 [-]** → 5/8.

Enter 1 [ENTER] (T: 0, Z: 0, Y: 1, X: 1), then subtract . 3 . 8 [-] (T: 0, Z: 0, Y: 0, X: 5/8), leaving exactly 5/8 of the roll.

Problem 5.20: Chained Rope Ladder Splicing ((1 / 2) + (1 / 4) + (1 / 8) = (7 / 8))

Constructing a stepped rope ladder to reach the trapdoor requires splicing three rope sections measuring (1 / 2) yard, (1 / 4) yard, and (1 / 8) yard. In the Comparator Well, stacking a 1/2 block, a 1/4 block, and a 1/8 block matches seven 1/8 blocks (73.5 mm). Chain them smoothly on the stack without intermediate resets. Verify the calculation on your SC-6: `[.] 1 [.] 2 [ENTER] [.] 1 [.] 4 [+] [.] 1 [.] 8 [+]` → 7/8.

Enter `. 1 . 2` followed by **[ENTER]** (T: 0, Z: 0, Y: 1/2, X: 1/2), add `. 1 . 4 [+]` (T: 0, Z: 0, Y: 0, X: 3/4), and add `. 1 . 8 [+]` (T: 0, Z: 0, Y: 0, X: 7/8) to arrive at the total spliced length of 7/8 yard.

5.10.3 Expedition 3: The Custom Bicycle Gear Shop (Problems 5.21–5.28)

Mission Briefing: You are a race mechanic tuning chainrings, freewheel cassettes, and planetary hub gears. Gear inches and mechanical advantage require multiplying fractional gear ratios, dividing wheel circumferences, and simplifying mechanical reductions on the SC-6 stack without rounding errors.

Problem 5.21: Multiplying Carbon Mudguard Dimensions ((2 / 3) × (3 / 4) = (6 / 12) → (1 / 2))

Cutting a custom rectangular carbon-fiber mudguard patch measuring (2 / 3) meter wide by (3 / 4) meter long requires finding the surface area in square meters. In 2D space, a rectangle (2 / 3) high by (3 / 4) wide covers 6 out of 12 equal sub-rectangles, exactly half of a unit square. Multiply the dimensions on the stack to observe unreduced fraction preservation. Test this directly on your SC-6: `[.] 2 [.] 3 [ENTER] [.] 3 [.] 4 [×] [g] [SIMP]` → 1/2.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[.] 2 [.] 3` **[ENTER]**	0	0	2/3	2/3	Enter width (2 / 3) m into Register Y
`[.] 3 [.] 4` **[×]**	0	0	0	6/12	Multiply by length (3 / 4) m; stack yields unreduced (6 / 12)
[g] **[SIMP]**	0	0	0	1/2	Tap **[g]** **[SIMP]** to reduce (6 / 12) to (1 / 2) m^2

The SC-6 preserves the unreduced product 6/12 before simplifying to X = 1/2 m^2 upon tapping **[g]** **[SIMP]**.

Problem 5.22: Scaling Suspension Fork Damper Fluid (2 (1 / 4) × 1 (1 / 2) = 3 (3 / 8))

Mixing synthetic damper oil for high-performance downhill suspension forks requires scaling the standard cross-country volume of 2 (1 / 4) ounces by a factor of 1 (1 / 2). Scaling two 1-unit blocks and one 1/4 block by 1.5 in the Comparator Well yields three whole units and a 3/8 block (3 (3 / 8)). Multiply the mixed numbers directly on the stack. Bring this to the SC-6 stack: **[2]** `[.] 1 [.] 4 [ENTER]` **[1]** `[.] 1 [.] 2 [×]` **[a b/c]** → 3 3/8.

Enter `2 . 1 . 4` followed by **[ENTER]** (T: 0, Z: 0, Y: 2 1/4, X: 2 1/4), multiply by `1 . 1 . 2 [×]` (T: 0, Z: 0, Y: 0, X: 27/8), and press **[a b/c]** (T: 0, Z: 0, Y: 0, X: 3 3/8) to obtain 3 (3 / 8) ounces of damper fluid.

Problem 5.23: Bike Storage Rack Slat Saw Kerf (18 (3 / 8) + (1 / 8) = 18 (1 / 2))

Building oak wall racks to hang customer bikes requires cutting mounting slats measuring 18 (3 / 8) in each, with a table saw blade kerf removing (1 / 8) in per cut. In the Comparator Well, three 1/8 blocks plus one 1/8 block equal four 1/8 blocks (1/2 block). Sum the dimensions to find total stock consumed per slat. On your SC-6, enter `18 [.] 3 [.] 8 [ENTER] [.] 1 [.] 8 [+] [a b/c]` → `18 1/2`.

Enter `18 . 3 . 8` followed by **[ENTER]** (T: 0, Z: 0, Y: 18 3/8, X: 18 3/8), add `. 1 . 8 [+]` (T: 0, Z: 0, Y: 0, X: 148/8), and convert with **[a b/c]** (T: 0, Z: 0, Y: 0, X: 18 1/2) to establish an exact per-slat allowance of 18 (1 / 2) inches.

Problem 5.24: Slats Cut from an 8-Foot Oak Board (96 ÷ 18.5)

To determine how many 18 (1 / 2) in bike rack slats can be cut from an eight-foot (96 in) oak board, lay five 18.5-unit segments against a 96-unit rule to observe that a partial remnant remains. Execute the sequence on your SC-6: `96 [ENTER] 18 [.] 1 [.] 2 [÷]`.

Enter `96 [ENTER]` (T: 0, Z: 0, Y: 96, X: 96) and divide by `18 . 1 . 2 [÷]` (T: 0, Z: 0, Y: 0, X: 5.189), confirming that exactly 5 whole slats can be cut.

Problem 5.25: Scrap Wood Offcut Calculation (96 - 5 × 18.5)

Evaluating the leftover scrap tail piece from the 96-inch board requires subtracting the five full slats (5 × 18.5 = 92.5 in) from the 96-inch stock length. On your SC-6, key in **[5] [ENTER] 18 [.] 1 [.] 2 [×] 96 [x↔y] [-] [a b/c]** → `3 1/2`.

Enter `5 [ENTER]` (T: 0, Z: 0, Y: 5, X: 5), multiply by `18 . 1 . 2 [×]` (T: 0, Z: 0, Y: 0, X: 92 1/2), then key `96 [x⇄y] -` (T: 0, Z: 0, Y: 0, X: 3 1/2) to isolate the 3 (1 / 2) in offcut.

Problem 5.26: Bike Frame Polish Bottle Portions ((2 / 3) ÷ (1 / 4) = 2 (2 / 3))

You have (2 / 3) liter of ceramic frame polish, and each bicycle restoration consumes (1 / 4) liter. In the Comparator Well, two 1/3 blocks (56 mm) hold two 1/4 blocks (42 mm) with 14 mm leftover ((2 / 3) of a 1/4 block). Divide the fractional quantities on the stack. On the SC-6 keypad, enter **[.] 2 [.] 3 [ENTER] [.] 1 [.] 4 [÷] [a b/c]** → `2 2/3`.

Enter `. 2 . 3` followed by **[ENTER]** (T: 0, Z: 0, Y: 2/3, X: 2/3), divide by `. 1 . 4 [÷]` (T: 0, Z: 0, Y: 0, X: 8/3), and convert with **[a b/c]** (T: 0, Z: 0, Y: 0, X: 2 2/3), providing enough polish for 2 complete bicycles with (2 / 3) of a job remaining.

Problem 5.27: Braided Shifter Cable Housing Cuts (4 (1 / 2) ÷ (3 / 4) = 6)

A 4 (1 / 2)-foot coil of compressionless shifter housing must be cut into (3 / 4)-foot housing loops for rear derailleur bends. Nine halves contain eighteen quarters, which divided by three quarters yields exactly 6 segments. Turning to your SC-6, key in **[4] [.] 1 [.] 2 [ENTER] [.] 3 [.] 4 [÷]** → `36/6`.

Enter `4 . 1 . 2` followed by **[ENTER]** (T: 0, Z: 0, Y: 4 1/2, X: 4 1/2), then divide by `. 3 . 4 [÷]` (T: 0, Z: 0, Y: 0, X: 6), producing exactly 6 finished cable housing loops.

Problem 5.28: Three-Stage Planetary Hub Reduction ((1 / 2) × (2 / 3) × (3 / 4) = (1 / 4))

Calculating the overall gear reduction through a three-stage internal planetary hub with stage ratios of (1 / 2), (2 / 3), and (3 / 4) demonstrates physical numerator-denominator cancellation on the stack. With your SC-6 ready, enter **[.] 1 [.] 2 [ENTER] [.] 2 [.] 3 [×] [.] 3 [.] 4 [×] [g] [SIMP]** → 1/4.

Enter . 1 . 2 followed by **[ENTER]** (T: 0, Z: 0, Y: 1/2, X: 1/2), multiply by . 2 . 3 [×] (T: 0, Z: 0, Y: 0, X: 2/6), multiply by . 3 . 4 [×] (T: 0, Z: 0, Y: 0, X: 6/24), and tap **[g] [SIMP]** (T: 0, Z: 0, Y: 0, X: 1/4) to simplify the total reduction to 1/4.

5.10.4 Expedition 4: The Farmer's Market & Currency Counter (Problems 5.29–5.36)

Mission Briefing: You are managing the financial register at a bustling regional growers' market. Shoppers purchase organic produce, artisanal honey, and handmade pottery with promotional discounts, local sales taxes, and customer gratuities. Use the SC-6 percent key **[%]** to compute deductions and compound totals directly on the stack without losing the starting price.

Problem 5.29: Market Cafe 15% Gratuity Calculation

At the bustling market cafe counter, you calculate a 15% tip on a $48.00 lunch order for the farm crew. Model the base bill with four $10 tokens and eight $1 tokens: taking 10% ($4.80) plus half of that (5% = $2.40) gives a $7.20 tip. On the SC-6, computing percent preserves the base in Register Y, allowing an instant total. Step over to your SC-6 and key in 48 [ENTER] 15 [%] → X = $7.20 tip. Press **[+]** → X = $55.20 total!.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
48 **[ENTER]**	0	0	48	48	Enter base restaurant bill into holding Register Y
15 **[%]**	0	0	48	7.20	Calculate 15% tip (0.15 × 48 = 7.20); base $48 preserved in Y
[+]	0	0	0	55.20	Add tip directly to base bill in Y without re-entering numbers!

Holding the base in Register Y allows a single **[+]** stroke to yield the total bill of $55.20.

Problem 5.30: Farm Apparel 20% Discount Coupon

At the farm apparel stall, a heavy wool work coat costs $85.00. You apply a 20% off coupon. Modeling the $85 coat with base-10 blocks shows that taking 2 tens out of every hundred saves $17.00. Execute the deduction directly on the stack. Now compute it on your SC-6: 85 [ENTER] 20 [%] → X = $17.00 discount. Press **[-]** → X = $68.00 sale price!.

Enter 85 [ENTER] (T: 0, Z: 0, Y: 85, X: 85), calculate discount with 20 [%] (T: 0, Z: 0, Y: 85, X: 17.00), and press **[-]** (T: 0, Z: 0, Y: 0, X: 68.00) to subtract savings in a single keystroke.

Problem 5.31: Utility Garden Cart 8.5% Sales Tax

Purchasing a $120.00 heavy-duty market garden cart incurs an 8.5% sales tax. The tax represents $8.50 per hundred dollars plus $1.70 on the remaining $20 ($10.20 tax). Compute the tax and final checkout total. Run the sequence on your SC-6: 120 [ENTER] 8.5 [%] → X = $10.20 tax. Press **[+]** → X = $130.20 total!.

Enter `120 [ENTER]` (T: 0, Z: 0, Y: 120, X: 120), compute tax via `8.5 [%]` (T: 0, Z: 0, Y: 120, X: 10.20), and press **[+]** (T: 0, Z: 0, Y: 0, X: 130.20) to combine base price and tax directly.

Problem 5.32: Honey Batch Quality Inspection Percentage

At the artisan honey booth, quality control inspects jars for crystal clarity: 42 out of 50 jars pass the golden crest inspection. Model small with your kit ≤ 24 tiles: place 4 red counters on a 5-frame (or 8 on a ten-frame) to model that four out of five equal 80%, while 42 out of 50 simplifies to (21 / 25) = 84%. Then scale big on StackCalc to verify the full 50-jar inspection lot. Verify the calculation on your SC-6: `42 [ENTER] 50 [÷] 100 [×]`.

Enter `42 [ENTER] 50 [÷]` (T: 0, Z: 0, Y: 0, X: 0.84), then scale with `100 [×]` (T: 0, Z: 0, Y: 0, X: 84) to verify an 84% certification rate.

Problem 5.33: Nursery Sunflower Growth Percent Increase

At the plant nursery stall, a prize potted sunflower grew from 80 cm last week to 100 cm this week. Comparing an 80 cm rod with a 100 cm rod shows the 20 cm growth represents one fourth (25%) of the baseline height. Compute the growth percentage. Test this directly on your SC-6: `100 [ENTER] 80 [-] 80 [÷] 100 [×]`.

Subtract `100 [ENTER] 80 [-]` (T: 0, Z: 0, Y: 0, X: 20), divide by baseline `80 [÷]` (T: 0, Z: 0, Y: 0, X: 0.25), and scale by `100 [×]` (T: 0, Z: 0, Y: 0, X: 25) to establish 25% height growth.

Problem 5.34: 30% Off End-of-Season Clearance

A pair of leather work boots originally $110.00 is marked 30% off on the clearance shelf. With eleven $10 bills, removing 30% removes three $10 bills and $3 from the last bill, saving $33 and leaving $77. Evaluate the transaction on the stack. Bring this to the SC-6 stack: `110 [ENTER] 30 [%] [-]`.

Key `110 [ENTER] 30 [%]` (T: 0, Z: 0, Y: 110, X: 33.00), then tap **[-]** (T: 0, Z: 0, Y: 0, X: 77.00) to deduct the discount, yielding the final price of $77.00.

Problem 5.35: Cooperative Membership Attendance

At the regional growers' co-op of 450 members, 60% attend the annual harvest banquet. Partitioning 450 members into tenths gives 45 members per 10%; six groups of 45 equal 6 × 45 = 270 attendees. On your SC-6, enter `450 [ENTER] 60 [%]`.

Enter `450 [ENTER]` (T: 0, Z: 0, Y: 450, X: 450) and tap `60 [%]` (T: 0, Z: 0, Y: 450, X: 270) to compute attendance at 270 members.

Problem 5.36: Compound Discount: Solar Battery Station (20% then 10%)

At the market hardware depot, a $200.00 solar backup battery is discounted 20%, and an additional 10% co-op member discount applies to the sale price. Taking 20% off $200 saves $40 ($160 sale price), and 10% off $160 saves $16, resulting in $144. Execute the sequence on your SC-6: `200 [ENTER] 20 [%] [-] 10 [%] [-]`.

Enter `200 [ENTER] 20 [%] [-]` (T: 0, Z: 0, Y: 0, X: 160), then apply the secondary discount with `10 [%] [-]` (T: 0, Z: 0, Y: 0, X: 144.00) to reach the final checkout cost of $144.00.

5.10.5 Expedition 5: The Architectural Scale Model Lab (Problems 5.37–5.44)

Mission Briefing: You are an architectural model maker building scaled blueprints and miniature prototypes of bridges, towers, and civic stadiums. Scale models depend on exact ratios and proportions (1:50, 3:8, unit rates). You will use the SC-6 Ratio Mode **`[g] [a:b]`** and ratio tables to scale dimensions up and down with structural integrity.

Problem 5.37: Model Drawbridge Motor Gear Ratio (12:36 → 1:3)

In an architectural scale model, a motorized drawbridge operates using a 12-tooth motor pinion and a 36-tooth sector gear. Model small with your kit ≤ 24 tiles: lay 1 tile next to 3 tiles to visualize the simplified 1:3 ratio, or set 12 unit tiles to see that three groups of 12 equal 36. Enter the teeth counts into Ratio Mode and simplify directly on the stack. On your SC-6, key in **`[.] 12 [.] 36 [g] [a:b] [g] [SIMP]`** → `1:3`.

Enter `. 12 . 36` (T: 0, Z: 0, Y: 0, X: 12/36), press **`[g] [a:b]`** (T: 0, Z: 0, Y: 0, X: 12:36) to switch to Ratio Mode, and tap **`[g] [SIMP]`** (T: 0, Z: 0, Y: 0, X: 1:3) to reduce by common factor 12 to lowest terms 1:3.

Problem 5.38: Winch Rotation Speed via Gear Ratio

The drawbridge motor spins at 1,800 RPM. With the 1:3 gear reduction ratio, the large sector gear turns once for every 3 turns of the pinion, dividing motor speed by 3. Compute final winch speed on the stack. On the SC-6 keypad, enter `1800 [ENTER] 3 [÷]`.

Enter `1800 [ENTER] 3 [÷]` (T: 0, Z: 0, Y: 0, X: 600), determining a smooth winch rotation speed of 600 RPM.

Problem 5.39: Living-Wall Nutrient Solution Dilution (2:15)

Mixing liquid nutrient solution for an automated living-wall architectural model requires 2 parts nutrient concentrate with 15 parts water for a 34-liter irrigation reservoir. Combining 2 green tiles and 15 blue tiles establishes 17 total parts, where each part equals 34 ÷ 17 = 2 liters: **Keystrokes:**

1. Total parts: `2 [ENTER] 15 [+]` → 17 parts.
2. Volume per part: `34 [ENTER] 17 [÷]` → 2.0 L/part.
3. Concentrate: `2 [ENTER] 2 [×]` → 4.0 L.
4. Water: `15 [ENTER] 2 [×]` → 30.0 L.

Enter `2 [ENTER] 15 [+]` (T: 0, Z: 0, Y: 0, X: 17), then divide the reservoir volume with `34 [x⇄y] ÷` (T: 0, Z: 0, Y: 0, X: 2), confirming 4.0 L of concentrate and 30.0 L of water.

Problem 5.40: Miniature Promenade Mortar Mix (1:2:3)

Casting miniature stone promenade pavers for a civic plaza model requires blending cement, sand, and fine aggregate in a 1:2:3 ratio to produce 12 cubic feet of mortar. Stacking 1 gray tile (cement), 2 gold tiles (sand), and 3 white tiles (gravel)

confirms 6 total parts, so each recipe part equals 2 cubic feet. Evaluate the ratio batching on the stack. Turning to your SC-6, key in `1 [ENTER] 2 [+] 3 [+] 12 [x⇔y] [÷]` → `2`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
1 **[ENTER]** 2 +	0	0	0	3	Add cement and sand parts (1 + 2 = 3)
3 **[+]**	0	0	0	6	Add gravel parts: 3 + 3 = 6 total parts
12 **[x⇔y]** ÷	0	0	0	2	Divide 12 cu ft batch by 6 parts to find 2 cu ft per part

Each part equals 2 cu ft, allocating 2 cu ft cement, 4 cu ft sand, and 6 cu ft gravel.

Problem 5.41: Model Shop Studio Snack Mix (16 cups)

During drafting sessions in the model shop, you prepare 16 cups of snack mix: (3 / 8) dried cranberries, (1 / 4) almonds, and (3 / 8) chocolate drops. Dividing 16 cups into eighths yields 2 cups per eighth (16 ÷ 8 = 2), so three eighths equal 3 × 2 = 6 cups. Verify the ingredient proportion on the stack. With your SC-6 ready, enter `16 [ENTER] [.] 3 [.] 8 [×]` → `48/8`.

Enter `16 [ENTER]` (T: 0, Z: 0, Y: 16, X: 16) and multiply by `. 3 . 8 [×]` (T: 0, Z: 0, Y: 0, X: 6), allocating exactly 6 cups of cranberries.

Problem 5.42: Facade Stucco Pigment Mixing Ratio (3 (1 / 2) : 1 (3 / 4))

Mixing custom facade stucco pigment for a gallery model combines 3 (1 / 2) pints of base color with 1 (3 / 4) pints of white tint. Because 3 (1 / 2) = (14 / 4) is exactly twice 1 (3 / 4) = (7 / 4), the ingredients form a clean 2:1 proportional ratio. Sum the mixture and evaluate the volume on the stack. Step over to your SC-6 and key in `3 [.] 1 [.] 2 [ENTER] 1 [.] 3 [.] 4 [+] [a b/c]` → `5 1/4`.

Enter `3 . 1 . 2` followed by **[ENTER]** (T: 0, Z: 0, Y: 3 1/2, X: 3 1/2), add `1 . 3 . 4 [+]` (T: 0, Z: 0, Y: 0, X: 21/4), and convert with **[a b/c]** (T: 0, Z: 0, Y: 0, X: 5 1/4) to find 5 (1 / 4) pints total pigment.

Problem 5.43: Regional Map Scale Distance Conversion (1 in = 3 (1 / 2) mi)

On a regional topographical site map, 1 inch represents 3 (1 / 2) miles. A proposed light rail transit corridor measures 4 (1 / 4) inches on the blueprint. Four inches represent 4 × 3.5 = 14 miles, and a quarter inch adds 3.5 ÷ 4 = 0.875 miles, totaling 14 (7 / 8) mi. Scale the map length on the stack. Now compute it on your SC-6: `4 [.] 1 [.] 4 [ENTER] 3 [.] 1 [.] 2 [×] [a b/c]` → `14 7/8`.

Enter `4 . 1 . 4` followed by **[ENTER]** (T: 0, Z: 0, Y: 4 1/4, X: 4 1/4), multiply by `3 . 1 . 2 [×]` (T: 0, Z: 0, Y: 0, X: 119/8), and press **[a b/c]** (T: 0, Z: 0, Y: 0, X: 14 7/8) to establish the real-world corridor distance of 14 (7 / 8) miles.

Problem 5.44: Miniature Transit Layout Splits (1 (1 / 10) + 1 (1 / 6) + 1 (1 / 12) + 1 (1 / 15))

Timing four automated scale tram loops on a miniature transit layout records splits of 1 (1 / 10), 1 (1 / 6), 1 (1 / 12), and 1 (1 / 15) minutes. With common denominator 60 (sixtieths of a minute, or seconds!), the fractional parts sum smoothly to

exact minutes and seconds. Chain the mixed splits on the stack. Run the sequence on your SC-6: `1 [.] 1 [.] 10 [ENTER] 1 [.] 1 [.] 6 [+] 1 [.] 1 [.] 12 [+] 1 [.] 1 [.] 15 [+] [a b/c]` → `4 5/12`.

Enter `1 . 1 . 10` (T: 0, Z: 0, Y: 0, X: 1 1/10), add `1 . 1 . 6 [+]` (T: 0, Z: 0, Y: 0, X: 34/15), add `1 . 1 . 12 [+]` (T: 0, Z: 0, Y: 0, X: 67/20), add `1 . 1 . 15 [+]` (T: 0, Z: 0, Y: 0, X: 53/12), and convert with **`[a b/c]`** (T: 0, Z: 0, Y: 0, X: 4 5/12) to yield a complete transit cycle of 4 (5 / 12) minutes (4 minutes and 25 seconds).

5.10.6 Expedition 6: High-Speed Rational Sprints & Science Olympiad (Problems 5.45–5.50)

Mission Briefing: You represent your academy at the State Mathematics Tournament and Science Olympiad. Under tournament clock constraints, you must solve chained fractional rate problems, compound gear reductions, and harmonic proportions without pencil-and-paper scratch work. Harness the full power of RPN to claim the gold medal.

Problem 5.45: Chained Reciprocal Sum Sprint ((1 / 2) + (1 / 3) + (1 / 6) = 1)

In the tournament mental math sprint, evaluate the classic harmonic unit fraction sum: (1 / 2) + (1 / 3) + (1 / 6). In the Twin Comparator Well, dropping a 1/2 block (42 mm), a 1/3 block (28 mm), and a 1/6 block (14 mm) sums to 42 + 28 + 14 = 84.0 mm, aligning flush with the 1 Whole tower! Chain the fractions on the stack. Verify the calculation on your SC-6: **`[.] 1 [.] 2 [ENTER] [.] 1 [.] 3 [+] [.] 1 [.] 6 [+]`** → `6/6`.

Enter `. 1 . 2` followed by **`[ENTER]`** (T: 0, Z: 0, Y: 1/2, X: 1/2), add `. 1 . 3 [+]` (T: 0, Z: 0, Y: 0, X: 5/6), and add `. 1 . 6 [+]` (T: 0, Z: 0, Y: 0, X: 1) to simplify directly to 1 complete whole.

Problem 5.46: Unit Price Comparison Sprint

In the applied economics sprint: Supplier A sells 18 oz of copper foil for $3.24, and Supplier B sells 24 oz for $4.08. Which supplier offers the lower cost per ounce? Compare unit rates directly on the stack: **Keystrokes:**

- Brand A: `3.24 [ENTER] 18 [÷]` → X = $0.18/oz.
- Brand B: `4.08 [ENTER] 24 [÷]` → X = $0.17/oz.

Enter `3.24 [ENTER] 18 [÷]` (T: 0, Z: 0, Y: 0, X: 0.18) for Brand A, then load Brand B with `4.08 [ENTER] 24 [÷]` (T: 0, Z: 0, Y: 0.18, X: 0.17), proving Brand B is cheaper by $0.01 per ounce with both values visible on screen!

Problem 5.47: Rapid Fraction Simplification Sprint ((84 / 144))

In the rapid-fire reduction sprint: reduce (84 / 144) to simplest terms in under 3 seconds. Recognizing that 84 and 144 share common factor 12 (84 = 7 × 12 and 144 = 12 × 12), the hardware factor engine eliminates 12 in a single tap. Test this directly on your SC-6: **`[.] 84 [.] 144 [ENTER] [g] [SIMP]`** → `7/12`.

Enter `. 84 . 144` (T: 0, Z: 0, Y: 0, X: 84/144), lift with **`[ENTER]`** (T: 0, Z: 0, Y: 84/144, X: 84/144), and tap **`[g] [SIMP]`** (T: 0, Z: 0, Y: 84/144, X: 7/12) to reduce instantly to lowest terms 7/12.

Problem 5.48: Speed Ratio Scaling Sprint (4:7 → scale by 15)

In the engineering proportions sprint: scale the gear ratio 4:7 by a factor of 15. Scaling a ratio multiplies both terms by the same factor: $4 \times 15 = 60$ and $7 \times 15 = 105$. Bring this to the SC-6 stack: **[.] 4 [.] 7 [g] [a:b] 15 [×]** → 60:105.

Enter . 4 . 7 in Ratio Mode (T: 0, Z: 0, Y: 0, X: 4:7) and multiply by 15 [×] (T: 0, Z: 0, Y: 0, X: 60:105) to scale both terms simultaneously.

Problem 5.49: Complex Mixed Number Speed Challenge ((3 (1 / 2) × 2 (2 / 3)) ÷ 1 (1 / 6))

In the championship round: evaluate (3 (1 / 2) × 2 (2 / 3)) ÷ 1 (1 / 6) on your stack without scratch paper. Mentally converting to improper fractions reveals ((7 / 2) × (8 / 3)) ÷ (7 / 6) = (28 / 3) × (6 / 7) = 4 × 2 = 8. Solve the chained expression on the live stack. On your SC-6, enter 3 [.] 1 [.] 2 [ENTER] 2 [.] 2 [.] 3 [×] 1 [.] 1 [.] 6 [÷] [a⌧/c] → 8.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[3 [.] 1 [.] 2] [ENTER]	0	0	3 1/2	3 1/2	Enter first mixed factor 3 (1 / 2)
[2 [.] 2 [.] 3] [×]	0	0	0	28/3	Multiply by 2 (2 / 3); unreduced product is (28 / 3)
[1 [.] 1 [.] 6] [÷]	0	0	0	8	Divide by 1 (1 / 6); stack resolves directly to exact integer 8!

Chained mixed operations resolve to exact integer 8 with zero parentheses and zero register overflow.

Problem 5.50: Secret Partner Rule Sprint (gcd(36, 48) × lcm(36, 48))

In the final number theory sprint: prove the secret partner rule GCF(36, 48) × LCM(36, 48) = 36 × 48 on the stack. With $36 = 2^2 \times 3^2$ and $48 = 2^4 \times 3$, intersection is $2^2 \times 3 = 12$ (GCF) and union is $2^4 \times 3^2 = 144$ (LCM), yielding product $12 \times 144 = 1{,}728$: **Keystrokes:**

1. GCF: 36 [ENTER] 48 [GCF] → 12.
2. LCM: 36 [ENTER] 48 [f] [LCM] → 144.
3. Product: 12 [ENTER] 144 [×] → 1,728.
4. Direct: 36 [ENTER] 48 [×] → 1,728.

Enter 36 [ENTER] 48 [GCF] (T: 0, Z: 0, Y: 0, X: 12), re-enter 36 [ENTER] 48 [f] [LCM] (T: 0, Z: 0, Y: 12, X: 144), then tap **[×]** (T: 0, Z: 0, Y: 0, X: 1728), confirming the Secret Partner Rule invariant 1,728 = 36 × 48 directly on the stack!

5.11 What You Mastered & Looking Ahead

In this chapter, you have conquered the world of rational numbers:

1. **Concrete Heights:** Your 84 mm Fraction Studio blocks give rational numbers physical geometry and tactile mass, proving equivalence in the Comparator Well.

2. **Two-Dot Syntax:** Entering proper, improper, and mixed numbers requires only natural decimal point presses (`. n . d`).
3. **Unreduced Arithmetic:** The SC-6 honors your mathematical work by displaying unreduced fractions by default.
4. **Superpower 3 (`[g] [SIMP]`):** Step-by-step reduction reveals factor cancellation with instant lowest-terms feedback.
5. **Number Theory Power:** Hardware `[GCF]` and `[f] [LCM]` unlock the secret partner rule GCF × LCM = a × b.
6. **Proportional Reasoning:** Ratio Mode (`[g] [a:b]`) and percentage calculations (`[%]`) empower real-world cooking, carpentry, and financial literacy.

In **Chapter 06: Geometry, Surface Area & Planetary Geared Time**, you will transition into spatial and geometric dimensions. You will unfold 3D polymer nets, master the **Master Surface Area Technique via Stats Mode (`[Σ+]`)**, calculate 3D prism and pyramid volumes, and explore continuous modulo-60 elapsed time on the Planetary Geared Clock (`[CLOCK]`). Welcome to the spatial geometry of the stack!

Geometry, Surface Area & Planetary Geared Time

6.1 Why Does Surface Area Matter in the Real World?

Ask almost any fourth or fifth grader why they need to calculate the "surface area of a rectangular prism," and they will give you the same exhausted answer: *"Because my math worksheet told me Aunt Martha is wrapping 50 birthday gift boxes."*

Nobody actually wraps 50 identical rectangular boxes with wrapping paper. That is textbook fiction. But in the physical universe, **surface area and volume are the fundamental laws of survival, cooking, 3D printing, and spacecraft design**.

6.1.1 The Antarctic Penguin Huddle: How Geometry Saves Lives at -40°C

Imagine you are a newborn Emperor penguin chick standing on the Antarctic ice shelf. The temperature has plummeted to -40^°C, and howling gale-force blizzards blast across the frozen tundra at 100 km/h.

An adult Emperor penguin weighs 35 kg, but a baby chick weighs under 1 kg. Why does an isolated chick freeze in under 10 minutes, while an adult stands calmly against the polar gale?

The Secret Ratio: Volume vs. Surface Area

- **Volume** is where an animal stores and produces internal body heat (proportional to its biological mass).
- **Surface Area** is the outer skin where heat escapes into the freezing wind!

A baby chick has a massive amount of skin (surface area) compared to its tiny body volume. Heat radiates out into the arctic gale far faster than the chick's little heart and metabolism can generate it. Alone on the ice, the chick cannot survive.

The Geometric Miracle: The Huddle

What do the chicks do? Hundreds of baby penguins press tightly together shoulder-to-shoulder into a giant, slowly circulating hexagonal huddle.

Suddenly, all their interior skin touches warm, insulating feathers instead of sub-zero wind! To the freezing blizzard, 500 huddled chicks act as **one giant super-organism**. Their combined volume is massive, but their exposed surface area is drastically reduced! Inside the center of the rotating huddle, the ambient temperature climbs to a toasty +20^°C while the blizzard rages at -40^°C outside. Geometry literally keeps them alive.

> **The Kitchen-Table Proof: French Fries vs. Baked Potatoes**
>
> You observe this exact same surface-area-to-volume geometry every day in your kitchen:
>
> • **The Whole Potato:** A whole baked potato takes 45 to 60 minutes to cook through in a 400^°F oven because heat must conduct slowly through its large volume.
>
> • **The French Fry:** Slice that identical potato into thin batons, and it cooks crisp in boiling oil in just 3 minutes! Slicing didn't change the potato's volume—it multiplied its exposed surface area by over **600%**!

• **The Ice Cube:** A single large ice sphere melts slowly in a drink; crushed ice chills your juice in 10 seconds because surface area is everywhere.

When you calculate surface area on your SC-6, you are not wrapping theoretical gift boxes. You are calculating the universal mathematical law governing heat exchange, fluid drag, chemical reaction rates, and living thermodynamics!



Figure: SC-6 Clock Mode displaying 3:30 on the geared dial

Chapter Baseline Mode: `[NUM]`

Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Transflective Display

Unlocked Keycaps Ribbon — Grades 3–5 Geometry & Measurement Suite

• **2D Geometry Keys:** `[f] [RECT]` Rectangle Area, `[g] [TRI]` Triangle Area, `[f] [CIRC]` Circle Area, `[π]` Pi Constant.

• **3D Solid Volume Keys:** `[f] [PRISM]` Prism Volume, `[g] [CONE]` Cone Volume (Square Pyramids evaluated via Base × Height ÷ 3).

• **The Master Surface Area Technique:** `[Σ+]` (Accumulate Face Pairs), `[f] [Σ-]` (Deduct Cutouts), `[f] [Σx]` (Recall Total Surface Area), `[g] [CLΣ]` (Reset Statistical Registers).

• **Planetary Clock & Modulo-60 Time:** `[CLOCK]` (Planetary Clock Mode), `[f] [→HR]` (HMS to Decimal Hours), `[g] [→HMS]` (Decimal Hours to HMS).

6.2 Concrete Foundations: Manipulative Nets & Planetary Gear Trains

Geometry is inherently spatial, yet many school textbooks reduce three-dimensional shapes to flat drawings on a page. When you calculate the surface area of a box or the volume of a cylinder, you don't need to struggle with confusing textbook formulas like $A = 2lw + 2lh + 2wh$ or $V = \pi r^2 h$. The StackCalc SC-6 grounds every geometric shape in physical blocks and folding nets you can touch and manipulate.



Figure: Algebra & Geometry Area Studio: Concrete 2D Grids and Surface Factoring

Concrete Geometry & Time Manipulatives Ecosystem

1. Precision Folding Polyhedral Nets (Durable Folding Polymer):

- Rectangular Prism Net: 6 hinged faces fold into a 5×4×3 cm solid.
- Triangular Prism Net: 2 triangular bases + 3 rectangular walls.
- Square Pyramid Net: 1 square base + 4 equilateral triangular walls.
- Cylindrical Wrapper Net: 2 circular disks + 1 unrolled rectangle.

2. 19 mm Stacking Unit Cubes & Tiles:

- 19×19 mm precision interlocking base & socket.
- Stack of 3 tiles = 21.0 mm (1 unit cube); stack of 12 = 84.0 mm tower.
- Smooth docking with 45° chamfers — blocks do not snap or fatigue.

3. Planetary Geared Clock:

- Exact 12.0000:1 compound planetary reduction gear train.
- Continuous, non-stepping hour hand moves in lockstep with minutes.
- Stored in protective desk organizer bin.

6.2.1 The Folding Polyhedral Net Experience

When you handle a physical folding net, the concept of surface area ceases to be an equation to memorize. You lay the net completely flat on your worktable. All six faces of a rectangular prism lie open to direct tactile inspection:

- Two identical large rectangles (the top and bottom lids): 5 cm × 4 cm = 20 cm^2 each.
- Two identical long rectangles (the front and back panels): 5 cm × 3 cm = 15 cm^2 each.
- Two identical end rectangles (the left and right tabs): 4 cm × 3 cm = 12 cm^2 each.

You don't need to write down intermediate numbers on scratch paper. Using your SC-6, you enter each face pair directly into the calculator's hardware statistical accumulator using the **[Σ+]** key. As you accumulate each pair, the LCD displays your sample count: `n = 1`, `n = 2`, `n = 3`. Finally, tapping **[f] [Σx]** reveals your total surface area: 94 cm^2.

You then physically fold the hinged panels upward until the tabs fit together, forming a rigid three-dimensional prism. The mystery is solved: *total surface area is simply the sum of all flat 2D faces wrapping the 3D solid*.

Prism Face Pair	Opposing Faces	Dimensions	Face Area	Pair Area (2 × A)
Pair 1	Top Face & Bottom Face	5 cm × 4 cm	20 cm^2	40 cm^2
Pair 2	Front Panel & Back Panel	5 cm × 3 cm	15 cm^2	30 cm^2
Pair 3	Left End & Right End	4 cm × 3 cm	12 cm^2	24 cm^2
Total Surface Area	All 6 Unfolded Faces	5 × 4 × 3 cm	—	**94 cm^2**

6.2.2 Interlocking Snap Cubes and Unit Volumes

Volume measures internal capacity—how many unit cubes fill a solid without gaps or overlaps. By assembling 24 interlocking 20 mm snap cubes into arrays of 2 × 3 × 4, 1 × 2 × 12, and 2 × 2 × 6, you physically discover that while the spatial arrangement changes, the total volume remains constant at 24 cubic units.

6.2.3 Named Idiom: The Stack Drop & Building 3D Volumes

On the SC-6, Stack Math works just like stacking blocks to build a room:

1. **Laying Down the Floor:** When you type Length ENTER Width, you set the floor dimensions on the two active shelves (Y = Length, X = Width).
2. **Floor Area:** Tapping `[×]` multiplies length by width. The two numbers fuse together onto Level X to give the floor area (B = L × W).
3. **Raising the Walls:** Now type Height and tap `[×]`. The floor area multiplies by the height, turning the flat floor into a solid 3D box (V = B × H)!

You never have to memorize a long, confusing formula all at once—you build your math step-by-step from the floor up!

> **For Parents & Teachers: Spatial Reasoning & Dimensional Scaling**
>
> Following Jerome Bruner's learning framework *(Bruner, 1966)* and George Pólya's strategy of decomposing spatial bodies into simpler sub-problems *(Pólya, 1945)*, students avoid rote formula memorization. As Randall Munroe demonstrates in dimensional scaling *(Munroe, 2014)*, Steven Strogatz illustrates in geometric discovery *(Strogatz, 2012)*, and David Macaulay illustrates in mechanical systems *(Macaulay, 2016)*, spatial volume grows with the cube of linear scale (L^3). The step-by-step visibility of the RPN stack drop anchors this physical intuition.

6.3 2D Plane Geometry & Direct Area Solvers

In Grades 3 through 5, you explore two-dimensional plane geometry, unlocking powerful formulas for perimeter and area across polygons and circles.

6.3.1 Rectangles and Squares ([f] [RECT])

A rectangle is a quadrilateral with four right angles. The perimeter P measures the linear distance around the boundary, while the area A quantifies the surface bounded by the perimeter: **P = 2L + 2W = 2(L + W), A = L × W**

Worked Example 6.1: Schoolyard Garden Enclosure

A school garden measures 14 meters in length and 8.5 meters in width. Find:

1. The length of fencing required to completely enclose the garden.
2. The total square meterage of weed barrier cloth needed to carpet the ground.

RPN Solution for Perimeter:
14 `[ENTER]` 8.5 `[+]` `[2]` `[×]` → 45.00 meters

RPN Solution for Area:
14 `[ENTER]` 8.5 `[×]` → 119.00 square meters

Keystroke	Register T	Register Z	Register Y	Register X
14	0	0	0	14
`[ENTER]`	0	0	14	14
8.5	0	0	14	8.5
`[+]`	0	0	0	22.5
`[2]`	0	0	22.5	2
`[×]`	0	0	0	45

For dedicated fast evaluation, the SC-6 provides `[f]` `[RECT]`, which evaluates Y × X directly:

- `14` `[ENTER]` `8.5` `[f]` `[RECT]` → X = **119.00 m²**.

Worked Example 6.2: Square Classroom Carpet Tile

A modular classroom carpet tile is a square with side length s = 0.5 meters. What is its area in square meters?
Keystrokes: `0.5 [x²]` → X = **0.25 m²**

- Entering `0.5` places the square tile side length (s = 0.5 m) into Register X (X = 0.5), and tapping `[x²]` squares Register X in place (0.5 × 0.5), yielding the area X = **0.25 m²** with zero intermediate registers.

6.3.2 Triangles ([g] [TRI])

Every triangle can be viewed as exactly half of an enclosing parallelogram. Regardless of whether the triangle is right-angled, acute, or obtuse, its area is given by: **A = (1 / 2) × b × h** where b is the length of any base and h is the perpendicular altitude dropped to that base.

Triangle Classification	Altitude (h) Location	Area Formula
Right Triangle	Vertical leg serves directly as perpendicular height h	A = (1 / 2) × b × h
Obtuse Triangle	Perpendicular height h drops outside the base extension	A = (1 / 2) × b × h
Acute Triangle	Perpendicular height h drops inside the triangle interior	A = (1 / 2) × b × h

Worked Example 6.3: Wooden Sailboat Rigging

A scale model yacht features a mainsail with a base of b = 18 cm and a vertical mast height of h = 32 cm. Find the sail cloth area.

Classical Formulation: A = (18 × 32 / 2) = 288 cm^2

RPN Execution:

18 [ENTER] 32 [×] [2] [÷] → 288.00 cm²

Direct Shortcut using [g] [TRI] :

18 [ENTER] 32 [g] [TRI] → 288.00 cm²

Keystroke	Register T	Register Z	Register Y	Register X
18	0	0	0	18
[ENTER]	0	0	18	18
32	0	0	18	32
[g] [TRI]	0	0	0	288

Worked Example 6.4: Arbitrary Triangle via Heron's Formula

In Grade 6 advanced mathematics, you encounter triangles where all three side lengths are known (a = 7 cm, b = 8 cm, c = 9 cm), but no perpendicular height is provided. Heron's Formula calculates the area using the semi-perimeter s = (a + b + c / 2): **A = √(s(s - a)(s - b)(s - c))**

Step 1: Compute semi-perimeter s and fill all 4 stack levels (X, Y, Z, T = 12):

[7] [ENTER] [8] [+] [9] [+] [2] [÷] → s = 12.00 cm

[ENTER] [ENTER] [ENTER] → X=12, Y=12, Z=12, T=12

Step 2: Compute terms (s - a), (s - b), (s - c) and multiply on the 4-level stack:

[7] [-] → (12 - 7) = 5 (Y=12, Z=12, T=12)

[x⇔y] [8] [-] [×] → 5 * (12 - 8) = 20 (Y=12, Z=12)

[x⇔y] [9] [-] [×] → 20 * (12 - 9) = 60 (Y=12)

[×] → 12 * 60 = 720

[f] [√x] → 26.8328 cm²

The triangle's exact area is √720 ≈ **26.83 cm^2**.

6.3.3 Circles, Disks & Annuli ([f] [CIRC])

A circle is defined by all points equidistant from a central origin. The ratio of circumference to diameter is the irrational circle constant π ≈ 3.1415926535..., accessed on the SC-6 via the shifted key [π]: **C = 2π r = π d, A = π r^2 = (π d^2 / 4)**

Circle Anatomy Element	Geometric Definition & Formula
Radius (r)	Distance from center origin O to the circular boundary
Diameter (d)	Full chord passing through the center: d = 2r
Circumference (C)	Perimeter distance around one full revolution: C = 2π r = π d

Circle Anatomy Element	Geometric Definition & Formula
Disk Area (A)	Total 2D surface enclosed by the circle: $A = \pi r^2 = (\pi d^2 / 4)$ (`[f]` `[CIRC]`)

In classic handheld RPN calculator engineering, computing circle circumference and disk area with full hardware-precision π eliminated the accumulated drift of rough 3.14 textbook approximations.

Worked Example 6.5: Schoolyard Running Track Turn

The circular turnaround loop of a physical education sprint track has a radius of r = 15 meters. Find:

1. The distance you run along one full circular revolution.
2. The total grass seeding area enclosed by the loop.

Circumference:
15 `[ENTER]` `[2]` `[×]` [π] `[×]` → 94.2478 meters

Area using `[f]` `[CIRC]` :
15 `[f]` `[CIRC]` → 706.8583 square meters

Keystroke	Register T	Register Z	Register Y	Register X
15	0	0	0	15
`[f]` `[CIRC]`	0	0	0	706.8583

Worked Example 6.6: Circular Annulus (Washer / Doughnut)

A 3D-printed spacer washer has an outer radius R = 12 mm and a center bore hole of radius r = 5 mm. What is the net surface area of the top plastic face? **$A_{annulus} = \pi(R^2 - r^2)$**

RPN Execution:
12 `[x²]` `[5]` `[x²]` `[-]` [π] `[×]`

- 12 [x²] → 144 (enters outer radius 12 into Register X and squares in place to 144).
- 5 [x²] → 25
- `[-]` → 119
- `[π]` `[×]` → **373.85 mm²**.

6.3.4 Parallelograms & Trapezoids

A parallelogram consists of two pairs of parallel opposite sides. Because an end triangle can be sheared off and translated to the opposite side to form a rectangle, its area formula is identical to that of a rectangle: **$A_{parallelogram} = b \times h$**

A trapezoid (or trapezium) has exactly one pair of parallel bases (a and b). The area equals the perpendicular height multiplied by the average length of the two parallel bases: **$A_{trapezoid} = (a + b / 2) \times h$**

Trapezoid Dimension	Measurement	Role in Area Formula
Top Parallel Base (a)	6 cm	Averaged with bottom base: (a + b) / 2
Bottom Parallel Base (b)	10 cm	Average width = (6 + 10) / 2 = 8 cm
Perpendicular Height (h)	4 cm	Total Area A = 8 × 4 = **32 cm^2**

Worked Example 6.7: Drainage Trench Cross-Section

A storm runoff culvert has a trapezoidal cross-section with bottom width a = 60 cm, top opening width b = 110 cm, and depth h = 40 cm. Calculate the water discharge flow area.

RPN Evaluation:
60 **[ENTER]** 110 **[+]** **[2]** **[÷]** 40 **[×]** → 3400.00 cm²

Keystroke	Register T	Register Z	Register Y	Register X
60	0	0	0	60
[ENTER]	0	0	60	60
110	0	0	60	110
[+]	0	0	0	170
2	0	0	170	2
[÷]	0	0	0	85
40	0	0	85	40
[×]	0	0	0	3400

The flow area is exactly **3,400 cm^2** (0.34 m^2).

6.3.5 Regular Polygons: Hexagons, Octagons & Floor Tiles

A regular polygon with n sides of length s can be partitioned into n congruent isosceles triangles meeting at the center. The perpendicular distance from the center to any side is the apothem a: **A = (1 / 2) × Perimeter × Apothem = (1 / 2) (n × s) × a**

For a regular hexagon with side length s, the internal triangles are equilateral, yielding an exact apothem of a = (s√3 / 2): **A_{hex} = (3√3 / 2) s^2 ≈ 2.598076 × s^2**

Worked Example 6.8: Hexagonal Ceramic Paver

A courtyard is paved with regular hexagonal pavers, each having side length s = 10 cm. Find the surface area of one paver.

Grade 3–5 Elementary Method (Using Constant Factor 2.5981): In elementary grades, evaluate regular hexagon area directly using the geometric constant factor 2.5981 × s^2:

`10 [x²] 2.5981 [×]` → **259.81 cm^2**.

Grade 6+ Mathematical Extension: Exact Radical Apothem Solver

For middle school mathematicians, the exact regular hexagonal area is derived from 6 equilateral triangles: $A = (3\sqrt{3} / 2) s^2$. Evaluate using the hardware square root key `[f] [√x]`:

> **RPN Exact Evaluation:**

> 10 `[x²]` `[3]` `[×]` `[3]` `[f]` `[√x]` `[×]` `[2]` `[÷]` → 259.8076 cm²

- `10 [x²]` → 100 (enters side length 10 into Register X and squares in place to 100).
- `[3] [×]` → 300
- `3 [f] [√x]` → 1.73205
- `[×]` → 519.6152
- `[2] [÷]` → **259.81 cm²**.

6.4 The Master Surface Area Technique via Stats Mode ([Σ+])

6.4.1 Why Wrapping a 3D Box Can Trick Your Brain

Calculating the total surface area of a three-dimensional solid is notoriously error-prone when using old-fashioned calculators. Consider the standard formula for a rectangular prism: **Total Surface Area = 2(L × W) + 2(L × H) + 2(W × H)**

When using a standard algebraic calculator, you face three frustrating obstacles:

1. **Parenthesis Clutter:** The expression requires at least 6 opening and closing parentheses: `2*(5*4) + 2*(5*3) + 2*(4*3)`. Forgetting a single bracket generates a syntax error.
2. **Scratch Paper Degradation:** You might resort to computing 2 × 5 × 4 = 40 on the calculator, writing down "40" on scrap paper, computing 2 × 5 × 3 = 30, writing down "30", computing 2 × 4 × 3 = 24, writing down "24", and then re-entering all three numbers. Copying numbers down by hand wastes time and causes transcription mistakes.
3. **Loss of Intermediate Visibility:** An algebraic display shows only an unfinished text string, giving you zero feedback on whether individual face pairs make geometric sense.

The Master Surface Area Technique (`[Σ+]`)

- **Rule 1:** Always reset statistical memory before starting: `[g] [CLΣ]`.
- **Rule 2:** Compute each face pair and press `[Σ+]` immediately.
- **Rule 3:** The screen displays `n = 1, 2, 3...`, counting face pairs accumulated in hardware.
- **Rule 4:** Press `[f] [Σx]` to reveal the total surface area!

Zero scratch paper • Zero parentheses • 100% hardware stack verified.

6.4.2 Algebraic Trap vs. StackCalc Superpower Showdown: Rectangular Prism Surface Area

Challenge / Equation	The Algebraic Calculator Trap (TI-30X / Smartphone)	The StackCalc SC-6 + Manipulative Superpower	Keystroke Reduction	Live Stack Visibility	Pedagogical Breakthrough
Rectangular Prism Surface Area: • 2(8 × 5 + 8 × 3 + 5 × 3)	2 * (8 * 5 + 8 * 3 + 5 * 3) = • (19 keystrokes). • One missed bracket or operator typo ruins the entire expression. • No individual face audit is possible. • *Trap: Decimals or typos force complete re-entry; zero visual verification of intermediate face pairs.*	**SC-6 + Stats Mode ([Σ+]):** • [g] [CLΣ] 8 [ENTER] 5 [×] [Σ+] 3 [×] [Σ+] 5 [ENTER] 3 [×] [Σ+] [f] [Σx] 2 [×] • → **158.0 cm²** (17 keystrokes). • Every face pair verified on screen before accumulating; zero scratch paper.	**11% fewer keystrokes** • (17 vs. 19)	**100% Face Visibility:** • Tracks item count n = 1, 2, 3 and lets you inspect intermediate face areas (40, 24, 15) before multiplying by 2.	**Modular Face Decomposition:** • Transforms abstract bracket clutter into an intuitive physical inventory of 2D nets; mistakes can be corrected face-by-face without starting over.

6.4.3 Station Lesson 6.1: Folding Polyhedral Nets & The Master Surface Area Technique ([Σ+])

Station Lesson 6.1: Tactile Setup

- **Manipulatives:** Hinged Polyhedral Net (5×4×3 cm Rectangular Prism), 19 mm Stacking Unit Cubes (Counting Studio)
- **Hardware:** StackCalc SC-6 Elementary in [Σ+] Stats Mode
- **Challenge:** Total surface area without scratch paper or parentheses

A classroom maker project requires designing an injection-molded instrument case measuring:

- Length L = 5 cm
- Width W = 4 cm
- Height H = 3 cm

Face Pair 1 (Top & Bottom): 2 x (5 x 4) = 40 cm² → [Σ+] (n = 1)
Face Pair 2 (Front & Back): 2 x (5 x 3) = 30 cm² → [Σ+] (n = 2)
Face Pair 3 (Left & Right): 2 x (4 x 3) = 24 cm² → [Σ+] (n = 3)
Total Surface Area: 40 + 30 + 24 = 94 cm² → [f] [Σx]

Complete RPN Keystroke Audit:

[g] [CLΣ] → Clears stats registers (n = 0)
[5] [ENTER] [4] [×] [2] [×] → 40.00 cm² (Top/Bottom pair)
[Σ+] → Accumulates face 1; screen shows n = 1
[5] [ENTER] [3] [×] [2] [×] → 30.00 cm² (Front/Back pair)
[Σ+] → Accumulates face 2; screen shows n = 2
[4] [ENTER] [3] [×] [2] [×] → 24.00 cm² (Left/Right pair)
[Σ+] → Accumulates face 3; screen shows n = 3
[f] [Σx] → Recalls Σx = 94.00 cm²!

Keystroke	Register T	Register Z	Register Y	Register X	Stat n, Σx
[g] [CLΣ]	0	0	0	0	n=0, Σx=0
[5]	0	0	0	5	n=0, Σx=0

Keystroke	Register T	Register Z	Register Y	Register X	Stat n, Σx
[ENTER]	0	0	5	5	n=0, Σx=0
[4]	0	0	5	4	n=0, Σx=0
[×]	0	0	0	20	n=0, Σx=0
[2]	0	0	20	2	n=0, Σx=0
[×]	0	0	0	40	n=0, Σx=0
[Σ+]	0	0	0	1	n=1,Σx=40
[5]	0	0	0	5	n=1,Σx=40
[ENTER]	0	0	5	5	n=1,Σx=40
[3]	0	0	5	3	n=1,Σx=40
[×]	0	0	0	15	n=1,Σx=40
[2]	0	0	15	2	n=1,Σx=40
[×]	0	0	0	30	n=1,Σx=40
[Σ+]	0	0	0	2	n=2,Σx=70
[4]	0	0	0	4	n=2,Σx=70
[ENTER]	0	0	4	4	n=2,Σx=70
[3]	0	0	4	3	n=2,Σx=70
[×]	0	0	0	12	n=2,Σx=70
[2]	0	0	12	2	n=2,Σx=70
[×]	0	0	0	24	n=2,Σx=70
[Σ+]	0	0	0	3	n=3,Σx=94
[f] [Σx]	0	0	0	94	Total: 94

6.4.4 The Cube Manipulative

A regular cube has 6 congruent square faces. For a solid cube manipulative with side length s = 4 cm: **Area of 1 face = 4 cm × 4 cm = 16 cm^2 Total Surface Area = 6 × 16 cm^2 = 96 cm^2**

You can accumulate all 6 faces individually to physically confirm the 6-face count:

[g] [CLΣ]
Loop 6 times: [4] [ENTER] [4] [×] [Σ+]
Display shows: n = 6
[f] [Σx] → 96.00 cm²

Or you can use the direct face-pair shortcut: `4 [x²] 6 [×]` → **96.00 cm^2**.

6.4.5 Triangular Prism

A right triangular prism manipulative features:

- Two right-triangular end bases with legs a = 3 cm and b = 4 cm (hypotenuse c = 5 cm).
- Prism length (extrusion depth) L = 6 cm.

Triangular Prism Face	Geometry & Dimensions	Area Calculation
2 Triangular Ends	Right triangle legs a = 3 cm, b = 4 cm	2 × ((1 / 2) × 3 × 4) = 12 cm^2
1 Bottom Rectangular Base	Base 3 cm, length L = 6 cm	1 × (3 × 6) = 18 cm^2
1 Vertical Rectangular Back	Height 4 cm, length L = 6 cm	1 × (4 × 6) = 24 cm^2
1 Slanted Rectangular Roof	Hypotenuse 5 cm, length L = 6 cm	1 × (5 × 6) = 30 cm^2
Total Surface Area	Accumulated via `[Σ+]` (n = 4)	**84 cm^2**

Step-by-Step Face Inventory:

1. **Two Triangular Ends:** Each end has area (1 / 2) × 3 × 4 = 6 cm^2. Together, the pair equals 2 × 6 = 12 cm^2.
2. **Bottom Rectangular Face:** 3 cm × 6 cm = 18 cm^2.
3. **Vertical Rectangular Back:** 4 cm × 6 cm = 24 cm^2.
4. **Slanted Rectangular Roof:** 5 cm × 6 cm = 30 cm^2.

Total Surface Area = 12 + 18 + 24 + 30 = 84 cm^2

Keystrokes:

`[g]` `[CLΣ]`
`[3]` `[ENTER]` `[4]` `[×]` `[Σ+]` → n = 1 (Accumulates 12 cm² ends)
`[3]` `[ENTER]` `[6]` `[×]` `[Σ+]` → n = 2 (Accumulates 18 cm² bottom)
`[4]` `[ENTER]` `[6]` `[×]` `[Σ+]` → n = 3 (Accumulates 24 cm² back)
`[5]` `[ENTER]` `[6]` `[×]` `[Σ+]` → n = 4 (Accumulates 30 cm² slant)
`[f]` `[Σx]` → Recalls 84.00 cm²!

6.4.6 Right Circular Cylinder

A right cylinder consists of two parallel circular disks of radius r joined by a curved lateral wall of height h. When unrolled flat, the lateral wall forms a rectangle whose width is the circular circumference 2π r and whose height is h: **Total Surface Area = 2(π r^2) + 2π r h**

Worked Example 6.9: Steel Storage Silo

A cylindrical water storage tank has a radius r = 3 meters and a height h = 8 meters. Find the total metal plating required (top disk, bottom disk, and cylindrical wall).

RPN Solution via `[Σ+]`:

`[g]` `[CLΣ]`
`[3]` `[f]` `[CIRC]` `[2]` `[×]` `[Σ+]` → Disk pair: 2 (π 3²) ≈ 56.5487 m² (n = 1)

`[3]` `[ENTER]` `[2]` `[×]` [π] `[×]` → Circumference: 2 π 3 ≈ 18.8496 m
`[8]` `[×]` `[Σ+]` → Lateral wall: 18.8496 * 8 ≈ 150.7964 m² (n = 2)
`[f]` `[Σx]` → Total Surface Area: 207.3451 m²

The tank requires **207.35 m^2** of steel sheeting.

6.4.7 Right Circular Cone

A right cone has a circular base of radius r and a pointed vertex. The lateral surface unrolls into a circular sector of radius s (the slant height), where $s = \sqrt{(r^2 + h^2)}$: **Base Area = πr^2, Lateral Area = π r s Total Surface Area = $\pi r^2 + \pi r \sqrt{(r^2 + h^2)}$**

Worked Example 6.10: Traffic Pylon Cover

(Grade 6 Advanced Extension: Exploring Slant Heights with `[f]` `[√x]` *)*

A highway safety cone has a base radius r = 15 cm and a vertical height h = 36 cm. Find:

1. The slant height s (*Note for Grades 3–5: Students may use the given slant height s = 39 cm; Grade 6 students evaluate $s = \sqrt{(r^2 + h^2)}$ directly*).
2. The reflective vinyl sheeting required for the lateral surface (open bottom, no base).

Step 1: Compute Slant Height s (Grade 6 Pythagorean Extension):
`15` `[x²]` `36` `[x²]` `[+]` `[f]` `[√x]` → s = **39.00 cm** (Exact Pythagorean triple!)

Step 2: Compute Lateral Area A = π r s:
`[π]` `[×]` `15` `[×]` → **1,837.83 cm^2**

The cone requires **1,837.83 cm^2** of reflective vinyl.

6.4.8 Regular Square-Based Pyramid

A square pyramid features a flat square base of side s and four congruent isosceles triangular walls meeting at the apex. The slant height l runs from the apex down the center of each triangular face: **Base Area = s^2, Wall Area = 4 × ((1 / 2) s l) = 2 s l Total Surface Area = s^2 + 2 s l**

Worked Example 6.11: Canvas Camping Tent

A pyramid tent has a square floor of side s = 3 meters and a slant height l = 2.5 meters. Find the total canvas required including the waterproof floor.

Keystrokes via `[Σ+]` **:**
`[g]` `[CLΣ]`
`[3]` `[x²]` `[Σ+]` → Floor base: 9.00 m² (n = 1)
`[3]` `[ENTER]` 2.5 `[×]` → Base * slant = 7.5
`[2]` `[÷]` → 1 triangle = 3.75 m²

`[4]` `[×]` `[Σ+]` → 4 triangular walls = 15.00 m² (n = 2)
`[f]` `[Σx]` → Total Canvas Area = 24.00 m²

6.4.9 Open-Top Solids & Custom Maker Enclosures

Real-world engineering frequently demands calculating surface areas of open containers, such as an acrylic aquarium, an electronics project box with a removable lid, or a sheet metal tool tray.

Worked Example 6.12: Acrylic Glass Aquarium

An open-top aquarium measures L = 10 inches, W = 8 inches, and H = 6 inches. Because the top is open, the solid has only 5 faces (1 bottom base + 2 front/back walls + 2 left/right walls).

Keystrokes via `[Σ+]`:
`[g]` `[CLΣ]`
10 `[ENTER]` `[8]` `[×]` `[Σ+]` → Single bottom face: 80.00 in² (n = 1)
10 `[ENTER]` `[6]` `[×]` `[2]` `[×]` `[Σ+]` → Front/Back pair: 120.00 in² (n = 2)
`[8]` `[ENTER]` `[6]` `[×]` `[2]` `[×]` `[Σ+]` → Left/Right pair: 96.00 in² (n = 3)
`[f]` `[Σx]` → Total Glass Area: 296.00 in²

You verify with a single glance at the accumulator count: `n = 3` face groups added, total area **296 in²**.

6.5 3D Solid Volume Dynamics

Volume quantifies the three-dimensional space enclosed within the boundary of a solid. In the SC-6 system, all prism and cylinder volumes share a unified conceptual definition: **Volume = Base Area (A_{base}) × Height (h)**

For pointed solids (cones and pyramids), the volume is exactly one-third of the enclosing prism or cylinder:
$Volume_{pointed} = (1 / 3) \times A_{base} \times h$

Solid Type	Base Area (A_b)	Volume Formula
Rectangular Prism	$A_b = L \times W$	$V = L \times W \times H$
Cube	$A_b = s^2$	$V = s^3$
Right Cylinder	$A_b = \pi \times r^2$	$V = \pi \times r^2 \times h$
Square Pyramid	$A_b = s^2$	$V = (1 / 3) \times s^2 \times h$
Right Cone	$A_b = \pi \times r^2$	$V = (1 / 3) \times \pi \times r^2 \times h$
Sphere	*(Full Solid)*	$V = (4 / 3) \times \pi \times r^3$

6.5.1 Rectangular Prisms & Cubes

Worked Example 6.13: Shipping Crate Capacity

A cargo container measures 12 meters long, 2.4 meters wide, and 2.6 meters tall. How many cubic meters of freight can it hold?

RPN Execution:
12 `[ENTER]` 2.4 `[×]` 2.6 `[×]` → 74.88 m³

Keystroke	Register T	Register Z	Register Y	Register X
12	0	0	0	12
`[ENTER]`	0	0	12	12
2.4	0	0	12	2.4
`[×]`	0	0	0	28.8
2.6	0	0	28.8	2.6
`[×]`	0	0	0	74.88

The cargo volume is **74.88 m^3**.

6.5.2 Cylinders & Storage Tanks

Worked Example 6.14: Farm Milk Silo

A cylindrical dairy storage tank has an inside diameter d = 2.4 meters (radius r = 1.2 m) and a vertical height h = 4.5 meters.

1. Find the volume in cubic meters.
2. Given that 1 m^3 = 1,000 liters, determine total milk storage capacity in liters.

Step 1: Compute Volume in m³:
1.2 `[f]` `[CIRC]` 4.5 `[×]` → 20.3575 m³

Step 2: Convert to Liters (multiply by 1,000):
1000 `[×]` → 20,357.52 Liters

The silo holds **20.36 m^3** or **20,358 liters** of milk.

6.5.3 Cones & Pyramids: The 3:1 Pouring Proof

In hands-on math stations, you can perform the classic experiment: take a hollow cone and a hollow cylinder of identical base radius r and vertical height h. Filling the cone with dry rice or water, you discover that it takes exactly three full cones to fill the cylinder. Thus: $V_{cylinder} = 3 \times V_{cone} \Leftrightarrow V_{cone} = (1/3)\,\pi\, r^2\, h$

Worked Example 6.15: Laboratory Glass Funnel

A conical funnel has an opening radius r = 6 cm and an internal depth h = 10 cm. Find its liquid capacity.

RPN Evaluation:
`[6]` `[f]` `[CIRC]` 10 `[×]` `[3]` `[÷]` → 376.9911 cm³

- `[6] [f] [CIRC]` → 113.0973 cm^2 (Base area πr^2)
- `10 [×]` → 1130.9734 cm^3 (Enclosing cylinder volume)
- `[3] [÷]` → **376.99 cm^3** (Exact conical volume).

6.5.4 Spheres & Hemispheres

A sphere is a perfectly symmetrical three-dimensional ball. Archimedes famously proved that the volume of a sphere is two-thirds the volume of its circumscribed cylinder: **$V_{sphere} = (4 / 3) \pi r^3$**

Worked Example 6.16: Weather Observation Balloon

A meteorological sounding balloon is inflated to a spherical radius $r = 1.5$ meters. Find the helium gas volume needed to fill it. As Steven Strogatz notes *(Strogatz, 2012)*, Archimedes regarded his proof of the spherical volume formula ($V = (4 / 3)\pi r^3$) as his greatest mathematical triumph.

RPN Keystrokes:
`[4]` `[ENTER]` `[3]` `[÷]` [π] `[×]` 1.5 `[ENTER]` `[3]` `[g]` [y■] `[×]` → 14.1372 m³

- `4 [ENTER] 3 [÷]` → 1.33333 (stages numerator 4 onto Floor Y and divides by 3 to form Archimedes' spherical ratio $4/3 \approx 1.3333$).
- Tap `[π] [×]` to scale by the circle constant π → 4.18879 (the universal spherical volume coefficient $(4 / 3)\pi$).
- Key `1.5 [ENTER] 3 [g] [y⊠]` to cube the balloon's physical radius (1.5^3) → 3.375 m^3.
- Tap `[×]` to multiply the spherical coefficient by the cubic radius → **14.14 m^3** of helium gas.

6.5.5 Fluid Displacement & Irregular Objects

When an irregularly shaped object (such as a metal machine bolt or a mineral sample) is submerged in a graduated cylinder of water, the volume of displaced liquid equals the exact solid volume of the submerged body (Archimedes' Principle).

Worked Example 6.17: Mineral Specimen Density Trial

You pour water into a cylindrical beaker with internal radius $r = 4$ cm. When you gently lower a mineral sample beneath the surface, the water level rises by $\Delta h = 1.8$ cm. Find the mineral's volume.

RPN Calculation:
`[4]` `[f]` `[CIRC]` 1.8 `[×]` → 90.4779 cm³

The mineral sample has a volume of **90.48 cm^3**.

6.6 Planetary Geared Clock & Continuous Modulo-60 Elapsed Time

6.6.1 How the Gears Inside Your Planetary Clock Work Together

Traditional elementary classroom clocks feature stepping hands or disconnected dials that let you accidentally position hands in physically impossible configurations (such as pointing the hour hand directly at 4:00 while the minute hand points to 30 minutes, representing 4:30).

The StackCalc ecosystem pairs the SC-6 with an authentic 3D-printed **Planetary Geared Clock**. The clock mechanism utilizes an exact compound planetary gear train with an exact 12.0000:1 gear reduction ratio:

- As the minute hand completes one full 360^° rotation (60 minutes), the planet gears smoothly drive the sun carrier forward by exactly (1 / 12)th of a turn (30^°, or 1 hour).
- At 3:30, the hour hand does **not** sit on the 3; it is mechanically locked at 3.5 hours × 30^°/hr = 105^°, exactly halfway between 3 and 4!

As Matt Parker observes in *Humble Pi (Parker, 2019)*, real-world engineering failures frequently trace back to uncoordinated mechanical linkages and rounding off fractional gear cycles. The SC-6 planetary gear train eliminates stepping backlash and locks angle and elapsed time into an unbreakable physical invariant.

Clock Hand at 3:30	Dial Position	Continuous Mechanical Angle
Minute Hand	Points directly at **6** (30 min)	30 × 6^° = **180.0^°** (π rad)
Hour Hand	Halfway between **3** and **4** (3.5 hr)	(3 + 30/60) × 30^° = 3.5 × 30^° = **105.0^°**

6.6.2 Continuous Hand Angle Verification

In the SC-6 firmware engine (`SC6VisualConversions`), the continuous angle of the hands is computed using full floating-point precision: **θ_{minute} = minutes × (2π / 60) = minutes × (π / 30) radians θ_{hour} = (hours + (minutes / 60)) × (2π / 12) = (hours + (minutes / 60)) × (π / 6) radians**

For 3:30 (3.30 HMS):

- θ_{minute} = 30 × (π / 30) = π rad = **180.0^°**.
- θ_{hour} = (3 + (30 / 60)) × (π / 6) = 3.5 × (π / 6) ≈ **1.8325957 rad** = **105.0^°**.

6.6.3 Clock Time (H.MMSS) Entry and [f] [■HR] / [g] [■HMS] Conversion

Clock time operates in base 60 (60 minutes in an hour), whereas standard calculator numbers operate in base 10 (decimal). A common mistake is trying to add 9:45 + 2:35 = 11.80, treating 45 minutes and 35 minutes as decimal numbers!

The SC-6 adopts the clear, classic time notation:

- Time is entered as Hours.MinutesSeconds (e.g., 9.45 for 9:45 AM).
- Pressing `[f] [→HR]` instantly converts clock time to pure decimal hours.

- Arithmetic is executed cleanly in decimal hours.
- Pressing `[g] [→HMS]` converts the decimal result back to standard clock format H.MMSS.

Strict No-Units Rule:

As mandated in the SC-6 design specification, `[f] [→HR]` converts to pure numeric decimal hours without appending trailing text units like "HR". The display shows `9.7500`, allowing direct subsequent multiplication by hourly wage rates or speeds!

6.6.4 Station Lesson 6.2: Continuous Geared Clock Elapsed Time ([■])



Figure: Planetary Clock Planetary Gear Stages: 12:1 Compound Reduction

Station Lesson 6.2: Tactile Setup

- **Manipulatives:** Planetary Geared Clock, 12.0000:1 compound planetary reduction gear train
- **Hardware:** StackCalc SC-6 Elementary with `[f] [→HR]` and `[g] [→HMS]` keys
- **Challenge:** Elapsed flight time across 60-minute clock boundaries



Figure: Planetary Geared Clock: 12.0000:1 Planetary Reduction Gear Train at 3:30 (105.0° Continuous Hour Hand)

A transcontinental flight departs New York at 9:45 AM (9.45 HMS) and has a scheduled flight duration of 2 hours and 35 minutes (2.35 HMS). What is the scheduled arrival time?

Hands-On Mechanical Verification:

1. **Clock Setup:** Turn the dial of the physical Planetary Geared Clock until the hands show 9:45. Notice that the hour hand is physically locked three-quarters of the way between 9 and 10 (9.75 hours × 30^°/hr = 292.5^°).
2. **Kinematic Rotation:** Rotate the minute ring through 2 full turns (120 minutes = 2 hours) and an additional 35 minutes. Observe the continuous movement of the hour hand as it sweeps past 12 to rest at 12:20.
3. **RPN Execution:**

RPN Keystrokes:

`9.45` `[f]` `[→HR]` → 9.7500 decimal hours (stack lift armed)

`2.35` `[f]` `[→HR]` → 2.5833 decimal hours in Register X (9.7500 lifted to Y)

`[+]` → 12.3333 decimal hours

`[g]` `[→HMS]` → **12.2000 (12:20 PM)**!

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`9.45` `[f]` `[→HR]`	0	0	0	9.7500	Enter 9:45 AM and convert to decimal hours (9.7500 hr; stack lift armed)
`2.35` `[f]` `[→HR]`	0	0	9.7500	2.5833	Enter 2 hr 35 min flight duration (automatically lifting 9.7500 to Y) and convert (2.5833 hr)
`[+]`	0	0	0	12.3333	Add decimal hours: 9.75 + 2.5833 = 12.3333 hr
`[g]` `[→HMS]`	0	0	0	12.2000	Convert back to clock time: 12:20 PM arrival!

The flight lands at exactly **12:20 PM**, matching the physical clock face to the second!

For Parents & Teachers: Diagnostic Dialogue

Teacher: "Why couldn't we just add 9.45 + 2.35 on a standard calculator?"

Student: "Because 45 + 35 is 80, and there are only 60 minutes in an hour!"

Teacher: "Exactly. Time is base-60. What does `[f]` `[→HR]` do on the SC-6?"

Student: "It turns the minutes into regular decimal hours so we can add them normally, and then `[g]` `[→HMS]` turns them back into clock time!"

6.6.5 Midnight Boundary Crossings

When a journey spans across midnight, the departure hour exceeds the arrival hour on a 24-hour clock. The SC-6 resolves this using modular arithmetic (modulo 24).

Worked Example 6.18: Overnight Sleeper Train

An overnight passenger train departs at 22:45 (10:45 PM) and travels for 3 hours and 30 minutes (3.30 HMS). When does it arrive?

RPN Evaluation:

22.45 `[f]` `[→HR]` → 22.7500 hr

`[ENTER]`

3.30 `[f]` `[→HR]` → 3.5000 hr

`[+]` → 26.2500 hr (exceeds 24 hours!)

24 `[-]` → 2.2500 hr (modulo 24 subtraction)

`[g]` `[→HMS]` → 2.1500 (02:15 AM)!

The train pulls into the station at **2:15 AM**.

6.6.6 Planetary Clock Gear Ratio Derivation

For robotics builders and young makers like you, the gear geometry of the Planetary Geared Clock demonstrates applied ratio mathematics. The compound planetary train consists of:

- Sun Gear (N_s = 12 teeth)
- Three Planet Gears (N_p = 60 teeth each)
- Stationary Ring Gear (N_r = 132 teeth)

The gear ratio R between the input minute carrier and the output hour sun is derived from planetary kinematics: **$R = 1 + (N_r / N_s) = 1 + (132 / 12) = 1 + 11 = 12.0000$** The gear train provides an exact, unvarying 12:1 kinematic reduction with zero angular backlash!

6.6.7 How Gear Teeth Fit Together Without Jamming

In STEM maker labs, you can fabricate functional clock gears using open-source blueprints (see Appendix A). The physical size of a gear depends on its **metric module** m, which defines the pitch diameter D per tooth: **$D = m \times N$** where

m = 1.0 mm for our precision classroom gear set.

- Sun Gear ($N_s = 12$): $D_s = 1.0 \times 12 = 12.0$ mm
- Planet Gears ($N_p = 60$): $D_p = 1.0 \times 60 = 60.0$ mm
- Ring Gear ($N_r = 132$): $D_r = 1.0 \times 132 = 132.0$ mm

You can verify the secret geometry rule that makes all your clock gears sit flat and fit together: the diameter across the big outer ring gear must equal the center sun gear plus two planet gears side-by-side: **$D_r = D_s + 2 \times D_p \Leftrightarrow 132 = 12 + 2(60) = 12 + 120 = 132.0$ mm** This perfect algebraic identity confirms why all three planet gears mesh simultaneously with zero binding or distortion!

For Parents & Teachers: Spatial Accumulation, Modulo-60 Invariants & Diagnostic Dialogue

Pedagogical & Architectural Insights: The geometric algorithms and time primitives of the SC-6 embody key instructional principles: concrete-to-abstract mapping with polyhedral nets, modulo-60 elapsed time conversion preventing decimal fallacies, and hardware summation isolation in statistical registers (**[f] [Σx]**).

Classroom Script 6.1: The Open-Top Aquarium Dilemma

Teacher: "Class, our science lab just ordered an open-top glass aquarium measuring 10 inches long, 8 inches wide, and 6 inches tall. We need to buy sheets of acrylic glass to build it. How many faces does our box have?"

Student (Maya): "A box always has six faces! Top, bottom, front, back, left, right."

Teacher: "Look at the real aquarium on the lab bench. What happens if we put a solid glass lid glued to the top?"

Maya: "The fish can't breathe, and we can't feed them! The top has to be completely open!"

Teacher: "Exactly! So how many faces do we need to calculate?"

Maya: "Only five! One bottom, two long sides, and two short ends."

Teacher: "Right. If you used the textbook formula 2lw + 2lh + 2wh, what would happen?"

Maya: "It would add two tops, which would be totally wrong!"

Teacher: "Let's use the SC-6 Master Surface Area technique: `10 [ENTER] 8 [×] [⊠+]`, then `10 [ENTER] 6 [×] 2 [×] [⊠+]`, then `8 [ENTER] 6 [×] 2 [×] [⊠+]`, and press **[f] [Σx]** !"

Maya: "296 square inches, and we didn't use a single piece of scratch paper!"

Classroom Script 6.2: The Mystery of the 3:30 Clock Hands

Student (Leo): "Teacher, on this worksheet question about clock angles, it asks for the angle between the hour hand and minute hand at 3:30. I wrote 90^° because the hour hand is pointing at 3 and the minute hand is pointing at 6."

Teacher: "Take our Planetary Geared Clock off the shelf, Leo. Turn the dial until the hands show 3:00, then turn the minute hand to 30 minutes. Watch the hour hand carefully."

Leo: "Hey! The hour hand didn't stay on the 3! It moved halfway toward the 4!"

Teacher: "Why did it move?"

Leo: "Because the gears inside are connected! If the hour hand stayed at 3 until 4:00, it would have to jump instantly to 4 at the last second!"

Teacher: "Brilliant! So at 3:30, the hour hand has moved 15^° past the 3 (to 105^°), and the minute hand is at 180^°. So the angle between them is 180^° - 105^° = 75^°!"

For Parents & Teachers: Geometry & Measurement Diagnostic Playbook

| Observable Error | Cognitive Root Cause | Targeted Remediation Prompt |

| :--- | :--- | :--- |

| **Adding 9.45 + 2.35 = 11.80** | Confusing base-60 clock minutes with base-10 decimal fractions. | *"There are 60 minutes in an hour, not 100! 45 minutes + 35 minutes = 80 minutes, which is 1 hour and 20 minutes. Always convert using* `[f] [→HR]` *before adding, then convert back with* `[g] [→HMS]` *."* |

| **Forgetting to multiply faces by 2** | Omitting the congruent opposite face in a rectangular prism. | *"Hold the 3D wooden box. Does it have only one top, or both a top AND a bottom? Every rectangular box has 3 pairs of matching faces. Always multiply each face product by 2 before tapping* `[Σ+]` *."* |

| **Calculating 6 faces for an open container** | Blindly executing the formula 2(lw + lh + wh) without analyzing physical boundary conditions. | *"Look at the real object. Is the tank sealed shut like a shipping crate, or open like a bucket? Only multiply by 2 if both opposing faces actually exist!"* |

| **Static hour-hand misconception (3:30 → 90^°)** | Assuming the hour hand jumps instantaneously on the hour. | *"Look at the planetary gears in our clock manipulative. The hour hand moves continuously in lockstep with the minutes. At 30 minutes past, the hour hand is exactly halfway to the next number."* |

| **Treating volume as surface area** | Confusing boundary area (units of cm^2) with interior capacity (units of cm^3). | *"Area is the wrapping paper covering the outside of the present; volume is the number of toy blocks packed inside the box."* |

| **Omitting the (1 / 3) factor in cone volume** | Assuming a cone holds the same volume as a cylinder of equal height. | *"Remember our water pouring experiment! It took 3 full cones of water to fill the cylinder. A cone is always exactly one-third of the cylinder: divide by 3!"* |

6.7 Comprehensive Problem Bank: 50 Worked Reference Problems

The following problem bank provides complete, publication-grade reference solutions spanning Grade 3 through Grade 6 geometry and measurement standards. Every keystroke sequence assumes the SC-6 baseline mode `[NUM]`.

Hands-On Studio Proof: Blocks → Calculator

Step 1 (Physical Concrete Intuition): Unfold the 3D hinged net of a 5 cm × 4 cm × 3 cm rectangular prism on your desk. Touch each congruent face pair: the top and bottom lids (5 × 4 = 20 cm^2 each), the front and back walls (5 × 3 = 15 cm^2 each), and the two end caps (4 × 3 = 12 cm^2 each). You physically hold the entire surface area of 94 cm^2 in your hands.

Step 2 (The Representational Bridge): Turn to your SC-6. Instead of writing long parenthetical formulas or messy scratch paper notes, tap `[g] [CLΣ]` to clear statistical memory. Compute Face Pair 1: `5 [ENTER] 4 [×] 2 [×] [Σ+]` → `n = 1`. Compute Face Pair 2: `5 [ENTER] 3 [×] 2 [×] [Σ+]` → `n = 2`. Compute Face Pair 3: `4 [ENTER] 3 [×] 2 [×] [Σ+]` → `n = 3`. Tap `[f] [Σx]`: the display instantly reveals `94.00`! Every fold of the net corresponds to one accumulation step on the calculator.

Step 3 (Scaling on the Calculator): Now scale from a toy block to an aircraft cargo container (1,200 cm × 240 cm × 260 cm): execute the exact same three face pairs with `[Σ+]` to get 1,324,800 cm^2 with 100% hardware precision and zero scratch paper errors!

6.7.1 Expedition 1: The Landscape Architect's Park Masterplan (Challenges 6.1–6.10)

Mission Briefing: You are the lead civil planner and landscape architect mapping out a vibrant 50-acre city park. You must calculate paving perimeters, sod turf areas, circular pond boundaries, and floral polygon parterres—verifying that every square meter of land is budgeted to perfection.

6.7.2 Expedition 1: The Park Surveyor & Rectangular Tile Studio (Challenges 1–12)

Thematic Arc: Starting with 2D perimeter frames and rectangular tile arrays on the desk before scaling up to park boundaries and sensor enclosures on the SC-6.

Challenge 1: Park Perimeter Ribbon Framing

The landscape architect plans a rectangular information kiosk bulletin board in the central plaza measuring 2.4 meters wide and 1.2 meters high. A durable aluminum edging ribbon must be ordered to frame its full perimeter. Model the kiosk proportions using a small 2 × 4 tile array on your desk. Touch the top and right edges to see the half-perimeter (6). Then scale big on StackCalc: enter the true 2.4 m × 1.2 m dimensions, sum to find the half-perimeter (3.6 m), and double it for the full perimeter. On your SC-6, key in `2.4 [ENTER] 1.2 [+] [2] [×]` → `7.2`.

Key `2.4` and press **[ENTER]** to hold the kiosk width in Register Y `(T:0, Z:0, Y:2.4, X:2.4)`. Key `1.2` and press **[+]** to compute the half-perimeter 3.6 m `(T:0, Z:0, Y:0, X:3.6)`. Key `2` and press **[×]** to double the L-shape, giving the full perimeter `(T:0, Z:0, Y:0, X:7.2)`. Register X displays 7.2000. Total perimeter is **7.20 meters**.

Challenge 2: Square Playground Sandpit Cover

The community adventure playground features a square sandpit with side length s = 3.5 meters. A heavy-duty waterproof canvas tarp must be cut to protect the sand from overnight rain. Lay out a square array of counting tiles (3.5 × 3.5 scale). Squaring a side length tiles the two-dimensional interior plane directly, turning a linear measure (3.5 m) into areal units (m^2). On the SC-6 keypad, enter `3.5 [x²]` → `12.25`.

Key `3.5` and press **[x²]** to square the edge length in place, directly producing the square tarp area `(T:0, Z:0, Y:0, X:12.25)`. Register X displays 12.2500. Canvas tarp area required is **12.25 m^2**.

Challenge 3: Triangular Park Pavilion Pennant

A ceremonial triangular felt pennant hangs above the park entrance pavilion, with base b = 25 cm along the crossbeam and vertical altitude h = 60 cm. Calculate the felt fabric required. Cut a 25 × 60 cm rectangle of paper diagonally. Two identical right triangles emerge. The area of one triangle is exactly half of the enclosing rectangle (A = (1 / 2) b h). Turning to your SC-6, key in `25 [ENTER] 60 [g] [TRI]` → `750`.

Key `25`, press **[ENTER]**, key `60`, and press **[g] [TRI]** to execute the dedicated triangle area solver in one step `(T:0, Z:0, Y:0, X:750)`. Register X displays 750.0000. Felt fabric area is **750.00 cm^2**.

Challenge 4: Floral Plaza Circular Sundial Clockface

A circular sundial in the central plaza has a diameter of 30 cm (radius r = 15 cm). The bronze faceplate must be cut from polished sheet metal. Divide a circular paper disc into 16 wedge sectors and interlock them alternately: they form an approximate parallelogram of height r and base π r. Area equals π r^2. With your SC-6 ready, enter `15 [f] [CIRC]` → `706.85834706`.

Key `15` and press **[f] [CIRC]** to square the radius and multiply by π in a single hardware cycle `(T:0, Z:0, Y:0, X:706.8583)`. Register X displays 706.8583. Bronze plate area is **706.86 cm^2**.

Challenge 5: Circular Fountain Stone Curb Perimeter

A decorative circular fountain has radius r = 4.2 meters. Granite stone curbing must be laid around its outer perimeter. Roll a circular disk along a metric tape rule. One complete revolution travels exactly π times the diameter (C = 2 π r ≈ 6.283 × r). Step over to your SC-6 and key in `4.2 [ENTER] [2] [×] [π] [×]` → `26.38937829`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
4.2	0.0000	0.0000	0.0000	4.2	Key fountain radius (4.2 m)
[ENTER]	0.0000	0.0000	4.2	4.2	Stack lifts; radius locked into Register Y
2	0.0000	0.0000	4.2	2.0000	Key diameter doubling factor 2
[×]	0.0000	0.0000	0.0000	8.4	Multiply to obtain full diameter (8.4 m) in Register X
[π]	0.0000	0.0000	8.4	3.1416	Push circle constant $\pi \approx 3.141593$ onto stack
[×]	0.0000	0.0000	0.0000	26.3894	Multiply diameter by π to wrap curb perimeter

Register X displays 26.3894. Granite curb perimeter is **26.39 meters**.

Challenge 6: Parallelogram Flower Bed

An ornamental botanical flower bed is laid out as a parallelogram with base b = 8 meters and perpendicular altitude h = 4.5 meters. Calculate the topsoil area. Cut a triangular slice from the left edge of a paper parallelogram and slide it to the right edge: it forms a rectangle of identical base and height ($A = b \times h$). Now compute it on your SC-6: **[8] [ENTER] 4.5 [×]** → 36.

Key 8, press **[ENTER]**, key 4.5, and press **[×]** to evaluate parallelogram area (8 × 4.5) (T:0, Z:0, Y:0, X:36). Register X displays 36.0000. Flower bed area is **36.00 m^2**.

Challenge 7: Trapezoid Highway Ramp Embankment

An access ramp retaining embankment bordering the park has parallel bases a = 14 m (top crest) and b = 22 m (ground base), with vertical height h = 6 m. Calculate reinforced sod area. Join two identical trapezoids upside down: they form a large parallelogram of base (a + b) and height h. Halving the combined base yields the average midline width (18 m). Run the sequence on your SC-6: 14 [ENTER] 22 [+] [2] [÷] [6] [×] → 108.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
14	0.0000	0.0000	0.0000	14.0000	Key top crest base (14 m)
[ENTER]	0.0000	0.0000	14.0000	14.0000	Stack lifts; top base locked into Register Y
22	0.0000	0.0000	14.0000	22.0000	Key ground base (22 m) into floor X
[+]	0.0000	0.0000	0.0000	36.0000	Sum parallel bases (14 + 22 = 36 m)
2	0.0000	0.0000	36.0000	2.0000	Key divisor 2 on floor X
[÷]	0.0000	0.0000	0.0000	18.0000	Divide sum by 2 to compute average midline width (18 m)
6	0.0000	0.0000	18.0000	6.0000	Key embankment vertical height (6 m)
[×]	0.0000	0.0000	0.0000	108.0000	Multiply average width by height for total area

Register X displays 108.0000. Sod embankment area is **108.00 m^2**.

Challenge 8: Rhombus Decorative Pathway Pavers

Plaza pathways are tiled with diamond-shaped granite pavers having diagonal spans d_1 = 40 cm and d_2 = 70 cm. Find the paver face area ($A = (1 / 2)\ d_1\ d_2$). The perpendicular diagonals split the rhombus into four identical right triangles. Reassembling them forms a rectangle of dimensions $d_1 \times (1 / 2)\ d_2$. Verify the calculation on your SC-6: 40 [ENTER] 70 [×] [2] [÷] → 1400.

Key 40, press [ENTER], key 70, and press [×] to compute the bounding rectangle 2800 cm^2 (T:0, Z:0, Y:0, X:2800). Key 2 and press [÷] to halve the product, yielding the net rhombus area (T:0, Z:0, Y:0, X:1400). Register X displays 1400.0000. Paver face area is **1400.00 cm^2**.

Challenge 9: Regular Hexagonal Gazebo Floor

A shaded park gazebo has a regular hexagonal floor with side length s = 12 cm (modeled at 1:10 scale). Calculate the stone floor area using $A = (3\sqrt{3} / 2) s^2$. A regular hexagon decomposes into 6 congruent equilateral triangles radiating from its center, each of area $(\sqrt{3} / 4) s^2$. Multiplying by 6 gives $(3\sqrt{3} / 2) s^2$. Test this directly on your SC-6: 12 [x²] [3] [×] [3] [f] [√x] [×] [2] [÷] → 374.12297443.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
12	0.0000	0.0000	0.0000	12.0000	Key hexagon side length (12 cm)
[x²]	0.0000	0.0000	0.0000	144.0000	Square side length (12^2 = 144)
3	0.0000	0.0000	144.0000	3.0000	Key multiplier 3 for triangular sectors
[×]	0.0000	0.0000	0.0000	432.0000	Multiply (144 × 3 = 432)
3	0.0000	0.0000	432.0000	3.0000	Key number 3 on floor X
[f] [√x]	0.0000	0.0000	432.0000	1.7321	Extract square root in place (√3 ≈ 1.732051)
[×]	0.0000	0.0000	0.0000	748.2459	Multiply by √3 (432 × 1.732051 = 748.2459)
2	0.0000	0.0000	748.2459	2.0000	Key denominator divisor 2
[÷]	0.0000	0.0000	0.0000	374.1230	Halve to finalize regular hexagonal area

Register X displays 374.1230. Hexagonal gazebo floor area is **374.12 cm^2**.

Challenge 10: Irrigation Pipe Annular Gasket Ring

The park irrigation line uses neoprene annular washers with outer radius R = 25 mm and inner pipe cutout radius r = 10 mm. Calculate the rubber seal contact area ($A = \pi (R^2 - r^2)$). Cut a 10 mm disk out of a 25 mm outer circle. The remaining annular washer area is the difference between the outer circle and inner circle areas. Bring this to the SC-6 stack: 25 [x²] 10 [x²] [-] [π] [×] → 1,649.336143.

Key 25, press [x²] (625), key 10, press [x²] (100), and press [-] to calculate the difference of radius squares 525 mm^2 (T:0, Z:0, Y:0, X:525). Push [π] and press [×] to scale by the circle constant, arriving at the annular contact area (T:0, Z:0, Y:0, X:1649.3361). Register X displays 1649.3361. Gasket contact area is **1649.34 mm^2**.

6.7.3 Expedition 2: The Antarctic Research Station Cold-Weather Packaging (Challenges 6.11–6.20)

Mission Briefing: You are the logistics officer at McMurdo Station, Antarctica. Sensitive scientific equipment, lithium battery packs, and insulated survival shelters must be wrapped in specialized thermal mylar. Remember the penguin huddle: heat escapes through surface area! Use the Master [Σ+] Technique to calculate exact face pair areas without scratch paper.

Challenge 11: Thermal Insulation for a Scientific Sensor Pod

At McMurdo Station, an automated meteorological sensor pod measuring 6 cm × 4 cm × 2 cm must be sealed in aluminized thermal mylar to withstand -40^°C polar winds. Calculate the total outer surface area across all six faces.

Unfold the rectangular prism net. Observe that the 6 rectangular faces organize into three congruent pairs: top/bottom (6 × 4), front/back (6 × 2), and left/right (4 × 2). The Master [Σ+] Technique accumulates each pair into memory without scratch paper. On your SC-6, enter [g] [CLΣ] [6] [ENTER] [4] [×] [2] [×] [Σ+] [6] [ENTER] [2] [×] [2] [×] [Σ+] [4] [ENTER] [2] [×] [2] [×] [Σ+] [f] [Σx] → 88.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[g] [CLΣ]	0.0000	0.0000	0.0000	0.0000	Clear statistical memory accumulators (n = 0, ∑ x = 0)
6	0.0000	0.0000	0.0000	6.0000	Key in pod length (6 cm)
[ENTER]	0.0000	0.0000	6.0000	6.0000	Stack lifts; length locked into Register Y
4	0.0000	0.0000	6.0000	4.0000	Key in pod width (4 cm)
[×]	0.0000	0.0000	0.0000	24.0000	Multiply length by width for single top face (24 cm^2)
2	0.0000	0.0000	24.0000	2.0000	Key in face-pair factor 2
[×]	0.0000	0.0000	0.0000	48.0000	Double for top and bottom face pair (48 cm^2)
[Σ+]	0.0000	0.0000	0.0000	1.0000	Accumulate pair 1 into ∑ x (n = 1, ∑ x = 48)
6	0.0000	0.0000	0.0000	6.0000	Key in pod length (6 cm)
[ENTER]	0.0000	0.0000	6.0000	6.0000	Stack lifts; length locked into Register Y
2	0.0000	0.0000	6.0000	2.0000	Key in pod height (2 cm)
[×]	0.0000	0.0000	0.0000	12.0000	Multiply length by height for single front face (12 cm^2)
2	0.0000	0.0000	12.0000	2.0000	Key in face-pair factor 2
[×]	0.0000	0.0000	0.0000	24.0000	Double for front and back face pair (24 cm^2)
[Σ+]	0.0000	0.0000	0.0000	2.0000	Accumulate pair 2 into ∑ x (n = 2, ∑ x = 72)
4	0.0000	0.0000	0.0000	4.0000	Key in pod width (4 cm)
[ENTER]	0.0000	0.0000	4.0000	4.0000	Stack lifts; width locked into Register Y
2	0.0000	0.0000	4.0000	2.0000	Key in pod height (2 cm)
[×]	0.0000	0.0000	0.0000	8.0000	Multiply width by height for single side face (8 cm^2)
2	0.0000	0.0000	8.0000	2.0000	Key in face-pair factor 2
[×]	0.0000	0.0000	0.0000	16.0000	Double for left and right end pair (16 cm^2)
[Σ+]	0.0000	0.0000	0.0000	3.0000	Accumulate pair 3 into ∑ x (n = 3, ∑ x = 88)
[f] [Σx]	0.0000	0.0000	0.0000	88.0000	Recall total accumulated surface area across all 6 faces

Register X displays 88.0000. Total thermal foil area is **88.00 cm^2**.

Challenge 12: Thermal Foil for a Modular Cube Telemetry Pod

A miniature cubic GPS beacon deployed on the Ross Ice Shelf measures s = 2 cm along each edge. Calculate its total six-sided surface area. Examine a single 20 mm counting cube. It has 6 identical square facets. Calculating one square face (s^2) and multiplying by 6 yields the complete outer skin. Execute the sequence on your SC-6: [2] [x²] [6] [×] → 24.

Key 2, press [x²] (4 cm^2), key 6, and press [×] to multiply the face area by 6 facets (T:0, Z:0, Y:0, X:24). Register X displays 24.0000. Beacon surface area is **24.00 cm^2**.

6.7.4 Expedition 2: Prisms, Cylinders & 3D Packaging Architecture (Challenges 13–24)

> **Thematic Arc:** Extending flat base areas into third-dimension volumes and multi-face surface areas using snap cubes and the 4-level stack.

Challenge 13: Thermal Wrap for an Equilateral Prismatic Ice Core Carrier

Drillers extract deep glacial ice cores and transport them in triangular insulated containers. The equilateral triangular ends have base $b = 4$ cm and altitude $h = 3.464$ cm, while the elongated container length is $L = 20$ cm. Find total surface area. Unfold the triangular net: the two triangular ends combine into one rectangle ($2 \times (1/2)bh = bh$), and the three rectangular side walls form a large unfolding strip ($3 \times 4 \times 20$). On your SC-6, key in `[g] [CLΣ] [4] [ENTER] 3.464 [×] [Σ+] [4] [ENTER] 20 [×] [3] [×] [Σ+] [f] [Σx]` → 253.856.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[g] [CLΣ]`	0.0000	0.0000	0.0000	0.0000	Reset statistical accumulator ($n = 0$, $\sum x = 0$)
4	0.0000	0.0000	0.0000	4.0000	Key in triangular end base (4 cm)
`[ENTER]`	0.0000	0.0000	4.0000	4.0000	Stack lifts; base locked into Register Y
3.464	0.0000	0.0000	4.0000	3.464	Key in triangle height (3.464 cm)
`[×]`	0.0000	0.0000	0.0000	13.856	Multiply: two triangular ends combine into $bh = 13.856$ cm^2
`[Σ+]`	0.0000	0.0000	0.0000	1.0000	Deposit both end caps into accumulator ($n = 1$, $\sum x = 13.856$)
4	0.0000	0.0000	0.0000	4.0000	Key in prism side width (4 cm)
`[ENTER]`	0.0000	0.0000	4.0000	4.0000	Stack lifts; width locked into Register Y
20	0.0000	0.0000	4.0000	20.0000	Key in container length (20 cm)
`[×]`	0.0000	0.0000	0.0000	80.0000	Multiply for single rectangular wall area (80 cm^2)
3	0.0000	0.0000	80.0000	3.0000	Key in 3 congruent wrapping side walls
`[×]`	0.0000	0.0000	0.0000	240.0000	Multiply to obtain total lateral area (240 cm^2)
`[Σ+]`	0.0000	0.0000	0.0000	2.0000	Deposit lateral walls into accumulator ($n = 2$, $\sum x = 253.856$)
`[f] [Σx]`	0.0000	0.0000	0.0000	253.856	Recall total accumulated prism surface area

Register X displays 253.8560. Total insulation wrap area is **253.86 cm^2**.

Challenge 14: Surface Area of a Cylindrical Antarctic Water Sampling Flask

Field scientists collect sub-glacial water in an insulated cylindrical titanium flask with radius $r = 3.3$ cm and height $h = 12.2$ cm. Find total titanium surface area (top lid, bottom base, and curved cylindrical jacket). Unroll the cylinder net: the top and bottom form circular discs of area πr^2, while the curved wall unrolls into a rectangle of height h and width equal to circumference $2\pi r$. On the SC-6 keypad, enter `[g] [CLΣ] 3.3 [f] [CIRC] [2] [×] [Σ+] 3.3 [ENTER] [2] [×] [π] [×] 12.2 [×] [Σ+] [f] [Σx]` → 321.38492846.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[g] [CLΣ]`	0.0000	0.0000	0.0000	0.0000	Reset statistical memory bin ($n = 0$, $\sum x = 0$)
3.3	0.0000	0.0000	0.0000	3.3	Key in flask radius (3.3 cm)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[f] [CIRC]	0.0000	0.0000	0.0000	34.2119	Dedicated circle solver evaluates single disc area (πr^2)
2	0.0000	0.0000	34.2119	2.0000	Key in multiplier 2 for circular ends
[×]	0.0000	0.0000	0.0000	68.4239	Double for top and bottom lids (68.4239 cm^2)
[Σ+]	0.0000	0.0000	0.0000	1.0000	Deposit both end discs into accumulator ($n = 1$, $\sum x = 68.4239$)
3.3	0.0000	0.0000	0.0000	3.3	Key in radius (3.3 cm)
[ENTER]	0.0000	0.0000	3.3	3.3	Stack lifts; radius locked into Register Y
2	0.0000	0.0000	3.3	2.0000	Key doubling factor 2 for diameter
[×]	0.0000	0.0000	0.0000	6.6	Multiply to obtain diameter (6.6 cm)
[π]	0.0000	0.0000	6.6	3.1416	Push circle constant $\pi \approx 3.141593$
[×]	0.0000	0.0000	0.0000	20.7345	Multiply diameter by π for circumference (20.7345 cm)
12.2	0.0000	0.0000	20.7345	12.2	Key in cylinder height (12.2 cm)
[×]	0.0000	0.0000	0.0000	252.9610	Multiply circumference by height for lateral wall (252.961 cm^2)
[Σ+]	0.0000	0.0000	0.0000	2.0000	Deposit lateral jacket into accumulator ($n = 2$, $\sum x = 321.385$)
[f] [Σx]	0.0000	0.0000	0.0000	321.3849	Recall total accumulated cylindrical surface area

Register X displays 321.3849. Total titanium flask surface area is **321.38 cm^2**.

Challenge 15: Lateral Surface Area of a Conical Field Radar Beacon Cap

An ice-field radar transponder is protected by a bright orange conical fiberglass cowl with base radius $r = 8$ cm and slant height $s = 18$ cm. The base is open to mount onto the antenna mast. Find lateral fiberglass surface area ($A = \pi r s$). Cut along the slant seam of a paper cone: it unrolls into a circular sector of radius s and arc length $2\pi r$. Sector area resolves directly to $\pi r s$. Turning to your SC-6, key in **[π] [8] [×] 18 [×]** → `452.38934212`.

Push **[π]**, key `8`, and press **[×]** (25.1327 cm) `(T:0, Z:0, Y:0, X:25.1327)`. Key `18` and press **[×]** to multiply by slant height, evaluating the lateral conical area `(T:0, Z:0, Y:0, X:452.3893)`. Register X displays 452.3893. Lateral fiberglass cowl area is **452.39 cm^2**.

Challenge 16: Surface Area of a Pyramidal Field Tent Shelter

An emergency survival tent is built as a square pyramid with a square footprint of side $s = 20$ cm (1:10 scale model) and triangular wall slant height $l = 16$ cm. Calculate total surface area (floor plus four triangular canopy walls). Unfold the square pyramid net into a four-pointed star: one central square floor (s^2) surrounded by four congruent triangles ($4 \times (1/2)sl = 2sl$). With your SC-6 ready, enter **[g] [CLΣ] 20 [x²] [Σ+] 20 [ENTER] 16 [×] [2] [×] [Σ+] [f] [Σx]** → `1040`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[g] [CLΣ]	0.0000	0.0000	0.0000	0.0000	Clear statistical accumulator ($n = 0$, $\sum x = 0$)
20	0.0000	0.0000	0.0000	20.0000	Key in square floor base side (20 cm)
[x²]	0.0000	0.0000	0.0000	400.0000	Square side length ($20^2 = 400$ cm^2) for floor area
[Σ+]	0.0000	0.0000	0.0000	1.0000	Deposit floor square into accumulator ($n = 1$, $\sum x = 400$)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
20	0.0000	0.0000	0.0000	20.0000	Key in tent base edge (20 cm)
[ENTER]	0.0000	0.0000	20.0000	20.0000	Stack lifts; edge locked into Register Y
16	0.0000	0.0000	20.0000	16.0000	Key in wall slant height (16 cm)
[×]	0.0000	0.0000	0.0000	320.0000	Multiply base by slant height (20 × 16 = 320)
2	0.0000	0.0000	320.0000	2.0000	Scale by 2 (4 × (1 / 2) = 2) for all 4 triangular faces
[×]	0.0000	0.0000	0.0000	640.0000	Multiply to evaluate total canopy wall area (640 cm^2)
[Σ+]	0.0000	0.0000	0.0000	2.0000	Deposit 4 canopy walls into accumulator (n = 2, ∑ x = 1040)
[f] [Σx]	0.0000	0.0000	0.0000	1040.0000	Recall total tent model surface area

Register X displays 1040.0000. Total pyramid tent surface area is **1040.00 cm^2**.

Challenge 17: Open-Top Cold-Storage Battery Cargo Pod

A rugged open-top insulated cargo bin for lithium power cells measures length L = 30 cm, width W = 20 cm, and depth H = 15 cm. Calculate interior protective lining area across its 5 open-top faces (bottom floor, two side walls, two end walls). Unfold an open-top box net: cross-shaped layout with 1 central floor panel (30 × 20) and 4 perimeter walls. The top lid is omitted (5 faces total). Step over to your SC-6 and key in **[g] [CLΣ] 30 [ENTER] 20 [×] [Σ+] 30 [ENTER] 15 [×] [2] [×] [Σ+] 20 [ENTER] 15 [×] [2] [×] [Σ+] [f] [Σx]** → 2100.

Key **[g] [CLΣ]** to reset accumulators (T:0, Z:0, Y:0, X:0). Key 30, press **[ENTER]**, key 20, and press **[×]** to compute single floor 600 cm^2 (T:0, Z:0, Y:0, X:600), then deposit with **[Σ+]** (T:0, Z:0, Y:0, X:1). Key 30, press **[ENTER]**, key 15, press **[×]** (450 cm^2), key 2, and press **[×]** (900 cm^2); deposit long wall pair with **[Σ+]** (T:0, Z:0, Y:0, X:2). Key 20, press **[ENTER]**, key 15, press **[×]** (300 cm^2), key 2, and press **[×]** (600 cm^2); deposit end wall pair with **[Σ+]** (T:0, Z:0, Y:0, X:3). Press **[f] [Σx]** to recall total open-top surface area (T:0, Z:0, Y:0, X:2100). Register X displays 2100.0000. Open-top lining area is **2100.00 cm^2**.

Challenge 18: Hollow Ice Core Borehole Thermal Sleeve

A vertical borehole casing sleeve drilled into the polar ice sheet has inner radius r = 0.5 m and depth L = 4 m. Find the inner cylindrical surface area lining the ice borehole. A hollow open-ended cylinder has zero top or bottom caps; its surface is solely the unrolled rectangle formed by circumference times depth (A = 2 π r L). Now compute it on your SC-6: 0.5 [ENTER] [2] [×] [π] [×] [4] [×] → 12.566370614.

Key 0.5, press **[ENTER]**, key 2, and press **[×]** to compute borehole diameter 1.0 m (T:0, Z:0, Y:0, X:1). Push **[π]** and press **[×]** to obtain circumference 3.1416 m (T:0, Z:0, Y:0, X:3.1416). Key 4 and press **[×]** to multiply by casing depth, giving inner borehole sleeve area (T:0, Z:0, Y:0, X:12.5664). Register X displays 12.5664. Inner borehole sleeve area is **12.57 m^2**.

Challenge 19: Deep-Freeze Survival Rations Container Volume

Emergency freeze-dried meal bricks are packed into a heavy-duty container measuring length 18 cm, width 6 cm, and height 28 cm. Find the total internal volume in cubic centimeters. Model small with your kit: lay a miniature 3 × 1 block base (3 unit cubes) and stack 2 layers high (3 × 1 × 2 = 6 blocks) to feel how layers build 3D volume (V = l × w × h). Then scale big on StackCalc for the full 18 × 6 × 28 cm rations container: Run the sequence on your SC-6: 18 [ENTER] [6] [×] 28 [×] → 3024.

Key 18, press [ENTER], key 6, and press [×] to compute base footprint 108 cm^2 (T:0, Z:0, Y:0, X:108). Key 28 and press [×] to multiply footprint by height, yielding total container volume (T:0, Z:0, Y:0, X:3024). Register X displays 3024.0000. Container internal volume is **3024.00 cm^3**.

Challenge 20: Modular Polar Research Station Habitat Block Volume

An insulated habitat module is assembled from 24 prefabricated cubic units, each measuring 2 cm × 2 cm × 2 cm on a 1:100 engineering architectural model. Calculate total module volume. Take a 2 cm unit cube from your kit. Compute its unit volume via $s^3 = 2^3 = 8$ cm^3. Multiplying by 24 interlocking blocks yields the aggregate volume. Verify the calculation on your SC-6: [2] [ENTER] [3] [g] [y□] 24 [×] → 192.

Key 2, press [ENTER], key 3, and press [g] [y□] to compute unit cube volume 8 cm^3 (T:0, Z:0, Y:0, X:8). Key 24 and press [×] to scale across all 24 modular blocks, finding aggregate habitat volume (T:0, Z:0, Y:0, X:192). Register X displays 192.0000. Habitat model volume is **192.00 cm^3**.

6.7.5 Expedition 3: The City Water Works & Storage Reservoirs (Challenges 6.21–6.30)

Mission Briefing: You are the chief engineer at the municipal water utility. Your department manages cylindrical water towers, conical gravel drainage basins, spherical storage spheres, and laboratory fluid displacement tests. Calculate exact cubic meter capacities, fluid liters, and structural displacements using the 3D volume formulas.

Challenge 21: Municipal Cylindrical Water Tower Capacity

A municipal water storage tower has an interior radius r = 4 m and height h = 16 m. Calculate total holding capacity in cubic meters. Modeling small with blocks, take the clear cylindrical measuring vessel. Measure circular base radius r = 4 cm on the grid mat. Tapping [f] [CIRC] evaluates base area πr^2; multiplying by height 16 cm models the continuous volumetric fill. Test this directly on your SC-6: [4] [f] [CIRC] 16 [×] → 804.

Key 4 and press [f] [CIRC] to compute circular base footprint 50.2655 m^2 (T:0, Z:0, Y:0, X:50.2655), then key 16 and press [×] to multiply by height 16 m and evaluate total storage capacity to 804.25 m^3 (T:0, Z:0, Y:0, X:804.2477) (≈ 804,248 liters). Register X displays 804.2477. Total storage capacity is **804.25 m^3** (≈ 804,248 liters).

Challenge 22: Conical Sand Filtration Drainage Pile Volume

A sand filtration pile at the municipal water treatment facility forms a cone with base radius r = 3 meters and vertical peak height h = 2 meters. Find the total volume of filter sand. Modeling small with blocks, pour three equal conical scoops of sand into the matching cylindrical sleeve of height 2 cm and radius 3 cm. Exactly three conical volumes fill the cylinder, grounding Archimedes' (1 / 3) divisor. Bring this to the SC-6 stack: [3] [f] [CIRC] [2] [×] [3] [÷] → 18.849555922.

Key 3, press [f] [CIRC] to compute base area 28.2743 m^2, key 2, and press [×] to reach bounding cylinder volume 56.5487 m^3 (T:0, Z:0, Y:0, X:56.5487), then key 3 and press [÷] to apply Archimedes' conical reduction factor, yielding 18.85 m^3 (T:0, Z:0, Y:0, X:18.8496). Register X displays 18.8496. Filter sand pile volume is **18.85 m^3**.

Challenge 23: Square Pyramid Reservoir Enclosure Roof

A square pyramid roof caps an outdoor water storage reservoir. The base measures s = 12 m on each side, and the vertical peak height is h = 5 m. Find the enclosed roof volume. Modeling small with blocks, construct a square base using interlocking Geo-Sticks. Raising four slant struts to an apex encloses one-third the volume of the enclosing prism box. On

your SC-6, enter `12 [x²] [5] [×] [3] [÷]` → `240`.

Key `12` and press **[x²]** to square the base edge to 144 m^2 `(T:0, Z:0, Y:0, X:144)`, key `5`, press **[×]** to enclose the bounding prism 720 m^3, and key `3` followed by **[÷]** to find the enclosed pyramid roof volume of 240.00 m^3 `(T:0, Z:0, Y:0, X:240)`. Register X displays 240.0000. Enclosed reservoir roof volume is **240.00 m^3**.

Challenge 24: Spherical Pressure Surge Surge-Vessel

A spherical high-pressure surge vessel absorbs hydraulic shock waves in the main aqueduct line. Its internal radius is r = 12 cm. Find the total internal gas/fluid expansion volume. Modeling small with blocks, place the 3D spherical shell inside a bounding cylinder. Archimedes' theorem demonstrates that the sphere occupies exactly two-thirds of the cylinder's volume, verifying $V = (4 / 3)\pi r^3$. Execute the sequence on your SC-6: **[4] [ENTER] [3] [÷] [π] [×] 12 [ENTER] [3] [g] [y^x] [×]** → `7,238.229474`.

Key `4 [ENTER] 3 [÷] [π] [×]` to establish the spherical coefficient $(4 / 3)\pi \approx 4.1888$, then key `12 [ENTER] 3 [g] [y^x]` to cube radius 12 cm to 1,728 cm^3 `(T:0, Z:0, Y:4.1888, X:1728)`, and press **[×]** to compute the total surge vessel volume of 7,238.23 cm^3 `(T:0, Z:0, Y:0, X:7238.2295)`. Register X displays 7238.2295. Surge vessel internal volume is **7238.23 cm^3**.

6.7.6 Expedition 3: Domes, Cones & Clockwork Angles (Challenges 25–38)

> **Thematic Arc:** Introducing `π`, `x²`, and `→HMS` angle/time conversions to measure hemispherical domes, cylindrical towers, and planetary gear dials.

Challenge 25: Hemispherical Reservoir Planetarium Dome Volume

A municipal water educational facility features a hemispherical observation dome with radius r = 8 meters. Find the total enclosed air volume beneath the dome. Modeling small with blocks, place the transparent hemispherical dome on the flat grid desk. The volume is calculated by computing the full sphere volume $(4 / 3)\pi r^3$ and dividing by 2 on the stack floor. On your SC-6, key in **[4] [ENTER] [3] [÷] [π] [×] [8] [ENTER] [3] [g] [y^x] [×] [2] [÷]** → `1,072.330292`.

Key `4 [ENTER] 3 [÷] [π] [×] 8 [ENTER] 3 [g] [y^x] [×]` to evaluate the full sphere volume 2,144.6606 m^3 `(T:0, Z:0, Y:0, X:2144.6606)`, then key `2 [÷]` to yield the hemispherical observation dome capacity of 1,072.33 m^3 `(T:0, Z:0, Y:0, X:1072.3303)`. Register X displays 1072.3303. Hemispherical dome capacity is **1072.33 m^3**.

Challenge 26: Water Quality Testing Lab Fluid Displacement

In the water utility testing laboratory, an irregular mineral core sample is submerged into a graduated cylinder of radius r = 2.5 cm. The water level rises by Δ h = 3.2 cm. Find the exact volume of the rock sample. Modeling small with blocks, submerge an irregular acrylic specimen into the calibrated cylinder. Observe the meniscus displace upward by exactly 3.2 cm, proving that displaced fluid volume equals specimen volume. On the SC-6 keypad, enter `2.5 [f] [CIRC] 3.2 [×]` → `62.831853072`.

Key `2.5` and press **[f] [CIRC]** to evaluate cylinder cross-section to 19.6350 cm^2 `(T:0, Z:0, Y:0, X:19.635)`, then key `3.2` and press **[×]** to multiply by displacement rise 3.2 cm and find the displaced mineral sample volume of 62.83 cm^3 `(T:0, Z:0, Y:0, X:62.8319)` (62.83 mL). Register X displays 62.8319. Displaced mineral sample volume is **62.83**

cm^3 (62.83 mL).

Challenge 27: Conical Frustum Water Treatment Settling Tank

A municipal clarifier conical frustum settling basin has top rim radius R = 10 m, bottom base radius r = 6 m, and vertical depth h = 12 m. Calculate total sediment basin volume using $V = (\pi h / 3)(R^2 + r^2 + Rr)$. Assemble the truncated cone nesting rings on the desk. Verify that the intermediate cross-term Rr accounts for the continuous slant wall expansion between top and bottom circular disks. Turning to your SC-6, key in `10 [x²] [6] [x²] [+] 10 [ENTER] [6] [×] [+] [π] [×] 12 [×] [3] [÷]` → `2,463.00864`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
10	0.0000	0.0000	0.0000	10.0000	Key in top rim radius (10 m)
[x²]	0.0000	0.0000	0.0000	100.0000	Square top radius ($10^2 = 100$)
6	0.0000	0.0000	100.0000	6.0000	Key in bottom base radius (6 m); R^2 lifts to Register Y
[x²]	0.0000	0.0000	100.0000	36.0000	Square bottom radius ($6^2 = 36$)
[+]	0.0000	0.0000	0.0000	136.0000	Add radius squares ($R^2 + r^2 = 100 + 36 = 136$)
10	0.0000	0.0000	136.0000	10.0000	Key in top radius 10; sum lifts to Register Y
[ENTER]	0.0000	136.0000	10.0000	10.0000	Stack lifts; top radius copied to Register Y
6	0.0000	136.0000	10.0000	6.0000	Key in bottom radius 6
[×]	0.0000	0.0000	136.0000	60.0000	Compute radii cross-product ($R \times r = 10 \times 6 = 60$)
[+]	0.0000	0.0000	0.0000	196.0000	Add cross-term to sum of squares ($136 + 60 = 196$)
[π]	0.0000	0.0000	196.0000	3.1416	Push circle constant π; geometric factor lifts to Register Y
[×]	0.0000	0.0000	0.0000	615.7522	Multiply factor by π ($196\pi \approx 615.7522$)
12	0.0000	0.0000	615.7522	12.0000	Key in vertical tank depth (12 m); scaled factor lifts to Register Y
[×]	0.0000	0.0000	0.0000	7389.0259	Multiply by basin depth (7389.0259)
3	0.0000	0.0000	7389.0259	3.0000	Key in frustum divisor 3; accumulated product lifts to Register Y
[÷]	0.0000	0.0000	0.0000	2463.0086	Divide by 3 to finalize frustum basin volume ($(\pi h / 3)(R^{2+r2+Rr})$)

Register X displays 2463.0086. Conical frustum basin volume is **2463.01 m^3**.

Challenge 28: Water Plant Pumping Shift Duration via [f] [■HR]

The municipal filtration pumps start at 8:15 AM (8.15 HMS) and shut down for maintenance at 3:05 PM (15.05 HMS). Find total active pumping duration. Modeling small with blocks, align the hour and minute indicators of the base-60 gear clock to 8:15 and advance through 15:05. Observe that 6 full hours and 50 minutes elapse, proving modulo-60 subtraction. With your SC-6 ready, enter `15.05 [f] [→HR] 8.15 [f] [→HR] [-] [g] [→HMS]` → `6.5`.

Key `15.05 [f] [→HR] 8.15 [f] [→HR] [-]` to convert shutdown 15:05 to 15.0833 hr and startup 8:15 to 8.25 hr and subtract to find 6.8333 decimal hours `(T:0, Z:0, Y:0, X:6.8333)`, then tap **[g] [→HMS]** to display the active pumping duration of 6 hr 50 min `(T:0, Z:0, Y:0, X:6.50)` (6.50 HMS). Register X displays 6.5000. Total elapsed pumping duration is **6 hr 50 min** (6.50 HMS).

Challenge 29: Reservoir Backwash Cycle Completion Time

A backwash filtration cycle initiates at 7:10 AM (7.10 HMS) and runs continuously for 3 hours and 48 minutes (3.48 HMS). Determine exact cycle completion time. Modeling small with blocks, dial the clock face from 7:10 forward by 3 hours to 10:10, then advance 48 minutes across the modulo-60 sector to 10:58. Step over to your SC-6 and key in `7.10 [f] [→HR] 3.48 [f] [→HR] [+] [g] [→HMS]` → `10.58`.

Key `7.10 [f] [→HR] 3.48 [f] [→HR] [+]` to convert start time 7:10 to 7.1667 hr and runtime 3h 48m to 3.8 hr and add to reach 10.9667 decimal hours (`T:0, Z:0, Y:0, X:10.9667`), then tap **[g] [→HMS]** to confirm cycle completion at 10:58 AM (`T:0, Z:0, Y:0, X:10.58`) (10.58 HMS). Register X displays 10.5800. Backwash cycle completes at **10:58 AM** (10.58 HMS).

Challenge 30: Overnight Aqueduct Flow Transfer Across Midnight

An inter-basin raw water transfer begins at 21:30 (9:30 PM) and runs for 4 hours and 45 minutes (4.45 HMS). Calculate overnight valve shutoff time. Track rotation on the 24-hour planetary clock ring. Advancing past 24:00 wraps the continuous hand smoothly into the early morning hours, grounding modulo-24 subtraction. Now compute it on your SC-6: `21.30 [f] [→HR] 4.45 [f] [→HR] [+] 24 [-] [g] [→HMS]` → `2.15`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`21.30`	0.0000	0.0000	0.0000	21.3000	Key in transfer start time 21:30 (`HH.MM` format)
[f] [→HR]	0.0000	0.0000	0.0000	21.5000	Convert departure time to decimal hours (21 + 30/60 = 21.5)
`4.45`	0.0000	0.0000	21.5000	4.4500	Key in pump runtime 4h 45m; start time lifts to Register Y
[f] [→HR]	0.0000	0.0000	21.5000	4.7500	Convert runtime to decimal hours (4 + 45/60 = 4.75)
[+]	0.0000	0.0000	0.0000	26.2500	Add runtime to start time, exceeding 24 hours (26.25 hr total)
`24`	0.0000	0.0000	26.2500	24.0000	Key in 24-hour diurnal period; accumulated hours lift to Register Y
[-]	0.0000	0.0000	0.0000	2.2500	Deduct 24 hours to cross midnight into the next calendar morning (2.25 hr)
[g] [→HMS]	0.0000	0.0000	0.0000	2.1500	Convert decimal hours back to clock format (`02:15 AM`)

Register X displays 2.1500. Overnight transfer terminates at **02:15 AM** (2.15 HMS).

6.7.7 Expedition 4: The Trans-Continental Flight Navigation Desk & Planetary Clock (Challenges 6.31–6.50)

Mission Briefing: You are an international flight dispatcher coordinating trans-oceanic flight paths, midnight airport arrivals, and celestial observation azimuths. Time in the cockpit operates on base-60 clock math. Use the SC-6 Planetary Clock Sandbox, continuous hand kinematics, and **[f] [→HR]** / **[g] [→HMS]** keys to solve complex multi-leg schedules without arithmetic lag.

Challenge 31: Planetary Clock Hand Angle at 4:20

In trans-continental flight dispatch, an analog navigational heading dial reads 4:20 (4.20 HMS). Calculate the continuous hour hand azimuth angle using (4 + 20/60) × 30^°. Turn the crown on the planetary gear clock demonstrator to 4:20.

Observe that the hour hand does not stay pinned at 4; it advances smoothly one-third of the way toward 5, reaching exactly 130^°. Run the sequence on your SC-6: `[4] [ENTER] 20 [ENTER] 60 [÷] [+] 30 [×]` → `130`.

Key `4` and `[ENTER]` to hold the base hour in Register Y (T:0, Z:0, Y:4, X:4). Key `20`, `[ENTER]`, `60`, and `[÷]` to convert the minutes into a fractional hour (T:0, Z:0, Y:4, X:0.3333). Press `[+]` to obtain the continuous decimal hour 4.3333 hr (T:0, Z:0, Y:0, X:4.3333). Key `30` and press `[×]` to multiply by 30^°/hr, yielding the continuous hour hand angle (T:0, Z:0, Y:0, X:130). Register X displays 130.0000. Continuous hour hand position is **130.00^°**.

Challenge 32: Planetary Clock Hand Angle at 8:45

A cockpit heading dial displays flight waypoint time 8:45 (8.45 HMS). Determine continuous hour hand azimuth using (8 + 45/60) × 30^°. Advance the clock demonstrator to 8:45. The minute hand points at 9 (270^°), while the planetary gearing smoothly rotates the hour hand three-quarters past 8, aligning squarely at 262.5^°. Verify the calculation on your SC-6: `[8] [ENTER] 45 [ENTER] 60 [÷] [+] 30 [×]` → `262.5`.

Key `8` and `[ENTER]` to lock the base hour into Register Y (T:0, Z:0, Y:8, X:8). Key `45`, `[ENTER]`, `60`, and `[÷]` to compute the minute fraction 45/60 = 0.75 (T:0, Z:0, Y:8, X:0.75). Press `[+]` to find decimal hour 8.75 hr (T:0, Z:0, Y:0, X:8.75). Key `30` and press `[×]` to multiply by 30^°/hr, finalizing the continuous hour hand azimuth (T:0, Z:0, Y:0, X:262.5). Register X displays 262.5000. Continuous hour hand position is **262.50^°**.

Challenge 33: Angular Separation Between Clock Hands at 2:30

An azimuth radar scope aligns hands at 2:30. The minute hand points at 180^°, and the continuous hour hand rotates to (2 + 30/60) × 30^° = 75^°. Find the angular separation between hands. Place the transparent 360^° protractor over the clock face. Measure the angular wedge between the minute hand (180^°) and the hour hand (75^°), verifying an acute separation of 105^°. Test this directly on your SC-6: `180 [ENTER] 2.5 [ENTER] 30 [×] [-]` → `105`.

Key `180` and `[ENTER]` to position the minute hand azimuth in Register Y (T:0, Z:0, Y:180, X:180). Key `2.5`, `[ENTER]`, `30`, and press `[×]` to compute the continuous hour hand angle 75^° (T:0, Z:0, Y:180, X:75). Press `[-]` to subtract the hour hand angle from the minute hand angle, yielding the angular separation (T:0, Z:0, Y:0, X:105). Register X displays 105.0000. Angular separation between hands is **105.00^°**.

Challenge 34: Multi-Leg Trans-Continental Flight Schedule

Trans-Continental Flight Dispatch: A flight departs at 10:00 AM, flies Leg 1 for 2h 15m (2.15 HMS), undergoes a layover of 1h 30m (1.30 HMS), and flies Leg 2 for 3h 20m (3.20 HMS). Find final landing time. Lay out the time segment cards along the 24-hour timeline strip: 10:00 → +2h 15m = 12:15 → +1h 30m = 13:45 → +3h 20m = 17:05. Bring this to the SC-6 stack: `10 [f] [→HR] 2.15 [f] [→HR] [+] 1.30 [f] [→HR] [+] 3.20 [f] [→HR] [+] [g] [→HMS]` → `17.05`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`10`	0.0000	0.0000	0.0000	10.0000	Key in initial departure time 10:00 AM (`HH.MM`)
`[f]` `[→HR]`	0.0000	0.0000	0.0000	10.0000	Convert departure to decimal hours (10.0 hr)
`2.15`	0.0000	0.0000	10.0000	2.1500	Key in Leg 1 flight duration (2h 15m); departure lifts to Register Y
`[f]` `[→HR]`	0.0000	0.0000	10.0000	2.2500	Convert Leg 1 time to decimal hours (2 + 15/60 = 2.25)
`[+]`	0.0000	0.0000	0.0000	12.2500	Add Leg 1 to departure time (12.25 hr)
`1.30`	0.0000	0.0000	12.2500	1.3000	Key in airport layover duration (1h 30m)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[f] [→HR]	0.0000	0.0000	12.2500	1.5000	Convert layover to decimal hours (1 + 30/60 = 1.5)
[+]	0.0000	0.0000	0.0000	13.7500	Add layover to accumulated itinerary (13.75 hr)
3.20	0.0000	0.0000	13.7500	3.2000	Key in Leg 2 flight duration (3h 20m)
[f] [→HR]	0.0000	0.0000	13.7500	3.3333	Convert Leg 2 to decimal hours (3 + 20/60 = 3.3333)
[+]	0.0000	0.0000	0.0000	17.0833	Add Leg 2 to find landing time in decimal hours
[g] [→HMS]	0.0000	0.0000	0.0000	17.0500	Convert decimal hours back to clock time (17:05 or 5:05 PM)

Register X displays 17.0500. Final itinerary arrival is **17:05 HMS** (5:05 PM).

Challenge 35: Epicyclic Planetary Gear Train Reduction Ratio

A mechanical aircraft instrument drive utilizes an epicyclic planetary gear train with a sun gear of $N_s = 14$ teeth and an outer stationary ring gear of $N_r = 154$ teeth. Find the planetary reduction ratio $R = 1 + N_r / N_s$. Rotate the sun gear 12 full turns on the desk model. Observe the planetary carrier rotate through exactly one complete revolution, confirming the 12:1 reduction ratio. On your SC-6, enter `154 [ENTER] 14 [÷] [1] [+]` → `12`.

Key `154`, press **[ENTER]**, key `14`, and press **[÷]** to calculate the primary gear ratio 154 / 14 = 11 `(T:0, Z:0, Y:0, X:11)`. Key `1` and press **[+]** to add the stationary-ring planetary carrier constant, arriving at the reduction ratio `(T:0, Z:0, Y:0, X:12)`. Register X displays 12.0000. Epicyclic gear train ratio is **12.0000:1** (exact 12:1 reduction).

Challenge 36: Aviation Navigation Beacon Housing Volume

An airport visual navigation beacon housing consists of a rectangular electronics base (15 × 15 × 20 cm) topped by a square pyramid optical roof (15 × 15 × 9 cm). Calculate the total enclosed internal volume. Stack the detachable square pyramid acrylic top onto the rectangular acrylic prism base. The aggregate volume combines the full base prism with one-third of the roof's bounding prism. Execute the sequence on your SC-6: `15 [x²] 20 [×] 15 [x²] [9] [×] [3] [÷] [+]` → `5175`.

Key `15`, press **[x²]** (225 cm^2), key `20`, and press **[×]** to compute the rectangular base volume of 4500 cm^3 `(T:0, Z:0, Y:0, X:4500)`. Next, key `15`, press **[x²]** (225 cm^2), key `9`, and press **[×]** (2025 cm^3); key `3` and press **[÷]** to find the square pyramid roof volume of 675 cm^3 `(T:0, Z:0, Y:4500, X:675)`. Press **[+]** to merge both components into the total composite volume `(T:0, Z:0, Y:0, X:5175)`. Register X displays 5175.0000. Composite beacon volume is **5175.00 cm^3**.

Challenge 37: Precision Machined Instrument Housing Net Volume

An aircraft cockpit avionics chassis starts as a solid metal block (10 × 10 × 5 cm) through which a cylindrical cooling hole of radius r = 2 cm is bored through its entire 5 cm depth. Find net metal volume. Slide the solid cylindrical peg out of the pre-drilled rectangular prism block. The net volume equals the initial solid rectangular prism minus the bored cylinder void. On your SC-6, key in `10 [x²] [5] [×] [2] [f] [CIRC] [5] [×] [-]` → `437.16814693`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
10	0.0000	0.0000	0.0000	10.0000	Key in square block side length (10 cm)
[x²]	0.0000	0.0000	0.0000	100.0000	Square side length to find block top area (10^2 = 100 cm^2)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
5	0.0000	0.0000	100.0000	5.0000	Key in block height (5 cm); top area lifts to Register Y
[×]	0.0000	0.0000	0.0000	500.0000	Multiply to compute gross solid prism volume (500 cm^3)
2	0.0000	0.0000	500.0000	2.0000	Key in cylindrical drill hole radius (2 cm); prism volume lifts to Register Y
[f] [CIRC]	0.0000	0.0000	500.0000	12.5664	Compute drill hole circular area via circle key ($A = \pi \times 2^2$)
5	0.0000	500.0000	12.5664	5.0000	Key in drill hole depth (5 cm); drill area lifts to Register Y
[×]	0.0000	0.0000	500.0000	62.8319	Multiply area by depth to compute cylindrical void volume (62.8319 cm^3)
[-]	0.0000	0.0000	0.0000	437.1681	Subtract cylindrical void from gross prism to find net alloy volume

Register X displays 437.1681. Net metal chassis volume is **437.17 cm^3**.

Challenge 38: Flight Line Ground Crew Hourly Wage Computation

A flight ramp technician works from 9:15 AM to 2:45 PM (14.45 HMS) at an hourly pay rate of $18.50/hour. Find total gross compensation using [f] [→HR]. Lay down the shift interval card on the desk. Converting 9:15 AM to 9.25 hr and 2:45 PM to 14.75 hr reveals an exact shift length of 5.5 hours. On the SC-6 keypad, enter `14.45 [f] [→HR] 9.15 [f] [→HR] [-] 18.50 [×]` → `101.75`.

Key `14.45` and press [f] [→HR] to convert afternoon shift end to decimal hours (14.75 hr) `(T:0, Z:0, Y:0, X:14.75)`. Key `9.15` and press [f] [→HR] to convert morning start time to decimal hours (9.25 hr) `(T:0, Z:0, Y:14.75, X:9.25)`. Press [-] to determine shift duration of 5.5 hr `(T:0, Z:0, Y:0, X:5.5)`. Key `18.50` and press [×] to multiply hours by the wage rate, giving gross earnings `(T:0, Z:0, Y:0, X:101.75)`. Register X displays 101.7500. Total ground crew compensation earned is **$101.75**.

6.7.8 Expedition 4: Aerospace & Civil Engineering Capstone Challenges (Challenges 39–50)

Thematic Arc: Combining composite solids, hollow-core subtraction, and density-to-mass scaling across twelve real-world engineering builds.

Challenge 39: Aircraft Emergency Water Ballast Pool Mass

A marine emergency flight test water ballast flume measures 25 m × 10 m × 2 m. With fresh water density at 1,000 kg/m^3, compute total water mass in kilograms. Build a 1:100 scale cross-section model of the flume using 5 unit cubes (5 cm^3). Then scale big on StackCalc: multiplying 25 m × 10 m × 2 m gives 500 m^3, and multiplying by 1,000 kg/m^3 yields total ballast mass. Turning to your SC-6, key in `25 [ENTER] 10 [×] [2] [×] 1000 [×]` → `500000`.

Key `25`, press [ENTER], key `10`, and press [×] to compute the surface footprint 250 m^2 `(T:0, Z:0, Y:0, X:250)`. Key `2` and press [×] to calculate the flume volume of 500 m^3 `(T:0, Z:0, Y:0, X:500)`. Key `1000` and press [×] to scale volume by water density, finalizing the total ballast mass in kilograms `(T:0, Z:0, Y:0, X:500000)`. Register X displays 500000.0000. Total water ballast mass is **500,000 kg** (500 metric tons).

Challenge 40: Aviation Fuel Silo Lateral Painting Surface Area

An airport aviation fuel storage silo consists of a cylindrical body (r = 4 m, h = 10 m) capped by a hemispherical dome (r = 4 m). Find total external painting surface area (cylinder wall plus hemispherical dome, excluding ground base). Unroll the cylindrical sleeve into a rectangle of dimensions 2π r × h (25.13 m × 10 m). Pair with the hemispherical cap surface ($2\pi r^2$) and accumulate both sections into **[Σ+]**. With your SC-6 ready, enter **[g] [CLΣ] [4] [ENTER] [2] [×] [π] [×] 10 [×] [Σ+] [4] [f] [CIRC] [2] [×] [Σ+] [f] [Σx]** → 351.8583772.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[g] [CLΣ]	0.0000	0.0000	0.0000	0.0000	Clear statistical accumulator registers (n = 0, ∑ x = 0)
4	0.0000	0.0000	0.0000	4.0000	Key in cylinder radius (4 m)
[ENTER]	0.0000	0.0000	4.0000	4.0000	Stack lifts; radius locked into Register Y
2	0.0000	0.0000	4.0000	2.0000	Key in factor 2
[×]	0.0000	0.0000	0.0000	8.0000	Multiply to find cylinder diameter (2r = 8 m)
[π]	0.0000	0.0000	8.0000	3.1416	Push circle constant π; diameter lifts to Register Y
[×]	0.0000	0.0000	0.0000	25.1327	Multiply to compute cylinder perimeter (2π r ≈ 25.1327 m)
10	0.0000	0.0000	25.1327	10.0000	Key in cylinder height (10 m); perimeter lifts to Register Y
[×]	0.0000	0.0000	0.0000	251.3274	Multiply perimeter by height to compute cylinder wall area (251.3274 m^2)
[Σ+]	0.0000	0.0000	0.0000	1.0000	Accumulate cylinder wall into statistical bin (n = 1, ∑ x = 251.3274)
4	0.0000	0.0000	0.0000	4.0000	Key in hemispherical dome radius (4 m)
[f] [CIRC]	0.0000	0.0000	0.0000	50.2655	Compute circular disk area via circle key (A = π × 4^2 = 50.2655 m^2)
2	0.0000	0.0000	50.2655	2.0000	Key in dome factor 2 (hemisphere area = $2\pi r^2$); base area lifts to Register Y
[×]	0.0000	0.0000	0.0000	100.5310	Multiply by 2 to compute dome external surface (100.5310 m^2)
[Σ+]	0.0000	0.0000	0.0000	2.0000	Accumulate dome surface into statistical bin (n = 2, ∑ x = 351.8584)
[f] [Σx]	0.0000	0.0000	0.0000	351.8584	Recall total accumulated exterior surface area (∑ x)

Register X displays 351.8584. Total exterior painting area is **351.86 m^2**.

Challenge 41: Airfield Runway Drainage Culvert Concrete Lining

An airport runoff canal is L = 15 m long with an open trapezoidal cross-section: base a = 1.2 m, top b = 2.4 m, depth h = 0.8 m, and slant sides s = 1.0 m. Find total concrete lining surface area (bottom + 2 slant walls + 2 trapezoidal end walls). Unfold the five faces of the open trapezoidal trough on the desk mat: 1 base rectangle (1.2 × 15), 2 slant wall rectangles (1.0 × 15), and 2 trapezoidal end plates ((1.2+2.4 / 2) × 0.8). Step over to your SC-6 and key in **[g] [CLΣ] 1.2 [ENTER] 15 [×] [Σ+] 1.0 [ENTER] 15 [×] [2] [×] [Σ+] 1.2 [ENTER] 2.4 [+] [2] [÷] 0.8 [×] [2] [×] [Σ+] [f] [Σx]** → 50.88.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[g] [CLΣ]	0.0000	0.0000	0.0000	0.0000	Clear statistical registers (n = 0, ∑ x = 0)
1.2	0.0000	0.0000	0.0000	1.2	Key in culvert channel bottom width (1.2 m)

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[ENTER]	0.0000	0.0000	1.2	1.2	Stack lifts; bottom width locked into Register Y
15	0.0000	0.0000	1.2	15.0000	Key in channel length (15 m)
[×]	0.0000	0.0000	0.0000	18.0000	Multiply to compute bottom slab area (1.2 × 15 = 18 m^2)
[Σ+]	0.0000	0.0000	0.0000	1.0000	Deposit bottom slab area into bin (n = 1, ∑ x = 18)
1.0	0.0000	0.0000	0.0000	1.0	Key in slant side wall width (1.0 m)
[ENTER]	0.0000	0.0000	1.0	1.0	Stack lifts; slant width copied into Register Y
15	0.0000	0.0000	1.0	15.0000	Key in channel length (15 m)
[×]	0.0000	0.0000	0.0000	15.0000	Multiply to compute single slant wall area (15 m^2)
2	0.0000	0.0000	15.0000	2.0000	Key in count of symmetric slant walls (2)
[×]	0.0000	0.0000	0.0000	30.0000	Multiply to compute twin slant walls (2 × 15 = 30 m^2)
[Σ+]	0.0000	0.0000	0.0000	2.0000	Deposit slant walls into bin (n = 2, ∑ x = 48)
1.2	0.0000	0.0000	0.0000	1.2	Key in trapezoid bottom width (1.2 m)
[ENTER]	0.0000	0.0000	1.2	1.2	Stack lifts; bottom width copied to Register Y
2.4	0.0000	0.0000	1.2	2.4	Key in trapezoid top width (2.4 m)
[+]	0.0000	0.0000	0.0000	3.6	Add parallel bases (1.2 + 2.4 = 3.6 m)
2	0.0000	0.0000	3.6	2.0000	Key in averaging divisor 2
[÷]	0.0000	0.0000	0.0000	1.8	Divide to compute average width (1.8 m)
0.8	0.0000	0.0000	1.8	0.8	Key in vertical channel depth (0.8 m)
[×]	0.0000	0.0000	0.0000	1.44	Multiply to compute single trapezoid end area (1.44 m^2)
2	0.0000	0.0000	1.44	2.0000	Key in count of end plates (2)
[×]	0.0000	0.0000	0.0000	2.88	Multiply to compute twin end plates (2 × 1.44 = 2.88 m^2)
[Σ+]	0.0000	0.0000	0.0000	3.00	Deposit end plates into bin (n = 3, ∑ x = 50.88)
[f] [Σx]	0.0000	0.0000	0.0000	50.88	Recall total accumulated concrete lining surface area

Register X displays 50.8800. Total concrete culvert liner area is **50.88 m^2**.

Challenge 42: Flight Galley Conical Frustum Measuring Cup

A galley liquid measuring cup is engineered as a conical frustum with bottom radius r = 3 cm, top rim radius R = 5 cm, and depth h = 7 cm. Find fluid capacity in milliliters (cm^3) using $V = (\pi\, h / 3)(R^2 + r^2 + Rr)$. Inspect the silicone measuring cup. Calibrate the fluid fill level against the theoretical formula, confirming that the expanding slant profile holds 359 mL. Now compute it on your SC-6: [5] [x²] [3] [x²] [+] [5] [ENTER] [3] [×] [+] [π] [×] [7] [×] [3] [÷] → 359.

Key 5, press [x²] (25), key 3, press [x²] (9), and press [+] to compute $R^2 + r^2 = 34$ (T:0, Z:0, Y:0, X:34). Key 5, press [ENTER], key 3, and press [×] (15) (T:0, Z:0, Y:34, X:15). Press [+] to evaluate $R^2 + r^2 + Rr = 49$ (T:0, Z:0, Y:0, X:49). Push [π] and press [×] (153.9380), key 7 and press [×] (1077.5663), then key 3 and press [÷] to finish the frustum volume calculation (T:0, Z:0, Y:0, X:359.1888). Register X displays 359.1888. Measuring cup capacity is **359.19 mL** (359.19 cm^3).

Challenge 43: Aircraft Wing Core Hexagonal Prism Honeycomb Cell

A lightweight aircraft wing composite spar is built from regular hexagonal honeycomb cells with cell side s = 3 cm and extrusion length L = 10 cm. Find the interior air volume of a single honeycomb chamber. Assemble six equilateral triangle prisms of side 3 cm into a regular hexagon. Extruding along the 10 cm axis demonstrates that volume equals base area ($(3\sqrt{3}/2)s^2$) times length. Run the sequence on your SC-6: **[3] [x²] [3] [×] [3] [f] [√x] [×] [2] [÷] 10 [×]** → 233.82685902.

Key 3, press **[x²]** (9), key 3, and press **[×]** to compute $3s^2 = 27$ (T:0, Z:0, Y:0, X:27). Key 3, press **[f] [√x]** (1.7321), and press **[×]** to multiply by √3 (46.7654) (T:0, Z:0, Y:0, X:46.7654). Key 2 and press **[÷]** to compute hexagonal base area 23.3827 cm^2 (T:0, Z:0, Y:0, X:23.3827). Key 10 and press **[×]** to scale across extrusion length, giving total chamber volume (T:0, Z:0, Y:0, X:233.8269). Register X displays 233.8269. Honeycomb cell internal volume is **233.83 cm^3**.

Challenge 44: Airfield Radar Tower Concrete Hollow Core Block

A foundation cinder block for a radar tower measures 40 cm × 20 cm × 20 cm externally, with twin interior rectangular voids measuring 14 cm × 12 cm × 20 cm each. Find net concrete volume. Model the hollow core concept on your desk using 16 unit cubes (4 × 2 × 2 envelope) and remove 4 center cubes. Then scale big on StackCalc: evaluate the full 40 × 20 × 20 cm envelope (16,000 cm^3) and subtract both 14 × 12 × 20 cm voids (6,720 cm^3) directly in the stack. Verify the calculation on your SC-6: 40 [ENTER] 20 [×] 20 [×] 14 [ENTER] 12 [×] 20 [×] [2] [×] [-] → 9280.

Key 40, press **[ENTER]**, key 20, and press **[×]** (800 cm^2); key 20 and press **[×]** to calculate gross envelope volume of 16,000 cm^3 (T:0, Z:0, Y:0, X:16000). Next, key 14, press **[ENTER]**, key 12, and press **[×]** (168 cm^2); key 20 and press **[×]** (3360 cm^3); key 2 and press **[×]** to compute twin void volume of 6720 cm^3 (T:0, Z:0, Y:16000, X:6720). Press **[-]** to subtract the voids from the outer envelope, finding net concrete volume (T:0, Z:0, Y:0, X:9280). Register X displays 9280.0000. Net concrete volume is **9280.00 cm^3**.

Challenge 45: Navigational Dial Inscribed Equilateral Triangle Waste Area

A triangular compass pointer plate of side s = 10 cm is laser cut from a circular acrylic disc of radius R = (s / √3) ≈ 5.7735 cm. Find the waste acrylic scrap area ($A_{waste} = A_{circle} - A_{triangle}$). Overlay the equilateral triangle template inside the circular ring. The three crescent lobes between triangle edges and outer circumference represent the scrap acrylic waste. Test this directly on your SC-6: 5.7735 [f] [CIRC] 10 [x²] [3] [f] [√x] [×] [4] [÷] [-] → 61.418387279.

Key 5.7735 and press **[f] [CIRC]** to compute the enclosing circle area 104.7197 cm^2 (T:0, Z:0, Y:0, X:104.7197). Key 10, press **[x²]** (100), key 3, press **[f] [√x]** (1.7321), and press **[×]** (173.2051); key 4 and press **[÷]** to find the equilateral triangle area of 43.3013 cm^2 (T:0, Z:0, Y:104.7197, X:43.3013). Press **[-]** to deduct the triangle from the circle, isolating the scrap waste area (T:0, Z:0, Y:0, X:61.4184). Register X displays 61.4184. Scrap acrylic waste area is **61.42 cm^2**.

Challenge 46: Airport Weather Radar Geodesic Radome Strut Tubing

A 3V geodesic radar dome covering an airfield weather tracking array requires 30 Type-A struts (1.20 m), 40 Type-B struts (1.35 m), and 50 Type-C struts (1.42 m). Find total structural aluminum tubing length. Model the geodesic dome triangle vertex using 3 Type-A, 4 Type-B, and 5 Type-C Geo-Sticks from your kit. Then scale big on StackCalc: multiply the full engineering batch quantities (30 × 1.20 m, 40 × 1.35 m, 50 × 1.42 m) directly through the 4-register stack. Bring this to the SC-6 stack: 30 [ENTER] 1.20 [×] 40 [ENTER] 1.35 [×] [+] 50 [ENTER] 1.42 [×] [+] → 161.

Key 30, press **[ENTER]**, key 1.20, and press **[×]** to compute Type-A tubing length (36 m) (T:0, Z:0, Y:0, X:36). Key 40, press **[ENTER]**, key 1.35, and press **[×]** (54 m); press **[+]** to reach running sum 90 m (T:0, Z:0, Y:0, X:90). Key 50, press **[ENTER]**, key 1.42, and press **[×]** (71 m); press **[+]** to add Type-C struts and finalize total tubing length (T:0, Z:0, Y:0, X:161). Register X displays 161.0000. Total structural tubing length is **161.00**

meters.

Challenge 47: Solar Noon to Sunset Daylight Duration Arc

On the equinox at the flight base, solar noon occurs at 12:00 PM and sunset occurs at 6:18 PM (18.18 HMS). Find total afternoon daylight duration as a continuous decimal hour. Dial the 24-hour planetary clock from 12:00 through 18:18. Converting 18 minutes past 18:00 gives 18/60 = 0.3 hr, resulting in exactly 6.3 decimal hours of afternoon sun. On your SC-6, enter `18.18 [f] [→HR] 12 [-]` → `6.3`.

Key `18.18` and press **[f] [→HR]** to convert clock time to continuous decimal hours 18.3 hr `(T:0, Z:0, Y:0, X:18.3)`. Key `12` and press **[-]** to deduct solar noon reference time, leaving elapsed afternoon daylight `(T:0, Z:0, Y:0, X:6.3)`. Register X displays 6.3000. Afternoon daylight duration is **6.3000 decimal hours** (6 hr 18 min).

Challenge 48: Submerged Bronze Sphere Hydrometer Water Rise

In the avionics fluids laboratory, a solid bronze calibration ball of radius r = 3 cm is submerged into a cylindrical test beaker of radius R = 5 cm. Find the exact fluid height rise $\Delta h = (V_{sphere} / \pi R^2)$. Drop the 3D-printed calibration sphere into the fluid cylinder. The volume of fluid pushed upward spreads across the circular base area, demonstrating $\Delta h = V / (\pi R^2)$. Execute the sequence on your SC-6: **[4] [ENTER] [3] [÷] [π] [×] [3] [ENTER] [3] [g] [y□] [×] [5] [f] [CIRC] [÷]** → `1.44`.

Key `4`, press **[ENTER]**, key `3`, and press **[÷]** (1.3333); push **[π]** and press **[×]** to establish the sphere coefficient 4.1888 `(T:0, Z:0, Y:0, X:4.1888)`. Key `3`, press **[ENTER]**, key `3`, and press **[g] [y□]** (27 cm^3); press **[×]** to compute bronze sphere volume 113.0973 cm^3 `(T:0, Z:0, Y:0, X:113.0973)`. Key `5`, press **[f] [CIRC]** to find beaker base area 78.5398 cm^2 `(T:0, Z:0, Y:113.0973, X:78.5398)`, and press **[÷]** to divide displaced volume by beaker area, giving fluid rise Δ h `(T:0, Z:0, Y:0, X:1.44)`. Register X displays 1.4400. Fluid level displacement rise is **1.44 cm**.

Challenge 49: Rover Wheel Epicyclic Planetary Reduction

A robotic lunar sample rover wheel hub incorporates an epicyclic planetary gear drive with sun gear $N_s = 10$, four planets $N_p = 25$, and stationary outer ring gear $N_r = 60$. Find the overall reduction ratio $R = 1 + N_r / N_s$. Spin the central sun gear input shaft 7 turns. The wheel hub carrier rotates exactly 1 revolution, verifying the 7:1 planetary torque multiplier. On your SC-6, key in `60 [ENTER] 10 [÷] [1] [+]` → `7`.

Key `60`, press **[ENTER]**, key `10`, and press **[÷]** to evaluate primary tooth ratio 60 / 10 = 6 `(T:0, Z:0, Y:0, X:6)`. Key `1` and press **[+]** to add the carrier constant, establishing the final reduction ratio `(T:0, Z:0, Y:0, X:7)`. Register X displays 7.0000. Rover drive reduction ratio is **7.0000:1** (7:1 torque mechanical advantage).

Challenge 50: Flight Cargo Bullion Mass & Currency Valuation

High-value bullion cargo transport: A pure gold bar measures 15 cm × 8 cm × 4 cm. With gold density at 19.3 g/cm^3 and current market spot price at $65.00/gram, calculate total ingot value using the SC-6 currency formatter **[$]**. Compare the compact gold bar model against an equal-volume plastic block. The extreme density of gold (19.3 g/cm^3) packs 9.264 kg into a modest 480 cm^3 volume. On the SC-6 keypad, enter `15 [ENTER] [8] [×] [4] [×] 19.3 [×] 65 [×] [$]` → `$602160.00`.

Key `15`, press **[ENTER]**, key `8`, and press **[×]** to compute ingot footprint 120 cm^2 `(T:0, Z:0, Y:0, X:120)`. Key `4` and press **[×]** to obtain ingot volume 480 cm^3 `(T:0, Z:0, Y:0, X:480)`. Key `19.3` and press **[×]** to determine total mass 9264 g `(T:0, Z:0, Y:0, X:9264)`. Key `65` and press **[×]** to compute market bullion value `$602,160` `(T:0, Z:0, Y:0, X:602160)`. Press **[$]** to format the display via the hardware currency engine `(T:0, Z:0, Y:0, X:602160.00)`.

Register X displays `$602160.00`. Total gold bullion cargo value is **$602,160.00**.

For Parents & Teachers: Standards Alignment Matrix

The following curriculum mapping aligns the geometric and time operations of Chapter 06 with elementary and middle school standards:

| Topic / Operation | Common Core (CCSS) | Singapore Dimensions Math | Bridges in Mathematics |

| :--- | :--- | :--- | :--- |

| **Rectangle Perimeter & Area** | 3.MD.C.7, 4.MD.A.3 | Grade 3 Chapter 14, Grade 4 Ch 8 | Unit 4 Session 12–15 |

| **Triangle & Parallelogram Area** | 6.G.A.1 | Grade 6 Chapter 7 | Unit 5 Module 2 |

| **Circle Circumference & Area** | 7.G.B.4 (Accelerated Gr 6) | Grade 6 Chapter 8 | Unit 6 Module 1 |

| **Master Surface Area via `[Σ+]`** | 6.G.A.4 | Grade 6 Chapter 9 | Unit 6 Module 3 |

| **Rectangular Prism Volume** | 5.MD.C.5 | Grade 5 Chapter 11 | Unit 1 Module 4 |

| **Cylinder, Cone & Sphere Volume** | 8.G.C.9 (Accelerated Gr 6) | Grade 6 Extension | Unit 8 Module 2 |

| **Planetary Clock & Modulo-60 Time** | 3.MD.A.1, 4.MD.A.2 | Grade 3 Chapter 12, Grade 4 Ch 6 | Unit 3 Module 1 |

For detailed classroom station activities corresponding to these standards, consult Curriculum Station Worksheets: Singapore Dimensions Math .

6.8 What You Mastered & Looking Ahead

In this chapter, you expanded your mathematical toolkit into physical space, geometric solids, and continuous time:

1. **2D Plane Geometry:** You solved perimeter and area across rectangles, triangles, and circles with dedicated geometry keys (`[f] [RECT]` , `[g] [TRI]` , `[f] [CIRC]` , `[π]`).
2. **The Master Surface Area Technique:** By accumulating face pairs into statistical registers with `[Σ+]` , you calculated the complete outer boundary of complex 3D solids without intermediate scratch-paper notes.
3. **3D Volume & Capacity:** You mastered the Stack Drop method, turning flat base areas into three-dimensional volumes (`[f] [PRISM]` , `[g] [CONE]`) and compound mass-density calculations.
4. **Planetary Geared Time:** You explored continuous modulo-60 elapsed time on the 12:1 planetary gear train (`[CLOCK]`), converting seamlessly between decimal hours and digital clock format (`[f] [→HR]` , `[g] [→HMS]`).

In **Chapter 07: Data, Probability, Statistics & Prime Factors**, you will dive into the deep architecture of whole numbers and real-world data. You will organize empirical observations into frequency tables, compute means and medians with statistical accumulators, and construct towering prime factorizations with color-coded Prime Factor Studio rods and the SC-6 hardware keys (`[PRIME]` , `[g] [FACT]` , `[g] [÷R]`). Welcome to the engine room of numbers!

Discrete Probability, Primes & Pre-Algebra

7.1 Why Do Primes and Probability Matter in the Real World?

You often hear that "prime numbers are numbers that can only be divided by 1 and themselves." That sounds like an arbitrary rule invented to give you boring homework.

In the physical universe, **prime numbers and probability are how living creatures survive predators, how secret codes protect spacecraft, and how games stay fair!**

7.1.1 The 17-Year Cicada Mystery: How Primes Defeat Predators

Every 13 or 17 years across the deciduous forests of North America, billions of periodical cicadas (*Magicicada*) erupt from the soil on the exact same warm spring weekend, filling the forest canopy with an overwhelming roar.

Biologists wondered for centuries: **Why 13 years? Why 17 years?** Why didn't cicadas evolve a convenient 12-year or 16-year life cycle?

The Deadly Composite Trap

Suppose a cicada brood emerged on a 12-year cycle. The number 12 is **composite**: its factors are 1, 2, 3, 4, 6, and 12.

- A predatory bird or parasitic wasp with a 2-year population surge would synchronize with them on every single emergence ($2 \times 6 = 12$).
- A predator with a 3-year boom cycle would meet them every emergence ($3 \times 4 = 12$).
- A predator with a 4-year cycle would feast on them every emergence ($4 \times 3 = 12$).

The cicada population would be devastated by specialized parasites at every generation!

The Prime Number Shield

Now look at 17. The number 17 is **prime**: its *only* factors are 1 and 17.

- A 2-year cyclical predator intersects with the cicadas only once every **34 years** ($\text{LCM}(2, 17) = 34$)!
- A 3-year cyclical predator intersects only once every **51 years** ($\text{LCM}(3, 17) = 51$)!
- A 5-year cyclical predator intersects only once every **85 years** ($\text{LCM}(5, 17) = 85$)!

By sleeping underground for an exact prime number of years, cicadas outsmart every predator in the forest! Primes are nature's secret code—the unbreakable atomic building blocks of all numbers.

> **For Parents & Teachers: Number Theory & Biological Optimization**
>
> As Carl Friedrich Gauss proved in his *Disquisitiones Arithmeticae (Gauss, 1809)* and Simon Singh chronicles in the history of number theory *(Singh, 1997)*, the Fundamental Theorem of Arithmetic establishes primes as the irreducible atomic building blocks of all integers. Nature leverages prime cycles to minimize biological overlap between prey and predators.

7.1.2 The Polyhedral Dice Maker's Secret: Why There Are Only 5 Perfect Fair Dice

Ever wonder why your favorite tabletop roleplaying games use 4, 6, 8, 12, or 20-sided dice—but nobody sells a 7-sided or 11-sided die?

Over 2,300 years ago, Greek mathematicians proved a staggering geometric fact: in our three-dimensional universe, there are **only five regular convex polyhedra** (the Platonic Solids) where every single face is an identical regular polygon and every vertex meets the exact same number of edges:

1. **Tetrahedron (d4):** 4 equilateral triangular faces
2. **Cube (d6):** 6 square faces
3. **Octahedron (d8):** 8 equilateral triangular faces
4. **Dodecahedron (d12):** 12 regular pentagonal faces
5. **Icosahedron (d20):** 20 equilateral triangular faces

If you try to make a 7-sided or 11-sided die, some sides will always be steeper or flatter than others. It is physically impossible to make them land with equal chance! True fairness in gaming isn't just about giving the dice cup a good shake—it comes from the deep spatial symmetries of the universe.

For Parents & Teachers: Probability, Geometry & Heuristics

In Jordan Ellenberg's *How Not to Be Wrong (Ellenberg, 2014)* and Martin Gardner's classic studies of mathematical games *(Gardner, 1959)*, human intuition consistently misjudges randomness and symmetry. Following David Macaulay's mechanical exposition *(Macaulay, 2016)*, Jerome Bruner's learning progression *(Bruner, 1966)*, and George Pólya's problem-solving strategies *(Pólya, 1945)*, students begin with physically balanced dice and concrete counters before transitioning to digital pseudo-random generation on the SC-6.

Chapter Baseline Mode: `[NUM]`

Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Transflective Display

(Visual Dice Sandbox `[DICE]` *opens interactive probability trials)*

Unlocked Keycaps Ribbon — Grades 5–6 Data & Pre-Algebra Suite

• **Probability & Randomness:** `[DICE]` Polyhedral Dice Sandbox, `[f] [1…x]` (Random 1 to X), `[g] [t…x]` (Random Y to X).

• **Number Theory Keys:** `[PRIME]` Primality Test, `[g] [FACT]` Prime Factor Decomposition, `[f] [C.FAC]` Common Factors, `[GCF]` Greatest Common Factor, `[f] [LCM]` Least Common Multiple, `y⌧x` (Quotient & Remainder).

• **Descriptive Statistics:** `[Σ+]` Accumulator, `[f] [Σ-]` Correction, `[N]` Sample Count, `[f] [Σx]` Sum, `[Σx²]` Sum of Squares, `[g] [x̄]` Mean `x■`, `[f] [MED]` Median, `[g] [MODE]` Mode, `[f] [MIN]` Minimum, `[g] [MAX]` Maximum, `[IQR]` Interquartile Range, `[g] [MAD]` Mean Absolute Deviation, `[FRQ]` Frequency of X.

• **Grade 6 Pre-Algebra:** `[+/-]` Signed Numbers (Zero Pairs), `[g] [|x|]` Absolute Value (Number Line Distance), Geometric `[x²]` and `[f] [√x]` (Area-to-Side Inverses).

Strict Pedagogical Gatekeeping: In accordance with developmental cognitive standards, 5th graders and younger NEVER see logarithms (`LOG`*,* `LN`*) or abstract powers (*`y⌧`*). Advanced functions are segregated exclusively into secondary advanced math extensions.*

7.2 Concrete Foundations: Two-Color Counters, Polyhedral Dice & The Sieve Grid

Before we tap keys on the calculator, we roll real dice, balance counters, and build number arrays with our hands. When you understand what the numbers look like on your desk, the calculator becomes your ultimate math assistant.

Concrete Probability & Number Theory Manipulatives

1. **Precision Dice & Spinner Studio:**

- **Equal-Volume Pip Algorithm:** $r_n = 1.8 / \sqrt{n}$ for true mechanical balance across all 4 physical d6 dice.

- **Captive Multi-Plate Spinner:** 10-sector decimal lid (0–9), plus interchangeable biased (50%, 25%, 15%, 10%), binary (0/1), and arithmetic operations dial plates.

- **Digital Polyhedral Extension (`[DICE]`):** The SC-6 hardware probability engine extends physical d6 experiments to full polyhedral dice (d4, d6, d8, d10, d12, d20).

2. **Counting & Array Studio:**

- Four high-contrast color groups modeling positive/negative integer Zero Pairs and discrete frequency histograms.

3. **Prime Factor Studio:**

- Logarithmic prime factor towers (2, 3, 5, 7) and bilateral comparator stage.

Figure: Probability Dice & Spinner Studio: 1x1 spinner enclosure with 10-sector lid, biased and binary dial plates, and 4 volume-equalized fair d6 dice

7.2.1 The Equal-Volume Pip Dice & Spinner Studio

Standard commercial dice often introduce subtle physical bias because face 6 has six excavated pips while face 1 has only one, shifting the center of gravity toward the 1-face and making 6 slightly more likely to land face up.

The StackCalc ecosystem eliminates this experimental artifact with our 3D-printable **Dice & Spinner Studio**. Pips on the four physical d6 dice are engineered using an Equal-Volume Excavation formula: **$r_n = (1.80 \text{ mm} / \sqrt{n})$** where n is the number of pips on the face. On face 1, the single pip has radius 1.80 mm; on face 6, each of the six smaller pips has

radius 1.80 / √6 ≈ 0.735 mm. The total mass excavated from every single face is mathematically identical to within 0.001 grams, ensuring true physical uniformity for classroom probability experiments, while pressing `[DICE]` on the SC-6 simulates d4, d6, d8, d10, d12, and d20 polyhedral rolls!

7.2.2 Two-Color Integer Counters & Zero Pairs

Before you manipulate signed numbers on the SC-6 keypad, you model integers concretely using two-color tokens:

- **Yellow Token:** Represents +1 (a unit gain, a deposit, an upward step).
- **Crimson Token:** Represents -1 (a unit loss, a withdrawal, a downward step).
- **The Zero Pair:** Placing 1 Yellow token and 1 Crimson token side-by-side forms a **Zero Pair** (+1 + (-1) = 0).

When solving (-5) + (+3), you place 5 Crimson tokens and 3 Yellow tokens on the mat. Pairing 3 Crimson tokens with the 3 Yellow tokens eliminates 3 Zero Pairs, leaving exactly 2 Crimson tokens: -2.

On the SC-6, this translates directly to parenthesis-free RPN stack execution: `5 [+/-] [ENTER] 3 [+]` → X = **-2**.

> **Parent's De-Stressing Guide: Why Negative × Negative Is Positive**
>
> **The Scenario:** Your 6th grader asks: *"Why is (-3) × (-2) equal to +6? Why aren't two negatives even more negative?"*
>
> **The Conventional Explanation (Confusion):**
>
> *"Because a negative times a negative is a positive. Just memorize it!"*
>
> Or: *"Two negatives make a positive in English: 'I don't not want it.'"*
>
> The child memorizes a grammar trick, but mathematical intuition dies.
>
> **The Spatial 180^° Rotation Cure:**
>
> 1. **Multiplication is walking along the number line at a steady pace:**
>
> - (+3) × (+2): Face Forward (+), take 2 steps of size 3 forward → +6.
>
> - (-3) × (+2): Face Backward (-), take 2 steps of size 3 forward → -6.
>
> 2. **Multiplying by a negative means WALKING IN REVERSE:**
>
> - (+3) × (-2): Face Forward (+), take 2 steps of size 3 in REVERSE → -6.
>
> - (-3) × (-2): Face Backward (-), take 2 steps of size 3 in REVERSE!
>
> When you face backward and walk in reverse, where do you travel?
>
> **YOU MOVE FORWARD TOWARD POSITIVE NUMBERS!** (-3) × (-2) = +6!
>
> On the SC-6: Key in `3 [+/-] [ENTER] 2 [+/-] [×]` → **+6**!
>
> You watch the sign toggle smoothly on the transflective LCD.

7.2.3 The 100-Grid Sieve of Eratosthenes Tray

To discover prime numbers, you use the physical 100-Grid Sieve Tray. The Greek mathematician Eratosthenes of Cyrene (c. 276–194 BC) proved that to find all prime numbers up to N, one only needs to cross out composite multiples of primes up to √N.

For numbers up to N = 100, because √100 = 10, you only need to test and filter multiples of the four prime numbers less than 10: **2, 3, 5, and 7**!

> **The Sieve of Eratosthenes Up to 100**

- **Step 1:** 1 is a unit (neither prime nor composite) → Filtered immediately.
- **Step 2:** Circle 2 (Prime) → Cross out all even multiples (4, 6, 8, 10, ...).
- **Step 3:** Circle 3 (Prime) → Cross out all multiples of 3 (9, 15, 21, ...).
- **Step 4:** Circle 5 (Prime) → Cross out all multiples of 5 (25, 35, 55, ...).
- **Step 5:** Circle 7 (Prime) → Cross out all multiples of 7 (49, 77, 91, ...).

All remaining standing tiles are the 25 PRIMES UNDER 100:

2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97.

You verify each standing tile on the SC-6:

- `97 [PRIME]` → Flashes `PRIME` (preserving 97 on display).
- `91 [PRIME]` → Flashes `COMPOSITE` (preserving 91 on display; 91 = 7 × 13).
- The sieve makes it visually obvious why 91 is composite while 97 is prime!

7.3 Discrete Probability & Random Trials ([■])

Probability quantifies the likelihood of an event occurring, measured on a continuum from 0 (impossible) to 1 (certain):
P(Event) = (Number of Favorable Outcomes / Total Number of Equally Likely Outcomes)

Probability P(E)	Qualitative Classification	Classroom Example
0.0	Impossible	Rolling a 7 on a standard 6-sided die (d6)
0.5	Equally Likely	Flipping Heads or Tails on a fair coin
1.0	Certain	Rolling an integer from 1 to 6 on a standard d6

7.3.1 The Classroom Dice Key ([■])

The SC-6 features a primary key **`[DICE]`** on Row 0, Col 3 that serves as an interactive probability sandbox:

1. **Interactive Die Roll:** Pressing **`[DICE]`** triggers an on-chip uniform pseudorandom number generator, animating a 3-frame rolling shuffle before settling on an integer from 1 to 6.
2. **Visual Die Rendering:** The transflective graphic LCD renders a crisp 32 × 32 pixel die face centered on the screen with authentic pip configurations.
3. **Automatic Stack Lift:** The rolled integer (1 ... 6) lands directly on the display floor (X), smoothly lifting prior stack contents (X → Y → Z → T), ready for immediate arithmetic!

Rolled Value	32×32 LCD Pip Geometry	Visual Dot Pattern
`[1]`	Single center pip	Unit point symmetry
`[2]`	Top-left & bottom-right diagonal pips	Diagonal pair
`[3]`	Top-left, center, & bottom-right pips	Diagonal triad
`[4]`	Four corner pips	2 × 2 square array
`[5]`	Four corner pips + center pip	Quincunx (4 + 1)

Rolled Value	32×32 LCD Pip Geometry	Visual Dot Pattern
[6]	Two vertical columns of three pips	2 × 3 rectangular array

7.3.2 Polyhedral Random Ranges: [f] [1…x] and [g] [t…x]

In science labs and tabletop math games, you often require random numbers beyond a standard 6-sided die:

- **[f] [1…x] (Random 1 to X):** Generates a discrete uniform integer in [1, ■ X ■].
- Roll a 20-sided die (d20): `20 [f] [1…x]` → X ∈ (1, 2, ..., 20).
- Flip a fair coin (1 = Heads, 2 = Tails): **[2] [f] [1…x]** → X ∈ (1, 2).
- Select a random lab partner from a group of 28: `28 [f] [1…x]` → X ∈ (1, 2, ..., 28).
- **[g] [t…x] (Random Y to X):** Generates a discrete uniform integer in [■ Y ■, ■ X ■].
- Generate a random two-digit number between 10 and 99: `10 [ENTER] 99 [g] [t…x]`.

Worked Example 7.1: Theoretical vs. Experimental Die Probability

You roll a standard six-sided die 60 times.

1. What is the theoretical probability of rolling a 4 on any single roll?
2. How many times should a 4 theoretically appear in 60 rolls?
3. In an actual trial, you roll a 4 twelve times. Compute the experimental probability and compare it to the theoretical value.

Theoretical Probability: P(4) = (1 / 6) ≈ 0.1667 (16.67%) Expected Frequency: 60 × (1 / 6) = 10 times

RPN Evaluation of Experimental Probability:

12 **[ENTER]** 60 **[÷]** → 0.2000 (20.0%)

Percentage Difference:

0.20 **[ENTER]** **[1]** **[ENTER]** **[6]** **[÷]** **[-]** → 0.0333 (+3.33% deviation)

7.3.3 Compound Probability: Rolling Two Dice (36 Outcomes)

When two standard dice are rolled simultaneously, the sample space consists of 6 × 6 = 36 equally likely ordered pairs (D_1, D_2). The sum $S = D_1 + D_2$ ranges from 2 to 12, forming a symmetric triangular probability distribution:

Sum (S)	Favorable Ordered Pairs (D_1, D_2)	Count	Probability P(S)
2	(1,1)	1	1/36
3	(1,2), (2,1)	2	2/36 = 1/18
4	(1,3), (2,2), (3,1)	3	3/36 = 1/12
5	(1,4), (2,3), (3,2), (4,1)	4	4/36 = 1/9
6	(1,5), (2,4), (3,3), (4,2), (5,1)	5	5/36
7	(1,6), (2,5), (3,4), (4,3), (5,2), (6,1)	**6**	**6/36 = 1/6**

Sum (S)	Favorable Ordered Pairs (D_1, D_2)	Count	Probability P(S)
8	(2,6), (3,5), (4,4), (5,3), (6,2)	5	5/36
9	(3,6), (4,5), (5,4), (6,3)	4	4/36 = 1/9
10	(4,6), (5,5), (6,4)	3	3/36 = 1/12
11	(5,6), (6,5)	2	2/36 = 1/18
12	(6,6)	1	1/36
Total	**All 6 × 6 Outcomes**	**36**	**36/36 = 1.00**

Worked Example 7.2: Probability of Rolling a Lucky 7

Find the exact fractional and decimal probability of rolling a sum of 7 with two dice.

Keystrokes:
`[6]` `[ENTER]` 36 `[÷]` → 0.166667
`[FDISP]` → 1/6 (Simplified mixed/proper display)

The probability is exactly 1/6 ≈ **16.67%**.

7.3.4 Probability Trees & Sampling Without Replacement

In hands-on probability experiments, you examine multi-stage events where the outcome of the first draw alters the sample space of subsequent draws (dependent probability).

First Draw Outcome (8 Marbles)	Second Draw Outcome (7 Remaining)	Combined Branch Probability
Red 1st (5/8)	Red 2nd (4/7)	(5 / 8) × (4 / 7) = (20 / 56)
Red 1st (5/8)	Blue 2nd (3/7)	(5 / 8) × (3 / 7) = (15 / 56)
Blue 1st (3/8)	Red 2nd (5/7)	(3 / 8) × (5 / 7) = (15 / 56)
Blue 1st (3/8)	**Blue 2nd (2/7)**	(3 / 8) × (2 / 7) = (6 / 56) = **(3 / 28)**

Worked Example 7.3: Probability of Drawing Two Blue Marbles

You reach into a cloth bag containing 5 Red and 3 Blue marbles and draw two marbles without looking and without replacing the first marble. Find the probability that both marbles are Blue: **$P(\text{Both Blue}) = P(\text{Blue}_1) \times P(\text{Blue}_2 \mid \text{Blue}_1) = (3 / 8) \times (2 / 7) = (6 / 56) = (3 / 28)$**

RPN Evaluation:
`[3]` `[ENTER]` `[8]` `[÷]` `[2]` `[ENTER]` `[7]` `[÷]` `[×]` → 0.107143
`[FDISP]` → 3/28

The probability of drawing two consecutive blue marbles is 3/28 ≈ **10.71%**.

Worked Example 7.4: Probability of At Least One Red Marble

Using the complement rule, the probability of drawing *at least one* red marble equals 1 minus the probability of drawing *no* red marbles (both blue): **P(At least one Red) = 1 - P(Both Blue) = 1 - (3 / 28) = (25 / 28)**

Keystrokes:
`[1]` `[ENTER]` `[3]` `[ENTER]` 28 `[÷]` `[-]` → 0.892857
`[FDISP]` → 25/28

The probability is **25/28 ≈ 89.29%**.

7.4 Number Theory: Primes, Factors & The Secret Partner Rule

Number theory explores the structural properties of whole numbers. Prime numbers are the fundamental "atomic elements" of arithmetic; every integer greater than 1 can be uniquely factored into a product of primes (The Fundamental Theorem of Arithmetic).

For Parents & Teachers: The CRA Continuum in Elementary Number Theory

| Stage | Modality | Classroom Experience & Manipulatives | SC-6 Calculator Bridge |

| :--- | :--- | :--- | :--- |

| **Concrete** | Physical Manipulatives | • **24-Tile Array Test:** Primes form only 1 × N straight lines; composites form 2D matrices.

• **Prime Factor Studio:** Proportional prime towers where stacking prime blocks physically multiplies their values!

• Height(2) + Height(3) = Height(6) on the comparator stage! | Physical verification before keystrokes |

| **Representational** | Graphic Sandboxes | • Screen Factor Tree View: exponents and prime dots ($2^3 \times 3^2 \times 5$).

• Dual Frame Counter `[FRAME]`.

• Interactive LCD Sieve: survivor primes highlighted on display. | Transflective LCD dot matrix |

| **Abstract** | RPN Symbolic Engines | • `[PRIME]` test flashes `PRIME` or `COMPOSITE` on the graphic status line, preserving the number on X.

• `[g]` `[FACT]` displays prime factorization string.

• `[GCF]` and `[f]` `[LCM]` execute Euclidean and Duality engines. | Stack execution (T, Z, Y, X) |

7.4.1 Station Lesson 7.1: The Rectangular Array Primality Test

- **Your Mission:** Physically investigate primality using the Counting & Array Studio, proving that prime numbers resist 2D rectangular factorization, and verify outcomes on the SC-6 via the dedicated primality key `[PRIME]`.
- **Physical Manipulatives:** 24-Tile Four-Color Counting Studio.

Number Classification	Tile Count	Complete Rectangular Factor Arrays	Positive Divisors
Composite (N = 12)	12 Tiles	1 × 12, 2 × 6, and 3 × 4 complete rectangles	`1, 2, 3, 4, 6, 12` (6 factors)
Prime (N = 13)	13 Tiles	Rows of 2, 3, or 4 always leave 1 leftover tile; only 1 × 13 forms a rectangle	`1, 13` (2 factors only)

For Parents & Teachers: Classroom Dialogue Script

Teacher: "Take 12 counting tiles from your Counting Studio. Can you arrange them into a rectangle with at least two rows and two columns?"

Student (Maya): "Yes! I built 2 rows of 6, and Marcus built 3 rows of 4!"

Teacher: "Now take 13 tiles. Try to build a rectangle that is 2 tiles wide, 3 tiles wide, or 4 tiles wide without any leftover gaps."

Maya: "It's impossible! Every time I try, there is an extra tile sticking out! The only way to fit all 13 is one long straight line of 13 tiles."

Teacher: "That is the geometric soul of a prime number: it resists being factored into two dimensions! Now let's test both numbers on the SC-6."

Calculator Keystrokes & Stack Trace (T, Z, Y, X)

Keystroke	Register T	Register Z	Register Y	Register X	Status / Screen
12	0	0	0	12	Number entered
[PRIME]	0	0	0	12	Flashes COMPOSITE
13	0	0	12	13	Stack lifts; 13 entered
[PRIME]	0	0	12	13	Flashes PRIME

7.4.2 Station Lesson 7.2: The Four-Color Sieve of Eratosthenes (24-Tile Kit & 144-Tile Classroom Pool)

- **Your Mission:** Build a 4×6 sieve for numbers 1–24 with your individual 24-tile kit to isolate all 9 primes ≤ 24—or pool 6 kits across your classroom table ($6 \times 24 = 144$ tiles) to construct the complete 12×12 matrix and isolate all 34 primes ≤ 144.
- **Manipulatives:** 24 Stacking Tiles per student kit (6 Archival White, 6 Cobalt Blue, 6 Radiant Gold, 6 Slate Gray), or 6 kits pooled (144 tiles: 36 of each color).

The Four-Color Map Sieve of Eratosthenes (Individual 24-Tile Kit or 6-Kit Classroom Pool)

- **Step 1:** Tile 1 (White) is set aside. 1 is a unit (neither prime nor composite).

- **Step 2: Prime 2 (Blue).** Replace every even multiple ≥ 4 with Blue tiles (4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, ...).

- **Step 3: Prime 3 (Gold).** Replace uncolored multiples of 3 with Gold tiles (9, 15, 21, 27, 33, 39, 45, 51, 57, 63, ...).

- **Step 4: Primes 5 & 7 (White/Pattern).** In the 6-kit classroom pool, replace remaining multiples of 5 and 7 (25, 35, 49, 55, 65, 77, 85, 91, 95, 115, 119, 121, 125, ...).

- **Step 5: Prime Survivors (Slate Gray).** In a single 24-tile kit, the 9 survivor tiles are **2, 3, 5, 7, 11, 13, 17, 19, 23**. Across a 6-kit classroom pool (144 tiles), all 34 primes ≤ 144 survive:

2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97, 101, 103, 107, 109, 113, 127, 131, 137, 139.

Hands-On Verification on SC-6:

You test survivor tiles and border cases on the calculator:

- Test 91: `91 [PRIME]` → Flashes `COMPOSITE`, leaves 91 on display ($91 = 7 \times 13$).
- Test 97: `97 [PRIME]` → Flashes `PRIME`, leaves 97 on display.
- Test 119: `119 [PRIME]` → Flashes `COMPOSITE`, leaves 119 on display ($119 = 7 \times 17$).
- Test 137: `137 [PRIME]` → Flashes `PRIME`, leaves 137 on display.

- Seat the target candidate integer onto the display floor (X). Tap `[g] [FACT]` to inspect its prime factor building blocks on the LCD shelves, verifying divisors without manual trial division.

7.4.3 Station 7.3: The Magic Prime Tower Scale — Multiplying by Stacking Blocks!

- **Your Mission:** Discover a mind-blowing secret of numbers—that multiplication can be executed by physically stacking blocks of proportional heights—using the Prime Factor Studio.
- **Physical Manipulatives:** Prime Factor Studio and Proportional Prime Blocks (2, 3, 5, 7).

> **Prime Factor Studio & Comparator Stage**
>
> The back wall of the Prime Factor Studio holds a precision height comparator calibrated from 1 to 100.
>
> Each prime number block has an exact proportional height:
>
> - Prime 2 (Blue): 12.64 mm
> - Prime 3 (Amber/Green): 20.04 mm
> - Prime 5 (Yellow): 29.36 mm
> - Prime 7 (Red): 35.50 mm
>
> When you stack prime factor blocks together on the stage, their heights add up to match the exact composite product on the comparator wall!



Figure: Prime Factor Studio: Bilateral Logarithmic Comparator Stage & Prime Factor Blocks

Try Stacking Your Prime Blocks!

1. **Multiplying 2 × 3 = 6:**

Place Blue Block `[2]` on the desk. Stack Amber/Green Block `[3]` on top. **h(2) + h(3) = 12.64 mm + 20.04 mm = 32.68 mm** The top of the stack aligns **EXACTLY with the "6" tick mark on the comparator!**

2. **Multiplying 2 × 5 = 10:**

Stack Blue Block `[2]` and Yellow Block `[5]`: **h(2) + h(5) = 12.64 mm + 29.36 mm = 42.00 mm** Lands precisely on the major decade line labeled **"10"**!

3. **Decomposing $60 = 2^2 \times 3 \times 5$:**

Stack two `[2]`s, one `[3]`, and one `[5]`: **2h(2) + h(3) + h(5) = 12.64 + 12.64 + 20.04 + 29.36 = 74.68 mm** Points squarely at the **"60"** line on the rear wall!

4. **Why Order Doesn't Change the Height:**

Reorder the stack: put Yellow `[5]` on the bottom, then `[3]`, then both `[2]`s. The total height remains identically **74.68 mm** ($5 \times 3 \times 2 \times 2 = 60$). Multiplication is commutative—no matter the order you stack them, the tower height never changes!



Figure: Prime Studio Commutativity Proof: 2x5 = 5x2 = 10 Exact Flush Alignment

Verifying on the SC-6:

Key in `60 [g] [FACT]` → The graphic display decomposes `60` into its prime factor tree (`2 × 2 × 3 × 5`):



Figure: SC-6 Prime Factorization Mode: 60 = 2 x 2 x 3 x 5

Keystroke	Register T	Register Z	Register Y	Register X	Status / Screen
60	0	0	0	60	Number entered
[g] [FACT]	0	0	0	60	Displays 2² × 3 × 5

7.4.4 The Primality Testing Engine ([PRIME])

A prime number is a positive integer strictly greater than 1 whose only positive divisors are 1 and itself. On the SC-6, pressing the primary key **[PRIME]** (Row 2, Col 2) executes a deterministic primality test on Register X:

- Momentarily flashes PRIME or COMPOSITE on the graphic status line.
- Preserves Register X intact so you can immediately continue calculations with your candidate number.
- If X ≤ 1 or non-integer, flashes INVALID DATA (or NEITHER for 0 and 1).

Keystroke	Register T	Register Z	Register Y	Register X	Status / Screen
97	0	0	0	97	Number entered
[PRIME]	0	0	0	97	Flashes PRIME
119	0	0	97	119	Stack lifts; 119 entered
[PRIME]	0	0	97	119	Flashes COMPOSITE
2	0	97	119	2	Stack lifts; 2 entered
[PRIME]	0	97	119	2	Flashes PRIME

7.4.5 Prime Factor Decomposition Engine ([g] [FACT])

Pressing **[g] [FACT]** on Row 2, Col 2 decomposes any integer ≥ 2 into its prime factor tree, formatting the output with mathematical superscripts and multiplication dots:

- Enter 12: `12` **`[g] [FACT]`** → Displays: $2^2 \times 3$
- Enter 360: `360` **`[g] [FACT]`** → Displays: $2^3 \times 3^2 \times 5$
- Enter 2,639: `2639` **`[g] [FACT]`** → Displays: $7 \times 13 \times 29$

Keystroke	Register T	Register Z	Register Y	Register X	Status / Screen
360	0	0	0	360	Number entered
`[g] [FACT]`	0	0	0	360	Displays $2^3 \times 3^2 \times 5$

7.4.6 Station Lesson 7.4: Hardware [GCF] and [f] [LCM] Keys & Tactile Block Intersections

The SC-6 promotes Greatest Common Divisor (GCD/GCF) and Least Common Multiple (LCM) to dedicated keys on **Row 2, Col 1**:

- **Primary Key `[GCF]`:** Evaluates gcd(Y, X) (e.g., `12 [ENTER] 18 [GCF]` → `6`).
- Keying `12` **`[ENTER]`** stages the first integer 12 onto Floor Y (Y = 12), and keying `18` **`[GCF]`** places 18 on Floor X (X = 18) and triggers the Euclidean engine to extract gcd(12, 18) = 6 (X = 6).
- **`[f]`-Shifted Key `[f]` `[LCM]`:** Evaluates lcm(Y, X) (e.g., `12 [ENTER] 18 [f] [LCM]` → `36`).

Tactile Venn Intersection with Prime Studio Blocks:

Take a = 48 and b = 72:

- Decompose $48 = 2^4 \times 3^1$: Assemble four **`[2]`** blocks and one **`[3]`** block.
- Decompose $72 = 2^3 \times 3^2$: Assemble three **`[2]`** blocks and two **`[3]`** blocks.
- **The Intersection (GCF):** The shared factor blocks common to both towers are **three `[2]` s and one `[3]`**:

GCF = $2^3 \times 3 = 8 \times 3 = 24$

- **The Union (LCM):** Take the maximum power of each prime (**four `[2]` s and two `[3]` s**):

LCM = $2^4 \times 3^2 = 16 \times 9 = 144$



Figure: Prime Factor Studio: Prime Factorization and Venn Intersection Model

Application 1: Rectangle Tiling (GCF)

A maker lab needs to tile a tabletop measuring 24 cm × 36 cm using the largest possible congruent square tiles with zero waste or cutting. Key `24 [ENTER] 36 [GCF]` → (T: 0, Z: 0, Y: 0, X: 12), instantly revealing that the optimal tile dimension is Tile Side = gcd(24, 36) = **12 cm**.

Application 2: Synchronized Flashing Cycle (LCM)

Two beacon lights flash at fixed intervals: Light A flashes every 6 seconds, while Light B flashes every 8 seconds. Key `6 [ENTER] 8 [f] [LCM]` → (T: 0, Z: 0, Y: 0, X: 24), confirming that the beacons flash in unison every Next Flash = lcm(6, 8) = **24 seconds**.

Application 3: Fraction Least Common Denominator (LCD)

When adding unlike fractions (3 / 8) + (5 / 12), the Least Common Denominator is the LCM of the denominators. Key `8 [ENTER] 12 [f] [LCM]` → (T: 0, Z: 0, Y: 0, X: 24), providing the exact denominator bridge LCD = lcm(8, 12) = **24** in a single keystroke.

7.4.7 Algebraic Trap vs. StackCalc Superpower Showdown: Number Theory, Statistics & Probability

Challenge / Real-World Task	The Algebraic Calculator Trap (TI-84 / Infix)	Algebraic Keystrokes & Clutter	The StackCalc Superpower (RPN Stack + Visual Studio)	StackCalc Keystrokes	The Stack Advantage
GCF & LCM Duality: • Secret Partner Rule verification: • gcd(24, 36) × lcm(24, 36) = 864	No hardware GCF or LCM keys: students must sketch manual factor trees on scratch paper, find prime powers, and re-enter multi-step arithmetic from scratch. Intermediate products vanish.	`2 4 * 3 6 =` • Manual scratch work factor trees • (28+ keystrokes, zero live factors)	**Hardware `[GCF]` & `[f] [LCM]` Stack Duality:** • Single-tap prime engines extract GCF (12) and LCM (72). The 4-register stack preserves the GCF in Register Y while computing LCM in X, verifying 12 × 72 = 864 with one keystroke.	`24 [ENTER] 36 [GCF] 18 [ENTER] 24 [f] [LCM] [×]` • (13 keystrokes)	**54% fewer keystrokes** • Zero scratch paper; the stack proves the Secret Partner Rule invariant live on screen.

Challenge / Real-World Task	The Algebraic Calculator Trap (TI-84 / Infix)	Algebraic Keystrokes & Clutter	The StackCalc Superpower (RPN Stack + Visual Studio)	StackCalc Keystrokes	The Stack Advantage
Euclidean Division: • Hydraulic gate synchronizatio n: • 105 ÷ 45 ⇒ Q = 2, R = 15	Infix division yields decimal 2.3333333. Finding integer quotient and remainder requires rounding down, re-multiplying 2 × 45 = 90, and subtracting 105 - 90 = 15 across multiple steps.	`1 0 5 / 4 5 =` → 2.333 • `1 0 5 - ( 2 * 4 5 ) =` • (18 keystrokes, modal confusion)	**Single-Tap Euclidean `[g] [÷R]` :** • Hardware integer division deposits integer quotient Q = 2 in Register X and exact remainder R = 15 in Register Y simultaneously in one step.	`105 [ENTER] 45 [g] [÷R]` • (8 keystrokes)	**56% fewer keystrokes** • Simultaneous quotient and remainder display matches physical token tray distribution.
Prime Factorization: • Cryptographic vault key factoring: • 2,639 = 7 × 13 × 29	Standard algebraic calculators provide no hardware factoring. Students must manually test trial divisors on scratch paper (2,639 ÷ 3, ÷ 7, ...) through tedious, error-prone trial division.	`2 6 3 9 / 3 =` • `2 6 3 9 / 7 =` → 377 • `3 7 7 / 1 1 =` ... • (35+ keystrokes, manual logging)	**Hardware Prime Engine `[g] [FACT]` :** • Dedicated factoring co-processor parses composite numbers instantly into prime components, rendering 7 × 13 × 29 across the transflective dot-matrix display.	`2639 [g] [FACT]` • (5 keystrokes)	**85% fewer keystrokes** • Instant canonical decomposition; flashes `PRIME` or renders prime tower strings without guesswork.
Statistical Mean: • Four test scores averaging: • 88, 92, 79, 95 ⇒ x■ = 88.5	Must enter chained addition with parentheses `( 88 + 92 + 79 + 95 ) / 4 =`. Forgetting outer brackets divides only 95 by 4, creating an undetected order-of-operations error (283.75).	`( 8 8 + 9 2 + 7 9 + 9 5 ) / 4 =` • (23 keystrokes, bracket risk)	**Hardware Statistical Accumulator (`[Σ+]`):** • Each data point accumulates into dedicated ∑ registers with running sample count n. Pressing `[g] [x̄]` extracts the exact mean with zero syntax parentheses.	**`[g] [CLΣ] 88 [Σ+] 92 [Σ+] 79 [Σ+] 95 [Σ+] [g] [x̄]`** • (16 keystrokes)	**Zero Parentheses Clutter** • Running sample count protects data entry; enables instant standard deviation and ∑ x queries.

7.4.8 The Secret Partner Rule: Why GCF × LCM Always Equals a × b!

For any two positive integers a and b, the product of their greatest common factor and least common multiple is strictly equal to the product of the original numbers: **gcd(a, b) × lcm(a, b) = a × b**

Mathematical Proof & Stack Verification:

Consider a = 24 and b = 36:

- gcd(24, 36) = 12
- lcm(24, 36) = 72
- Product of GCF and LCM: 12 × 72 = 864
- Product of original numbers: 24 × 36 = 864

Keystroke	Register T	Register Z	Register Y	Register X
24	0	0	0	24
`[ENTER]`	0	0	24	24
36	0	0	24	36
`[f]` `[LCM]`	0	0	0	72
12	0	0	72	12
`[×]`	0	0	0	864

Check against direct product on the stack: `24 [ENTER] 36 [×]` → X = **864.00** (Secret Partner Rule confirmed!).

7.4.9 The Euclidean Division Algorithm via Hardware [g] [÷R]

Euclid of Alexandria discovered over 2,300 years ago that the greatest common divisor of two integers can be found by repeated division with remainders: **gcd(a, b) = gcd(b, a mod b)**

On the SC-6, you execute the Euclidean algorithm using the shifted key **[g]** **[÷R]** (`÷R` on `/`). Each press of **[g]** **[÷R]** divides Y by X, placing the quotient Q in Register X and the remainder R in Register Y.

Worked Example 7.3: Step-by-Step Euclidean Ladder for gcd(105, 45)

Find gcd(105, 45) using Euclidean division:

1. 105 ÷ 45 = 2 with remainder 15 ⇒ gcd(105, 45) = gcd(45, 15).
2. 45 ÷ 15 = 3 with remainder 0 ⇒ gcd(45, 15) = 15.

The last non-zero remainder is **15**, so gcd(105, 45) = **15**.

Keystroke	Register T	Register Z	Register Y	Register X	Status / Commentary
105	0	0	0	105	Dividend entered
[ENTER]	0	0	105	105	Stack lifts; 105 staged to Y
45	0	0	105	45	Divisor 45 entered on floor X
[g] [÷R]	0	0	15	2	Integer quotient Q = 2 in X, remainder R = 15 in Y
[x⇔y]	0	0	2	15	Swap: remainder 15 now in X

Euclidean Division Ladders for Large Number Pairs

For larger composite numbers, you construct an RPN division ladder, using the quotient and remainder output of **[g]** **[÷R]** to systematically reduce the problem to zero remainder:

Worked Example 7.5: Euclidean Ladder for gcd(252, 105)

1. 252 ÷ 105 = 2 with remainder 42 (252 = 2 × 105 + 42)
2. 105 ÷ 42 = 2 with remainder 21 (105 = 2 × 42 + 21)
3. 42 ÷ 21 = 2 with remainder 0 (42 = 2 × 21 + 0)

The last non-zero remainder is **21**, so gcd(252, 105) = **21**.

Step / Key	Dividend (Y)	Divisor (X)	Quotient (X)	Remainder (Y)
252 [ENTER] 105	252	105	-	-
[g] [÷R]	-	-	2	42
[x⇔y]	2	42	42	2
105 [x⇔y]	105	42	-	-

Step / Key	Dividend (Y)	Divisor (X)	Quotient (X)	Remainder (Y)
[g] [÷R]	-	-	2	21
42 [x⇔y]	42	21	-	-
[g] [÷R]	-	-	2	0

You can directly verify this result in a single step using the hardware key: 252 [ENTER] 105 [GCF] → X = **21.00**!

7.5 Elementary Descriptive Statistics & Data Analysis

> **For Parents & Teachers: Curriculum Standards**
>
> Common Core Standards Alignment: CCSS 6.SP.A.2, 6.SP.B.5.

In Grades 5 and 6, you transition from counting discrete numbers to analyzing datasets: describing the center (mean, median, mode) and measuring the spread or variability (range, interquartile range, mean absolute deviation).

Metric	Key / Shift	Mathematical Definition
Sample Size (n)	[N]	Count of data points
Sum of Data (∑ x)	[f] [Σx]	Total accumulation
Mean (Average)	[g] [x̄]	(∑ x) / n
Median	[f] [MED]	Middle value of sorted set
Mode	[g] [MODE]	Most frequent value
Range	[RNG]	Maximum - Minimum
Interquartile Range	[IQR]	$Q_3 - Q_1$
Mean Absolute Deviation	[g] [MAD]	$(1 / n) \sum \lvert x_i - \bar{x} \rvert$

7.5.1 Dataset 1: The 10-Quiz Score Frequency Table & The Seed of Distributions

A 5th-grade math class records scores on a 100-point weekly quiz across 10 students: **70, 75, 80, 80, 85, 85, 85, 90, 90, 95**

Score (x)	Tally	Frequency (f)	Dot Plot Visual Representation
70	I	1	●
75	I	1	●
80	II	2	● ●
85	III	3	● ● ● *(Peak Mode!)*
90	II	2	● ●
95	I	1	●
Total Count (n = ∑ f)	—	**10**	10 total observations

The Intellectual Bridge to Distributions:

Notice the shape of the dot plot! The data rises smoothly from 70 to a central peak at 85, and then descends symmetrically down to 95. This bell-shaped mound is your first intuitive encounter with **symmetric distributions**. In middle and high school, this exact visual symmetry develops into the continuous Gaussian Normal Distribution curve!

Complete SC-6 Statistical Evaluation:

```
[g] [CLΣ] → Clears all stats registers (n = 0)
70 [Σ+] → n = 1
75 [Σ+] → n = 2
80 [Σ+] 80 [Σ+] → n = 4
85 [Σ+] 85 [Σ+] 85 [Σ+] → n = 7
90 [Σ+] 90 [Σ+] → n = 9
95 [Σ+] → n = 10
```

1. **Sample Size (n):** `[N]` → X = **10**.
2. **Sum of Scores (∑ x):** `[f] [Σx]` → X = **835.0**.
3. **Mean Score (x■):** `[g] [x̄]` → X = **83.5**.
4. **Median Score (Med):** `[f] [MED]` → X = **85.0**.
5. **Mode Score (Mode):** `[g] [MODE]` → X = **85.0**.
6. **Range (Max - Min):** `[RNG]` → X = **25.0** (95 - 70 = 25).

Because the distribution is perfectly symmetrical around 85, the **Median** and **Mode** are identical (85.0), while the **Mean** (83.5) sits just below the peak due to the lower score of 70.

7.5.2 Dataset 2: 5-Quiz Empirical Investigation (Measures of Spread: IQR & MAD)

A smaller study group records five scores: 85, 90, 75, 90, 100.

Statistical Metrics Audit:

1. **Sorted Data:** 75, 85, 90, 90, 100.
2. **Count:** n = 5.
3. **Sum:** ∑ x = 75 + 85 + 90 + 90 + 100 = 440.0.
4. **Mean (x■):** (440 / 5) = **88.0**.
5. **Median:** Middle ranked value = **90.0**.
6. **Mode:** Most frequent value = **90.0**.
7. **Minimum: 75.0**, **Maximum: 100.0**.
8. **Range:** 100 - 75 = **25.0**.
9. **Interquartile Range (IQR):** On the SC-6, inclusive-median quartiles yield Q_1 = 85.0 and Q_3 = 90.0:

IQR = Q_3 - Q_1 = 90.0 - 85.0 = 5.0

10. **Mean Absolute Deviation (MAD):** Measures the average distance between each data point and the mean ($\bar{x}$ = 88.0):

|75 - 88| = 13, |85 - 88| = 3, |90 - 88| = 2, |90 - 88| = 2, |100 - 88| = 12 Sum of Deviations = 13 + 3 + 2 + 2 + 12 = 32.0 MAD = (32.0 / 5) = 6.4

Keystrokes:
`[g]` `[CLΣ]`
85 `[Σ+]` 90 `[Σ+]` 75 `[Σ+]` 90 `[Σ+]` 100 `[Σ+]`
`[f]` `[Σx]` → 440.00
`[g]` [$\bar{x}$] → 88.00
`[f]` `[MED]` → 90.00
`[g]` `[MODE]` → 90.00
`[IQR]` → 5.00
`[g]` `[MAD]` → 6.40

7.5.3 The Five-Number Summary, Box Plots & Outlier Analysis

In data science, you represent distributions graphically using **Box-and-Whisker Plots**. A box plot partitions any ordered dataset into four quartiles using five milestone numbers:

1. **Minimum (Min):** Lowest observed value (`[f]` `[MIN]`).
2. **First Quartile (Q_1):** 25th percentile boundary.
3. **Median (Med):** 50th percentile center (`[f]` `[MED]`).
4. **Third Quartile (Q_3):** 75th percentile boundary.
5. **Maximum (Max):** Highest observed value (`[g]` `[MAX]`).

Box Plot Milestone	Statistical Keycap	Percentile / Structural Role
Lower Whisker Tip (Min)	`[f]` `[MIN]`	0th percentile (minimum non-outlier observation)
Left Box Edge (Q_1)	`[f]` `[1Q]`	25th percentile (lower boundary of central 50% box)
Interior Vertical Line (Med)	`[f]` `[MED]`	50th percentile (median dividing the box)
Right Box Edge (Q_3)	`[g]` `[3Q]`	75th percentile (upper boundary of central 50% box)
Central Box Span (IQR)	`[IQR]`	Interquartile range IQR = Q_3 - Q_1
Upper Whisker Tip (Max)	`[g]` `[MAX]`	100th percentile (maximum non-outlier observation)

The 1.5 × IQR Outlier Detection Rule

An **outlier** is an anomalous data point that lies unusually far from the central cluster. In competitive STEM challenges and introductory data science, points beyond the inner fences are classified as statistical outliers: **Lower Fence = Q_1 - 1.5 × IQR Upper Fence = Q_3 + 1.5 × IQR**

Worked Example 7.6: Detecting an Outlier in Running Times

A group of 8 runners complete a race in the following minutes: 25, 28, 30, 32, 34, 35, 38, 58. Runner 8 took 58 minutes. Is 58 a statistical outlier?

Step 1: Compute Quartiles:

Ordered data: 25, 28, 30, 32, 34, 35, 38, 58

Q1 = (28 + 30) / 2 = 29.0

Median = (32 + 34) / 2 = 33.0

Q3 = (35 + 38) / 2 = 36.5

IQR = 36.5 - 29.0 = 7.5

Step 2: Compute Upper Fence via RPN:

36.5 **[ENTER]** 7.5 **[ENTER]** 1.5 **[×]** **[+]** → 47.75 minutes

- `7.5 [ENTER] 1.5 [×]` → 11.25 (1.5 × IQR)
- `36.5 [+]` → **47.75 minutes** (Upper Fence).

Since 58 > 47.75, the score of 58 minutes lies well outside the upper fence and is confirmed as a **true statistical outlier**!

7.6 Grade 6 Pre-Algebra: Signed Numbers, Absolute Value & Inverses

In pre-algebra, you cross a thrilling new threshold: numbers are no longer merely static amounts—they possess **direction** along the real number line.

Negative Direction (x < 0)	Origin (0)	Positive Direction (x > 0)
-5, -4, -3, -2, -1	0	+1, +2, +3, +4, +5

7.6.1 Signed Number Entry via the Negation Key [+/-]

A vital distinction in early algebra is the difference between:

- The **binary operation of subtraction** (**[-]**), which combines two numbers (Y - X).
- The **unary sign toggle** (**[+/-]**), which negates the active number in Register X.

On the SC-6:

- To enter -8: type **[8] [+/-]**. The screen displays `-8`.
- Pressing **[+/-]** again toggles back to `8`.
- **Zero Invariant:** Negating zero leaves `0` unchanged.

Worked Example 7.4: Winter Temperature Differential

At 6:00 AM, the outdoor temperature in Chicago is -14^°C. By 2:00 PM, the temperature rises by +9^°C. What is the afternoon temperature?

Equation: -14 + 9 = -5^°C

On the stack, key `14 [+/-] [ENTER] 9 [+]` → (T: 0, Z: 0, Y: 0, X: -5), confirming an afternoon temperature of -5^°C directly on the LCD.

7.6.2 Absolute Value as Number Line Distance ([g] [|x|])

The absolute value of a real number x, denoted |x|, represents its non-negative distance from zero along the number line, regardless of direction: **|x| = x if x ≥ 0 ; -x if x < 0**

On the SC-6, pressing **[g] [|x|]** (Row 0, Col 4 **[g]** Shift) instantly strips the negative sign from Register X, preserving magnitude:

- `42 [+/-] [g] [|x|]` → X = **42**.
- `15 [g] [|x|]` → X = **15**.

Worked Example 7.5: Elevation Difference: Death Valley vs. Mountain Peak

A hiker descends to Badwater Basin in Death Valley at an elevation of -86 meters (below sea level), then ascends to Telescope Peak at +3,366 meters. Find the total vertical elevation climbed.

Vertical Climb: |3366 - (-86)| = |3366 + 86| = 3,452 meters

RPN Evaluation:
3366 **[ENTER]** 86 **[+/-]** **[-]** **[g]** **[|x|]** → 3452.00 meters

7.6.3 Geometric Inverses: Area-to-Side-Length ([x²] and [f] [√x])

In elementary school, the square key **[x²]** and square root key **[f] [√x]** are taught strictly as **geometric area-to-side-length inverses**, not as abstract exponential powers:

- Squaring a number finds the **area** of a square given its side length: $A = s^2$.
- Taking the square root finds the **side length** of a square given its enclosed area: $s = \sqrt{A}$.

Square Geometry	Forward Operation ([x²])	Inverse Operation ([f] [√x])
5 cm × 5 cm Tile Square	Side s = 5 cm → Area A = s^2 = **25 cm^2**	Area A = 25 cm^2 → Side s = √25 = **5 cm**

Worked Example 7.6: Fencing a Square Pasture

A horse pasture has an exact square area of 1,225 square meters.

1. What is the length of one side of the pasture?
2. What is the total length of fencing required to surround all four sides?

Step 1: Compute side length s = √A:
1225 **[f]** **[√x]** → 35.00 meters

Step 2: Compute perimeter P = 4 * s:
[4] **[×]** → 140.00 meters

Each side is **35 meters**, requiring **140 meters** of fence.

7.6.4 Real-World Pre-Algebra Word Problems: Directed Integers in Motion

To master pre-algebra, you can solve multi-step signed integer problems reflecting real-world engineering, financial, and environmental contexts.

Scenario 1: Skyscraper Elevator Traversal

A high-rise tower features 3 subterranean parking levels (Floors -3, -2, -1), a ground lobby (Floor 0), and 60 tower floors (Floors 1 ... 60). An elevator starts at subterranean parking Level -3, travels up +45 floors to deliver office supplies, descends -12 floors to the cafeteria, and finally descends -33 floors:

Equation: -3 + 45 - 12 - 33 = -3 (Back at parking Level -3!)

Key `3 [+/-] [ENTER] 45 [+] 12 [-] 33 [-]` → (T: 0, Z: 0, Y: 0, X: -3), returning the elevator precisely to subterranean parking Level -3 with zero register overflow!

Scenario 2: Deep-Sea Oceanographic Research Submersible

A marine biology autonomous vehicle begins a mission on the deck of a research ship at +4 meters above sea level. It dives to a survey trench at -350 meters.

1. Find the total vertical descent distance.
2. The vehicle then ascends +125 meters to sample a hydrothermal vent, before descending an additional -45 meters. Find its final depth.

Step 1: Total vertical descent distance:

`[4]` **`[ENTER]`** 350 `[+/-]` `[-]` `[g]` `[|x|]` → 354.00 meters

Step 2: Final depth:

350 `[+/-]` **`[ENTER]`** 125 `[+]` 45 `[-]` → -270.00 meters

The vehicle surveyed the vent at a final depth of **-270 meters**.

Scenario 3: Bank Account Ledger with Overdraft Fees

Your student checking account starts with a positive balance of +$120.00.

- You buy school books for $85.00 (-$85.00).
- You buy an art supply kit for $60.00 (-$60.00).
- The bank assesses an overdraft penalty of $25.00 (-$25.00).
- You deposit a lawn-mowing paycheck of $95.00 (+$95.00).

Calculate your net account balance using the SC-6 currency formatter `[$]`.

RPN Ledger Evaluation:

120 **`[ENTER]`** 85 `[-]` 60 `[-]` 25 `[-]` 95 `[+]` `[$]`

- `120 [ENTER] 85 [-]` → 35.00
- `60 [-]` → -25.00 (Account in overdraft!)
- `25 [-]` → -50.00 (Penalty assessed)
- `95 [+]` → 45.00 (Deposit restores positive balance!)
- **`[$]`** → **$45.00**.

For Parents & Teachers: Empirical Probability, Number Theory & Zero Pairs

Empirical Probability Distributions and Statistical Accumulation: Teaching data and discrete probability in upper elementary requires guiding learners from subjective guesswork ("seven feels lucky") toward rigorous empirical evidence. The SC-6 hardware probability engine (**`[DICE]`**) paired with the statistical accumulator (**`[Σ+]`**) provides a real-time experimental laboratory directly in the learner's hands. When collecting sample datasets, learners observe empirical distributions stabilize as sample size n increases. Entering successive data points into **`[Σ+]`** reveals how measures of center—mean, median, and mode—converge in symmetric unimodal distributions. In number theory, dedicated hardware keys for **`[GCF]`** and **`[f] [LCM]`** allow students to verify the Fundamental Duality Theorem ($\gcd(a,b) \times \text{lcm}(a,b) = a \times b$) empirically, transforming abstract identities into tangible discoveries.

Tactile Zero-Pair Balances and Pre-Algebra Mental Models: Directed negative numbers frequently present a major cognitive hurdle in transition to pre-algebra, particularly the misconception that subtraction always results in a smaller quantity (such as -8 - (-5) = -3). The SC-6 grounds integer arithmetic by pairing the hardware negation toggle (**`[+/-]`**) with physical two-color counters. Learners model negative numbers as Crimson tokens and positive numbers as Yellow tokens. Removing five Crimson tokens from a group of eight Crimson tokens visually leaves three Crimson tokens, reinforcing that taking away debt increases net value. On the calculator, typing `8 [+/-] ENTER 5 [+/-] -` delivers X = -3 with zero syntax ambiguity.

Silicon Architecture & Hardware Primitives: The SC-6 statistical architecture incorporates dedicated accumulators ($\sum x$, $\sum x^2$, and sample count n) that update independently of the four-register working stack (T, Z, Y, X). Data points can be transformed or computed through intermediate formulas without overwriting running summation totals. Similarly, hardware Euclidean division via **`[g] [÷R]`** executes integer division in a single cycle: dividend and divisor are processed, quotient is deposited into Register X, and remainder is retained in Register Y. Tapping **`[x⇔y]`** instantly prepares the remainder as the divisor for the next Euclidean iteration, illustrating the elegance and efficiency of hardware RPN architecture.

For Parents & Teachers: Classroom Dialogue Scripts & Misconception Diagnostics

Script 7.1: The Definition of a Prime Number:

Teacher: "Class, who can tell me: is the number 1 a prime number?"

Student (Liam): "Yes! Because 1 can only be divided by 1 and itself!"

Teacher: "Let's check the formal mathematical definition. A prime number is a positive integer that has *exactly two distinct positive divisors*: 1 and itself. How many different divisors does the number 1 have?"

Liam: "Just... 1."

Teacher: "Right! 1 only has one factor, not two! What about composite numbers?"

Liam: "Composite numbers have three or more factors."

Teacher: "So where does 1 belong?"

Liam: "It's not prime, and it's not composite. It's special!"

Teacher: "Exactly! 1 is called a unit. Now test it on your SC-6: type `1 [PRIME]`. What does the screen say?"

Liam: "It flashes `INVALID DATA`! It won't let me call 1 a prime!"

Teacher: "Now try the number 2: `2 [PRIME]`."

Liam: "It flashes `PRIME`! And preserves 2 right on the display!"

Teacher: "2 is the smallest prime number, and the only even prime in the entire universe!"

Script 7.2: Subtracting a Negative Number:

Student (Chloe): "Teacher, I don't understand why 7 - (-3) equals 10. When you subtract, shouldn't the number get smaller?"

Teacher: "Take our two-color counters, Chloe. Imagine you are running a school store. A customer owes you $3, which is a debt of -3. If you decide to forgive the debt—meaning you *take away* the negative $3—does the customer have more money or less money?"

Chloe: "They have more money! Because their debt is gone!"

Teacher: "Taking away a negative is the exact same as adding a positive! Now test it on your SC-6: `7 [ENTER] 3 [+/-] [-]`."

Chloe: "It says 10! Because taking away 3 negatives leaves 10 positives!"

Misconception Diagnostic Table

| Observable Error | Cognitive Root Cause | Targeted Remediation Prompt |

| :--- | :--- | :--- |

| **Claiming 1 is prime** | Conflating "divisible only by 1" with "having exactly two distinct factors." | *"A prime must have exactly two distinct factors: 1 and itself. 1 only has one factor. The SC-6 classifies 1 as a unit, neither prime nor composite."* |

| **Confusing GCF and LCM** | Assuming "Greatest" must yield a larger number than "Least." | *"A factor divides INTO a number, so it must be smaller than or equal to the number. A multiple MULTIPLIES the number, so it grows larger! GCF ≤ numbers ≤ LCM."* |

| **Treating | x| as 'change the sign'** | Believing absolute value turns positive numbers into negative numbers. | *"Absolute value is distance on a number line. Distance is never negative! The distance from 5 to 0 is 5; the distance from -5 to 0 is also 5. | 5| = 5 and | -5| = 5."* |

| **Adding negatives: -4 + (-3) = -1** | Subtracting magnitudes instead of accumulating directed negative quantities. | *"If you take 4 steps backward (-4), and then take 3 more steps backward (-3), you are 7 steps backward (-7), not 1 step! Use Crimson tokens to model the sum."* |

| **Expecting Mean = Median always** | Assuming all datasets are perfectly symmetrical. | *"In skewed datasets (like home prices or quiz scores with an outlier), extreme values pull the mean away from the center. The median stays fixed in the middle."* |

| **Confusing `[+/-]` with `[-]`** | Using the binary subtraction operator to enter negative values. | *"The `[-]` key subtracts two numbers (Y - X). The `[+/-]` key changes the sign of the single number you are actively typing."* |

7.7 Comprehensive Problem Bank: 65 Worked Reference Problems

The following problem bank provides complete, publication-grade reference solutions spanning Grade 5 and Grade 6 discrete probability, number theory, descriptive statistics, and pre-algebra. Every keystroke sequence assumes the SC-6 baseline mode `[NUM]`.

Hands-On Studio Proof: Blocks → Calculator

Before executing probability distributions, primality tests, and statistical summaries symbolically, you ground each mathematical principle in physical manipulatives:

1. **Discrete Probability & Geometry (The Dice Studio):** Roll the 3D-printed equal-volume pip dice 60 times. Record outcomes on the dot plot board. Compare empirical frequencies against theoretical fractions on the SC-6 (`[FDISP]`), proving why P(Odd) = 3/6 = 1/2.

2. **Primality & Rectangular Factoring (The 24-Tile Studio):** Model small with 13 tiles from your 24-Tile Counting & Array Studio—attempt to form rectangular grids of 2 or 3 rows and watch every attempt leave leftover tiles—then scale big to 83 tiles on your SC-6 by pressing `83 [PRIME]`, watching the LCD illuminate `PRIME` (preserving 83 on display). Repeat with 91 on the calculator to discover 7 × 13 = 91 (`COMPOSITE`, preserving 91 on display).

3. **Tactile Venn Intersections (The Prime Factor Studio):** Model 48 and 72 using proportional logarithmic blocks. Physically place common factor blocks ($2^3 \times 3$) into the central comparator well to verify gcd(48, 72) = 24 (`48 [ENTER] 72 [GCF]`).

4. **Zero-Pair Balances (Two-Color Counters):** Pair Sun Yellow (+1) and Signal Crimson (-1) tokens to eliminate zero pairs before executing signed integer arithmetic on the stack (**`[+/-]`**).

7.7.1 Expedition 1: The High-Rollers Tabletop & Spinner Tournament (Problems 7.1–7.5)

Mission Briefing: You are the chief statistician for a tabletop gaming tournament. Compute exact single-event probabilities, compound die throws, and complementary odds using RPN stack division and fraction displays.

Problem 7.1: Single Die Roll Probability

Tabletop Gaming Tournament: In the championship match, a referee rolls a precision equal-volume pip six-sided die. Calculate the theoretical probability of rolling an odd face (1, 3, 5). Inspect the physical equal-volume pip dice. Notice that 3 out of 6 faces are odd numbers. Rolling the die 60 times yields approximately 30 odd occurrences, validating the 3/6 = 0.5 theoretical ratio.

On your SC-6, key in **`[3] [ENTER] [6] [÷]`** → `0.5 (T=0, Z=0, Y=0, X=0.5)`. Divide favorable by total to compute theoretical probability (3/6 = 0.5). Register X displays 0.5000. Theoretical probability of rolling an odd face is **0.5000** (50%).

Problem 7.2: Tournament Card Deck Draw

Tournament Card Deck Draw: In a card tournament, a standard 52-card deck contains 4 aces. What is the probability of drawing an ace at random on the first draw? Partition the deck into 4 aces and 48 non-aces. The 4 target aces represent a 1/13 fraction of the total 52-card sample space.

On the SC-6 keypad, enter **`[4] [ENTER] 52 [÷]`** → `0.0769230769 (T=0, Z=0, Y=0, X=0.0769)`. Divide to calculate single-draw ace probability (4/52 ≈ 0.0769). Register X displays 0.0769. Ace drawing probability is **0.0769** (≈ 7.69%).

Problem 7.3: Compound Coin Toss: Three Consecutive Heads

Triple Coin Toss Tournament Tiebreaker: A match tiebreaker requires flipping three consecutive heads with a balanced coin ($P = (1/2)^3$). Determine the compound probability of three consecutive heads. Arrange a 3-tier binary tree using two-color counters. Out of 8 possible paths (HHH, HHT, ..., TTT), exactly 1 path yields three consecutive heads.

Turning to your SC-6, key in `0.5 [ENTER] [3] [g] [y⊠]` → `0.125 (T=0, Z=0, Y=0, X=0.125)`. Raise to 3rd power to compute compound probability ($0.5^3 = 0.125$). Register X displays 0.1250. Probability of three consecutive heads is **0.1250** (12.5%).

Problem 7.4: Sum of Two Dice: Rolling an 11 or 12

High-Rollers Two-Dice Roll: Two dice are rolled simultaneously in the final round. The sum is 11 for two combinations ((5,6), (6,5)) and 12 for one combination ((6,6)). Find the probability of rolling an 11 or 12. Map the 6 × 6 grid of 36 equally likely outcomes. Highlight the 3 winning combinations in the top-right corner.

With your SC-6 ready, enter **`[3] [ENTER] 36 [÷]`** → `0.0833333333 (T=0, Z=0, Y=0, X=0.0833)`. Divide favorable by total combinations (3/36 ≈ 0.0833). Register X displays 0.0833. Probability of rolling 11 or 12 is **0.0833** (≈ 8.33%).

Problem 7.5: Complementary Probability

Complementary Event Probability: The championship venue weather report indicates a 35% probability of rain ($P = 0.35$). Determine the complementary probability of fair weather ($P' = 1 - P$). Inspect the circular probability spinner with 100 divisions. Shading 35 sectors for rain leaves 65 unshaded sectors for fair weather, grounding $1 - P$.

Step over to your SC-6 and key in **`[1] [ENTER] 0.35 [-]`** → `0.65 (T=0, Z=0, Y=0, X=0.65)`. Deduct rain probability from total space to find complementary dry odds. Register X displays 0.6500. Complementary probability of fair weather is **0.6500** (65%).

7.7.2 Expedition 2: The Prime Number Fortress & Sieve (Problems 7.6–7.18)

Mission Briefing: Journey into the heart of number theory. Test for prime numbers using rectangular resistance, unlock prime factor trees, find greatest common factors and least common multiples, and verify the Secret Partner Rule across the ancient Prime Number Fortress.

Problem 7.6: Prime Fortress Outer Gate Cipher: Primality of 83

The outer massive gate of the Prime Fortress opens only when presented with an indivisible prime credential. Test candidate code 83 for primality. Modeling small with blocks before scaling up on your SC-6, take 13 tiles from your kit and attempt to assemble them into rectangles of 2, 3, or 5 rows. Every attempt leaves uneven remainders—13 forms only a single linear row of 1×13, proving rectangular resistance. Now scale big to 83 on your StackCalc: test divisibility by primes 2, 3, 5, and 7 to verify rectangular resistance without needing 83 loose tiles.

Now compute it on your SC-6: `83 [PRIME]` → `83 (T=0, Z=0, Y=0, X=83)`. Execute primality test: status line flashes `PRIME`, preserving candidate 83 in Register X.

Status line flashes `PRIME`; Register X preserves **83**. Outer gate cipher unlocks!

Problem 7.7: Prime Fortress Barbican Trap Door: Primality of 91

The fortress barbican is guarded by a deceptive trap door set to trigger on composite impostor codes. Evaluate candidate code 91. Modeling small with blocks before scaling up on your SC-6, take 21 tiles (7×3) and arrange them into 3 rows of 7 with zero gaps to demonstrate composite grouping. Then scale big to 91 on your StackCalc: test 91 against prime factor 7 ($91 \div 7 = 13$), exposing 91 as composite.

Run the sequence on your SC-6: `91 [PRIME]` → `91 (T=0, Z=0, Y=0, X=91)`. Execute primality test: status line flashes `COMPOSITE`, preserving candidate 91 in Register X.

Status line flashes `COMPOSITE`; Register X preserves **91** ($91 = 7 \times 13$). Barbican trap door disarmed!

Problem 7.8: Prime Fortress Moat Portcullis: Primality of 143

The iron portcullis over the fortress moat evaluates candidate 143. Determine if the credential is prime or composite. Modeling small with blocks before scaling up on your SC-6, take 22 tiles (11×2) to see how groups of 11 assemble into neat rectangles. Then scale big to 143 on your StackCalc: test $143 \div 11 = 13$, confirming factor pairs beyond 1 and itself.

Verify the calculation on your SC-6: `143 [PRIME]` → `143 (T=0, Z=0, Y=0, X=143)`. Execute primality test: status line flashes `COMPOSITE`, preserving candidate 143 in Register X.

Status line flashes `COMPOSITE`; Register X preserves **143** ($143 = 11 \times 13$). Portcullis barrier confirmed!

Problem 7.9: Prime Fortress Armory Key: Prime Factorization of 72

The fortress armory lock requires the exact prime decomposition string of tumbler code 72. Decompose 72 into prime factors. Take three Blue 2-blocks ($2^3 = 8$) and two Amber 3-blocks ($3^2 = 9$). Stack them vertically against the calibrated back-wall slide rule: the combined height aligns precisely with index 72.

Test this directly on your SC-6: `72 [g] [FACT]` → `72 (T=0, Z=0, Y=0, X=72)`. Execute prime factorization: graphic screen renders prime decomposition string.

Graphic screen renders `2³ × 3²`. Armory lock disengages!

Problem 7.10: Prime Fortress Citadel Key: Prime Factorization of 210

The inner citadel vault is sealed with master product code 210. Find its complete prime factor decomposition. Select one 2-block, one 3-block, one 5-block, and one 7-block. Stacking these four distinct prime towers models the square-free product $2 \times 3 \times 5 \times 7 = 210$.

Bring this to the SC-6 stack: `210 [g] [FACT]` → `210 (T=0, Z=0, Y=0, X=210)`. Execute prime factorization: graphic screen renders four-prime string.

Graphic screen renders `2 × 3 × 5 × 7`. Citadel vault credential accepted!

Problem 7.11: Prime Fortress High Tower Vault Key: Prime Factorization of 504

The high observatory tower is protected by an astronomical key code of 504. Determine its prime factor components. Factor 504 using prime blocks: three 2-blocks ($2^3 = 8$), two 3-blocks ($3^2 = 9$), and one 7-block (7). Product: $8 \times 9 \times 7 = 504$.

On your SC-6, enter `504 [g] [FACT]` → `504 (T=0, Z=0, Y=0, X=504)`. Execute prime factorization: graphic screen displays canonical factor string.

Graphic screen renders `2³ × 3² × 7`. High tower observatory unsealed!

Problem 7.12: Fortress Twin Bastions Gear Synchronization: gcd(48, 72)

Twin drawbridge drive winches with 48 teeth and 72 teeth must mesh via a common drive gear. Find the greatest common factor $\gcd(48, 72)$. Model $48 = 2^4 \times 3$ and $72 = 2^3 \times 3^2$. Place shared prime blocks into the central intersection well: three 2-blocks and one 3-block $\Rightarrow 2^3 \times 3 = 24$.

Execute the sequence on your SC-6: `48 [ENTER] 72 [GCF]` → `24 (T=0, Z=0, Y=0, X=24)`. Execute hardware GCF engine to extract greatest common divisor. Register X displays 24.0000. Maximum shared drive gear size is **24 teeth**.

Problem 7.13: Fortress Water Gate Sluice Synchronization: gcd(84, 140)

Two hydraulic sluice floodgates operate on cycles of 84 seconds and 140 seconds. Find the greatest common synchronization interval $\gcd(84, 140)$. Factor $84 = 2^2 \times 3 \times 7$ and $140 = 2^2 \times 5 \times 7$. Shared intersection: two 2-blocks and one 7-block $\Rightarrow 2^2 \times 7 = 28$.

On your SC-6, key in `84 [ENTER] 140 [GCF]` → `28 (T=0, Z=0, Y=0, X=28)`. Execute hardware GCF engine to find greatest common factor. Register X displays 28.0000. Sluice synchronization step is **28 seconds**.

Problem 7.14: Fortress Sentry Patrol Synchronization: lcm(15, 20)

Two rampart sentry patrols cycle every 15 minutes and 20 minutes respectively. Find the least common multiple lcm(15, 20) when both sentries meet at the gate. Model $15 = 3 \times 5$ and $20 = 2^2 \times 5$. The union takes maximum powers: two 2-blocks, one 3-block, and one 5-block $\Rightarrow 2^2 \times 3 \times 5 = 60$. Stacking blocks aligns with mark 60.

On the SC-6 keypad, enter `15 [ENTER] 20 [f] [LCM]` → `60 (T=0, Z=0, Y=0, X=60)`. Execute hardware LCM engine to find least common multiple. Register X displays 60.0000. Sentries meet at the gate every **60 minutes** (1 hour).

Problem 7.15: Fortress Signal Beacon Cycle: lcm(12, 18)

Two optical signal beacons on the fortress bastions flash at intervals of 12 seconds and 18 seconds. Find the least common interval lcm(12, 18) when both flash in unison. Decompose $12 = 2^2 \times 3$ and $18 = 2 \times 3^2$. The union of prime blocks takes two 2-blocks and two 3-blocks $\Rightarrow 4 \times 9 = 36$.

Turning to your SC-6, key in `12 [ENTER] 18 [f] [LCM]` → `36 (T=0, Z=0, Y=0, X=36)`. Execute hardware LCM engine to calculate least common multiple. Register X displays 36.0000. Beacons flash simultaneously every **36 seconds**.

Problem 7.16: Fortress Archival Seal: The Secret Partner Rule for 18 and 24

The grand seal of the Prime Fortress verifies that for any pair a = 18, b = 24, the product of their greatest common factor and least common multiple equals their arithmetic product: gcd(a,b) × lcm(a,b) = a × b. Compute $18 \times 24 = 432$. The shared intersection (gcd = 6) multiplied by the total union (lcm = 72) yields $6 \times 72 = 432$, proving conservation of prime factors. With your SC-6 ready, enter `18 [ENTER] 24 [GCF] 18 [ENTER] 24 [f] [LCM] [×]` → `432`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
18	0.0000	0.0000	0.0000	18.0000	Key in first fortress parameter 18
[ENTER]	0.0000	0.0000	18.0000	18.0000	Stack lifts; 18 locked into Register Y
24	0.0000	0.0000	18.0000	24.0000	Key in second parameter 24
[GCF]	0.0000	0.0000	0.0000	6.0000	Compute greatest common factor gcd(18, 24) = 6
18	0.0000	0.0000	6.0000	18.0000	Key in parameter 18; GCF lifts to Register Y
[ENTER]	0.0000	6.0000	18.0000	18.0000	Stack lifts; 18 locked into Register Y, 6 into Register Z
24	0.0000	6.0000	18.0000	24.0000	Key in parameter 24
[f] [LCM]	0.0000	0.0000	6.0000	72.0000	Compute least common multiple lcm(18, 24) = 72; GCF remains in Register Y
[×]	0.0000	0.0000	0.0000	432.0000	Multiply GCF by LCM (6 × 72 = 432)

Register X displays 432.0000. Secret partner rule holds identically ($18 \times 24 = 432$).

Problem 7.17: Fortress Supply Depot Allocation: Euclidean Division 148 ÷ 32

In the fortress provisions depot, 148 ration packs are organized into standard field cases holding 32 packs each. Find the number of full cases packed and remaining loose packs using **[g] [÷R]**. Distribute 148 tokens into trays of 32. Exactly 4 trays are completely filled ($4 \times 32 = 128$), leaving 20 loose tokens on the packing bench.

Step over to your SC-6 and key in `148 [ENTER] 32 [g] [÷R]` → `4 (T=0, Z=0, Y=20, X=4)`. Execute Euclidean division: quotient 4 in X, remainder 20 in Y. Register X displays 4 (Quotient), Register Y displays 20 (Remainder). 4 full cases packed with 20 leftover packs.

Problem 7.18: Fortress Treasury Safe Cipher Wheel: gcd(24, 36)

The fortress treasury safe wheel requires identifying the greatest shared factor of 24 and 36 to engage the master locking tumblers. List all divisors: for 24: (1, 2, 3, 4, 6, 8, 12, 24); for 36: (1, 2, 3, 4, 6, 9, 12, 18, 36). The shared common factor set is (1, 2, 3, 4, 6, 12), with greatest factor 12.

Now compute it on your SC-6: `24 [ENTER] 36 [GCF]` → `12 (T=0, Z=0, Y=0, X=12)`. Execute hardware GCF engine to extract greatest common divisor. Register X displays 12.0000. Treasury master tumbler code is **12**.

7.7.3 Expedition 3: The Data Detective & Bell-Curve Mystery (Problems 7.19–7.26)

Mission Briefing: Accumulate datasets into the statistical memory registers. Compute measures of center (mean, median, mode) and measures of spread (range, IQR, MAD) to characterize real-world measurements.

Problem 7.19: Mean of 4 Test Scores

Science Evaluation Analysis: You score 88, 92, 79, and 95 on four consecutive science tests. Calculate your arithmetic mean x■. Place pegs at marks 88, 92, 79, and 95 on the numerical balance beam. The beam balances in perfect horizontal equilibrium at the fulcrum point 88.5. Run the sequence on your SC-6: **`[g] [CLΣ] 88 [Σ+] 92 [Σ+] 79 [Σ+] 95 [Σ+] [g] [x̄]`** → `88.5`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[g] [CLΣ]`	0.0000	0.0000	0.0000	0.0000	Reset statistical registers (n = 0, ∑ x = 0)
88	0.0000	0.0000	0.0000	88.0000	Key in first test score 88
`[Σ+]`	0.0000	0.0000	0.0000	1.0000	Accumulate score (n = 1, ∑ x = 88)
92	0.0000	0.0000	0.0000	92.0000	Key in second test score 92
`[Σ+]`	0.0000	0.0000	0.0000	2.0000	Accumulate score (n = 2, ∑ x = 180)
79	0.0000	0.0000	0.0000	79.0000	Key in third test score 79
`[Σ+]`	0.0000	0.0000	0.0000	3.0000	Accumulate score (n = 3, ∑ x = 259)
95	0.0000	0.0000	0.0000	95.0000	Key in fourth test score 95
`[Σ+]`	0.0000	0.0000	0.0000	4.0000	Accumulate score (n = 4, ∑ x = 354)
`[g] [x̄]`	0.0000	0.0000	0.0000	88.5	Compute sample mean x■ = 354 / 4 = 88.5; sample size n=4 stored in Z

Register X displays 88.5000. Mean score is **88.50**.

Problem 7.20: Median of an Odd Dataset

Sprint Velocity Analysis: Five track athletes record 100m sprint times: 12.4, 12.8, 13.1, 13.5, 14.0 seconds. Find the median running time. Arrange five runner cards in ascending order along the desk. The third card sits precisely in the middle with two cards on each side, isolating the median at 13.1 s.

Verify the calculation on your SC-6: **`[g] [CLΣ] 12.4 [Σ+] 12.8 [Σ+] 13.1 [Σ+] 13.5 [Σ+] 14.0 [Σ+] [f] [MED]`** → `13.1 (T=0, Z=0, Y=5, X=13.1)`. Compute median value across odd dataset (n = 5 in Y). Register X displays 13.1000. Median sprint time is **13.10 seconds**.

Problem 7.21: Median of an Even Dataset

Environmental Temperature Monitoring: Six ambient temperatures are recorded: 68, 72, 74, 76, 80, 84^°F. Find the median temperature (average of two central elements 74 and 76). Arrange the six data cards in order. Because n = 6 is even, there is no single middle card; fold the middle pair (74 and 76) to find their midpoint: (74+76 / 2) = 75^°F.

Test this directly on your SC-6: **[g] [CLΣ] 68 [Σ+] 72 [Σ+] 74 [Σ+] 76 [Σ+] 80 [Σ+] 84 [Σ+] [f] [MED]** → 75 (T=0, Z=0, Y=6, X=75). Evaluate median of even dataset: (74+76 / 2) = 75 (n=6 in Y). Register X displays 75.0000. Median temperature is **75.00^°F**.

Problem 7.22: Mode of a Shoe Size Survey

Footwear Inventory Survey: Shoe sizes collected from 8 customers: 6, 7, 7, 7, 8, 8, 9, 10. Find the statistical mode (most frequent size). Stack counting cubes for each size. Size 7 forms the tallest column with 3 cubes, visually standing out as the statistical mode.

Bring this to the SC-6 stack: **[g] [CLΣ] [6] [Σ+] [7] [Σ+] [7] [Σ+] [7] [Σ+] [8] [Σ+] [8] [Σ+] [9] [Σ+] 10 [Σ+] [g] [MODE]** → 7 (T=0, Z=0, Y=8, X=7). Identify statistical mode across sample (X = 7, n=8 in Y). Register X displays 7.0000. Most common shoe size (mode) is **7.00**.

Problem 7.23: Range of High Temperatures

Weather Station Spread Analysis: Weekly maximum temperatures: 62, 65, 78, 81, 74, 69, 85^°F. Calculate the temperature range (max - min = 85 - 62). Pin the minimum temperature (62^°) and maximum temperature (85^°) on a number line strip. The distance spanned between the extremes measures 23^°.

On your SC-6, enter **[g] [CLΣ] 62 [Σ+] 65 [Σ+] 78 [Σ+] 81 [Σ+] 74 [Σ+] 69 [Σ+] 85 [Σ+] [RNG]** → 23 (T=0, Z=0, Y=7, X=23). Compute range (max - min = 85 - 62 = 23). Register X displays 23.0000. Weekly temperature range is **23.00^°F**.

Problem 7.24: Interquartile Range of Daily Rainfall

Precipitation Variance: Weekly rainfall measurements: 0.1, 0.2, 0.4, 0.6, 0.9, 1.2, 1.5 inches. Find the interquartile range (Q_3 - Q_1). Divide the sorted 7-point rainfall dataset into lower and upper quartiles. Mark Q_1 = 0.2 and Q_3 = 1.2; the width of the middle 50% box spans the interquartile range.

Execute the sequence on your SC-6: **[g] [CLΣ] 0.1 [Σ+] 0.2 [Σ+] 0.4 [Σ+] 0.6 [Σ+] 0.9 [Σ+] 1.2 [Σ+] 1.5 [Σ+] [IQR]** → 0.75 (T=0, Z=0, Y=7, X=0.75). Compute interquartile range (Q_3 - Q_1 = 0.75). Register X displays 0.7500. Interquartile range of rainfall is **0.75 inches**.

Problem 7.25: Mean Absolute Deviation of a 5-Point Dataset

Sensor Error Analysis: A 5-point dataset: 10, 15, 20, 25, 30 has mean x■ = 20.0. Deviations from mean are |-10|, |-5|, |0|, |+5|, |+10|. Sum of deviations = 30. Find the Mean Absolute Deviation (MAD = 30 / 5 = 6.0). Lay out the points on a number line. Measure the physical distance from each point to the center mark 20: 10 + 5 + 0 + 5 + 10 = 30. Dividing by 5 yields the average distance from center.

On your SC-6, key in **[g] [CLΣ] 10 [Σ+] 15 [Σ+] 20 [Σ+] 25 [Σ+] 30 [Σ+] [g] [MAD]** → 6 (T=0, Z=0, Y=5, X=6). Compute Mean Absolute Deviation (MAD = 6). Register X displays 6.0000. Mean Absolute Deviation is **6.00**.

Problem 7.26: Frequency of Score 85

Scorecard Frequency Binning: In survey dataset 70, 75, 80, 80, 85, 85, 85, 90, 90, 95, accumulate observation 85 and inspect active sample counter. Place a token into the score 85 column. The stack records the entry into the statistical registers.

On the SC-6 keypad, enter `85 [⊠+]` → `1 (T=0, Z=0, Y=0, X=1)`. Accumulate score into statistical register (n = 1). Register X displays 1. Single observation of score 85 registered in sample bin.

7.7.4 Expedition 4: The Zero-Pair Vault & Pre-Algebra Ascent (Problems 7.27–65)

Mission Briefing: Model positive and negative integers with two-color zero pairs, master spatial sign negation, and solve pre-algebra expressions across powers, roots, and randomized ranges.

Problem 7.27: Adding Directed Negative Numbers

Evaluate (-15) + (-28). Place 15 red debt tokens on the workspace. Add 28 more red debt tokens alongside them. Count the accumulated total of 43 red tokens, representing directed deficit (-43).

Turning to your SC-6, key in `15 [+/-] [ENTER] 28 [+/-] [+]` → `-43 (T=0, Z=0, Y=0, X=-43)`. Add -15 + (-28) = -43; stack drops. Register X displays -43. Adding two negative quantities accumulates total magnitude while preserving the negative sign.

Problem 7.28: Subtracting a Larger Positive Number

A bank account has $45. An automatic withdrawal of $70 occurs. What is the balance? Place 45 green credit tokens in a dish. To remove 70 tokens, pair 45 green tokens with 45 red debt tokens (forming zero pairs), then add 25 additional red debt tokens. Removing 70 tokens leaves 25 red debt tokens (-25).

With your SC-6 ready, enter `45 [ENTER] 70 [-]` → `-25 (T=0, Z=0, Y=0, X=-25)`. Subtract 45 - 70 = -25; stack drops. Register X displays -25. Account is overdrawn by $25.

Problem 7.29: Subtracting a Negative Number

Evaluate 12 - (-18). Place 12 yellow positive tiles on the board. To subtract 18 negative red tiles, introduce 18 zero pairs (+18 yellow and -18 red). Physically remove the 18 red tiles. Exactly 12 + 18 = 30 yellow tiles remain.

Step over to your SC-6 and key in `12 [ENTER] 18 [+/-] [-]` → `30 (T=0, Z=0, Y=0, X=30)`. Subtract 12 - (-18) = 12 + 18 = 30; stack drops. Register X displays 30. Subtracting a negative is mathematically and physically identical to adding its positive opposite.

Problem 7.30: Multiplying Signed Numbers (Negative times Negative)

Evaluate (-7) × (-8). On a coordinate grid, establish positive orientation. Multiplying by a negative factor reverses direction 180^° into negative territory. Multiplying by a second negative factor reverses direction another 180^°, returning to positive orientation +56.

Now compute it on your SC-6: **`[7] [+/-] [ENTER] [8] [+/-] [×]`** → `56 (T=0, Z=0, Y=0, X=56)`. Multiply (-7) × (-8) = 56; stack drops. Register X displays 56. The product of two negative factors evaluates to a positive result.

Problem 7.31: Dividing Signed Numbers (Negative divided by Positive)

Evaluate (-72) ÷ (+9). Take 72 red negative tokens representing a total deficit of -72. Partition them evenly into 9 cups. Each cup receives exactly 8 red negative tokens (-8).

Run the sequence on your SC-6: `72 [+/-] [ENTER] [9] [÷]` → `-8 (T=0, Z=0, Y=0, X=-8)`. Divide (-72) ÷ 9 = -8; stack drops. Register X displays -8. Dividing a negative quantity by a positive divisor yields a negative quotient.

Problem 7.32: Absolute Value of Negative Integer

Evaluate |-125|. Locate -125 on a real number line runner. Measure the distance from 0 to -125 using a meter tape. Regardless of direction from the origin, geometric distance is strictly scalar and non-negative: 125 units.

Verify the calculation on your SC-6: `125 [+/-] [g] [|x|]` → `125 (T=0, Z=0, Y=0, X=125)`. Absolute value operator strips sign; magnitude is 125. Register X displays 125. Absolute value computes geometric distance from zero.

Problem 7.33: Absolute Value Expression: |-18| + |+12|

Evaluate |-18| + |12|. Measure distance from -18 to 0 (18 units) and distance from 0 to 12 (12 units). Lay both measurement segments end-to-end to obtain a combined distance of 30 units.

Test this directly on your SC-6: `18 [+/-] [g] [|x|] 12 [g] [|x|] [+]` → `30 (T=0, Z=0, Y=0, X=30)`. Sum absolute distances 18 + 12 = 30; stack drops. Register X displays 30. Sum of magnitudes evaluated without parentheses.

Problem 7.34: Number Line Distance: Between -12 and +15

Find distance between -12 and +15 on the real line: |15 - (-12)|. Place a peg at -12 and a peg at +15 on a numbered track. Count the total unit intervals between them: 12 units to reach zero, plus 15 units beyond zero, totaling 27 units.

Bring this to the SC-6 stack: `15 [ENTER] 12 [+/-] [-] [g] [|x|]` → `27 (T=0, Z=0, Y=0, X=27)`. Confirm positive distance magnitude: |27| = 27. Register X displays 27. Euclidean distance between -12 and +15 confirmed as 27 units.

Problem 7.35: Square of Negative Number: $(-9)^2$

Evaluate $(-9)^2$. Modeling small with blocks before scaling up on your SC-6, take 9 tiles from your kit and assemble a 3 × 3 grid ($(-3)^2 = +9$) to see that squaring a negative magnitude yields a positive area. Now scale big to $(-9)^2$ on your StackCalc: tap 9, negate, and square to confirm 81 positive unit squares without needing 81 loose tiles.

On your SC-6, enter **[9] [+/-] [x²]** → `81 (T=0, Z=0, Y=0, X=81)`. Square in place: (-9) × (-9) = 81. Register X displays 81. Even powers of negative real numbers evaluate to positive values.

Problem 7.36: Geometric Square Root: √289

A square plaza has area 289 m^2. Find side length. Modeling small with blocks before scaling up on your SC-6, first, model the square root concept on a small scale with your Counting Tiles: assemble a 4 × 4 square using 16 tiles to see that edge length is √16 = 4. Now scale big on StackCalc for the 289-tile plaza: enter 289 and tap **[f]** **[√x]** to find the 17-tile edge without needing 289 plastic tiles on the classroom floor.

Execute the sequence on your SC-6: `289 [f] [√x]` → `17 (T=0, Z=0, Y=0, X=17)`. Extract principal square root: √289 = 17. Register X displays 17. Side length of plaza is 17 m.

Problem 7.37: Geometric Square Root: √625

A square chessboard has area 625 cm^2. Find side length. Model area using a 625-square grid overlay. Decompose 625 into prime squares (25 × 25). Verify each dimension equals 25 units.

On your SC-6, key in `625 [f] [√x]` → `25 (T=0, Z=0, Y=0, X=25)`. Extract principal square root: √625 = 25. Register X displays 25. Chessboard side length is 25 cm.

Problem 7.38: Random Number in Range 10 to 50

Generate a random integer between 10 and 50 using **`[g] [t…x]`**. Place 41 numbered tiles (10 through 50) into an opaque urn. Draw one tile at random to model discrete uniform sampling across a bounded interval.

On the SC-6 keypad, enter `10 [ENTER] 50 [g] [t…x]` → `28 (T=0, Z=0, Y=10, X=28)`. Generate uniform pseudo-random integer in [10, 50]. Register X displays a random integer r ∈ [10, 50], while Register Y preserves the lower bound 10.

7.7.5 Expedition 5: Number Theory Challenges & Directed Integer Navigation (Problems 7.39–7.50)

> **Thematic Arc:** Combining `PRIME`, `FACT`, `÷R`, and `LCM` with signed-integer elevation and ledger tracking.

Problem 7.39: Prime Twin Pair Verification: (29, 31)

Model small with your 24-tile kit by testing twin primes (11, 13)—neither 11 tiles nor 13 tiles can form a multi-row rectangle without a leftover tile. Now scale up on your SC-6 to test the larger twin prime pair (29, 31) and compute their sum. Turning to your SC-6, key in `29 [PRIME] 31 [PRIME] [+]` → `60`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 60), confirming both candidates flash `PRIME` on the transflective LCD and sum to the even integer 60.

Problem 7.40: Divisibility by 9 Check via Remainder

Check if 1,557 is divisible by 9 using Euclidean division (**`[g] [÷R]`**). First, model small with your Place Value kit: test divisibility by 9 on 18 (1 ten-bar and 8 cubes), grouping into 2 sets of 9 with zero remainder (18 ÷ 9 = 2 R 0). Now scale big on StackCalc without needing 1,557 blocks:

With your SC-6 ready, enter `1557 [ENTER] [9] [g] [÷R]` → `173 (T=0, Z=0, Y=0, X=173)`. Euclidean division yields quotient 173 in X and remainder 0 in Y, confirming exact divisibility by 9.

Problem 7.41: LCD of Three Denominators: (1 / 4), (1 / 6), (1 / 10)

Model small with your kit by aligning 4-unit and 6-unit tile rows until their edges meet flush at 12 units (lcm(4,6)=12), then scale up on your SC-6 to include a third period of 10. Step over to your SC-6 and key in **`[4] [ENTER] [6] [f] [LCM] 10 [f] [LCM]`** → `60`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 60), chaining the two LCM operations directly to establish the common denominator of 60.

Problem 7.42: Temperature Range Across a Sub-Zero Week

Lowest temperature was -22^°F, highest was +14^°F. Find total temperature swing. On a vertical thermometer scale, mark -22 below zero and +14 above zero. Trace the mercury column rising from -22 to 0 (22 degrees) and from 0 to +14 (14 degrees), measuring the total thermal excursion: 36 degrees.

Now compute it on your SC-6: `14 [ENTER] 22 [+/-] [-]` → `36 (T=0, Z=0, Y=0, X=36)`. Subtract 14 - (-22) = 14 + 22 = 36; stack drops. Register X displays 36. Total temperature variation is 36^°F.

Problem 7.43: Submarine Depth Change

A submarine at depth -180 m ascends +65 m, then dives -40 m. Find final depth. Move a depth marker on a vertical bathymetric track: start at -180 m, slide upward +65 m to -115 m, then slide downward -40 m to settle at -155 m. Run the sequence on your SC-6: `180 [+/-] [ENTER] 65 [+] 40 [-]` → `-155`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
180	0.0000	0.0000	0.0000	180.0000	Key in initial depth magnitude 180
[+/-]	0.0000	0.0000	0.0000	-180.0000	Negate to depth -180 m
[ENTER]	0.0000	0.0000	-180.0000	-180.0000	Push initial depth to Register Y
65	0.0000	0.0000	-180.0000	65.0000	Key in ascent +65 m
[+]	0.0000	0.0000	0.0000	-115.0000	Add ascent: -180 + 65 = -115 m; stack drops
40	0.0000	0.0000	-115.0000	40.0000	Key in dive descent 40 m; stack lifts -115 to Y
[-]	0.0000	0.0000	0.0000	-155.0000	Deduct descent: -115 - 40 = -155 m; stack drops

Register X displays -155. Final depth is 155 m below sea level.

Problem 7.44: Rolling Double Sixes with Two Dice

What is the probability of rolling double sixes with two fair six-sided dice (1 favorable outcome out of 36)? Examine a 6 × 6 grid of dice pairings (36 cells). Only one cell represents (6,6). Compute the fractional area occupied by that single cell.

Verify the calculation on your SC-6: **[1] [ENTER] 36 [÷]** → `0.0277777778 (T=0, Z=0, Y=0, X=0.0278)`. Divide 1 ÷ 36 ≈ 0.0278; stack drops. Register X displays 0.0277777778. Probability is approximately 2.78% (or 1/36).

Problem 7.45: Probability of Not Rolling a 6 on a Die

Five faces are not 6. Compute 5/6. Set out 6 die faces: {1, 2, 3, 4, 5, 6}. Remove the face labeled 6. The remaining 5 faces represent the complement event (E'). Calculate 5/6.

Test this directly on your SC-6: **[5] [ENTER] [6] [÷]** → `0.8333333333 (T=0, Z=0, Y=0, X=0.8333)`. Divide 5 ÷ 6 ≈ 0.8333; stack drops. Register X displays 0.8333333333. Complementary probability is approximately 83.33%.

Problem 7.46: Prime Factor Decomposition of 1,001

Decompose 1,001 into prime factors (famous number-theory product). Modeling small with blocks before scaling up on your SC-6, take 12 unit cubes from your kit and build a 2 × 2 × 3 prism to see how three prime dimensions multiply into a single volume. Now scale big to 1,001 on your StackCalc: enter 1001 and tap **[g]** **[FACT]** to discover the beautiful prime dimensions 7 × 11 × 13 without needing 1,001 physical cubes!

Bring this to the SC-6 stack: `1001 [g] [FACT]` → `1001 (T=0, Z=0, Y=0, X=1001)`. LCD decomposes into prime factors: `7 × 11 × 13`. Register X preserves 1001 while the display shows 7 × 11 × 13.

Problem 7.47: Prime Factor Decomposition of 1,729 (Hardy-Ramanujan Number)

Decompose 1,729 into prime factors. Inspect 1,729, known as the smallest integer expressible as the sum of two cubes in two different ways ($1^3 + 12^3 = 9^3 + 10^3$). Deconstruct it into prime factor blocks: 7 × 13 × 19.

On your SC-6, enter `1729 [g] [FACT]` → `1729 (T=0, Z=0, Y=0, X=1729)`. LCD decomposes into prime factors: `7 × 13 × 19`. Register X preserves 1729 while the display reveals 7 × 13 × 19, three primes in arithmetic progression with common difference 6.

Problem 7.48: Weighted Mean of Classroom Grades

A grading syllabus weights homework (average 90, weight 2), quizzes (average 82, weight 3), and exams (average 88, weight 5) for a total weight of 10. Accumulate the weighted points directly on the stack by executing the sequence on your SC-6: `90 [ENTER] [2] [×] 82 [ENTER] [3] [×] [+] 88 [ENTER] [5] [×] [+] 10 [÷]` → `86.6`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 86.6), computing the weighted grade average of 86.6% without scratch paper or order-of-operations ambiguity.

Problem 7.49: Goldbach Conjecture Sample Check: 28 = 11 + 17

Test if 11 and 17 are both prime and sum to 28. Lay out 11 yellow unit tiles (prime length) and 17 yellow unit tiles (prime length). Verify neither can be factored into non-trivial rectangles. Join them end-to-end to form a single train of 28 units, demonstrating that even integer 28 decomposes into the sum of two primes. On your SC-6, key in `11 [PRIME] 17 [PRIME] [+] 11 [ENTER] 17 [+]` → `28`.

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`11`	0.0000	0.0000	0.0000	11.0000	Key in first prime candidate 11
[PRIME]	0.0000	0.0000	0.0000	11.0000	LCD flashes `PRIME`; preserves 11 in Register X
`17`	0.0000	0.0000	11.0000	17.0000	Key in second candidate 17; stack lifts 11 to Y
[PRIME]	0.0000	0.0000	11.0000	17.0000	LCD flashes `PRIME`; preserves 17 in Register X
[+]	0.0000	0.0000	0.0000	28.0000	Sum primes 11 + 17 = 28; stack drops
`11`	0.0000	0.0000	28.0000	11.0000	Key in 11 for second partition check; stack lifts 28 to Y
[ENTER]	0.0000	28.0000	11.0000	11.0000	Push 11 to Y; lifts 28 to Z (stack lift disabled)
`17`	0.0000	28.0000	11.0000	17.0000	Key in 17; overwrites X since `ENTER` disabled lift
[+]	0.0000	0.0000	28.0000	28.0000	Sum 11 + 17 = 28; stack drops, preserving first sum in Y

Register X displays 28 and Register Y preserves 28. Both 11 and 17 confirmed prime, summing to even integer 28.

Problem 7.50: Net Profit Across 4 Business Quarters

Tracking corporate financial performance across four business quarters records Q1 profit +$14,500, Q2 loss -$3,200, Q3 profit +$8,900, and Q4 loss -$1,400. Pair credits and debits on the stack—on the SC-6 keypad, enter `14500 [ENTER] 3200 [-] 8900 [+] 1400 [-]` → `18800`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 18800), yielding net annual earnings of $18,800.00.

7.7.6 Expedition 6: Compound Probability & Pre-Algebra Mastery Sprints (Problems 7.51–7.65)

Thematic Arc: Evaluating dependent and independent multi-stage probabilities, prime factor trees, and algebraic integer expressions.

Problem 7.51: Compound Probability: Coin Flip and Die Roll

Flipping Heads on a fair coin (1/2) and rolling a 6 on a six-sided die (1/6) forms a 2 × 6 outcome grid with 12 equal cells. Compute the joint probability of the independent events on the stack: key in **[1] [ENTER] [2] [÷] [1] [ENTER] [6] [÷] [×]** → `0.0833333333`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 0.0833333333), yielding P(Heads and 6) = 1/12 ≈ 8.33%.

Problem 7.52: Drawing Two Aces Without Replacement

Drawing two cards sequentially from a standard 52-card deck without replacement yields 4/52 on the first draw, leaving 3 aces among 51 remaining cards (3/51) on the second draw. Multiply the dependent probabilities on the stack: enter **[4] [ENTER] 52 [÷] [3] [ENTER] 51 [÷] [×]** → `0.0045248869`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 0.0045248869), giving a joint probability of 1/221 ≈ 0.45%.

Problem 7.53: Drawing Consecutive Matching Socks

A drawer holds 6 black socks and 4 blue socks (10 total). The probability of drawing a first black sock is 6/10, and drawing a second black sock without replacement is 5/9. Evaluate the dependent pair probability on the stack: key in **[6] [ENTER] 10 [÷] [5] [ENTER] [9] [÷] [×]** → `0.3333333333`.

Running this sequence → (T: 0, Z: 0, Y: 0, X: 0.3333333333), proving an exact 1/3 (33.33%) chance of drawing a matching pair.

Problem 7.54: Prime Factorization of 3,600

Decompose 3,600 into prime factors ($3600 = 60^2$). Constructing a factor tree shows $3600 = 36 \times 100 = 2^4 \times 3^2 \times 5^2$:

Now compute it on your SC-6: `3600 [g] [FACT]` → `3600 (T=0, Z=0, Y=0, X=3600)`. LCD decomposes into prime factors: $2^4 \times 3^2 \times 5^2$.

Problem 7.55: GCD and LCM of 45 and 75

Decomposing $45 = 3^2 \times 5$ and $75 = 3 \times 5^2$ reveals their prime intersection $3 \times 5 = 15$ (gcd) and prime union $3^2 \times 5^2 = 225$ (lcm). Compute both dual parameters on the stack by running the sequence on your SC-6: `45 [ENTER] 75 [GCF] 45 [ENTER] 75 [f] [LCM]` → `225`.

Running this sequence → (T: 0, Z: 0, Y: 15, X: 225), displaying LCM = 225 and preserving GCF = 15 in Register Y (15 × 225 = 3,375 = 45 × 75).

Problem 7.56: Synchronized Municipal Traffic Signal Cycles

Signal A cycles every 45 seconds, Signal B cycles every 60 seconds. Find the synchronized cycle time: lcm(45, 60). On a timing tape, place red markers every 45 units (45, 90, 135, 180...) and blue markers every 60 units (60, 120, 180...). The first point of co-occurrence is 180 units.

Verify the calculation on your SC-6: `45 [ENTER] 60 [f] [LCM]` → `180 (T=0, Z=0, Y=0, X=180)`. Compute lcm(45, 60) = 180; stack drops. Register X displays 180. Both traffic lights synchronize every 180 seconds (3 minutes).

Problem 7.57: Euclidean Division Ladder for gcd(546, 210)

Compute Euclidean steps for 546 and 210: 546 ÷ 210 = 2 R 126; 210 ÷ 126 = 1 R 84; 126 ÷ 84 = 1 R 42; 84 ÷ 42 = 2 R 0. Cut a ribbon 546 cm long and measure with a 210 cm rod: two rods fit with 126 cm remainder (546 = 2 × 210 + 126). Next, measure 210 cm with 126 cm: one rod fits with 84 cm remainder. Measure 126 cm with 84 cm: one rod fits with 42 cm remainder. Finally, 84 cm divides into two 42 cm segments with 0 remainder. The last non-zero remainder is 42.

Test this directly on your SC-6: `546 [ENTER] 210 [GCF]` → `42 (T=0, Z=0, Y=0, X=42)`. Execute hardware Euclidean ladder: gcd(546, 210) = 42. Register X displays 42. Greatest common divisor of 546 and 210 is 42.

Problem 7.58: Mean Absolute Deviation of a 7-Element Dataset

Dataset: 12, 14, 15, 16, 18, 20, 24 (Mean = 17.0). Deviations: 5, 3, 2, 1, 1, 3, 7. Sum = 22. MAD = 22/7. Plot the 7 points on a dot plot. Draw a fulcrum at the mean 17. Measure the physical distance from each dot to the mean (5, 3, 2, 1, 1, 3, 7). Add the lengths to get 22, and divide evenly among the 7 data points: 22/7 ≈ 3.1429.

Bring this to the SC-6 stack: **`[g] [CLΣ] 12 [Σ+] 14 [Σ+] 15 [Σ+] 16 [Σ+] 18 [Σ+] 20 [Σ+] 24 [Σ+] [g] [MAD]`** → `3.1428571429 (T=0, Z=0, Y=7, X=3.1428571429)`. Compute mean absolute deviation; Y holds count n = 7. Register X displays 3.1428571429 and Register Y displays 7. Average distance from data points to mean is ≈ 3.14.

Problem 7.59: Interquartile Range Across Grade 6 Science Scores

Scores: 65, 72, 75, 80, 84, 88, 92, 96. Find IQR (Q_3 - Q_1 = 90 - 73.5 = 16.5). Arrange 8 test score cards in ascending order. Divide into lower half (65, 72, 75, 80) and upper half (84, 88, 92, 96). Find the median of lower half (Q_1 = 73.5) and median of upper half (Q_3 = 90). Measure the spread between quartiles: 90 - 73.5 = 16.5.

On your SC-6, enter **`[g] [CLΣ] 65 [Σ+] 72 [Σ+] 75 [Σ+] 80 [Σ+] 84 [Σ+] 88 [Σ+] 92 [Σ+] 96 [Σ+] [IQR]`** → `16.5 (T=0, Z=0, Y=8, X=16.5)`. Compute interquartile range Q_3 - Q_1 = 16.5; Y holds count n = 8. Register X displays 16.5 and Register Y displays 8. Interquartile range of middle 50% of class is 16.5 points.

Problem 7.60: Chemical Freezing Point Depression

Pure water freezes at 0^°C. Adding rock salt lowers the freezing point by -7.8^°C. Adding calcium chloride drops it an additional -6.4^°C. Find final freezing point. Use a downward-pointing thermometer strip. Move down 7.8^° below zero. Move down another 6.4^° further below zero. Measure total drop from zero: 14.2^°, giving final temperature of -14.2^°C.

Execute the sequence on your SC-6: `7.8 [+/-] [ENTER] 6.4 [+/-] [+]` → `-14.2 (T=0, Z=0, Y=0, X=-14.2)`. Add depressions: -7.8 + (-6.4) = -14.2; stack drops. Register X displays -14.2. Final depressed freezing point is -14.2^°C.

Problem 7.61: Product of Three Signed Integers

Evaluate (-4) × (-5) × (-6). On a number ray, multiplying negative by negative flips the orientation to positive: (-4) × (-5) = +20. Multiplying by a third negative flips the direction back into negative territory: +20 × (-6) = -120. On your SC-6, key in **[4] [+/-] [ENTER] [5] [+/-] [×] [6] [+/-] [×]** → -120.

Tap 4 [+/-] [ENTER] 5 [+/-] [×] → (T=0, Z=0, Y=0, X=20). Multiply (-4) × (-5) = 20. Tap 6 [+/-] [×] → (T=0, Z=0, Y=0, X=-120). Multiply 20 × (-6) = -120; stack drops. Register X displays -120. An odd number of negative factors produces a negative product.

Problem 7.62: Order of Operations with Negative Numbers

Evaluate (-18) × 4 - (-36) ÷ (-9) = -72 - 4 = -76. Model the two terms separately: Term 1 is 4 groups of -18 red chips (-72). Term 2 is -36 divided into -9 parts (+4). Deducting 4 positive units from 72 red debt units leaves 76 red debt units (-76). On the SC-6 keypad, enter 18 [+/-] [ENTER] [4] [×] 36 [+/-] [ENTER] [9] [+/-] [÷] [-] → -76.

Tap 18 [+/-] [ENTER] 4 [×] → (T=0, Z=0, Y=0, X=-72). Compute first product -18 × 4 = -72. Tap 36 [+/-] [ENTER] 9 [+/-] [÷] → (T=0, Z=0, Y=-72, X=4). Compute quotient (-36) ÷ (-9) = 4 while -72 is preserved in Y. Tap **[-]** → (T=0, Z=0, Y=0, X=-76). Subtract -72 - 4 = -76; stack drops. Register X displays -76. Subtraction of two grouped terms completed cleanly without parentheses.

Problem 7.63: Geometric Square Root of a Square Ranch

A square ranch has an area of 4,096 m^2. Find side length. On a square grid, identify that $4096 = 2^{12}$. Taking the square root halves the exponent: $\sqrt{(2^{12})} = 2^6 = 64$.

Turning to your SC-6, key in 4096 [f] [√x] → 64 (T=0, Z=0, Y=0, X=64). Extract square root: √4096 = 64. Register X displays 64. Ranch perimeter boundary is 64 m per side.

Problem 7.64: Divisibility by 11 Verification

Test if 2,596 is divisible by 11 using Euclidean division (**[g] [÷R]**). Apply the alternating digit sum divisibility rule for 11: (2 + 9) - (5 + 6) = 11 - 11 = 0. Since the alternating difference is a multiple of 11, the number is divisible with zero remainder.

With your SC-6 ready, enter 2596 [ENTER] 11 [g] [÷R] → 236 (T=0, Z=0, Y=0, X=236). Euclidean division: Quotient 236 in X, Remainder 0 in Y. Register X displays 236 and Register Y displays 0. Remainder of 0 confirms exact divisibility by 11 ($2596 = 236 \times 11$).

Problem 7.65: Mersenne Number Primality Check: $2^5 - 1 = 31$

Compute $2^5 - 1$ and check if the result is prime. Lay out power-of-two blocks: 1, 2, 4, 8, 16. Summing these 5 blocks produces $2^5 - 1 = 31$. Just as 7 or 13 tiles from your 24-tile kit can only form a single $1 \times p$ row, scaling up to $2^5 - 1 = 31$ on your SC-6 confirms that 31 has no rectangular factors.

Step over to your SC-6 and key in **[2] [ENTER] [5] [g] [y□] [1] [-] [PRIME]** → Flashes (T=0, Z=0, Y=0, X=31). Test primality: LCD status flashes PRIME. Register X preserves 31 and LCD flashes PRIME. The 3rd Mersenne prime $M_5 = 2^5 - 1 = 31$ is verified.

For Parents & Teachers: Standards Alignment Matrix

Topic / Skill	Common Core (CCSS)	Singapore Dimensions Math	Bridges in Mathematics
Simple & Compound Probability	7.SP.C.5, 7.SP.C.8	Grade 6 Chapter 14	Unit 7 Module 1
Prime Factorization & Primes	6.NS.B.4	Grade 6 Chapter 1	Unit 1 Module 2
GCF & LCM via Hardware Keys	6.NS.B.4	Grade 6 Chapter 1	Unit 1 Module 3
Mean, Median, Mode, Range	6.SP.B.5.C	Grade 6 Chapter 13	Unit 8 Module 1
IQR & Mean Absolute Deviation	6.SP.B.5.C	Grade 6 Chapter 13	Unit 8 Module 3
Signed Numbers & Zero Pairs	6.NS.C.5, 7.NS.A.1	Grade 6 Chapter 2	Unit 6 Module 2
Absolute Value as Distance	6.NS.C.7.C	Grade 6 Chapter 2	Unit 6 Module 3
Geometric Square & Root Inverses	8.EE.A.2 (Accelerated Gr 6)	Grade 6 Chapter 10	Unit 5 Module 4

For detailed classroom station activities corresponding to these standards, consult Curriculum Station Worksheets: Big Ideas Math & AP Standards .

7.8 What You Mastered & Looking Ahead

In this chapter, you unlocked the fundamental atomic architecture of numbers and real-world data:

1. **Discrete Probability & Fair Symmetries:** You investigated fair polyhedral dice (`[DICE]`), experimental frequencies, and compound probability events without tree confusion.
2. **The Prime Factor Engine:** You harnessed the Prime Factor Studio and SC-6 dedicated hardware keys (`[PRIME]` , `[g] [FACT]` , `[GCF]` , `[f] [LCM]` , `[g] [÷R]`) to decompose composite numbers, calculate greatest common factors, and prove the Secret Partner Rule.
3. **Descriptive Statistics:** With the non-volatile statistical accumulator (`[Σ+]`), you evaluated real datasets, discovering how means, medians, and modes capture central tendencies while IQR and MAD reveal spread.
4. **Pre-Algebra & Directed Numbers:** You conquered negative numbers and zero pairs with the sign toggle (`[+/-]`) and distance metrics (`[g] [|x|]`).

In **Chapter 08: The Math Quiz Engine**, you will take everything you have learned and put your operational speed to the test. You will enter the interactive quiz game mode on your SC-6, solving rapid-fire arithmetic challenges, racing against the hardware timer, and tracking your accuracy streaks on the transflective LCD. Let's see how fast your mathematical reflexes really are!

The Gamified Math Quiz Engine

8.1 The Musician's Scales & The Astronaut's Simulator: Why Instant Math Reflexes Set Your Creative Brain Free

Watch a master concert pianist sit before a Steinway grand piano to perform a Rachmaninoff concerto. Their fingers fly across eighty-eight ebony and ivory keys with dizzying speed, striking chords of astonishing harmonic complexity. If that pianist had to pause for even a quarter of a second to consciously calculate which fingers belong on middle C, E-flat, and G, the music would instantly collapse into dissonant stuttering. The pianist can pour their soul into emotional nuance, rubato tempo, and melodic phrasing *only because their fingers mastered scales, arpeggios, and Hanon drills years ago*. The mechanical technique was drilled into smooth muscle memory so thoroughly that it became invisible.

Now journey to Cape Canaveral during the golden age of Apollo spaceflight. Inside the mission flight simulators, astronauts like Neil Armstrong and Jim Lovell spent hundreds of grueling hours strapped into mock command modules while flight instructors deliberately triggered catastrophic thruster failures, computer alarms, and guidance malfunctions. In an emergency traveling at 25,000 miles per hour, there is no time to consult a flight manual or ponder first principles from scratch. The astronauts drilled until their physical reactions were instantaneous, cool-headed reflexes. Because survival instincts were completely automated, their mental energy was liberated to make life-or-death decisions when the unexpected occurred.

In mathematics, **elementary fact fluency is your musical scale and your flight simulator**.

When you look at 7 × 8 and have to count by sevens on your fingers (7, 14, 21, 28, 35, 42, 49, 56), your brain gets tired before you even start the rest of the problem. When basic math facts become second nature, your brain stays fresh and energized for exciting puzzles, big ideas, and creative solutions!

The StackCalc SC-6 does not replace your human brain—it coaches it. By integrating an authentic, hardware-timed mental sprint engine directly into the calculator's silicon, the SC-6 transforms math practice into a focused, rhythmic, distraction-free flow state.



Figure: The SC-6 Elementary Hardware Calculator

Chapter Baseline Mode: `[NUM]`

Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Display

(Quiz Sandbox `[f]` `[?]` *opens timed mental arithmetic sprints)*

Unlocked Keycaps Ribbon — Quiz Sprint Suite

• **Quiz Activation & Control:** `[f]` `[?]` (Launch Quiz Sandbox), `[ENTER]` (Submit Answer & Evaluate), `[g]` `[SHOW]` (Inspect Active Score, Streak, & Average Latency).

• **Numeric Answer Entry:** Digits `[0]` through `[9]`, Two-Dot Fraction `[.]`, Negative Toggle `[+/-]`, Destructive Backspace `[<-]`.

• **Operational Verification:** `[+]`, `[-]`, `[×]`, `[÷]`, `[g]` `[÷R]`, `[g]` `[SIMP]`, `[ENTER]`, `[f]` `[LASTX]`.

• **Exit Quiz Sandbox:** Pressing `[C]` twice or pressing any base display mode key (`[NUM]`, `[g]` `[FIX]`, `[f]` `[ALL]`, `[FDISP]`) immediately dismisses the quiz engine and restores standard stack calculations with 100% register preservation.



Figure: Launch SC-6 Gamified Arithmetic Sprint Quiz Engine

For Parents & Teachers: Cognitive Automaticity & The Hardware Quiz Philosophy

Pedagogical Vision & Cognitive Load: In elementary mathematics, **fact fluency**—the effortless, instantaneous recall of basic addition, subtraction, multiplication, and division relationships—is the foundational cognitive gateway to higher-level mathematical reasoning *(Ma, 1999)*. Cognitive science research (George Miller *(Miller, 1956)* and John Sweller *(Sweller, 1988)*) demonstrates that human working memory has a strictly limited bandwidth. When a student expends precious cognitive energy manually counting on their fingers or executing slow column arithmetic to find $7 \times 8 = 56$, their working memory is completely saturated. They have zero remaining mental capacity to comprehend the multi-step structure of complex word problems, balance algebraic equations, or reason about proportional relationships.

Deficiencies of Conventional Methods: Paper flashcards reward passive memorization without measuring reaction latency, while mobile math apps introduce cartoon distractions and loot boxes. The SC-6 embeds an authentic, distraction-free, hardware-timed sprint engine running bare-metal on dedicated silicon. Missed questions re-enter the Leitner queue for spaced retrieval practice (see Appendix B).

8.2 The RPN Prompt & Rapid Sprint Evaluation ([f] [?] & [ENTER])

8.2.1 Pure RPN Puzzles & Direct Mental-Math Prompts

Traditional educational software traps students in parenthesized algebraic expressions or multiple-choice guessing games.

The SC-6 Quiz Engine challenges you with two complementary prompt styles on the transflective graphic LCD:

1. **RPN Missing-Value Puzzles (`3 [f] [?] + = 10` or `8 [f] [?] × = 56`):** Shows how numbers sit on Floor Y and Floor X before an operation combines them:

3 [?] + = 10

2. **Direct Mental-Math Prompts (`4 + 5 = ?`, `1/2 + 1/4 = ?`, or `35² = ?`):** Shows a classic arithmetic or pre-algebra challenge where you compute the result in your head, type the answer into Register X, and tap **[ENTER]**!

[f] **[?]** **LVL 1 SCORE: 40 STREAK: 3 ●●●**

3 **[f]** **[?]** + = 10

Y: 3

X: _

Figure 8.1: Graphic LCD Layout in Quiz Mode: Solving for Missing Value ?

What This Display Teaches You:

- *"Start with 3 resting on Floor Y."*
- *"Place the missing mystery token `?` on the Ground Floor (X)."*
- *"Add them together (+)."*
- *"The target result must equal 10 (`10`)."*

You immediately recognize that this RPN sequence represents the familiar question: *"What number added to 3 makes 10?"* And after any quiz sprint, you can test every single problem right in **[NUM]** mode using the RPN stack sequences shown in the 48 drills below!

8.2.2 Rapid Sprint Evaluation Workflow via [ENTER]

Unlike scientific calculators that require cumbersome variable assignment menus (`STO A`, `RCL A`, `SOLVE`), answering a quiz question on the SC-6 requires **zero configuration**:

1. You read the RPN prompt on screen.
2. You type your candidate answer using the numeric digits: e.g. **[7]** .

3. You press the evaluate and submit key **[ENTER]**.

Hardware Evaluation Pipeline:

When **[ENTER]** is pressed, the internal calculator engine executes three atomic operations in under 5 milliseconds:

1. **Variable Substitution:** Binds candidate value 7 to variable `?`.
2. **RPN Stack Execution:** Evaluates the stack sequence: `3 [ENTER] 7 [+]` → 10.
3. **Equality Verification:** Compares the evaluated result to the target value 10:

- **If Match (10 = 10):** Flashes `☒ NICE!`, plays an encouraging success chirp, increments the score, and generates the next problem.
- **If Mismatch:** Flashes `☒ TRY AGAIN`, records an error penalty, and leaves the equation visible on screen so you can inspect your mistake and re-attempt the problem!

Elapsed Time	Quiz Engine Verification Step
t = 0.0 ms	Tactile snap-dome switch closes when you press **[ENTER]**
t = 1.0 ms	Engine reads your candidate answer from Register X
t = 2.4 ms	Evaluates candidate inside the RPN equation and checks exact match
t = 4.2 ms	Updates streak counter and refreshes transflective LCD with instant feedback

8.3 The 6-Level Adaptive Curriculum Ladder

The SC-6 Quiz Engine spans six exciting levels that grow with you from Kindergarten through Grade 6, building speed, accuracy, and confidence at every step:

Level	Target Grade	Operations & Mathematical Concepts	Speed Target	Passing Threshold
Level 1	K – Grade 1	**Single-Digit Number Bonds (Sums to 10):** • • Band 1: Sums ≤ 5, additive identity with zero (3 + ?, 4 - ? = 1). • • Band 2: Sums 6 to 10, combinations to ten (7 + ? = 10, 10 - ? = 4). • • Band 3: Doubles & near-doubles (4 + 4 = ?, 5 + 4 = ?).	< 3.0 s	80% accuracy
Level 2	Grade 2	**Whole Number Addition & Subtraction to 100:** • • Band 1: Multiples of ten (40 + 30 = ?, 80 - 20 = ?). • • Band 2: Two-digit mental math without regrouping (34 + 12 = ?, 67 - 25 = ?). • • Band 3: Two-digit mental math with regrouping (47 + 38 = ?, 72 - 45 = ?).	< 4.0 s	85% accuracy
Level 3	Grades 3–4	**Times Tables & Division Facts to 12:** • • Band 1: Core foundational tables: 2, 5, 10 (5 × 6 = ?, 40 ÷ 5 = ?). • • Band 2: Intermediate tables: 3, 4, 6 (4 × 8 = ?, 36 ÷ 6 = ?). • • Band 3: Challenging tables: 7, 8, 9, 11, 12, squares (7 × 8, 12 × 11, 9^2).	< 2.5 s	90% accuracy
Level 4	Grades 4–5	**Fractions & Remainders:** • • Band 1: Division with whole quotients and remainders (17 ÷ 5 → Q=3, R=2). • • Band 2: Like denominator addition and subtraction (2/5 + 1/5 = ?). • • Band 3: Related and unlike denominators (1/2 + 1/4 = ?, 3/4 - 1/3 = ?).	< 5.0 s	85% accuracy
Level 5	Grade 5	**Mixed Arithmetic & Order of Operations:** • • Band 1: Chained operations without parentheses: 24 ÷ 6 + 7 = ?. • • Band 2: Mixed numbers and improper conversions: 1(3 / 4) + 2(1 / 2) = ?. • • Band 3: Decimal mental arithmetic and percentages: 0.25 × 80 = ?.	< 4.5 s	85% accuracy
Level 6	Grade 6	**Pre-Algebra & Mental Math Number Sense Sprint:** • • Band 1: Mental squaring shortcuts for numbers ending in 5: 35^2, 65^2. • • Band 2: Multiplication by 11: 43 × 11 = 473, 56 × 11 = 616. • • Band 3: Signed integers and absolute values: -18 + 7 = ?, | -42 | - 15 = ?. • • Band 4: Prime checks and GCF/LCM: gcd(24, 36) = ?, lcm(6, 8) = ?.	< 2.0 s	95% accuracy



Figure: Math Dominoes Pairing: Concrete Number Bonds and Commutative Pairs

Figure: Dominoes Studio: Modular Enclosure and Tactile Training Tiles

8.4 Hardware Scoring Dynamics, Fast Streaks & Latency Tracking

The SC-6 Quiz Engine evaluates both **accuracy** and **reaction speed**, encouraging you to transcend slow finger counting and achieve true mental fluency.

Quiz Event	Point Delta	Streak Effect
Correct Answer (Regular Speed)	`+10 Points`	Streak increments (`+1`)
Correct Answer (Fast Speed $< T_{max}$)	`+20 Points`	Streak increments (`+1`)
Incorrect Answer	`-10 Points`	Streak resets to `0` (⌧)

Quiz Event	Point Delta	Streak Effect
Time-Out (No answer in 15 s)	-5 Points	Streak resets to 0 (☒)

8.4.1 Speed Thresholds (T_{max}) by Level

To earn the coveted **+20 Fast Point Bonus**, you must submit your verified answer within the level's calibrated response threshold:

- **Level 1 (Single-digit sums):** T_{max} = 3.0 seconds
- **Level 2 (Two-digit addition):** T_{max} = 4.0 seconds
- **Level 3 (Multiplication facts):** T_{max} = 2.5 seconds
- **Level 4 (Fractions & remainders):** T_{max} = 5.0 seconds
- **Level 5 (Order of operations):** T_{max} = 4.5 seconds
- **Level 6 (Advanced mental sprint):** T_{max} = 2.0 seconds

8.4.2 Fast Streak Banners & Unlock Tiers

As you answer consecutive problems correctly within the fast speed threshold, the graphic LCD illuminates active streak pips (☒☒☒☒☒):

- **3 Fast Streak:** Displays `BRONZE STREAK! +10 BONUS`
- **5 Fast Streak:** Displays `SILVER STREAK! +25 BONUS`
- **10 Fast Streak:** Displays `GOLDEN MASTER! +50 BONUS`
- **20 Fast Streak (Flawless Run):** Triggers the legendary graphic celebratory banner:

```
>>> NUMBER SENSE CHAMPION! FLAWLESS SPRINT <<<
```



Figure 8.2: Transflective LCD Frame: 5 Fast Streak Unlock in Level 3

8.4.3 Algebraic Trap vs. StackCalc Superpower Showdown: Mental Sprint & Subtraction Complements

Challenge / Equation	The Algebraic Calculator Trap (TI-30X / Smartphone)	The StackCalc SC-6 + Manipulative Superpower	Keystroke Reduction	Live Stack Visibility	Pedagogical Breakthrough
Rapid Subtraction Complement : • 1000 - 647 = 353	Must type `1 0 0 0 - 6 4 7 =` (8 keystrokes). On paper, requires crossing out three zeros with repeated borrowing across multiple columns (slow and error-prone).	Vedic / 9s Complement Shortcut: subtract each digit from 9, and the last digit from 10: (9-6)(9-4)(10-7) = **353**! On the stack: `1000 [ENTER] 647 [-]` → **353** (5 strokes). Instant verification with zero borrowing!	**38% fewer strokes**	Register Y retains the 1000 base while Register X receives 647, confirming difference 353 immediately on the transflective screen.	Learners discover the base-10 complement rule using Place Value blocks, eliminating multi-column borrowing anxiety completely.

8.5 Walkthrough: An Elite Level 6 Sprint Simulation

To appreciate how the quiz engine trains rapid mental calculation, consider an actual 5-problem sprint session in **Level 6 (Mental Math & Number Sense Sprint)**:

Sprint Prompt	Mental Math Strategy	Your Keystrokes	Elapsed Time & Score
Prompt 1: `35² = ?`	Multiply tens digit by (tens + 1): 3 × 4 = 12; append 25 → 1225	`1225` **[ENTER]**	1.8 s (`+20 pts`)
Prompt 2: `48 × 5 = ?`	Halve 48 → 24, multiply by 10 → 240	`240` **[ENTER]**	1.4 s (`+20 pts`)
Prompt 3: `1000 - 647 = ?`	Complement from 999: (9-6)(9-4)(10-7) = 353	`353` **[ENTER]**	1.7 s (`+20 pts`)
Prompt 4: `144 ÷ 12 = ?`	Known square root inverse $12^2 = 144 \rightarrow 12$	`12` **[ENTER]**	1.1 s (`+20 pts`)
Prompt 5: `25 × 16 = ?`	Quarter of 16 is 4; multiply by 100 → 400	`400` **[ENTER]**	1.5 s (`+20 pts`, **5-Streak Bonus** `+25 pts`**!**)

The entire 5-problem sequence required less than 10 seconds of active calculation, demonstrating how RPN muscle memory and mental arithmetic algorithms unite on the SC-6!

8.6 Classroom Sprint Stations, Relays & Tournament Protocols

The SC-6 Quiz Engine is designed to fit seamlessly into daily math workshop routines across elementary and middle school classrooms:

8.6.1 Protocol 1: The 2-Minute Daily Warmup Sprint

At the beginning of your math practice session, set your SC-6 to your target level and participate in a focused 2-minute warmup sprint:

- **Duration:** Exactly 120 seconds.
- **Goal:** Personal best progression (surpassing yesterday's score).
- **Tracking:** Log your score, accuracy percentage, and longest fast streak in your math notebook.
- **Outcome:** Focuses your attention on active mathematical processing within 60 seconds of sitting down.

Date	Target Level	Final Score	Fast Streak	Personal Best?
Oct 14	Level 3 (×/÷)	140	4	No
Oct 15	Level 3 (×/÷)	180	6	**YES!**
Oct 16	Level 3 (×/÷)	210	8	**YES!**
Oct 17	Level 4 (Fractions)	90	2	New Level!

8.6.2 Protocol 2: The 4-Person Relay Challenge

For cooperative review stations, teams of four can run a quiz sprint relay:

1. Team members sit in a row with a single SC-6 calculator placed in the center.
2. Player 1 starts the sprint, aiming for a **3 Fast Streak** before passing the calculator to Player 2.
3. If Player 1 enters a wrong answer, their streak resets, and they keep solving until they achieve the 3-streak.
4. Player 2 receives the calculator, achieves a 3-streak, and passes to Player 3, who passes to Player 4.
5. The team timer stops when Player 4 completes the final 3-streak (12 total consecutive correct answers).
6. **Cooperative Benefit:** Teammates cheer for each other, share mental shortcut tips during handoffs, and value accuracy over careless rushing.

8.6.3 Protocol 3: Factory Baseline Memory Reset & Fresh Starts

Before a tournament sprint or math quiz relay, you can wipe previous scores and registers so your calculator starts completely fresh:

Factory Baseline Memory Purge Protocol

1. Hold down key **`[C]`** (Row 7, Col 1).
2. Momentarily tap **`[g] [OFF]`** (Power key).
3. Release **`[C]`**.
4. Screen momentarily displays: `"MEMORY CLEARED - ALL REGISTERS PURGED"`.
5. Stack resets to X = Y = Z = T = 0.0000; continuous statistical and quiz registers reset to zero.
6. Calculator enters clean baseline state: **`[NUM]`** 4-Stack XYZT.

For Parents & Teachers: Pedagogical Architecture of the Quiz Engine

Private Formative Feedback & Affective Resilience: Research in mathematics anxiety demonstrates that public performance pressure during timed paper testing can induce affective paralysis in young learners. The SC-6 transforms the emotional climate of arithmetic practice: feedback is immediate, private, and localized to the display. When an entry is incorrect, the instrument avoids punitive red-pen cues, presenting a clear diagnostic prompt (`✉ TRY AGAIN`) while keeping the problem active. Learners inspect the register stack, identify intermediate regrouping or factor errors, and execute instant correction, building grit and mathematical resilience.

Scoring Incentives & Decision Theory: The engine's scoring rubric enforces deliberate pacing over impulsive guessing: correct answers submitted within 2.0 seconds receive a +20 point bonus plus streak acceleration, while incorrect answers incur an immediate -10 point penalty and reset the active streak counter to zero. This mathematical structure guarantees that rapid guessing yields a negative net expected score ($E[score] < 0$), teaching students that taking an extra second to reflect and verify yields vastly superior outcomes.

Bare-Metal Execution & Latency Invariance: Unlike tablet or web-based drill applications that suffer from operating system background interrupts, touch-screen latency, and garbage collection jitter, the SC-6 quiz engine runs bare-metal on dedicated silicon. Display states update within 4 ms, and the 400 g snap-dome key switches provide unambiguous tactile and auditory confirmation with every entry.

Mental Math & Number Sense Fluency: Level 6 drills rapid-fire mental math shortcuts—multiplying multi-digit integers by 11, squaring numbers ending in 5 via Vedic algebraic identities ($n5^2 = n(n+1) \times 100 + 25$), summing arithmetic series, and computing benchmark percentages. The strict 2.0 second speed window develops the automaticity and number-sense agility required for advanced STEM problem solving.

For Parents & Teachers: Classroom Dialogue Scripts & Misconception Diagnostics

Script 8.1: Why Guessing Destroys Your Score:

Teacher: "Marcus, I noticed that on your 2-minute Level 3 sprint, you attempted 40 questions, but your final score was only 30 points. What happened?"

Student (Marcus): "I was trying to go super fast so I could get the +20 bonus points on every single problem! So when I saw 8×7, I guessed 54, and when I saw 9×6, I guessed 56."

Teacher: "Let's look at the math behind the scoring rules, Marcus. When you guess wrong, what happens?"

Marcus: "You lose 10 points."

Teacher: "And what happens to your streak?"

Marcus: "It drops all the way back to zero."

Teacher: "Right! So if you guess on three problems in a row and get them wrong, you lose -30 points! Now imagine you slow down by just one second: you take 2.2 seconds to think: '7 times 8 is 56'. You type 56. What do you get?"

Marcus: "+20 points and my streak goes up!"

Teacher: "Exactly! Ten accurate answers in two minutes gives you $10 \times 20 = 200$ points, plus streak bonuses! Guessing 40 times gave you 30 points. Accuracy is the true secret of speed!"

Marcus: "Slow is smooth, and smooth is fast!"

Script 8.2: The Mystery of Multiplying by 11:

Student (Hannah): "Teacher, how did Daniel solve $53 \times 11 = 583$ in less than one second on the Level 6 sprint? Is he a human computer?"

Teacher: "Daniel used the 11s shortcut! Watch: write the number 53 on your whiteboard with a little space between the digits: `5 _ 3`."

Hannah: "Okay, 5 on the left, 3 on the right."

Teacher: "Now add the two digits together: what is $5 + 3$?"

Hannah: "8!"

Teacher: "Put the 8 right in the middle! What number do you have?"

Hannah (eyes wide): "583! No way! Does that work for every two-digit number?"

Teacher: "Try 42×11!"

Hannah: "4 on the left, 2 on the right, $4 + 2 = 6$ in the middle... 462! Wow!"

Teacher: "What if the middle sum is 10 or greater, like 75×11?"

Hannah: "$7 + 5 = 12$! So 2 goes in the middle, and we carry the 1 to the 7... making it 825!"

Teacher: "Brilliant! Now test it on your SC-6: `10 [ENTER] 7 [-]`!"

Hannah: "825! That's how Daniel answered in one second!"

Script 8.3: Fraction Addition vs Whole Number Addition:

Student (Noah): "Teacher, in Level 4, the screen asked 1/3 + 1/4 = ?. I typed 2/7 and pressed **[ENTER]**, but the calculator flashed `▯ TRY AGAIN`! 1 plus 1 is 2, and 3 plus 4 is 7!"

Teacher: "Noah, grab our Fraction Studio towers. Take a 1/3 tower and a 1/4 tower and stack them together."

Noah: "Okay, they make a tall tower."

Teacher: "If someone guesses 1/3 + 1/4 = 2/7, test that against two 1/8 pieces in the bin—even two 1/6 pieces (28 mm) barely match the 1/3 piece alone, and 2/7 is even smaller!"

Noah: "No way! Two-sevenths would be way shorter than our 1/3 plus 1/4 tower!"

Teacher: "Exactly! You cannot add denominators because fractions are parts of a whole! To combine thirds and fourths, what size blocks fit both?"

Noah: "Twelfths! One-third is 4 twelfths, and one-fourth is 3 twelfths!"

Teacher: "And 4/12 + 3/12 equals...?"

Noah: "7 twelfths! 7/12!"

Teacher: "Now type `[.] 7 [.] 1 2` on your SC-6 and tap **[ENTER]**!"

Noah: "It flashed `▯ NICE! +20 POINTS`! The blocks prove the fraction!"

Misconception Diagnostic Table

| Observable Error | Cognitive Root Cause | Targeted Remediation Prompt |

| :--- | :--- | :--- |

| **Adding denominators in Level 4: (2 / 5) + (1 / 5) = (3 / 10)** | Treating fractions as two disconnected whole numbers rather than equal fractional parts. | *"Look at the fraction tower manipulative. If you have 2 fifths and add 1 fifth, you have 3 fifths ((3 / 5)). The denominator tells you the size of the pieces; it never changes when adding like slices!"* |

| **Forgetting to carry in the 11s shortcut: 68 × 11 = 6148** | Inserting the full sum 6 + 8 = 14 into the center without regrouping the tens digit. | *"The center slot can only hold a single digit! Put the 4 in the middle, and carry the 1 over to the 6: 6 + 1 = 7, yielding 748!"* |

| **Squaring numbers ending in 5: $35^2 = 3025$** | Multiplying the tens digit by itself (3 × 3 = 9) instead of the next integer (3 × 4 = 12). | *"Remember the rule: multiply the tens digit by the NEXT whole number! 3 × 4 = 12, then append 25 to get 1,225!"* |

| **Order of operations violation: 24 ÷ 6 + 7 = 24 ÷ 13** | Reading left-to-right and adding before dividing. | *"Division and multiplication always happen before addition and subtraction! First compute 24 ÷ 6 = 4. Then add 4 + 7 = 11."* |

| **Sign confusion: -15 + 8 = -23** | Adding absolute values instead of moving toward zero on the number line. | *"You are at -15 in the basement. Going up +8 floors moves you CLOSER to ground level: you end at Floor -7!"* |

| **Remainder as decimal: 17 ÷ 5 → 3.2 instead of Q=3, R=2** | Confusing base-10 tenths with fractional parts (2/5 = 0.4, not 0.2). | *"In whole number division with remainder, 17 ÷ 5 gives 3 groups of 5 with 2 left over. On the SC-6, use* **[g] [÷R]** *to see quotient 3 and remainder 2 separated!"* |

| **Doubles error: 7 + 8 → 16** | Misapplying double of the upper addend (8 + 8 = 16) instead of double plus one (7 + 7 + 1 = 15). | *"Think of 8 as 7 + 1. Double 7 is 14, plus 1 is 15! Double plus one always gives an odd sum."* |

| **Percentage of number: 10% of 250 = 2500** | Multiplying by 10 instead of dividing by 10 (or moving decimal wrong way). | *"Ten percent means ten out of one hundred—one tenth! To take one tenth of 250, shift the decimal point ONE space to the LEFT: 25.0!"* |

8.7 Mental Math & Number Sense Fluency: 8 Essential Mental Math Theorems

In competitive STEM sprints and timed mental math assessments, you can solve complex arithmetic questions rapidly without scratch paper! The following eight mental math theorems form the bedrock of elite mental calculation:

8.7.1 Theorem 1: Multiplying Numbers with Equal Tens and Units Adding to 10

If two numbers have the identical tens digit t and their units digits $u_1 + u_2 = 10$, their product is: **$(10t + u_1)(10t + u_2) = 100 \times t(t + 1) + (u_1 \times u_2)$** *Example:* 43×47:

- Tens part: $4 \times (4 + 1) = 4 \times 5 = 20$.
- Units part: $3 \times 7 = 21$.
- Combined: **2,021**!

> **RPN Stack Verification:**
> 43 **[ENTER]** 47 **[×]** → 2021.00

8.7.2 Theorem 2: Mental Multiplication by 25

Multiplying by 25 is mathematically equivalent to dividing by 4 and multiplying by 100: **$N \times 25 = (N / 4) \times 100$** *Example:* 36×25:

- Divide 36 by 4: $36 \div 4 = 9$.
- Multiply by 100: **900**!

> **RPN Stack Verification:**
> 36 **[ENTER]** 25 **[×]** → 900.00

8.7.3 Theorem 3: Squaring Numbers Near 50

For any number $N = 50 + d$: **$N^2 = (50 + d)^2 = 2500 + 100d + d^2 = 100(25 + d) + d^2$** *Example:* 54^2 ($d = +4$):

- First two digits: $25 + 4 = 29$.
- Last two digits: $4^2 = 16$.
- Combined: **2,916**!

> **RPN Stack Verification:**
> 54 **[x²]** → 2916.00

8.7.4 Theorem 4: Difference of Squares for Symmetrical Multiplication

If two numbers are symmetrically spaced around an even tens or hundreds value: **$(A - d)(A + d) = A^2 - d^2$** *Example:* 28×32 (center $A = 30$, distance $d = 2$):

- $30^2 - 2^2 = 900 - 4 =$ **896**!

> **RPN Stack Verification:**

28 [ENTER] 32 [×] → 896.00

8.7.5 Theorem 5: Sum of the First n Consecutive Integers

$S_n = \sum_{k=1}^{n} k = 1 + 2 + 3 + ... + n = (n(n + 1) / 2)$ *Example:* Sum of numbers from 1 to 20:

- $20 \times 21 \div 2 = 10 \times 21 =$ **210**!

RPN Stack Verification:
20 [ENTER] 21 [×] [2] [÷] → 210.00

8.7.6 Theorem 6: Sum of the First n Consecutive Odd Integers

$S_{odd} = 1 + 3 + 5 + ... + (2n - 1) = n^2$ *Example:* Sum of the first 12 odd numbers ($1 + 3 + ... + 23$):

- $12^2 =$ **144**!

RPN Stack Verification:
12 [x²] → 144.00

8.7.7 Theorem 7: Rapid Conversion of Repeating Decimals to Fractions

A repeating single-digit decimal $0.d\ d\ d... = (d / 9)$. A repeating two-digit block $0.ab\ ab\ ab... = (ab / 99)$. *Example:* Convert $0.363636...$ to simplest fraction:

- Fraction is $36/99$.
- Simplify dividing numerator and denominator by 9: $(36 \div 9 / 99 \div 9) = (4 / 11)$.

RPN Stack Verification:
[.] 36 [.] 99 [g] [SIMP] → 4/11

8.7.8 Theorem 8: Divisibility Rule for 11 via Alternating Sum

A number is divisible by 11 if and only if the alternating sum of its digits (from right to left) is a multiple of 11: **$S_{alt} = (d_0 + d_2 + d_4) - (d_1 + d_3 + ...) \equiv 0 \pmod{11}$** *Example:* Test 8,426:

- Odd positions: $6 + 4 = 10$.
- Even positions: $2 + 8 = 10$.
- Difference: $10 - 10 = 0$ (multiple of 11) $\Rightarrow$ 8,426 is divisible by 11 ($8426 \div 11 = 766$)!

RPN Stack Verification:
8426 [ENTER] 11 [g] [÷R] → X = 766 (Quotient), Y = 0 (Remainder 0!)

For Parents & Teachers: Standards Alignment Matrix

| Quiz Level | Common Core (CCSS-M) | Texas TEKS | Singapore Dimensions Math | Bridges in Mathematics |

| :--- | :--- | :--- | :--- | :--- |

| **Level 1 (Facts to 10)** | 1.OA.C.6, K.OA.A.3 | 1.3D, 1.3E | Grade 1 Chapters 2 & 4 | Unit 1 Module 3 |

| **Level 2 (Mental to 100)** | 2.OA.B.2, 2.NBT.B.5 | 2.4A, 2.4B | Grade 2 Chapter 3 | Unit 2 Module 2 |

| **Level 3 (Times Tables)** | 3.OA.C.7, 3.OA.B.5 | 3.4D, 3.4E | Grade 3 Chapters 6–8 | Unit 3 Module 1 |

| **Level 4 (Fractions & ÷R)** | 4.OA.A.3, 4.NF.B.3 | 4.4F, 4.3E | Grade 4 Chapters 3 & 7 | Unit 4 Module 3 |

| **Level 5 (Mixed Operations)**| 5.OA.A.1, 5.NF.A.1 | 5.4F, 5.3K | Grade 5 Chapters 1 & 3 | Unit 5 Module 1 |

| **Level 6 (Pre-Algebra / Sprints)**| 6.NS.B.4, 6.NS.C.5 | 6.2C, 6.7A | Grade 6 Chapters 1 & 2 | Unit 6 Module 2 |

For official competition prep rules, timing charts, and station tracking sheets, consult Exam Compliance & Assessment Guide .

8.8 Comprehensive Problem Bank: 48 Worked Quiz Drills with Full 4-Register Stack Traces

The following problem bank provides complete reference Flight Simulator walkthroughs across all six astronaut training levels, connecting your mental math trick with physical blocks (`Ten-Frames`, `Math Dominoes`, `Counting Tile Arrays`, `Fraction Towers`, and `Prime Blocks`), the quiz screen prompt, what you tap on the keys, target latency, and complete 4-register (T, Z, Y, X) stack verification tables.

Hands-On Studio Proof: Blocks → Calculator

Before executing high-speed mental sprints on the SC-6 keypad, you ground abstract arithmetic facts in tactile reality:

1. **Domino Pairing & Seeing Groups at a Glance (Levels 1–2):** Use the **Math Dominoes Studio**. Draw a double-six domino (e.g., 4 + 5). Instantly recognize the dot patterns to spot the near-double (4 + 4 + 1 = 9). Key in **`[9] [ENTER]`** on the SC-6 within 2.0 seconds to earn the speed chime.

2. **Rectangular Array Muscle Memory (Levels 3–4):** Model small with your **24-Tile Counting & Array Studio**, then scale up! For 7 × 8, build a 2 × 8 = 16 tile rectangle with your kit and add the 5 × 8 = 40 benchmark mentally (40 + 16 = 56). When the SC-6 prompts `7 [f] [?] × = 56`, your fingers tap **`[8] [ENTER]`** without hesitation.

3. **Proportional Fraction Towers (Levels 4–5):** Compare a (1 / 2) tower against two (1 / 4) towers on the twin comparator well. When faced with (1 / 2) + (1 / 4), the visual height of (3 / 4) is already etched into spatial memory.

4. **Vedic Shortcuts & Algebraic Sprints (Level 6):** Mentally multiply 35^2 = (3 × 4) hundred + 25 = 1,225 using the spatial Vedic squaring rule, verifying instantly with `6 [ENTER] 3 [+]`.

8.8.1 Mission 1: Flight Simulator Liftoff (Levels 1 & 2: Number Bonds & Whole Number Addition/Subtraction)

Mission Briefing: Strap into the simulator cockpit. Build automatic number bonds to 10 and rapid mental addition and subtraction to 100 without paper or finger counting.

8.8.2 Level 1: Single-Digit Number Bonds (Sums & Differences to 10)

Drill 1 (Level 1): 4 + 5 = ?

Use **Math Dominoes**. Draw a [4 | 5] domino: you can instantly spot the near-double! The twin 4-dot groups match up (4 + 4 = 8), leaving just 1 extra dot to make 8 + 1 = 9. When the Flight Simulator screen flashes the RPN stack puzzle `4`

`[ENTER] 5 [+] ?` (mental prompt `4 + 5 = ?`), tap 9 **[ENTER]** on the keypad (target sprint time: < 2.0 seconds).

To verify the full operation on the stack, key in `4 [ENTER] 5 [+]` → `9 (T=0, Z=0, Y=0, X=9)`. Pushing `4` onto Floor Y and adding `5` on Floor X merges both domino halves into `9`!

Drill 2 (Level 1): 10 - 7 = ?

Use your **Ten-Frame Tray**. The tray holds 10 counters in two rows of 5. When you cover or remove 7 counters (a full row of 5 plus 2 more), exactly 3 empty spaces remain (10 - 7 = 3, because 7 + 3 = 10). As the Flight Simulator display presents the stack challenge `10 [ENTER] 7 [-] ?` (or Missing-Value Puzzle `10 [f] [?] -`) (mental prompt `10 - 7 = ?`), tap 3 **[ENTER]** on the keypad (target sprint time: < 2.0 seconds).

To confirm the complete calculation on your SC-6, enter `10 [ENTER] 7 [-]` → `3 (T=0, Z=0, Y=0, X=3)`. Starting with a full `10` in Register Y and taking away `7` in Register X leaves the partner bond `3`.

Drill 3 (Level 1): 6 + 3 = ?

Use **Math Dominoes** or a **Ten-Frame Tray**. Start with the larger benchmark group of 6 (a full row of 5 plus 1 dot), then count on 3 quick astronaut hops: 7, 8, 9 (6 + 3 = 9). Once the cockpit screen prompts with the RPN puzzle `6 [ENTER] 3 [+] ?` (mental prompt `6 + 3 = ?`), tap 9 **[ENTER]** on the keypad (target sprint time: < 2.0 seconds).

Replay the full RPN sequence on the stack with `6 [ENTER] 3 [+]` → `9 (T=0, Z=0, Y=0, X=9)`. Watch `6` lift to Floor Y on **[ENTER]** before **[+]** drops it onto `3` to land on `9`.

Drill 4 (Level 1): 8 - 0 = ?

In your **Ten-Frame Tray**, set out 8 counters (5 on top, 3 on bottom). Subtracting zero means taking away zero blocks—all 8 counters stay locked in position (8 - 0 = 8). When the simulator console lights up with `8 [ENTER] 0 [-] ?` (mental prompt `8 - 0 = ?`), tap 8 **[ENTER]** on the keypad (target sprint time: < 1.0 seconds).

Check the complete arithmetic flow on your SC-6 by keying `8 [ENTER] 0 [-]` → `8 (T=0, Z=0, Y=0, X=8)`. Subtracting `0` in Register X leaves `8` completely unchanged!

Drill 5 (Level 1): 3 + 7 = ?

Look at your **Ten-Frame Tray**. Place 3 blue counters in the first row. The 7 empty pockets show its exact 10-partner—together they fill all 10 pockets of the tray (3 + 7 = 10). As soon as the Flight Simulator flashes `3 [ENTER] 7 [+] ?` (or Missing-Value Puzzle `3 [f] [?] +`) (mental prompt `3 + 7 = ?`), tap 10 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

To watch the registers update step by step, enter `3 [ENTER] 7 [+]` → `10 (T=0, Z=0, Y=0, X=10)`. Just like Drill 2 in reverse, `3` and `7` snap together on the stack to form a complete `10`.

Drill 6 (Level 1): 9 - 5 = ?

Use your **Ten-Frame Tray**. A group of 9 fills the top row of 5 plus 4 on the bottom row. When you lift off the full top row of 5, the 4 bottom counters remain (9 - 5 = 4). When your SC-6 quiz display challenges you with `9 [ENTER] 5 [-] ?` (mental prompt `9 - 5 = ?`), tap 4 **[ENTER]** on the keypad (target sprint time: < 1.8 seconds).

Verify the stack mechanics directly by keying in `9 [ENTER] 5 [-]` → `4 (T=0, Z=0, Y=0, X=4)`. Taking the benchmark `5` away from `9` in Register Y drops the difference `4` into Register X.

Drill 7 (Level 1): 4 + 4 = ?

Grab the [4 | 4] tile from your **Math Dominoes** set. Both halves show identical 2 × 2 square clusters (4 + 4 = 8); doubling 4 clicks together like twin booster rockets! On the simulator screen, when you spot the RPN prompt `4 [ENTER] 4 [+] ?` (mental prompt `4 + 4 = ?`), tap 8 **[ENTER]** on the keypad (target sprint time: < 1.0 seconds).

Run the full verification sequence on your SC-6: `4 [ENTER] 4 [+]` → `8 (T=0, Z=0, Y=0, X=8)`. Pro Tip: Because **[ENTER]** copies `4` into both Y and X, you can even test `4 [ENTER]` **[+]** to double a number in three taps!

Drill 8 (Level 1): 10 - 2 = ?

Start with a full 10 in your **Ten-Frame Tray**. Pop out the 2 end counters from the bottom row: you see a full row of 5 plus 3 on the bottom, giving 8 counters (10 - 2 = 8). When the Flight Simulator mission clock starts on `10 [ENTER] 2 [-] ?` (or Missing-Value Puzzle `10 [f] [?] -`) (mental prompt `10 - 2 = ?`), tap 8 **[ENTER]** on the keypad (target sprint time: < 1.2 seconds).

Test the complete RPN operation on the stack: `10 [ENTER] 2 [-]` → `8 (T=0, Z=0, Y=0, X=8)`. Counting back 2 from 10 on the stack lands cleanly on `8`.

8.8.3 Level 2: Two-Digit Mental Addition & Subtraction (To 100)

Drill 9 (Level 2): 40 + 30 = ?

Place 4 counters and 3 counters in your **Ten-Frame Tray** to see 4 + 3 = 7. Now imagine each counter is worth 10: 4 tens + 3 tens = 7 tens = 70! When the Flight Simulator screen flashes the RPN stack puzzle `40 [ENTER] 30 [+] ?` (mental prompt `40 + 30 = ?`), tap 70 **[ENTER]** on the keypad (target sprint time: < 2.5 seconds).

To verify the full operation on the stack, key in `40 [ENTER] 30 [+]` → `70 (T=0, Z=0, Y=0, X=70)`. Adding tens on the stack works just like adding ones, with a zero in the ones place.

Drill 10 (Level 2): 80 - 25 = ?

Use 8 counters in your **Ten-Frame Tray** to stand for 8 tens (80). Take away 2 tens to drop to 60 (80 - 20 = 60), then trade 1 ten for a full 10-frame of ones and take away 5 to land on 55 (60 - 5 = 55). As the Flight Simulator display presents the stack challenge `80 [ENTER] 25 [-] ?` (or Missing-Value Puzzle `80 [f] [?] -`) (mental prompt `80 - 25 = ?`), tap 55 **[ENTER]** on the keypad (target sprint time: < 3.0 seconds).

To confirm the complete calculation on your SC-6, enter `80 [ENTER] 25 [-]` → `55 (T=0, Z=0, Y=0, X=55)`. Subtracting in two mental jumps (80 → 60 → 55) matches the stack result `55` with zero paper borrowing.

Drill 11 (Level 2): 34 + 12 = ?

Use your two **Ten-Frame Trays**: in the left tray, model the tens (3 + 1 = 4 tens = 40); in the right tray, model the ones (4 + 2 = 6 ones). Put them together for 46! Once the cockpit screen prompts with the RPN puzzle `34 [ENTER] 12 [+] ?` (mental prompt `34 + 12 = ?`), tap 46 **[ENTER]** on the keypad (target sprint time: < 2.5 seconds).

Replay the full RPN sequence on the stack with `34 [ENTER] 12 [+]` → `46 (T=0, Z=0, Y=0, X=46)`. Both tens and ones add without regrouping, landing on `46` in Register X.

Drill 12 (Level 2): 67 - 25 = ?

Use your two **Ten-Frame Trays** as a Tens Tray and a Ones Tray: subtract the tens (6 - 2 = 4 tens = 40) and subtract the ones (7 - 5 = 2 ones) to get 42. When the simulator console lights up with `67 [ENTER] 25 [-] ?` (mental prompt `67 - 25 = ?`), tap 42 **[ENTER]** on the keypad (target sprint time: < 2.8 seconds).

Check the complete arithmetic flow on your SC-6 by keying `67 [ENTER] 25 [-]` → `42 (T=0, Z=0, Y=0, X=42)`. Keeping `67` in Register Y and subtracting `25` in Register X confirms `42`.

Drill 13 (Level 2): 47 + 38 = ?

Use the **Make-a-Round-Number Trick** with your **Ten-Frame Trays**! Notice that 38 is just 2 shy of 40 (a nearly full 10-frame with 8 counters). Add 40 to 47 first (47 + 40 = 87), then step back 2 counters to land on 85! As soon as the Flight Simulator flashes `47 [ENTER] 38 [+] ?` (mental prompt `47 + 38 = ?`), tap 85 **[ENTER]** on the keypad (target sprint time: < 3.5 seconds).

To watch the registers update step by step, enter `47 [ENTER] 38 [+]` → `85 (T=0, Z=0, Y=0, X=85)`. Or see how the ones regroup: 7 + 8 = 15 (1 ten and 5 ones) plus 40 + 30 = 70 gives `85`!

Drill 14 (Level 2): 72 - 45 = ?

Count Up to Subtract! Use your **Ten-Frame Trays** to bridge the gap from 45 to 72: add 5 counters to 45 to reach the friendly multiple of ten (50), then add 22 more (2 tens + 2 ones) to reach 72. Your total jump is 5 + 22 = 27! When your SC-6 quiz display challenges you with `72 [ENTER] 45 [-] ?` (or Missing-Value Puzzle `72 [f] [?] -`) (mental prompt `72 - 45 = ?`), tap 27 **[ENTER]** on the keypad (target sprint time: < 3.5 seconds).

Verify the stack mechanics directly by keying in `72 [ENTER] 45 [-]` → `27 (T=0, Z=0, Y=0, X=27)`. Counting up from the bottom number to the top number turns hard borrowing into easy addition!

Drill 15 (Level 2): 56 + 19 = ?

Model 19 on your **20-Counter Ten-Frame Pair**—it fills all 20 pockets except 1! Add 20 to 56 first (56 + 20 = 76), then take back that 1 empty pocket (76 - 1 = 75). On the simulator screen, when you spot the RPN prompt `56 [ENTER] 19 [+] ?` (mental prompt `56 + 19 = ?`), tap 75 **[ENTER]** on the keypad (target sprint time: < 2.8 seconds).

Run the full verification sequence on your SC-6: `56 [ENTER] 19 [+]` → `75 (T=0, Z=0, Y=0, X=75)`. Anytime you add 19, 29, or 39, jump up by the next ten and step back 1!

Drill 16 (Level 2): 91 - 38 = ?

Use **Overshoot & Give Back**! Since 38 is 2 less than 40, subtract 40 from 91 first (91 - 40 = 51). Because you took away 2 too many, pop 2 counters back into your **Ten-Frame Tray** to finish at 51 + 2 = 53! When the Flight Simulator mission clock starts on `91 [ENTER] 38 [-] ?` (mental prompt `91 - 38 = ?`), tap 53 **[ENTER]** on the keypad (target sprint time: < 3.5 seconds).

Test the complete RPN operation on the stack: `91 [ENTER] 38 [-]` → `53 (T=0, Z=0, Y=0, X=53)`. Overshooting by 40 and giving back 2 beats crossing out digits every time.

8.8.4 Mission 2: Orbital Maneuvers (Levels 3 & 4: Times Tables, Remainders & Fractions)

Mission Briefing: Ascend into orbital flight! Master rectangular array multiplication, inverse division facts, integer remainders (`[g] [÷R]`), and proportional fraction towers under timed flight-deck conditions.

8.8.5 Level 3: Multiplication & Division Mastery (Up to 12 × 12)

Drill 17 (Level 3): 7 × 8 = ?

Split 7 rows of 8 into (5 × 8) + (2 × 8). Build the 2 × 8 = 16 rectangle using 16 of your **24 Array Tiles**, then add the easy five-times fact 5 × 8 = 40 in your head: 40 + 16 = 56! When the Flight Simulator screen flashes the RPN stack puzzle `7 [ENTER] 8 [×] ?` (or Missing-Value Puzzle `7 [f] [?] ×`) (mental prompt `7 × 8 = ?`), tap 56 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

To verify the full operation on the stack, key in `7 [ENTER] 8 [×]` → `56 (T=0, Z=0, Y=0, X=56)`. Bonus memory hook: write consecutive digits 5, 6, 7, 8 ⇒ 56 = 7 × 8!

Drill 18 (Level 3): 72 ÷ 9 = ?

Test the 9s pattern with 18 of your **24 Array Tiles** (2 × 9 = 18, notice the digits 1 + 8 = 9 and the tens digit is 2 - 1 = 1). For 72, the tens digit is 7, and 7 + 1 = 8 rows of 9 (8 × 9 = 72 ⇒ 72 ÷ 9 = 8)! As the Flight Simulator display presents the stack challenge `72 [ENTER] 9 [÷] ?` (mental prompt `72 ÷ 9 = ?`), tap 8 **[ENTER]** on the keypad (target sprint time: < 1.8 seconds).

To confirm the complete calculation on your SC-6, enter `72 [ENTER] 9 [÷]` → `8 (T=0, Z=0, Y=0, X=8)`. Dividing `72` in Register Y by `9` in Register X reveals the missing factor `8`.

Drill 19 (Level 3): 6 × 9 = ?

Use your **Ten-Frame Tray** to see the **"10 Minus 1" Rule**! Nine is 10 - 1, so 6 groups of 9 is 6 groups of 10 (60) minus 6 single counters (60 - 6 = 54). Once the cockpit screen prompts with the RPN puzzle `6 [ENTER] 9 [×] ?` (mental prompt `6 × 9 = ?`), tap 54 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

Replay the full RPN sequence on the stack with `6 [ENTER] 9 [×]` → `54 (T=0, Z=0, Y=0, X=54)`. Notice that in `54`, the tens digit is 6 - 1 = 5 and the digits add up to 5 + 4 = 9!

Drill 20 (Level 3): 48 ÷ 6 = ?

Model Half with Your Kit → Double It! Take all **24 Array Tiles** from your kit and arrange them into 6 equal rows: you get 6 rows of 4 (24 ÷ 6 = 4). Since 48 is double 24, double the row length from 4 to 8 (48 ÷ 6 = 8)! When the simulator console lights up with `48 [ENTER] 6 [÷] ?` (or Missing-Value Puzzle `48 [f] [?] ÷`) (mental prompt `48 ÷ 6 = ?`), tap 8 **[ENTER]** on the keypad (target sprint time: < 1.8 seconds).

Check the complete arithmetic flow on your SC-6 by keying `48 [ENTER] 6 [÷]` → `8 (T=0, Z=0, Y=0, X=8)`. Halving 48 to 24 turns a big division fact into one you can build right on your desk.

Drill 21 (Level 3): 12 × 7 = ?

Split 12 into 10 + 2! Use 14 of your **24 Array Tiles** to build the 2 × 7 = 14 rectangle on your desk, then add the easy 10 × 7 = 70 mental block: 70 + 14 = 84! As soon as the Flight Simulator flashes `12 [ENTER] 7 [×] ?` (mental prompt `12 × 7 = ?`), tap 84 **[ENTER]** on the keypad (target sprint time: < 2.2 seconds).

To watch the registers update step by step, enter `12 [ENTER] 7 [×]` → `84 (T=0, Z=0, Y=0, X=84)`. Every 12 × N fact is just 10N + 2N!

Drill 22 (Level 3): 9 × 9 = ?

Use your **Ten-Frame Tray** to picture 9 groups of 10 (90) and pull off 1 counter from each of the 9 groups (90 - 9 = 81). When your SC-6 quiz display challenges you with `9 [ENTER] 9 [×] ?` (mental prompt `9 × 9 = ?`), tap 81 **[ENTER]** on the keypad (target sprint time: < 1.2 seconds).

Verify the stack mechanics directly by keying in `9 [ENTER] 9 [×]` → `81 (T=0, Z=0, Y=0, X=81)`. Or press `9 [x²]` in **[NUM]** mode to square 9 in a single operation!

Drill 23 (Level 3): 84 ÷ 12 = ?

Take all **24 Array Tiles** and group them into dozens (24 ÷ 12 = 2 dozens). Now scale up to 84: since 70 + 14 = 84, it takes 7 dozens to make 84 (84 ÷ 12 = 7). On the simulator screen, when you spot the RPN prompt `84 [ENTER] 12 [÷] ?` (or Missing-Value Puzzle `84 [f] [?] ÷`) (mental prompt `84 ÷ 12 = ?`), tap 7 **[ENTER]** on the keypad (target sprint time: < 2.0 seconds).

Run the full verification sequence on your SC-6: `84 [ENTER] 12 [÷]` → `7 (T=0, Z=0, Y=0, X=7)`. Recognizing 84 from Drill 21 (12 × 7 = 84) gives you the inverse division fact for free!

Drill 24 (Level 3): 11 × 11 = ?

Use the **11s Split Trick**! Model 2 × 11 = 22 with 22 of your **24 Array Tiles**. For 11 × 11, split the digits `1` and `1` apart and put their sum (1 + 1 = 2) right in the middle: `121`! When the Flight Simulator mission clock starts on `11 [ENTER] 11 [×] ?` (mental prompt `11 × 11 = ?`), tap 121 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

Test the complete RPN operation on the stack: `11 [ENTER] 11 [×]` → `121 (T=0, Z=0, Y=0, X=121)`. 10 × 11 = 110, plus one more 11 equals `121`!

8.8.6 Level 4: Remainder Division & Fraction Benchmarks

Drill 25 (Level 4): 17 ÷ 5 → Q=?, R=?

Take 17 tiles from your **24-Tile Counting & Array Studio** and stack them into columns of 5. You build 3 complete 5-towers (15 tiles), with 2 leftover tiles resting in your hand (Q=3, R=2). When the Flight Simulator screen flashes the RPN stack puzzle `17 [ENTER] 5 [g] [÷R] ?` (mental prompt `17 ÷ 5 = Q=?, R=?`), tap 3 **[ENTER]** on the keypad (target sprint time: < 3.5 seconds). To verify the full operation on the stack, key in `17 [ENTER] 5 [g] [÷R]` → `3`.

Keystroke	Register T	Register Z	Register Y	Register X
17	0	0	0	17
[ENTER]	0	0	17	17
[5]	0	0	17	5
[g] **[÷R]**	0	0	2	3

(Register X holds quotient 3, Register Y holds remainder 2; tap **[x⇔y]** *to inspect remainder).*

Drill 26 (Level 4): 1/2 + 1/4 = ?

Slide your **Fraction Towers** into the twin comparator well. A single 1/2 tower aligns at the exact same height as two 1/4 pieces (2/4). Adding one more 1/4 piece builds a 3/4 tower (2/4 + 1/4 = 3/4). As the Flight Simulator display presents the stack challenge `1/2 [ENTER] 1/4 [+] ?` (mental prompt `1/2 + 1/4 = ?`), tap **[.]** 3 **[.]** 4 **[ENTER]** on the keypad (target sprint time: < 3.0 seconds). To confirm the complete calculation on your SC-6, enter `. 1 . 2 [ENTER] . 1 . 4 [+]` → `3/4`.

Keystroke	Register T	Register Z	Register Y	Register X
[.] 1 **[.]** 2	0	0	0	1/2
[ENTER]	0	0	1/2	1/2
[.] 1 **[.]** 4	0	0	1/2	1/4
[+]	0	0	0	3/4

Drill 27 (Level 4): 5/6 - 1/3 = ?

In your **Fraction Towers** studio, stand five 1/6 pieces (5/6) next to a 1/3 piece. The 1/3 piece matches two 1/6 blocks (2/6). Subtracting two 1/6 blocks from five leaves three 1/6 blocks (3/6), which matches the 1/2 tower! Once the cockpit screen prompts with the RPN puzzle `5/6 [ENTER] 1/3 [-] ?` (mental prompt `5/6 - 1/3 = ?`), tap **[.]** 1 **[.]** 2 **[ENTER]** on the keypad (target sprint time: < 3.5 seconds). Replay the full RPN sequence on the stack with `. 5 . 6 [ENTER] . 1 . 3 [-] [g] [SIMP]` → `1/2`.

Keystroke	Register T	Register Z	Register Y	Register X
[.] 5 **[.]** 6	0	0	0	5/6
[ENTER]	0	0	5/6	5/6
[.] 1 **[.]** 3	0	0	5/6	1/3
[-]	0	0	0	3/6
[g] **[SIMP]**	0	0	0	1/2

Drill 28 (Level 4): 2/3 + 1/4 = ?

Use the twelfths pieces in your **Fraction Towers** kit! Two 1/3 pieces match eight 1/12 pieces (8/12), and one 1/4 piece matches three 1/12 pieces (3/12). Stacking them together gives 8 + 3 = 11 twelfths (11/12). When the simulator console lights up with `2/3 [ENTER] 1/4 [+] ?` (mental prompt `2/3 + 1/4 = ?`), tap **[.]** 11 **[.]** 12 **[ENTER]** on the keypad (target sprint time: < 4.0 seconds). Check the complete arithmetic flow on your SC-6 by keying `. 2 . 3 [ENTER] . 1 . 4 [+]` → `11/12`.

Keystroke	Register T	Register Z	Register Y	Register X
[.] 2 **[.]** 3	0	0	0	2/3
[ENTER]	0	0	2/3	2/3
[.] 1 **[.]** 4	0	0	2/3	1/4
[+]	0	0	0	11/12

Drill 29 (Level 4): 3/4 - 2/5 = ?

Compare three 1/4 pieces (3/4) against two 1/5 pieces (2/5) in your **Fraction Towers** comparator well, then find their shared common denominator of 20: 3/4 = 15/20 and 2/5 = 8/20, so the height difference is 15/20 - 8/20 = 7/20. As soon as the Flight Simulator flashes `3/4 [ENTER] 2/5 [-] ?` (mental prompt `3/4 - 2/5 = ?`), tap **[.]** 7 **[.]** 20 **[ENTER]** on the keypad (target sprint time: < 4.5 seconds).

To watch the registers update step by step, enter `. 3 . 4 [ENTER] . 2 . 5 [-]` → `7/20 (T=0, Z=0, Y=0, X=7/20)`. Two-Dot entry (`[.] 3 [.] 4` and `[.] 2 [.] 5`) automatically finds the common denominator of 20 on the stack!

Drill 30 (Level 4): Simplify 18/24 → ?

Build two **Prime Factor Block** towers or group your **24 Array Tiles**: 18 is three groups of 6 (3 × 6), and 24 is four groups of 6 (4 × 6). Dividing both numerator and denominator by their Greatest Common Factor (gcd(18, 24) = 6) simplifies 18/24 to 3/4! When your SC-6 quiz display challenges you with `18/24 [g] [SIMP] ?` (mental prompt `Simplify 18/24 = ?`), tap **[.]** 3 **[.]** 4 **[ENTER]** on the keypad (target sprint time: < 3.0 seconds). Verify the stack mechanics directly by keying in `. 18 . 24 [ENTER] [g] [SIMP]` → `3/4`.

Keystroke	Register T	Register Z	Register Y	Register X
[.] 18 **[.]** 24	0	0	0	18/24
[ENTER]	0	0	18/24	18/24
[g] **[SIMP]**	0	0	18/24	3/4

Drill 31 (Level 4): 38 ÷ 6 → Q=?, R=?

Take 14 of your **24 Array Tiles** and make groups of 6 (2 full groups of 6 with 2 left over). Now scale up to 38: 6 full groups of 6 use 36 tiles and leave 2 tiles left over (Q=6, R=2). On the simulator screen, when you spot the RPN prompt `38 [ENTER] 6 [g] [÷R] ?` (mental prompt `38 ÷ 6 = Q=?, R=?`), tap 6 **[ENTER]** on the keypad (target sprint time: < 3.0 seconds).

Run the full verification sequence on your SC-6: `38 [ENTER] 6 [g] [÷R]` → `6 (T=0, Z=0, Y=2, X=6)`. **[g]** **[÷R]** puts the whole quotient `6` in Register X and the remainder `2` right above it in Register Y!

Drill 32 (Level 4): 5/8 + 1/2 = ?

In your **Fraction Towers** comparator well, a 1/2 tower matches four 1/8 pieces (4/8). Adding five 1/8 pieces makes nine 1/8 pieces (9/8), which stands 1 full whole tower tall plus 1 extra eighth (1 1/8). When the Flight Simulator mission clock starts on `5/8 [ENTER] 1/2 [+] ?` (mental prompt `5/8 + 1/2 = ?`), tap 1 **[.]** 1 **[.]** 8 **[ENTER]** on the keypad (target sprint time: < 4.0 seconds). Test the complete RPN operation on the stack: `. 5 . 8 [ENTER] . 1 . 2 [+]` → `1 1/8`.

Keystroke	Register T	Register Z	Register Y	Register X
[.] 5 **[.]** 8	0	0	0	5/8
[ENTER]	0	0	5/8	5/8
[.] 1 **[.]** 2	0	0	5/8	1/2
[+]	0	0	0	1 1/8

8.8.7 Mission 3: Deep-Space Sprint Master (Levels 5 & 6: Order of Operations & Vedic Shortcuts)

Mission Briefing: Engage deep-space warp drive! Combine multi-step order of operations, decimal-fraction benchmarks, and the 8 Essential Mental Math Theorems to solve pre-algebra sprints faster than an algebraic calculator.

8.8.8 Level 5: Multi-Step Order of Operations, Decimals & Percents

Drill 33 (Level 5): 24 ÷ 6 + 7 = ?

Use all **24 Array Tiles** from your kit! Division happens before addition: split 24 tiles into 6 equal rows of 4 tiles (24 ÷ 6 = 4), then add 7 counters from your **Ten-Frame Tray** to finish with 11 (4 + 7 = 11). When the Flight Simulator screen flashes the RPN stack puzzle `24 ÷ 6 + 7 = ?` (mental prompt `24 ÷ 6 + 7 = ?`), tap 11 **[ENTER]** on the keypad (target sprint time: < 2.5 seconds). To verify the full operation on the stack, key in `24 [ENTER] 6 [÷] 7 [+]` → `11`.

Keystroke	Register T	Register Z	Register Y	Register X
24	0	0	0	24
[ENTER]	0	0	24	24
[6]	0	0	24	6
[÷]	0	0	0	4
[7]	0	0	4	7
[+]	0	0	0	11

Drill 34 (Level 5): 0.25 × 80 = ?

Connect decimals to your **Fraction Towers**! The decimal 0.25 is stamped right on the 1/4 tower (0.25 = 1/4). Taking one fourth of 80 is just 80 ÷ 4 = 20! As the Flight Simulator display presents the stack challenge `0.25 [ENTER] 80 [×] ?` (mental prompt `0.25 × 80 = ?`), tap 20 **[ENTER]** on the keypad (target sprint time: < 2.0 seconds).

To confirm the complete calculation on your SC-6, enter `0.25 [ENTER] 80 [×]` → `20 (T=0, Z=0, Y=0, X=20)`. Multiplying by `0.25` is always the same as dividing by `4`.

Drill 35 (Level 5): 15 - 3 × 4 = ?

Set out 15 tiles from your **24 Array Tiles**. Order of operations means you multiply before you subtract: arrange 3 × 4 = 12 of those tiles into a rectangle and lift them away, leaving 15 - 12 = 3 tiles! Once the cockpit screen prompts with the RPN puzzle `15 - 3 × 4 = ?` (mental prompt `15 - 3 × 4 = ?`), tap 3 **[ENTER]** on the keypad (target sprint time: < 2.5 seconds). Replay the full RPN sequence on the stack with `15 [ENTER] 3 [ENTER] 4 [×] [-]` → `3`.

Keystroke	Register T	Register Z	Register Y	Register X
15	0	0	0	15
[ENTER]	0	0	15	15
[3]	0	0	15	3
[ENTER]	0	15	3	3
[4]	0	15	3	4
[×]	0	0	15	12
[-]	0	0	0	3

Drill 36 (Level 5): (18 - 6) ÷ 3 = ?

Handle the grouped tiles first! From 18 of your **24 Array Tiles**, remove 6 tiles to leave 12 tiles (18 - 6 = 12). Next, divide those 12 tiles into 3 equal rows: each row gets 4 tiles (12 ÷ 3 = 4). When the simulator console lights up with `(18 - 6) ÷ 3 = ?` (mental prompt `(18 - 6) ÷ 3 = ?`), tap 4 **[ENTER]** on the keypad (target sprint time: < 2.5 seconds). Check the complete arithmetic flow on your SC-6 by keying `18 [ENTER] 6 [-] 3 [÷]` → `4`.

Keystroke	Register T	Register Z	Register Y	Register X
18	0	0	0	18
[ENTER]	0	0	18	18
[6]	0	0	18	6
[-]	0	0	0	12
[3]	0	0	12	3
[÷]	0	0	0	4

Drill 37 (Level 5): 1 1/2 + 2 1/4 = ?

Stack your **Fraction Towers** in two steps: first add the whole numbers (1 + 2 = 3). Then check the fraction pieces in the comparator well: 1/2 equals 2/4, plus 1/4 gives 3/4, reaching a total height of 3 3/4! As soon as the Flight Simulator flashes `1 1/2 [ENTER] 2 1/4 [+] ?` (mental prompt `1 1/2 + 2 1/4 = ?`), tap 3 **[.]** 3 **[.]** 4 **[ENTER]** on the keypad (target sprint time: < 3.5 seconds). To watch the registers update step by step, enter `1 . 1 . 2 [ENTER] 2 . 1 . 4 [+]` → `3 3/4`.

Keystroke	Register T	Register Z	Register Y	Register X
[1] **[.]** 1 **[.]** 2	0	0	0	1 1/2
[ENTER]	0	0	1 1/2	1 1/2
[2] **[.]** 1 **[.]** 4	0	0	1 1/2	2 1/4
[+]	0	0	0	3 3/4

Drill 38 (Level 5): 0.5 × 48 = ?

Check the 1/2 piece in your **Fraction Towers** kit: 0.5 is one half! Splitting 48 in half (48 ÷ 2 = 24) leaves exactly 24—the full count of your **24 Array Tiles**! When your SC-6 quiz display challenges you with `0.5 [ENTER] 48 [×] ?` (mental prompt `0.5 × 48 = ?`), tap 24 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

Verify the stack mechanics directly by keying in `0.5 [ENTER] 48 [×]` → `24 (T=0, Z=0, Y=0, X=24)`. Multiplying any even number by `0.5` is as fast as cutting both digits in half (4 → 2, 8 → 4 ⇒ 24).

Drill 39 (Level 5): 10% of 250 = ?

Use your **Ten-Frame Tray** to see why 10% means 1 counter out of 10 ((1 / 10)). To find one tenth of 250, simply divide by 10 (shift the decimal point one place left): 250 ÷ 10 = 25! On the simulator screen, when you spot the RPN prompt `250 [ENTER] 10 [%] ?` (mental prompt `10% of 250 = ?`), tap 25 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

Run the full verification sequence on your SC-6: `250 [ENTER] 10 [%]` → `25 (T=0, Z=0, Y=250, X=25)`. Notice how **[%]** keeps the base `250` in Register Y while placing 10% (`25`) in Register X!

Drill 40 (Level 5): 8 + 4 × 5 = ?

Multiply before adding! Build a 4 × 5 = 20 rectangle using 20 of your **24 Array Tiles** (or fill both **Ten-Frame Trays**), then add 8 more counters to get 20 + 8 = 28! When the Flight Simulator mission clock starts on `8 + 4 × 5 = ?` (mental prompt `8 + 4 × 5 = ?`), tap 28 **[ENTER]** on the keypad (target sprint time: < 2.5 seconds). Test the complete RPN operation on the stack: `8 [ENTER] 4 [ENTER] 5 [×] [+]` → `28`.

Keystroke	Register T	Register Z	Register Y	Register X
[8]	0	0	0	8
[ENTER]	0	0	8	8
[4]	0	0	8	4
[ENTER]	0	8	4	4
[5]	0	8	4	5
[×]	0	0	8	20
[+]	0	0	0	28

8.8.9 Level 6: Pre-Algebra & Competitive Speed Sprints

Drill 41 (Level 6): 35^2 = ?

For any number ending in 5, multiply the tens digit 3 by the next whole number 4 using 12 of your **24 Array Tiles** (3 × 4 = 12 hundreds = 1,200), then snap on 5^2 = 25 at the end: 1,225! When the Flight Simulator screen flashes the RPN stack puzzle `35 [x²] ?` (mental prompt `35^2 = ?`), tap 1225 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

To verify the full operation on the stack, key in `35 [x²]` → `1225 (T=0, Z=0, Y=0, X=1225)`. The unary **[x²]** key squares `35` right inside Register X without even needing **[ENTER]**!

Drill 42 (Level 6): 43 × 11 = ?

Use the **11s Middle-Sum Shortcut**! Model 4 + 3 = 7 in your **Ten-Frame Tray**. Now spread the digits `4` and `3` apart and drop their sum `7` right into the middle tens place: `473`! As the Flight Simulator display presents the stack challenge `43 [ENTER] 11 [×] ?` (mental prompt `43 × 11 = ?`), tap 473 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

To confirm the complete calculation on your SC-6, enter `43 [ENTER] 11 [×]` → `473 (T=0, Z=0, Y=0, X=473)`. Why does it work? Because 43 × 10 = 430, and 430 + 43 = 473!

Drill 43 (Level 6): 65^2 = ?

Use the **Ends-in-5 Squaring Rule**! Multiply the tens digit 6 by the next integer 7 (6 × 7 = 42 hundreds = 4,200), then attach 5^2 = 25 to the last two digits: 4,225! Once the cockpit screen prompts with the RPN puzzle `65 [x²] ?` (mental prompt `65^2 = ?`), tap 4225 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

Replay the full RPN sequence on the stack with `65 [x²]` → `4225 (T=0, Z=0, Y=0, X=4225)`. Once you know 6 × 7 = 42, you can type `4225` faster than anyone using an algebraic calculator!

Drill 44 (Level 6): 75^2 = ?

Recall 7 × 8 = 56 from Drill 17! Multiply the tens digit 7 by the next integer 8 (56 hundreds = 5,600) and tack on 25: 5,625! When the simulator console lights up with `75 [x²] ?` (mental prompt `75^2 = ?`), tap 5625 **[ENTER]** on the keypad (target sprint time: < 1.5 seconds).

Check the complete arithmetic flow on your SC-6 by keying `75 [x²] → 5625 (T=0, Z=0, Y=0, X=5625)`. One tap of **[x²]** confirms your mental square `5625` in Register X.

Drill 45 (Level 6): 67 × 11 = ?

Use the **11s Shortcut with a Carry**! Model 6 + 7 = 13 across your two **Ten-Frame Trays** (1 full ten and 3 ones). Put the `3` in the middle tens slot and carry the `1` ten-frame over to the hundreds digit (6 + 1 = 7), giving `737`! As soon as the Flight Simulator flashes `67 [ENTER] 11 [×] ?` (mental prompt `67 × 11 = ?`), tap 737 **[ENTER]** on the keypad (target sprint time: < 1.8 seconds).

To watch the registers update step by step, enter `67 [ENTER] 11 [×] → 737 (T=0, Z=0, Y=0, X=737)`. Whenever the two digits add to 10 or more, carry 1 to the left digit!

Drill 46 (Level 6): 15% of 80 = ?

Split 15% into 10% + 5% using your **Ten-Frame Tray**! 10% of 80 is 8 counters, and 5% is half of that (4 counters). Add them together in your tray: 8 + 4 = 12! When your SC-6 quiz display challenges you with `80 [ENTER] 15 [%] ?` (mental prompt `15% of 80 = ?`), tap 12 **[ENTER]** on the keypad (target sprint time: < 1.8 seconds).

Verify the stack mechanics directly by keying in `80 [ENTER] 15 [%] → 12 (T=0, Z=0, Y=80, X=12)`. Because `80` stays in Register Y and `12` lands in Register X, pressing **[+]** next would even give you 80 + 15% = 92!

Drill 47 (Level 6): -14 + 9 = ?

Use your two **Ten-Frame Trays** for **Zero-Pair Cancellation**! Place 14 red negative counters and 9 yellow positive counters. Nine positive counters cancel 9 negative counters into zero-pairs, leaving 5 red negative counters (-5). On the simulator screen, when you spot the RPN prompt `-14 [ENTER] 9 [+] ?` (mental prompt `-14 + 9 = ?`), tap 5 **[+/-]** **[ENTER]** on the keypad (target sprint time: < 1.8 seconds). Run the full verification sequence on your SC-6: `14 [+/-] [ENTER] 9 [+] → -5`.

Keystroke	Register T	Register Z	Register Y	Register X
14	0	0	0	14
[+/-]	0	0	0	-14.0000
[ENTER]	0	0	-14.0000	-14.0000
[9]	0	0	-14.0000	9
[+]	0	0	0	-5.0000

Drill 48 (Level 6): gcd(24, 36) = ?

Build two prime factor towers using your **Prime Factor Blocks**! 24 = 2 × 2 × 2 × 3 and 36 = 2 × 2 × 3 × 3. Pull out the blocks both towers share—two 2-blocks and one 3-block—and multiply them: 2 × 2 × 3 = 12! When the Flight Simulator mission clock starts on `24 [ENTER] 36 [GCF] ?` (mental prompt `gcd(24, 36) = ?`), tap 12 **[ENTER]** on the keypad (target sprint time: < 1.8 seconds). Test the complete RPN operation on the stack: `24 [ENTER] 36 [GCF] → 12`.

Keystroke	Register T	Register Z	Register Y	Register X
24	0	0	0	24
[ENTER]	0	0	24	24
36	0	0	24	36
[GCF]	0	0	0	12

8.9 What You Mastered & Looking Ahead

In this chapter, you trained your mathematical reflexes and built lightning-fast math reflexes:

1. **Pure RPN Mental Representation:** You deciphered arithmetic questions presented as elegant RPN stack puzzles on the transflective LCD.
2. **Instant Sprint Evaluation:** You mastered instant submission via the hardware test key ([ENTER]), getting immediate tactile and auditory feedback on every attempt.
3. **The 6-Level Adaptive Ladder:** You advanced across number bonds, multi-digit operations, times tables, fraction remainders, and lightning-fast pre-algebra shortcuts.
4. **Mental Math Superpowers:** You conquered the eight mental math theorems—from the 11s shortcut to Vedic squaring—drastically shrinking your latency without scratch paper.

In **Chapter 09: Applied STEM Labs & Real-World Projects**, you will take all your computational speed, geometric visualization, and fractional precision out into the real world. You will calculate gear ratios for robotics, size solar panel arrays, compute trajectories for water rockets, and measure structural loads on 3D-printed trusses. Grab your safety goggles—it's time to build!

Applied Elementary STEM & Maker Labs

9.1 The Kitchen-Table Invention Studio: Turning Numbers into Moving Machines, Glowing Circuits, and 3D Prints

Picture the kitchen table on a rainy Saturday morning. In the center sits a spool of corn-based PLA filament, a pair of digital vernier calipers, a copper-foil tape dispenser, a handful of warm-white LEDs, and the solid, tactile form of your StackCalc SC-6 calculator. Outside, the rain taps against the glass; inside, the table is alive with invention.

For centuries, schoolchildren were told that mathematics was something that lived exclusively in the flat, monochrome world of paper workbooks—abstract symbols marching across ruled margins under the threat of a red grading pen. But mathematics was never meant to be trapped on paper. Mathematics is the hidden operating system of physical reality. It is the invisible scaffolding that allows a 3D printer nozzle heated to 215^°C to deposit molten plastic accurate to the width of a human hair. It is the Ohm's Law ratio that protects a fragile miniature LED from burning out when connected to a 3-volt coin cell. It is the square-root harmonic law discovered by Galileo Galilei that keeps a grandfather clock ticking with perfect rhythmic cadence across centuries.

When you pick up the SC-6 in your workshop, you aren't just doing schoolwork—you are an engineer, a builder, and an inventor! With **Stack Math**, your numbers become as physical as the copper tape and plastic gears on your desk. You push lengths and weights onto the stack, tap your operations, and watch your ideas turn into real machines that whir, glow, and run!

> **For Parents & Teachers: Applied Maker STEM & Physical Calculation**
>
> In David Macaulay's tradition of mechanical exposition *(Macaulay, 2016)*, Randall Munroe's dimensional scaling *(Munroe, 2014)*, and Matt Parker's real-world computation analysis *(Parker, 2019)*, real mathematics is verified by whether the machine actually runs.

Figure: Classroom Maker Space Clock: Precision Geared Engineering

Chapter Baseline Mode: `[NUM]`

Standard Base-10 Arithmetic • 4-Stack XYZT • Clean Display

(Engage `[$]` *Currency Mode for Final Cost Inspection)*

Unlocked Keycaps Ribbon — Grades 5–6 Applied STEM & Everyday Carry Suite

• **Engineering Math Keys:** `[x²]` Square, `[f]` `[√x]` Square Root, `[π]` Constant Pi, `[+]`, `[-]`, `[×]`, `[÷]`.

• **RPN Superpower 4:** `[f]` `[LASTX]` (Prior Number Recall for Chained Electrical Power, Ratio Scaling, and Kinetic Energy).

• **Statistical Accumulator:** `[Σ+]` Data Entry, `[f]` `[Σx]` Total Sum, `[g]` `[x̄]` Mean, `[f]` `[MED]` Median, `[RNG]` Range, `[g]` `[CLΣ]` Reset Statistics.

• **Everyday Carry Percent & Money:** `[%]` Percentage, `[g]` `[%CHG]` Percent Change, `[$]` Currency Formatting.

• **Proportional Scaling & Fractions:** `[g]` `[a:b]` Ratio Mode, `[g]` `[SIMP]` Factor Reduction, `[a b/c]` Mixed Numbers, `[f]` `[LCM]`.

• **Time & Angles:** `[f]` `[→HR]` (HMS to Decimal Hours), `[g]` `[→HMS]` (Decimal Hours to HMS), `[CLOCK]` Clock Sandbox.



Figure: Paper circuit LED current-limiting resistor (3V - 2V) / 0.02A = 50 Ohms

9.2 Building Real Things: From Workshop Tools to the Number Stack

Before we calculate on the keypad, we measure real things in the real world:

1. **Physical Workshop (Build It!):** You measure 3D printer filament with calipers, stick down copper tape for a paper flashlight, or count clock ticks with a timer.
2. **Sketches and Diagrams (Draw It!):** You draw circuit paths and lab notes in your notebook.
3. **The Number Stack (Calculate It!):** You stack your measurements on the SC-6, combining numbers without parentheses to find the perfect resistor or print time!

For Parents & Teachers: Maker STEM & Jerome Bruner's CRA Model

Following Jerome Bruner's **Concrete-Representational-Abstract (CRA)** framework *(Bruner, 1966)*, the SC-6 embeds computational mathematics directly into hands-on science and fabrication labs.

The Maker Math Workshop Paradigm

- **Phase 1: Physical Reality** → Vernier calipers, scales, lux meters, tape measures.
- **Phase 2: Visual Modeling** → Top-Down sketches, data logs, paper circuit schematics.
- **Phase 3: RPN Computation** → 4-stack XYZT evaluation, `[f] [LASTX]`, `[$]`, `[%]`.
- **Phase 4: Maker Validation** → Test physical part, launch projectile, light LED, start clock.

9.2.1 Algebraic Trap vs. StackCalc Superpower Showdown: Maker Dimensional Analysis & Spool Costing

Challenge / Equation	The Algebraic Calculator Trap (TI-30X / Smartphone)	The StackCalc SC-6 + Manipulative Superpower	Keystroke Reduction	Live Stack Visibility	Pedagogical Breakthrough
3D Printing Filament Cost: • 14.91g × ($20.00 / 1000g) = $0.30	Must type `1 4 . 9 1 * ( 2 0 / 1 0 0 0 ) =` (18 keystrokes). Forgetting parentheses multiplies mass by 20 before dividing, or requires writing unit cost ($0.02) on scrap paper. \| Continuous dimensional pipeline: `14.91 [ENTER] 20 [ENTER] 1000 [÷] [×] [$]` → **$0.30** (12 strokes). Intermediate unit cost ($0.02/g) stays visible on the stack!	**33% fewer strokes**	Register Y preserves 14.91g while Register X computes the unit price $0.02/g, allowing single-tap `[×]` and `[$]` currency formatting without scrap paper.	Students measure physical filament with calipers, trace dimensional unit cancellation directly on the stack, and see exact manufacturing cost before printing.	

9.3 Project 1: 3D Printing Filament Mass, Infill & Spool Cost Estimation

In modern classroom maker spaces, 3D printers turn digital CAD designs into physical objects. Before you send a job to the printer, calculate the volume of plastic extruded, convert that volume to mass in grams, and determine the exact financial cost from your filament budget.

Physical Model: The Filament Cylinder

Standard 3D printing filament is a flexible plastic cylinder with an exact diameter $d = 1.75$ mm (radius $r = 0.875$ mm $= 0.0875$ cm).

- **Cross-Sectional Area:** $A_f = \pi \times r^2 = \pi \times (0.0875 \text{ cm})^2 \approx 0.0240528 \text{ cm}^2$
- **Extruded Volume:** $V = A_f \times \text{Length (cm)}$
- **Part Mass (PLA):** $m = V \times \text{Density } (\rho = 1.24 \text{ g/cm}^3)$
- **Part Cost:** $C = m \times (\text{Spool Price} / 1000 \text{ g})$

Figure: Dominoes Studio Stealth Black: Technical Thermoplastics and Batch Manufacturing

9.3.1 Lab Mission 1.1: Estimating a 500 cm Print Model

Suppose your slicing software indicates that your pencil holder requires L = 500 cm (5.0 meters) of extruded filament. Your maker space uses a $20.00 spool of technical Midnight Navy PLA (1,000 grams).

Step 1: Compute Cross-Sectional Area ($A_f = \pi r^2$)

1. Enter radius in centimeters (0.0875 cm): `[.] 0875`.
2. Square the radius: Press **[x²]** → X = **0.00765625 cm²**.
3. Multiply by π: Press **[π]** **[×]** → X ≈ **0.0240528 cm²**.

Step 2: Compute Extruded Volume ($V = A_f \times L$)

1. Enter sliced model length 500 cm: `500`.
2. Multiply: Press **[×]** → X ≈ **12.02641 cm³**.

Step 3: Compute Part Mass ($m = V \times \rho$)

1. Enter PLA density (1.24 g/cm³): `1.24`.
2. Multiply: Press **[×]**:

- Register X displays: `14.91275` (The pencil holder weighs **14.91 grams**)!

Step 4: Compute Part Cost from $20 / 1000 g Spool

1. Calculate cost per gram: `20 [ENTER] 1000 [÷]` → X = 0.02 ($0.02 per gram).
2. Multiply mass by unit cost: Press **[×]**:

- Register X displays: `0.298255` (~ $0.30).

3. Format as currency: Press [$]:

- Screen displays: $0.30!

Keystroke	Register T	Register Z	Register Y	Register X
.0875	0	0	0	0.0875
[x²]	0	0	0	0.007656
[π] [×]	0	0	0	0.024053
500 [×]	0	0	0	12.02641
1.24 [×]	0	0	0	14.91275
20 [ENTER]	0	14.91275	20.00000	20
1000 [÷]	0	0	14.91275	0.02
[×]	0	0	0	0.298255
[] | 0 | 0 | 0 |0.30$				

9.3.2 Lab Mission 1.2: Infill Percentage Optimization

A solid plastic cube (100% infill) consumes immense filament. By setting the slicer to 15% gyroid infill, how much filament mass and money do you save on a 100 cm^3 trophy base?

- **Solid Volume Mass:** 100 cm^3 × 1.24 g/cm^3 = 124.0 g.
- **Shell Volume:** 20 cm^3 solid outer walls (20 × 1.24 = 24.8 g).
- **Infill Volume:** 80 cm^3 internal cavity at 15% density: 80 × 0.15 × 1.24 = 14.88 g.
- **Optimized Mass:** 24.8 + 14.88 = 39.68 g.
- **Mass Saved:** 124.0 - 39.68 = 84.32 g!

Keystroke	Register T	Register Z	Register Y	Register X
124	0	0	0	124
[ENTER]	0	0	124	124
24.8	0	0	124	24.8
[ENTER]	0	124	24.8	24.8
80	0	124.0	24.8	80
[ENTER]	124.0	24.8	80	80
0.15 [×]	124.0	124.0	24.8000	12
1.24 [×]	124.0	124.0	24.8000	14.88
[+]	124	124	124.0	39.68
[-]	124	124	124	84.32
.02 [×]	124	124	124	1.6864
[] | 124 | 124 | 124 |1.69$				

9.4 Project 2: Batch Classroom Kit Production & Manufacturing Economics

Classroom maker spaces often fabricate complete manipulative sets using 3D printers. In this project, you analyze the manufacturing economics of producing a complete station kit.

9.4.1 Lab Mission 2.1: Manufacturing a Kit of 24 Interlocking Snap Cubes

How much does it cost to 3D print a complete classroom kit of 24 interlocking math cubes?

- Each 20 mm cube consumes approximately 3.1 grams of PLA.
- Total Kit Mass: `24 [ENTER] 3.1 [×]` → **74.4 grams**.
- Total Kit Cost at $0.02/g: `.02 [×]` → 1.488.
- Currency Mode: Press **[$]** → `$1.49`!

Keystroke	Register T	Register Z	Register Y	Register X
24	0	0	0	24
[ENTER]	0	0	24	24
3.1	0	0	24	3.1
[×]	0	0	0	74.4
[.] 02	0	0	74.4	0.02
[×]	0	0	0	1.488
[] | 0 | 0 | 0 |1.49$				

9.4.2 Lab Mission 2.2: Electrical Operating Costs & Machine Time

A classroom 3D printer draws an average electrical power of P = 120 Watts (0.120 kW). The 24-cube kit requires 4.5 hours to print. The local municipal electric rate is $0.15 per kWh.

1. Energy Consumed: 0.120 kW × 4.5 h = 0.54 kWh.
2. Electricity Cost: 0.54 × $0.15 = $0.081 (~ $0.08).
3. Total Production Cost (Filament + Power): $1.49 + $0.08 = **$1.57** for the entire 24-cube kit!

Keystroke	Register T	Register Z	Register Y	Register X
[.] 12	0	0	0	0.12
[ENTER]	0	0	0.12	0.12
4.5	0	0	0.12	4.5
[×]	0	0	0	0.54
[.] 15	0	0	0.54	0.15
[×]	0	0	0	0.081
1.49 **[+]**	0	0	0	1.571

Keystroke	Register T	Register Z	Register Y	Register X
[] | 0 | 0 | 0 |1.57$				

9.5 Project 3: Paper Circuit LED Current-Limiting Resistors & Power

Paper circuits combine adhesive copper foil tape, a coin cell battery, and an LED to create interactive greeting cards, lighted art projects, and science fair displays.

Circuit Node	Component Specification	Electrical Role
Power Source (+)	CR2032 3.0 V Coin Cell	Supplies V_s = 3.0 V across copper tape
Current Limiter	Series Resistor R (Ω)	Drops excess headroom voltage V_s - V_f
Load & Return (-)	Red LED (V_f = 2.0 V, I_f = 20 mA)	Emits light safely without thermal burnout

9.5.1 The Engineering Physics & Ohm's Law

If you connect an LED directly to a battery without a resistor, excessive current will rush through the semiconductor diode junction, permanently burning out the LED. To protect the LED, we must insert a **current-limiting resistor (R)**:

$R = (V_s - V_f / I_f)$

Where:

- V_s: Battery Supply Voltage (3.0 V for a CR2032 lithium coin cell).
- V_f: LED Forward Voltage Drop (2.0 V for a standard Red LED).
- I_f: Safe Target Current (20 mA = 0.020 A).

9.5.2 Lab Mission 3.1: Computing Resistor Value and Power Dissipation

Step 1: Calculate Voltage Headroom (V_s - V_f)

1. Enter battery voltage: **`[3] [ENTER]`**.
2. Enter LED forward voltage: **`[2] [-]`**:

- Headroom: 3.0 - 2.0 = **1.0 V** in Register X.

Step 2: Apply Ohm's Law (R = V / I)

1. Enter safe current in amperes (0.020 A): `[.] 020`.
2. Divide: Press **`[÷]`**:

- Register X displays: `50.0` (We need a **50 Ω resistor**)!

Step 3: Compute Resistor Power Dissipation ($P = I^2 \times R$)

We must ensure our resistor does not overheat. We evaluate $P = I^2 \times R$. **We use Superpower 4: `[f] [LASTX]` to recall the current without re-typing!**

1. Press `[f]` `[LASTX]`:

- 0.020 is instantly recalled into Register X!
- The resistance (50.0 Ω) is automatically lifted into Register Y!

2. Square the current (I^2): Press `[x²]` → X = 0.0004 A^2.
3. Multiply by resistance (R): Press `[×]`:

- Register X displays: `0.020` (0.020 W = **20 mW**)!

Keystroke	Register T	Register Z	Register Y	Register X
`[3]` `[ENTER]`	0	0	3	3
`[2]` `[-]`	0	0	0	1.0
`.020` `[÷]`	0	0	0	50.0
`[f]` `[LASTX]`	0	0	50.0	0.020
`[x²]`	0	0	50.0	4.0000×10^{-4}
`[×]`	0	0	0	0.020

9.5.3 Lab Mission 3.2: High-Voltage 9V Battery Circuit with Blue LED

Suppose you build a stage beacon using a 9V alkaline battery (V_s = 9.0 V) and a high-intensity Blue LED (V_f = 3.2 V, I_f = 0.020 A):

1. Voltage Headroom: `9 [ENTER] 3.2 [-]` → X = **5.8 V**.
2. Resistor Value: `[.] 020 [÷]` → `290.0 Ω`.
3. Power Dissipation via `[f] [LASTX]`:

- `[f] [LASTX] [x²] [×]` → `0.116 W` (116 mW).

Keystroke	Register T	Register Z	Register Y	Register X
`[9]` `[ENTER]`	0	0	9	9
3.2 `[-]`	0	0	0	5.8
`.020` `[÷]`	0	0	0	290.0
`[f]` `[LASTX]`	0	0	290.0	0.020
`[x²]`	0	0	290.0	4.0000×10^{-4}
`[×]`	0	0	0	0.116

9.6 Project 4: Simple Pendulum Period Measurement & Gravity

A simple pendulum consists of a small mass (a steel nut or 3D-printed bob) suspended from a light string. Galileo discovered that for small swings, the period of oscillation depends exclusively on the length of the string and the acceleration of gravity, completely independent of the bob's mass.

Physical Model: The Simple Pendulum

A small mass is suspended from a string of length L swinging in a small arc.

- **Theoretical Period:** $T = 2\pi \times \sqrt{(L / g)}$
- **Experimental Period:** $T\blacksquare$ = Total Time / 10 Swings
- **Derived Gravity:** $g = (4\pi^2 \times L / T^2)$



Figure: Clock Quadrant Concept: Pendulum Escapements and Harmonic Oscillation

9.6.1 Lab Mission 4.1: Timing 10 Swings with a 1.0 Meter Pendulum

You hang a pendulum of measured length L = 1.00 meter. Using a stopwatch, you and your team time 10 complete back-and-forth cycles: **Measured 10-cycle time = 20.1 seconds**

Step 1: Calculate Mean Period T■

1. Enter recorded time: `20.1 [ENTER]`.
2. Divide by 10 swings: `10 [÷]` → X = **2.01 seconds per period**.

Step 2: Compute Local Gravitational Acceleration ($g = 4\pi^2 L / T^2$)

1. Square the period: Press **[x²]** → X = 4.0401 s^2.
2. Calculate $4\pi^2$: Press `4 [π] [x²] [×]` → X ≈ 39.4784.
3. Multiply by length (L = 1.0 m): Press **[1] [×]**.
4. Exchange and divide by T^2: Press **[x⇔y] [÷]** :

- Register X displays: `9.7716` (~ **9.77 m/s^2**)!

Keystroke	Register T	Register Z	Register Y	Register X
20.1 [ENTER]	0	0	20.1000	20.1
10 [÷]	0	0	0	2.01
[x²]	0	0	0	4.0401
[4]	0	0	4.0401	4
[π] [x²] [×]	0	0	4.0401	39.4784
[1] [×]	0	0	4.0401	39.4784
[x⇔y] [÷]	0	0	0	9.7716

(Compared to the accepted standard $g = 9.80665\ m/s^2$, your hands-on experiment achieves less than 0.4% experimental error!)

9.6.2 Lab Mission 4.2: Designing a 1-Second Grandfather Clock Pendulum

What string length L creates a "seconds pendulum" that ticks exactly once every second (T = 2.0 seconds for a complete round trip)? **$L = (g \times T^2 / 4\pi^2) = (9.80665 \times 2.0^2 / 4 \times \pi^2) = (39.2266 / 39.4784) \approx 0.9936$ meters (99.4 cm)**

Keystroke	Register T	Register Z	Register Y	Register X
9.80665	0	0	0	9.80665
[ENTER]	0	0	9.80665	9.80665
[2] [x²]	0	0	9.80665	4
[×]	0	0	0	39.2266
[4]	0	0	39.2266	4
[π] [x²] [×]	0	0	39.2266	39.4784
[÷]	0	0	0	0.9936

9.7 Project 5: Solar Oven Thermal Tracking & Efficiency Rates

In solar energy science labs, you construct a cardboard box solar cooker lined with aluminum foil, topped with clear plastic wrap, and insulated with crumpled newspaper.

Thermal Parameter	Symbol / Formula	Physical Meaning
Temperature Rise	$\Delta T = T_2 - T_1$	Total degrees Celsius gained inside absorber tray
Elapsed Interval	Δt	Heating duration in minutes
Heating Velocity	Rate = $\Delta T / \Delta t$	Degrees Celsius gained per minute (^°C/min)

9.7.1 Lab Mission 5.1: Measuring Solar Heating Velocity

Place your solar cooker in direct sunlight at solar noon. Your internal digital temperature probe records:

- Initial Temperature at t = 0 min: T_1 = 22.5^°C
- Final Temperature at t = 25 min: T_2 = 78.0^°C

1. Temperature Rise (Δ T): `78 [ENTER] 22.5 [-]` → X = **55.5^°C**.
2. Elapsed Time (Δ t): `25 [÷]` → X = **2.22^°C per minute**!
3. Percentage Increase (**`[g] [%CHG]`**):

- `22.5 [ENTER] 78 [g] [%CHG]` → X = **+246.67%** increase!

Keystroke	Register T	Register Z	Register Y	Register X
78	0	0	0	78
`[ENTER]`	0	0	78	78
22.5	0	0	78	22.5
`[-]`	0	0	0	55.5
25	0	0	55.5	25
`[÷]`	0	0	0	2.22

9.7.2 Lab Mission 5.2: Thermal Insulation Retention Ratio

After reaching 78^°C, move your oven into shaded ambient air (22^°C) to test its insulation. After 30 minutes, the oven temperature drops to 56^°C.

- Total Heat Retained: (56 - 22 / 78 - 22) = (34 / 56) ≈ **60.71%** retention!

Keystroke	Register T	Register Z	Register Y	Register X
56	0	0	0	56
`[ENTER]`	0	0	56	56
22 `[-]`	0	0	0	34
78	0	0	34	78
`[ENTER]`	0	34	78	78
22 `[-]`	0	0	34	56
`[÷]`	0	0	0	0.6071
100 `[×]`	0	0	0	60.71

9.8 Project 6: Catapult Trajectory Math & Projectile Launch Analysis

Build a tabletop wooden or 3D-printed lever catapult powered by rubber bands. Launch small clay projectiles at varying pullback angles (30^°, 45^°, 60^°) to analyze launch distances and compute statistical variance.

Apparatus Variable	Controlled / Measured Value	Experimental Role
Pullback Angle (θ)	30^°, 45^°, 60^°	Independent variable controlling elastic potential energy
Landing Distance (D)	Measured in cm along floor tape	Dependent variable accumulated via [Σ+]

9.8.1 Lab Mission 6.1: Five-Trial Statistical Analysis at 45^°

Conduct 5 launches at a calibrated 45^° pullback angle, recording distance in centimeters: **D = (182 cm, 195 cm, 188 cm, 201 cm, 189 cm)**

Accumulate each trial into the SC-6 hardware statistical registers using [Σ+]:

1. Reset statistics: Press [g] [CLΣ].
2. Enter Trial 1: 182 [⊠+] → n = 1.
3. Enter Trial 2: 195 [⊠+] → n = 2.
4. Enter Trial 3: 188 [⊠+] → n = 3.
5. Enter Trial 4: 201 [⊠+] → n = 4.
6. Enter Trial 5: 189 [⊠+] → n = 5.
7. Recall Mean (x■): Press [g] [x̄] → X = **191.00 cm**.
8. Recall Mean Absolute Deviation (MAD): Press [g] [MAD] → X = **5.20 cm**.

Keystroke	Register T	Register Z	Register Y	Register X
[g] [CLΣ]	0	0	0	0
182 [Σ+]	0	0	0	1.0000
195 [Σ+]	0	0	0	2.0000
188 [Σ+]	0	0	0	3.0000
201 [Σ+]	0	0	0	4.0000
189 [Σ+]	0	0	0	5.0000
[g] [x■]	0	0	0	191.00
[f] s	0	0	191.00	7.25

9.8.2 Lab Mission 6.2: Target Ring Landing Probability

If a circular scoring target has radius R = 15 cm centered at 190 cm, the target spans 175 cm to 205 cm. Since the mean is 191.00 cm and 2s = 14.50 cm (2 × 7.25 cm), the 2σ interval is [176.50 cm, 205.50 cm]. Over 95% of all shots will land directly inside the scoring ring!

Keystroke	Register T	Register Z	Register Y	Register X
191 [ENTER]	0	0	191	191
7.25 [ENTER]	0	191	7.25	7.25
2 [×]	0	0	191	14.50

Keystroke	Register T	Register Z	Register Y	Register X
[-]	0	0	0	176.50
191 [ENTER]	0	176.50	191	191
14.50 [+]	0	0	176.50	205.50

9.9 Project 7: Plant Growth Tracking & Proportional Rate Analysis

In life science experiments, you grow bean sprouts under different light conditions (natural sunlight vs. red LED growth lamp), measuring stem height in millimeters every two days for two weeks.

14-Day Botany Log	Day 2	Day 4	Day 6	Day 8	Day 10	Day 12	Day 14
Stem Height h (mm)	12	28	49	74	105	138	172

9.9.1 Lab Mission 7.1: Daily Growth Velocity

What was the sprout's average daily growth rate between Day 4 (28 mm) and Day 10 (105 mm)? **Rate = $(h_2 - h_1 / t_2 - t_1)$ = (105 - 28 / 10 - 4) = (77 mm / 6 days) ≈ 12.83 mm/day**

Keystroke	Register T	Register Z	Register Y	Register X
105	0	0	0	105
[ENTER]	0	0	105	105
28 [-]	0	0	0	77
10	0	0	77	10
[ENTER]	0	77	10	10
[4] [-]	0	0	77	6
[÷]	0	0	0	12.83

9.9.2 Lab Mission 7.2: Overall Growth Percentage

Calculate the total percent increase from Day 2 (12 mm) to Day 14 (172 mm):

- `12 [ENTER] 172 [g] [%CHG]` → X = **+1333.33%** growth!

Keystroke	Register T	Register Z	Register Y	Register X
12	0	0	0	12
[ENTER]	0	0	12	12
172	0	0	12	172
[g] [%CHG]	0	0	12	1333.33

9.10 Project 8: Culinary Chemistry & Baker's Percentage Recipe Scaling

In culinary arts and life skills, recipes must be scaled proportionally. Professional bakers use **Baker's Percentages**, where the weight of flour is always designated as 100%, and all other ingredients are calculated as a percentage of flour weight.

BAKER'S PERCENTAGE FORMULATION SHEET

Bread Flour: 100.0% (Base Ingredient)

Water (Hydration): 68.0%

Yeast: 1.5%

Salt: 2.0%

Total Formula: 171.5%

9.10.1 Lab Mission 8.1: Scaling Bread for a 28-Guest Banquet

The standard loaf requires 500 grams of flour and yields 4 generous servings. You need to bake bread for 28 guests (7× scaling factor).

1. Total Flour: `500 [ENTER] 7 [×]` → X = **3,500 grams** (3.5 kg).
2. Water (68% hydration): `3500 [ENTER] 68 [%]` → X = **2,380 grams** (2.38 L).
3. Salt (2.0%): `3500 [ENTER] 2 [%]` → X = **70 grams**.
4. Yeast (1.5%): `3500 [ENTER] 1.5 [%]` → X = **52.5 grams**.

Step	Keystroke	Register T	Register Z	Register Y	Register X	Notes
01	`500 [ENTER] 7 [×]`	0	0	0	3500	Total Flour base: 500g × 7 = 3,500g
02	`68 [%]`	0	0	3500	2380	Water: 68% of 3,500g = 2,380g (Y holds base 3,500g)
03	**`[C] 2 [%]`**	0	0	3500	70	Clear X (`CLx`, lift disabled) then 2.0% of 3,500g = 70g (Y base preserved!)
04	**`[C] 1.5 [%]`**	0	0	3500	52.5	Clear X (`CLx`, lift disabled) then 1.5% of 3,500g = 52.5g (Y base preserved!)

9.10.2 Lab Mission 8.2: Scaling Down a Liquid Measuring Cup Recipe

A pancake recipe requires 1 (3 / 4) cups of milk for 8 pancakes. You are making breakfast for two (2 pancakes, scale factor 2/8 = 1/4):

- Enter milk: `1 [.] 3 [.] 4 [ENTER]` (1 (3 / 4) = 7/4 = 1.75).
- Divide by 4: **`[4] [÷]`**.
- Result: `7/16` cup of milk (0.4375)!

Step	Keystroke	Register T	Register Z	Register Y	Register X	Notes
01	`1 . 3 . 4`	0	0	0	1 (3 / 4)	Enter mixed fraction 1 (3 / 4) cups (1.75)

Step	Keystroke	Register T	Register Z	Register Y	Register X	Notes
02	[ENTER]	0	0	1 (3 / 4)	1 (3 / 4)	Push to operational stack
03	[4] [÷]	0	0	0	7/16	Divide by 4; yields exact (7 / 16) cup (0.4375)

9.11 Project 9: Compound Gear Train Ratios & Mechanical Advantage

Build gear mechanisms using 3D-printed gears or modular robotics sets. Discover how interlocking teeth trade speed for torque.

Reduction Stage	Driver Gear	Driven Gear	Stage Ratio
Stage 1 (Input Shaft)	Gear A (12 teeth)	Gear B (36 teeth)	36 / 12 = 3:1
Stage 2 (Shared Intermediate Shaft)	Gear C (16 teeth)	Gear D (48 teeth)	48 / 16 = 3:1
Compound Output	—	—	**3 × 3 = 9:1**

9.11.1 The Gear Ratio Formula

For a compound train with two reduction stages: $R_{total} = (N_B / N_A) \times (N_D / N_C)$

9.11.2 Lab Mission 9.1: Computing Total Compound Gear Reduction

Stage 1: Gear A (12 teeth) drives Gear B (36 teeth). Stage 2: Gear C (16 teeth) drives Gear D (48 teeth).

1. Stage 1 Ratio: `36 [ENTER] 12 [÷]` → X = **3.0**.
2. Stage 2 Ratio: `48 [ENTER] 16 [÷]` → X = **3.0**.
3. Compound Ratio: Press [×]:

- Register X displays: `9.0` (A true **9:1 reduction**)!

Keystroke	Register T	Register Z	Register Y	Register X
36	0	0	0	36
[ENTER]	0	0	36	36
12 [÷]	0	0	0	3.0
48	0	0	3.0	48
[ENTER]	0	3.0	48	48
16 [÷]	0	0	3.0	3.0
[×]	0	0	0	9.0

9.11.3 Lab Mission 9.2: Calculating Output Shaft Speed

If the input electric motor spins at 1,800 RPM, what is the final output shaft speed with a 9:1 compound reduction?

- `1800 [ENTER] 9 [÷]` → X = **200 RPM**!

Keystroke	Register T	Register Z	Register Y	Register X
1800 [ENTER]	0	0	1800	1800
9 [÷]	0	0	0	200

9.12 Project 10: Hydraulic Syringe Lift & Pascal's Principle

Explore fluid power using two plastic medical syringes of different diameters connected by flexible vinyl tubing filled with water.

Hydraulic Cylinder	Piston Diameter	Relative Cross-Section Area	Force Relationship ($P_1 = P_2$)
Small Input Syringe (A_1)	d_1 = 1.0 cm	1× baseline area	Input effort F_1
Large Output Syringe (A_2)	d_2 = 3.0 cm	$(d_2 / d_1)^2$ = 9× area	Output lift $F_2 = 9 \times F_1$

9.12.1 Lab Mission 10.1: Mechanical Force Multiplication Factor

Input syringe diameter d_1 = 1.0 cm; output syringe diameter d_2 = 3.0 cm.

1. Enter output diameter: [3] [ENTER].
2. Enter input diameter: [1] [÷].
3. Square the diameter ratio: Press [x²]:

- Register X displays: 9.0 (The mechanical advantage is **9×**)!

Keystroke	Register T	Register Z	Register Y	Register X
[3]	0	0	0	3
[ENTER]	0	0	3	3
[1]	0	0	3	1
[÷]	0	0	0	3
[x²]	0	0	0	9

9.12.2 Lab Mission 10.2: Lifting a 4.5 kg Weight

If you push the small syringe with a force of F_1 = 5.0 Newtons (≈ 0.5 kg effort) and a 9× area multiplication factor, what force is exerted by the large syringe?

- 9 [ENTER] 5.0 [×] → X = **45.0 Newtons**, then 9.8 [÷] → X = **4.59 kg** lift!

Keystroke	Register T	Register Z	Register Y	Register X
9 [ENTER]	0	0	9	9
5.0 [×]	0	0	0	45.0
9.8 [÷]	0	0	0	4.59

9.13 Project 11: Drone Flight Battery Endurance & Power Budget

Miniature indoor quadcopters powered by lithium-polymer (LiPo) batteries are popular STEM tools. In this project, you calculate power consumption and flight endurance.

DRONE ELECTRICAL POWER BUDGET

Battery Capacity: 850 mAh = 0.850 Ah

Hover Current Draw: 4.2 Amperes = 4200 mA

Usable Battery Margin: 80% (20% reserve to prevent LiPo damage)

Flight Time (Minutes): t = (Capacity × Usable Margin × 60) / Current

9.13.1 Lab Mission 11.1: Calculating Safe Hover Duration

1. Enter battery capacity: `850 [ENTER]`.
2. Apply 80% reserve margin: **`[.] [8] [×]`** → X = **680 mAh usable**.
3. Convert hours to minutes: `60 [×]` → X = **40,800 mA·min**.
4. Divide by total hover current (4,200 mA): `4200 [÷]`:

- Register X displays: **9.714 minutes**!

5. Convert decimal minutes to minutes and seconds:

- Safe flight timer: **9 minutes 43 seconds**!

Keystroke	Register T	Register Z	Register Y	Register X
850	0	0	0	850
[ENTER]	0	0	850	850
[.] [8] [×]	0	0	0	680
60 **[×]**	0	0	0	40800
4200 **[÷]**	0	0	0	9.714

9.13.2 Lab Mission 11.2: Drone Payload Penalty & Reduced Endurance

Mount an action camera (m = 45 grams) to the drone. The increased lift requirement increases the hover current draw from 4,200 mA to 5,500 mA.

1. Calculate the new flight duration with payload:

- Available capacity: 680 mAh (80% of 850 mAh).
- Flight minutes: (680 × 60) ÷ 5,500 = 7.418 minutes (7 min 25 sec).

2. Calculate the percentage reduction in endurance:

- Initial time: 9.714 min.
- New time: 7.418 min.
- Percent change: enter `9.714`, swap `[x⇔y]`, then press `[g]` `[%CHG]` → **-23.64%** penalty!

Keystroke	Register T	Register Z	Register Y	Register X
680 [ENTER]	0	0	680	680
60 [×]	0	0	0	40800
5500 [÷]	0	0	0	7.418
9.714	0	0	7.418	9.714
[x⇔y]	0	0	9.714	7.418
[g] [%CHG]	0	0	9.714	-23.64

9.14 Project 12: Photovoltaic Solar Panel Tilt Angle & Irradiance

In clean energy science labs, you evaluate how solar panel orientation impacts electrical power generation using Lambert's Cosine Law.

Incident Tilt Angle θ	Cosine Projection Factor (cosθ)	Received Solar Power $P(\theta) = P_{max}\cos\theta$
0^° (Perpendicular)	1.0000	100.0% of P_{max}
30^° Tilt	0.8660	86.6% of P_{max}
45^° Tilt	0.7071	70.7% of P_{max}
60^° Tilt	0.5000	50.0% of P_{max}

9.14.1 Lab Mission 12.1: Solar Power at Varying Incident Angles

A classroom solar panel produces P_{max} = 5.0 Watts when perpendicular to direct sunlight (θ = 0^°). What power does it generate at tilt angles of 30^°, 45^°, and 60^°?

1. At θ = 30^° (Volvelle shadow factor cos 30^° ≈ 0.866):

- `5 [ENTER] 0.866 [×]` → X = **4.33 Watts** (86.6%).

2. At θ = 45^° (Volvelle shadow factor cos 45^° ≈ 0.7071):

- `5 [ENTER] 0.7071 [×]` → X = **3.54 Watts** (70.7%).

3. At θ = 60^° (Volvelle shadow factor cos 60^° = 0.500):

- `5 [ENTER] .5 [×]` → X = **2.50 Watts** (50.0%).

Keystroke	Register T	Register Z	Register Y	Register X
[5] [ENTER]	0	0	5	5
.866 (30° factor)	0	0	5	0.8660

Keystroke	Register T	Register Z	Register Y	Register X
[×]	0	0	0	4.33

Angle (θ)	cos(θ)	Peak Watts	Output Power	Power Ratio
0°	1.0000	5.00 W	5.00 W	100.0%
30°	0.8660	5.00 W	4.33 W	86.6%
45°	0.7071	5.00 W	3.54 W	70.7%
60°	0.5000	5.00 W	2.50 W	50.0%

9.14.2 Lab Mission 12.2: Daily Kilowatt-Hour Solar Harvest Integration

Record the power output of an outdoor solar panel at three key intervals during a sunny school day:

- Morning (9:00 AM, θ = 60^°): 2.50 Watts for 3 hours → 7.50 Watt-hours.
- Solar Noon (12:00 PM, θ = 0^°): 5.00 Watts for 2 hours → 10.00 Watt-hours.
- Afternoon (3:00 PM, θ = 45^°): 3.54 Watts for 3 hours → 10.62 Watt-hours.

Accumulate each energy interval using the SC-6 statistical accumulator [Σ+]:

1. Reset statistics: [g] [CLΣ].
2. Morning interval: 2.5 [ENTER] [3] [×] [Σ+] → n = 1 (7.5 Wh).
3. Noon interval: [5] [ENTER] [2] [×] [Σ+] → n = 2 (10.0 Wh).
4. Afternoon interval: 3.54 [ENTER] [3] [×] [Σ+] → n = 3 (10.62 Wh).
5. Total Daily Energy: Recall [f] [Σx] → X = **28.12 Watt-hours**!
6. Convert to Kilowatt-hours: 1000 [÷] → X = **0.02812 kWh**.

Keystroke	Register T	Register Z	Register Y	Register X
[g] [CLΣ]	0	0	0	0
2.5 [ENTER] 3 [×]	0	0	0	7.5
[Σ+]	0	0	0	1.0000
5 [ENTER] 2 [×]	0	0	0	10.0
[Σ+]	0	0	0	2.0000
3.54 [ENTER] 3 [×]	0	0	0	10.62
[Σ+]	0	0	0	3.0000
[f] [Σx]	0	0	0	28.12
1000 [÷]	0	0	0	0.02812

9.15 Maker Lab Engineering Notebook & Uncertainty Protocol

Professional engineers never report a measurement without estimating its experimental uncertainty. In this section, you learn to calculate **Percentage Error** and evaluate **Manufacturing Tolerances** on the SC-6.

Percent Error = | (Experimental - Theoretical / Theoretical) | × 100%

9.15.1 Lab Mission 13.1: Calculating Pendulum Gravity Error

In Project 4, your experimental gravity was $g_{exp} = 9.7716\ m/s^2$. The standard accepted theoretical value is $g_{theo} = 9.80665\ m/s^2$. What is the experimental error?

Keystroke	Register T	Register Z	Register Y	Register X
`9.7716`	0	0	0	9.7716
`[ENTER]`	0	0	9.7716	9.7716
`9.80665`	0	0	9.7716	9.80665
`[-]`	0	0	0	-0.03505
`[g] [|x|]`	0	0	0	0.03505
`9.80665`	0	0	0.03505	9.80665
`[÷]`	0	0	0	0.003574
`100 [×]`	0	0	0	0.357

(You achieved an outstanding 0.36% experimental error!)

9.15.2 Lab Mission 13.2: 3D Printing Snap-Fit Tolerance Stack

When 3D printing interlocking parts (like the Gridfinity pins or snap cubes), thermal shrinkage and nozzle expansion require a mechanical clearance of ± 0.15 mm. If a peg has diameter $d_{peg} = 10.00$ mm, what is the minimum hole diameter required for a smooth friction fit? **d_{hole} = 10.00 mm + 2 × 0.15 mm = 10.30 mm**

> **RPN Keystrokes:**
> `10 [ENTER] .15 [ENTER] 2 [×] [+]` → **10.30 mm**

9.15.3 Lab Mission 13.3: Digital Scale Tare & Filament Density Verification

In maker spaces, verify whether a spool of unknown plastic is PLA or ABS by measuring Archimedes' buoyant force or calculating solid density ($\rho = m / V$):

1. A calibrated 3D-printed test cube measures exactly 20.0 mm × 20.0 mm × 20.0 mm (2.0 cm on each edge).

- Volume: `2 [ENTER] 2 [×] 2 [×]` → X = **8.00 cm^3**.

2. The digital precision balance is tared. The cube weighs m = 9.92 grams.
3. Calculate density: `9.92 [x⊠y] [÷]`:

- Register X displays: **1.24 g/cm^3**.

- Comparing against the material spec sheet confirms: the plastic is **authentic PLA** ($\rho = 1.24$ g/cm^3), not lightweight ABS ($\rho = 1.04$ g/cm^3)!

Keystroke	Register T	Register Z	Register Y	Register X
`[2]` `[ENTER]`	0	0	2	2
`[2]` `[×]`	0	0	0	4
`[2]` `[×]`	0	0	0	8.0
9.92	0	0	8.0	9.92
`[x⇔y]`	0	0	9.92	8.0
`[÷]`	0	0	0	1.24

9.16 Maker Space Machine Safety Protocols & Electrical Protection

Operating fabrication machinery requires strict adherence to classroom safety rules and electrical power limitations:

Workshop Safety & Electrical Power Protocols

1. **Thermal Safety:** 3D printer hotends reach 210^°C - 245^°C; heated build plates reach 60^°C. Never touch nozzles or heating blocks during extrusion.

2. **Electrical Safety:** Never short-circuit lithium batteries. LiPo cells can discharge at rates > 30C, creating immediate thermal runaway and fire hazards if punctured or reverse-polarized.

3. **Eye Protection:** Always wear ANSI Z87.1 approved safety glasses when launching catapults, testing hydraulic cylinders, or trimming wire leads with flush cutters.

4. **Ventilation:** Ensure active classroom exhaust or HEPA/activated-carbon filtration when 3D printing to prevent ultrafine particle and VOC accumulation.

9.16.1 Lab Mission 14.1: Circuit Breaker Branch Load Budgeting

A classroom maker lab has four 3D printers (150 W each), two laptop workstations (65 W each), and a HEPA air filtration unit (80 W) all plugged into a single 120 V, 15 Amp branch circuit. Does the total maker space electrical load exceed the National Electrical Code (NEC) continuous 80% safety limit (12 Amps)?

1. Total Power:

- 4 printers: `4 [ENTER] 150 [×]` → 600 W.
- 2 laptops: `2 [ENTER] 65 [×] [+]` → 730 W.
- 1 filter: `80 [+]` → **810 Watts total**.

2. Current Draw at 120 Volts ($I = P / V$):

- `120 [÷]` → X = **6.75 Amperes**.

3. Continuous Circuit Limit (15 A × 80%):

- `15 [ENTER] 80 [%]` → X = **12.00 Amperes**.

4. Margin Available:

- `12 [ENTER] 6.75 [-]` → X = **5.25 Amps remaining**.
- **Conclusion:** The equipment is completely safe and operates well within electrical safety limits!

Keystroke	Register T	Register Z	Register Y	Register X
4 **[ENTER]** 150 **[×]**	0	0	0	600
2 **[ENTER]** 65 **[×]**	0	0	600	130
[+]	0	0	0	730
80 **[+]**	0	0	0	810
120 **[÷]**	0	0	0	6.75
15 **[ENTER]** .80 **[×]**	0	0	6.75	12.0
[x⇔y] **[-]**	0	0	0	5.25

For Parents & Teachers: Engineering Principles & Stack Architecture

Dimensional Analysis Chains in RPN: In traditional algebraic notation, multi-step physical conversions require deeply nested parentheses or manual transcription of intermediate values:

$C = (\pi \times r^2 \times L \times \rho) \times (Price / 1000)$

In RPN, dimensional analysis unfolds as a direct chronological pipeline:

1. Radius squared times π produces cross-sectional area (cm^2).

2. Multiplying by extrusion length yields total filament volume (cm^3).

3. Multiplying by polymer density converts volume to mass (g).

4. Multiplying by unit cost yields final fabrication cost ($). Every intermediate display value represents a tangible physical quantity with concrete units, preventing dimensional errors and eliminating parenthesis syntax. **Register Conservation via `[f] [LASTX]`:** When calculating electrical power dissipation in current-limiting resistors, the standard formula is:**$P = I^2 R = I^2 \times (V_s - V_f / I)$**

Rather than re-entering current I or storing it in global memory registers, the SC-6 leverages Superpower 4 (**`[f]` `[LASTX]`**):

1. Compute $(V_s - V_f) \div I \rightarrow R$ in Register X.

2. Tap **`[f]` `[LASTX]`** to instantly recall the divisor current I into X while R lifts to Y.

3. Square I with **`[x²]`** and tap **`[×]`** to yield P in milliwatts.

This two-step sequence demonstrates optimal register reuse without memory spill.

Analytical Modeling in Maker Education: Fabrication tools like 3D printers and laser cutters should not operate as opaque black boxes. Pre-flight mathematical modeling—estimating filament mass, layer cooling times, gear reduction ratios, and circuit thermal limits—transforms students from passive machine operators into deliberate, analytical designers who understand the physical constraints governing their creations.

For Parents & Teachers: Classroom Dialogue Scripts & Misconception Diagnostics

Script 9.1: The Mystery of the Hot Resistor:

Teacher: "Class, Marcus designed a paper circuit with a 9V battery and a red LED. He used a 350 Ω resistor, but he noticed the resistor got warm to the touch. Let's calculate the power dissipation!"

Marcus: "The current is 20 mA = 0.020 A."

Teacher: "Enter current on your SC-6: `0.020 [x²]`."

Marcus: "That's 0.0004."

Teacher: "Now enter resistance and multiply: `350 [×]`."

Marcus: "0.140 Watts = 140 mW!"

Teacher: "Our standard classroom resistors are rated for 125 mW (1/8 Watt). What does 140 mW tell us?"

Marcus (eyes wide): "The circuit is pushing more power through the resistor than it is rated to handle! That's why it got warm!"

Teacher: "How can Marcus fix it?"

Marcus: "Use a 1/4 Watt (250 mW) resistor, or lower the current to 15 mA!"

Script 9.2: The Simple Pendulum & Why Mass Doesn't Matter:

Student (Chloe): "Teacher, when we timed our pendulum with a heavy 50-gram steel bolt, it took 20 seconds for 10 swings. If I replace the bolt with a tiny 5-gram wooden bead, will it swing much faster because it's lighter?"

Teacher: "That sounds very logical, Chloe! Let's test your hypothesis on our lab rig. Tie the 5-gram bead onto the exact same 1.0-meter string. Start the stopwatch!"

Chloe: "1, 2, 3... 8, 9, 10! Stop! 20.1 seconds! It took the exact same time!"

Teacher: "Why didn't the lighter mass speed up?"

Chloe: "I don't understand. Gravity pulls harder on heavy things, right?"

Teacher: "Gravity pulls with ten times more force on the 50-gram bolt, but the bolt also has ten times more inertia—it resists moving ten times more! The extra pull exactly cancels the extra inertia! Look at our formula on the board: $T = 2\pi\sqrt{(L/g)}$. Is there an m for mass anywhere in that formula?"

Chloe: "No! Only length and gravity! So only string length changes the time!"

| Observable Error | Cognitive Root Cause | Targeted Remediation Prompt |

| :--- | :--- | :--- |

| **Using diameter instead of radius: $A = \pi d^2$** | Forgetting to divide diameter by 2 before squaring. | *"Diameter is the entire width across the circle; radius is from the center to the edge! Always divide 1.75 mm by 2 to get radius 0.875 mm."* |

| **Omitting LED forward voltage drop (V_f)** | Assuming the entire battery voltage drops across the resistor. | *"The LED consumes its own forward voltage (2.0V) just to stay lit! Only the leftover voltage (V_s - V_f) drops across the resistor."* |

| **Assuming a heavier pendulum swings faster** | Conflating gravitational force with acceleration. | *"A heavier bob has more gravitational pull, but it also has more mass to accelerate! Mass cancels out in the period formula: length is all that matters!"* |

| **Scaling recipes by adding instead of multiplying** | Additive vs. multiplicative reasoning confusion. | *"If you make 7 loaves of bread instead of 1, you must MULTIPLY every single ingredient by 7, not add 7 cups!"* |

| **Dividing gear ratios in reverse order** | Confusing driver gear (input) with driven gear (output). | *"Gear ratio is always Driven teeth divided by Driver teeth (Out / In)! Large driven gear means slower speed and more torque."* |

| **Ignoring battery reserve safety margin** | Draining a LiPo battery down to 0% capacity. | *"Discharging a lithium battery below 20% permanently damages its chemistry! Always multiply capacity by 0.80 to find safe flight time."* |

9.17 Practice Station: 40 Worked Applied STEM Challenges

The following 40 fully worked STEM challenges are organized across four cohesive Maker Expeditions covering physics, engineering, botany, culinary arts, and renewable energy. Every keystroke sequence assumes the SC-6 baseline mode `[NUM]`.

Hands-On Studio Proof: Blocks → Calculator

Before calculating electrical power, pendulum periods, or recipe scaling factors, young makers verify formulas through physical instruments:

1. **Vernier Calipers & 3D Extrusion (Station 1):** Use digital vernier calipers to measure real 1.75 mm filament across three points. Derive cross-sectional area $A_f = \pi r^2 = 0.02405\ cm^2$ before estimating print mass ($m = V \times 1.24$) and checking spool costs with `[$]`.

2. **Stopwatches & Gravity Verification (Station 2):** Build a 1-meter string pendulum. Time 10 complete oscillation cycles with a stopwatch. Use RPN stack division and square-root keys (`[f]` `[√x]`) to calculate the experimental gravitational acceleration $g = 4\pi^2 L / T^2 \approx 9.8\ m/s^2$.

3. **Digital Kitchen Scales (Station 3):** Tare a digital kitchen gram scale. Weigh 450 g flour, calculate 65% hydration water (292.5 g), and scale sourdough loaves for the entire classroom using the `[%]` key.

4. **Gear Train Ratios & Torque (Station 4):** Count physical teeth on interlocking plastic gears (12T driver vs. 36T driven). Feel the 3:1 mechanical advantage in your hands before verifying speed reduction with `[g]` `[a:b]`.

9.17.1 Expedition 1: Kitchen Science & Density Explorations (Challenges 9.1–9.10)

You are the lead investigator in the Kitchen Invention Studio! In this expedition, you explore material density, circular cross-sections, LED indicator paper circuits, and precision pendulum timing—turning kitchen-table curiosity into rigorous physical measurements.

Challenge 9.1: PLA Filament Cross-Sectional Area (r = 0.0875 cm)

Calibrating a tabletop 3D printer for a new roll of Midnight Navy bioplastic filament begins with precision physical measurement. Before calculating how much molten plastic squirts through the heated 0.4 mm brass nozzle, you must determine the exact circular cross-sectional area of the solid plastic strand. Grip a digital vernier caliper and close the ground steel jaws gently across the filament; the digital readout confirms an outer diameter of exactly 1.75 mm, giving a radius of 0.875 mm = 0.0875 cm.

Enter the radius, square it, and multiply by π using the dedicated hardware constant key: `.0875 [x²] [π] [×]` → `0.02405 cm²`. Notice how the four-register stack maintains complete intermediate visibility without scratch paper:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`.0875`	0	0	0	0.0875	Key in filament radius in centimeters (r = 0.0875 cm)
`[x²]`	0	0	0	0.007656	Square the radius ($r^2 = 0.00765625\ cm^2$)
`[π]`	0	0	0.007656	3.141593	Call the constant π; stack lifts squared radius into Register Y
`[×]`	0	0	0	0.024053	Multiply $r^2 \times \pi$ to find circular cross-sectional area ($A_f \approx 0.02405\ cm^2$)

Register X confirms $A_f \approx$ **0.02405 cm²**. This cross-sectional area serves as the fundamental dimensional multiplier for all subsequent extrusion volume calculations in your workshop.

Challenge 9.2: Extruded Volume for Sliced Model (L = 1,200 cm)

Your slicing software previews a custom spice-jar funnel for kitchen experiments, reporting that the print requires 1,200 cm (12 meters) of extruded filament. To conceptualize this physical length, unspool a 1 meter reference ribbon of scrap filament from the workbench spool holder and imagine twelve of these meter ribbons bundled together into the solid walls of your funnel.

Evaluate the extruded volume with `.02405 [ENTER] 1200 [×]` → `28.86 cm³ (T=0, Z=0, Y=0, X=28.86)`. Multiplying cross-sectional area by length ($V = A_f \times L$) produces exactly **28.86 cm^3** of extruded volume, establishing the solid volume of plastic required for the print.

Challenge 9.3: Kitchen Model Mass from Density (ρ = 1.24 g/cm^3)

With the funnel volume established at 28.86 cm^3, you must convert that cubic volume into mass in grams so you can verify the finished print on your kitchen gram scale. Placing a 1 cm × 1 cm × 1 cm solid PLA calibration cube on your digital balance yields 1.24 grams, establishing the density ρ = 1.24 g/cm^3.

Calculate the total part mass using `28.86 [ENTER] 1.24 [×]` → `35.79 g (T=0, Z=0, Y=0, X=35.7864)`. Multiplying volume by polymer density ($m = V \times \rho$) shows that the finished bioplastic funnel will weigh approximately **35.79 grams**.

Challenge 9.4: Spool Material Cost for Kitchen Print ($0.02/g)

Your maker space purchased a 1,000 gram spool of corn-based PLA for $20.00, establishing an exact material cost ratio of $0.02 per gram. Setting two shiny copper pennies next to each 1 gram calibration weight on your scale pan provides a concrete visual of this unit cost before committing the print job.

Compute the fabrication expense with `35.79 [ENTER] .02 [×] [$]` → `$0.72 (T=0, Z=0, Y=0, X=0.7158)`. Formatting the result in two-decimal currency mode confirms that fabricating the custom spice funnel costs just **$0.72** in raw bioplastic.

Challenge 9.5: Red Indicator LED Current-Limiting Resistor on 3V (V_f = 1.8V, I_f = 15mA)

To build a backlit density-column stage for kitchen test tubes, you construct a paper circuit using self-adhesive copper tape and a CR2032 lithium coin cell. Touching multimeter test leads across the battery terminals confirms a supply potential of 3.0 V, while the red indicator LED datasheet specifies a forward drop of 1.8 V at an operating current of 15 mA (0.015 A).

Apply Ohm's Law to calculate the required series resistor: **`[3] [ENTER] 1.8 [-] .015 [÷]`** → `80.0 Ω`. The stack first determines the excess headroom voltage before dividing by current:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[3]`	0	0	0	3	Key in coin cell supply voltage (V_s = 3.0 V)
`[ENTER]`	0	0	3	3	Stack lift locks supply voltage into Register Y
`1.8`	0	0	3	1.8	Key in red LED forward voltage drop (V_f = 1.8 V)
`[-]`	0	0	0	1.2	Subtract to find voltage across resistor: $V_R = V_s - V_f$ = 1.2 V
`.015`	0	0	1.2	0.015	Key in operating current in amperes (15 mA = 0.015 A)
`[÷]`	0	0	0	80	Divide V_R by I via Ohm's law (R = V / I = 80 Ω)

Register X displays 80.0 Ω, proving that the paper circuit requires an **80.0 Ω** current-limiting resistor to protect the semiconductor diode junction from burning out.

Challenge 9.6: Thermal Power Dissipation in 80 Ω Resistor (15mA)

Before taping the small carbon-film resistor down to construction paper, you must verify that it will not dissipate excessive heat. Examining a standard miniature through-hole resistor confirms it has a 1/4-watt (250 mW) thermal rating; as long as dissipated power remains safely below this threshold, the paper project stays cool to the touch.

Evaluate Joule's Law ($P = I^2 R$) using Superpower 4 (**[f] [LASTX]**) to recall the operating current without re-typing: **[3] [ENTER] 1.8 [-] .015 [÷] [f] [LASTX] [x²] [×]** → `0.018 W (18 mW)`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[3] [ENTER] 1.8 [-] .015 [÷]	0	0	0	80	Compute resistance R = 80 Ω; current 0.015 A stored in LASTX
[f] [LASTX]	0	0	80	0.015	Recall current I = 0.015 A from LASTX via Superpower 4
[x²]	0	0	80	2.2500×10^{-4}	Square current: $I^2 = (0.015)^2 = 0.000225\ A^2$
[×]	0	0	0	0.018	Multiply $R \times I^2$ to calculate dissipated power (P = 0.018 W)

Register X displays 0.018 W (**18 mW**). Because 18 mW is less than a tenth of the 250 mW ceiling, the resistor will stay completely safe and cool against the paper card.

Challenge 9.7: High-Intensity Green Inspection LED on 9V (V_f = 2.2V, I_f = 20mA)

To inspect clarity in homemade kombucha fermentation jars, you assemble a high-intensity green flashlight powered by a 9V alkaline battery. Snapping a heavy-duty battery clip onto the terminal and probing with multimeter leads confirms a 9.0 V open-circuit potential, while the green LED specifies a forward drop of 2.2 V at an operating current of 20 mA (0.020 A).

Determine the required current-limiting resistor with **[9] [ENTER] 2.2 [-] .020 [÷]** → `340.0 ⊠ (T=0, Z=0, Y=0, X=340)`. Subtracting the forward drop isolates the 6.8 V resistor voltage headroom, and dividing by current yields an exact required resistance of **340.0 Ω**.

Challenge 9.8: Power Rating for 340 Ω Resistor at 20mA

With the inspection light resistance established at 340 Ω, check whether a standard 1/4 W (0.25 W = 250 mW) resistor can safely handle the thermal load under continuous operation. Comparing the tiny 1/4 W package against a larger ceramic power resistor underscores the importance of pre-flight thermal budgeting.

Evaluate dissipated power using **[f] [LASTX]** : **[9] [ENTER] 2.2 [-] .020 [÷] [f] [LASTX] [x²] [×]** → `0.136 W (136 mW) (T=0, Z=0, Y=0, X=0.136)`. The calculation yields 0.136 W (**136 mW**); because this is comfortably below 250 mW, a standard 1/4 W resistor handles the inspection beam with ample margin.

Challenge 9.9: Kitchen Timer Pendulum Period (L = 0.50 m, g = 9.8 m/s^2)

You are building an escapement for a mechanical kitchen egg timer using a weighted string pendulum suspended from a cabinet knob. Suspending a steel washer from a 50 cm (0.50 m) strand of baker's twine and timing 10 swings with a stopwatch provides an empirical benchmark to compare against Galileo's theoretical period $T = 2\pi\sqrt{(L/g)}$.

Calculate the oscillation period using the SC-6 square root primitive: `[2] [π] [×] .5 [ENTER] 9.8 [÷] [f] [√x] [×]` → `1.42 seconds`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`[2] [π] [×]`	0	0	0	6.283185	Calculate constant $2\pi \approx 6.283185$
`.5`	0	0	6.283185	0.5	Key in string length in meters ($L = 0.50$ m); lifts 2π to Y
`[ENTER]`	0	6.283185	0.5	0.5	Stack lift duplicates length into Register Y
`9.8`	0	6.283185	0.5	9.8	Key in gravitational acceleration ($g = 9.8$ m/s^2)
`[÷]`	0	0	6.283185	0.05102	Divide length by gravity ($L/g \approx 0.051020$)
`[f] [√x]`	0	0	6.283185	0.225877	Take square root: $\sqrt{(L/g)} \approx 0.225877$
`[×]`	0	0	0	1.419227	Multiply by 2π to obtain oscillation period ($T \approx 1.42$ s)

Register X confirms an oscillation period of **1.42 seconds**. One full cycle takes 1.42 s, meaning each single half-swing tick advances the escapement gear every 0.71 seconds.

Challenge 9.10: Engineering a Bread-Kneading Metronome Pendulum (T = 1.50 s)

To maintain a steady rhythmic cadence while hand-kneading sourdough loaves, you decide to construct a metronome pendulum that ticks with a period of exactly 1.50 seconds. Rearranging the pendulum harmonic formula to solve for cord length gives $L = g\,T^2 / (4\pi^2)$. Measuring baker's twine against a meter stick allows you to cut the line to the precise theoretical dimension.

Execute the inverted formula on the stack: `9.8 [ENTER] 1.5 [x²] [×] [4] [π] [x²] [×] [÷]` → `0.559 meters`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`9.8`	0	0	0	9.8	Key in gravitational acceleration ($g = 9.8$ m/s^2)
`[ENTER]`	0	0	9.8	9.8	Lift gravity into Register Y
`1.5`	0	0	9.8	1.5	Key in target period in seconds ($T = 1.50$ s)
`[x²]`	0	0	9.8	2.25	Square period ($T^2 = 2.25$ s^2)
`[×]`	0	0	0	22.05	Multiply $g \times T^2 = 9.8 \times 2.25 = 22.05$
`[4]`	0	0	22.05	4	Key in constant 4; lifts numerator 22.05 into Register Y
`[π]`	0	22.05	4	3.141593	Call constant π; stack lifts
`[x²]`	0	22.05	4	9.869604	Square π: $\pi^2 \approx 9.869604$
`[×]`	0	0	22.05	39.478418	Multiply $4 \times \pi^2 \approx 39.478418$
`[÷]`	0	0	0	0.558533	Divide numerator by denominator to compute length ($L \approx 0.559$ m)

Register X displays 0.559 meters, confirming that trimming your suspension twine to exactly **0.559 meters** (55.9 cm) delivers the desired 1.50-second baker's tempo.

9.17.2 Expedition 2: Solar Power & Battery Lab (Challenges 9.11–9.20)

You are deploying field equipment for the Solar Power & Renewable Energy Lab! In this expedition, you track thermal gains in solar cookers, calibrate seed-launching catapult trajectories, measure greenhouse sprout velocities, and scale high-energy bakery nutrition for field researchers.

Challenge 9.11: Pizza-Box Solar Oven Heating Rate (20^° → 65^°C in 15 min)

Your field crew builds a cardboard pizza-box solar oven lined with crumpled newspaper insulation and reflective aluminum foil wings. Inserting a digital probe thermometer through the clear plastic glazing at solar noon reveals the interior absorber temperature climbing from 20^°C to 65^°C over a 15-minute exposure.

Calculate the heating velocity using `65 [ENTER] 20 [-] 15 [÷]` → `3.00 °C/min (T=0, Z=0, Y=0, X=3)`. Subtracting ambient temperature isolates the 45^°C thermal gain, and dividing by 15 minutes yields a brisk heating rate of **3.00^°C/min**.

Challenge 9.12: Solar Oven Temperature Percent Increase (20^° → 65^°C)

To measure how effectively your foil reflectors concentrate sunlight compared to ambient shade, calculate the percentage thermal increase achieved by the cooker over its starting temperature. Comparing side-by-side thermometers placed in outdoor shade (20^°C) and inside the solar cooker (65^°C) visually highlights this solar amplification.

Evaluate the percentage surge with `20 [ENTER] 65 [g] [%CHG]` → `+225.0% (T=0, Z=0, Y=20, X=225)`. In RPN, **`[g] [%CHG]`** computes $(X_{new} - Y_{base}) / Y_{base} \times 100\%$ while preserving the baseline temperature in Register Y, confirming an outstanding **+225.0%** thermal boost.

Challenge 9.13: Seed-Bomber Catapult Mean Launch Distance (150, 162, 156 cm)

To reseed a barren community garden plot, you deploy an elastic lever catapult that launches clay wildflower seed balls. Staking colored survey flags along the playground lawn marks landing coordinates across three test launches at 150 cm, 162 cm, and 156 cm.

Accumulate the launches into hardware statistical registers with **`[g] [CLΣ] 150 [Σ+] 162 [Σ+] 156 [Σ+] [g] [x]`** → `156.00 cm (T=0, Z=0, Y=0, X=156)`. Tapping the mean key recalls the average launch distance of exactly **156.00 cm** across the three trials.

Challenge 9.14: Catapult Consistency & Mean Absolute Deviation (MAD)

Field accuracy requires understanding launch dispersion around the target line. By placing counting tiles along a tape measure, you find the distances from each landing flag to the 156 cm center: |150-156| = 6 cm, |162-156| = 6 cm, and |156-156| = 0 cm.

Evaluate catapult consistency using **`[g] [CLΣ] 150 [Σ+] 162 [Σ+] 156 [Σ+] [g] [MAD]`** → `4.00 cm (T=0, Z=0, Y=3, X=4)`. Averaging the deviations demonstrates high mechanical consistency, with a Mean Absolute Deviation of only **4.00 cm** around the center target.

Challenge 9.15: Solar Nursery Bean Sprout Growth Velocity (15 mm → 75 mm in 5 days)

Inside the solar heated greenhouse nursery, tender pole bean seedlings are monitored daily. Aligning a clear millimeter ruler against the main stem confirms that a test sprout grew from an initial height of 15 mm to 75 mm over a five-day growth trial.

Compute the daily growth rate using `75 [ENTER] 15 [-] [5] [÷]` → `12.0 mm/day (T=0, Z=0, Y=0, X=12)`. The stack subtracts baseline height to reveal 60 mm of total expansion, and dividing by 5 days yields an average vertical growth velocity of **12.0 mm/day**.

Challenge 9.16: Total Seedling Height Percentage Surge (15 mm → 75 mm)

To assess vegetative vigor under passive solar heating, you calculate the overall percentage surge in seedling height. Modeling at a 1:5 scale with your 24-tile kit—placing a 3-tile stack (15 mm at 5 mm/tile) beside a 15-tile stack (75 mm)—provides an immediate physical proof that the 60 mm gain is four times the starting height.

Determine the percentage expansion with `15 [ENTER] 75 [g] [%CHG]` → `+400.0% (T=0, Z=0, Y=15, X=400)`. The single-tap percent change evaluation shows that the seedling surged by **+400.0%** over its initial height.

Challenge 9.17: Field Bakery Scaling: Flour for 12 Loaves (450 g per loaf)

Your solar research expedition needs hearty fresh sourdough bread for a weekend field encampment. A single artisan loaf formulation requires 450 grams of stone-ground flour; you need to scale the recipe to bake a 12-loaf batch for the entire team. Scooping flour into a large mixing tub on a tare-zeroed scale connects bulk pantry purchasing directly to recipe scaling.

Compute the bulk flour requirement with `450 [ENTER] 12 [×]` → `5,400 grams (T=0, Z=0, Y=0, X=5400)`. Multiplying loaf flour by batch size yields exactly **5,400 grams** (5.4 kg) of flour for the field bake.

Challenge 9.18: Artisan Hydration: Water at 65% for 5,400 g Flour

Professional bakers express all ingredient quantities as a percentage of total flour weight (baker's percentages). To achieve an open, tender crumb structure without a sticky dough, the sourdough recipe specifies 65% hydration water. Pouring water into a tared measuring pitcher on your digital gram scale lets you match the exact water weight.

Calculate hydration water using `5400 [ENTER] 65 [%]` → `3,510 grams (T=0, Z=0, Y=5400, X=3510)`. Tapping **[%]** calculates 65% of 5,400 while preserving the flour base in Register Y, confirming you need **3,510 grams** (3.51 liters) of water.

Challenge 9.19: Baker's Salt Percentage at 2% for 5,400 g Flour

In artisan bread chemistry, fine salt tightens gluten proteins and moderates wild yeast activity, standardizing at exactly 2.0% of flour mass. Weighing out salt crystals into a small pinch bowl on a sensitive gram scale provides a concrete lesson in precision chemical formulation.

Find the salt mass with `5400 [ENTER] [2] [%]` → `108 grams (T=0, Z=0, Y=5400, X=108)`. Register X confirms you need **108 grams** of salt, while Register Y continues to hold the 5,400 g flour base ready for further recipe scaling.

Challenge 9.20: High-Energy Trail Cookies: Scaling 2 (1 / 4) Cups Sugar × 4

To supply high-energy snacks for an uphill ridge hike, you quadruple an energy cookie recipe. The base recipe requires 2 (1 / 4) cups of dark brown sugar. Stacking four sets of nesting dry measuring cups (two 1-cup scoops and one 1/4-cup scoop each) visually demonstrates the fourfold scaling factor.

Execute mixed-fraction multiplication on the stack: `2 [.] 1 [.] 4 [ENTER] [4] [×] [a b/c]` → `9 cups (T=0, Z=0, Y=0, X=9)`. The SC-6 evaluates the mixed numeral and displays the scaled batch amount as exactly **9 cups** of brown sugar.

9.17.3 Expedition 3: The 3D Printing & Filament Workshop (Challenges 9.21–9.30)

You are the chief mechanical engineer in the 3D Printing & Rapid Prototyping Workshop! In this expedition, you design reduction gear trains, calibrate stepper motor speeds, test hydraulic syringe multipliers, size drone battery flight times, and angle solar tracker brackets for peak wattage.

Challenge 9.21: Direct-Drive Extruder Gear Reduction (16T → 64T)

To push stiff specialty filaments through a 3D printer hotend without stripping the plastic, you 3D-print a custom gear reduction for the direct-drive extruder. The small motor pinion gear has 16 teeth and meshes into a large 64-tooth driven gear. Marking tooth #1 with a silver felt-tip pen reveals that the motor must turn 4 complete revolutions to turn the large gear once.

Calculate the mechanical reduction ratio: `64 [ENTER] 16 [÷]` → `4.0 : 1 (T=0, Z=0, Y=0, X=4)`. Dividing driven teeth by driver teeth delivers an exact **4.0 : 1** gear reduction ratio, trading rotational speed for filament-gripping torque.

Challenge 9.22: Stepper Motor Output RPM (1,200 RPM ÷ 4)

The NEMA-17 stepper motor driving the extruder spins at an operational speed of 1,200 RPM. With the 4:1 mechanical reduction from Challenge 9.21 installed, you must find the final rotational speed of the hobbed filament feed pulley to program the slicer's microstepping firmware.

Evaluate final shaft speed with `1200 [ENTER] [4] [÷]` → `300 RPM (T=0, Z=0, Y=0, X=300)`. Dividing motor speed by the reduction ratio reveals that the filament drive wheel turns smoothly at **300 RPM**.

Challenge 9.23: Two-Stage Compound Gear Reduction ((40/10) × (30/15))

For an ultra-high-torque filament spool winding machine, you assemble two gear reduction stages on compound axles: Stage 1 pairs a 10-tooth driver with a 40-tooth gear, while Stage 2 pairs a 15-tooth driver with a 30-tooth gear on the secondary shaft. Turning the input crank by hand demonstrates the cumulative mechanical multiplication across both stages.

Calculate the compound gear reduction on the 4-register stack: `40 [ENTER] 10 [÷] 30 [ENTER] 15 [÷] [×]` → `8.0 : 1`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`40 [ENTER] 10 [÷]`	0	0	0	4	Compute Stage 1 reduction ratio: 40 / 10 = 4.0
`30 [ENTER]`	0	4	30	30	Key in Stage 2 driven gear (30T); lifts Stage 1 ratio into Y

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
15 [÷]	0	0	4	2	Compute Stage 2 reduction ratio: 30 / 15 = 2.0
[×]	0	0	0	8	Multiply stage ratios to find compound reduction: 4 × 2 = 8.0

Register X displays 8.0, confirming that the compound gear train provides an overall **8.0 : 1** mechanical advantage. Eight motor turns produce one turn of the heavy spool shaft with eight times the driving torque.

Challenge 9.24: Hydraulic Syringe Mechanical Advantage (d_2 = 4 cm, d_1 = 1 cm)

To evaluate the crush resistance of 3D-printed hollow structures, you construct a hydraulic test press using two fluid-filled syringes linked by vinyl tubing. The small input syringe has an internal diameter of d_1 = 1.0 cm, while the heavy output cylinder has a diameter of d_2 = 4.0 cm. By Pascal's Principle, hydraulic force scales with the cross-sectional area ratio: $A_2 / A_1 = (d_2 / d_1)^2$.

Evaluate the hydraulic force multiplier with **[4] [ENTER] [1] [÷] [x²]** → `16.0 × (T=0, Z=0, Y=0, X=16)`. Squaring the diameter ratio reveals that the hydraulic press delivers a remarkable **16.0×** force multiplication.

Challenge 9.25: Hydraulic Press Lift Capacity (10 N input × 16)

With the 16× hydraulic multiplier calibrated, calculate the crushing force exerted on a 3D-printed test bracket when an operator applies an effort force of 10 Newtons (approximately 1 kg of thumb pressure) to the small plunger. Hooking a spring scale to the input plunger confirms the 10 N applied effort.

Calculate the output crush force with `10 [ENTER] 16 [×]` → `160 Newtons (T=0, Z=0, Y=0, X=160)`. Multiplying input effort by the mechanical advantage confirms an output force of **160 Newtons**, capable of lifting a 16 kg test mass.

Challenge 9.26: Quadcopter Drone Battery Flight Time (1,200 mAh, 80% safe, 5 A)

You design an ultra-lightweight 3D-printed airframe for an indoor quadcopter powered by a 1,200 mAh LiPo battery. To preserve the battery chemistry and prevent irreversible voltage collapse, you restrict discharge to an 80% usable margin (0.80). Telemetry logs show that all four brushless motors draw a combined current of 5 A (5,000 mA) during hover.

Calculate the safe flight duration in minutes on the 4-register stack: `1200 [ENTER] .8 [×] 60 [×] 5000 [÷]` → `11.52 min`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
1200 [ENTER]	0	0	1200	1200	Enter nominal battery capacity in milliamp-hours (1,200 mAh)
.8 [×]	0	0	0	960	Multiply by 80% safe discharge limit: usable capacity is 960 mAh
60 [×]	0	0	0	57600	Multiply by 60 min/hr to convert to milliamp-minutes (57,600 mA·min)
5000	0	0	57600	5000	Key in total quadcopter hover current draw (5 A = 5,000 mA)
[÷]	0	0	0	11.52	Divide usable capacity by current to find flight time (57600 / 5000 = 11.52 min)

Register X displays 11.52 minutes, indicating that the quadcopter can safely hover for **11.52 minutes** before sounding the low-voltage telemetry alarm.

Challenge 9.27: Drone Flight Duration in Minutes and Seconds

To configure the countdown timer on the drone's radio transmitter, convert the decimal flight duration of 11.52 minutes into whole minutes and exact seconds. Watching the flight telemetry timer on an LCD transmitter display requires setting the alarm to an exact MM:SS boundary before touchdown.

Extract whole minutes and convert the fractional portion: `11 [ENTER] .52 [ENTER] 60 [×]` → `11 min 31 sec (T=0, Z=0, Y=11, X=31.2)`. Multiplying the 0.52 min decimal fraction by 60 reveals that the safe mission timer should be set to **11 minutes and 31 seconds**.

Challenge 9.28: Solar Tracker Bracket: Power at 30^° Morning Tilt (10 W peak × 0.866)

You 3D-print an articulated mounting bracket to align a mini solar panel toward the morning sun. When the sun is oriented at a 30^° incident angle relative to the panel normal, Lambert's Cosine Law reduces the effective solar flux factor to cos 30^° ≈ 0.866. The panel carries a rated peak output of 10 W under perpendicular light.

Calculate actual morning electrical power with `10 [ENTER] .866 [×]` → `8.66 Watts (T=0, Z=0, Y=0, X=8.66)`. Multiplying peak power by the projection coefficient shows the panel delivers **8.66 Watts** at a 30^° tilt angle.

Challenge 9.29: Solar Tracker Bracket: Power at 45^° Autumn Tilt (10 W peak × 0.707)

During late autumn afternoon testing, the sun drops lower in the sky to an oblique 45^° angle of incidence (cos 45^° ≈ 0.707). Measuring the output current and voltage with an inline USB tester plugged into the charging port confirms the reduced solar harvesting rate.

Compute the lower sun angle generation with `10 [ENTER] .707 [×]` → `7.07 Watts (T=0, Z=0, Y=0, X=7.07)`. The calculation reveals that output drops to **7.07 Watts** at 45^°, demonstrating why automated two-axis solar tracking increases daily energy capture.

Challenge 9.30: Kinetic Energy of Derby Test Car (m = 0.20 kg, v = 4 m/s)

You 3D-print a streamlined soapbox derby racer equipped with low-friction miniature ball bearings to evaluate ramp rolling friction. Placing the car on your balance verifies a mass of m = 0.20 kg (200 g). As the car crosses a photogate at the base of an inclined aluminum track, the timer clocks its terminal velocity at v = 4.0 m/s.

Evaluate kinetic energy on the stack using the classical formula KE = (1 / 2)mv^2: `.5 [ENTER] .2 [×] [4] [x²] [×]` → `1.60 Joules`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
`.5 [ENTER]`	0	0	0.5	0.5	Enter constant half-factor (1/2 = 0.5) into Register Y
`.2 [×]`	0	0	0	0.1	Multiply by car mass (0.20 kg): (1 / 2)m = 0.10 kg
[4]	0	0	0.1	4	Key in velocity (v = 4.0 m/s); lifts (1 / 2)m to Register Y

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[x²]	0	0	0.1	16	Square velocity: $v^2 = 4^2 = 16\ m^2/s^2$
[×]	0	0	0	1.6	Multiply $(1 / 2)m \times v^2 = 0.10 \times 16 = 1.60$ Joules

Register X displays 1.60 Joules, confirming that the rolling test car carries **1.60 Joules** of kinetic energy ready to be transferred to the arrestor stop.

9.17.4 Expedition 4: The Physics of Ramps, Wheels & Pulley Mechanics (Challenges 9.31–9.40)

You are the master builder in the Mechanics & Fabrication Workshop! In this expedition, you audit workshop tool purchases, split material expenses across team members, optimize hollow infill on interlocking snap cubes, rig tall ceiling pulley pendulums, and budget commemorative STEM medal manufacturing.

Challenge 9.31: Outfitting the Workshop: Tool Backpack 30% Discount ($56.00)

To carry your SC-6 calculator, calipers, multimeter, and 3D printing tools between home and school, you select an engineering field backpack with a regular retail price of $56.00, currently on sale for 30% off. Laying out play money or counting bills on the workbench helps visualize the 30% savings before walking to the hardware register.

In RPN, tapping [%] computes the discount dollar savings while preserving the base price in Register Y, allowing a single subsequent tap of [-] to find the net discounted price: `56 [ENTER] 30 [%] [-] [$]` → `$39.20 (T=0, Z=0, Y=0, X=39.2)`. The stack reveals the discounted sale price of **$39.20** before taxes.

Challenge 9.32: Workshop Equipment Sales Tax (7.5% on $39.20)

At the cash register, state and municipal sales tax of 7.5% is applied to your $39.20 discounted backpack purchase. Inspecting a printed store receipt shows how sales tax adds a fractional charge to every dollar spent.

Evaluate the final receipt total with `39.20 [ENTER] 7.5 [%] [+] [$]` → `$42.14 (T=0, Z=0, Y=0, X=42.14)`. Tapping [%] computes the exact tax amount ($2.94) while keeping $39.20 in Register Y, and tapping [+] totals the purchase at **$42.14**.

Challenge 9.33: Team Material Budget Split ($124.80 ÷ 6 members)

Six student builders in your school robotics club jointly order a shared assortment of stainless ball bearings, pulleys, and stepper motors totaling $124.80. To settle the group hardware invoice fairly, you divide the total expense into six equal shares so every team member contributes their exact portion.

Calculate the individual contribution using `124.80 [ENTER] [6] [÷] [$]` → `$20.80 (T=0, Z=0, Y=0, X=20.8)`. Formatting the result in currency mode confirms that each student maker owes **$20.80** toward the team parts kit.

Challenge 9.34: Interlocking Snap Cube Sliced Volume (2 cm × 2 cm × 2 cm)

You are modeling custom interlocking snap cubes for classroom math manipulatives. Holding a physical plastic snap cube in your hand and measuring each of its three orthogonal edges with a millimeter ruler confirms dimensions of exactly 2.0 cm × 2.0 cm × 2.0 cm.

Compute the solid cube volume with **[2] [ENTER] [2] [×] [2] [×]** → `8.0 cm³ (T=0, Z=0, Y=0, X=8)`. Multiplying base area by height on the stack confirms an overall volume of exactly **8.0 cm^3**.

Challenge 9.35: Snap Cube Theoretical Solid Mass (ρ = 1.24 g/cm^3)

If you were to 3D-print the 8.0 cm^3 snap cube completely solid (100% infill) out of standard corn-based PLA thermoplastic (ρ = 1.24 g/cm^3), what would the block weigh? Placing an eight-cube block array on your balance pan provides a physical feel for solid plastic density before optimizing the internal slicer infill.

Calculate theoretical solid mass with **[8] [ENTER] 1.24 [×]** → `9.92 grams (T=0, Z=0, Y=0, X=9.92)`. Multiplying volume by density confirms that a 100% solid snap cube weighs **9.92 grams**.

Challenge 9.36: Material Savings with 20% Gyroid Infill (3.1 g actual)

To conserve filament and speed up batch fabrication, you slice the snap cube with lightweight 20% gyroid internal infill and 2 solid perimeter shells. Placing the printed cube on your sensitive digital scale reveals that it weighs only 3.1 grams. Comparing the printed cube against the 9.92 g solid benchmark on a two-pan balance highlights the significant material savings.

Find the mass of filament saved with `9.92 [ENTER] 3.1 [-]` → `6.82 g saved (T=0, Z=0, Y=0, X=6.82)`. The subtraction confirms that using 20% gyroid infill saves **6.82 grams** of plastic per block while preserving structural rigidity.

Challenge 9.37: Workshop Ceiling Pulley Pendulum (L = 2.0 meters)

In the mechanics workshop, you rig a long pendulum cord from a heavy eye-hook in the tall ceiling (L = 2.0 meters) through a low-friction swivel pulley to observe slow harmonic oscillation. Suspending a solid brass plumb bob and releasing it from an initial 5^° deflection allows you to time its sweeping, deliberate swings with a digital stopwatch.

Determine the oscillation period using the harmonic period formula: **[2] [π] [×] [2] [ENTER] 9.8 [÷] [f] [√x] [×]** → `2.84 seconds`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
[2] [π] [×]	0	0	0	6.283185	Calculate constant factor 2π ≈ 6.283185
[2]	0	0	6.283185	2	Key in pendulum cord length (L = 2.0 meters); lifts 2π to Y
[ENTER]	0	6.283185	2	2	Duplicate length into Register Y
9.8	0	6.283185	2	9.8	Key in gravitational acceleration (g = 9.8 m/s^2)
[÷]	0	0	6.283185	0.204082	Divide length by gravity: L/g = 2.0 / 9.8 ≈ 0.204082
[f] [√x]	0	0	6.283185	0.451754	Take square root: √(L/g) ≈ 0.451754
[×]	0	0	0	2.838454	Multiply by 2π to find period (T ≈ 2.84 seconds)

Register X confirms an oscillation period of **2.84 seconds**. The tall ceiling rig swings at roughly half the frequency of a tabletop pendulum, illustrating the square-root relationship between length and time.

Challenge 9.38: Solar Cooker Thermal Dissipation in Cloud Shade (70^° → 40^°C in 20 min)

While testing thermal insulation materials on your solar cooker box, a dense afternoon storm cloud covers the sun. Logging the cooker's internal temperature drop over a 20-minute shading period shows the absorber cooling from 70^°C down to 40^°C. Plotting the data points on graph paper generates a smooth exponential cooling curve.

Compute the rate of thermal dissipation with `70 [ENTER] 40 [-] 20 [÷]` → `1.50 °C/min (T=0, Z=0, Y=0, X=1.5)`. Subtracting temperatures yields a 30^°C thermal loss, and dividing by 20 minutes indicates a steady cooling rate of **1.50^°C/min**.

Challenge 9.39: Quarter-Batch Polymer Clay Recipe (3 (1 / 2) cups milk ÷ 4)

You are mixing a small experimental batch of homemade casein polymer clay using warm milk and vinegar to cast custom pulley wheels. The master studio recipe calls for 3 (1 / 2) cups of milk, but you only want to mix a 1/4 test batch. Filling an 8-fluid-ounce measuring cup to the 7-ounce mark provides a physical benchmark for 7/8 cup.

Calculate the scaled liquid volume using mixed fraction division: `3 [.] 1 [.] 2 [ENTER] [4] [÷] [a b/c]` → `7/8 cup (T=0, Z=0, Y=0, X=0.875)`. Tapping **[a b/c]** formats the result into a proper fraction, confirming that the quarter-batch requires exactly **7/8 cup** of milk.

Challenge 9.40: Batch Award Medals Production Cost (50 × 14.5 g × 0.02/g)

To celebrate the culmination of the Maker Expedition, your team 3D-prints 50 commemorative medals for the school STEM fair. Placing 10 sample medals on the digital scale verifies an average mass of 14.5 grams each. With bulk spool filament priced at $0.02 per gram, you must compute the total material budget required to manufacture all 50 awards.

Evaluate the multi-step batch manufacturing equation on the 4-register stack: `50 [ENTER] 14.5 [×] .02 [×] [$]` → `$14.50`:

Keystroke	Register T	Register Z	Register Y	Register X	Operational Commentary
50	0	0	0	50	Key in total medals to print (50 medals)
[ENTER]	0	0	50	50	Duplicate medal count into Register Y
14.5	0	0	50	14.5	Key in mass per individual printed medal (14.5 g)
[×]	0	0	0	725	Multiply to calculate total batch filament mass (50 × 14.5 = 725 g)
.02	0	0	725	0.02	Key in filament spool cost per gram ($0.02/g)
[×]	0	0	0	14.5	Multiply mass by unit price to find total batch expense (725 × 0.02 = 14.50)
[$] | 0.00 | 0.00 | 0.00 | 14.50	Format result in currency mode				

Register X displays $14.50, proving that fabricating all 50 commemorative STEM fair medals requires exactly **$14.50** in raw bioplastic.

For Parents & Teachers: Standards Alignment Matrix

| Project | Common Core (CCSS-M) | Next Gen Science (NGSS) | Texas TEKS |

| :--- | :--- | :--- | :--- |

| **1. 3D Printing Mass & Cost** | 5.MD.C.5, 6.RP.A.3 | MS-PS1-2, MS-ETS1-1 | 5.4H, 6.4B |

| **2. Batch Manufacturing** | 5.NBT.B.7, 6.RP.A.2 | MS-ETS1-2 | 5.3E, 6.5A |

| **3. Paper Circuit Resistors** | 6.EE.A.2, 6.NS.B.3 | 4-PS3-2, MS-PS3-3 | 5.6A, 6.6B |

| **4. Pendulum & Gravity** | 6.EE.A.1, 6.SP.B.5 | MS-PS2-2, MS-PS3-1 | 5.6D, 6.6C |

| **5. Solar Oven Tracking** | 5.G.A.2, 6.RP.A.3 | 4-PS3-4, MS-PS3-4 | 5.6A, 6.8C |

| **6. Catapult Trajectory** | 6.SP.B.4, 6.SP.B.5 | MS-PS2-2, MS-PS3-1 | 6.12B, 6.13A |

| **7. Plant Growth Velocity** | 5.G.A.2, 6.RP.A.2 | 5-LS1-1, MS-LS1-5 | 5.9A, 6.4B |

| **8. Culinary Recipe Scaling** | 5.NF.B.4, 6.RP.A.3 | MS-PS1-2 | 5.3I, 6.4E |

| **9. Compound Gear Trains** | 6.RP.A.3, 6.EE.B.6 | MS-PS3-5, MS-ETS1-4 | 6.5A, 6.8D |

| **10. Hydraulic Syringe Lift** | 6.RP.A.3, 6.G.A.1 | MS-PS2-2 | 6.4B, 6.8B |

| **11. Drone Battery Budget** | 5.NBT.B.7, 6.RP.A.3 | MS-PS3-3, MS-ETS1-1 | 5.3G, 6.4H |

| **12. Solar Panel Cosine Tilt**| 6.EE.A.2, 6.RP.A.3 | MS-PS3-3, MS-ESS3-3 | 6.7A, 6.11A |

For comprehensive station rubrics and printable laboratory datasheets, consult Curriculum Station Worksheets: Singapore Dimensions Math .

9.18 What You Mastered & Looking Ahead

Congratulations, Explorer! You have completed the ultimate maker and mathematician journey across the SC-6 manual:

1. **The RPN Mental Model & Stack Mastery:** You replaced parentheses and equals-sign confusion with an intuitive, chronological four-register stack (X, Y, Z, T) that visualizes numbers moving just like physical blocks.
2. **Tactile Fractions & Rational Arithmetic:** You explored fraction equivalence, common denominators, and mixed numerals by aligning real blocks and tapping dedicated fraction hardware keys (`[a ⌧/c]` , `[f] [d/c]` , `[g] [SIMP]`).
3. **Spatial Geometry & Dimensional Scaling:** You measured perimeters, surface areas, and 3D volumes, using the Volvelle shadow projection and square-root primitives to connect 2D nets to real solids.
4. **Number Theory & Experimental Probability:** You unlocked the atomic building blocks of numbers with prime factorization, GCF, and LCM, and gathered real empirical data with the hardware probability engine (`[DICE]`) and statistical accumulators (`[Σ+]`).
5. **Cognitive Reflexes & Mental Math Fluency:** You trained your speed and accuracy in the Quiz Engine, mastering Vedic squaring, the 11s shortcut, and instant verification without scratch paper.
6. **Applied STEM & Engineering Design:** You connected mathematical theory directly to physical reality—budgeting 3D printer filament mass and spool costs, protecting LEDs with Ohm's Law, measuring Earth's gravity with pendulums, tuning gear ratios, and calculating drone flight endurance.

Your SC-6 is more than a calculator—it is your permanent laboratory workbench, your tactile compass, and your engineering partner.

To fabricate your own manipulatives in CAD or on a 3D printer, check out **Appendix A: Manipulative Blueprints & Physical Fabrication Guide**, review classroom stations in **Appendix B: Teacher Lesson Plans & Classroom Station Guide**, look up conversion factors in **Appendix C: Formulas, Physical Constants & Unit Conversions**, or inspect every button function in **Appendix D: Complete Keycap Directory & Operational Reference**.

Keep building, keep measuring, and keep exploring!

Appendix A: Manipulative Blueprints & Physical Fabrication Guide

CHAPTER BASELINE MODE: `[NUM]`

Hardware Engineering Specifications • Zero Mode Dependencies

Unlocked Keycaps Ribbon — Makers, Fabricators & STEM Educators

• **Hardware Specifications:** 42 mm Gridfinity Base Standard, 7U (~53.4 mm) Height Profile, Octagonal MultiBuild Joinery (`fn=8`).

• **Production Tolerances:** ±0.15 mm mechanical snap fit, 0.20 mm layer height, 15% gyroid infill.

• **Approved Materials:** Non-toxic PLA 2.0+ or PETG (Midnight Navy, Clean Lab White, Blue-Gray), 3 mm Baltic Birch Plywood, 3 mm Cast Acrylic.

• **Fabrication Modalities:** FDM 3D Printing, Vector Laser Cutting & Engraving, Printable Cardstock Cutouts.

SINGULARITY WARNING // HARDWARE RECOVERY

CHOKING HAZARD — SMALL PARTS & 3D PRINTING SAFETY (16 CFR § 1501 / ASTM F963):

The physical manipulative studios documented in this appendix (including the 14.0 × 14.0 × 7.0 mm Counting Tiles, Ten-Frame Counters, (1 / 12) Fraction Studio blocks, Prime Factor blocks, and Polyhedral Dice) contain small parts that fit within the CPSC small-parts test cylinder (31.7 mm diameter). **Not for children under 3 years of age.** Recommended for supervised educational use in Grades K–6 (ages 5+).

FDM Fabrication Inspection: Always print classroom manipulatives using certified non-toxic PLA or PETG filament with a minimum of 3 perimeter walls so parts cannot fracture under bite or drop loads. Before handing newly printed parts to students, an adult must inspect each component and remove all support brims, stringing wisps, or loose filament strands.

A.1 The Philosophy of Physical Fabrication in Math Education

Why fabricate physical math manipulatives when digital screens are everywhere? Cognitive science demonstrates that human spatial intuition develops through tactile interaction with real three-dimensional mass. When a child grasps a physical 10-rod, stacks an 84 mm fraction tower, or balances a lever beam, neural networks in the motor cortex directly reinforce the abstract mathematical concepts represented on the SC-6 calculator screen.

Following Jerome Bruner's **Concrete-Representational-Abstract (CRA)** framework *(Bruner, 1966)*, Zoltan Dienes' multi-embodiment principle *(Dienes, 1960)*, and David Macaulay's vision of understandable physical structures *(Macaulay, 2016)*, physical tools must satisfy three rigorous criteria:

1. **Mathematical Invariance:** A 10-rod must equal exactly 10 unit cubes in length, volume, and mass. A (1 / 2) fraction tower must equal two (1 / 4) towers with zero dimensional loss.
2. **Universal Accessibility:** Every school and homeschool must be able to produce these tools using accessible fabrication methods: high-precision 3D printing, rapid laser cutting, or printable scissors-and-glue cardstock.
3. **Modular Classroom Organization:** All components must interlock within standardized storage bins to eliminate lost pieces and chaotic transitions.

The 3-Tier Fabrication Spectrum

| Fabrication Tier | Primary Medium & Tooling | Engineering Specifications |

| :--- | :--- | :--- |

| **Tier 1: FDM 3D Printing** | 0.2 mm PLA / PETG | Zero support structures, 45^° overhangs, snap joints |

| **Tier 2: Laser Cutting** | 3 mm Baltic birch plywood / acrylic | 0.15 mm kerf compensation, finger-joint assembly |

| **Tier 3: Cardstock Cutouts** | 110 lb archival paper | Folding tabs, classroom scissors, glue sticks |

A.2 The Zack Freedman Gridfinity Modular Standard & Dimensional Envelope

All physical math manipulatives in the StackCalc Learning Lab are engineered to the **Zack Freedman Gridfinity modular standard**:

- **Grid Module Pitch:** Exactly 42.0 mm × 42.0 mm center-to-center pitch.
- **Vertical Profile:** Normalized to **7U height (53.4 mm overall height with standard 4.4 mm stacking lip)**. This allows every kit in the collection to sit flush in classroom storage bins, rollable carts, or teacher drawers.
- **Octagonal MultiBuild Joinery:** Interconnecting trays and snap joints employ an octagonal profile (fn=8) featuring 45^° self-supporting overhangs that print cleanly without support structures.

Gridfinity 7U Standardization Profile

| Dimensional Feature | Metric Dimension | Functional Role |

| :--- | :---: | :--- |

| **Top Stacking Rim** | 4.4 mm | Mates with bin base above for secure modular stacking |

| **Outer Box Usable Wall** | 45.0 mm | Interior vertical clearance for manipulatives |

| **Bottom Base Profile** | 4.0 mm | Chamfered Gridfinity footprint with self-locating ribs |

| **Total Enclosure Height** | **53.4 mm** | Exact standardized 7U specification |

| **Standard Footprint 1 (3×1×7U)** | 125.5 × 41.5 × 53.4 mm | Compact bin for arrays, counters, and dominos |

| **Standard Footprint 2 (3×2×7U)** | 125.5 × 84.0 × 53.4 mm | Double-wide bin for base-ten blocks and balance scales |

A.2.1 Gridfinity Base Geometry & Dimensional Clearances

The bottom base profile of each storage box incorporates standard Gridfinity geometry:

- A 2.6 mm 45^° bottom chamfer allows smooth self-locating insertion into baseplates.
- A 0.8 mm vertical clearance step prevents debris binding.
- Corner radiuses are maintained at 3.75 mm to ensure complete compatibility with injection-molded and 3D-printed Gridfinity trays.

Gridfinity Profile Zone	Dimension	Mechanical Role
Module Pitch	42.0 mm × 42.0 mm	Universal classroom bin and baseplate grid standard
Bin Outer Footprint	41.5 mm (0.5 mm slip clearance)	Zero-bind insertion and removal for young hands

Gridfinity Profile Zone	Dimension	Mechanical Role
Stepped Base Chamfer	45^° self-centering bevel (2.6 mm height)	Guides bins smoothly into baseplate receptacles

A.3 Additive Manufacturing (3D Printing) Specification Matrix

All 3D models in the repository are optimized for single-extruder desktop FDM printers with **zero supports required**:

Slicing Parameter	Classroom Standard	Precision Gearing	Structural Rationale
Nozzle Diameter	0.40 mm Brass / Hardened Steel	0.40 mm	Universal desktop standard
Layer Height	0.20 mm (Standard)	0.12 mm (Planetary Gears)	Balances print speed with tactile finish
Wall Perimeters	3 perimeters (1.2 mm wall)	4 perimeters (1.6 mm)	Resists crushing during energetic desk drops
Infill Pattern	15% Gyroid Infill	25% Gyroid Infill	Omnidirectional structural stiffness
Top Solid Layers	4 solid layers (0.8 mm)	5 solid layers (0.6 mm)	Prevents infill telegraphing on faces
Bottom Solid Layers	3 solid layers (0.6 mm)	4 solid layers (0.48 mm)	Water-tight base closure
Bed Adhesion	Smooth PEI / Textured PEI	Smooth PEI (Gears)	Clean specular bottom face
Support Structure	**ZERO SUPPORTS (Disabled)**	**ZERO SUPPORTS (Disabled)**	All overhangs designed ≤ 45^°
Print Speed	150 - 250 mm/s	80 - 120 mm/s	Prevents corner ringing and dimensional drift
Cooling Fan	100% after Layer 2	100% after Layer 2	Sharp overhang definition

A.3.1 Thermal Profiles by Material

Material	Nozzle Temp	Bed Temp	Approved Application
Sunlu White PLA 2.0+	210^°C - 215^°C	55^°C - 60^°C	Storage bins, frames
Sunlu Midnight Navy PLA	215^°C - 220^°C	60^°C	Chassis, dark contrast
White PETG	235^°C - 245^°C	70^°C - 75^°C	Gears, flex snap studs
Dual-Color Silk PLA	215^°C - 225^°C	60^°C	Fraction towers, dice

A.4 Laser-Cutting Specifications & Vector Kerf Compensation

For schools equipped with CO_2 or diode laser cutters, flat 2D manipulative nets, balance scale beams, and protractors can be fabricated in seconds from 3.0 mm Baltic birch plywood or cast acrylic.

A.4.1 Kerf Compensation Mechanics

A laser beam vaporizes a narrow kerf of material (~ 0.15 mm to 0.20 mm wide). If parts are cut on the nominal line, slots will fit loosely and finger joints will wobble. To achieve tight friction fits:

- **Outside Edges:** Offset cut vectors outward by +(1 / 2) Kerf = +0.075 mm.

- **Inside Holes / Slots:** Offset cut vectors inward by -(1 / 2) Kerf = -0.075 mm.

Line Color	RGB Value	Vector Operation	Settings (40W CO_2)
Pure Red	`#FF0000`	Outer Cut (Final)	Speed 15, Power 100%
Pure Blue	`#0000FF`	Inner Hole Cut	Speed 15, Power 100%
Pure Magenta	`#FF00FF`	Vector Score Line	Speed 80, Power 20%
Pure Black	`#000000`	Raster Engrave	Speed 100, Power 40%

A.5 Printable Paper & Cardstock Blueprint Cutouts

For classrooms without digital fabrication machinery, all six manipulatives can be printed on standard desktop color printers:

- **Paper Weight:** Minimum 110 lb cardstock (199 g/m^2) or 65 lb cover stock.
- **Scoring Protocol:** Lightly score dashed fold lines using an empty ballpoint pen or bone folder against a metal straightedge before folding.
- **Adhesive:** Acid-free PVA glue stick or 6 mm double-sided permanent craft tape applied to designated glue tabs.

A.6 Blueprint 1: The Ten-Frame Studio (ten_frame_tray)

The Ten-Frame Studio provides a tactile bridge for early elementary counting, subitizing, and combinations to 10 and 20 (CCSS 1.OA.C.6).

Dimensional Blueprint: Ten-Frame Tray

Parameter	Metric Specification	Engineering / Classroom Notes
Overall Dimensions	125.5 × 41.5 × 12.0 mm	Fits within standard Gridfinity 3 × 1 bin
Well Architecture	Dual 2 × 5 array	10 captive counter wells for subitizing
Well Pocket	18.0 mm dia × 4.0 mm deep	Chamfered 45^° lip for effortless token removal
Well Pitch	20.0 mm center-to-center	Ergonomic spacing for small fingers
Bridge Separation	5.0 mm raised central rib	Distinguishes first 5 from second 5 (make-ten landmark)
Interlocking Lugs	Octagonal MultiBuild dovetails	Links two trays to form a 20-frame matrix

A.6.1 Two-Color Flip Counters

- **Diameter:** 16.5 mm (slips freely into 18.0 mm well).
- **Thickness:** 3.5 mm with 0.8 mm center rim.
- **Face A (Yellow):** Polished specular concave depression (simulating 10-frame dot).
- **Face B (Red):** Concentric tactile rings for sight-impaired differentiation.

A.6.2 OpenSCAD Parametric Code: Ten-Frame Tray & Flip Counters

```
// ============================================================================
// STACKCALC SC-6: TEN-FRAME TRAY & CAPTIVE COUNTERS GENERATOR
// Compatible with Gridfinity 3x1x7U Storage Footprints
// ============================================================================
$fn = 50;

tray_length   = 125.5;
tray_width    = 41.5;
tray_height   = 12.0;
well_radius   = 9.0;
well_depth    = 4.5;
pitch_x       = 20.0;
pitch_y       = 18.0;
central_rib   = 4.0;

module ten_frame_tray() {
    difference() {
        // Main Chamfered Body
        hull() {
            for (dx = [-tray_length/2 + 3, tray_length/2 - 3])
                for (dy = [-tray_width/2 + 3, tray_width/2 - 3])
                    translate([dx, dy, 0])
                        cylinder(r=3.0, h=tray_height, center=true);
        }

        // 2x5 Counter Well Matrix with Central Divider Rib
        for (row = [-0.5, 0.5]) {
            for (col = [-2:2]) {
                x_pos = col * pitch_x + (col >= 0 ? central_rib/2 : -central_rib/2);
                y_pos = row * pitch_y;
                translate([x_pos, y_pos, tray_height/2 - well_depth/2 + 0.1])
                    cylinder(r=well_radius, h=well_depth + 0.2, center=true);
            }
        }

        // Finger Grip Retrieval Channels
        translate([0, 0, tray_height/2 - 1.5])
            cube([tray_length - 8, 3.0, 3.2], center=true);
    }
}

module flip_counter() {
    difference() {
        cylinder(r=8.25, h=3.5, center=true);
        // Face A: Concave spherical cup
        translate([0, 0, 2.5])
            sphere(r=6.0);
        // Face B: Tactile blind concentric rings
        translate([0, 0, -1.8])
            difference() {
                cylinder(r=6.0, h=0.8, center=true);
                cylinder(r=4.5, h=1.0, center=true);
            }
    }
}

// Render Default Assembly
ten_frame_tray();
translate([0, 50, 0]) flip_counter();
```

A.7 Blueprint 2: Place Value Base-Ten Manipulative Studio

Base-ten blocks provide the physical foundation for multi-digit addition, subtraction, regrouping, and decimals (CCSS 2.NBT.A.1, 5.NBT.A.1).

Base-Ten Block Dimensional Audit

| Block Unit | Metric Dimensions | Volume (V) | Standard PLA Mass (m, ρ=1.24) |

| :--- | :---: | :---: | :---: |

| **Unit Cube (1s)** | 10.0 × 10.0 × 10.0 mm | 1.0 cm^3 | 1.24 g |

| **Ten-Rod (10s)** | 10.0 × 10.0 × 100.0 mm | 10.0 cm^3 | 12.4 g |

| **Hundred-Flat (100s)** | 10.0 × 100.0 × 100.0 mm | 100.0 cm^3 | 124.0 g |

| **Thousand-Cube (1,000s)** | 100.0 × 100.0 × 100.0 mm | 1,000.0 cm^3 | 1,240.0 g |

Physical Invariance: Exactly 10 Unit Cubes fit along the edge of a Ten-Rod; exactly 10 Ten-Rods tile a Hundred-Flat; exactly 10 Hundred-Flats form the Thousand-Cube.

A.7.1 Top-Down Net: Printable Hundred-Flat Net (Scale 1:1)

LID 100x10mm

Left End Panel	Top Face Panel	Right End Panel	Bottom Face Panel
100 × 10 mm	100 × 100 mm	100 × 10 mm	100 × 100 mm

BOTTOM 100x10mm

A.7.2 OpenSCAD Parametric Code: Complete Base-Ten System

```
// ============================================================================
// STACKCALC SC-6: COMPLETE BASE-TEN MANIPULATIVE SYSTEM
// Precision 10 mm Metric Standards with Registered Interlocking Pins
// ============================================================================

unit_size = 10.0;
groove_w  = 0.6;
groove_d  = 0.4;

module unit_cube() {
    difference() {
        cube([unit_size, unit_size, unit_size], center=true);
        // Subtle edge chamfers
        for (r = [0, 90, 180, 270]) {
            rotate([0, 0, r])
                translate([unit_size/2, unit_size/2, 0])
                    rotate([0, 0, 45])
                        cube([0.5, 0.5, unit_size + 1], center=true);
        }
    }
}

module ten_rod() {
    difference() {
        cube([unit_size * 10, unit_size, unit_size], center=false);
        // Engrave 9 unit divider lines on all 4 axial faces
        for (i = [1:9]) {
            translate([i * unit_size - groove_w/2, -0.1, unit_size - groove_d])
                cube([groove_w, unit_size + 0.2, groove_d + 0.1]);
            translate([i * unit_size - groove_w/2, -0.1, -0.1])
                cube([groove_w, unit_size + 0.2, groove_d + 0.1]);
            translate([i * unit_size - groove_w/2, unit_size - groove_d, -0.1])
                cube([groove_w, groove_d + 0.1, unit_size + 0.2]);
            translate([i * unit_size - groove_w/2, -0.1, -0.1])
                cube([groove_w, groove_d + 0.1, unit_size + 0.2]);
```

```
        }
    }
}

module hundred_flat() {
    difference() {
        cube([unit_size * 10, unit_size * 10, unit_size], center=false);
        // Grid scoring across 10x10 top surface
        for (i = [1:9]) {
            translate([i * unit_size - groove_w/2, -0.1, unit_size - groove_d])
                cube([groove_w, unit_size * 10 + 0.2, groove_d + 0.1]);
            translate([-0.1, i * unit_size - groove_w/2, unit_size - groove_d])
                cube([unit_size * 10 + 0.2, groove_w, groove_d + 0.1]);
        }
    }
}

// Render Showcase Grid
unit_cube();
translate([20, 0, 0]) ten_rod();
translate([20, 20, 0]) hundred_flat();
```

A.8 Blueprint 3: Fraction Studio Proportional Towers & Tiles

The Fraction Studio uses an exact **84.0 mm master height standard** (84 is divisible by 1, 2, 3, 4, 6, 8, 12), eliminating rounding errors during fraction additions (CCSS 3.NF.A.1, 4.NF.A.1).

Fraction Value	Nominal Height	Laser Vector Score	Silk Filament Color Palette
Whole (1)	84.00 mm	`"1.00 / 100%"`	Clean Lab White
Halves (1/2)	42.00 mm	`"1/2 / 0.50"`	Ocean Cyan
Thirds (1/3)	28.00 mm	`"1/3 / 0.333"`	Red + Gold Silk
Fourths (1/4)	21.00 mm	`"1/4 / 0.25"`	Red + Blue Silk
Sixths (1/6)	14.00 mm	`"1/6 / 0.167"`	Sunburst Yellow
Eighths (1/8)	10.50 mm	`"1/8 / 0.125"`	Emerald Green
Twelfths (1/12)	7.00 mm	`"1/12 / 0.083"`	Violet Purple

A.8.1 Zero-Loss Stacking Lap Joint

Unlike toy building bricks that lose vertical height when pressed together due to internal receiving cavities, the Fraction Studio towers incorporate a **stepped lap joint**:

- A 3.0 mm interlocking tongue fits into an adjacent cutout without altering the external 84.0 mm datum.
- Two (1 / 2) blocks stacked vertically in the **Twin Comparator Well** measure exactly 84.00 mm, perfectly level with the 1 WHOLE reference tower.

Lap Joint Feature	Nominal Dimension	Mechanical Function
Stacking Tongue	3.0 mm axial projection	Engages recessed lower socket for lateral alignment
Recessed Counterbore	3.2 mm depth (0.2 mm axial clearance)	Ensures outer shoulders seat flush with zero height gain

Lap Joint Feature	Nominal Dimension	Mechanical Function
Outer Reference Datum	84.0 mm whole-unit height	Guarantees (1 / 2) + (1 / 3) + (1 / 6) = 84.0 mm exactly

A.8.2 OpenSCAD Parametric Code: Fraction Tower Generator

```
// ============================================================================
// STACKCALC SC-6: FRACTION STUDIO PROPORTIONAL TOWER GENERATOR
// Generates Proportional Prisms with Embossed Fractions, Decimals, & %
// ============================================================================
master_h   = 84.0;
tower_w    = 20.0;
tower_d    = 20.0;
joint_lip  = 3.0;

module fraction_block(denominator=4, numerator=1, label="1/4", dec_label="0.25", pct_label="25%") {
    block_h = master_h * (numerator / denominator);

    difference() {
        union() {
            // Main Extrusion Block
            cube([tower_w, tower_d, block_h], center=false);
            // Stacking Tongue (Top)
            translate([tower_w/4, tower_d/4, block_h])
                cube([tower_w/2, tower_d/2, joint_lip]);
        }

        // Stacking Socket (Bottom)
        translate([tower_w/4 - 0.15, tower_d/4 - 0.15, -0.1])
            cube([tower_w/2 + 0.3, tower_d/2 + 0.3, joint_lip + 0.2]);

        // Front Face Embossed Fraction Text
        translate([tower_w/2, -0.1, block_h/2])
            rotate([90, 0, 0])
                linear_extrude(height=0.6)
                    text(label, size=block_h > 12 ? 6.0 : 4.0, halign="center", valign="center");

        // Right Face Decimal Value
        translate([tower_w + 0.1, tower_d/2, block_h/2])
            rotate([90, 0, 90])
                linear_extrude(height=0.6)
                    text(dec_label, size=block_h > 12 ? 4.5 : 3.0, halign="center", valign="center");
    }
}

// Render 1/1 Whole, 1/2 Half, and 1/4 Quarter
fraction_block(1, 1, "1", "1.0", "100%");
translate([30, 0, 0]) fraction_block(2, 1, "1/2", "0.50", "50%");
translate([60, 0, 0]) fraction_block(4, 1, "1/4", "0.25", "25%");
```

A.9 Blueprint 4: Equal-Arm Pan Balance Scale (balance_scale.scad)

The balance scale is the premier physical model for algebraic equality, solving for unknowns, and mass comparison (CCSS 6.EE.B.7).

Equal-Arm Balance Scale Blueprint

| Component | Metric Dimension | Engineering Specification |

| :--- | :---: | :--- |

| **Fulcrum Height** | 120.0 mm | Stable tabletop elevation above bench |

| **Beam Length** | 240.0 mm | Symmetrical 120.0 mm lever arm per side |

| **Fulcrum Pivot** | 60^° V-knife | Hardened knife-edge resting in low-friction Delrin cradle |

| **Graduated Notches** | 10 slots per arm | Exactly 10.0 mm rider intervals for torque labs |

| **Pan Diameter** | 60.0 mm | Suspended dish with three 120^° string anchor holes |

| **Suspension Line** | 100.0 mm | High-tensile braided Dacron cord |

A.9.1 OpenSCAD Parametric Code: Balance Beam & Fulcrum

```
// ============================================================================
// STACKCALC SC-6: EQUAL-ARM PAN BALANCE SCALE
// High-Sensitivity Knife-Edge Fulcrum and Graduated Lever Arm
// ============================================================================
$fn = 40;
arm_radius   = 120.0;
beam_thick   = 4.0;
beam_height  = 16.0;

module balance_beam() {
    difference() {
        // Tapered Balance Beam
        hull() {
            translate([0, 0, 0])
                cylinder(r=beam_height/2, h=beam_thick, center=true);
            translate([-arm_radius, 0, 0])
                cylinder(r=5.0, h=beam_thick, center=true);
            translate([arm_radius, 0, 0])
                cylinder(r=5.0, h=beam_thick, center=true);
        }

        // Knife-Edge Fulcrum Pivot Pocket (60 deg V-Notch)
        translate([0, -beam_height/4, 0])
            rotate([0, 0, 45])
                cube([6.0, 6.0, beam_thick + 1], center=true);

        // End Suspension Eyelets (Pan String Holes)
        translate([-arm_radius, 0, 0]) cylinder(r=1.5, h=beam_thick + 1, center=true);
        translate([arm_radius, 0, 0])  cylinder(r=1.5, h=beam_thick + 1, center=true);

        // 10 Calibrated Rider Mass Slots on Left and Right Arms
        for (i = [1:9]) {
            translate([-i * 12.0, 4.0, 0]) cube([1.0, 3.0, beam_thick + 1], center=true);
            translate([i * 12.0, 4.0, 0])  cube([1.0, 3.0, beam_thick + 1], center=true);
        }
```

```
    }

    // Vertical Indicator Needle Pointer
    translate([0, 25.0, 0])
        cylinder(r1=2.0, r2=0.5, h=50.0, center=true);
}

module pan_dish() {
    difference() {
        // Spherical Pan Body
        sphere(r=30.0);
        translate([0, 0, 30.0]) cube([70.0, 70.0, 60.0], center=true);
        translate([0, 0, 1.5]) sphere(r=28.5);

        // 3 Equidistant Suspension Eyelets
        for (a = [0, 120, 240]) {
            rotate([0, 0, a])
                translate([28.0, 0, -2.0])
                    cylinder(r=1.2, h=10.0, center=true);
        }
    }
}

balance_beam();
translate([0, -60, 0]) pan_dish();
```

A.10 Blueprint 5: Circular 360^° Protractor & Planetary Angle Wheel

Students transition from elementary clock reading (modulo-60) to angular geometry (360^°) using the Planetary Clock dial and full-circle protractor (CCSS 4.MD.C.5, 4.MD.C.6).

360° Circular Protractor Specifications

Parameter	Metric Dimension	Engineering Specification
Outer Diameter	100.0 mm	Full circular protractor disc
Center Bore	8.0 mm	Pivot axle hole (mates to clock gear shaft)
Degree Graduations	1^°, 5^°, 10^° ticks	1^° ticks (0.8 mm), 5^° (1.8 mm), 10^° major labeled
Quadrant Badges	Compass cardinal points	0^° (East), 90^° (North), 180^° (West), 270^° (South)
Radian Equivalence	Concentric inner track	Direct angular landmarks (0, π/2, π, 3π/2, 2π)

A.10.1 OpenSCAD Parametric Code: 360^° Protractor Wheel

```
// ============================================================================
// STACKCALC SC-6: 360 DEGREE CIRCULAR PROTRACTOR & VOLVELLE DIAL
// Features 1-Degree Laser-Grade Ticks and Concentric Radian Scales
// ============================================================================
$fn = 120;
dial_r   = 50.0;
center_d = 8.0;
thick    = 2.0;

module protractor_dial() {
    difference() {
        // Base Disc
        cylinder(r=dial_r, h=thick, center=true);

        // Center Axle Bore
        cylinder(d=center_d, h=thick + 1, center=true);

        // 360 Degree Tick Marks
        for (a = [0:359]) {
            tick_len = (a % 10 == 0) ? 5.0 : ((a % 5 == 0) ? 3.0 : 1.5);
            rotate([0, 0, a])
                translate([dial_r - tick_len/2, 0, thick/2 - 0.25])
                    cube([tick_len, 0.4, 0.6], center=true);
        }

        // Four Crosshair Alignment Channels
        cube([dial_r * 2 - 14, 0.6, thick + 0.1], center=true);
        cube([0.6, dial_r * 2 - 14, thick + 0.1], center=true);
    }
}

protractor_dial();
```

A.11 Blueprint 6: Geoboard Layouts (Cartesian & Isometric)

Geoboards allow students to explore polygon perimeters, coordinate graphing, and Pick's Theorem for plane area (A = i + (b / 2) - 1) using elastic rubber bands (CCSS 3.MD.C.5, 5.G.A.1).

5×5 Cartesian Geoboard Blueprint

Parameter	Metric Dimension	Functional Role
Plate Dimensions	120.0 × 120.0 × 8.0 mm	Sturdy base plate with non-slip desk feet
Pin Matrix	5 × 5	square grid	25 retention pegs spanning coordinates (0,0) to (4,4)
Pin Pitch	20.0 mm	Standard center-to-center Euclidean unit spacing
Pin Geometry	6.0 mm height, 4.0 mm shank	Undercut mushroom head (6.0 mm dia) securely traps bands

A.11.1 The Mushroom Retention Peg Profile

Conventional 3D-printed pegs allow rubber bands to slip upward and fly across the classroom. The SC-6 geoboard features an **undercut mushroom cap**:

- Shank diameter: 4.0 mm.
- Mushroom head: 6.0 mm diameter with a 45^° self-supporting bottom chamfer that prints cleanly without supports while securely trapping multi-strand rubber bands.

Peg Feature	Nominal Dimension	Mechanical Function
Top Retention Cap	6.0 mm diameter	Prevents elastic bands from slipping off under tension
Undercut Chamfer	45^° conical transition	Traps rubber bands downward against the shank
Cylindrical Shank	4.0 mm diameter	Resists lateral shear forces across the 5 × 5 geoboard grid

A.11.2 OpenSCAD Parametric Code: Dual Cartesian & Isometric Geoboard

```
// ============================================================================
// STACKCALC SC-6: DUAL CARTESIAN & ISOMETRIC GEOBOARD
// Reversible Board: Face A = 5x5 Square Grid; Face B = Triangular Isometric
// ============================================================================
$fn = 30;
board_w    = 120.0;
board_h    = 8.0;
pitch      = 20.0;
shank_d    = 4.0;
cap_d      = 6.0;
peg_h      = 8.0;

module mushroom_peg() {
    // Vertical Shank
    cylinder(d=shank_d, h=peg_h - 2.0);
    // 45 Degree Self-Supporting Retention Undercut
    translate([0, 0, peg_h - 2.0])
        cylinder(d1=shank_d, d2=cap_d, h=1.0);
    // Flat Mushroom Head
    translate([0, 0, peg_h - 1.0])
        cylinder(d=cap_d, h=1.0);
}

module geoboard() {
    difference() {
        // Baseplate with Rounded Safety Corners
        hull() {
            for (x = [-board_w/2 + 5, board_w/2 - 5])
                for (y = [-board_w/2 + 5, board_w/2 - 5])
                    translate([x, y, 0])
                        cylinder(r=5.0, h=board_h, center=true);
        }
        // Laser / Slicer Coordinate Engravings
        translate([0, 0, board_h/2 - 0.3])
            linear_extrude(height=0.4)
                text("STACKCALC GEOBOARD 5x5", size=5, halign="center", valign="center");
    }

    // 5x5 Square Peg Matrix on Top Face
    translate([0, 0, board_h/2]) {
        for (gx = [-2:2]) {
            for (gy = [-2:2]) {
                translate([gx * pitch, gy * pitch, 0])
                    mushroom_peg();
            }
        }
    }
}

geoboard();
```

A.12 3D Printing Troubleshooting & Dimensional Calibration

Achieving reliable press-fit joinery and true mathematical tolerances (± 0.15 mm) across classroom desktop 3D printers requires careful slicer tuning:

Defect Symptom	Root Slicer Cause	Corrective Slicer Setting
Elephant's Foot Flange	First layer squish over-extrusion	Initial Layer Horizontal Expansion = -0.15 mm
Pegs Too Tight / Bind	Horizontal XY hole shrinkage	XY Hole Compensation: +0.10 mm to +0.15 mm
Z-Seam Jam in Well	Random seam placement leaves blobs	Z-Seam Alignment: Set to "Sharpest Corner"
Fraction Tower Curl	Inadequate bed adhesion on sharp corners	Bed Temp: Increase to 60^°C; add 3 mm brim
Gear Teeth Binding	Over-extrusion on perimeter walls	Extrusion Multiplier: Calibrate Flow to 96%

A.13 Kinematic Transmission: 12:1 Compound Planetary Clock (monolithic_clock.scad)

The StackCalc Planetary Geared Clock manipulative provides an exact mechanical visualization of continuous modulo-60 time arithmetic (CCSS 2.MD.C.7, 3.MD.A.1). Unlike cheap toy clocks with independent loose hands or 60:1 gear friction that jams in small hands, this mechanism uses a **two-stage compound planetary reduction**:

Planetary Gear Component	Teeth / Count	Module & Geometry	Kinematic Role & Mounting
Sun Gear (Input)	12 teeth	Module m = 0.8 mm, 20^° pressure angle	High-speed central input driven by minute arbor
Planet Gears (3×)	18 teeth	Module m = 0.8 mm, spur involute	Mounted symmetrically at 120^° on spider carrier
Ring Gear (Internal)	48 teeth	Module m = 0.8 mm, internal pitch	Fixed statically to outer chassis housing

Kinematic Gear Ratio Formulation:

Stage 1 Ratio = (Ring Teeth + Sun Teeth / Sun Teeth) = (48 + 12 / 12) = (60 / 12) = 5.0000 : 1

Stage 2 Secondary Planetary Carrier Reduction = 2.4000 : 1

Overall Compound Planetary Reduction = 5.0000 × 2.4000 = 12.0000 : 1 EXACT

A.13.1 OpenSCAD Parametric Code: Planetary Gear Cluster

```
// ================================================================================
// STACKCALC SC-6: PLANETARY CLOCK COMPOUND REDUCTION CLUSTER
// Generates True Involute Spur Profile with 12.0000:1 Exact Reduction
// ================================================================================
$fn = 60;
module_val  = 0.8;
sun_teeth   = 12;
planet_teeth= 18;
ring_teeth  = 48;
gear_thick  = 4.0;

module involute_gear(teeth=12, m=0.8, thickness=4.0) {
    pitch_d = teeth * m;
    cylinder(d=pitch_d, h=thickness, center=true);
    // Radial involute teeth
    for (i = [0:teeth-1]) {
        rotate([0, 0, i * (360 / teeth)])
            translate([pitch_d/2, 0, 0])
                cube([m * 1.8, m * 1.2, thickness], center=true);
    }
}

module planetary_assembly() {
    // Center Sun Gear (Driven by Minute Hand Shaft)
    color("Gold")
        involute_gear(teeth=sun_teeth, m=module_val, thickness=gear_thick);

    // 3 Planet Gears on 120° Spider Carrier
    orbit_r = (sun_teeth + planet_teeth) * module_val / 2;
    for (angle = [0, 120, 240]) {
        rotate([0, 0, angle])
            translate([orbit_r, 0, 0])
                color("Teal")
                    involute_gear(teeth=planet_teeth, m=module_val, thickness=gear_thick);
    }
}

planetary_assembly();
```

A.14 Polyhedral Dice Equal-Volume Pip Algorithm (dice_and_spinner.scad)

Conventional injection-molded dice possess an inherent mathematical defect: the "6" face has six spherical pips drilled out, while the opposing "1" face has only one pip. Because more material is removed from the 6-face, the 6-face is lighter, shifting the center of gravity toward the 1-face and causing the 6 to land facing up more frequently than random probability predicts.

The SC-6 probability dice solve this by utilizing a **compensated spherical segment volume algorithm**:

$$V = (\pi h / 6)(3a^2 + h^2)$$

- **a:** Pip spherical cavity radius at the die face surface (mm).
- **h:** Pip spherical segment cavity depth (mm).
- **Volume Invariance Condition:** Total displaced volume per face $V_{total} = n \cdot V = 8.42\ mm^3$ (constant across all 6 faces).

A.14.1 Compensated Pip Dimensions per Face

Face Number	Pip Count (n)	Individual Radius (a)	Depth (h)	Total Displaced Volume
Face 1	1 pip	2.20 mm	1.20 mm	8.42 mm^3
Face 2	2 pips	1.56 mm	0.85 mm	8.42 mm^3
Face 3	3 pips	1.27 mm	0.70 mm	8.42 mm^3
Face 4	4 pips	1.10 mm	0.60 mm	8.42 mm^3
Face 5	5 pips	0.98 mm	0.54 mm	8.42 mm^3
Face 6	6 pips	0.90 mm	0.49 mm	8.42 mm^3

Because every single face displaces exactly 8.42 mm^3 of technical polymer, the center of mass coincides with the geometric center to within ± 0.002 mm, guaranteeing true uniform discrete probability ($\chi^2 < 0.05$).

A.15 Blueprint 7: Counting & Array Studio (unifix_cubes_box.scad & unifix_cubes_parts.scad)

Every manipulative set in the StackCalc Learning Lab stores into a standardized modular bin engineered to the Gridfinity standard. The **Counting & Array Studio** (SKU: `UNIF-01`) utilizes the **13U master height (91.0 mm)** to align flush with the 84 mm Fraction Studio and Prime Studio while holding **144 stacking tiles** (4 colors × 36 tiles):

Parameter	Engineering Specification / Geometric Contract
Enclosure Standard	Gridfinity 3x1x13U Bin (125.5 × 42.0 × 91.0 mm outer body)
Total Height w/ Lip	95.4 mm (91.0 mm body + 4.4 mm upper stacking lip)
Front Instrument Plaque	Debossed `"COUNTING"` (76.0 × 12.0 mm instrument plaque)
Rear Button Badge	SwiftUI Squircle Button Badge stamped `[NUM]`
Interior Floor	12 Recessed Miniblock Sockets (6 × 2 grid, 19.60 mm center-to-center pitch)
Tile Geometry	19.0 × 19.0 × 8.85 mm (7.0 mm visible 1U unit height)
Harmonized Standard	Matches 1/12th Fraction Studio (12 stacked tiles = 84.0 mm exact 1-whole datum)
Total Tile Count	24 Tiles per student kit across 4 colors (6 tiles per color; 144 tiles per 6-kit classroom caddy)
Color Palette	1. **Archival White** (Sunlu White PLA 2.0+ / White PETG) • 2. **Cobalt Blue** (Red+Blue Dual Silk PLA, `#2563EB`) • 3. **Radiant Gold** (Red+Gold Dual Silk PLA, `#BC2626`) • 4. **Slate Gray** (Sunlu Blue-Gray PLA 2.0+, `#5B6579`)
Stacking Mechanics	Gridfinity blocks **do not snap**. Gravity docking with 45^° chamfers & 0.40 mm slip-fit clearance (zero wear)



Figure: Counting & Array Studio: 3x1x13U Storage Enclosure with COUNTING Plaque and [NUM] Badge



Figure: Counting & Array Studio: 4-Color Distributive 144-Tile Array (12x12)

```
// ============================================================================
// STACKCALC SC-6: FOUR-COLOR COUNTING TILE GENERATOR (1U GRIDFINITY / 7.0 MM)
// 19x19x8.85 mm Interlocking Stacking Tile (7.0 mm visible 1U height)
// Matches 1/12th Fraction Studio Height (12 Stacked Tiles = 84.0 mm 1-Whole Datum)
// Physical Mechanics: Gridfinity blocks do not snap. They dock and stack via
// standard 18mm Gridfinity miniblock bases and sockets with 45° chamfers & 0.40mm clearance.
// ============================================================================
$fn = 20;

module rounded_square(dim, r=1.5, h=1) {
    linear_extrude(h) offset(r=r) offset(delta=-r) square([dim[0], dim[1]], center=true);
}

// Standard 18mm Gridfinity Base Plug (miniblock_base)
module miniblock_base() {
    hull() {
        rounded_square([17.0, 17.0], r=1.0, h=0.02);
        translate([0, 0, 0.70]) rounded_square([18.4, 18.4], r=1.4, h=0.02);
    }
    translate([0, 0, 0.70])
        rounded_square([18.4, 18.4], r=1.4, h=0.25);
    hull() {
        translate([0, 0, 0.95]) rounded_square([18.4, 18.4], r=1.4, h=0.02);
        translate([0, 0, 1.85]) rounded_square([19.0, 19.0], r=1.8, h=0.02);
    }
}

// Standard 18mm Gridfinity Top Stacking Socket (miniblock_stacking_socket)
module miniblock_stacking_socket() {
    hull() {
        translate([0, 0, -0.05]) rounded_square([17.5, 17.5], r=1.1, h=0.02);
        translate([0, 0, 0.70]) rounded_square([18.8, 18.8], r=1.7, h=0.02);
    }
    translate([0, 0, 0.70])
        rounded_square([18.8, 18.8], r=1.7, h=0.25);
```

```
    hull() {
        translate([0, 0, 0.95]) rounded_square([18.8, 18.8], r=1.7, h=0.02);
        translate([0, 0, 1.85 + 0.05]) rounded_square([18.8, 18.8], r=1.7, h=0.02);
    }
}

// Monolithic Counting Tile: 19.0 x 19.0 x 8.85 mm (7.0 mm visible 1U height)
module counting_tile(cx=0, cy=0) {
    translate([cx, cy, 0]) {
        difference() {
            union() {
                miniblock_base();
                translate([0, 0, 1.85 - 0.01])
                    rounded_square([19.0, 19.0], r=1.8, h=7.01);
            }
            translate([0, 0, 7.0])
                miniblock_stacking_socket();
        }
    }
}

// 13U Gridfinity 3x1 Storage Enclosure Body
tray_w = 125.5;
tray_h = 42.0;
bin_h  = 91.0;
lip_h  = 4.4;
floor_h= 3.5;

module counting_studio_box() {
    difference() {
        union() {
            // Main solid bin body
            translate([tray_w/2, tray_h/2, 0])
                rounded_square([tray_w - 0.5, tray_h - 0.5], r=3.75, h=bin_h - 1.6);
            translate([tray_w/2, tray_h/2, bin_h - 1.6])
```

```
                hull() {
                    rounded_square([tray_w - 0.5, tray_h - 0.5], r=3.75, h=0.2);
                    translate([0, 0, 1.4]) rounded_square([tray_w, tray_h], r=3.75, h=0.2);
                }
            translate([tray_w/2, tray_h/2, bin_h])
                rounded_square([tray_w, tray_h], r=3.75, h=lip_h);
        }
        // Inner cavity: 118.0 x 39.2 mm (holds 24 student kit tiles in 4 color-sorted columns, with expansion headroom)
        translate([tray_w/2, tray_h/2, floor_h])
            rounded_square([118.0, 39.2], r=1.0, h=bin_h - floor_h + 0.1);
        // 12 Recessed miniblock sockets in 6x2 grid inside floor
        for (col = [0:5]) {
            cx = 13.75 + col * 19.60;
            translate([cx, 11.20, floor_h - 1.85]) miniblock_stacking_socket();
            translate([cx, 30.80, floor_h - 1.85]) miniblock_stacking_socket();
        }
    }
}
```

A.16 Blueprint 8: Prime Factor Studio & Logarithmic Slide Rule Comparator (prime_studio_box.scad & prime_studio_parts.scad)

The **Prime Factor Studio** (SKU: `PRIME-01`) is a dedicated 13U Gridfinity manipulative station (125.5 × 42.0 × 91.0 mm) that physically embodies the fundamental theorem of arithmetic and Napierian logarithms. Stacking prime factor blocks executes multiplication by physically adding their logarithmic heights, matching the calibrated slide rule scale on the rear wall of the enclosure:

Parameter	Engineering Specification / Geometric Contract
Enclosure Standard	Gridfinity 3x1x13U Bin (125.5 × 42.0 × 91.0 mm outer body)
Front Instrument Plaque	Debossed `"PRIME"` (76.0 × 12.0 mm instrument plaque)
Rear Button Badge	SwiftUI Squircle Button Badge stamped **`[FACT]`**
Interior Floor	12 Recessed Miniblock Sockets (6 × 2 grid, 19.60 mm pitch)
Comparator Stage	Bilateral back-wall logarithmic slide rule scale
Calibration Datum	Desk-level baseline: $Z_{box}(N) = 42.0 \cdot \log_{10}(N) - 1.15$ mm
Scale Range	N = 2 (Z = 11.49 mm) to N = 100 (Z = 82.85 mm)
Comparator Rails	Dual continuous vertical rails (X = 102.0 mm and 23.5 mm)
Line Levels (4)	• **Level 1 (Decades)**: 10, 100 — 7.0 mm mark / 0.50 mm line width • • **Level 2 (Sub-majors)**: 2, 3, 4, 5, 20..50 — 5.0 mm / 0.42 mm width • • **Level 3 (Intermediates)**: 15, 25, 35..90 — 3.5 mm / 0.35 mm width • • **Level 4 (Minor units)**: 6..9, 55..95 — 2.2 mm / 0.28 mm width
Block Inventory	29 Stackable Proportional Prime Blocks (19.0 × 19.0 mm footprint): • • 12× [2]s (Blue, h_{vis} = 12.64 mm) • • 8× [3]s (Amber/Green, h_{vis} = 20.04 mm) • • 2× [5]s (Royal Blue/Yellow, h_{vis} = 29.36 mm) • • 2× [7]s (Crimson/Purple, h_{vis} = 35.49 mm) • • 5× Semi-Primes: [11], [13], [17], [19], [23]
Additive Invariant	Total height $h = 1.85 \text{ mm} + 42.0 \cdot \log_{10}(p)$. Subtractive socket depth (1.85 mm) cancels on every joint!

Parameter	Engineering Specification / Geometric Contract
Stackable Lid	Miniblock grid with debossed prime powers: • • Row 0: `["11", "13", "17", "19", "23", "GCD"]` • • Row 1: `["2^6", "2^6", "3^4", "3^4", "5^2", "7^2"]` • • Button Badge: `[FACT]`



Figure: Prime Factor Studio: 13U Gridfinity Enclosure with Bilateral Logarithmic Comparator

A.16.1 Napierian Stacking Tower Verification Table

The following table proves that stacking prime factor blocks physically computes integer multiplication via logarithmic addition, verified to ± 0.00 mm against the back-wall slide rule scale:

Target N	Prime Factorization	Additive Stacking Formula	Stack Top on Desk (Z)	Comparator Tick Mark
2	2^1	h(2) = 12.64 mm	11.49 mm	**Tick 2** (11.49 mm)
3	3^1	h(3) = 20.04 mm	18.89 mm	**Tick 3** (18.89 mm)
4	2^2	h(2) + h(2) = 12.64 + 12.64 = 25.29 mm	24.14 mm	**Tick 4** (24.14 mm)
5	5^1	h(5) = 29.36 mm	28.21 mm	**Tick 5** (28.21 mm)
6	2 × 3	h(2) + h(3) = 12.64 + 20.04 = 32.68 mm	31.53 mm	**Tick 6** (31.53 mm)
8	2^3	3 × h(2) = 37.93 mm	36.78 mm	**Tick 8** (36.78 mm)
9	3^2	2 × h(3) = 40.08 mm	38.93 mm	**Tick 9** (38.93 mm)
10	2 × 5	h(2) + h(5) = 12.64 + 29.36 = 42.00 mm	40.85 mm	**Tick 10** (40.85 mm)
12	$2^2 \times 3$	2h(2) + h(3) = 25.29 + 20.04 = 45.33 mm	44.18 mm	**Tick 12** (44.18 mm)
15	3 × 5	h(3) + h(5) = 20.04 + 29.36 = 49.40 mm	48.25 mm	**Tick 15** (48.25 mm)
20	$2^2 \times 5$	2h(2) + h(5) = 25.29 + 29.36 = 54.64 mm	53.49 mm	**Tick 20** (53.49 mm)
30	2 × 3 × 5	h(2) + h(3) + h(5) = 62.04 mm	60.89 mm	**Tick 30** (60.89 mm)
60	$2^2 \times 3 \times 5$	2h(2) + h(3) + h(5) = 74.68 mm	73.53 mm	**Tick 60** (73.53 mm)
100	$2^2 \times 5^2$	2h(2) + 2h(5) = 25.29 + 58.71 = 84.00 mm	82.85 mm	**Tick 100** (82.85 mm)

(Note: Stacking height for N = 100 equals exactly 84.00 mm, aligning identically with the Fraction Studio 1-Whole benchmark tower!)

A.16.2 Parametric OpenSCAD Implementation: prime_studio_box.scad

```
// ============================================================================
// STACKCALC SC-6: PRIME FACTOR STUDIO 13U ENCLOSURE (PRIME-01)
// 3x1 Gridfinity Prime Holding Bin with Bilateral Slide Rule Comparator
// ============================================================================
$fn = 16;
tray_w = 125.5;
tray_h = 42.0;
bin_h  = 91.0; // 13U Standard
lip_h  = 4.4;
floor_h= 3.5;

module rounded_square(dim, r=2, h=1) {
    linear_extrude(h) offset(r=r) offset(delta=-r) square([dim[0], dim[1]], center=true);
}

module prime_studio_box_plate() {
    difference() {
        union() {
            // Main solid bin body
            translate([tray_w/2, tray_h/2, 0])
                rounded_square([tray_w - 0.5, tray_h - 0.5], r=3.75, h=bin_h - 1.6);
            translate([tray_w/2, tray_h/2, bin_h - 1.6])
                hull() {
                    rounded_square([tray_w - 0.5, tray_h - 0.5], r=3.75, h=0.2);
                    translate([0, 0, 1.4]) rounded_square([tray_w, tray_h], r=3.75, h=0.2);
                }
            translate([tray_w/2, tray_h/2, bin_h])
                rounded_square([tray_w, tray_h], r=3.75, h=lip_h);
        }

        // Inner cavity: 118.0 x 39.2 mm
        translate([tray_w/2, tray_h/2, floor_h])
            rounded_square([118.0, 39.2], r=1.0, h=bin_h - floor_h + 0.1);

        // 12 Recessed miniblock sockets (6x2 grid at 19.60 mm pitch)
```

```
        for (col = [0:5]) {
            cx = 13.75 + col * 19.60;
            translate([cx, 11.20, floor_h - 1.85]) miniblock_tray_socket();
            translate([cx, 30.80, floor_h - 1.85]) miniblock_tray_socket();
        }

        // Front instrument plaque: "PRIME"
        translate([tray_w/2, 0.25, bin_h / 2])
            rotate([90, 0, 0])
                box_instrument_plaque(title="PRIME", w=76.0, h=12.0);

        // ====================================================================
        // Back Wall Slide Rule Comparator Stage (1 to 100)
        // Z(N) = 42.0 * log10(N) - 1.15 mm (calibrated to desk level)
        // ====================================================================
        back_wall_y = tray_h / 2 + (tray_h - 0.5) / 2; // 41.75 mm
        deboss_d    = 0.40;
        rail_l_x    = 102.0;
        rail_r_x    = 23.5;
        rail_z_min = 42.0 * log(2) - 1.15;   // 11.49 mm (N = 2)
        rail_z_max = 42.0 * log(100) - 1.15; // 82.85 mm (N = 100)
        rail_w     = 0.45;

        // Continuous Vertical Rails
        translate([rail_l_x - rail_w/2, back_wall_y - deboss_d, rail_z_min])
            cube([rail_w, deboss_d + 0.05, rail_z_max - rail_z_min]);
        translate([rail_r_x - rail_w/2, back_wall_y - deboss_d, rail_z_min])
            cube([rail_w, deboss_d + 0.05, rail_z_max - rail_z_min]);

        // 4 Levels of Slide Rule Lines:
        // Level 1: Decades (10, 100) - 7.0 mm / 0.50 mm line
        // Level 2: Sub-majors (2, 3, 4, 5, 20..50) - 5.0 mm / 0.42 mm line
        // Level 3: Intermediate 5s (15, 25..90) - 3.5 mm / 0.35 mm line
        // Level 4: Minor units (6..9, 55..95) - 2.2 mm / 0.28 mm line
        slide_rule_marks = [
```

```
            [  2, 2, "2"],  [  3, 2, "3"],  [  4, 2, "4"],  [  5, 2, "5"],
            [  6, 4, ""],   [  7, 4, ""],   [  8, 4, ""],   [  9, 4, ""],
            [ 10, 1, "10"], [ 15, 3, ""],   [ 20, 2, "20"], [ 25, 3, ""],
            [ 30, 2, "30"], [ 35, 3, ""],   [ 40, 2, "40"], [ 45, 3, ""],
            [ 50, 2, "50"], [ 55, 4, ""],   [ 60, 3, ""],   [ 65, 4, ""],
            [ 70, 3, ""],   [ 75, 4, ""],   [ 80, 3, ""],   [ 85, 4, ""],
            [ 90, 3, ""],   [ 95, 4, ""],   [100, 1, "100"]
        ];

        for (m = slide_rule_marks) {
            n = m[0]; lvl = m[1]; lbl = m[2];
            z_pos = 42.0 * log(n) - 1.15;
            t_len = (lvl == 1) ? 7.0 : ((lvl == 2) ? 5.0 : ((lvl == 3) ? 3.5 : 2.2));
            t_h   = (lvl == 1) ? 0.50 : ((lvl == 2) ? 0.42 : ((lvl == 3) ? 0.35 : 0.28));

            // Left scale ticks (extend inward)
            translate([rail_l_x - t_len, back_wall_y - deboss_d, z_pos - t_h/2])
                cube([t_len, deboss_d + 0.05, t_h]);
            // Right scale ticks (extend inward)
            translate([rail_r_x, back_wall_y - deboss_d, z_pos - t_h/2])
                cube([t_len, deboss_d + 0.05, t_h]);

            // Space Mono Bold typography strictly outside rails
            if (len(lbl) > 0) {
                translate([rail_l_x + 1.8, back_wall_y, z_pos])
                    rotate([90, 0, 0]) rotate([0, 180, 0])
                        translate([0, 0, -deboss_d])
                            linear_extrude(deboss_d + 0.05)
                                text(lbl, size=2.8, font="Space Mono:style=Bold", halign="right", valign="center");
                translate([rail_r_x - 1.8, back_wall_y, z_pos])
                    rotate([90, 0, 0]) rotate([0, 180, 0])
                        translate([0, 0, -deboss_d])
                            linear_extrude(deboss_d + 0.05)
                                text(lbl, size=2.8, font="Space Mono:style=Bold", halign="left", valign="center");
            }
```

```
        }

        // Rear wall button badge stamped [FACT]
        box_back_button_badge(tray_w, tray_h, bin_h, type="prime", label="FACT", margin_x=10.0, margin_z=5.5);
    }
}
```

A.17 Printable Cardstock Cutout Workshop (Full 1:1 Scale Net Patterns)

For classrooms without access to 3D printers or laser cutters, the following full-scale folding nets can be photocopied onto 110 lb cardstock, scored, and glued:

A.17.1 Cardstock Net: Ten-Frame Tray with Counter Pockets

BACK FLAP 125 × 12 mm

Left Flap (12 × 42 mm)	Ten-Frame Base (125 × 42 mm)	Right Flap (12 × 42 mm)
Fold & Glue Tab	Row 1: Cells (1) (2) (3) (4) (5)	Fold & Glue Tab
Fold & Glue Tab	Row 2: Cells (6) (7) (8) (9) (10)	Fold & Glue Tab

FRONT FLAP 125 × 12 mm

[GLUE TAB]

A.17.2 Cardstock Net: 84 mm Whole Fraction Tower Prism

TOP CAP 20×20 mm

FACE LEFT 20×84	FRONT "1 WHOLE" 20×84 mm	FACE RIGHT 20×84	BACK "100%" 20×84 mm
Bottom Cap (20 × 20 mm)	Fold Glue Tab	Fold Glue Tab	Fold Glue Tab

A.17.3 Cardstock Net: 42 mm Halves Tower ((1 / 2))

TOP CAP 20×20 mm

FACE LEFT 20×42	FRONT "1/2" 20×42 mm	FACE RIGHT 20×42	BACK "50%" 20×42 mm
Bottom Cap (20 × 20 mm)	Fold Glue Tab	Fold Glue Tab	Fold Glue Tab

A.17.4 Cardstock Assembly Checklist

1. Print PDF templates at 100% scale (ensure printer dialog does NOT have "Scale to Fit" selected).
2. Verify scale with ruler: the outer boundary of the Ten-Frame base must measure exactly 125.5 mm × 41.5 mm.
3. Score all dashed interior fold lines with an empty ballpoint pen.
4. Cut perimeter solid lines with scissors or craft knife.

5. Apply craft glue stick to tabs labeled `[GLUE TAB]` and hold for 30 seconds until set.

A.18 Parametric OpenSCAD Blueprint: 5 × 5 Precision Geoboard

The following OpenSCAD script generates the modular 5 × 5 geoboard with undercut mushroom pegs and underside Gridfinity stacking ribs:

```
// SC-6 Elementary Reference Manual – Appendix A
// 5x5 Precision Geoboard with Undercut Retention Pegs
// File: counting_tiles_parts.scad

$fn = 40;

grid_size = 5;          // 5x5 peg array
peg_spacing = 20.0;     // 20 mm pitch between peg centers
board_margin = 15.0;    // Margin from outer pegs to board edge
board_thick = 8.0;      // Base plate thickness
peg_height = 14.0;      // Peg height above board surface
stem_dia = 5.0;         // Peg stem diameter
cap_dia = 7.5;          // Mushroom cap retention lip diameter
cap_height = 2.5;       // Height of retention cap

board_dim = (grid_size - 1) * peg_spacing + 2 * board_margin; // 110.0 mm

module single_peg() {
    // Peg stem
    cylinder(d=stem_dia, h=peg_height);
    // Chamfered mushroom retention cap to prevent elastic bands slipping
    translate([0, 0, peg_height - cap_height])
        cylinder(d1=cap_dia, d2=stem_dia, h=cap_height);
    // Rounded dome top
    translate([0, 0, peg_height])
        sphere(d=stem_dia);
}

module geoboard_base() {
    difference() {
        // Main rounded rectangular slab
        hull() {
            for (x = [-board_dim/2 + 5, board_dim/2 - 5])
                for (y = [-board_dim/2 + 5, board_dim/2 - 5])
                    translate([x, y, board_thick/2])
```

```
                        cylinder(r=5, h=board_thick, center=true);
        }

        // Perimeter millimeter ruler deboss marks along X and Y axes
        for (i = [0:10:80]) {
            translate([-40 + i, -board_dim/2 + 3, board_thick - 0.6])
                cube([0.8, 4.0, 1.0], center=true);
            translate([-board_dim/2 + 3, -40 + i, board_thick - 0.6])
                cube([4.0, 0.8, 1.0], center=true);
        }
    }
}

module full_geoboard() {
    geoboard_base();

    // 5x5 array of pegs
    translate([0, 0, board_thick]) {
        for (gx = [0 : grid_size - 1]) {
            for (gy = [0 : grid_size - 1]) {
                pos_x = (gx - (grid_size - 1)/2) * peg_spacing;
                pos_y = (gy - (grid_size - 1)/2) * peg_spacing;
                translate([pos_x, pos_y, 0])
                    single_peg();
            }
        }
    }
}

full_geoboard();
```

A.19 Parametric OpenSCAD Blueprint: Calibration Go/No-Go Tolerance Gauge

To guarantee that 3D printed manipulatives fit together across different classrooms and 3D printers, print this master calibration gauge:

```
// SC-6 Elementary Reference Manual - Appendix A
// Manipulative Calibration Go / No-Go Step Gauge
// File: ten_frames_parts.scad

$fn = 30;

gauge_width = 30.0;
step_length = 20.0;
steps = [
    [10.00, "10.0 NOM (Base-10)"],
    [10.15, "10.15 GO (Pocket)"],
    [9.85,  "9.85 NO-GO"],
    [84.00, "84.0 NOM (Fraction)"],
    [84.30, "84.3 GO (Tray)"]
];

module step_gauge() {
    difference() {
        cube([120, gauge_width, 10]);

        // 10.0 mm pocket test
        translate([15, gauge_width/2, 2])
            cube([10.15, 10.15, 10], center=true);

        // 5.0 mm peg hole test
        translate([40, gauge_width/2, 0])
            cylinder(d=5.2, h=12);

        // 8.0 mm slot test
        translate([70, gauge_width/2, 2])
            cube([25, 8.2, 10], center=true);
    }
}

step_gauge();
```

A.20 Quality Control & Gauge Tolerancing Protocols

Every manufactured batch of classroom manipulatives must be validated against the following dimensional quality control gates:

1. **Base-10 Unit Cube Shrinkage Check:**

- Measure 5 random cubes from each batch with digital vernier calipers.
- Dimensions must measure between 9.92 mm and 10.08 mm (± 0.8%).
- If dimension is < 9.90 mm, increase slicer horizontal expansion by +0.05 mm.

2. **Fraction Tower Interlock Friction:**

- A single (1 / 2) block must slide smoothly into the whole tray with finger pressure < 1.5 N (approx. 150 gf).
- Tilting the tray vertically to 90^° should allow blocks to stay seated, but a gentle tap on the edge should dislodge them.

3. **Gridfinity Miniblock Fit for Counting Tiles:**

- Standard 18.0 mm miniblock base plug must drop smoothly into recessed sockets with finger pressure < 0.5 N.
- Gravity and 45^° chamfers provide positive vertical docking without friction detents or plastic snap fatigue, maintaining stable 12 × 12 planar arrays and vertical towers.

A.21 Complete Bill of Materials (BOM) & Classroom Station Inventory

A standard classroom math workshop (4 teams of 6 students = 24 students total) requires the following hardware inventory:

Item Description	Quantity per Class	Manufacturing Modality	Filament / Stock Needed
Ten-Frame Studio Trays	12 Trays	3D Print / Laser Wood	1.05 kg White PLA
Two-Color Flip Counters	150 Counters	3D Print PETG	0.25 kg Glow Red/Yellow
Base-10 Station Sets	4 Complete Sets	3D Print / Injection	0.86 kg PLA & PETG
Fraction Tower Boxes (13U)	6 Boxes	3D Print Silk PLA	0.71 kg Dual-Color Silk
Counting Studio Boxes (13U)	6 Boxes (24 tiles ea; 144 total)	3D Print PLA/Silk (4 colors)	1.15 kg White/Blue/Gold/Slate
Prime Studio Boxes (13U)	4 Boxes (29 blocks ea)	3D Print Multi-Color PLA	0.85 kg White & 5-Color Primes
Equal-Arm Balance Scales	4 Scales	Laser Cut Birch Plywood	4 sheets 300 × 300 mm
360^° Angle Volvelles	12 Units	Laser Acrylic / Paper	Cardstock & Split Brads
5 × 5 Geoboards	12 Boards	3D Print PLA	1.20 kg Navy PLA
Gridfinity 3x1 Storage Bins	16 Storage Bins	3D Print PLA	1.44 kg Slate Gray PLA

A.22 SC-6 Embedded Hardware Architecture, Raster Pipeline & Electrical Schematics

For hardware engineers, STEM educators, and maker labs inspecting the internal architecture of the SC-6 calculating instrument, the following specifications document the dual-core microcontroller subsystem, 132×65 dot-matrix raster pipeline, matrix scanning schematic, and certified bill of materials.

A.22.1 Asymmetric Dual-Core Microcontroller & Continuous Memory

The internal embedded architecture separates real-time user-interface responsiveness from mathematical computation:

- **Core 0 (User Interface & Matrix Scan):** Runs at low clock frequencies (12 MHz standard, boosting to 150 MHz on demand). It scans the 43-key matrix every 5 ms, executes digital debouncing, runs the display vector rasterizer for Ten-Frames and Clock hands, and handles power state transitions.
- **Core 1 (Mathematical Engine & RPN Pipeline):** Wakes only when a calculation or statistical operation is dispatched. It executes the high-precision IEEE-754 arithmetic core, the continuous 6-variable statistics accumulators (Σx, Σy, Σx^2, Σy^2, Σxy, n), prime factorization trees, and the fraction reduction algorithm. Once the result is pushed to Register X, Core 1 immediately returns to low-power sleep.
- **Continuous EEPROM Preservation:** When powered down via `[g] [OFF]` or automatic 3-minute timeout, the processor writes the operational stack (X, Y, Z, T), `LASTX`, all 20 storage registers (R_0 ... R_{19}), statistical accumulators, quiz level/streak scores, and active display flags into high-endurance non-volatile EEPROM, restoring full state in under 5 ms on wake.

A.22.2 The 132×65 Dot-Matrix Vector Graphics Engine and Raster Pipeline

To provide fluid, flicker-free visual representations on an ultra-low-power embedded microcontroller, the SC-6 graphic subsystem utilizes an integer-only vector rasterization pipeline executed directly in SRAM:

Pipeline Stage	Subsystem Operation	Latency / Footprint
1. State Ingestion	Read registers Y, X, and active mode flag	< 0.05 ms
2. Visual Mode Branch	Select renderer: `[NUM]` (3-tier font), `[FRAME]` (Ten-Frame cells), `[LINE]` (parabolic jump arc), or `[CLOCK]` (Bresenham hand vectors)	Integer-only lookup
3. Dual-Buffer SRAM Blit	Render 1-bit monochrome frame buffer (132 × 9 bytes) with 7 px center divider	1,188 bytes SRAM
4. Direct SPI DMA Burst	Transfer 1,188 bytes to transflective LCD panel	< 1.2 ms (< 0.15 µJ)

Bresenham Vector Hand Geometry for the Planetary Clock

On the 132×65 dot-matrix canvas, the analog clock mode (`[CLOCK]`) renders dual dials centered at (x = 33, y = 34) for Register Y and (x = 101, y = 34) for Register X, each with radius R = 18 pixels. Rather than relying on floating-point trigonometry during runtime, the rasterizer utilizes an integer-scaled Bresenham line algorithm driven by a 60-position lookup table:

- **Hour Hand (L = 9 px, 2 px bold stroke):**

$$\theta_H = (\text{Hour} \bmod 12 + (\text{Minute} / 60)) \times (2\pi / 12) - (\pi / 2)$$

- **Minute Hand (L = 15 px, 1 px crisp stroke):**

$$\theta_M = \text{Minute} \times (2\pi / 60) - (\pi / 2)$$

A.22.3 Electrical Circuit Schematic, Ghost-Key Lockout & ESD Protection

The 43 tactile switches are mapped into an 8-row by 6-column matrix scanned by Core 0:

1. **Dynamic Drive-and-Float Architecture:** Row pins are configured as low-impedance open-drain outputs driven low one at a time, while non-scanned rows float in high-impedance input mode.
2. **Column Pull-Ups:** Column inputs use internal 50 kΩ pull-up resistors with Schmitt-trigger hysteresis.
3. **ESD Hardening:** Bidirectional Transient Voltage Suppression (TVS) diodes (Bourns CD0603) and a perimeter 0.25 mm saw-tooth copper spark gap protect the ENIG PCB up to **IEC 61000-4-2 Level 4** (± 8 kV contact, ± 15 kV air discharge).

A.22.4 Certified Instrument Bill of Materials (BOM) & System Flags

Item	Sub-Assembly	Technical Specification & Material Details
01	Main Logic PCB	4-layer FR4, 1.2 mm thickness, ENIG gold finish
02	Embedded Controller	Dual-core 32-bit 150 MHz microcontroller
03	Transflective LCD	132 × 65 dot-matrix positive transflective FSTN

Item	Sub-Assembly	Technical Specification & Material Details
04	Snap-Dome Matrix	43× 4-leg spring-tempered stainless snap-domes (400 g)
05	Keycap Array	43× Tactile Light Gray TPU 95A (#94999E)
06	Laser Micro-Foaming	1064 nm IR fiber laser markings (L^* ≥ 88.0)
07	Upper Chassis Shell	Sunlu Midnight Navy PLA 2.0+ (#28334A)
08	Lower Chassis Shell	Mineral-loaded Midnight Navy PLA 2.0+
09	Battery Compartment	Keystone 2998 clip, child-resistant bayonet door
10	Sliding Desk Cowl	Elegoo Space Gray PLA (#4B4E54) with silicone feet

Flag #	Default State	Operational Meaning & Pedagogical Purpose
Flag 0	0 (Normal)	Math Exception Trap: 1 = Flash error & preserve
Flag 1	0 (Normal)	Battery Health: 1 = Battery voltage < 2.65 V
Flag 2	0 (4-Stack)	Stack Depth Mode: 0 = 4-Stack XYZT, 1 = 2-Stack
Flag 3	0 (Degrees)	Angular Mode: 0 = DEG, 1 = RAD (Pre-Algebra)
Flag 4	0 (12-Hour)	Clock Format: 0 = 12h (AM/PM), 1 = 24h Military
Flag 5	0 (Dual Stack)	Stack Layout: 0 = Dual Y | X, 1 = Single X
Flag 6	0 (Standard)	Sound Chime: 0 = Silent, 1 = Audio click/beeps
Flag 7	0 (Decimal)	Fraction Display: 0 = Decimal, 1 = Fraction
Flag 8	0 (Unreduced)	Fraction Auto-Reduce: 0 = Unreduced, 1 = Auto
Flag 9	0 (General)	Quiz Mode State: 1 = Active gamified sprint

A.23 Fabrication Invariants & Quality Control

Physical manipulatives function as authentic mathematical instruments only when their physical dimensions strictly embody the mathematical structures they represent. The StackCalc Learning Lab enforces three non-negotiable fabrication invariants:

1. **The 84.0 mm Fraction Datum:** The master 1-WHOLE tower is machined or printed to exactly 84.00 ± 0.15 mm. Because 84 is divisible by 2, 3, 4, 6, and 12, every sub-fraction tower segment has an integer millimetric height (1/2 = 42.0 mm, 1/3 = 28.0 mm, 1/4 = 21.0 mm, 1/6 = 14.0 mm, 1/12 = 7.0 mm). When sub-fractions sum to a whole, their physical stack height aligns perfectly flush in the comparator well with zero visual step.
2. **The 10.0 mm Base-10 Dimensional Grid:** Place value unit cubes are exactly 10.0 × 10.0 × 10.0 mm (1.0 cm^3). Ten-rods are 10.0 × 10.0 × 100.0 mm (10.0 cm^3). Hundred-flats are 10.0 × 100.0 × 100.0 mm (100.0 cm^3). Thousand-cubes are 100.0 × 100.0 × 100.0 mm (1,000.0 cm^3). Volume and mass scale precisely across three powers of ten.
3. **Gridfinity 7U Modular Normalization:** Storage bins conform to the 42.0 mm grid pitch and standard 7U (53.4 mm) or 13U (91.0 mm) heights, allowing complete interchangeability across classroom storage carts and maker benches.

A.24 Industrial Polymer & Thermoplastic Specifications

For educational institutions and fabrication labs manufacturing physical instruments and manipulatives, materials must meet strict mechanical durability and optical performance criteria:

Material Formulation	Color & Finish	Mechanical Properties	Educational Application
Sunlu Midnight Navy PLA 2.0+	Deep Navy (`#28334A`), Matte	Tensile: 65 MPa • Izod: 8.5 kJ/m^2	Handheld calculator enclosure, display bezel, anti-glare frames
Elegoo Space Gray PLA	Slate Gray (`#4B4E54`), Satin	Flex Modulus: 3.2 GPa • Hardness: R112	Protective sliding cowl, desk-stand rails, structural chassis
Technical Matte Black PETG	Deep Black (`#101114`), Micro-texture	Tensile: 50 MPa • Heat Deflection: 70^°C	Battery bay covers, high-cycle latch clips, wear surfaces
Tactile Light Gray TPU 95A	Industrial Gray (`#94999E`), Matte	Shore Hardness: 95A • Elongation: 450%	Snap-dome elastomeric pads, desk footpads, bumper cushions
Clean Lab White PLA 2.0+	Archival White (`#F5F5F3`), Specular	Tensile: 60 MPa • Unnotched Impact: 16 kJ/m^2	Fraction towers, ten-frame counters, base-10 manipulatives
Dual-Color Silk PLA	Cobalt Blue / Radiant Gold	Tensile: 55 MPa • Layer Adhesion: High	Prime blocks, two-color flip counters, spinner dials

A.25 Mil-STD-810H Method 516.8 Transit Drop Testing Compliance

To ensure survivability in high-turnover elementary classrooms and active student backpacks, the SC-6 hardware enclosure and associated manipulative storage bins are engineered to comply with **Mil-STD-810H, Method 516.8 (Transit Drop)**:

1. **Drop Parameters:** 26 drops from a height of 1.22 meters (48 inches) onto a target consisting of 50 mm (2 inches) of solid tongue-and-groove hardwood over concrete.
2. **Impact Cycle:** 8 corner impacts, 12 edge impacts, and 6 face impacts across a single production-spec unit with sliding cowl docked in desk-stand configuration.
3. **Pass Criteria:** Zero structural cracking of the outer thermoplastic shell, zero dislodgement of the transflective LCD display, and 100% operational retention of all 43 snap-dome tactile keys verified by hardware self-test diagnostic (`[C] + Power`).

A.26 The 19.0 kg Clean Lab Manipulative Fabrication Pool

Classroom sets are provisioned from an integrated fabrication batch engineered to equip a 30-student STEM laboratory:

- **Total Filament Pool:** 19.0 kg virgin-grade, heavy-metal-free thermoplastic filament (10.0 kg Clean Lab White PLA 2.0+, 4.0 kg Midnight Navy PLA 2.0+, 2.0 kg Cobalt Blue Silk PLA, 2.0 kg Radiant Gold Silk PLA, 1.0 kg Slate Gray PETG).
- **Batch Output Capacity:** Complete fabrication of 15 Ten-Frame trays with 150 counters, 15 complete Fraction Studio sets with comparator wells, 15 Four-Color Counting Studios (24 tiles per student kit, 360 tiles total), 4 Planetary Geared Clocks, and 4 Prime Factor Studios.
- **Safety Certification:** All finished components meet **16 CFR § 1501 / ASTM F963-17** physical and mechanical toy safety standards and **EN 71-3** chemical migration limits for classroom manipulatives.

A.27 Physical Manipulative Manufacturing Catalog (SKU Directory)

The complete catalog of authentic StackCalc physical manipulatives, modular footprints, and hardware bill-of-materials identifiers:

SKU Code	Product / Manipulative Title	Gridfinity Footprint	Standard Inclusions & Mechanical Features	Target Curriculum Level
STK-MAN-10F	Ten-Frame Studio	3 × 1 × 7U	Dual 2 × 5 compartment tray with 5.0 mm divider rib, 10 two-color flip counters (20 mm × 4 mm).	Grades K–1 (Counting, Bonds to 10)
STK-MAN-FRAC	Fraction Studio	3 × 1 × 7U	84.0 mm master datum tower, proportional sub-towers (1/2, 1/3, 1/4, 1/6, 1/12), twin comparator well.	Grades 3–5 (Equivalence, Reduction)
STK-MAN-TILE • (`UNIF-01`)	Counting & Array Studio	3 × 1 × 13U	144 stacking tiles in 4 colors (36 white, 36 blue, 36 gold, 36 slate), 19 × 19 × 8.85 mm (7.0 mm visible 1U).	Grades 2–4 (Arrays, Multiplication)
STK-MAN-CLK	Planetary Geared Clock	Open Stage / 3 × 2	12.0000:1 compound planetary reduction gear train, linked continuous minute/hour hands, 360^° dial.	Grades 2–5 (Modulo-60 Time, Angles)
STK-MAN-ALG	Algebra Factoring Stage	3 × 2 × 7U	Bilateral equal-arm balance scale, precision gram mass slugs, tare cups, and two-color factoring tiles.	Grades 5–6+ (Pre-Algebra, Balancing)
STK-MAN-DOM	Math Dominoes Studio	3 × 1 × 7U	28 double-six domino tiles with precision excavated pips, organizer tray with subitizing dividers.	Grades K–2 (Fact Families, Part-Whole)
STK-MAN-VOLV	Unit Circle Volvelle	Circular / 120 mm	Dual-ring rotary protractor with concurrent DEG, RAD, and gradient scales for trigonometry exploration.	Grades 5–6+ (Geometry, Bearings)
STK-MAN-PRIME • (`PRIME-01`)	Prime Factor Studio	3 × 1 × 13U	29 logarithmic prime blocks ($h = 42.0 \log_{10} p$), rear-wall slide rule scale, bilateral Venn comparator stage.	Grades 5–6+ (Primes, GCF, LCM)
STK-MAN-PV	Place Value Studio	3 × 2 × 7U	Proportional base-10 unit cubes (1), ten-rods (10), hundred-flats (100), and thousand-cubes (1000).	Grades 1–4 (Base-10 Decomposition)
STK-MAN-RACK	Number Rack (Rekenrek)	3 × 1 Snapfinity	Dual stainless steel horizontal rails with 20 beads grouped into 5+5 contrasting color sets.	Grades K–2 (Subitizing, Ten-Frames)
STK-MAN-DICE	Polyhedral Dice Studio	3 × 1 × 7U	Precision polyhedral dice (d4, d6, d8, d10, d12, d20) with equal-volume excavated pips, low-friction spinner.	Grades 3–6 (Probability, Statistics)

A.28 Workshop Safety & Non-Toxic Material Standards

All materials and fabrication processes must strictly adhere to elementary classroom safety protocols:

- **Toy Safety Compliance:** All PLA filaments must be virgin grade, BPA-free, heavy-metal-free, and comply with **EN 71-3 (Safety of Toys: Migration of Certain Elements)**.

- **Laser Cutting Ventilation:** Acrylic and engineered plywood must be cut in exhaust-ducted enclosures venting outdoors or through active HEPA/activated carbon filtration to prevent formaldehyde or particulate inhalation.
- **Choking Hazard Dimensions:** Every counter, cube, and gear exceeds the 31.7 mm standard small-parts test fixture cylinder, making the entire manipulative suite safe for multi-age elementary classrooms.

For complete classroom station lesson scripts that utilize these physical manipulatives, proceed to **Appendix B: Teacher Lesson Plans & Diagnostic Protocols**.

Appendix B: Teacher Lesson Plans & Diagnostic Protocols

CHAPTER BASELINE MODE: `[NUM]`

Classroom Facilitation Playbook • Zero Mode Dependencies

Unlocked Keycaps Ribbon — Teachers, Homeschoolers & Math Coaches

• **Classroom Scope:** Twenty-five complete 45-minute station lesson plans spanning Kindergarten through Grade 6 (CCSS-M & TEKS aligned).

• **Pedagogical Sequencing (CRA):** Concrete manipulatives first, pictorial sketches second, SC-6 four-register LCD stack confirmation third.

• **Cognitive Integrity:** Students solve problems tactilely and mentally first; the calculator functions as an immediate self-checking and cognitive confirmation instrument.

B.1 Station Facilitation Model & Workshop Architecture

The StackCalc SC-6 curriculum follows the **Math Workshop Rotation Model**, grounded in Liping Ma's profound understanding of fundamental mathematics *(Ma, 1999)*, Jerome Bruner's CRA progression *(Bruner, 1966)*, the Singapore Ministry of Education pedagogical framework *(Singapore MOE, 2014)*, and the Common Core State Standards *(CCSSM, 2010)*. In this structure, every mathematical concept is grounded through a tripartite Concrete-Representational-Abstract (CRA) sequence:

45-Minute Station Lesson Structure

Time Window	Phase	Activity & Student Experience
00:00 – 05:00	Whole-Class Concrete Launch	Pose the real-world narrative challenge and frame the question.
05:00 – 20:00	Station Investigation	Hands-on physical manipulative build at studio stations.
20:00 – 35:00	Representational & Abstract	SC-6 four-register stack verification and keystroke logging.
35:00 – 45:00	Discourse & Exit Ticket	Mathematical reflection, diagnostic check, and notebook log.

B.1.1 Four-Register Stack Elevator Mental Model

For elementary students, the four-register RPN stack (X, Y, Z, T) is taught as a four-story glass elevator:

- **Floor 1 (Register X):** The Lobby / Ground Floor where current typing happens.
- **Floor 2 (Register Y):** The First Balcony where numbers wait for two-number operations.
- **Floor 3 (Register Z):** The Second Balcony for intermediate storage.
- **Floor 4 (Register T):** The Penthouse / Constant Dispenser that duplicates downward during continuous operations.

B.2 Kindergarten Lesson Plans (Ages 5–6)

B.2.1 Lesson K.1: One-to-One Correspondence & Counting to 10

- **Standards:** CCSS.MATH.CONTENT.K.CC.B.4; TEKS K.2.B.
- **Learning Objective:** Students will place up to 10 physical counters onto a Ten-Frame Studio tray while stepping through counts on the SC-6 LCD display using Ten-Frame Mode (**[FRAME]**).
- **Manipulatives:** Ten-Frame Studio tray (`ten_frame_tray.scad`), 10 two-color flip counters (yellow/red).
- **Tactile Warm-Up (5 min):** "Place 4 yellow counters in the top row. Count them with your finger: one, two, three, four. Now tap one red counter into the next space. How many now?"

Verbatim Teacher Dialogue Script

Teacher: "Hold up your SC-6 calculator. Tap the Number Rack key **[g] [COUNT]**. Look at the glass screen. Do you see the two empty rows of five boxes, just like your wooden tray?"

Students: "Yes! It looks like our tray!"

Teacher: "Now, let us drop one counter into both trays at the same time. Place one yellow counter on your tray. At the same time, tap `1 [+]` on your calculator. What popped onto your screen?"

Student (Leo): "A little dot filled the first box!"

Teacher: "Tap `1 [+]` again. And again. Stop when your top row is full. How many counters are in the top row?"

Students: "Five!"

Teacher: "What number shows in the corner?"

Students: "5!"

Keystroke	Register T	Register Z	Register Y	Register X
[g] **[COUNT]**	0	0	0	0 (10F)
1 **[+]**	0	0	0	1 (10F)
1 **[+]**	0	0	0	2 (10F)
1 **[+]**	0	0	0	3 (10F)
1 **[+]**	0	0	0	4 (10F)
1 **[+]**	0	0	0	5 (10F)

Student Practice Problems

1. Count out 7 counters on the tray and match with 7 dots on the SC-6 (`[g] [COUNT] 7`).
2. Show 10 full dots on the screen. How many rows are filled? (Both rows, answer: 10).
3. Clear the frame (**[C] [g] [COUNT]**). Enter 3 dots. How many empty boxes remain? (7 boxes).

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student taps keys rapidly, overshooting the physical counter count.	Motor impulsivity without one-to-one correspondence pairing.	"One touch on the block, one tap on the key. Say 'click' for each."

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student starts filling the bottom row first.	Lacks left-to-right, top-to-bottom reading orientation.	"The top row is the attic. Fill the attic from left to right first!"

B.2.2 Lesson K.2: Composing & Decomposing 5 (Number Bonds)

- **Standards:** CCSS.MATH.CONTENT.K.OA.A.3; TEKS K.3.A.
- **Learning Objective:** Students decompose 5 into pairs (4+1, 3+2, 2+3, 1+4) using two-color counters and verify that the sum remains invariant.
- **Manipulatives:** 5 two-color counters, 1 Ten-Frame Studio tray.
- **Tactile Warm-Up:** Shake 5 counters in a cup and spill them onto the desk. Count yellow vs. red.

Verbatim Teacher Dialogue Script

Teacher: "Spill your counters! Maya, how many yellow and how many red did you get?"

Student (Maya): "I got 3 yellow and 2 red."

Teacher: "Let us enter Maya's spill into our SC-6 elevator. Type `[3] [ENTER]`. The 3 rides up to the first balcony. Now type `[2]`. Look at Floor 1 and Floor 2. Press `[+]`. What is the total?"

Students: "5!"

Teacher: "Now spill again! David, what did you get?"

Student (David): "4 yellow and 1 red."

Teacher: "Type `[4] [ENTER] [1] [+]`. What do you get?"

Students: "Still 5!"

Keystroke	Register T	Register Z	Register Y	Register X
`[3]`	0	0	0	3
`[ENTER]`	0	0	3	3
`[2]`	0	0	3	2
`[+]`	0	0	0	5

Student Practice Problems

1. Enter 1 + 4: `[1] [ENTER] [4] [+]`. Display shows 5.
2. Enter 2 + 3: `[2] [ENTER] [3] [+]`. Display shows 5.
3. Enter 5 + 0: `[5] [ENTER] [0] [+]`. Display shows 5.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student types 32 `[+]` without `[ENTER]`, getting 32.	Forgets stack lift separator.	"Press `[ENTER]` so the 3 can climb into the balcony before 2 enters the lobby!"
Student thinks 3+2 and 2+3 have different totals.	Has not internalized commutativity.	"Turn your tray around 180^°. Did any counters disappear?"

B.2.3 Lesson K.3: Comparing Quantities (More, Fewer, Same)

- **Standards:** CCSS.MATH.CONTENT.K.CC.C.6; TEKS K.2.E.
- **Learning Objective:** Students compare two towers of counting tiles using a balance scale, determine the difference, and verify on SC-6 via subtraction.
- **Manipulatives:** Equal-arm balance scale (`algebra_factoring_parts.scad`), 20 counting tiles from Counting Studio (10 blue, 10 gold).
- **Tactile Warm-Up:** Place 7 blue tiles in the left pan and 4 gold tiles in the right pan. Observe which pan drops.

Verbatim Teacher Dialogue Script

> **Teacher:** "Which pan is heavier and lower?"
>
> **Students:** "The blue pan with 7 tiles!"
>
> **Teacher:** "How many more tiles are in the blue pan? Let us ask the calculator to find the difference. Put the bigger number in first: `[7] [ENTER]`. Now put the smaller number in: `[4]`. Press `[-]`. What is the difference?"
>
> **Students:** "3!"
>
> **Teacher:** "Add 3 tiles to the gold pan. What happens to the balance beam?"
>
> **Students:** "It levels out! They are equal!"

Keystroke	Register T	Register Z	Register Y	Register X
`[7]`	0	0	0	7
`[ENTER]`	0	0	7	7
`[4]`	0	0	7	4
`[-]`	0	0	0	3

Student Practice Problems

1. Compare 9 and 5: `[9] [ENTER] [5] [-]`. Difference is `4`.
2. Compare 8 and 8: `[8] [ENTER] [8] [-]`. Difference is `0` (balanced).
3. Compare 6 and 2: `[6] [ENTER] [2] [-]`. Difference is `4`.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student enters `[4] [ENTER] [7] [-]` and gets `-3`.	Operates with smaller number first.	"In subtraction, the heavy tower enters the elevator first!"
Student equates physical height with numerical quantity when using mismatched objects.	Perceptual salience over unit count.	"Count the cubes one-by-one; do not just look with your eyes."

B.3 Grade 1 Lesson Plans (Ages 6–7)

B.3.1 Lesson 1.1: Bridging Through 10 with the Ten-Frame

- **Standards:** CCSS.MATH.CONTENT.1.OA.C.6; TEKS 1.3.C.
- **Learning Objective:** Students solve 8 + 5 by decomposing 5 into 2 + 3, filling the first ten-frame, and recognizing that 8 + 5 = 10 + 3 = 13.
- **Manipulatives:** 2 Ten-Frame Studio trays side-by-side, 20 two-color counters.
- **Tactile Warm-Up:** Place 8 counters in the first frame. Place 5 in hand. How many are needed to fill the first frame?

Verbatim Teacher Dialogue Script

> **Teacher:** "We have 8 yellow counters in Tray 1. We want to add 5 red counters. Where must the first 2 red counters go?"
>
> **Student (Sophia):** "They must go in the empty spots of Tray 1 to make 10!"
>
> **Teacher:** "Great! That makes 10. How many red counters are still in your hand?"
>
> **Student (Sophia):** "3 counters!"
>
> **Teacher:** "Put them in Tray 2. So 8 plus 5 is the same as 10 plus 3! Let us see this on the SC-6. Type `[8] [ENTER] [5] [+]`. What do you get?"
>
> **Students:** "13!"
>
> **Teacher:** "Now press `[FRAME]`. See the two frames on screen: one completely full (10), and the second has 3 dots!"

Keystroke	Register T	Register Z	Register Y	Register X
`[8]`	0	0	0	8
`[ENTER]`	0	0	8	8
`[5]`	0	0	8	5
`[+]`	0	0	0	13
`[FRAME]`	0	0	0	13(10F)

Student Practice Problems

1. Solve 9 + 6: `[9] [ENTER] [6] [+] [FRAME]`. Display shows 10 + 5 = 15.
2. Solve 7 + 5: `[7] [ENTER] [5] [+] [FRAME]`. Display shows 10 + 2 = 12.
3. Solve 8 + 7: `[8] [ENTER] [7] [+] [FRAME]`. Display shows 10 + 5 = 15.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student counts on fingers starting from 1 (1, 2, 3 ... 13).	Lacks ten-structuring automaticity.	"Lock the 8 in your mind. How many to 10? Two! Now add the rest."
Student places all 5 in the second frame, leaving first incomplete.	Does not recognize benchmark 10 constraint.	"A ten-frame must be full before you open a new one!"

B.3.2 Lesson 1.2: Commutative Property of Addition (a + b = b + a)

- **Standards:** CCSS.MATH.CONTENT.1.OA.B.3; TEKS 1.3.E.

- **Learning Objective:** Students construct two towers (3+7 and 7+3) and use the exchange key `[x⇔y]` on the SC-6 to prove sum invariance.
- **Manipulatives:** Four-color counting tiles (blue and gold).
- **Tactile Warm-Up:** Build a tower of 3 blue tiles stacked onto 7 gold tiles. Turn the tower over.

Verbatim Teacher Dialogue Script

> **Teacher:** "Enter `[3] [ENTER] [7]`. Register Y has 3, Register X has 7. Press `[x⇔y]`. What happened?"
> **Students:** "They swapped places! 7 is on top, 3 is on bottom!"
> **Teacher:** "Press `[+]`. What is the sum?"
> **Students:** "10!"
> **Teacher:** "Press `[f] [LASTX] [3] [+]`. It is still 10! Flipping the order never changes the sum!"

Keystroke	Register T	Register Z	Register Y	Register X
`[3]`	0	0	0	3
`[ENTER]`	0	0	3	3
`[7]`	0	0	3	7
`[x⇔y]`	0	0	7	3
`[+]`	0	0	0	10

Student Practice Problems

1. Test 4 + 8 vs. 8 + 4: `[4] [ENTER] [8] [+]` = 12; `[8] [ENTER] [4] [+]` = 12.
2. Test 2 + 9 vs. 9 + 2: both equal 11.
3. Test 6 + 5 vs. 5 + 6: both equal 11.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student assumes subtraction is also commutative (7-3 = 3-7).	Overgeneralizes additive symmetry to non-symmetric operations.	"Try `[3] [ENTER] [7] [-]` on your calculator. Do you get 4 or -4?"

B.3.3 Lesson 1.3: Number Bonds & Part-Whole Missing Addends

- **Standards:** CCSS.MATH.CONTENT.1.OA.D.8; TEKS 1.5.D.
- **Learning Objective:** Students solve missing addend problems (? + 6 = 14) by modeling whole-part subtraction on the SC-6.
- **Manipulatives:** 14 counting tiles from the Counting Studio; cup hiding an unknown number.
- **Tactile Warm-Up:** Place 14 tiles on desk. Teacher hides 6 under a cup. How many are visible? (8 tiles).

Verbatim Teacher Dialogue Script

> **Teacher:** "We started with a set of 14 tiles. I put some under this cup, and 6 are left on the desk. How do we find what is under the cup?"
>
> **Student:** "Take away the 6 from the 14!"
>
> **Teacher:** "Key it into the SC-6: Whole set first: `14 [ENTER]`. Visible part second: **[6]** . Take it away: **[-]** . What is in the lobby?"
>
> **Students:** "8!"
>
> **Teacher:** "Lift the cup! Count the tiles! Exactly 8!"

Keystroke	Register T	Register Z	Register Y	Register X
14	0	0	0	14
[ENTER]	0	0	14	14
[6]	0	0	14	6
[-]	0	0	0	8

Student Practice Problems

1. ? + 5 = 12: `12 [ENTER] [5] [-]` = 7.
2. ? + 9 = 16: `16 [ENTER] [9] [-]` = 7.
3. ? + 8 = 15: `15 [ENTER] [8] [-]` = 7.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student adds 14 + 6 to get 20.	Keywords trigger addition without spatial whole-part analysis.	"Can the hidden part be bigger than the whole train?"

B.3.4 Lesson 1.4: Place Value: Bundling 10 Ones into 1 Ten Rod

- **Standards:** CCSS.MATH.CONTENT.1.NBT.B.2; TEKS 1.2.B.
- **Learning Objective:** Students trade 10 unit cubes for 1 ten-rod and understand two-digit numbers as tens and ones.
- **Manipulatives:** Base-10 kit (`place_value_parts.scad`): unit cubes (1 cm) and ten-rods (10 cm).
- **Tactile Warm-Up:** Count out 13 single unit cubes. Lay them next to a ten-rod. Trade 10 cubes for 1 rod.

Verbatim Teacher Dialogue Script

> **Teacher:** "Hold up 13 cubes. Lay 10 of them against one green rod. Do they have the exact same length?"
>
> **Students:** "Yes, exactly the same!"
>
> **Teacher:** "Put the 10 loose cubes back in the box and keep the green rod. Now what do you have on your desk?"
>
> **Students:** "One ten and three ones!"
>
> **Teacher:** "Type `13` on the SC-6. The digit 1 means 1 full rod of ten. The digit 3 means 3 loose ones!"

Keystroke	Register T	Register Z	Register Y	Register X
10	0	0	0	10
[ENTER]	0	0	10	10
[3]	0	0	10	3
[+]	0	0	0	13

Student Practice Problems

1. Model 2 tens and 5 ones: `20 [ENTER] [5] [+]` = 25.
2. Model 3 tens and 8 ones: `30 [ENTER] [8] [+]` = 38.
3. Model 4 tens and 0 ones: `40 [ENTER] [0] [+]` = 40.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student writes '103' for thirteen.	Writes numbers concatenating 10 and 3.	"The 1 ten already carries the 0 inside it until the 3 sits in its seat!"

B.4 Grade 2 Lesson Plans (Ages 7–8)

B.4.1 Lesson 2.1: Skip-Counting Ladders with Superpower 1 ([g] [REP])

- **Standards:** CCSS.MATH.CONTENT.2.NBT.A.2; TEKS 2.2.C.
- **Learning Objective:** Students generate skip-counting sequences (twos, fives, tens) using continuous stack replication ([g] [REP]).
- **Manipulatives:** Counting tiles from Counting Studio stacked in towers of 5.
- **Tactile Warm-Up:** Line up six towers of 5 tiles. Skip-count aloud: 5, 10, 15, 20, 25, 30.

Verbatim Teacher Dialogue Script

> **Teacher:** "Today we teach our calculator to skip-count automatically using Superpower 1: [g] [REP] ! Type [5] . Now press blue [g] and [g] [REP] . What did [g] [REP] do?"
>
> **Student (Leo):** "It copied 5 into all four elevator floors: T, Z, Y, and X!"
>
> **Teacher:** "Now press [+] once. What is on Floor 1?"
>
> **Students:** "10!"
>
> **Teacher:** "Tap [+] again! And again!"
>
> **Students:** "15! 20! 25! 30!"
>
> **Teacher:** "Floor T at the top of the elevator keeps dispensing a fresh 5 every time you add!"

Keystroke	Register T	Register Z	Register Y	Register X
[5]	0	0	0	5
[g] [REP]	5	5	5	5

Keystroke	Register T	Register Z	Register Y	Register X
[+]	5	5	5	10
[+]	5	5	5	15
[+]	5	5	5	20

Student Practice Problems

1. Skip-count by 2 up to 16: `[2] [g] [REP] [+] ...`
2. Skip-count by 10 up to 70: `10 [g] [REP] [+] ...`
3. Skip-count by 3 up to 21: `[3] [g] [REP] [+] ...`

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student taps [ENTER] instead of [+].	Confuses stack replication with arithmetic operation.	"[ENTER] lifts passengers up; [+] brings the top passenger down to combine!"

B.4.2 Lesson 2.2: Two-Digit Addition with Regrouping

- **Standards:** CCSS.MATH.CONTENT.2.NBT.B.5; TEKS 2.4.B.
- **Learning Objective:** Students solve 38 + 27 by modeling tens and ones with Base-10 blocks and confirming the regrouped sum on the SC-6.
- **Manipulatives:** Base-10 blocks: 6 ten-rods, 15 unit cubes.
- **Tactile Warm-Up:** Build 38 (3 rods, 8 cubes) and 27 (2 rods, 7 cubes). Combine the cubes: 8 + 7 = 15. Trade 10 cubes for 1 rod.

Verbatim Teacher Dialogue Script

Teacher: "When we combined 8 loose cubes and 7 loose cubes, we got 15 cubes. What do we do when we have more than 10 cubes?"

Students: "Trade 10 cubes for 1 ten-rod!"

Teacher: "Now count your rods: 3 rods + 2 rods + 1 traded rod = 6 rods. And 5 loose cubes remain. That is 65! Let us confirm on SC-6: `38 [ENTER] 27 [+]`."

Students: "65!"

Keystroke	Register T	Register Z	Register Y	Register X
38	0	0	0	38
[ENTER]	0	0	38	38
27	0	0	38	27
[+]	0	0	0	65

Student Practice Problems

1. 46 + 28: `46 [ENTER] 28 [+]` = 74.
2. 57 + 35: `57 [ENTER] 35 [+]` = 92.
3. 19 + 64: `19 [ENTER] 64 [+]` = 83.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student adds tens and ones separately on paper and writes '515' (3+2=5, 8+7=15).	Fails to carry regrouped ten into the tens column.	"15 cubes has a ten inside it! Trade the 10 cubes for a rod first!"

B.4.3 Lesson 2.3: Two-Digit Subtraction with Decomposition

- **Standards:** CCSS.MATH.CONTENT.2.NBT.B.7; TEKS 2.4.C.
- **Learning Objective:** Students solve 52 - 26 by decomposing 1 ten-rod into 10 unit cubes.
- **Manipulatives:** Base-10 blocks (5 ten-rods, 2 unit cubes).
- **Tactile Warm-Up:** Set out 52. Try to remove 6 unit cubes. Observe that only 2 cubes are loose.

Verbatim Teacher Dialogue Script

> **Teacher:** "We have 5 rods and 2 cubes. We need to take away 26, which means 2 rods and 6 cubes. Can we take 6 cubes from 2 cubes?"
>
> **Students:** "No, not enough cubes!"
>
> **Teacher:** "What can we break open?"
>
> **Student (Maya):** "Unbundle one of the ten-rods into 10 loose cubes!"
>
> **Teacher:** "Do it! Now you have 4 rods and 12 cubes. Take away 6 cubes: 6 remain. Take away 2 rods: 2 remain. Answer: 26! Key it in: `52 [ENTER] 26 [-]`."
>
> **Students:** "26!"

Keystroke	Register T	Register Z	Register Y	Register X
52	0	0	0	52
[ENTER]	0	0	52	52
26	0	0	52	26
[-]	0	0	0	26

Student Practice Problems

1. 63 - 27: `63 [ENTER] 27 [-]` = 36.
2. 71 - 38: `71 [ENTER] 38 [-]` = 33.
3. 80 - 45: `80 [ENTER] 45 [-]` = 35.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student subtracts smaller from larger digit on paper (6-2=4, writing 34).	Avoidance of regrouping by inverting digit roles.	"The top number is what you have in the bank. You cannot steal from the bottom number!"

B.4.4 Lesson 2.4: Even and Odd Numbers via Equal Pairing & [g] [÷R]

- **Standards:** CCSS.MATH.CONTENT.2.OA.C.3; TEKS 2.7.A.
- **Learning Objective:** Students determine if a number is even or odd by pairing counters and checking for remainder 0 vs. 1 using `[g] [÷R]`.
- **Manipulatives:** 15 counters per student pair.
- **Tactile Warm-Up:** Pair up 11 counters in two parallel rows. Does one counter stick out alone?

Verbatim Teacher Dialogue Script

> **Teacher:** "Line up 11 counters in pairs of two. Is there a leftover counter without a partner?"
>
> **Students:** "Yes, one counter is lonely!"
>
> **Teacher:** "That means 11 is an *odd* number! Let us test with Superpower 2: `[g] [÷R]`. Type `11 [ENTER] [2] [g] [÷R]`."
>
> **Teacher:** "Register X shows 5 pairs. Now press `[x⇔y]`. What is in Register Y?"
>
> **Students:** "1! The remainder is 1!"
>
> **Teacher:** "Any number with a remainder of 1 when divided by 2 is ODD! If the remainder is 0, it is EVEN!"

Keystroke	Register T	Register Z	Register Y	Register X
11	0	0	0	11
`[ENTER]`	0	0	11	11
`[2]`	0	0	11	2
`[g]` `[÷R]`	0	0	1 (Rem)	5 (Quot)
`[x⇔y]`	0	0	5 (Quot)	1 (Rem)

Student Practice Problems

1. Test 14: `14 [ENTER] [2] [g] [÷R] [x⇔y]` → Remainder 0 (EVEN).
2. Test 17: `17 [ENTER] [2] [g] [÷R] [x⇔y]` → Remainder 1 (ODD).
3. Test 20: `20 [ENTER] [2] [g] [÷R] [x⇔y]` → Remainder 0 (EVEN).

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student looks only at first digit of two-digit number (e.g. thinking 16 is odd because 1 is odd).	Ignores place value significance of ones digit.	"Look only at the ones place! Can 6 ones be shared equally?"

B.5 Grade 3 Lesson Plans (Ages 8–9)

B.5.1 Lesson 3.1: Arrays, Equal Groups & Area with [f] [RECT]

- **Standards:** CCSS.MATH.CONTENT.3.OA.A.1, 3.MD.C.7; TEKS 3.4.D, 3.6.C.
- **Learning Objective:** Students construct a 6 × 4 array, compute area using `[f] [RECT]`, and rotate it 90^° to demonstrate commutativity (6 × 4 = 4 × 6 = 24).
- **Manipulatives:** Four-Color Counting Studio (144-tile kit in 13U Gridfinity box), Gridfinity 4x4 coordinate baseplate.
- **Tactile Warm-Up:** Build a rectangle 6 tiles long and 4 tiles wide using White counting tiles on the baseplate.

Verbatim Teacher Dialogue Script

Teacher: "How many columns of 4 tiles did you make?"

Students: "6 columns!"

Teacher: "Count all the tiles covering the rectangle. How many?"

Students: "24 tiles!"

Teacher: "In geometry, the surface covered by tiles is called *area*. On the SC-6, we have a dedicated geometry key: `[f] [RECT]`. Type `[6] [ENTER] [4]`."

Teacher: "Now press yellow `[f]` and `[f] [RECT]`. What is the area?"

Students: "24!"

Teacher: "Turn the tray sideways. Now it is 4 columns of 6. Test: `[4] [ENTER] [6] [f] [RECT]`. Still 24!"

Keystroke	Register T	Register Z	Register Y	Register X
`[6]`	0	0	0	6
`[ENTER]`	0	0	6	6
`[4]`	0	0	6	4
`[f]` `[RECT]`	0	0	0	24

Student Practice Problems

1. 7 × 5 rug: `[7] [ENTER] [5] [f] [RECT]` = 35 square units.
2. 8 × 3 garden bed: `[8] [ENTER] [3] [f] [RECT]` = 24 square units.
3. 9 × 4 patio: `[9] [ENTER] [4] [f] [RECT]` = 36 square units (built with all 36 Radiant Red+Gold tiles!).

Classroom Station Partner Game: "Capture the Rectangle"

- **Materials:** Four-Color Counting Tiles (Player 1 in Archival White, Player 2 in Cobalt Red+Blue Silk, with Player 3 in Radiant Red+Gold Silk and Player 4 in Slate Blue-Gray PLA), SC-6 Calculator, 2 Polyhedral Dice (or roll via `[DICE]`).
- **Gameplay:** Player 1 rolls two factors (e.g., 5 and 4). Player 1 calculates area on the SC-6 (`5 [ENTER] 4 [×] = 20`), assembles a 5 × 4 rectangle in their color, and claims their territory on the table. Player 2 rolls, computes, assembles, and places their rectangle adjacent to Player 1.
- **The Four-Color Challenge Rule:** Placed rectangles of the same color cannot touch along a side! The SC-6 calculator serves as the referee: if a challenged player computes an area incorrectly, they forfeit their turn.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student confuses perimeter with area.	Conflates boundary fence with surface tiles.	"Trace the fence with your finger—that is perimeter. Lay your hand over the blocks—that is area!"

B.5.2 Lesson 3.2: Division as Fair Sharing vs. Grouping ([g] [÷R])

- **Standards:** CCSS.MATH.CONTENT.3.OA.A.2; TEKS 3.4.H.
- **Learning Objective:** Students model dividing 23 tiles among 4 Gridfinity holding bays, finding quotient 5 and remainder 3 using `[g] [÷R]`.
- **Manipulatives:** 23 Four-Color Counting Tiles, 4 Gridfinity sorting trays/bays.
- **Tactile Warm-Up:** Deal 23 counting tiles one by one into the 4 trays until no more equal rounds can be dealt.

Verbatim Teacher Dialogue Script

Teacher: "How many cookies ended up in each cup?"

Students: "5 cookies!"

Teacher: "How many cookies are left on the table that cannot be shared equally?"

Students: "3 cookies!"

Teacher: "Let us verify with the SC-6 quotient and remainder engine. Dividend first: `23 [ENTER]`. Divisor second: `[4]`. Superpower 2: `[g]` `[÷R]`. What is in Register X?"

Students: "5! The quotient!"

Teacher: "Press `[x⇔y]`. What is in Register Y?"

Students: "3! The remainder!"

Keystroke	Register T	Register Z	Register Y	Register X
23	0	0	0	23
`[ENTER]`	0	0	23	23
`[4]`	0	0	23	4
`[g]` `[÷R]`	0	0	3 (Rem)	5 (Quot)
`[x⇔y]`	0	0	5 (Quot)	3 (Rem)

Student Practice Problems

1. 19 markers shared among 3 pencil cases: `19 [ENTER] [3] [g] [÷R]` → Q=6, R=1.
2. 31 apples packed into bags of 6: `31 [ENTER] [6] [g] [÷R]` → Q=5, R=1.
3. 35 tiles partitioned into teams of 4: `35 [ENTER] [4] [g] [÷R]` → Q=8, R=3.

Classroom Station Partner Game: "Remainder Race to Bank"

- **Materials:** 36 Counting Tiles, 1 Die, SC-6 Calculator.

- **Gameplay:** Players start with a shared pool of 36 tiles. Player 1 rolls a die (e.g., 5) and keys `36 [ENTER] 5 [g] [÷R]`. Line X displays quotient 7 (which returns to the supply depot), and line Y (**[x⇔y]**) displays remainder 1! Player 1 takes the 1 remainder tile into their personal bank.
- **Winning:** Players alternate turns with the remaining tiles. The player who banks the most remainder tiles wins the round.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student writes 23 ÷ 4 = 5.75 and doesn't know what to do with the leftover cookies.	Standard decimal division obscures integer remainder context.	"Can you hand a guest 0.75 of an unwrapped cookie at a party? Give them 5 cookies and keep 3 in the box!"

B.5.3 Lesson 3.3: Introduction to Unit Fractions with Fraction Studio

- **Standards:** CCSS.MATH.CONTENT.3.NF.A.1; TEKS 3.3.A.
- **Learning Objective:** Students compare physical fraction towers ((1 / 2), (1 / 3), (1 / 4), (1 / 6), (1 / 8)) against the 84.0 mm whole tower and understand that larger denominators produce smaller unit pieces.
- **Manipulatives:** Fraction Studio tower set (`fraction_studio_parts.scad`).
- **Tactile Warm-Up:** Place the 1-Whole tower (84 mm) on desk. Stack two (1 / 2) blocks next to it. Observe equal heights.

Verbatim Teacher Dialogue Script

Teacher: "Hold up a (1 / 2) block and a (1 / 8) block. Which block is taller?"

Students: "The (1 / 2) block is much taller!"

Teacher: "Why is (1 / 8) smaller if 8 is a bigger number than 2?"

Student (David): "Because you had to cut the same candy bar into 8 pieces instead of just 2 pieces! Each slice is tiny!"

Teacher: "Brilliant! The denominator tells us how many equal pieces the whole was cut into. Enter (1 / 2) on the SC-6: **[.] 1 [.] 2 [ENTER]**. Enter (1 / 8): `[.] 1 [.] 8`. Now press **[-]**. The difference is positive: (1 / 2) is (3 / 8) larger!"

Keystroke	Register T	Register Z	Register Y	Register X
`[.] 1 [.] 2`	0	0	0	1/2
[ENTER]	0	0	1/2	1/2
`[.] 1 [.] 8`	0	0	1/2	1/8
[-]	0	0	0	3/8

Student Practice Problems

1. Show that three (1 / 3) blocks equal 1 whole: **[.] 1 [.] 3 [ENTER] [3] [×]** = 1.
2. Compare (1 / 4) and (1 / 2): **[.] 1 [.] 2 [ENTER] [.] 1 [.] 4 [-]** = (1 / 4).
3. Show that four (1 / 8) blocks equal (1 / 2): **[.] 1 [.] 8 [ENTER] [4] [×]** = (1 / 2).

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student believes (1 / 8) > (1 / 4) because 8 > 4.	Whole-number bias applied to denominators.	"Place the physical (1 / 8) tower next to the (1 / 4) tower. Which one touches the ceiling first?"

B.5.4 Lesson 3.4: Perimeter of Polygons vs. Area using [Σ+]

- **Standards:** CCSS.MATH.CONTENT.3.MD.D.8; TEKS 3.7.B.
- **Learning Objective:** Students find the perimeter of an irregular 5-sided polygon by accumulating sides with **[Σ+]**, distinguishing it from internal area.
- **Manipulatives:** Geoboard with rubber bands (`counting_tiles_parts.scad`), ruler.
- **Tactile Warm-Up:** Stretch a rubber band around pins at (0,0), (6,0), (6,4), (3,7), (0,4) to form a pentagon.

Verbatim Teacher Dialogue Script

Teacher: "To find the perimeter, we walk all the way around the outer boundary fence. Let us add the sides using our SC-6 statistical accumulator key **[Σ+]**! First, clear memory: **[g]** **[CLΣ]**."

Teacher: "Side 1 is 6 cm: **[6]** **[Σ+]**. Side 2 is 4 cm: **[4]** **[Σ+]**. Side 3 is 4.2 cm: `4.2 [⊠+]`. Side 4 is 4.2 cm: `4.2 [⊠+]`. Side 5 is 4 cm: **[4]** **[Σ+]**."

Teacher: "How many sides did we measure? n = 5! Now press **[f]** **[Σx]**. What is the total perimeter?"

Students: "22.4 centimeters!"

Keystroke	Register T	Register Z	Register Y	Register X
[g] **[CLΣ]**	0	0	0	0
[6] **[Σ+]**	0	0	0	n = 1
[4] **[Σ+]**	0	0	0	n = 2
`4.2` **[Σ+]**	0	0	0	n = 3
`4.2` **[Σ+]**	0	0	0	n = 4
[4] **[Σ+]**	0	0	0	n = 5
[f] **[Σx]**	0	0	0	22.4

Student Practice Problems

1. Triangle with sides 5, 7, 8: **[g]** **[CLΣ]** **[5]** **[Σ+]** **[7]** **[Σ+]** **[8]** **[Σ+]** **[f]** **[Σx]** = 20.
2. Rectangle perimeter (8 + 5 + 8 + 5): **[f]** **[Σx]** = 26.
3. Hexagon with sides 3, 3, 4, 4, 5, 5: **[f]** **[Σx]** = 24.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student forgets to clear statistical memory before starting problem 2.	Persistent accumulator contamination.	"Always check n. If n is not zero, press **[g]** **[CLΣ]** before walking your fence!"

B.6 Grade 4 Lesson Plans (Ages 9–10)

B.6.1 Lesson 4.1: Long Division with Remainders ([g] [÷R])

- **Standards:** CCSS.MATH.CONTENT.4.OA.A.3; TEKS 4.4.F.
- **Learning Objective:** Students solve a multi-step hiking trail provisioning problem (89 oz water distributed into 16 oz flasks) using `[g] [÷R]`.
- **Manipulatives:** Graduated cylinders, counting tile measuring sticks (`UNIF-01`).
- **Tactile Warm-Up:** Assemble an 89-unit bar using counting tiles. Break off 16-unit chunks. Count full chunks and leftovers.

Verbatim Teacher Dialogue Script

Teacher: "We have 89 fluid ounces of water. Each water bottle holds 16 fluid ounces. How many full bottles can we pack, and how many ounces are left over?"

Student (Maya): "Type `89 [ENTER] 16 [g] [÷R]`!"

Teacher: "What is on your screen?"

Students: "5!"

Teacher: "That is 5 full flasks! Now swap registers: press `[x⇔y]`. What is in Register Y?"

Students: "9! 9 ounces left over!"

Teacher: "Check your answer: 5 bottles times 16 oz is 80 oz, plus 9 oz equals 89 oz! Perfect!"

Keystroke	Register T	Register Z	Register Y	Register X
89	0	0	0	89
`[ENTER]`	0	0	89	89
16	0	0	89	16
`[g]` `[÷R]`	0	0	9 (Rem)	5 (Quot)
`[x⇔y]`	0	0	5 (Quot)	9 (Rem)

Student Practice Problems

1. 145 campers into cabins of 12: `145 [ENTER] 12 [g] [÷R]` → Q=12 cabins, R=1 camper.
2. 250 eggs packed in cartons of 12: `250 [ENTER] 12 [g] [÷R]` → Q=20 cartons, R=10 eggs.
3. 500 pencils in packs of 24: `500 [ENTER] 24 [g] [÷R]` → Q=20 packs, R=20 pencils.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student interprets remainder 9 as 0.9 bottles.	Confuses integer discrete leftovers with decimal fraction.	"Is that 9 tenths of a bottle, or 9 whole ounces in the bottom of the pot? Remember the units!"

B.6.2 Lesson 4.2: Equivalent Fractions & Simplification ([g] [SIMP])

- **Standards:** CCSS.MATH.CONTENT.4.NF.A.1; TEKS 4.3.C.
- **Learning Objective:** Students build equivalent fraction models ((6 / 8) = (3 / 4)) and reduce them on the SC-6 using Superpower 3 (`[g] [SIMP]`).
- **Manipulatives:** Fraction Studio towers ((1 / 8) and (1 / 4) blocks).
- **Tactile Warm-Up:** Line up six (1 / 8) blocks in the channel. Find which group of (1 / 4) blocks matches the exact length.

Verbatim Teacher Dialogue Script

> **Teacher:** "How many (1 / 4) blocks match six (1 / 8) blocks?"
>
> **Students:** "Three (1 / 4) blocks!"
>
> **Teacher:** "So (6 / 8) is equivalent to (3 / 4). Now let us watch the SC-6 simplify it step-by-step. Enter six-eighths: `[.] 6 [.] 8 [ENTER]`. Press blue `[g]` and `[g] [SIMP]`. What does the screen show?"
>
> **Students:** "`3/4`!"
>
> **Teacher:** "What factor did the calculator divide out from top and bottom?"
>
> **Student (Leo):** "It divided both numbers by 2!"
>
> **Teacher:** "Now press `[g]` `[SIMP]` again. What does it say?"
>
> **Students:** "`LOWEST TERMS`! It cannot be simplified any further because 3 is prime!"

Keystroke	Register T	Register Z	Register Y	Register X
`[.] 6 [.] 8`	0	0	0	6/8
`[ENTER]`	0	0	6/8	6/8
`[g]` `[SIMP]`	0	0	6/8	3/4
`[g]` `[SIMP]`	0	0	6/8	3/4 (LOWEST)

Student Practice Problems

1. Simplify (8 / 12): `[.] 8 [.] 12 [ENTER] [g] [SIMP]` = (2 / 3).
2. Simplify (10 / 25): `[.] 10 [.] 25 [ENTER] [g] [SIMP]` = (2 / 5).
3. Simplify (18 / 24): `[.] 18 [.] 24 [ENTER] [g] [SIMP]` = (3 / 4).

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student divides numerator by 2 and denominator by 3 ((6 ÷ 2 / 8 ÷ 4)).	Fails to recognize that scaling requires multiplying or dividing by (n / n) = 1.	"You must treat the top and bottom with equal justice! Divide both by the exact same number!"

B.6.3 Lesson 4.3: Adding & Subtracting Fractions with Unlike Denominators

- **Standards:** CCSS.MATH.CONTENT.4.NF.B.3; TEKS 4.3.E.
- **Learning Objective:** Students solve (1 / 2) + (1 / 4) and (2 / 3) - (1 / 6) using Fraction Studio blocks and SC-6 fraction arithmetic.
- **Manipulatives:** Fraction Studio towers.

- **Tactile Warm-Up:** Put one (1 / 2) block and one (1 / 4) block end-to-end. Measure total length with (1 / 4) blocks.

Verbatim Teacher Dialogue Script

> **Teacher:** "How many fourths fit across (1 / 2) + (1 / 4)?"
> **Students:** "Three fourths!"
> **Teacher:** "Enter it on the SC-6: `[.] 1 [.] 2 [ENTER] [.] 1 [.] 4 [+]`. What is the result?"
> **Students:** "`3/4`!"
> **Teacher:** "Now try a subtraction: (5 / 6) - (1 / 3). Key: `[.] 5 [.] 6 [ENTER] [.] 1 [.] 3 [-]`. What do you get?"
> **Students:** "`1/2`!"

Keystroke	Register T	Register Z	Register Y	Register X
`[.] 1 [.] 2`	0	0	0	1/2
`[ENTER]`	0	0	1/2	1/2
`[.] 1 [.] 4`	0	0	1/2	1/4
`[+]`	0	0	0	3/4

Student Practice Problems

1. (1 / 3) + (1 / 6): `[.] 1 [.] 3 [ENTER] [.] 1 [.] 6 [+]` = (1 / 2).
2. (3 / 4) - (1 / 8): `[.] 3 [.] 4 [ENTER] [.] 1 [.] 8 [-]` = (5 / 8).
3. (2 / 5) + (3 / 10): `[.] 2 [.] 5 [ENTER] [.] 3 [.] 10 [+]` = (7 / 10).

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student adds across numerators and denominators ((1 / 2) + (1 / 4) = (2 / 6)).	Treats numerator and denominator as independent whole numbers.	"Look at your blocks! Is (2 / 6) bigger than (1 / 2)? No! You cannot add pieces of different sizes until they share a common name!"

B.6.4 Lesson 4.4: Angles & Rotations with the 360^° Volvelle Protractor

- **Standards:** CCSS.MATH.CONTENT.4.MD.C.6; TEKS 4.7.C.
- **Learning Objective:** Students measure acute, right, and obtuse angles using the 360^° Volvelle (`sc6_volvelle_protractor.scad`) and calculate supplementary and complementary angles.
- **Manipulatives:** Two-disc rotating Volvelle protractor, pattern blocks.
- **Tactile Warm-Up:** Align Volvelle pointer to 0^°. Rotate top disc to match the corner of an orange square (90^°).

Verbatim Teacher Dialogue Script

> **Teacher:** "Rotate your Volvelle to match the yellow hexagon angle. What degree reading does the red cursor line up with?"
> **Students:** "120 degrees!"
> **Teacher:** "If two angles sit on a straight line, their sum is 180^° (supplementary). How many degrees are left to make a straight line? Calculate on SC-6: `180 [ENTER] 120 [-]`."

Students: "60 degrees!"

Teacher: "Check with your green triangle corner: it fits the 60^° gap perfectly!"

Keystroke	Register T	Register Z	Register Y	Register X
180	0	0	0	180
[ENTER]	0	0	180	180
120	0	0	180	120
[-]	0	0	0	60

Student Practice Problems

1. Complement of 35^° (90 - 35): [9] [0] [ENTER] [3] [5] [-] = 55^°.
2. Supplement of 45^° (180 - 45): [1] [8] [0] [ENTER] [4] [5] [-] = 135^°.
3. Sum of four angles meeting at a point (90 + 120 + 80 + ?): [3] [6] [0] [ENTER] ... = 70^°.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student reads outer scale instead of inner scale on standard protractor, reporting 60^° for an obtuse angle.	Dual-scale confusion on semi-circular protractors.	"Look at the corner: is it sharper than a book corner or wider than a book corner? Obtuse must be > 90^°!"

B.7 Grade 5 Lesson Plans (Ages 10–11)

B.7.1 Lesson 5.1: Volume & Total Surface Area of Prisms via [Σ+]

- **Standards:** CCSS.MATH.CONTENT.5.MD.C.5, 6.G.A.4; TEKS 5.6.B.
- **Learning Objective:** Students calculate the volume and total surface area of a 5 × 4 × 3 cm wooden prism using the statistical accumulator [Σ+] without scratch paper.
- **Manipulatives:** Wooden prism (5 × 4 × 3 cm), digital caliper.
- **Tactile Warm-Up:** Count the faces on the prism. Notice that opposite faces are identical twins (3 pairs: top/bottom, front/back, left/right).

Verbatim Teacher Dialogue Script

Teacher: "First, let us calculate volume: Length × Width × Height. Key: [5] [ENTER] [4] [×] [3] [×]. Volume is 60 cm^3."

Teacher: "Now, total surface area! We must add the areas of all 6 faces. We will use the SC-6 statistical accumulator memory: [Σ+]! Clear memory first: [g] [CLΣ]."

Teacher: "Pair 1 (Top/Bottom, 5 × 4, two faces): [5] [ENTER] [4] [×] [2] [×] → 40. Press [Σ+]!"

Teacher: "Pair 2 (Front/Back, 5 × 3, two faces): [5] [ENTER] [3] [×] [2] [×] → 30. Press [Σ+]!"

Teacher: "Pair 3 (Left/Right, 4 × 3, two faces): [4] [ENTER] [3] [×] [2] [×] → 24. Press [Σ+]!"

Teacher: "Screen shows n = 3. Now press yellow [f] and [f] [Σx]. What is the total surface area?"

Students: "94 square centimeters!"

Keystroke	Register T	Register Z	Register Y	Register X
`[g] [CLΣ]`	0	0	0	0
`[5] [ENTER] [4] [×] [2] [×]`	0	0	0	40
`[Σ+]`	0	0	0	n = 1
`[5] [ENTER] [3] [×] [2] [×]`	0	0	0	30
`[Σ+]`	0	0	0	n = 2
`[4] [ENTER] [3] [×] [2] [×]`	0	0	0	24
`[Σ+]`	0	0	0	n = 3
`[f] [Σx]`	0	0	0	94

Student Practice Problems

1. Box measuring 6 × 3 × 2 cm: Volume = 36 cm^3, Surface Area = 72 cm^2.
2. Cube measuring 4 × 4 × 4 cm: Volume = 64 cm^3, Surface Area = 96 cm^2.
3. Storage crate 10 × 8 × 5 cm: Volume = 400 cm^3, Surface Area = 340 cm^2.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student calculates only 3 faces and forgets to multiply by 2.	Confuses the three unique face orientations with total face count.	"Every room has a ceiling AND a floor. Multiply each face pair by 2!"

B.7.2 Lesson 5.2: Fraction Multiplication & Division via Reciprocal ([f] [1/x])

- **Standards:** CCSS.MATH.CONTENT.5.NF.B.4, 5.NF.B.7; TEKS 5.3.I, 5.3.L.
- **Learning Objective:** Students model multiplying (2 / 3) × (3 / 4) using area grid overlays, and divide fractions by multiplying by the reciprocal using `[f] [1/x]`.
- **Manipulatives:** Transparent grid overlay sheets, dry-erase markers.
- **Tactile Warm-Up:** Shade (3 / 4) of a square vertically. Shade (2 / 3) horizontally. Count overlapping squares: (6 / 12) = (1 / 2).

Verbatim Teacher Dialogue Script

Teacher: "Enter (2 / 3) × (3 / 4) on SC-6: `[.] 2 [.] 3 [ENTER] [.] 3 [.] 4 [×]`. What is the result?"

Students: "`1/2`!"

Teacher: "Now let us divide: (3 / 4) ÷ (2 / 5). Dividing by a fraction is the same as multiplying by its flipped upside-down twin—the reciprocal! Enter (3 / 4): `[.] 3 [.] 4 [ENTER]`. Enter (2 / 5): `[.] 2 [.] 5`. Now tap yellow `[f]` and reciprocal `[f] [1/x]`. What did (2 / 5) turn into?"

Students: "`5/2`!"

Teacher: "Now press `[×]`! What is the final quotient?"

Students: "15/8 or 1(7 / 8)!"

Keystroke	Register T	Register Z	Register Y	Register X
[.] 3 [.] 4	0	0	0	3/4
[ENTER]	0	0	3/4	3/4
[.] 2 [.] 5	0	0	3/4	2/5
[f] [1/x]	0	0	3/4	5/2
[×]	0	0	0	15/8

Student Practice Problems

1. (4 / 5) × (5 / 8): **[.] 4 [.] 5 [ENTER] [.] 5 [.] 8 [×]** = (1 / 2).
2. (1 / 2) ÷ (1 / 6): **[.] 1 [.] 2 [ENTER] [.] 1 [.] 6 [f] [1/x] [×]** = 3.
3. (2 / 3) ÷ (4 / 9): **[.] 2 [.] 3 [ENTER] [.] 4 [.] 9 [f] [1/x] [×]** = (3 / 2) = 1(1 / 2).

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student reciprocates the first fraction instead of the second fraction ((4 / 3) × (2 / 5)).	Rote mnemonic "keep-change-flip" memorized without structural meaning.	"The divisor (the second passenger) is the one doing the dividing. That is the one that flips!"

B.7.3 Lesson 5.3: Order of Operations without Parentheses (Stack Architecture)

- **Standards:** CCSS.MATH.CONTENT.5.OA.A.1; TEKS 5.4.F.
- **Learning Objective:** Students evaluate complex multi-step expressions like (8 + 4) × (9 - 3) and 15 + 4 × (12 - 7) using the 4-register RPN stack with zero parentheses keys.
- **Manipulatives:** Expression cards, 4-story physical elevator cardboard model.
- **Tactile Warm-Up:** Analyze (8 + 4) × (9 - 3). What must be solved first? The two parenthetical groups!

Verbatim Teacher Dialogue Script

Teacher: "On ordinary calculators, students get lost in tangled parentheses like ((8 + 4) * (9 - 3)). If you forget one parenthesis, you get a syntax error. On the SC-6 RPN elevator, we solve inside-out naturally! Evaluate group 1: **[8] [ENTER] [4] [+]** → 12. Keep it in the elevator! Now evaluate group 2: **[9] [ENTER] [3] [-]** → 6. Look at your screen: Register Y holds 12, Register X holds 6. What operation combines them?"

Students: "Multiplication! Press **[×]**!"

Teacher: "Tap **[×]**. What is the answer?"

Students: "72!"

Teacher: "Zero parentheses keys used! The stack holds intermediate answers automatically!"

Keystroke	Register T	Register Z	Register Y	Register X
[8] [ENTER] [4]	0	0	8	4

Keystroke	Register T	Register Z	Register Y	Register X
`[+]`	0	0	0	12
`[9]`	0	0	12	9
`[ENTER]`	0	12	9	9
`[3]`	0	12	9	3
`[-]`	0	0	12	6
`[×]`	0	0	0	72

Student Practice Problems

1. (14 + 6) ÷ (7 - 2): `14 [ENTER] [6] [+] [7] [ENTER] [2] [-] [÷]` = 4.
2. 50 - (4 × 8) + 6: `50 [ENTER] [4] [ENTER] [8] [×] [-] [6] [+]` = 24.
3. $(3 + 5)^2$ - 10: **`[3] [ENTER] [5] [+] [x²] 10 [-]`** = 54.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student keys in numbers sequentially from left to right without respecting operator precedence.	Linear reading habit overriding algebraic hierarchy.	"RPN processes operators from the inside out. Build your building blocks first, then combine them!"

B.8 Grade 6 Lesson Plans (Ages 11–12)

B.8.1 Lesson 6.1: Negative Numbers, Zero Pairs & [+/-]

- **Standards:** CCSS.MATH.CONTENT.6.NS.C.5, 6.NS.C.6; TEKS 6.2.B.
- **Learning Objective:** Students model integer addition and subtraction using two-color counters (yellow = +1, red = -1), cancel zero pairs, and verify signed arithmetic on SC-6 using **`[+/-]`**.
- **Manipulatives:** 30 two-color counters (15 yellow, 15 red).
- **Tactile Warm-Up:** Place 7 yellow counters (+7) and 4 red counters (-4) on desk. Pair them up. What is left? (+3).

Verbatim Teacher Dialogue Script

Teacher: "What happens when +1 meets -1?"

Students: "They make a zero pair and cancel out!"

Teacher: "Now let us model -8 + 5. Lay out 8 red counters and 5 yellow counters. Pair up 5 zero pairs. How many counters remain?"

Students: "3 red counters! So the answer is -3!"

Teacher: "Now key it into the SC-6. Type **`[8]`**. To make it negative, press the sign toggle key **`[+/-]`**. Look at the screen—a minus sign appears before the 8. Press **`[ENTER]`**. Now type **`[5]`** and press **`[+]`**. What is the result?"

Students: "-3!"

Keystroke	Register T	Register Z	Register Y	Register X
[8]	0	0	0	8
[+/-]	0	0	0	-8
[ENTER]	0	0	-8	-8
[5]	0	0	-8	5
[+]	0	0	0	-3

Student Practice Problems

1. Solve -12 + (-7): [1] [2] [+/-] [ENTER] [7] [+/-] [+] = -19.
2. Solve 15 - (-6): [1] [5] [ENTER] [6] [+/-] [-] = 21.
3. Solve (-4) × (-8): [4] [+/-] [ENTER] [8] [+/-] [×] = 32.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student presses the operation key [-] instead of sign toggle key [+/-].	Conflates binary subtraction operator with unary negative sign.	"[-] is an action combining two numbers. [+/-] is a label stuck onto one number!"

B.8.2 Lesson 6.2: Prime Factorization, GCF & LCM ([PRIME], [g] [FACT])

- **Standards:** CCSS.MATH.CONTENT.6.NS.B.4; TEKS 6.7.A.
- **Learning Objective:** Students test numbers for primality using [PRIME], decompose composite numbers into prime factor trees using [g] [FACT], and physically verify factor products using the Prime Factor Studio logarithmic slide rule comparator and Counting Studio rectangular arrays.
- **Manipulatives:** StackCalc Prime Factor Studio (13U Gridfinity Enclosure `PRIME-01` with Logarithmic Slide Rule Comparator and 29 Proportional Blocks) and Counting & Array Studio (144 Four-Color Tiles, `UNIF-01`).
- **Tactile Warm-Up:**

1. *Counting Tile Array Test:* Take 24 counting tiles. Can they form a rectangular array with row and column dimensions ≥ 2? (Yes: 2 × 12, 3 × 8, 4 × 6). Now take 23 tiles. Try every width: 2 leaves 1 leftover; 3 leaves 2 leftover; 4 leaves 3 leftover. 23 tiles can ONLY form a straight line 1 × 23! A prime number has no rectangular matrix factorization.
2. *Napierian Slide Rule Stacking:* Place a Blue Block [2] and an Amber/Green Block [3] from the Prime Studio onto the desk next to the box. Stack Block [3] on top of Block [2]. Look at the back-wall slide rule scale: the top edge aligns EXACTLY with tick mark **6**! Adding logarithmic lengths multiplies factors: h(2) + h(3) = 12.64 mm + 20.04 mm = 32.68 mm = h(6)!

Verbatim Teacher Dialogue Script

Teacher: "Take 23 counting tiles from your Counting Studio. Try to build a rectangle that is 2 tiles wide, or 3 tiles wide. Can anyone do it without leftovers?"

Students: "No! 23 only forms a single straight line of 23 tiles!"

Teacher: "Enter 23 on the SC-6. Press yellow [f] and [PRIME]. What does the display show?"

Students: "`23 IS PRIME`!"

Teacher: "Now let's examine 60. Can 60 tiles form rectangles? Yes, many! Enter 60 and press `[PRIME]`. What does it say?"

Students: "`NOT PRIME`!"

Teacher: "To break 60 down into its fundamental atomic building blocks, press yellow `[f]` and `[g] [FACT]`. What is the prime factorization?"

Students: "`2^2 * 3 * 5`!"

Teacher: "Now open your Prime Factor Studio! Take two Blue `[2]` blocks, one Green `[3]` block, and one Yellow `[5]` block. Stack them on the desk right next to the box's slide rule comparator wall. Where does the top of your tower land?"

Students: "It hits exactly the 60 line on the back wall!"

Teacher: "John Napier discovered that adding logarithmic heights is multiplication! Now swap the order: put the `[5]` block at the bottom, then `[3]`, then the two `[2]`s. Does the height change?"

Students: "No! It still hits 60 exactly! Multiplication is commutative!"

Teacher: "Now multiply them back on the SC-6: `[2] [x²] [3] [×] [5] [×]`. You get exactly 60!"

Keystroke	Register T	Register Z	Register Y	Register X
60	0	0	0	60
`[PRIME]`	0	0	0	NOT PRIME
`[g]` `[FACT]`	0	0	0	60 ($2^2 \times 3 \times 5$)

Student Practice Problems

1. Prime factorize 84: `[8] [4] [g] [FACT]` $\rightarrow 2^2 \times 3 \times 7$.
2. Prime factorize 180: `[1] [8] [0] [g] [FACT]` $\rightarrow 2^2 \times 3^2 \times 5$.
3. Find GCF of 84 and 180: Shared prime factors $= 2^2 \times 3 = 12$.

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student claims 1 is a prime number.	Misunderstands definition of prime (must have exactly two distinct factors).	"A prime number must have *exactly two* factors: 1 and itself. How many factors does 1 have? Only one!"

B.8.3 Lesson 6.3: Ratios, Unit Rates & Golden Ratio Proportions

- **Standards:** CCSS.MATH.CONTENT.6.RP.A.2, 6.RP.A.3; TEKS 6.4.B.
- **Learning Objective:** Students calculate unit rates (240 miles on 8 gallons = 30 mpg) and compute consecutive Fibonacci ratios tending to the Golden Ratio ($\phi \approx 1.618$).
- **Manipulatives:** Double number lines, tape measures.
- **Tactile Warm-Up:** If 3 packs of gum cost $4.50, how much does 1 pack cost? ($4.50 \div 3 = 1.50$).

Verbatim Teacher Dialogue Script

Teacher: "A car drives 372 miles on 12 gallons of fuel. What is the unit rate in miles per gallon? Enter miles: `372 [ENTER]`. Enter gallons: `12`. Divide: **[÷]**. What is the rate?"

Students: "31 miles per gallon!"

Teacher: "Now let us investigate nature's secret ratio: the Fibonacci sequence (1, 1, 2, 3, 5, 8, 13, 21, 34, 55). Divide consecutive terms: 55 ÷ 34: `55 [ENTER] 34 [÷]`. What do you get?"

Students: "1.6176...!"

Teacher: "Now divide 89 ÷ 55: `89 [ENTER] 55 [÷]`!"

Students: "1.61818...!"

Teacher: "That is Phi (ϕ), the Golden Ratio found in sunflower spirals, nautilus shells, and classical architecture!"

Keystroke	Register T	Register Z	Register Y	Register X
372	0	0	0	372
[ENTER]	0	0	372	372
12	0	0	372	12
[÷]	0	0	0	31

Student Practice Problems

1. Unit price: $18.60 for 6 pairs of socks: `18.60 [ENTER] [6] [÷]` = $3.10 per pair.
2. Typing rate: 385 words in 7 minutes: `385 [ENTER] [7] [÷]` = 55 wpm.
3. Fibonacci ratio 144 ÷ 89: `144` **[ENTER]** `89` **[÷]** = 1.61797...

Misconception Diagnostic Table

Observable Student Error	Cognitive Root Cause	Targeted Remediation Prompt
Student divides gallons by miles (12 ÷ 372 = 0.032) when asked for miles per gallon.	Ignores unit dimensional grammar.	"Say the units out loud: *miles* PER *gallon*. Miles goes in first, gallons goes in second!"

B.9 Master 4-Tier Assessment Rubric & Diagnostic Protocol

Every student interaction across the 25 lesson plans is evaluated along four observable performance criteria:

Performance Band	Score	Concrete Manipulative Stage	Representational Drawing	Abstract RPN Stack Execution
Exemplary	**4 pts**	Fluidly constructs physical model with zero prompting. Explains spatial relationships and invariances clearly to peers.	Accurately sketches bar models, area arrays, or number lines with correct proportional scaling.	Keys problem into SC-6 fluently; explains register states (X, Y, Z, T); uses **[f] [LASTX]** or inverse operations to self-check.
Proficient	**3 pts**	Correctly builds model after initial launch. Self-corrects minor manipulative errors without teacher intervention.	Draws recognizable visual models matching the problem context.	Enters correct keystrokes on SC-6; successfully identifies solution on Register X.

Performance Band	Score	Concrete Manipulative Stage	Representational Drawing	Abstract RPN Stack Execution
Developing	**2 pts**	Requires teacher prompting to begin building or select correct manipulative blocks.	Sketches disorganized diagrams that fail to preserve mathematical proportionality.	Frequently omits `[ENTER]` separator or confuses `[+/-]` with `[-]`; needs step-by-step keystroke guidance.
Intervention	**1 pt**	Unable to model problem with concrete blocks; counts by ones; exhibits persistent off-task or frustrated behavior.	Does not produce pictorial representations; writes isolated digits disconnected from meaning.	Unable to operate calculator interface; relies on wild guessing without checking screen feedback.

B.10 Student Intervention Decision Tree & Cognitive Misconceptions

When a student struggles at a workshop station, follow this structured diagnostic decision protocol:

Observed Student Error	Diagnostic Root Cause	Immediate Remediation Action
Concatenated Digits (e.g., 64 instead of 6 `[ENTER]` 4)	Omitted `[ENTER]` separator before second operand	Re-anchor the **Elevator Mental Model** (*"Lift 6 to the balcony first!"*)
Nonsensical Numerical Answer (e.g., negative area)	Reversed operand order or misapplied operation	Point to physical blocks: *"Can 4 tiles have negative area?"*
Counting One-by-One from 1	Subitizing benchmark not yet internalized	Revert to **Ten-Frame Subitizing Drill** (`[FRAME]`); focus on 5 and 10 benchmarks
Blind Guessing in Quiz Mode	Cognitive overload from pace or difficulty tier	Drop down two difficulty levels; re-engage tactile blocks before restarting timer

B.11 Cognitive Science of Fluency, Spaced Retrieval & Quiz Engine Architecture

B.11.1 Spaced Retrieval Practice & The Ebbinghaus Forgetting Curve

Why does passive flashcard drilling fail so often in elementary classrooms? The answer lies in Hermann Ebbinghaus's pioneering work on the **Forgetting Curve** and modern cognitive research on **Retrieval-Induced Facilitation** (Roediger & Karpicke, 2006). Actively *retrieving* a mathematical fact from memory alters its neural representation, making it exponentially more durable than passively re-reading multiplication charts:

Review Milestone	Scheduled Interval	Typical Memory Retention Floor
Initial Acquisition	Day 1	100% → 40% without review
1st Spaced Retrieval	Day 2	Restores to 100%; floor rises to 60%
2nd Spaced Retrieval	Day 4	Restores to 100%; floor rises to 80%
3rd Spaced Retrieval	Day 8	Restores to 100%; floor rises to 90%
Long-Term Automaticity	Day 16+	Consolidated in permanent semantic memory

B.11.2 The Leitner Stack Algorithm in Calculator Silicon

The SC-6 Quiz Engine (`[f] [?]`) incorporates a modified **Leitner Spaced Retrieval Queue** directly into its memory registers:

- When a student answers a challenge correctly within the fast latency threshold ($T < T_{max}$), the question moves up to the highest stability tier and does not reappear for at least 30 problem cycles.
- When a student answers incorrectly, the problem is tagged as an **active learning defect** and re-inserted at queue positions +3 and +7, cementing the neural pathway while the solution is still fresh in working memory.

Student Evaluation (`[≠]`)	Queue Transition	Scoring & Cooldown Policy
Accurate & Fast ($T < T_{max}$)	Promoted to **Tier 3 (Mastered)**	Cooldown of 30 problem cycles; streak incremented
Inaccurate or Slow	Tagged as **Defect Re-Queue**	Re-inserted at queue positions +3 and +7; -10 pt penalty

B.11.3 Quiz PRNG, Keypress Entropy & Continuous EEPROM Partitioning

To guarantee unpredictable practice drills across classroom stations, the quiz engine uses a 32-bit Linear Congruential Generator ($X_{n+1} = (1664525 \cdot X_n + 1013904223) \pm od2^{32}$) continuously re-seeded by microsecond timing jitter from the student's physical keystrokes on the 400 g snap-dome matrix. A dedicated 64-byte EEPROM partition preserves unlocked levels (`0x01`), active session scores (`0x02`), high scores per level (`0x06`), fastest latencies (`0x1E`), and the 26-byte Leitner active defect re-queue ring (`0x2A`) across power cycles.

For printable student companion station worksheets and practice forms, proceed to **Curriculum Station Worksheets Library**. For foundational formula references and prime catalogs, see **Appendix C: Formulas, Conversions & Prime Catalogs**.

Appendix C: Formulas, Conversions & Prime Catalogs

CHAPTER BASELINE MODE: `[NUM]`

Hardware Precision Reference • Zero Mode Dependencies

Unlocked Keycaps Ribbon — Students, Engineers & Mathletes

• **Geometry Stack Templates:** Complete RPN keystroke sequences and 4-register elevator stack traces (T, Z, Y, X) for all elementary 2D perimeters/areas and 3D volumes/surface areas.

• **Polyhedron Surface Area Accumulator:** Zero-scratch-paper multi-face surface area evaluation via statistical memory `[Σ+]` and `[f] [Σx]`.

• **Bidirectional Unit Conversions:** High-precision conversion factors across Length, Mass/Weight, Capacity/Liquid Volume, Area, Speed, Pressure, Time, and Temperature (F ↔ C ↔ K).

• **Prime Directory & Divisibility:** Full catalog of all 46 primes under 200 with binary/hex encodings, Sieve of Eratosthenes walk-through, hardware prime factorization via `[PRIME]` and `[g] [FACT]`, algorithmic divisibility tests, and Euclidean GCF/LCM duality via `[g] [÷R]`.

C.1 The RPN Formula Advantage

In standard elementary textbooks, geometric formulas and unit conversions are presented in algebraic notation with tangled parentheses:

$A = (1 / 2)bh$ $V = (4 / 3)\pi r^3$ $C = (5 / 9)(F - 32)$ $A = \pi r (r + \sqrt{(h^2 + r^2)})$

When elementary students attempt to enter these formulas into conventional algebraic calculators, syntax errors frequently arise from misplaced parentheses, incorrect order-of-operation hierarchies, or premature rounding of intermediate values.

On the **StackCalc SC-6**, grounded in Jan Lukasiewicz's parenthesis-free notation *(Lukasiewicz, 1924)* and Kathy Hamrick's history of RPN calculator architecture *(Hamrick, 1980)*, the four-register automatic operational stack (X, Y, Z, T) eliminates parentheses entirely. Following David Macaulay's cutaway principles *(Macaulay, 2016)*, intermediate values remain clearly visible on upper elevator floors and drop into place exactly when an operator is tapped. This appendix provides validated RPN execution templates for every standard elementary formula.

Four-Register Stack Elevator Architecture

Register	Metaphor	Architectural Role
Register T	Penthouse	Holds top constants and duplicates on stack drop
Register Z	Second Balcony	Holds intermediate sub-expressions
Register Y	First Balcony	Holds waiting number for binary operation
Register X	Ground Lobby	Active entry and current computed result

C.2 Table 1: Elementary Mathematical & Geometric Formulas Directory

C.2.1 Foundational Arithmetic Properties & Identity Matrix

Elementary mathematics is anchored in fundamental structural symmetries. The following master matrix pairs each property with its physical manipulative proof, chapter reference, and validated SC-6 stack verification:

Mathematical Property	Formal Algebraic Identity	Manipulative Model (CRA)	Curriculum Reference	SC-6 RPN Verification
Commutative (Addition)	a + b = b + a	Number rack bead grouping (slide left vs. right)	**Chapter 4.1**	`a [ENTER] b [+] = b [ENTER] a [+]`
Commutative (Multiplication)	a × b = b × a	144-tile rectangular array rotated 90^°	**Chapter 4.1**	`a [ENTER] b [×] = b [ENTER] a [×]`
Associative (Addition)	(a + b) + c = a + (b + c)	Combining 3 color segments of snap cubes	**Chapter 4.1**	Chained `[+]` collapses identically in stack
Associative (Multiplication)	(a × b) × c = a × (b × c)	Regrouping 3D unit block prism layers	**Chapter 4.1**	`a [ENTER] b [×] c [×]`
Distributive Property	a(b + c) = ab + ac	Splitting 4-color array mat along color seam	**Chapter 4.1**	`b [ENTER] c [+] a [×]`
Identity Elements	a + 0 = a, a × 1 = a	Zero tiles added; 1 group of a tiles	**Chapter 4.1**	Stack preserves operand unmodified
Division Algorithm	a = b × q + r (0 ≤ r < b)	Distributing counters into b equal cups	**Chapter 4.2** & **Ch 7**	`a [ENTER] b [g] [÷R]` → (Y: q, X: r)
Fundamental GCD/LCM Duality	gcd(a, b) × lcm(a, b) = a × b	Overlapping prime factor studio rods	**Chapter 7.3**	`a [ENTER] b [GCF] a [ENTER] b [f] [LCM] [×]`
Fraction-to-Decimal Bridge	(a / b) = a ÷ b	Fraction studio rods scaled to unit 1-tower	**Chapter 5.1**	`a [ENTER] b [÷]`

C.2.2 Two-Dimensional Perimeter & Area Formulas

The following table summarizes 2D geometric formulas, standard metric and customary units, chapter cross-references, and their validated SC-6 RPN keystroke sequences:

Shape	Metric / Customary Formula	Curriculum Reference	SC-6 RPN Keystroke Sequence	Stack Registers Used
Square (Perimeter)	P = 4s	**Chapter 6.2**	`s [ENTER] [4] [×]`	Y, X
Square (Area)	$A = s^2$	**Chapter 6.2**	`s [x²]`	X (Unary)
Rectangle (Perimeter)	P = 2(l + w)	**Chapter 6.2**	`l [ENTER] w [+] [2] [×]`	Y, X
Rectangle (Area)	A = l × w	**Chapter 6.2**	`l [ENTER] w [f] [RECT]`	Y, X
Triangle (Perimeter)	P = a + b + c	**Chapter 6.2**	`a [ENTER] b [+] c [+]`	Z, Y, X
Triangle (Area)	A = (1 / 2) b h	**Chapter 6.2**	`b [ENTER] h [×] [2] [÷]`	Y, X
Parallelogram (Area)	A = b × h	**Chapter 6.2**	`b [ENTER] h [×]`	Y, X
Trapezoid (Area)	A = (a + b / 2) × h	**Chapter 6.2**	`a [ENTER] b [+] [2] [÷] h [×]`	Z, Y, X

Shape	Metric / Customary Formula	Curriculum Reference	SC-6 RPN Keystroke Sequence	Stack Registers Used
Circle (Circumference)	$C = 2\pi r = \pi d$	**Chapter 6.2**	`d [π] [×]`	Y, X
Circle (Area)	$A = \pi r^2$	**Chapter 6.2**	`r [xʸ] [π] [×]`	Y, X
Circle Sector (Area)	$A = (\theta / 360) \pi r^2$	**Chapter 6.2**	`r [xʸ] [π] [×] ⊠ [×] 360 [÷]`	Z, Y, X
Circle Arc Length	$s = (\theta / 360) \pi d$	**Chapter 6.2**	`d [π] [×] ⊠ [×] 360 [÷]`	Z, Y, X
Regular Polygon (Area)	$A = (1 / 2) P \times a$	**Chapter 6.2**	`P [ENTER] a [×] [2] [÷]`	Y, X
Regular Hexagon (Area)	$A = (3\sqrt{3} / 2) s^2$	**Chapter 6.2**	`s [xʸ] [3] [×] [3] [f] [√x] [×] [2] [÷]`	Z, Y, X
Ellipse (Area)	$A = \pi \times a \times b$	**Chapter 6.2**	`a [ENTER] b [×] [π] [×]`	Y, X

C.2.3 Deep-Dive 2D Stack Traces & Worked Numerical Examples

Example 2.2.1: Area of an Acute Triangle (b = 14 cm, h = 9 cm)

Formula: $A = (1 / 2) \times 14 \times 9 = 63\ cm^2$.

Keystroke	Register T	Register Z	Register Y	Register X
14	0	0	0	14
[ENTER]	0	0	14	14
[9]	0	0	14	9
[×]	0	0	0	126
[2]	0	0	126	2
[÷]	0	0	0	63

Stack Inspection: The product $14 \times 9 = 126$ is evaluated first, then 2 enters Register X, pushing 126 to Y. Tapping **[÷]** divides $Y \div X = 126 \div 2 = 63$.

Example 2.2.2: Area of an Isosceles Trapezoid (a = 8 in, b = 14 in, h = 6 in)

Formula: $A = (8 + 14 / 2) \times 6 = (22 / 2) \times 6 = 11 \times 6 = 66\ sq\ in$.

Keystroke	Register T	Register Z	Register Y	Register X
[8]	0	0	0	8
[ENTER]	0	0	8	8
14	0	0	8	14
[+]	0	0	0	22
[2]	0	0	22	2
[÷]	0	0	0	11

Keystroke	Register T	Register Z	Register Y	Register X
[6]	0	0	11	6
[×]	0	0	0	66

Example 2.2.3: Area of a Circular Splash Pad (r = 3.5 m)

Formula: $A = \pi \times 3.5^2 = \pi \times 12.25 \approx 38.48451\ m^2$.

Keystroke	Register T	Register Z	Register Y	Register X
3.5	0	0	0	3.5
[x²]	0	0	0	12.25
[π]	0	0	12.25	3.1415926
[×]	0	0	0	38.484510

Example 2.2.4: Area of a Regular Hexagon (s = 8 cm)

Formula: $A = (3\sqrt{3} / 2)\ s^2 = (3 \times 1.7320508 / 2) \times 64 = 2.598076 \times 64 \approx 166.27688\ cm^2$.

Keystroke	Register T	Register Z	Register Y	Register X
[8]	0	0	0	8
[x²]	0	0	0	64
[3]	0	0	64	3
[×]	0	0	0	192
[3]	0	0	192	3
[f] [√x]	0	0	192	1.7320508
[×]	0	0	0	332.553759
[2]	0	0	332.553759	2
[÷]	0	0	0	166.276879

Example 2.2.5: Circular Sector Area and Arc Length (r = 12 cm, θ = 60^°)

- Arc Length: $s = (60 / 360) \times 2\ \pi\ (12) = (1 / 6) \times 24\pi = 4\pi \approx 12.56637\ cm$.
- Sector Area: $A = (60 / 360) \times \pi\ (12^2) = (1 / 6) \times 144\pi = 24\pi \approx 75.39822\ cm^2$.

Keystrokes for Sector Area:

- Key in: `12 [x²] [π] [×] 60 [×] 360 [÷]`.
- LCD Result: **75.39822 cm²**.

C.2.4 Three-Dimensional Solid Volume & Surface Area Formulas

Solid	Volume Formula (V)	Total Surface Area Formula (A)	Curriculum Reference	SC-6 Volume Keystrokes
Cube (s)	$V = s^3$	$A = 6s^2$	**Chapter 6.3**	`s [ENTER] [3] [g] [y^x]`
Rectangular Prism (l, w, h)	$V = l \times w \times h$	$A = 2(lw + lh + wh)$	**Chapter 6.3**	`l [ENTER] w [×] h [×]`
Triangular Prism (b, h_{tri}, L)	$V = (1 / 2)\ b\ h_{tri}\ L$	$A = b\ h_{tri} + (s_1 + s_2 + s_3)\ L$	**Chapter 6.3**	`b [ENTER] h [×] 2 [÷] L [×]`
Right Cylinder (r, h)	$V = \pi\ r^2\ h$	$A = 2\pi\ rh + 2\pi\ r^2$	**Chapter 6.3**	`r [x²] [π] [×] h [×]`
Right Cone (r, h)	$V = (1 / 3)\pi\ r^2\ h$	$A = \pi\ r(r + \sqrt{(h^2 + r^2)})$	**Chapter 6.3**	`r [x²] [π] [×] h [×] [3] [÷]`
Square Pyramid (b, h)	$V = (1 / 3)b^2\ h$	$A = b^2 + 2b\sqrt{((b/2)^2 + h^2)}$	**Chapter 6.3**	`b [x²] h [×] [3] [÷]`
Sphere (r)	$V = (4 / 3)\pi\ r^3$	$A = 4\pi\ r^2$	**Chapter 6.3**	**`[4] [ENTER] [3] [÷] [π] [×] r [ENTER] [3] [g] [y^x] [×]`**
Hemisphere (r)	$V = (2 / 3)\pi\ r^3$	$A = 3\pi\ r^2$ (solid)	**Chapter 6.3**	**`[2] [ENTER] [3] [÷] [π] [×] r [ENTER] [3] [g] [y^x] [×]`**
Torus (R, r)	$V = 2\pi^2\ R\ r^2$	$A = 4\pi^2\ R\ r$	**Chapter 6.3**	**`[2] [π] [x²] [×] R [×] r [x²] [×]`**

C.2.5 Deep-Dive 3D Stack Traces & Worked Numerical Examples

Example 2.4.1: Volume & Surface Area of a Storage Silo Cylinder (r = 4 m, h = 10 m)

- Volume: $V = \pi \times 4^2 \times 10 = 160\pi \approx 502.6548\ m^3$.
- Surface Area: $A = 2\pi(4)(10) + 2\pi(4^2) = 80\pi + 32\pi = 112\pi \approx 351.8584\ m^2$.

Volume Stack Trace:

Keystroke	Register T	Register Z	Register Y	Register X
`[4]`	0	0	0	4
`[x²]`	0	0	0	16
`[π]`	0	0	16	3.1415926
`[×]`	0	0	0	50.265482
10	0	0	50.265482	10
`[×]`	0	0	0	502.654824

Total Surface Area Stack Trace:

Keystroke	Register T	Register Z	Register Y	Register X
`[2]`	0	0	0	2
`[π]` **`[×]`**	0	0	0	6.2831853
`[4]` **`[×]`**	0	0	0	25.132741
10 **`[×]`**	0	0	0	251.327412
`[2]`	0	0	251.327412	2

Keystroke	Register T	Register Z	Register Y	Register X
[π] [×]	0	0	251.327412	6.2831853
[4] [x²] [×]	0	0	251.327412	100.530964
[+]	0	0	0	351.858376

Example 2.4.2: Volume & Surface Area of a Right Cone (r = 6 cm, h = 8 cm)

Slant height: $s = \sqrt{(r^2 + h^2)} = \sqrt{(6^2 + 8^2)} = \sqrt{(36 + 64)} = \sqrt{100} = 10$ cm.

- Volume: $V = (1 / 3)\pi (6^2) (8) = (1 / 3) \times 288\pi = 96\pi \approx 301.59289$ cm^3.
- Surface Area: $A = \pi r (r + s) = \pi (6) (6 + 10) = 96\pi \approx 301.59289$ cm^2.

Cone Volume Stack Trace:

Keystroke	Register T	Register Z	Register Y	Register X
[6] [x²]	0	0	0	36
[π] [×]	0	0	0	113.097336
[8] [×]	0	0	0	904.778684
[3] [÷]	0	0	0	301.592895

Example 2.4.3: Volume & Surface Area of a Sphere (r = 9 cm)

- Volume: $V = (4 / 3)\ \pi\ (9^3) = (4 / 3)\ \pi\ (729) = 972\pi \approx 3053.628$ cm^3.
- Surface Area: $A = 4\pi\ (9^2) = 4\pi\ (81) = 324\pi \approx 1017.876$ cm^2.

Sphere Volume Keystrokes:

- [4] [ENTER] [3] [÷] [π] [×] [9] [ENTER] [3] [g] [y⊠] [×].
- LCD Result: **3053.628059 cm^3**.

Sphere Surface Area Keystrokes:

- [9] [x²] [4] [×] [π] [×].
- LCD Result: **1017.876020 cm^2**.

C.3 Total Surface Area via Statistical Accumulator ([Σ+])

For multi-faceted polyhedra (prisms, pyramids, and irregular engineering enclosures), calculating surface area face-by-face with scratch paper is prone to transcription errors. The SC-6 provides a zero-scratch-paper workflow using the statistical accumulator key [Σ+].

Polyhedron Total Surface Area Accumulator Protocol

Step	Action	SC-6 Keystroke	Statistical State
Step 1: Clear Memory	Reset registers	`[g]` `[CLΣ]`	n = 0
Step 2: Face Pair 1 (L × W)	Top & Bottom	`l [ENTER] w [×] 2 [×] [⊠+]`	Stored (n = 1)
Step 3: Face Pair 2 (L × H)	Front & Back	`l [ENTER] h [×] 2 [×] [⊠+]`	Stored (n = 2)
Step 4: Face Pair 3 (W × H)	Left & Right	`w [ENTER] h [×] 2 [×] [⊠+]`	Stored (n = 3)
Step 5: Recall Total Area	Sum all faces	`[f] [Σx]`	Total Area on X

C.3.1 Worked Prism Example (l = 12 cm, w = 7 cm, h = 5 cm)

- Face Pair 1 (Top & Bottom): $2 \times (12 \times 7) = 168$ cm^2.
- Face Pair 2 (Front & Back): $2 \times (12 \times 5) = 120$ cm^2.
- Face Pair 3 (Left & Right): $2 \times (7 \times 5) = 70$ cm^2.
- Total Surface Area: $168 + 120 + 70 = 358$ cm^2.

Keystroke Execution:

1. `[g]` `[CLΣ]` → LCD confirms n = 0.
2. `12 [ENTER] [7] [×] [2] [×] [⊠+]` → LCD confirms n = 1.
3. `12 [ENTER] [5] [×] [2] [×] [⊠+]` → LCD confirms n = 2.
4. `[7] [ENTER] [5] [×] [2] [×] [Σ+]` → LCD confirms n = 3.
5. `[f] [Σx]` → Result: **358.00 cm^2**.

C.3.2 Worked Triangular Prism Example

A right triangular tent has triangular end faces with base b = 6 ft, height h = 4 ft, and hypotenuse legs s = 5 ft. The tent length is L = 10 ft.

- Two Triangular Ends: $2 \times ((1 / 2) \times 6 \times 4) = 24$ sq ft.
- Floor Face: $6 \times 10 = 60$ sq ft.
- Two Slanted Roof Faces: $2 \times (5 \times 10) = 100$ sq ft.
- Total Surface Area: $24 + 60 + 100 = 184$ sq ft.

Keystrokes:

1. `[g]` `[CLΣ]` → n = 0.
2. Ends: `[6] [ENTER] [4] [×] [Σ+]` → n = 1 (24 stored).
3. Floor: `[6] [ENTER] 10 [×] [Σ+]` → n = 2 (60 stored).
4. Roof: `[5] [ENTER] 10 [×] [2] [×] [Σ+]` → n = 3 (100 stored).
5. Recall: `[f] [Σx]` → Result: **184.00 sq ft**.

C.4 Table 2: Complete Unit Conversions Directory

Unit conversions are expressed as exact rational ratios or internationally standardized conversion multipliers.

C.4.1 Length Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Forward Keystrokes	Reverse Multiplier (To)
Inches (in)	**Centimeters (cm)**	2.54	`[in] [ENTER] 2.54 [×]`	÷ 2.54
Feet (ft)	**Inches (in)**	12.0	`[ft] [ENTER] 12 [×]`	÷ 12
Feet (ft)	**Meters (m)**	0.3048	`[ft] [ENTER] [.] 3048 [×]`	÷ 0.3048
Yards (yd)	**Feet (ft)**	3.0	`[yd] [ENTER] [3] [×]`	÷ 3
Yards (yd)	**Meters (m)**	0.9144	`[yd] [ENTER] [.] 9144 [×]`	÷ 0.9144
Miles (mi)	**Feet (ft)**	5280.0	`[mi] [ENTER] 5280 [×]`	÷ 5280
Miles (mi)	**Kilometers (km)**	1.609344	`[mi] [ENTER] 1.609344 [×]`	÷ 1.609344
Nautical Miles (NM)	**Kilometers (km)**	1.852	`[NM] [ENTER] 1.852 [×]`	÷ 1.852
Nautical Miles (NM)	**Statute Miles (mi)**	≈ 1.150779	`[NM] [ENTER] 1.1508 [×]`	÷ 1.1508
Meters (m)	**Centimeters (cm)**	100.0	`[m] [ENTER] 100 [×]`	÷ 100
Centimeters (cm)	**Millimeters (mm)**	10.0	`[cm] [ENTER] 10 [×]`	÷ 10
Kilometers (km)	**Meters (m)**	1000.0	`[km] [ENTER] 1000 [×]`	÷ 1000

Worked Length Conversion

Convert a 100 yard football field into meters:

- Keystrokes: `100 [ENTER] 0.9144 [×]`
- Result: **91.44 meters**.
- Reverse to check: `[.] 9144 [÷]`. Result: **100.00 yards**.

C.4.2 Area Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Forward Keystrokes	Reverse Multiplier
Square Feet (sq ft)	**Square Inches (sq in)**	144.0	`[sq ft] [ENTER] 144 [×]`	÷ 144
Square Yards (sq yd)	**Square Feet (sq ft)**	9.0	`[sq yd] [ENTER] [9] [×]`	÷ 9
Acres (ac)	**Square Feet (sq ft)**	43,560.0	`[ac] [ENTER] 43560 [×]`	÷ 43560
Acres (ac)	**Hectares (ha)**	≈ 0.4046856	`[ac] [ENTER] [.] 4047 [×]`	÷ 0.4047
Hectares (ha)	**Square Meters (m^2)**	10,000.0	`[ha] [ENTER] 10000 [×]`	÷ 10000
Square Miles (mi^2)	**Acres (ac)**	640.0	`[sq mi] [ENTER] 640 [×]`	÷ 640

From Unit	To Unit	Exact Multiplier	SC-6 Forward Keystrokes	Reverse Multiplier
Square Meters (m^2)	Square Feet (sq ft)	≈ 10.76391	`[m²] [ENTER] 10.764 [×]`	÷ 10.764

Worked Area Conversion

How many square feet are in a 2.5 acre homestead parcel?

- Keystrokes: `2.5 [ENTER] 43560 [×]`
- Result: **108,900 sq ft**.

C.4.3 Mass & Weight Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Forward Keystrokes	Reverse Multiplier (To)
Ounces (oz)	Grams (g)	28.349523	`[oz] [ENTER] 28.35 [×]`	÷ 28.3495
Pounds (lb)	Ounces (oz)	16.0	`[lb] [ENTER] 16 [×]`	÷ 16
Pounds (lb)	Kilograms (kg)	0.45359237	`[lb] [ENTER] [.] 4536 [×]`	÷ 0.4536
Kilograms (kg)	Pounds (lb)	≈ 2.2046226	`[kg] [ENTER] 2.2046 [×]`	÷ 2.2046
Tons (US Short)	Pounds (lb)	2000.0	`[ton] [ENTER] 2000 [×]`	÷ 2000
Metric Tons (t)	Kilograms (kg)	1000.0	`[t] [ENTER] 1000 [×]`	÷ 1000
Kilograms (kg)	Grams (g)	1000.0	`[kg] [ENTER] 1000 [×]`	÷ 1000
Grams (g)	Milligrams (mg)	1000.0	`[ENTER] 1000 [×]`	÷ 1000

Worked Weight Conversion

Convert a 65 lb bicycle packing crate into kilograms:

- Keystrokes: `65 [ENTER] 0.453592 [×]`
- Result: **29.483 kg**.

C.4.4 Capacity & Liquid Volume Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Forward Keystrokes	Reverse Multiplier
Fluid Ounces (fl oz)	Milliliters (mL)	29.57352956	`[fl oz] [ENTER] 29.57 [×]`	÷ 29.5735
Cups (c)	Fluid Ounces (fl oz)	8.0	`[c] [ENTER] [8] [×]`	÷ 8
Pints (pt)	Cups (c)	2.0	`[pt] [ENTER] [2] [×]`	÷ 2
Quarts (qt)	Pints (pt)	2.0	`[qt] [ENTER] [2] [×]`	÷ 2
Gallons (gal US)	Quarts (qt)	4.0	`[gal] [ENTER] [4] [×]`	÷ 4
Gallons (gal US)	Liters (L)	3.785411784	`[gal] [ENTER] 3.7854 [×]`	÷ 3.7854
Gallons (Imperial)	Liters (L)	4.54609	`[gal imp] [ENTER] 4.546 [×]`	÷ 4.5461
Liters (L)	Milliliters (mL)	1000.0	`[L] [ENTER] 1000 [×]`	÷ 1000

From Unit	To Unit	Exact Multiplier	SC-6 Forward Keystrokes	Reverse Multiplier
Cubic Meters (m^3)	**Liters (L)**	1000.0	`[m³] [ENTER] 1000 [×]`	÷ 1000

Worked Liquid Volume Conversion

Convert a 15 gallon vehicle fuel tank into liters:

- Keystrokes: `15 [ENTER] 3.7854 [×]`
- Result: **56.781 liters**.

C.4.5 Speed & Velocity Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Keystrokes
Miles per Hour (mph)	**Kilometers per Hour (km/h)**	1.609344	`[mph] [ENTER] 1.609 [×]`
Miles per Hour (mph)	**Feet per Second (ft/s)**	≈ 1.466667	`[mph] [ENTER] 5280 [×] 3600 [÷]`
Kilometers per Hour (km/h)	**Meters per Second (m/s)**	≈ 0.277778	`[km/h] [ENTER] 1000 [×] 3600 [÷]`
Knots (kt)	**Miles per Hour (mph)**	≈ 1.150779	`[kt] [ENTER] 1.151 [×]`
Knots (kt)	**Kilometers per Hour (km/h)**	1.852	`[kt] [ENTER] 1.852 [×]`

Worked Speed Conversion

A drone flies at 45 mph. How fast is that in feet per second?

- Keystrokes: `45 [ENTER] 5280 [×] 3600 [÷]`
- Result: **66.0 ft/s**.

C.4.6 Pressure Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Keystrokes
Atmospheres (atm)	**Pounds per Sq Inch (psi)**	14.6959488	`[atm] [ENTER] 14.696 [×]`
Atmospheres (atm)	**Kilopascals (kPa)**	101.325	`[atm] [ENTER] 101.325 [×]`
Bar (bar)	**Kilopascals (kPa)**	100.0	`[bar] [ENTER] 100 [×]`
Pounds per Sq Inch (psi)	**Kilopascals (kPa)**	6.894757	`[psi] [ENTER] 6.895 [×]`

Worked Pressure Conversion

Bicycle tire is inflated to 85 psi. Convert to kilopascals:

- Keystrokes: `85 [ENTER] 6.89476 [×]`
- Result: **586.05 kPa**.

C.4.7 Time Conversions

From Unit	To Unit	Exact Multiplier	SC-6 Keystroke Sequence
Minutes (min)	**Seconds (s)**	60.0	`[min] [ENTER] 60 [×]`
Hours (hr)	**Minutes (min)**	60.0	`[hr] [ENTER] 60 [×]`
Hours (hr)	**Seconds (s)**	3600.0	`[hr] [ENTER] 3600 [×]`
Days (d)	**Hours (hr)**	24.0	`d [ENTER] 24 [×]`
Weeks (wk)	**Days (d)**	7.0	`[wk] [ENTER] [7] [×]`
Years (yr standard)	**Days (d)**	365.0	`[yr] [ENTER] 365 [×]`
Years (yr leap)	**Days (d)**	366.0	`[yr] [ENTER] 366 [×]`

Worked Time Conversion

How many seconds are in one full 24-hour day?

- Keystrokes: `24 [ENTER] 3600 [×]`
- Result: **86,400 seconds**.

C.4.8 Temperature Conversions (F ↔ C ↔ K)

Temperature conversions require affine transformations (scaling plus constant offsets):

C = (F - 32) × (5 / 9) F = (C × (9 / 5)) + 32 K = C + 273.15

Temperature Conversion RPN Protocols

Conversion	Formula	RPN Keystroke Protocol
Fahrenheit to Celsius	C = (F - 32) × (5 / 9)	`[F] [ENTER] 32 [-] [5] [×] [9] [÷]`
Celsius to Fahrenheit	F = (C × (9 / 5)) + 32	`[C] [ENTER] [9] [×] [5] [÷] 32 [+]`
Celsius to Kelvin	K = C + 273.15	`[C] [ENTER] 273.15 [+]`
Kelvin to Celsius	C = K - 273.15	`[K] [ENTER] 273.15 [-]`

Worked Temperature Conversion Stack Trace: Normal Body Temp (98.6^°F → ^°C)

Keystroke	Register T	Register Z	Register Y	Register X
`98.6`	0	0	0	98.6
`[ENTER]`	0	0	98.6	98.6
32	0	0	98.6	32
`[-]`	0	0	0	66.6
`[5]`	0	0	66.6	5
`[×]`	0	0	0	333.0
`[9]`	0	0	333.0	9

Keystroke	Register T	Register Z	Register Y	Register X
[÷]	0	0	0	37.0

Result: Normal human body temperature is exactly **37.0^°C** (or on the SC-6 keypad, `98.6 [f] [→°C]` → `37.00`).

C.4.9 Deep-Dive Multimodal Unit Conversion Stack Traces

Example 4.9.1: Marathon Footrace Distance (26.2 miles → kilometers → meters)

Exact international definition: 1 statute mile = 1.609344 kilometers = 1,609.344 meters. **Distance in km = 26.2 × 1.609344 ≈ 42.1648128 km**

Keystroke	Register T	Register Z	Register Y	Register X
[2] [6] [.] [2]	0	0	0	26.2
[ENTER]	0	0	26.2	26.2
1.609344	0	0	26.2	1.609344
[×]	0	0	0	42.164813
1000	0	0	42.164813	1000
[×]	0	0	0	42164.81280

Stack Inspection: Register X now holds the exact Olympic marathon distance: **42,164.81 meters**.

Example 4.9.2: Commercial Jet Cruising Altitude (36,000 ft → meters → kilometers)

Conversion factor: 1 foot = 0.3048 meters exact.

Keystroke	Register T	Register Z	Register Y	Register X
36000	0	0	0	36000
[ENTER]	0	0	36000	36000
.3048	0	0	36000	0.3048
[×]	0	0	0	10972.8
1000	0	0	10972.8	1000
[÷]	0	0	0	10.9728

Cruising altitude: **10,972.8 meters** or **10.97 km** (stratosphere).

Example 4.9.3: Automobile Fuel Economy (35.0 MPG (US) ↔ Liters per 100 km)

The international automotive conversion constant is: **L/100km = (235.215 / MPG)**

Keystroke	Register T	Register Z	Register Y	Register X
235.215	0	0	0	235.215
[ENTER]	0	0	235.215	235.215
35	0	0	235.215	35
[÷]	0	0	0	6.720429

A vehicle rated at 35 MPG consumes **6.72 liters of gasoline per 100 kilometers**.

Example 4.9.4: Absolute Zero Verification (-459.67^°F → ^°C → Kelvin)

Absolute zero in Fahrenheit is -459.67^°F.

Keystroke	Register T	Register Z	Register Y	Register X
459.67 [+/-]	0	0	0	-459.67
[ENTER]	0	0	-459.67	-459.67
32	0	0	-459.67	32
[-]	0	0	0	-491.67
[5]	0	0	-491.67	5
[×]	0	0	0	-2458.35
[9]	0	0	-2458.35	9
[÷]	0	0	0	-273.15
273.15	0	0	-273.15	273.15
[+]	0	0	0	0.00

Result: Exactly **-273.15^°C** and **0.00 K** (absolute zero).

C.5 Table 3: Prime Number Catalog & Factorization Directory

A prime number is an integer greater than 1 whose only positive divisors are 1 and itself. Composite numbers can be uniquely factored into products of primes (Fundamental Theorem of Arithmetic).

C.5.1 Complete Catalog of All 46 Prime Numbers Under 200

There are exactly **46 prime numbers** strictly less than 200. The table below details each prime, its sequential prime index p_n, binary/hex representation, twin prime pairing status, and mathematical properties:

Index (n)	Prime (p_n)	Binary (2)	Hex (16)	Twin Status	Mathematical Properties
p_1	**2**	10	0x02	Sole Even Prime	Only even prime; smallest prime; foundational binary radix.
p_2	**3**	11	0x03	Twin with 5	Smallest odd prime; first Mersenne prime ($2^2 - 1$).

Index (n)	Prime (p_n)	Binary (2)	Hex (16)	Twin Status	Mathematical Properties
p_3	**5**	101	0x05	Twin with 3, 7	Only prime in two twin pairs (3,5 and 5,7); Fermat prime ($2^2 + 1$).
p_4	**7**	111	0x07	Twin with 5	Second Mersenne prime ($2^3 - 1$); Mersenne exponent.
p_5	**11**	1011	0x0B	Twin with 13	Smallest two-digit prime; palindromic prime; Sophie Germain ($2 \times 11 + 1 = 23$).
p_6	**13**	1101	0x0D	Twin with 11	Wilson prime; reversal is 31 (emirp); star number.
p_7	**17**	10001	0x11	Twin with 19	Fermat prime ($2^4 + 1$); constructible regular 17-gon; sum of first 4 primes.
p_8	**19**	10011	0x13	Twin with 17	Keith number; centered triangular number; safe prime.
p_9	**23**	10111	0x17	Isolated	Safe prime ($2 \times 11 + 1$); smallest prime requiring 9 cubes.
p_{10}	**29**	11101	0x1D	Twin with 31	Sum of three consecutive squares ($2^2 + 3^2 + 4^2$); Sophie Germain.
p_{11}	**31**	11111	0x1F	Twin with 29	Third Mersenne prime ($2^5 - 1$); repunit in base 2.
p_{12}	**37**	100101	0x25	Isolated	Palindromic in octal (45_8); emirp with 73; regular prime.
p_{13}	**41**	101001	0x29	Twin with 43	Generates primes via Euler's polynomial $n^2 + n + 41$; Sophie Germain.
p_{14}	**43**	101011	0x2B	Twin with 41	Star number; centered heptagonal number.
p_{15}	**47**	101111	0x2F	Isolated	Lucas number L_8; safe prime ($47 = 2 \times 23 + 1$).
p_{16}	**53**	110101	0x35	Isolated	Sophie Germain prime ($2 \times 53 + 1 = 107$, which is prime).
p_{17}	**59**	111011	0x3B	Twin with 61	Regular prime; sum of three consecutive primes ($17 + 19 + 23$).
p_{18}	**61**	111101	0x3D	Twin with 59	Emirp with 16; cuban prime ($x=5, y=4 \rightarrow 5^3 - 4^3 = 61$).
p_{19}	**67**	1000011	0x43	Isolated	Sum of five consecutive primes ($7 + 11 + 13 + 17 + 19$).
p_{20}	**71**	1000111	0x47	Twin with 73	Largest prime dividing the order of the Monster group.
p_{21}	**73**	1001001	0x49	Twin with 71	Sheldon prime (21st prime; reversed index 12 is prime 37; binary 1001001_2 palindrome).
p_{22}	**79**	1001111	0x4F	Isolated	Emirp with 97; sum of first four prime powers.
p_{23}	**83**	1010011	0x53	Isolated	Sophie Germain prime ($2 \times 83 + 1 = 167$).
p_{24}	**89**	1011001	0x59	Isolated	Fibonacci prime F_{11}; Mersenne prime exponent (2^{89}-1).
p_{25}	**97**	1100001	0x61	Isolated	Largest two-digit prime; emirp with 79.
p_{26}	**101**	1100101	0x65	Twin with 103	Smallest three-digit prime; palindromic prime.
p_{27}	**103**	1100111	0x67	Twin with 101	Twin prime partner of 101.
p_{28}	**107**	1101011	0x6B	Twin with 109	Fourth Mersenne prime exponent (2^{107}-1).

Index (n)	Prime (p_n)	Binary (2)	Hex (16)	Twin Status	Mathematical Properties
p_{29}	**109**	1101101	0x6D	Twin with 107	Twin prime partner of 107; centered triangular number.
p_{30}	**113**	1110001	0x71	Isolated	Permutable prime (113, 131, 311 are all prime); Sophie Germain ($2 \times 113 + 1 = 227$).
p_{31}	**127**	1111111	0x7F	Isolated	Fifth Mersenne prime ($2^7 - 1 = 127$); binary repunit 1111111_2.
p_{32}	**131**	10000011	0x83	Isolated	Palindromic prime; permutable prime with 113; Sophie Germain.
p_{33}	**137**	10001001	0x89	Twin with 139	Close approximation to fine structure constant reciprocal (≈ 137.036).
p_{34}	**139**	10001011	0x8B	Twin with 137	Twin prime partner of 137.
p_{35}	**149**	10010101	0x95	Twin with 151	Strong prime; emirp.
p_{36}	**151**	10010111	0x97	Twin with 149	Palindromic prime; lucky prime.
p_{37}	**157**	10011101	0x9D	Isolated	Balanced prime (halfway between 151 and 163).
p_{38}	**163**	10100011	0xA3	Isolated	Heegner number; $e^{\pi\sqrt{163}}$ is an "almost integer".
p_{39}	**167**	10100111	0xA7	Isolated	Safe prime of 83; Eisenstein prime.
p_{40}	**173**	10101101	0xAD	Isolated	Sum of two squares ($2^2 + 13^2 = 4 + 169 = 173$).
p_{41}	**179**	10110011	0xB3	Twin with 181	Sophie Germain prime ($2 \times 179 + 1 = 359$).
p_{42}	**181**	10110101	0xB5	Twin with 179	Palindromic prime; strobogrammatic prime (reads same upside down).
p_{43}	**191**	10111111	0xBF	Twin with 193	Palindromic prime; Sophie Germain prime ($2 \times 191 + 1 = 383$).
p_{44}	**193**	11000001	0xC1	Twin with 191	Pierpont prime ($2^6 \times 3 + 1 = 193$).
p_{45}	**197**	11000101	0xC5	Twin with 199	Twin prime partner of 199; sum of first 12 primes.
p_{46}	**199**	11000111	0xC7	Twin with 197	Largest prime under 200; Lucas number L_{11}.

C.5.2 Algorithmic Divisibility Tests with RPN Verification

Before testing large integers with `[PRIME]`, mental mathletes and students use rapid divisibility rules:

Divisor	Mental Math Criterion	SC-6 RPN Verification Procedure	Worked Example
2	Last digit is even (0, 2, 4, 6, 8).	`[N] [ENTER] [2] [g] [÷R] [x⇔y]` → 0	$84 \div 2 \rightarrow R = 0$ (Even)
3	Sum of digits is divisible by 3.	`[d1] [ENTER] [d2] [+] ... [3] [g] [÷R]`	$153 \rightarrow 1+5+3=9 \div 3 \rightarrow R = 0$

Divisor	Mental Math Criterion	SC-6 RPN Verification Procedure	Worked Example
4	Last two digits form number divisible by 4.	`[last2] [ENTER] [4] [g] [÷R] [x⇔y]` → 0	3,728 → 28 ÷ 4 → R = 0
5	Last digit is 0 or 5.	Inspect last digit on LCD display.	95 → Ends in 5 (Div by 5)
6	Divisible by both 2 and 3.	Test 2 (even) and test 3 (digit sum).	78 → Even, and 7+8=15 (Div by 6)
7	Double last digit, subtract from remaining part.	`[rem] [ENTER] [last] [2] [×] [-] [7] [g] [÷R]`	203 → 20 - (2 × 3) = 14 (Div by 7)
8	Last three digits form number divisible by 8.	`[last3] [ENTER] [8] [g] [÷R] [x⇔y]` → 0	5,128 → 128 ÷ 8 = 16, R = 0
9	Sum of digits is divisible by 9.	`[d1] [ENTER] [d2] [+] ... [9] [g] [÷R]`	423 → 4+2+3=9 ÷ 9 → R = 0
10	Last digit is 0.	Inspect Register X display.	340 → Ends in 0
11	Alternating sum of digits is multiple of 11.	`[d1] [ENTER] [d2] [-] [d3] [+] ...`	913 → 9 - 1 + 3 = 11 (Div by 11)
13	Add 4 times last digit to remaining part.	`[rem] [ENTER] [last] [4] [×] [+] 13 [g] [÷R]`	299 → 29 + (4 × 9) = 65 = 5 × 13

C.5.3 Ten Classic Canonical Prime Factorizations

The Fundamental Theorem of Arithmetic guarantees that every integer N > 1 decomposes uniquely into primes:

$$N = p_1^{e_1} \times p_2^{e_2} \times \dots \times p_k^{e_k}$$

The table below shows 10 foundational composite numbers, their canonical prime factorization, and their RPN reconstruction verification sequences:

Composite Number (N)	Canonical Factorization	SC-6 Hardware `[g]` `[FACT]` LCD Output	RPN Reconstruction Keystroke Sequence
72	$2^3 \times 3^2$	`2^3 * 3^2`	`[2] [ENTER] [3] [g] [y⊠] [3] [x²] [×]` → 72
84	$2^2 \times 3 \times 7$	`2^2 * 3 * 7`	`[2] [x²] [3] [×] [7] [×]` → 84
180	$2^2 \times 3^2 \times 5$	`2^2 * 3^2 * 5`	`[2] [x²] [3] [x²] [×] [5] [×]` → 180
252	$2^2 \times 3^2 \times 7$	`2^2 * 3^2 * 7`	`[2] [x²] [3] [x²] [×] [7] [×]` → 252
360	$2^3 \times 3^2 \times 5$	`2^3 * 3^2 * 5`	`[2] [ENTER] [3] [g] [y⊠] [3] [x²] [×] [5] [×]` → 360
504	$2^3 \times 3^2 \times 7$	`2^3 * 3^2 * 7`	`[2] [ENTER] [3] [g] [y⊠] [3] [x²] [×] [7] [×]` → 504
720	$2^4 \times 3^2 \times 5$	`2^4 * 3^2 * 5`	`[2] [ENTER] [4] [g] [y⊠] [3] [x²] [×] [5] [×]` → 720
1,000	$2^3 \times 5^3$	`2^3 * 5^3`	`[2] [ENTER] [3] [g] [y⊠] [5] [ENTER] [3] [g] [y⊠] [×]` → 1000
1,024	2^{10}	`2^10`	`[2] [ENTER] 10 [g] [y⊠]` → 1024
1,729	$7 \times 13 \times 19$	`7 * 13 * 19`	`[7] [ENTER] 13 [×] 19 [×]` → 1729

Note on 1,729 (Hardy-Ramanujan Taxicab Number): It is the smallest integer expressible as the sum of two positive cubes in two different ways: **$1729 = 1^3 + 12^3 = 9^3 + 10^3$** Verify on SC-6:

- Pair 1: `[1] [ENTER] [3] [g] [y^x] 12 [ENTER] [3] [g] [y^x] [+]` → 1 + 1728 = 1729.
- Pair 2: `[9] [ENTER] [3] [g] [y^x] 10 [ENTER] [3] [g] [y^x] [+]` → 729 + 1000 = 1729.

C.5.4 Euclidean Algorithm Master Reference Table

The table below catalogs 10 number pairs, their step-by-step Euclidean quotient and remainder sequences, and their calculated GCF and LCM:

Number Pair (a, b)	Euclidean Division Steps	GCF(a,b)	Product a × b	LCM = (a × b / GCF)
(24, 18)	24 = 1(18) + 6; 18 = 3(6) + 0	**6**	432	**72**
(36, 24)	36 = 1(24) + 12; 24 = 2(12) + 0	**12**	864	**72**
(60, 42)	60 = 1(42) + 18; 42 = 2(18) + 6; 18 = 3(6) + 0	**6**	2,520	**420**
(84, 36)	84 = 2(36) + 12; 36 = 3(12) + 0	**12**	3,024	**252**
(105, 45)	105 = 2(45) + 15; 45 = 3(15) + 0	**15**	4,725	**315**
(120, 75)	120 = 1(75) + 45; 75 = 1(45) + 30; 45 = 1(30) + 15; 30 = 2(15) + 0	**15**	9,000	**600**
(144, 96)	144 = 1(96) + 48; 96 = 2(48) + 0	**48**	13,824	**288**
(210, 165)	210 = 1(165) + 45; 165 = 3(45) + 30; 45 = 1(30) + 15; 30 = 2(15) + 0	**15**	34,650	**2,310**
(252, 105)	252 = 2(105) + 42; 105 = 2(42) + 21; 42 = 2(21) + 0	**21**	26,460	**1,260**

C.5.5 Goldbach's Conjecture Verification Matrix (Evens 4 to 60)

Goldbach's Conjecture (posed by Christian Goldbach to Leonhard Euler in 1742) asserts that every even integer greater than 2 can be expressed as the sum of two prime numbers:

$2n = p_a + p_b \ (p_a, p_b \in P)$

Elementary students can verify Goldbach partitions on the SC-6 by entering the prime pair into the stack and testing both components with `[PRIME]`:

Even Number (2n)	Canonical Prime Pair ($p_a + p_b$)	Alternative Partitions	SC-6 RPN Verification Keystrokes
4	2 + 2	Unique	`[2] [ENTER] [2] [+]` → 4
6	3 + 3	Unique	`[3] [ENTER] [3] [+]` → 6
8	3 + 5	Unique	`[3] [ENTER] [5] [+]` → 8
10	3 + 7	5 + 5	`[3] [ENTER] [7] [+]` → 10
12	5 + 7	Unique	`[5] [ENTER] [7] [+]` → 12
14	3 + 11	7 + 7	`[3] [ENTER] 11 [+]` → 14
16	3 + 13	5 + 11	`[3] [ENTER] 13 [+]` → 16

Even Number ($2n$)	Canonical Prime Pair ($p_a + p_b$)	Alternative Partitions	SC-6 RPN Verification Keystrokes
18	5 + 13	7 + 11	`[5] [ENTER] 13 [+]` → 18
20	3 + 17	7 + 13	`[3] [ENTER] 17 [+]` → 20
22	3 + 19	5 + 17, 11 + 11	`[3] [ENTER] 19 [+]` → 22
24	5 + 19	7 + 17, 11 + 13	`[5] [ENTER] 19 [+]` → 24
26	3 + 23	7 + 19, 13 + 13	`[3] [ENTER] 23 [+]` → 26
28	5 + 23	11 + 17	`[5] [ENTER] 23 [+]` → 28
30	7 + 23	11 + 19, 13 + 17	`[7] [ENTER] 23 [+]` → 30
32	3 + 29	13 + 19	`[3] [ENTER] 29 [+]` → 32
34	3 + 31	5 + 29, 11 + 23, 17 + 17	`[3] [ENTER] 31 [+]` → 34
36	5 + 31	7 + 29, 13 + 23, 17 + 19	`[5] [ENTER] 31 [+]` → 36
38	3 + 35 (No, 35 comp); 7 + 31	19 + 19	`[7] [ENTER] 31 [+]` → 38
40	3 + 37	11 + 29, 17 + 23	`[3] [ENTER] 37 [+]` → 40
42	5 + 37	11 + 31, 13 + 29, 19 + 23	`[5] [ENTER] 37 [+]` → 42
44	3 + 41	7 + 37, 13 + 31	`[3] [ENTER] 41 [+]` → 44
46	3 + 43	5 + 41, 17 + 29, 23 + 23	`[3] [ENTER] 43 [+]` → 46
48	5 + 43	7 + 41, 11 + 37, 17 + 31, 19 + 29	`[5] [ENTER] 43 [+]` → 48
50	3 + 47	7 + 43, 13 + 37, 19 + 31	`[3] [ENTER] 47 [+]` → 50
52	5 + 47	11 + 41, 23 + 29	`[5] [ENTER] 47 [+]` → 52
54	7 + 47	11 + 43, 13 + 41, 17 + 37, 23 + 31	`[7] [ENTER] 47 [+]` → 54
56	3 + 53	13 + 43, 19 + 37	`[3] [ENTER] 53 [+]` → 56
58	5 + 53	11 + 47, 17 + 41, 29 + 29	`[5] [ENTER] 53 [+]` → 58
60	7 + 53	13 + 47, 17 + 43, 19 + 41, 23 + 37, 29 + 31	`[7] [ENTER] 53 [+]` → 60

C.5.6 Mersenne Primes & Euclid-Euler Perfect Numbers

A **Mersenne prime** is a prime number of the form $M_p = 2^p - 1$ where the exponent p is itself prime. Euclid (Book IX, Proposition 36) proved that whenever $2^p - 1$ is prime, the number:

$$N = 2^{p-1}(2^p - 1)$$

is an **even perfect number** (equal to the exact sum of its proper positive divisors). Euler later proved that *all* even perfect numbers must follow this exact formula.

The table below catalogs the first four Mersenne primes and their associated perfect numbers:

Prime Exponent (p)	Mersenne Prime ($M_p = 2^p - 1$)	Perfect Number Formula	Evaluated Perfect Number (N)	Proper Divisors Sum Check
$p = 2$	$2^2 - 1 = \mathbf{3}$	$2^1 \times 3$	**6**	$1 + 2 + 3 = 6$
$p = 3$	$2^3 - 1 = \mathbf{7}$	$2^2 \times 7$	**28**	$1 + 2 + 4 + 7 + 14 = 28$

Prime Exponent (p)	Mersenne Prime ($M_p = 2^p - 1$)	Perfect Number Formula	Evaluated Perfect Number (N)	Proper Divisors Sum Check
p = 5	$2^5 - 1 =$ **31**	$2^4 \times 31$	**496**	1 + 2 + 4 + 8 + 16 + 31 + 62 + 124 + 248 = 496
p = 7	$2^7 - 1 =$ **127**	$2^6 \times 127$	**8,128**	1 + 2 + 4 + 8 + 16 + 32 + 64 + 127 + ... = 8128

Worked Stack Trace: Computing Third Perfect Number (N = 496)

Formula: $N = 2^{5-1} \times (2^5 - 1) = 16 \times 31 = 496$.

Keystroke	Register T	Register Z	Register Y	Register X
[2] [ENTER]	0	0	2	2
[5] [g] [y■]	0	0	0	32
[1] [-]	0	0	0	31
[PRIME]	0	0	0	31 IS PRIME
[2] [ENTER]	0	31	2	2
[4] [g] [y■]	0	0	31	16
[×]	0	0	0	496

Result: **496** confirmed prime-constructed perfect integer.

C.5.7 Fermat Primes & Gauss Constructible Regular Polygons

A **Fermat number** has the form $F_n = 2^{2^n} + 1$. When F_n is prime, it is called a Fermat prime. Carl Friedrich Gauss proved in 1796 (at age 19) that a regular polygon of N sides can be constructed with straightedge and compass if and only if N is the product of a power of 2 and any number of distinct Fermat primes:

$$N = 2^k \times F_a \times F_b \times \ldots$$

There are only **five known Fermat primes** in mathematics:

Index (n)	Expression ($2^{2^n} + 1$)	Fermat Prime (F_n)	Constructible Regular Polygons
n = 0	$2^{2^0} + 1 = 2^1 + 1$	**3**	Equilateral Triangle (N = 3)
n = 1	$2^{2^1} + 1 = 2^2 + 1$	**5**	Regular Pentagon (N = 5)
n = 2	$2^{2^2} + 1 = 2^4 + 1$	**17**	Regular Heptadecagon (N = 17, Gauss's discovery)
n = 3	$2^{2^3} + 1 = 2^8 + 1$	**257**	Regular 257-gon (N = 257)
n = 4	$2^{2^4} + 1 = 2^{16} + 1$	**65,537**	Regular 65,537-gon (N = 65,537)

Note on F_5 (Euler's Famous Counterexample): Pierre de Fermat conjectured that all F_n are prime. In 1732, Leonhard Euler disproved this by factoring F_5: **$F_5 = 2^{32} + 1 = 4{,}294{,}967{,}297 = 641 \times 6{,}700{,}417$** Verify factor on SC-6:

- Keystrokes: `4294967297 [ENTER] 641 [÷]`
- LCD Result: Exactly **6,700,417.00** (composite!).

C.6 Comprehensive Formula Quick-Reference Index Matrix

C.6.1 Geometric & Physical Quick Matrix

Mathematical Problem	Known Inputs	Target Output	RPN Key Sequence Template
Area of Circle	Radius r	Area A	`r [x²] [π] [×]`
Circumference of Circle	Diameter d	Circumference C	`d [π] [×]`
Hypotenuse of Right Triangle	Legs a, b	Hypotenuse c	`a [x²] b [x²] [+] [√x]`
Area of Triangle	Base b, Height h	Area A	`b [ENTER] h [×] [2] [÷]`
Area of Trapezoid	Bases a, b, Height h	Area A	`a [ENTER] b [+] [2] [÷] h [×]`
Volume of Cylinder	Radius r, Height h	Volume V	`r [x²] [π] [×] h [×]`
Volume of Cone	Radius r, Height h	Volume V	`r [x²] [π] [×] h [×] [3] [÷]`
Volume of Sphere	Radius r	Volume V	`[4] [ENTER] [3] [÷] [π] [×] [r] [3] [y⊠] [×]`
Volume of Rectangular Box	Length l, Width w, Height h	Volume V	`l [ENTER] w [×] h [×]`
Surface Area of Cube	Side s	Surface Area A	`s [x²] [6] [×]`
Percent of a Number	Whole W, Rate r%	Part P	`[W] [ENTER] r [%]`
Percent Increase / Decrease	Old O, New N	Change % Δ	`[O] [ENTER] [N] [⊠%]`
Fahrenheit to Celsius	Temp F	Temp C	`[F] [ENTER] 32 [-] [5] [×] [9] [÷]`
Celsius to Fahrenheit	Temp C	Temp F	`[C] [ENTER] [9] [×] [5] [÷] 32 [+]`
Speed / Rate	Distance d, Time t	Speed s	`d [ENTER] [t] [÷]`
Unit Price	Cost C, Quantity Q	Price per unit	`[C] [ENTER] [Q] [÷]`
Miles to Kilometers	Distance mi	Distance km	`[mi] [ENTER] 1.609344 [×]`
Pounds to Kilograms	Weight lb	Mass kg	`[lb] [ENTER] [.] 453592 [×]`
Gallons to Liters	Volume gal	Volume L	`[gal] [ENTER] 3.7854 [×]`

C.6.2 Elementary Financial Mathematics Protocols

Everyday consumer mathematics problems (interest, taxes, tips, unit cost comparisons) map directly onto the SC-6 stack:

Financial Operation	Mathematical Formula	SC-6 RPN Execution Template
Simple Interest (I)	I = P × r × t	`[P] [ENTER] [r] [%] [t] [×]`
Total Amount (A)	A = P + I = P(1 + rt)	`[P] [ENTER] [r] [%] [t] [×] [+]`
Sales Tax (T)	T = P × r	`[P] [ENTER] r [%]`
Total with Tax	Total = P × (1 + r)	`[P] [ENTER] [r] [%] [+]`
Discount Amount (D)	D = P × d	`[P] [ENTER] d [%]`

Financial Operation	Mathematical Formula	SC-6 RPN Execution Template
Sale Price	Sale = P × (1 - d)	`[P] [ENTER] [d] [%] [-]`
Restaurant Tip (18%)	Tip = Bill × 0.18	`[Bill] [ENTER] 18 [%]`
Compound Interest (A)	$A = P(1 + r)^t$ (annual)	`[1] [ENTER] [r] [+] [t] [y^x] [P] [×]`

Worked Financial Stack Trace: 3-Year Certificate of Deposit (P = 500 USD, r = 4%, t = 3 years)

Formula: $A = 500 \times (1 + 0.04)^3 = 500 \times (1.04)^3 = 500 \times 1.124864 = \$562.43$.

Keystroke	Register T	Register Z	Register Y	Register X
1.04	0	0	0	1.04
`[ENTER]`	0	0	1.04	1.04
`[3]`	0	0	1.04	3
[y■]	0	0	0	1.124864
500	0	0	1.124864	500
`[×]`	0	0	0	562.43

Result: **$562.43** total balance (yielding $62.43 compound interest).

C.7 Alignment with Elementary & Middle School Standards

The formulas, conversion standards, and prime algorithms detailed in this appendix directly support:

- **Common Core State Standards for Mathematics (CCSS-M):**
- `4.OA.B.4`: Find all factor pairs for a whole number in the range 1–100; recognize that a whole number is a multiple of each of its factors; determine whether a given whole number is prime or composite.
- `4.MD.A.1`: Know relative sizes of measurement units within one system of units (km, m, cm; kg, g; lb, oz; l, ml; hr, min, sec); express measurements in a larger unit in terms of a smaller unit.
- `5.MD.C.5`: Relate volume to the operations of multiplication and addition and solve real-world and mathematical problems involving volume.
- `6.G.A.1, 6.G.A.2, 6.G.A.4`: Find area of right triangles, other triangles, special quadrilaterals, and polygons; represent three-dimensional figures using nets; apply techniques in context of real-world problems.
- `6.NS.B.4`: Find the greatest common factor of two whole numbers less than or equal to 100 and the least common multiple of two whole numbers less than or equal to 12.
- **Texas Essential Knowledge and Skills (TEKS):**
- `4.5.C, 4.5.D`: Solve problems related to perimeter and area of rectangles.
- `5.4.A`: Identify prime and composite numbers using concrete objects, pictorial models, and patterns in factor pairs.
- `5.6.A, 5.6.B`: Recognize volume as an attribute of three-dimensional space; determine the volume of a rectangular prism.

- 6.4.H: Convert units within a measurement system, including the use of proportions and unit rates.
- 6.7.A: Generate equivalent numerical expressions using order of operations, including whole number exponents and prime factorization.
- **Competitive STEM & Number Sense Sprints:**
- Fast prime verification and factor decomposition under 200.
- Rapid mental and RPN execution of geometric area and volume benchmarks.

C.8 Annotated Bibliography & Primary Mathematical Sources

C.8.1 Foundations of Logic & Computer Architecture

 [lukasiewicz1924] Jan Lukasiewicz (1924) — *Oznaczenie bez nawiasów (Parenthesis-Free Notation)*. *Komunikaty Polskiego Towarzystwa Matematycznego, Vol. 1, pp. 1--6*.

> **Annotation:** Introduces parenthesis-free prefix and postfix notation, demonstrating that operator position alone uniquely determines evaluation order without grouping symbols.
>
> **Cited in Chapters:** Ch 02

 [burks1954] Arthur W. Burks, Don W. Warren & Jesse B. Wright (1954) — *An Analysis of a Logical Machine Using Parenthesis-Free Notation*. *Mathematical Tables and Other Aids to Computation, Vol. 8, No. 46, pp. 53--57*.

> **Annotation:** Formalizes Polish parenthesis-free postfix notation for electronic digital computers, laying the theoretical foundation for hardware-evaluated operational stacks.
>
> **Cited in Chapters:** *Foundational reference & curriculum background*

C.8.2 Corvallis Silicon & Handheld Architecture

 [hamrick1980] Kathy B. Hamrick (1980) — *The History of Reverse Polish Notation*. *The Two-Year College Mathematics Journal, Vol. 11, No. 5, pp. 317--326*.

> **Annotation:** Traces the historical evolution of Polish notation from abstract Warsaw mathematical logic to Corvallis handheld scientific computing.
>
> **Cited in Chapters:** Ch 02

C.8.3 Numerical Stability & Scientific Algorithms

 [napier1614] John Napier (1614) — *Mirifici Logarithmorum Canonis Descriptio*. *Andrew Hart, Edinburgh*.

> **Annotation:** The invention of logarithms, transforming laborious multi-digit multiplication into addition and doubling the working lifespan of astronomers.
>
> **Cited in Chapters:** Ch 05

 [gauss1809] Carl Friedrich Gauss (1809) — *Theoria Motus Corporum Coelestium in Sectionibus Conicis Solem Ambientium*. *Perthes and Besser, Hamburg*.

Annotation: Introduces the Method of Least Squares and the Gaussian Normal error distribution, recovering the lost celestial orbit of Ceres.

Cited in Chapters: Ch 02, Ch 04, Ch 07, Foreword

 [kahan1979] William M. Kahan (1979) — *Personal Calculator Has Key to Solve Any Equation f(x) = 0*. *Hewlett-Packard Journal, Vol. 30, No. 12, pp. 20--26*.

Annotation: Establishes the non-destructive base-preserving percentage invariant and foundational floating-point error bounds for handheld solvers.

Cited in Chapters: *Foundational reference & curriculum background*

C.8.4 Breakout Mathematics & Scientific Nonfiction

 [gardner1959] Martin Gardner (1959) — *The Scientific American Book of Mathematical Puzzles and Diversions*. *Simon & Schuster, New York*.

Annotation: Pioneered popular mathematical recreations, flexagons, hexaflexagons, and spatial puzzles that celebrate mathematical play.

Cited in Chapters: Ch 07

 [singh1997] Simon Singh (1997) — *Fermat's Enigma: The Epic Quest to Solve the World's Greatest Mathematical Problem*. *Walker & Company, New York*.

Annotation: Captures the three-century human quest to prove Fermat's Last Theorem, conveying the passion and stakes of mathematical discovery.

Cited in Chapters: Ch 07

 [strogatz2012] Steven Strogatz (2012) — *The Joy of x: A Guided Tour of Math, from One to Infinity*. *Eamon Dolan / Houghton Mifflin Harcourt, Boston*.

Annotation: Opens every mathematical section with everyday curiosity and intuitive aha-moments, showing how mathematical beauty connects to human experience.

Cited in Chapters: Ch 02, Ch 05, Ch 06, Foreword

 [ellenberg2014] Jordan Ellenberg (2014) — *How Not to Be Wrong: The Power of Mathematical Thinking*. *Penguin Press, New York*.

Annotation: Exposes common cognitive biases, non-linear scaling traps, and statistical survivorship fallacies with conversational wit.

Cited in Chapters: Ch 07

 [munroe2014] Randall Munroe (2014) — *What If?: Serious Scientific Answers to Absurd Hypothetical Questions*. *Houghton Mifflin Harcourt, Boston*.

Annotation: Applies order-of-magnitude dimensional analysis, physics Fermi approximations, and creative mathematical modeling to wild scenarios.

Cited in Chapters: Ch 06, Ch 09

 [macaulay2016] David Macaulay (2016) — *The Way Things Work Now*. *HMH Books for Young Readers, Boston*.

Annotation: Visualizes mechanical physical mechanisms and gear systems through step-by-step illustrations, inspiring the SC-6 tactile manipulative studio design.

Cited in Chapters: App A, Ch 01, Ch 02, Ch 04, Ch 05, Ch 06, Ch 07, Ch 09, Foreword

 [parker2019] Matt Parker (2019) — *Humble Pi: A Comedy of Maths Errors*. *Riverhead Books, New York*.

Annotation: Explores famous engineering catastrophes and numerical bugs caused by round-off errors, integer overflows, and unit conversion failures.

Cited in Chapters: Ch 04, Ch 06, Ch 09

C.8.5 Pedagogy, Cognitive Science & Manipulatives

 [polya1945] George Pólya (1945) — *How to Solve It: A New Aspect of Mathematical Method*. *Princeton University Press, Princeton, NJ*.

Annotation: Defines the heuristic problem-solving framework (Understand, Plan, Carry Out, Look Back), aligned with step-by-step RPN stack inspection.

Cited in Chapters: Ch 04, Ch 06, Ch 07

 [miller1956] George A. Miller (1956) — *The Magical Number Seven, Plus or Minus Two: Some Limits on Our Capacity for Processing Information*. *Psychological Review, Vol. 63, No. 2, pp. 81--97*.

Annotation: Identifies the 7 ± 2 item capacity limit of human short-term working memory, validating the 4-register stack as the optimal cognitive span.

Cited in Chapters: Ch 01, Ch 02, Ch 08

 [dienes1960] Zoltan P. Dienes (1960) — *Building Up Mathematics*. *Hutchinson Educational, London*.

Annotation: Introduces Multibase Arithmetic Blocks and the Dynamic Principle of mathematical learning, grounding the SC-6 Place Value Studio.

Cited in Chapters: App A, Ch 02, Ch 03, Ch 05, Foreword

 [bruner1966] Jerome S. Bruner (1966) — *Toward a Theory of Instruction*. *Harvard University Press, Cambridge, MA*.

Annotation: Formulates the Concrete-Representational-Abstract (CRA) instructional framework underpinning the SC-6 manipulative studios and display modes.

Cited in Chapters: App A, App B, Ch 02, Ch 03, Ch 05, Ch 06, Ch 07, Ch 09, Foreword

 [sweller1988] John Sweller (1988) — *Cognitive Load During Problem Solving: Effects on Learning*. *Cognitive Science, Vol. 12, No. 2, pp. 257--285*.

Annotation: Establishes Cognitive Load Theory, demonstrating that parentheses and operator precedence buffering in algebraic calculators impose extraneous cognitive load.

Cited in Chapters: Ch 01, Ch 02, Ch 08

 [ma1999] Liping Ma (1999) — *Knowing and Teaching Elementary Mathematics: Teachers' Understanding of Fundamental Mathematics in China and the United States*. *Lawrence Erlbaum Associates, Mahwah, NJ*.

Annotation: Demonstrates Profound Understanding of Fundamental Mathematics (PUFM) through transparent conceptual operations and division with remainders.

Cited in Chapters: App B, Ch 02, Ch 03, Ch 04, Ch 08, Foreword

 [singapore2014] Ministry of Education Singapore (2014) — *Primary Mathematics Teaching and Learning Syllabus*. *Curriculum Planning and Development Division, Singapore*.

Annotation: The Singapore Math framework emphasizing bar modeling, Concrete-Pictorial-Abstract transitions, and relational understanding in fractions and ratios.

Cited in Chapters: App B, Ch 02, Ch 03, Ch 04, Ch 05, Foreword

C.8.6 Standards & Hardware Handbooks

 [ccssm2010] National Governors Association Center for Best Practices & Council of Chief State School Officers (2010) — *Common Core State Standards for Mathematics*. *National Governors Association & CCSSO, Washington, DC*.

Annotation: The foundational curriculum standards framework governing K-12 operations, algebraic thinking, number sense, and geometry in US classrooms.

Cited in Chapters: App B, Ch 03

C.8.7 Complete BibTeX Catalog (StackCalc SC-6 Elementary)

```
@article{lukasiewicz1924,
  author    = {Łukasiewicz, Jan},
  title     = {Oznaczenie bez nawiasów (Parenthesis-Free Notation)},
  journal   = {Komunikaty Polskiego Towarzystwa Matematycznego},
  volume    = {1},
  pages     = {1--6},
  year      = {1924},
  note      = {Introduces parenthesis-free prefix and postfix notation, demonstrating that operator position alone uniquely determines evaluation order w
}

@article{burks1954,
  author    = {Burks, Arthur W. and Warren, Don W. and Wright, Jesse B.},
  title     = {An Analysis of a Logical Machine Using Parenthesis-Free Notation},
  journal   = {Mathematical Tables and Other Aids to Computation},
  volume    = {8},
  number    = {46},
  pages     = {53--57},
  year      = {1954},
  note      = {Formalizes Polish parenthesis-free postfix notation for electronic digital computers, laying the theoretical foundation for hardware-evalu
}

@article{hamrick1980,
  author    = {Hamrick, Kathy B.},
  title     = {The History of Reverse Polish Notation},
  journal   = {The Two-Year College Mathematics Journal},
  volume    = {11},
  number    = {5},
  pages     = {317--326},
  year      = {1980},
  note      = {Traces the historical evolution of Polish notation from abstract Warsaw mathematical logic to Corvallis handheld scientific computing.}
}

@book{napier1614,
  author    = {Napier, John},
  title     = {Mirifici Logarithmorum Canonis Descriptio},
```

```
  publisher = {Andrew Hart},
  address   = {Edinburgh},
  year      = {1614},
  note      = {The invention of logarithms, transforming laborious multi-digit multiplication into addition and doubling the working lifespan of astronom
}

@book{gauss1809,
  author    = {Gauss, Carl Friedrich},
  title     = {Theoria Motus Corporum Coelestium in Sectionibus Conicis Solem Ambientium},
  publisher = {Perthes and Besser},
  address   = {Hamburg},
  year      = {1809},
  note      = {Introduces the Method of Least Squares and the Gaussian Normal error distribution, recovering the lost celestial orbit of Ceres.}
}

@article{kahan1979,
  author    = {Kahan, William M.},
  title     = {Personal Calculator Has Key to Solve Any Equation f(x) = 0},
  journal   = {Hewlett-Packard Journal},
  volume    = {30},
  number    = {12},
  pages     = {20--26},
  year      = {1979},
  note      = {Establishes the non-destructive base-preserving percentage invariant and foundational floating-point error bounds for handheld solvers.}
}

@book{strogatz2012,
  author    = {Strogatz, Steven},
  title     = {The Joy of x: A Guided Tour of Math, from One to Infinity},
  publisher = {Eamon Dolan / Houghton Mifflin Harcourt},
  address   = {Boston},
  year      = {2012},
  isbn      = {978-0547517650},
  note      = {Opens every mathematical section with everyday curiosity and intuitive aha-moments, showing how mathematical beauty connects to human expe
}
```

```
@book{ellenberg2014,
  author    = {Ellenberg, Jordan},
  title     = {How Not to Be Wrong: The Power of Mathematical Thinking},
  publisher = {Penguin Press},
  address   = {New York},
  year      = {2014},
  isbn      = {978-1594205224},
  note      = {Exposes common cognitive biases, non-linear scaling traps, and statistical survivorship fallacies with conversational wit.}
}

@book{parker2019,
  author    = {Parker, Matt},
  title     = {Humble Pi: A Comedy of Maths Errors},
  publisher = {Riverhead Books},
  address   = {New York},
  year      = {2019},
  isbn      = {978-0593084694},
  note      = {Explores famous engineering catastrophes and numerical bugs caused by round-off errors, integer overflows, and unit conversion failures.}
}

@book{munroe2014,
  author    = {Munroe, Randall},
  title     = {What If?: Serious Scientific Answers to Absurd Hypothetical Questions},
  publisher = {Houghton Mifflin Harcourt},
  address   = {Boston},
  year      = {2014},
  isbn      = {978-0544272996},
  note      = {Applies order-of-magnitude dimensional analysis, physics Fermi approximations, and creative mathematical modeling to wild scenarios.}
}

@book{macaulay2016,
  author    = {Macaulay, David},
  title     = {The Way Things Work Now},
  publisher = {HMH Books for Young Readers},
  address   = {Boston},
  year      = {2016},
  isbn      = {978-0544824386},
  note      = {Visualizes mechanical physical mechanisms and gear systems through step-by-step illustrations, inspiring the SC-6 tactile manipulative stu
}

@book{singh1997,
  author    = {Singh, Simon},
  title     = {Fermat's Enigma: The Epic Quest to Solve the World's Greatest Mathematical Problem},
  publisher = {Walker & Company},
  address   = {New York},
  year      = {1997},
  isbn      = {978-0385493628},
  note      = {Captures the three-century human quest to prove Fermat's Last Theorem, conveying the passion and stakes of mathematical discovery.}
}

@book{gardner1959,
  author    = {Gardner, Martin},
  title     = {The Scientific American Book of Mathematical Puzzles and Diversions},
  publisher = {Simon & Schuster},
  address   = {New York},
  year      = {1959},
  note      = {Pioneered popular mathematical recreations, flexagons, hexaflexagons, and spatial puzzles that celebrate mathematical play.}
}

@article{miller1956,
  author    = {Miller, George A.},
  title     = {The Magical Number Seven, Plus or Minus Two: Some Limits on Our Capacity for Processing Information},
  journal   = {Psychological Review},
  volume    = {63},
  number    = {2},
  pages     = {81--97},
  year      = {1956},
  note      = {Identifies the 7 ± 2 item capacity limit of human short-term working memory, validating the 4-register stack as the optimal cognitive span
}
```

```
@book{bruner1966,
  author    = {Bruner, Jerome S.},
  title     = {Toward a Theory of Instruction},
  publisher = {Harvard University Press},
  address   = {Cambridge, MA},
  year      = {1966},
  note      = {Formulates the Concrete-Representational-Abstract (CRA) instructional framework underpinning the SC-6 manipulative studios and display mod
}

@book{dienes1960,
  author    = {Dienes, Zoltan P.},
  title     = {Building Up Mathematics},
  publisher = {Hutchinson Educational},
  address   = {London},
  year      = {1960},
  note      = {Introduces Multibase Arithmetic Blocks and the Dynamic Principle of mathematical learning, grounding the SC-6 Place Value Studio.}
}

@book{polya1945,
  author    = {Pólya, George},
  title     = {How to Solve It: A New Aspect of Mathematical Method},
  publisher = {Princeton University Press},
  address   = {Princeton, NJ},
  year      = {1945},
  note      = {Defines the heuristic problem-solving framework (Understand, Plan, Carry Out, Look Back), aligned with step-by-step RPN stack inspection.}
}

@article{sweller1988,
  author    = {Sweller, John},
  title     = {Cognitive Load During Problem Solving: Effects on Learning},
  journal   = {Cognitive Science},
  volume    = {12},
  number    = {2},
  pages     = {257--285},
  year      = {1988},
  note      = {Establishes Cognitive Load Theory, demonstrating that parentheses and operator precedence buffering in algebraic calculators impose extran
}

@book{ma1999,
  author    = {Ma, Liping},
  title     = {Knowing and Teaching Elementary Mathematics: Teachers' Understanding of Fundamental Mathematics in China and the United States},
  publisher = {Lawrence Erlbaum Associates},
  address   = {Mahwah, NJ},
  year      = {1999},
  note      = {Demonstrates Profound Understanding of Fundamental Mathematics (PUFM) through transparent conceptual operations and division with remainde
}

@techreport{singapore2014,
  author      = {{Ministry of Education Singapore}},
  title       = {Primary Mathematics Teaching and Learning Syllabus},
  institution = {Curriculum Planning and Development Division},
  address     = {Singapore},
  year        = {2014},
  note        = {The Singapore Math framework emphasizing bar modeling, Concrete-Pictorial-Abstract transitions, and relational understanding in fraction
}

@techreport{ccssm2010,
  author      = {{National Governors Association Center for Best Practices and Council of Chief State School Officers}},
  title       = {Common Core State Standards for Mathematics},
  institution = {NGA Center for Best Practices and CCSSO},
  address     = {Washington, DC},
  year        = {2010},
  note        = {The foundational curriculum standards framework governing K-12 operations, algebraic thinking, number sense, and geometry in US classroo
}
```

For detailed hands-on lesson plans implementing these formulas in classroom workshop stations, see **Appendix B: Teacher Lesson Plans & Diagnostic Protocols**. For physical fabrication of geometric models and calibration gauges, see **Appendix A: Manipulative Blueprints & Physical Fabrication Guide**.

Appendix D: Keycap Matrix & Layout Directory

CHAPTER BASELINE MODE: `[NUM]` (Standard 4-stack XYZT decimal arithmetic; 2-digit fixed display default; visual modes toggleable via `[FRAME]`, `[CLOCK]`, and `[LINE]`).

D.1 Keypad Physical Geometry & Tactile Matrix

The StackCalc SC-6 elementary human-machine interface is engineered specifically for young hands, high durability in classroom maker environments, and immediate tactile validation of mathematical operations.

The physical keypad comprises 43 mechanical switch positions organized into three kid-proof, ergonomic functional zones:



Figure: StackCalc SC-6 Elementary Calculator Faceplate & 43-Key Topography

Figure D.1: StackCalc SC-6 Elementary RPN Calculator physical hardware faceplate render, showing the 43-key layout, double-wide `[ENTER]`*, concrete manipulative mode keys (* `[FRAME]` *Ten-Frame,* `[CLOCK]` *Planetary Clock), and high-contrast* `[f]` *and* `[g]` *shift legends.*

StackCalc SC-6 Physical Keypad Topology

Upper Math & Number Sense Zone (Rows 0–2, 6 Columns)

- **Pitch:** 11.50 mm horizontal pitch, 11.30 mm vertical pitch
- **Keycaps:** 10.40 mm round cylindrical concave tops with 0.40 mm dished depth

Row	Col 0	Col 1	Col 2	Col 3	Col 4	Col 5
Row 0	`[x²]`	`[x!]`	`[π]`	`[x³]`	`[PV]`	`[$]`
Row 1	`[FDISP]`	`[α ⌧/c]`	`[GCF]`	`[PRIME]`	`[x⇔y]`	`[+/-]`

| **Row 2** | `[FRQ]` | `[RNG]` | `[IQR]` | `[Σ+]` | `[N]` | `[%]` |

Concrete Manipulative & Stack Transition Zone (Row 3)

- **ENTER Key:** Double-wide 21.90 mm × 10.40 mm spanning Columns 0 and 1 (primary RPN stack commit target positioned directly beneath left thumb).

Row	Col 0 & 1 (Double-Wide)	Col 2	Col 3	Col 4	Col 5
Row 3	`[ENTER]`	`[CLOCK]`	`[FRAME]`	`[NUM]`	`[<-]`

Lower Arithmetic & Geometry Zone (Rows 4–7, 5 Columns)

- **Pitch:** Generous 13.80 mm horizontal pitch, 11.30 mm vertical pitch
- Dedicated power switch at Row 7, Col 0 serves as `[C]` and quiz launcher.

Row	Col 0	Col 1	Col 2	Col 3	Col 4
Row 4	`[DICE]`	`[7]`	`[8]`	`[9]`	`[÷]`
Row 5	`[f]` (f-Shift)	`[4]`	`[5]`	`[6]`	`[×]`
Row 6	`[g]` (g-Shift)	`[1]`	`[2]`	`[3]`	`[-]`
Row 7	`[C]` (ON)	`[0]`	`[.]`	`[≠]`	`[+]`

D.1.1 Tactile Snap-Dome Mechanics & Debouncing Algorithm

- **Actuation Force:** 400 g tactile stainless steel snap domes providing an unambiguous mechanical snap threshold. This physical click reinforces the sensory loop, reassuring students that an entry has registered without double-tapping.
- **Key Travel:** 0.35 mm short-stroke actuation ensuring zero lost motion.
- **Firmware Debounce Architecture:** Eager actuation on leading falling edge (0 ms latency) followed by a 20 ms lockout window. This completely eliminates accidental double-strike bounce artifacts even when excited students rapidly enter numbers.

D.2 Electrical Matrix & Keypad Scanning Bus

The switch matrix is wired as an 8 × 6 crossbar scanned by the dual-core 32-bit microcontroller:

- **Row Lines (Strobed Outputs):** GPIO pins `[6, 7, 8, 9, 10, 14, 18, 19]`. Strobed low sequentially in round-robin sequence at 1 kHz scanning frequency.
- **Column Lines (Sensed Inputs):** GPIO pins `[11, 12, 13, 15, 16, 17]`. Pulled high internally by 50 kΩ resistors; active-low detection.
- **Hardware Sleep Wake Interrupt:** Row 7, Column 0 (`[C]`/ON switch) is routed to an asynchronous edge-triggered interrupt. When the calculator is in deep 11.8 µA sleep inside a backpack or desk cubby, depressing this key immediately wakes the system clock within 5 ms.

D.3 The Definitive 43-Key Hardware Matrix Directory & Curriculum Index

The table below catalogs every physical switch position, electrical matrix coordinate, laser-foamed keycap legend, `[f]` and `[g]` shift combinations, developmental grade ribbon, internal scancode, and direct cross-references to the textbook chapters where each operation is fully explained and practiced:

Key #	Matrix (R, C)	Primary Legend	`[f]` Shift	`[g]` Shift	Grade Ribbon	Code	Primary & Shift Tutorial Links
1	R0, C0	`[x²]`	`[√x]` Root	`[y□]` Power	Gr 5–6+	`0x00`	**Ch 6.2 Square Area • Ch 6.3 Geometric Roots • Ch 4.4 Powers**
2	R0, C1	`[x!]`	`[nCr]` Comb	`[nPr]` Perm	Gr 6+	`0x01`	**Ch 7.4 Polyhedral Combinatorics**
3	R0, C2	`[π]`	`[e]` Euler	`[□√y]` Radic	Gr 5–6+	`0x02`	**Ch 6.4 Circle Geometry • Ch 6.5 Constant E**
4	R0, C3	`[x³]`	`[10□]` Exp	`[LOG]` Base-10	Gr 5–6+	`0x03`	**Ch 6.6 3D Volumes • Ch 3.2 Place Value Powers**
5	R0, C4	`[PV]`	`[IP]` Int Part	`[FP]` Frac Part	Gr 2–4	`0x04`	**Ch 3.1 Place Value Decomposition • Ch 5.3 Integer & Frac Parts**
6	R0, C5	`[$]`	`[ALL]` Full	`[RND]` Round	Gr 2–5	`0x05`	**Ch 3.4 Currency Arithmetic • Ch 4.3 Rounding**
7	R1, C0	`[FDISP]`	`[1/x]` Recip	`[/c]` Denom	Gr 3–5	`0x10`	**Ch 5.1 Fraction Entry & Toggle • Ch 5.2 Reciprocals • Ch 5.3 Fixed Denominator**
8	R1, C1	`[a□/c]`	`[d/c]` Improper	`[SIMP]` Step	Gr 3–5	`0x11`	**Ch 5.1 Mixed Numbers • Ch 5.1 Improper Fractions • Ch 5.2 Superpower 3: SIMP Reduction**
9	R1, C2	`[GCF]`	`[LCM]` Multiple	`[a:b]` Ratio	Gr 5–6	`0x12`	**Ch 7.3 Number Theory GCF/LCM • Ch 5.4 Ratios & Rates**
10	R1, C3	`[PRIME]`	`[C.FAC]` ComFac	`[FACT]` Tree	Gr 5–6	`0x13`	**Ch 7.3 Prime Studio & Factorization**
11	R1, C4	`[x⇔y]`	`[R↓]` Roll Down	`[REP]` Ladder	Gr 2–4	`0x14`	**Ch 2.3 Stack Swapping • Ch 4.1 Superpower 1: REP Skip-Counting**
12	R1, C5	`[+/-]`	`[E]` Exponent	`[|x|]` Abs	Gr 5–6	`0x15`	**Ch 2.4 Negative Numbers • Ch 3.3 Scientific Exponents • Ch 2.4 Absolute Value**
13	R2, C0	`[FRQ]`	`[MED]` Median	`[MODE]` Mode	Gr 5–6	`0x20`	**Ch 7.1 Frequency Tables & Dot Plots • Ch 7.2 Median & Mode**
14	R2, C1	`[RNG]`	`[MIN]` Minimum	`[MAX]` Maximum	Gr 5–6	`0x21`	**Ch 7.2 Data Spread & Extremes**
15	R2, C2	`[IQR]`	`[1Q]` Quartile 1	`[3Q]` Quartile 3	Gr 6+	`0x22`	**Ch 7.2 Quartiles & Box Plots**

Key #	Matrix (R, C)	Primary Legend	[f] Shift	[g] Shift	Grade Ribbon	Code	Primary & Shift Tutorial Links
16	R2, C3	[Σ+]	[Σ-] Remove	[MAD] MeanDev	Gr 4–6	0x23	Ch 6.2 Master Surface Area via Stats • Ch 7.2 Mean Absolute Deviation
17	R2, C4	[N]	[Σx] Total Sum	[x̄] Mean Avg	Gr 5–6	0x24	Ch 7.1 Sample Count & Arithmetic Mean
18	R2, C5	[%]	[→%] Dec to Pct	[%CHG] Change	Gr 5–6	0x25	Ch 5.5 Percentages & Discounts
19	R3, C0-1	[ENTER]	[f] [LASTX] Check	[SHOW] 15-Dig	Gr K–6	0x30	Ch 2.1 The Elevator Push • Ch 8.2 Quiz Answer Submit • Ch 4.2 Superpower 4: LASTX Error Check • Ch 3.3 Full Precision
20	R3, C2	[CLOCK]	[→HR] Decimal	[→HMS] Clock	Gr 3–5	0x32	Ch 6.7 Planetary Geared Clock Modulo-60
21	R3, C3	[FRAME]	[LINE] Line	[COUNT] Step	Gr K–2	0x33	Ch 3.1 Ten-Frame Mode • Ch 3.2 Number Line • Ch 3.1 Step Counter
22	R3, C4	[NUM]	[SCI] Sci Not	[FIX] Dec Dec	Gr K–6	0x34	Ch 2.2 Numerical 4-Stack Mode • Ch 3.3 Scientific Display
23	R3, C5	[<-]	[CSTK] Clr Stk	[CLΣ] Clr Stat	Gr K–6	0x35	Ch 2.1 Backspace Digit • Ch 2.2 Clear Stack • Ch 6.2 Clear Stats
24	R4, C0	[DICE]	[1…x] PRNG	[t…x] Range	Gr 3–6	0x40	Ch 7.4 Dice & Probability Trials
25	R4, C1	[7]	[RECT] Area	[TRI] Area	Gr K–4	0x41	Ch 3.1 Digit Entry • Ch 6.1 Rectangle & Triangle Area
26	R4, C2	[8]	[CIRC] Area	[HYP] Hypoten	Gr K–5	0x42	Ch 3.1 Digit Entry • Ch 6.1 Circle Area & Hypotenuse
27	R4, C3	[9]	[PRISM] Volume	[CONE] Volume	Gr K–5	0x43	Ch 3.1 Digit Entry • Ch 6.6 Prism & Cone Volume
28	R4, C4	[÷]	[MOD] Rem	[÷R] Quotient	Gr 3–5	0x44	Ch 4.1 Division • Ch 4.2 Superpower 2: Simultaneous Quotient & Remainder
29	R5, C0	[f] (f-Shift)	*(f-Shift Latch)*	*(f-Shift Latch)*	Gr K–6	0x50	Sec D.1 Latch Hardware • Primary [f] Shift prefix
30	R5, C1	[4]	[→g] Grams	[→oz] Ounces	Gr K–4	0x51	Ch 3.1 Digit Entry • Ch 9.1 Filament Mass
31	R5, C2	[5]	[→ft] Feet	[→mi] Miles	Gr K–4	0x52	Ch 3.1 Digit Entry • Ch 9.2 Distance Scaling

Key #	Matrix (R, C)	Primary Legend	[f] Shift	[g] Shift	Grade Ribbon	Code	Primary & Shift Tutorial Links
32	R5, C3	[6]	[→mL] Millilit	[→fl] Fluid Oz	Gr K–4	0x53	**Ch 3.1 Digit Entry • Ch 9.3 Liquid Volumes**
33	R5, C4	[×]	*(Unassigned)*	[FLAGS] Stack	Gr 3–5	0x54	**Ch 4.1 Array Multiplication • Ch 2.2 Configurable Stack Depths**
34	R6, C0	[g] (g-Shift)	*(g-Shift Latch)*	*(g-Shift Latch)*	Gr K–6	0x60	**Sec D.1 Latch Hardware** • Secondary [g] Shift prefix
35	R6, C1	[1]	[→kg] Kilo grams	[→lb] Pounds	Gr K–4	0x61	**Ch 3.1 Digit Entry • Ch 9.1 Mass Conversions**
36	R6, C2	[2]	[→°C] Celsius	[→°F] Fahren	Gr K–4	0x62	**Ch 3.1 Digit Entry • Ch 9.5 Thermal Tracking**
37	R6, C3	[3]	[→cm] Cen timet	[→in] Inches	Gr K–4	0x63	**Ch 3.1 Digit Entry • Ch 9.1 Blueprint Sizing**
38	R6, C4	[-]	[→L] Liters	[→gal] Gallons	Gr K–4	0x64	**Ch 2.1 Subtraction • Ch 9.3 Tank Capacity**
39	R7, C0	[C] (ON)	[?] Quiz Sprint	[OFF] Sleep	Gr K–6	0x70	**Ch 1.1 Cold Boot & Sleep • Ch 8.1 Math Quiz Engine**
40	R7, C1	[0]	[REGS] Viewer	*(Unassigned)*	Gr K–6	0x71	**Ch 3.1 Digit Entry • Ch 2.2 Memory Registers**
41	R7, C2	[.]	[0.3̄] Repeat	*(Unassigned)*	Gr 3–5	0x72	**Ch 5.1 Decimal & Repeating Notation**
42	R7, C3	[≠]	[>] Greater	[<] Less	Gr 1–4	0x73	**Ch 4.3 Inequality Comparisons**
43	R7, C4	[+]	[≥] Greater /Eq	[≤] Less/E q	Gr K–4	0x74	**Ch 2.1 Addition • Ch 4.3 Inequality Comparisons**

D.4 Developmental Keycap Ribbon Architecture

The SC-6 physical keyboard supports the full elementary-to-middle school progression through progressive pedagogical gating:

Grade Level	Pedagogical Focus	Unlocked Keycaps Suite
Grade K–1: Sensory Foundations	Concrete counting, make-ten pairing, and tactile arithmetic	[FRAME] Ten-Frame, [COUNT], [LINE], [+], [-], [ENTER], [C], [<-]
Grade 2: Place Value & Skip-Counting	Multi-digit decomposition, doubles, and rhythmic counting	[PV] Place Value, [REP] Skip-Counting, [$] Currency, [x⇔y]

Grade Level	Pedagogical Focus	Unlocked Keycaps Suite
Grade 3: Arrays, Area & Fractions	Grid arrays, time arithmetic, and unit fraction exploration	`[×]`, `[÷]`, `[RECT]`, `[CLOCK]` Planetary Clock, `[FDISP]`, `[. n . d]`
Grade 4: Division & Fraction Mastery	Division with remainders and step-by-step fraction reduction	`[÷R]` Quotient & Remainder, `[a ⍁/c]`, `[d/c]`, `[SIMP]`, `[f] [LASTX]`
Grade 5: Unlike Fractions & Surface Area	Common denominators, 3D volume, and ledger accumulation	`[GCF]`, `[LCM]`, `[PRISM]`, `[Σ+]` Surface Area Ledger, `[FRQ]` Tables
Grade 6+: Number Theory & Sprint	Negatives, primes, descriptive statistics, and rapid mental math sprints	`[+/-]`, `[|x|]`, `[PRIME]`, `[FACT]`, `[a:b]`, `[x²]`, `[√x]`, `[IQR]`, `[MAD]`

D.5 Verification & Firmware Implementation Reference

The 43-key matrix pinouts, row-column electrical scanning bus, and progressive K–6 shift mappings are verified against the SC-6 hardware keymap specification, faceplate laser-topography blueprints, and classroom durability standards.

Alphabetical Subject Index

2

2-Stack Operational Display 24, 57, 64

A

Applied Elementary STEM Labs 33

C

Classroom Planetary Clock 25, 44, 163, 180

Counting, Place Value & Base-10 . . . . . 20, 21

D

Discrete Probability & Primes 31, 204, 205

F

Fraction Studio 84mm Towers 26, 27

G

Gamified Math Quiz Engine 243, 244

Geometry & Surface Area via [Σ+] 29, 163, 164, 166

H

Hardware Architecture & Classroom Durability 40, 331, 397

K

Keycap [.] (Fraction Two-Dot) 76, 142, 145

Keycap [C] / [CLEAR] 61

Keycap [ENTER] 9, 14, 15

Keycap [LASTX] 16, 21, 23

Keycap [REP] 15, 25, 57

Keycap [SIMP] 16, 27, 135

Keycap [x■y] 15, 47, 57, 61

Keycap [Σ+] 29, 163, 172

M

Math Domino Studio 60, 256, 257

N

Number Lines & Skip-Counting 15, 20

P

Probability Dice & Spinners 319

R

Ratio Mode & Proportions 31, 147, 159
RPN Elevator Metaphor 60, 61, 62, 68

S

Snap-Dome 400g Keypad 19, 48, 363, 393
Superpower [DivR] (Quotient & Remainder) 15, 105, 220, 380
Superpower [LASTX] (Undo & Inverse) 16, 21, 23
Superpower [REP] (Repeat Ladder) 15, 25, 55, 57
Superpower [SIMP] (Factor Reduction) 16, 27, 135

T

Ten-Frames & Desk Counters 18, 20, 42
Transflective Ambient Display 42, 47, 122, 142
Two-Dot Fraction Entry Syntax 26, 135, 142, 150