

MASTER DEVICE & CONNECTIVITY MATRIX

Provider-neutral engineering matrix — NOT deployed inventory / topology selection / provider architecture / installation plan

16 CANDIDATE RECORDS × 12 ATTRIBUTE DIMENSIONS = 192 RELATIONSHIPS • PHYSICAL READY 0 • CONCEPTUAL READY 16 • FINAL TOPOLOGY SELECTED 0

BAND A — IDENTITY / OBSERVABLE / FUNCTION / TRAFFIC • ROWS 001–016						
DEV ID	OBS ID	OBSERVABLE CONDITION	FUNCTION SET	DEVICE CLASS	TRAFFIC PATTERN	UPLINK / DOWNLINK
DEV-CAND-001	OBS-CAND-001	Temperature condition (heating entry)	FSET-MEASURE	D-CLASS-01	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-002	OBS-CAND-002	Pressure condition (heating entry)	FSET-MEASURE	D-CLASS-01	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-003	OBS-CAND-003	Flow/consumption condition (heating metering)	FSET-READ	D-CLASS-03	COUNTER/METERING	UPLINK + DOWNLINK
DEV-CAND-004	OBS-CAND-004	Pressure condition (CW entry)	FSET-MEASURE	D-CLASS-01	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-005	OBS-CAND-005	Flow condition (CW entry)	FSET-MEASURE	D-CLASS-01	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-006	OBS-CAND-006	Flow/consumption condition (CW metering)	FSET-READ	D-CLASS-03	COUNTER/METERING	UPLINK + DOWNLINK
DEV-CAND-007	OBS-CAND-007	Temperature/availability condition (hot water)	FSET-MEASURE	D-CLASS-01	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-008	OBS-CAND-008	Leakage indication (hot water)	FSET-DETECT	D-CLASS-04	STATE CHANGE	UPLINK ONLY
DEV-CAND-009	OBS-CAND-009	Water-presence/flooding indication (basement)	FSET-DETECT	D-CLASS-04	EVENT-DRIVEN	UPLINK ONLY
DEV-CAND-010	OBS-CAND-010	Temperature condition (basement)	FSET-MEASURE	D-CLASS-02	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-011	OBS-CAND-011	Humidity condition (basement)	FSET-MEASURE	D-CLASS-02	PERIODIC TELEMETRY	UPLINK ONLY
DEV-CAND-012	OBS-CAND-012	Supply-availability condition (electrical)	FSET-DETECT	D-CLASS-04	STATE CHANGE	UPLINK ONLY
DEV-CAND-013	OBS-CAND-013	Outage/event condition (electrical)	FSET-DETECT	D-CLASS-04	EVENT-DRIVEN	UPLINK ONLY
DEV-CAND-014	OBS-CAND-015	Moisture/water-ingress condition (roof)	FSET-DETECT	D-CLASS-04	EVENT-DRIVEN	UPLINK ONLY
DEV-CAND-015	OBS-CAND-017	Availability/operational condition (lift)	FSET-DETECT	D-CLASS-04	STATE CHANGE	UPLINK ONLY
DEV-CAND-016	OBS-CAND-018	Outage/event condition (lift)	FSET-DETECT	D-CLASS-04	EVENT-DRIVEN	UPLINK ONLY

BAND B — CONNECTIVITY / PATTERN / READINESS • SYNCHRONIZED DEV KEY						
DEV ID	PROFILE	PATTERN CLASS	STORE / FWD	REACHABILITY	PHYSICAL READINESS	CONCEPTUAL READINESS
DEV-CAND-001	CP-CAND-001	BOTH PLAUSIBLE	HIGH	MEDIUM	L1 — NOT READY	READY
DEV-CAND-002	CP-CAND-001	BOTH PLAUSIBLE	HIGH	MEDIUM	L1 — NOT READY	READY
DEV-CAND-003	CP-CAND-002	BOTH PLAUSIBLE	HIGH	LOW	L1 — NOT READY	READY
DEV-CAND-004	CP-CAND-001	BOTH PLAUSIBLE	HIGH	MEDIUM	L1 — NOT READY	READY
DEV-CAND-005	CP-CAND-001	BOTH PLAUSIBLE	HIGH	MEDIUM	L1 — NOT READY	READY
DEV-CAND-006	CP-CAND-002	BOTH PLAUSIBLE	HIGH	LOW	L1 — NOT READY	READY
DEV-CAND-007	CP-CAND-001	DIRECT-FRIENDLY	HIGH	MEDIUM	L1 — NOT READY	READY
DEV-CAND-008	CP-CAND-003	DIRECT-FRIENDLY	HIGH	HIGH	L1 — NOT READY	READY
DEV-CAND-009	CP-CAND-003	EDGE-FRIENDLY	HIGH	HIGH	L1 — NOT READY ZONE-EXISTENCE-GATED	READY
DEV-CAND-010	CP-CAND-004	EDGE-FRIENDLY	MEDIUM	LOW	L1 — NOT READY ZONE-EXISTENCE-GATED	READY
DEV-CAND-011	CP-CAND-004	EDGE-FRIENDLY	MEDIUM	LOW	L1 — NOT READY ZONE-EXISTENCE-GATED	READY
DEV-CAND-012	CP-CAND-003	BOTH PLAUSIBLE	HIGH	HIGH	L1 — NOT READY	READY
DEV-CAND-013	CP-CAND-003	BOTH PLAUSIBLE	HIGH	HIGH	L1 — NOT READY	READY
DEV-CAND-014	CP-CAND-001	TBD	HIGH	MEDIUM	L1 — NOT READY ACCESS-GATED	READY
DEV-CAND-015	CP-CAND-003	EDGE-FRIENDLY	HIGH	HIGH	L1 — NOT READY	READY
DEV-CAND-016	CP-CAND-003	EDGE-FRIENDLY	HIGH	HIGH	L1 — NOT READY	READY

FUNCTION SET LEGEND — EXACT
FSET-MEASURE = MEASURE / TIMESTAMP / BUFFER / STORE / FORWARD / REPORT STATUS
FSET-READ = READ INTERFACE / COUNT / TIMESTAMP / BUFFER / STORE / FORWARD / REPORT STATUS
FSET-DETECT = DETECT / TIMESTAMP / BUFFER / STORE / FORWARD / REPORT STATUS
UPLINK ONLY = 14 • UPLINK + DOWNLINK = 2 • UPLINK + DOWNLINK ≠ ENGINEERING ACTUATION

SOURCE-DERIVED SUMMARY
CANDIDATES 16 • INSTALLED DEVICES ESTABLISHED 0
PHYSICAL READY 0 • L1 — NOT READY 16 • CONCEPTUAL READY 16
DIRECT-FRIENDLY 2 • EDGE-FRIENDLY 5 • BOTH PLAUSIBLE 8 • TBD 1
FINAL TOPOLOGY SELECTED 0
READY ≠ IMPLEMENTED OR DEPLOYED
L1 — NOT READY ≠ PROVED ABSENCE

EC03-08-TBD-01
Physical readiness / candidate location across all 16 = **L1 — NOT READY / NOT ESTABLISHED**
Includes DEV-009 / 010 / 011 zone-existence gates and DEV-014 roof access gate.
Owner: NOT ESTABLISHED IN ASSIGNED SOURCE SCOPE

EC03-08-TBD-02
Final Direct/Edge topology = **NOT SELECTED** • DEV-CAND-014 pattern class = **TBD**
Owner: NOT ESTABLISHED IN ASSIGNED SOURCE SCOPE

1 DEVICE CANDIDATE ≠ INSTALLED DEVICE

2 L1 — NOT READY ≠ PROVED ABSENCE

3 CONCEPTUAL ARCHITECTURE READY ≠ IMPLEMENTED OR DEPLOYED

4 PATTERN LABELS = PLAUSIBILITY, NOT TOPOLOGY SELECTION

5 CONNECTIVITY PROFILE ≠ SIM / TARIFF / APN / VPN / NETWORK TECHNOLOGY / OPERATOR PRODUCT

6 UPLINK + DOWNLINK ≠ ENGINEERING ACTUATION

7 D-CLASS-05 IS CONCEPTUAL ONLY; NO EDGE-01 IS NAMED OR PLACED

8 MASTER MATRIX VALUES ARE SOURCE-REUSED; NO CELL MAY BE INVENTED OR NORMALIZED

PROVIDER-NEUTRAL • RESPONSIBILITY DOMAINS 0 • PLANES 0 • TRUST / ACCESS / INTEGRATION BOUNDARY NOT APPLICABLE • DIRECT-FRIENDLY ≠ DIRECT SELECTED • EDGE-FRIENDLY ≠ EDGE SELECTED • BOTH PLAUSIBLE = CO-APPLICABLE / NOT SEQUENTIAL / NOT SELECTED

No responsibility swimlanes, Trust boundary, DATA / CONTROL / OPERATIONS planes, winner colors, severity heatmap, deployment icons, Direct/Edge flow, network topology, SIM/device/gateway inventory, ALAU AI, or 3D.

REFERENCE CONTEXT ONLY • SEM-MCD-001 — Semey, Shakarima 13A • No new building fact inferred • SOURCE: EC-03 §33 • DIRECT DEFINITIONS: §§16–19 / §25