

SCOPE & OPEN QUESTIONS

Which operator-specific technical assumptions, interfaces, constraints, responsibilities, and pilot parameters must be jointly validated with Beeline before the HouseMaster reference architecture can become a validated pilot architecture?

15 UNRESOLVED QUESTIONS • 7 VALIDATION TRACKS | NONE ANSWERED | OWNER ASSIGNMENTS 0 | NO BEELINE COMMITMENT

TBD WITH BEELINE = Operator-specific implementation detail requiring validation with Beeline.
DOES NOT MEAN: architecture error / missing HouseMaster design / assumed Beeline capability / Beeline commitment.

BEELINE FULL INTERNAL NETWORK / PLATFORM DISCLOSURE IS NOT REQUIRED
Only information needed to validate the agreed integration surface is requested. No Beeline internal architecture is depicted.

TECH-01 CONNECTIVITY / SIGNAL PATH	TECH-03 API / DATA	TECH-05 DEPLOYMENT / CLOUD
Q1 What IoT/M2M connectivity models can Beeline support for a Connected Building pilot? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q6 Which operator APIs, events or integration interfaces are available for connectivity management and telemetry/event exchange? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q11 What infrastructure or cloud role, if any, should Beeline play in the pilot architecture? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK
Q2 Which transport options and connectivity-state events can be exposed to an external domain platform such as HouseMaster? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q7 Which data objects may cross the Beeline ↔ HouseMaster boundary, and what restrictions apply? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q12 What Kazakhstan data-residency, resilience, backup, DR and deployment constraints should be incorporated into the validated architecture? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK
Q3 What network-side constraints should be assumed for basement, technical-room and other difficult indoor MCD environments? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q8 Which interaction model is preferred: synchronous API, asynchronous events, webhook/callback, message transport, or another operator-approved mechanism? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	TECH-06 OPERATIONS / SLA
TECH-02 IDENTITY / LIFECYCLE	TECH-04 SECURITY / TRUST	Q13 How should operational responsibility be divided between Beeline connectivity operations and HouseMaster building-domain operations? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK
Q4 Which SIM/eSIM/M2M identity objects and lifecycle states can Beeline expose to HouseMaster? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q9 What authentication, authorization and trust model would Beeline require for HouseMaster integration? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q14 What incident, escalation, observability, support and SLA/SLO interfaces can be agreed for the pilot? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK
Q5 What provisioning, activation, suspension, replacement and deactivation interfaces are available or feasible? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	Q10 What security, audit, logging, credential and incident-response requirements must the pilot satisfy? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK	TECH-07 PILOT
		Q15 What minimum pilot scope, technical acceptance criteria, participants and duration would Beeline consider sufficient to make a scale-up decision? STATUS: TBD WITH BEELINE • DECISION: TBD • OWNER / NOTE: UNASSIGNED / BLANK

ARCHITECTURE-VALIDATION OUTCOMES — 4 EQUAL OPTIONS

CONFIRM — Reference model applies | REPLACE — Use Beeline actual / alternative mechanism
CONSTRAIN — Apply technical / security / operational limit | REMOVE — Not used in pilot
Not commercial / approval / contract / deployment statuses. No ranking, score, winner, or traffic-light semantics.

VALIDATION PIPELINES

HOUSEMASTER REFERENCE ARCHITECTURE + BEELINE TECHNICAL INPUT → JOINT VALIDATION → VALIDATED PILOT ARCHITECTURE

TBD → CONFIRM / REPLACE / CONSTRAIN / REMOVE → PILOT DESIGN
VALIDATED PILOT ARCHITECTURE ≠ PRODUCTION ARCHITECTURE

EXPECTED AFTER JOINT VALIDATION — 7

1 Confirmed integration capabilities
2 Agreed alternative mechanisms
3 Documented technical constraints
4 Removed out-of-scope assumptions
5 Assigned unresolved TBDs
6 Validated integration surface
7 Inputs for Pilot Architecture v0.1

OPEN / TBD STATUS • OPEN/TBD 15 • TBD WITH BEELINE 15 • DECISION = TBD 15 • OWNER ASSIGNMENTS 0 • UNASSIGNED / BLANK IS AN OPEN FIELD, NOT APPROVAL

1 REFERENCE ARCHITECTURE ≠ BEELINE INTERNAL ARCHITECTURE

2 VALIDATED PILOT ARCHITECTURE ≠ PRODUCTION ARCHITECTURE

3 TBD WITH BEELINE ≠ ARCHITECTURE ERROR

4 TBD WITH BEELINE ≠ MISSING HOUSEMASTER DESIGN

5 TBD WITH BEELINE ≠ ASSUMED BEELINE CAPABILITY

6 TBD WITH BEELINE ≠ BEELINE COMMITMENT

7 VALIDATION INPUT / OUTCOME ≠ COMMERCIAL COMMITMENT OR STATUS

NOT an approval sheet / readiness scorecard / commercial status page / Beeline commitment page / production architecture page. No SEM-MCD-001, scoring, maturity or readiness percentage, severity colors, approval badge, Beeline architecture diagram, deployment diagram, implementation drawing, commercial layer, ALAU AI, or 3D.