

abaisero.sty

Andrea Baisero

June 28, 2024

1 Options

Options are processes left-to-right. If no options are provided, or none are enabled by the end of the processing, then by default they are all considered to be enabled.

Option	Description
<code>all</code>	Enable all commands
<code>math</code>	Enable mathematical commands
<code>no-math</code>	Disable mathematical commands
<code>linalg</code>	Enable linear algebra commands
<code>no-linalg</code>	Disable linear algebra commands
<code>optim</code>	Enable optimization commands
<code>no-optim</code>	Disable optimization commands
<code>stats</code>	Enable statistics commands
<code>no-stats</code>	Disable statistics commands
<code>dists</code>	Enable distributions commands
<code>no-dists</code>	Disable distributions commands
<code>ml</code>	Enable machine learning commands
<code>no-ml</code>	Disable machine learning commands
<code>rl</code>	Enable reinforcement learning commands
<code>no-rl</code>	Disable reinforcement learning commands
<code>marl</code>	Enable multi-agent reinforcement learning commands
<code>no-marl</code>	Disable multi-agent reinforcement learning commands
<code>theorem</code>	Enable theorem commands
<code>no-theorem</code>	Disable theorem commands
<code>misc</code>	Enable miscellanea commands
<code>no-misc</code>	Disable miscellanea commands

2 Commands

Option [math]

Symbol	Command	Description	Example
\mathbb{N}	<code>\naturalset</code>	the set of natural numbers	$\mathbb{N} \doteq \{1, 2, 3, \dots\}$
\mathbb{Z}	<code>\integerset</code>	the set of integer numbers	$\mathbb{Z} \doteq \{0, 1, -1, 2, -3, \dots\}$
\mathbb{R}	<code>\realset</code>	the set of real numbers	$\sqrt{2} \in \mathbb{R}$
$*$	<code>\kstar</code>	the Kleene star operator	$\mathcal{X}^* \doteq \bigcup_{k=0}^{\infty} \mathcal{X}^k$
$+$	<code>\kplus</code>	the Kleene plus operator	$\mathcal{X}^+ \doteq \bigcup_{k=1}^{\infty} \mathcal{X}^k$
softmax	<code>\softmax</code>		
softmin	<code>\softmin</code>		
sign	<code>\sign</code>		$x = \text{sign } x \cdot x $

Option [linalg]

Symbol	Command	Description	Example
diag	<code>\diag</code>		
rank	<code>\rank</code>		
tr	<code>\trace</code>		$\text{tr}(M) \doteq \sum_{i=1}^n M_{ii}$
col	<code>\colspace</code>		
ker	<code>\nullspace</code>	Nullspace (a.k.a kernel) of a linear mapping	
span	<code>\spanspace</code>		
$^{\top}$	<code>\T</code>	Transpose superscript	symmetric $M \implies M = M^{\top}$
$^{-1}$	<code>\I</code>	Inverse superscript	invertible $M \implies MM^{-1} = I$
$^{+}$	<code>\PI</code>	Pseudo-inverse superscript	$MM^{+}M = M$
$^{-\top}$	<code>\IT</code>	Inverse transpose superscript	$M^{-\top} = (M^{-1})^{\top} = (M^{\top})^{-1}$
$^{+\top}$	<code>\PIT</code>	Pseudo-inverse transpose superscript	$M^{+\top} = (M^{+})^{\top} = (M^{\top})^{+}$

Option [optim]

Symbol	Command	Description	Example
argmax	<code>\argmax</code>		$\text{argmax}_a Q^{\pi}(s, a)$
argmin	<code>\argmin</code>		$\theta^* \doteq \text{argmin}_{\theta} \mathcal{L}(\theta)$
$*$	<code>\opt</code>	Optimality superscript	$\pi^*(s) = \text{argmax}_a Q^*(s, a)$

Option [stats]

Symbol	Command	Description	Example
\mathbb{C}	<code>\Cov</code>	Covariance	$\mathbb{C}(x, y) = \mathbb{E}[xy] - \mathbb{E}[x] \mathbb{E}[y]$
\mathbb{H}	<code>\Ent</code>	Entropy	$\mathbb{H}[x] = -\mathbb{E}[\log \Pr(x)]$
\mathbb{E}	<code>\Exp</code>	Expectation	$\mathbb{E}[f(x)] = \sum_x \Pr(x) f(x)$
\mathbb{I}	<code>\Ind</code>	Indicator function	$\Pr(x = 0) = \mathbb{E}[\mathbb{I}[x = 0]]$
KL	<code>\KL</code>	KL-divergence	$\text{KL}(p \parallel q) \doteq \mathbb{E}_{x \sim p}[\log p(x) - \log q(x)]$
D_{KL}	<code>\DKL</code>	KL-divergence (alternative)	
\mathbb{I}	<code>\MI</code>	Mutual Information	
\mathbb{V}	<code>\Var</code>	Variance	$\mathbb{V}[x] = \mathbb{E}[x^2] - \mathbb{E}[x]^2$

Option [dists]

Symbol	Command	Description
Categorical	<code>\Categorical</code>	Categorical
Dirichlet	<code>\Dirichlet</code>	Dirichlet
Normal	<code>\Normal</code>	Normal
Uniform	<code>\Uniform</code>	Uniform

Option [ml]

Symbol	Command	Description	Example
\mathcal{D}	<code>\data</code>	Data set	$\mathcal{D} \doteq \{(x_i, y_i)\}_{i=1}^N$
\mathcal{L}	<code>\loss</code>	Loss function	$\mathcal{L}(\theta; x, y) = \frac{1}{2} \ y - f(x; \theta)\ ^2$
nll	<code>\nll</code>	Neg-log-likelihood	$\text{nll}(x) \doteq -\log \Pr(x)$
MSE	<code>\mse</code>	Mean-squared-error	

Option [rl]

Symbol	Command	Description
\mathcal{A}	<code>\aset</code>	Action set
\mathcal{B}	<code>\bset</code>	Belief set
\mathcal{H}	<code>\hset</code>	History set
\mathcal{O}	<code>\oset</code>	Observation set
\mathcal{R}	<code>\rset</code>	Reward set
\mathcal{S}	<code>\sset</code>	State set
D	<code>\dfn</code>	Dynamics function
G	<code>\gfn</code>	Generative function
O	<code>\ofn</code>	Observation function
R	<code>\rfn</code>	Reward function
T	<code>\tfn</code>	Transition function
ε	<code>\nohistory</code>	Empty history
π	<code>\policy</code>	policy
Q^π	<code>\qpolicy</code>	Q policy values
\hat{Q}	<code>\qmodel</code>	Parametric model
V^π	<code>\vpolicy</code>	V policy values
\hat{V}	<code>\vmodel</code>	Parametric model
A^π	<code>\apolicy</code>	A policy values
\hat{A}	<code>\amodel</code>	Parametric model
U^π	<code>\upolicy</code>	U policy values
\hat{U}	<code>\umodel</code>	Parametric model

Option [marl]

Symbol	Command	Description
$\bar{\pi}$	<code>\policies</code>	Joint policy
\bar{h}	<code>\hs</code>	Joint history
\bar{a}	<code>\as</code>	Joint action
\bar{o}	<code>\os</code>	Joint observation
$Q^{\bar{\pi}}$	<code>\qpolicies</code>	Q joint-policy values
$V^{\bar{\pi}}$	<code>\vpolicies</code>	V joint-policy values
$A^{\bar{\pi}}$	<code>\apolicies</code>	A joint-policy values
$U^{\bar{\pi}}$	<code>\upolicies</code>	U joint-policy values

Option [theorem]

Symbol	Command	Description
	<code>\begin{definition}</code>	
	<code>\begin{example}</code>	
	<code>\begin{axiom}</code>	
	<code>\begin{conjecture}</code>	
	<code>\begin{proposition}</code>	
	<code>\begin{lemma}</code>	
	<code>\begin{theorem}</code>	
	<code>\begin{corollary}</code>	
	<code>\begin{generalization}</code>	

Option [misc]

Symbol	Command	Description
\dagger	<code>\D</code>	Dagger superscript
(k)	<code>\iter{k}</code>	Superscript indicating iteration