BOX NOW API Integration

PARTNER API

Ivan Bebek
BOX NOW D.O.O. | OREŠKOVIĆEVA 6H/1, ZAGREB

Version	Date	Description	Author
1,0	2022-10-20	Initial document	Igor Tomšić
2,0	2023-06-06	Updated Version	Ivan Bebek
3,0	2023-09-12	Returns, COD details	Ivan Bebek
4,0	2023-10-27	COD example	Ivan Bebek
5,0	2024-01-16	Update (Appendix)	Ivan Bebek
6,0	2024-02-13	checkAddressDelivery	Ivan Bebek
7,0	2024-09-26	APM endpoint change	Ivan Bebek
8,0	2024-11-27	Multiple label fetch	Ivan Bebek
9,0	2025-06-20	Location API text edit	Ivan Bebek
10,0	2026-03-18	locationapi,customerReturns	Ivan Bebek

Contents

Set up 4
Enviroments 5
Process of requesting a delivery 5
Authenticate yourself /auth-sessions 5
List all available destinations https://locationapi-production.boxnow.hr/v1/apms_hr-HR.json 6
List all available origins /origins 8
Request a delivery /delivery-requests 11
Prepaid: 11
Cash on Delivery: 12
Specific return location 13
Check Adress for delivery 14
Modify your delivery request /delivery-requests/{id} 17
See all parcels /parcels 18
Fetch a PDF label /parcels/{id}/label.pdf 20
Fetch multiple PDF labels /labels:search 22
Cancel delivery request /parcels/{id}:cancel 23
Creating customer return 24
Destination Map (Widget/Custom) 25
Troubleshooting 25
Appendix (API Endpoints) 29
Authentication 29
Locations 31
Origins: 31
Destinations: 33
Delivery Requests 36
Complex Delivery Request: 36
CSV Delivery Request: 38
Return Delivery Request: 39

Adress Delivery Request:....43
Update Delivery Request:....45
Labels....47
Single Shipping Label:....47
Multipe Shipping Label:....49
Parcels....51
Confirm AnyAPM Parcel Delivery:....51
Cancel Parcel:....52
Parcel Information:....54
Delivery Partners....58

Set up

To use our API, you must first register your company with our customer support. To do that, reach out to us at sales@boxnow.hr with the following information:

- **Company name, address, tax ID (OIB and VAT number), bank account number (IBAN)**
- **Phone numbers** of users that will have access to the Partner Portal system. We will use these numbers for 'One Time Password' (OTP) SMS authentications during log-in
- **All addresses of pickup points** where we will be picking up your orders for delivery

After you are successfully registered, you will receive from us the following:

OAUTH_CLIENT_ID

Keep this value private and safe! This is your OAuth2 Client ID that you will use to authenticate with the Partner API.

OAUTH_CLIENT_SECRET

Keep this value private and safe! This is your OAuth2 Client Secret that you will use to authenticate with the Partner API.

API_URL

This is your Base URL for the Partner API, to which you will then append the relevant endpoint paths.

Enviroments

Sandbox/Stage

An environment with limited functionalities, where you can test the integration.

Production

Use this environment with caution, as it is *live* and connected to real end-users.

Process of requesting a delivery

Follow these steps to successfully request a delivery and perform other related actions:

Authenticate yourself /auth-sessions

Authentication is based on OAuth 2.0 standard, Client Credentials grant.

In order to use the API, you **must attach the access token to Authorization header as a Bearer token**.

See an example of a successful integration:

POST *API URL*/api/v1/auth-sessions

```
{
“grant_type”: “client_credentials”,
“client_id”: “string”,
“client_secret”: ”string”
}
```

Status Code 200

```
{
“access_token”: “client_credentials”,
“token_type”: “Bearer”,
“expires_in”: 3600
}
```

List all available destinations https://locationapi-production.boxnow.hr/v1/apms_hr-HR.json

Only applicable if you are going to be using delivery to our APMs (**A**utomatic **P**arcel **M**achines).

This call will list all available APM locations where we can deliver your parcel to.

See an example of a successful integration:

```
GET https://locationapi-production.boxnow.hr/v1/apms_hr-HR.json
```

```
curl -X 'GET' \

https://locationapi-production.boxnow.hr/v1/apms_hr-HR.json
```

```
Status Code 200
```


```
{

“data”: [
        {
        "id": "string",
        "type": "apm",
        "image": "https://via.placeholder.com/150",
        "lat": "45.79359675448525",
        "lng": "15.928399281607227",
        "title": "Ulica Marice Barić 6, Zagreb",
        "name": "BOX NOW sjedište",
        "postalCode": "10000",
        "country": "HR",
        "note": "Paketomat se nalazi ispred BOX NOW sjedišta/depoa.",
        "addressLine1": "Ulica Marice Barić 6",
        "addressLine2": "string",
        "region": "hr-HR",
        "state": "string ",
        "expectedDeliveryTime": "string",

        }
    ]

}
```

Alternatively, refer to section 4 for a PHP script you can embed into your web to display all available APMs via a pop-up widget, or for a brief descriptions of successful custom map integration.

id

When requesting delivery, you will refer to these records by **id**.

You will need also to select location from which the delivery will be picked up – typically your warehouse.

List all available origins /origins

This call will list all available pick-up points locations where BOX NOW can pick up all your parcels from – typically your warehouses.

You can list all your warehouses using /origins API which has the same parameters as /destinations API call where you do not specify parameters latlng, radius or requiredSize, but you specify locationType as “warehouse”. You refer to this location by its ID.

Moreover there is one specific location called any-apm that can be listed by the same way and using locationType as “any-apm”, it returns just one location – any-apm. You can refer to it by its ID. Usage of this will be explained in next section.

Name	Type	Description
lating	String	If applied, only locations in the specified radius from this gps coordinate, are returned
radius	Number	Radius in meters to return only locations within selected radius from given GPS location. Ignored if latlng is not present. Default value: 25000

requiredSize	Number	Return only locations that can accept a package of your requiredSize
locationType	Array[string]	Return only locations with given a type. If not present, filter is not applied. Available values: any-apm, warehouse, depot
name	String	Return only locations with matching name
regionLangu ageTag	String	example hr-HR
X-PartnerID	String	Partner ID you want to manage. You can list partners you are allowed to manage from /entrusted-partners endpoint.

See an example of a successful integration:

GET *API URL*/api/v1/origins

```
curl -X 'GET' \
'.../origins\
-H 'accept: application/json'
```

Status Code 200


```
{

“data”: [
                {
                "id": "string",
                "type": "apm",
                "image": "https://via.placeholder.com/150",
                "lat": "45.79359675448525",
                "lng": "15.928399281607227",
                "title": "Ulica Marice Barić 6, Zagreb",
                "name": "BOX NOW sjedište",
                "postalCode": "10000",
                "country": "HR",
                "note": "Paketomat se nalazi ispred BOX NOW sjedišta/depoa.",
                "addressLine1": "Ulica Marice Barić 6",
                "addressLine2": "string",
                "region": "hr-HR"
                }
        ]

}
```


Further responses, which might occur:

Error Code	Description
400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.
403	Account disabled. Your account had been disabled, contact support.

Request a delivery /delivery-requests

Use this call to order a delivery of a parcel.

Once a **successful request** for delivery is made:

- (optional) We will send you an email notifying you of a successful delivery request creation with a PDF label attached
- (Described below) You should fetch the PDF label for each parcel using/parcels/{id}/label.pdf, print it and stick it to the parcel(s).
- We will send a courier to pick up the parcel(s) at agreed time
- We will notify the customer that we have received a delivery order and that a parcel will be delivered to them

See an example of a successful integration:

POST *API URL*/api/v1/delivery-requests

Prepaid:

```
{
        "orderNumber": "string",
        "invoiceValue": "25.50",
        "paymentMode": "prepaid",
        "amountToBeCollected": "0.00",
        "allowReturn": true,
        "origin": {
                "contactNumber": "+385 91 1234 1234",
                "contactEmail": "partner.example@boxnow.hr",
                "contactName": "Hrvoje Horvat",
                "locationId": "string"
                },
        "destination": {
                "contactNumber": "+385 91 123 123",
                "contactEmail": "customer.example@boxnow.hr",
                "contactName": "Ivan Ivanic",
                "locationId": "string"
                },
        "items": [
                {
                "id": "string",
                "name": "Smartphone",
                "value": "3.45",
                "weight": 0
                }
        ]
}
```

There are two possible payment modes, and those are **prepaid** and **cod (cash on delivery)**, difference between those two is that if **paymentMode** is **cod** than parameter **amountToBeCollected** cannot be 0 since that is the amount that customer needs to pay before picking up the parcel from APM. In case of **prepaid paymentMode, amountToBeCollected** should be 0.

Cash on Delivery:

```
{
        "orderNumber": "string",
        "invoiceValue": "25.50",
        "paymentMode": "cod",
        "amountToBeCollected": "10.00",
        "allowReturn": true,
        "origin": {
                "contactNumber": "+385 91 1234 1234",
                "contactEmail": "partner.example@boxnow.hr",
                "contactName": "Hrvoje Horvat",
                "locationId": "string"
                },
        "destination": {
                "contactNumber": "+385 91 123 123",
                "contactEmail": "customer.example@boxnow.hr",
                "contactName": "Ivan Ivanic",
                "locationId": "string"
                },
        "items": [
                {
                "id": "string",
                "name": "Smartphone",
                "value": "3.45",
                "weight": 0
                }
        ]
}
```

If you use wild-card (2) as origin location ID, then parameter **compartmentSize** is obligatory inside items object. (1-small, 2-medium, 3-large)

```
"items": [
                {
                "id": "string",
                "name": "Smartphone",
                "value": "3.45",
                "weight": 0,
                "compartmentSize":1/2/3
                }
        ]
```

items: weight

If the parcel weight is unknown, pass ”null”

These parameters are the main identifiers of pick up & delivery locations:

> origin: locationId
> The warehouse where the parcel will be picked up from.
> This parameter is required for delivery-request to be created.
>
> destination: locationId
> Automatic Parcel Machine (APM) where the parcel will be delivered to.

Specific return location

If you want to use specific return location,for expired returns (parcels not picked up from locker by customer), that is different than origin location, than you should add this object in body of request for creating delivery-request.

```
"returnLocation": {
                    "locationId": "XXXX",
                    },
```

You should change **XXXX** with locationId of warehouse that you want returns to be delivered to.
If this object is not used, then origin locationId is used as default for returns.

Check Adress for delivery

If you want to find nearest APM to specific address you can create POST request to:

```
POST API URL/api/v2/delivery-requests:checkAddressDelivery
```

with body of request:

```
{
        “city” : “string”,
        “street” : “string”,
        “postalCode” : “string”,
        “radius” : number,
        “compartmentSize”: 1/2/3,
        “region”: “hr-HR”
}
```

Parametars *postalCode* and *region* are only mandatory fields, but providing more detail data in request will result in more specific location of APM.

Example of successful response:

```
{
“data”: [
                {
                "id": "string",
                "type": "apm",
                "image": "https://via.placeholder.com/150",
                "lat": "45.79359675448525",
                "lng": "15.928399281607227",
                "region": "hr-HR",
                "title": "Ulica Marice Barić 6, Zagreb",
                "name": "BOX NOW sjedište",
                "addressLine1": " Ulica Marice Barić 6, Zagreb",
                "addressLine2": " Ulica Marice Barić 6, Zagreb",
                "postalCode": "10000",
                "country": "HR",
                "note": "Paketomat se nalazi ispred BOX NOW sjedišta/depoa.",
                "expectedDeliveryTime": " xxxx-xx-xx T xx:xx:xx:xx.xxZ",
                "distance": " xxx.xxxxx",
                }
        ]
        }
```

After data about nearest APM is successfully fetched in response, you can use for creating delivery-request for your parcel.

Also, do not forget to pass us the following personal details with each delivery request:

Sender:

- Name

Recipient:

- Name
- Phone Number
- Email

If you want to hide recipients personal information, you can add parameter:

- *showRecipientInformation: true/false*

Default value is true, but if set to false only customer name will be displayed on parcel label.

If you want to rewrite sender shipping label information you can use object:

- overwriteSenderShippingLabelInfo

This objects accepts three parameters:

- row1
- row2
- row3
- row4

So this object would look something like:

```
"overwriteSenderShippingLabelInfo": {
    "row1": "string",
    "row2": "string",
    "row3": "string",
    "row4": "string"
},
```

Note: This part is optional and will not hide sender name.

Status Code 200

```
{
        "referenceNumber": "string",
        "parcels":[
                {
                "id": "string"
                }
        ]

}
```

Note: The "items" correspond to parcels, but item ID is eShop unique ID (if you do not have unique ID of each item then create it by order number combined with sequential item number or any other way) while parcel ID is BoxNow internal unique ID used further to refer to the parcel.
For sending from APM you can use origin "any-APM" and destination specific APM. For delivering to APM where customer will pick up from the same APM you can use both origin and destination location any-APM.

Further responses, which might occur:

Error Code	Description
400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data
403	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct

Modify your delivery request /delivery-requests/{id}

After a delivery request is created, you can modify some parts of the request by calling the PUT method.
Only this parameter is available to you:

Name	Type	Description
orderNumber	string	Unique order reference number you have used to create the delivery request.

See an example of a successful integration:

PUT *API URL*/api/v1/delivery-requests/{id}

```
curl -X 'PUT' \
'…/delivery-requests/{id}' \
-H 'accept: application/json' \
-H 'Content-Type: application/json' \
-d '{
"allowReturn": true
}'
```

Status Code 200

```
{
        "referenceNumber": "string"
}
```

See all parcels /parcels

Use this call to list parcel information related to your delivery requests.
These parameters are available to you:

Name	Type	Description
limit	number	Number of entries per page
orderNumber	string	Return only parcels related to this order number
pageToken	string	Set this token to return records for given page. You get this for each response.
parcelId	string	Return all parcel information with that parcel number
state	string	Return all parcels with desired state (new,canceled etc.)
paymentMode	string	Return all parcels with specific payment mode (cod,prepaid)

See an example of a successful integration:

GET *API URL*/api/v1/parcels

```
curl -X 'GET' \
'.../parcels?limit=50' \
-H 'accept: application/json'
```

Status Code 200

```
{
"pagination": {
        "first": "string",
        "last": "string",
        "next": "string",
        "prev": "string"
},
"count": 0,
"data": [
{
        "id": "string",
        "state": "waiting-for-pickup",
        "deliveryRequest": {
                "typeOfService": "same-day",
                "codeOfDescription": "string",
                "orderNumber": "string",
                "invoiceValue": "string",
                "paymentMode": "prepaid",
                "amountToBeCollected": "string",
                "allowReturn": false,
                "notifyOnAccepted": "partner@example.com",
        "origin": {
                "locationId": "string"
        },
        "destination": {
                "locationId": "string"
        },
        "items": [
                {
                "id": "string",
                "name": "string",
                "code": "string",
                "status": "string",
                "value": "3.45",
                "weight": 0,
                "length": 0,
                "height": 0,
                "width": 0,
                "compartmentSize": 0
                }
        ]
        }
}
]
}
```

Fetch a PDF label /parcels/{id}/label.pdf

Use this call to request a .pdf file with a label you should print a stick onto each parcel. Only this parameter is available to you:

Name	Type	Description
id*	string	Unique parcel ID. You have received parcel ID after a successful delivery request creation or you can list all parcels, see …/parcels Example: 1234567890 Parcel ID is always a 10-digit number.
type*	string	Available values: pdf, zpl (zebra printer language)
dpi	number	Only applies to ZPL. 200 or 300 supported. Available values : 200, 300 Default value : 200
width	number	Label width in mm. Only applies to ZPL. Default value : 100
printerModel	string	Example: ZQ310
X-PartnerID	string	Partner ID you want to manage. You can list partners you are allowed to manage from /entrusted-partners endpoint.

*Required values

See an example of a successful integration:

GET *API URL*/api/v1/parcels/{id}/label.pdf

```
curl -X 'GET' \
'.../parcels/{id}/label.pdf' \
-H 'accept: application/pdf'
```

Status Code 200

.pdf file with the corresponding label

Alternatively, to print all shipping labels at once for your order, you can replace the /parcels/{id} part with /delivery-requests/{orderNumber}: See an example of a successful integration:

GET *API URL*/api/v1/delivery-requests

```
curl -X 'GET' \
'.../delivery-requests/{orderNumber}/label.pdf' \
-H 'accept: application/pdf'
```

Status Code 200

.pdf file with all the corresponding shipping labels of the specific order
Further responses, which might occur:

Error Code	Description
400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again..
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.
403	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.

Fetch multiple PDF labels /labels:search

If needed you can fetch multiple labels by using POST API request

POST *API URL*/api/v1/labels:search

Example of request body:

```
{
  "parcelIds":[
          "string",
          "string",
          "string",
          "string",
  ],

  "paperSize": "string", (usually A4 is the value)
  "perPage": "number",
}

},
```

And as the response you will get labels for parcels Ids listed inside parcelIds array, on paper format you choose and amount per page that you choose.

Cancel delivery request /parcels/{id}:cancel

If needed you can cancel your delivery request using POST API request for fetching parcels, including id of parcel and cancel in the end

POST *API URL*/v1/parcels/{id}:cancel

If your response is empty than delivery request should be successfully canceled.

IMPORTANT: You can only cancel a parcel label when the status of a parcel is "New". For other instances please refer to podrska@boxnow.hr or it@boxnow.hr

Name	Type	Description
id*	string	Unique parcel ID. You have received parcel ID after a successful delivery request creation or you can list all parcels, see …/parcels Example: 1234567890 Parcel ID is always a 10-digit number
X-PartnerID	string	Partner ID you want to manage. You can list partners you are allowed to manage from /entrusted-partners endpoint.

Further responses, which might occur:

Error Code	Description
400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again..
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.

403	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.

Creating customer return

Creating customer returns delivery-request is a bit different then regular delivery request.
First difference is in API request URL

```
POST API URL/api/v1/delivery-requests:customerReturns
```

Second difference is in request body, and it should look something like this:

```
{
  "sender": {
    "contactPhoneNumber": "+385 99 1234 123",
    "contactEmail": "Ivan.Ivanic@mail.hr",
    "contactName": "Ivan Ivanic",
    "locationId": "2"
  },
  "destination": {
    "locationId": "1234"
  },
  "parcels": [
    {
      "id": "123456789",
      "size": 1/2/3,
      "name": "Test",
      "value": "0.00"
    }
  ]
}
```

The biggest difference is that there is nor more **Origin** object, instead there is **Sender** object, and also there is **contactPhoneNumber** instead **contactNumber.** Important thing is that for sender **locationId** must be used **2 (wild card/any-APM),** and for destination **locationId** should be used ID of warehouse in which return is coming.

Destination Map (Widget/Custom)

BoxNow Website - Widget - Developers

Troubleshooting

Description of error codes for 400 Unprocessable entity responses:

Error Code P400
Invalid request data. Make sure you are sending the request according to the documentation

Error Code P401
Invalid request origin location reference. Make sure you are referencing a valid
location ID from Origins endpoint or valid address.

Error Code P402
Invalid request destination location reference. Make sure you are referencing a valid location ID from Destinations endpoint or valid address.

Error Code P403
You are not allowed to use AnyAPM-SameAPM delivery. Contact support if you believe this is a mistake.

Error Code P404
Invalid import CSV. See error contents for additional info.

Error Code C404
Invalid phone number. Make sure you are sending the phone number in full international format, e.g. +385 xx x xxx xxxx.

Error Code P405
Invalid phone number. Make sure you are sending the phone number in full international format, e.g. +385 xx xxxx xxxx.

Error Code P406

Invalid compartment/parcel size. Make sure you are sending one of required sizes 1, 2 or 3 (Small, Medium or Large). Size is required when sending from AnyAPM directly.

Error Code P407

Invalid country code. Make sure you are sending country code in ISO 3166-1 alpha-2 format, e.g. HR.

Error Code P408

Invalid amountToBeCollected amount. Make sure you are sending amount in the valid range of (0, 5000>

Error Code P409

Invalid delivery partner reference. Make sure you are referencing a valid delivery partner ID from Delivery partners endpoint.

Error Code P410

Order number conflict. You are trying to create a delivery request for order ID that has already been created. Choose another order ID.

Error Code P411

You are not eligible to use Cash-on-delivery payment type. Use another payment type or contact our support.

Error Code P412

You are not allowed to create customer returns deliveries. Contact support if you believe this is a mistake.

Error Code P413

Invalid return location reference. Make sure you are referencing a valid location warehouse ID from Origins endpoint or valid address.

Error Code P415

You are not allowed to create delivery to home address. Contact support if you believe this is a mistake.

Error Code P416

You are not allowed to use COD payment for delivery to home address. Contact support if you believe this is a mistake.

Error Code P420

Parcel not ready for cancel. You can cancel only new, undelivered, or parcels that are not returned or lost. Make sure parcel is in transit and try again.

Error Code P421

Invalid parcel weight. Make sure you are sending value between 0 and 10^6.

Error Code P422

Address not found. Try to call just with postal code and country.

Error Code P423

Nearby locker not found.

Error Code P424

Invalid region format. Please ensure the format includes a language code followed by a country code in ISO 3166-1 alpha-2 format, separated by a hyphen, e.g. el-GR, or region exists in context.

Error Code P430

Parcel not ready for AnyAPM confirmation. Parcel is probably already confirmed or being delivered. Contact support if you believe this is a mistake.

Error Code P440

Ambiguous partner. Your account is linked to multiple partners and is unclear on whose behalf you want to perform this action. Send X-PartnerID header with ID of the partner you want

Error Code P441

Invalid X-PartnerID header. Value you provided for X-PartnerID header is either invalid or references partner you don't have access to. Make sure you are sending ID from /entrustedpartners endpoint.

Error Code P442

Invalid limit query parameter. The query limit for this API has been exceeded. Please reduce the size of your query (max allowed is 100).

Description of error codes for 403 Forbidden responses:

Error Code X403

Account disabled. Your account had been disabled, contact support.

Error Code P414

Unauthorized parcel access. You are trying to access information to parcel/s that don't belong to you. Make sure you are requesting information for parcels you have access to.

Description of error codes for 503 Servuce Unavailable responses:

Error Code P600

Locker bridge communication failed. There has been some error when communicating with the locker bridge. Try again later or contact support

Error Code P610

Geolocation API failed. There has been some error when translating address to gps coordinates. Try again later or contact suppor

If you are having troubles integrating our API into your online store based on the current documentation, reach out to us at it@boxnow.hr.

Appendix (API Endpoints)

Below you can find all the API endpoints/calls with regards to the complete structure of the BOX NOW Partner API:

Authentication

TYPE	Endpoint	Description
POST	…/api/v1/auth-sessions	Obtain authentication tokens

Parametars:

N/A

Request body (example)

```
{
“grant_type”: “client_credentials”,
“client_id”: “string”,
“client_secret”: ”string”
}
```

Responses:

Code	Description	Example Value
200	OK	Below

{
“access_token”: “client_credentials”,
“token_type”: “Bearer”,
“expires_in”: 3600
}		

400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.	N/A

401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data	N/A
403	Account disabled. Your account had been disabled, contact support.	N/A

Locations

Origins:

TYPE	Endpoint	Description
GET	…/api/v1/origins	List available origins to pickup the order from

Parametars:

Name	Type	Description	Example
latlng	string	If applied only locations in the specified radiusfrom this gps coord are returned	48.78081955454138, 12.446962472273063
radius	number	Radius in meters to return only locations within selected radius from given GPS location. Ignoredif latlng is not present.	1000 Default Value: 25000
requiredSize	number	Return only locations that can accept a package of your requiredSize	1 Available values: 0, 1, 2, 3
locationType	Array[string]	Return only locations with given types. If not present, filter is not applied	Available values : any-apm, warehouse, depot
name	string	Return only locations with matching name	
regionLanguageTag	String	BCP 47 language tag format	hr-HR
X-Partner ID	String	Partner ID you want to manage. You can list partners you are allowed to manage from /entrusted-partners endpoint.	1

Note: In case of Any APM please disregard the value 0 in requiredSize, as it is necessaryto set a value in that case.

Request body (example):

N/A

Responses:

Code	Description	Example Value
200	OK	Below


```
{
“data”: [
        {
        "id": "string",
        "type": "apm",
        "image": "https://via.placeholder.com/150",
        "lat": "45.79359675448525",
        "lng": "15.928399281607227",
        "title": "Ulica Marice Barić 6, Zagreb",
        "name": "BOX NOW sjedište",
        "postalCode": "10000",
        "country": "HR",
        "note": "Paketomat se nalazi ispred BOX NOW sjedišta/depoa.",
        "addressLine1": "Ulica Marice Barić 6",
        "addressLine2": "string",
        "region": "hr-HR"
}
        ]
}
```


400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again	N/A

401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support	N/A

Destinations:

TYPE	Endpoint	Description
GET	https://locationapi-production.boxnow.hr/v1/apms_hr-HR.json	List available destinations to deliver the order to

Request body (example):
N/A
Responses:

Code	Description	Example Value
200	OK	Below


```
{
“data”: [
        {
        "id": "string",
        "type": "apm",
        "image": "https://via.placeholder.com/150",
        "lat": "45.79359675448525",
        "lng": "15.928399281607227",
        "title": "Ulica Marice Barić 6, Zagreb",
        "name": "BOX NOW sjedište",
        "postalCode": "10000",
        "country": "HR",
        "note": "Paketomat se nalazi ispred BOX NOW sjedišta/depoa.",
        "addressLine1": "Ulica Marice Barić 6",
        "addressLine2": "string",
        "region": "hr-HR"
}
        ]
}
```


400	The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again	N/A

401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support	N/A

Delivery Requests

Complex Delivery Request:

TYPE	Endpoint	Description
POST	…/api/v1/delivery-requests	Create a delivery request for your order

Parameters:

N/A

Request body (example):

```
{
        "orderNumber": "string",
        "invoiceValue": "25.50",
        "paymentMode": "prepaid/cod",
        "amountToBeCollected": "25.50",
        "allowReturn": true,
        "overwriteSenderShippingLabelInfo": {
                "row1": "string",
                "row2": "string",
                "row3": "string",
                "row4": "string"
        },
        "origin": {
                "contactNumber": "+385 91 1234 1234",
                "contactEmail": "partner.example@boxnow.hr",
                "contactName": "Hrvoje Horvat",
                "locationId": "string",
                },
        "destination": {
                "contactNumber": "+385 91 123 123",
                "contactEmail": "customer.example@boxnow.hr",
                "contactName": "Ivan Ivanic",
                "locationId": "string"
                },
        "items": [
                {
                "id": "string",
                "name": "Smartphone",
                "value": "3.45",
                "weight": 0
                }
        ]
}
```

Responses:

Code	Description	Example Value
200	OK	Below

```
{
        "referenceNumber": "string",
        "parcels":[
                {
                "id": "string"
                }
        ]
}
```

400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.	N/A
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support	N/A

CSV Delivery Request:

TYPE	Endpoint	Description
POST	…/api/v1/delivery-requests:fromCsv	Create a delivery request from CSV

Parametars

N/A

Request body (example):

- type *Required string
- file *Requred string ($binary)

CSV Example (Delivery from a warehouse):
from_location,destination_location,customer_phone_number,customer_email,customer_full_name,number_of_parcels(default 1),payment_mode(cod, prepaid - default),amount_to_be_collected(default 0.00),price_currency(default EUR) 1,2,+385 91 4 655 1234,someone@example.com,Marko Horvat,3,cod,24.00,EUR

CSV Example (Delivery from AnyAPM):
destination_location,parcel_size,customer_phone_number,customer_email,customer_full_name,number_of_parcels(default 1),payment_mode(cod, prepaid - default),amount_to_be_collected(default 0.00),price_currency(default EUR) 2,1,+30 21 4 655 1234,someone@example.com,Marko Horvat,3,cod,24.00,EUR

Responses:

Code	Description	Example Value
200	OK	Below

```
{
        "id": "string",
        "destination":[
                {
                "contactName": "string"
                }
        ]
        "parcels":[
                {
                "id": "string",
                "labelUrl":
https://www.w3.org/WAI/ER/tests/xhtml/testfiles/resources/pdf/dummy.pdf
                }
        ]

}
```

400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.	N/A
403	Account disabled. Your account had been disabled, contact support	N/A

Return Delivery Request:

TYPE	Endpoint	Description
POST	…/api/v1/delivery-requests:customerReturns	Create a request delivery of parcel that customer would like to return

Parameters:

N/A

Request body (example):

```
{
  "orderNumber": "123456",
  "invoiceValue": "0.00",
  "paymentMode": "prepaid",
  "amountToBeCollected": "0.00",
  "allowReturn": true,
  "sender": {
    "contactPhoneNumber": "+385 99 1234 123",
    "contactEmail": "Ivan.Ivanic@mail.hr",
    "contactName": "Ivan Ivanic",
    "locationId": "2"
  },
  "destination": {
    "locationId": "1234"
  },
  "items": [
    {
      "id": "123456789",
      "name": "Test",
      "value": "0.00"
    }
  ]
}
```

Responses:

Code	Description	Example Value
200	OK	Below

```
{
        "id": "string",
        "orderNumber": "12309284"
        "labels":[
                {
                "type": "pdf",
                "mimetype": "application/pdf",
                "url":   https://www.w3.org/WAI/ER/tests/xhtml/testfiles/resources/pdf/dummy.pdf
                }
        ]
        "parcels":[
                {
                "id": "string",
                "labelUrl":  [
                {
                        "type": "pdf",
                        "mimetype": "application/pdf",
                        "url":
https://www.w3.org/WAI/ER/tests/xhtml/testfiles/resources/pdf/dummy.pdf
                }
]
                }
        ]

}
```

400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the	N/A

	request before sending it again.	
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support	N/A

Adress Delivery Request:

TYPE	Endpoint	Description
POST	…/api/v2/delivery-requests:checkAdressDelivery	Check if address for delivery is available

Parameters:

N/A

Request body (example):

```
{
        “city” : “string”,
        “street” : “string”,
        “postalCode” : “string”,
        “radius” : number,
        “compartmentSize”: 1/2/3,
        “region”: “hr-HR”
}
```

Code	Description	Example Value
200	OK	Below

```
{
“data”: [
                {
                "id": "string",
                "type": "apm",
                "image": "https://via.placeholder.com/150",
                "lat": "45.79359675448525",
                "lng": "15.928399281607227",
                "title": "Ulica Marice Barić 6, Zagreb",
                "name": "BOX NOW sjedište",
                "postalCode": "10000",
                "country": "HR",
                "note": "Paketomat se nalazi ispred BOX NOW sjedišta/depoa.",
                "addressLine1": "Ulica Marice Barić 6",
                "addressLine2": "string",
                "region": "hr-HR"
```

`}`
`]`
`}`		

400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.	N/A
402	Location error. No location can be found for the request	N/A
503	Service Unavailable	N/A

Update Delivery Request:

TYPE	Endpoint	Description
PUT	…/api/v1/delivery-requests:{orderNumber}	Update a created delivery request

Parametars:

Name	Type	Description	Example
orderNumber*	string	Unique order number in Your system. The same you use to create the delivery request	N/A

*Required value

You can only update “allowReturn” variable

Request body (example):

```
{
        “allowReturn”: true/false
}
```

Responses:

Code	Description	Example Value
200	OK	Below

{
“id”: “string”,
}		

400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.	N/A
402	Location error. No location can be found for the request	N/A
404	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.	N/A

Labels

Single Shipping Label:

TYPE	Endpoint	Description
GET	… /api/v1/parcels/{id}/label.{type}	Get printable label for parcel.

Parametars:

Name	Type	Description	Example
Id*	string	Unique parcel ID. You have received parcel ID after a successful delivery request creation or you can list all parcels, see /parcels	Unique 10-digit parcel ID. Example: 1234567890
type*	string	The output format of the file you want your shipping label	Available values: .pdf, .zpl
dpi	number	Only applies to .zpl (Zebra Printing Language). 200 or 300 supported.	Available values: 200, 300 Default value: 200

*Required value

Request body (example):

N/A

Responses:

Code	Description	Example Value
200	OK	Below
string		
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support.	N/A
404	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.	N/A

Multipe Shipping Label:

TYPE	Endpoint	Description
GET	… /api/v1/parcels/{id}/label.{type}	Get printable label for parcel.

Parametars:

Name	Type	Description	Example
orderNumber*	string	Unique order number in Your system. The same you use to create the delivery request.	N/A
type*	string	The output format of the file you want your shipping label	Available values: .pdf, .zpl
dpi	number	Only applies to .zpl (Zebra Printing Language). 200 or 300 supported.	Available values: 200, 300 Default value: 200

*Required value

Request body (example):

N/A

Responses:

Code	Description	Example Value
200	OK	Below
string		
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize	N/A

	Auth session with invalid data.	
403	Account disabled. Your account had been disabled, contact support.	N/A
404	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.	N/A

Parcels

Confirm AnyAPM Parcel Delivery:

TYPE	Endpoint	Description
POST	…/api/v1/parcels/{id}:confirm-anyapm-delivery	Confirm parcel has been delivered to AnyAPM

Parametars:

Name	Type	Description	Example
Id*	string	Unique parcel ID. You have received parcel ID after a successful delivery request creation or you can list all parcels, see /parcels	Unique 10-digit parcel ID. Example: 1234567890

*Required value

Request body (example):

N/A

Responses:

Code	Description	Example Value
200	OK	N/A
400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again.	N/A

401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support.	N/A
404	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.	N/A
503	Service Unavailable	N/A

Cancel Parcel:

TYPE	Endpoint	Description
POST	…/api/v1/parcels/{id}:cance	Cancel parcel delivery

NOTE: Cancelling a cancelled parcel has no effect.

Parametars:

Name	Type	Description	Example
Id*	string	Unique parcel ID. You have received parcel ID after a successful delivery request creation or you can list all parcels, see /parcels	Unique 10-digit parcel ID. Example: 1234567890

*Required value

Request body (example):

N/A

Responses:

Code	Description	Example Value
200	OK	N/A
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data.	N/A
403	Account disabled. Your account had been disabled, contact support.	N/A
404	Resource not found. You are authorized but the requested resource does not exist. Make sure the requested URL is correct.	N/A

Parcel Information:

TYPE	Endpoint	Description
GET	… /api/v1/parcels	List all parcel info related to your delivery requests

Parametars:

Name	Type	Description	Example
q	string	Search in: Order ID, Parcel ID, Customer name, Customer email, Customer phone number	N/A
limit	number	Page size	24 Default Value: 50
orderNumber	string	Order number in your system. Return only parcels related to this order number	N/A
parcelId	string	ID of the parcel in our system. Return only parcel/s with this ID.	N/A
paymentState	string	The payment state of a parcel	Available values: pending, paid-by-customer, transferredto-partner
paymentMode	string	The payment method selected for the parce	Available values: prepaid, cod Default value: prepaid
state	array [string]	The state of the parcel during the whole process.	Available values: new, intransit, expired-return, returned, in-final-destination, delivered, wait-for-load, lost, cancelled, missing
pageToken	string	Set this token to return records for given page. You get this for each response.	N/A

Request body (example):

N/A

Responses:

Code	Description	Example Value
200	OK	Below


```
{
"pagination": {
        "first": "string",
        "last": "string",
        "next": "string",
        "prev": "string"
},
"count": 0,
"data": [
{
        "id": "string",
        "state": "waiting-for-pickup",
        "deliveryRequest": {
                "typeOfService": "same-day",
                "codeOfDescription": "string",
                "orderNumber": "string",
                "invoiceValue": "string",
                "paymentMode": "prepaid",
                "amountToBeCollected": "string",
                "allowReturn": false,
                "notifyOnAccepted": "partner@example.com",
        "origin": {
                "locationId": "string"
        },
        "destination": {
                "locationId": "string"
        },
        "items": [
                {
                "id": "string",
                "name": "string",
                "code": "string",
                "status": "string",
                "value": "3.45",
                "weight": 0,
```

```
                "length": 0,
                "height": 0,
                "width": 0,
                "compartmentSize": 0
                }
        ]
        }
}
]
}
```


400	Bad Request. The server cannot or will not process the request due to something that is perceived to be your error (e.g., malformed request syntax, invalid request message). You are to modify the request before sending it again	N/A
401	Not Authorized. You are either using an expired Access token to access the data or trying to initialize Auth session with invalid data	N/A
403	Account disabled. Your account had been disabled, contact support.	N/A

NOTE: The aforementioned “state“ parameter refers to the status of a parcel in a given timeframe. Following are the definitions of each parcel type event (state):

- new - Parcel has been registered in the system
- delivered - Parcel has been delivered
- expired-return - Parcel expired and will be returned to the sender
- returned - Parcel has been returned to the sender
- in-transit - Parcel is being transferred to a specific location
- in-depot - Parcel is in one of our warehouses
- in-final-destination - Parcel has reached its final destination, waiting for pickup
- cancelled - Parcel order had been canceled by the sender
- wait-for-load - Parcel is waiting in a specific APM to be taken over by BOX NOW courier for either to be returned to the sender or transferred to another APM.
- accepted-for-return - Parcel has been accepted from customer and will be returned to the sender
- missing - BOX NOW pickup courier was unable to obtain the parcel for pickup

Delivery Partners

TYPE	Endpoint	Description
GET	… /api/v1/ delivery-partners	List of available delivery partners

Parameters:
N/A

Request body (example):
N/A

Responses:

Code	Description	Example Value
200	OK	Below

```
{
        "data": [
                {
                "id": "string",
                "name": "string"
                }
        ]
}
```

403	Account disabled. Your account had been disabled, contact support.	N/A