

Copyright
by
Chenyu Tian
2025

The Dissertation Committee for Chenyu Tian
certifies that this is the approved version of the following dissertation:

Simulation of partial melting material

Committee:

Todd Arbogast, Supervisor

Marc Hesse, Co-supervisor

Omar Ghattas

Patric Heimbach

Thorsten Becker

Simulation of partial melting material

by
Chenyu Tian

Dissertation

Presented to the Faculty of the Graduate School of
The University of Texas at Austin
in Partial Fulfillment
of the Requirements
for the Degree of

Doctor of Philosophy

The University of Texas at Austin
May 2025

Dedication

To all future Longhorn graduate students.

Epigraph

What starts here changes the world.

—University of Texas at Austin

Acknowledgments

Thanks to the previous authors of this template, and to the Graduate School for providing it.

Preface

Readers, this document represents a great deal of time and effort. Enjoy.
Cheers, Chenyu Tian.

Abstract

Simulation of partial melting material

Chenyu Tian, PhD
The University of Texas at Austin, 2025

SUPERVISORS: Todd Arbogast, Marc Hesse

Table of Contents

List of Tables	10
List of Figures	11
Chapter 1: Governing Equations	12
1.1 Mechanics of Mantle Dynamics	12
1.1.1 Scaled variables	14
1.2 Conservation of Chemical Species and Energy	15
1.2.1 Effective Velocity	17
1.3 Eutectic Phase Behavior	18
1.3.1 Eutectic Phase Parameters	18
1.3.2 Eutectic Phase Split	19
1.4 Nondimensionalization	22
Chapter 2: numerics	24
2.1 The Mixed Finite Element Method	24
2.1.1 Sub Stokes Problem	24
2.1.2 Sub Darcy Problem	24
2.1.3 Coupled Degenerate System	24
2.1.4 Degenerate Saddle Point Problem	24
2.2 The Multi-level Weighted Essentially Non-Oscillatory (ML-WENO) Method	25
2.2.1 Stencil Polynomial	25
2.2.2 Stencil polynomial smoothness indicators	26
2.2.3 ML-WENO weighting	27
2.2.4 Boundary Treatment	27
2.2.5 Time Stepping	27
Works Cited	28

List of Tables

1.1 Parameters Table 23

List of Figures

1.1	An representative volume element (RVE).	16
1.2	Linear Eutectic Phase Splitting.	20
2.1	An example of (3,2,1) multi-level stencils combination on logically rectangular quadrilateral mesh.	27

Chapter 1: Governing Equations in Mantle Dynamics

1.1 Mechanics of Mantle Dynamics

Fluid dynamics of the mixture of two phase flow has been extensively discussed. We will discuss the three governing equations of mass and momentum referring to the similar discussion in Drew and Segel (1971), McKenzie (1984) and Katz (2022). Considering a conservation equation for given volumetric variable γ in a representative volume element V ,

$$\frac{d}{dt} \int_V \gamma d\mathbf{v} = - \int_{\partial V} \mathbf{f} \cdot d\boldsymbol{\sigma} + \int_V S d\mathbf{v}, \quad (1.1)$$

where $\mathbf{f}$ represents flux travelling across the boundary of a representative volume element V . The minus sign indicates that the positive direction aligns with normal unit vector pointing outwards. S , source/sink term, represents the volumetric production rate of γ . We can apply Gauss's theorem to obtain differential form,

$$\frac{\partial \gamma}{\partial t} + \nabla \cdot \mathbf{f} = S. \quad (1.2)$$

We also define the quantity of phase fraction rigorously with the help of an indicator function admitting that multiple phase cannot coexist at the same spatial point, which are regarded as immiscible phases. We define indicator function,

$$i(\mathbf{x}) = \begin{cases} 1 & \text{phase}_i, \\ 0 & \text{not phase}_i. \end{cases} \quad (1.3)$$

We then define macroscopic phase fraction function with the help of (1.3),

$$\phi_i = \frac{1}{\delta \mathbf{v}} \int_{\delta \mathbf{v}} i(\mathbf{x}) d\mathbf{v}. \quad (1.4)$$

In the beginning of my discussion, I will discuss two immiscible phases liquid magma and solid mantle. Phase fraction of liquid magma is labelled as ϕ_l and phase fraction of solid mantle is labelled as ϕ_s , where $\phi_l + \phi_s = 1$ is always attained. Phase fraction

can also be regarded as volume fraction in macroscopic sense. Substituting bulk density $\bar{\rho} = \phi_l \rho_l + \phi_s \rho_s$ for generalized volumetric variable γ in equation (1.1), we can obtain conservation law for bulk mass,

$$\frac{\partial \bar{\rho}}{\partial t} + \nabla \cdot \bar{\rho} \mathbf{v} = 0, \quad (1.5)$$

with the help of Boussinesq approximation ignoring compressibility of each individual phase, and extend Boussinesq approximation further applying to density difference between each phase except body force term. We can write continuous function for two phase mixture simply as,

$$\nabla \cdot \bar{\mathbf{v}} = 0. \quad (1.6)$$

Substituting phase averaged momentum $\bar{\rho} \bar{\mathbf{v}}$, we then write conservation of momentum with phase averaged term,

$$\frac{\partial \bar{\rho} \bar{\mathbf{v}}}{\partial t} + \nabla \cdot \bar{\rho} \mathbf{v} \otimes \bar{\mathbf{v}} = \bar{\rho} \mathbf{g} + \nabla \cdot \bar{\boldsymbol{\tau}} - \nabla \bar{P}, \quad (1.7)$$

where $\boldsymbol{\tau}$ represents deviatoric stress. Ignoring change of inertia term due to near zero Reynolds number in magma and mantle,

$$\bar{\rho} \mathbf{g} + \nabla \cdot \bar{\boldsymbol{\tau}} - \nabla \bar{P} = 0, \quad (1.8)$$

which represents the bulk conservation of momentum. We now take a closer look at the interphase force between solid and liquid phases. We will align governing equation of liquid flow through porous solid mantle with classic Darcy's law with the help of mixture theory Bowen (1980). We first assume balanced stress across the interface between solid and liquid phases.

Combining equations, I finally arrive with the full flow mechanical system,

$$\phi_l (\mathbf{v}_l - \mathbf{v}_s) + \frac{k_{\phi_l}}{\mu_l} \nabla (p_l - p_f \mathbf{g}) = 0, \quad (1.9)$$

$$\nabla \cdot (\phi_l \mathbf{v}_l + \phi_s \mathbf{v}_s) = 0, \quad (1.10)$$

$$\nabla \bar{p} - \nabla \cdot \boldsymbol{\tau}(\mathbf{v}_s) = (\rho_s - \rho_l) \mathbf{g}, \quad (1.11)$$

$$\mu_s \nabla \cdot \mathbf{v}_s - \phi_l (p_l - p_s) = 0, \quad (1.12)$$

where the deviatoric stress of the mixture is

$$\tau(\mathbf{v}_s) = 2\mu_s\phi_s(\mathcal{D}\mathbf{v}_s - \frac{1}{3}\nabla \cdot \mathbf{v}_s\mathbf{I}), \quad (1.13)$$

and $\mathcal{D}\mathbf{v}_s = \frac{1}{2}(\nabla\mathbf{v}_s + \nabla\mathbf{v}_s^T)$ is the symmetric gradient. Moreover, the relative permeability is $k_{\phi_l} = k_0\phi_l^{2+2\Theta}$, where $\Theta \in [0, 1/2]$. μ_s and μ_l are dynamic viscosities for solid and liquid correspondingly.

1.1.1 Scaled variables

The Darcy part will mathematically degenerate in regions where the porosity is zero. To handle this issue, we use the formulation developed previously Arbogast et al. (2017). We first define pressure potentials as,

$$q_l = p_l - \rho_l g z \quad \text{and} \quad q_s = p_s - \rho_l g z, \quad (1.14)$$

where $g = |\mathbf{g}|$ and z is the depth, so $\mathbf{g} = g\nabla z$. Note that ρ_f is used to define both potentials, so that with $q = \bar{q} = \bar{p} - \rho_l g z$,

$$p_l - p_s = q_l - q_s = \frac{1}{1 - \phi_l}(q_l - q).$$

We can then rewrite the system (1.9)–(1.12) omitting the subscript of liquid volumetric fraction,

$$\phi\mathbf{v}_r + \frac{k_0\phi^{2+2\Theta}}{\mu_l}\nabla q_l = 0, \quad (1.15)$$

$$\mu_s\nabla \cdot (\phi\mathbf{v}_r) + \frac{\phi}{1 - \phi}(q_l - q) = 0, \quad (1.16)$$

$$\nabla q - \nabla \cdot \tau(\mathbf{v}_s) = -(1 - \phi)\rho_r\mathbf{g}, \quad (1.17)$$

$$\mu_s\nabla \cdot \mathbf{v}_s - \frac{\phi}{1 - \phi}(q_l - q) = 0. \quad (1.18)$$

where relative velocity $\mathbf{v}_r = \mathbf{v}_l - \mathbf{v}_s$ and density difference $\rho_r = \rho_s - \rho_l$. We refer to ϕ as porosity in the later text. Scaled variables are defined,

$$\tilde{\mathbf{v}}_r = \phi^{-\Theta}\mathbf{v}_r \quad \text{and} \quad \tilde{q}_l = \phi^{1/2}q_l, \quad (1.19)$$

and the problem is reformulated as

$$\tilde{\mathbf{v}}_r + \frac{k_0 \phi^{1+\Theta}}{\mu_f} \nabla (\phi^{-1/2} \tilde{q}_l) = 0, \quad (1.20)$$

$$\mu_s \phi^{-1/2} \nabla \cdot (\phi^{1+\Theta} \tilde{\mathbf{v}}_r) + \frac{1}{1-\phi} (\tilde{q}_l - \phi^{1/2} q) = 0, \quad (1.21)$$

$$\nabla q - \nabla \cdot \tau(\mathbf{v}_s) = -(1-\phi) \rho_r \mathbf{g}, \quad (1.22)$$

$$\mu_s \nabla \cdot \mathbf{v}_s - \frac{\phi^{1/2}}{1-\phi} (\tilde{q}_l - \phi^{1/2} q) = 0. \quad (1.23)$$

Where the new scaled relative velocity maintain numerical stability in zero porosity region.

1.2 Conservation of Chemical Species and Energy

Chemical compositions of mantle and magma is very complicate and very hard to trace at the same time. We simplify the model to a two-phase system with two species. We negelect detailed description of chemical reaction process and effect on the Gibbs free energies. Similar discussion can be found in extensive literatures like Spiegelman and Elliott (1993), Hewitt and Fowler (2008), Katz (2008) and Hesse et al. (2022). Both two species can be solid or liquid. Two species are immiscible as solid but miscible as liquid. I consider a homogenous density ρ_s for solid phase and ρ_l for liquid phase. With extened Boussinesq approximation later assuming no density difference except in body force term, we can make further assumption that $\rho_l = \rho_s = \rho$ Within the representative volume element V , $\gamma_{i,j}$ represents one quantity of the specie i presenting in phase j , where $i \in 1, 2$ and $j \in \{s, l\}$. The mass fraction $c_{i,j}$ of a given specie i in phase j is often regarded as concentration. Hence, we can write transport equations for a individual specie i assuming a pseudo melting term Γ_i ,

$$\frac{\partial}{\partial t} (\phi_l \rho_l c_{i,l}) + \nabla \cdot (\phi_l \rho_l c_{i,l} \mathbf{v}_l - \phi_l \rho_l \mathcal{D}_{i,l} \nabla c_{i,l}) = \Gamma_i, \quad (1.24)$$

$$\frac{\partial}{\partial t} (\phi_s \rho_s c_{i,s}) + \nabla \cdot (\phi_s \rho_s c_{i,s} \mathbf{v}_s - \phi_s \rho_s \mathcal{D}_{i,s} \nabla c_{i,s}) = -\Gamma_i, \quad (1.25)$$




Figure 1.1: An representative volume element (RVE).

where we can safely get rid of dissuion term in solid phase. Summing up equation1.24 and equation1.25, we can write a advection-diffusion equation in phase averaged volumetric bulk variable,

$$\frac{\partial \overline{\rho c_i}}{\partial t} + \nabla \cdot (\overline{\rho c_i \mathbf{v}} - \phi_l \rho_l \mathcal{D}_{i,l} \nabla c_{i,l}) = 0, \quad (1.26)$$

where the phase averaged volumetric bulk variable are defined as $\overline{\rho c_i} = \sum_{j \in \{s,l\}} \phi_j \rho_j c_{i,j}$ and $\overline{\rho c_i \mathbf{v}} = \sum_{j \in \{s,l\}} \phi_j \rho_j c_{i,j} \mathbf{v}_j$. The subscript i will be omitted since only one chemical specie is traced in this two-component system. Extending Boussinessq approximation $\rho_l = \rho_s = \bar{\rho}$, the specie transport equation can be simplified as,

$$\frac{\partial \bar{c}}{\partial t} + \nabla \cdot (\bar{c} \mathbf{v} - \phi_l \mathcal{D}_l \nabla c_l) = 0. \quad (1.27)$$

We write energy balance equation in the phase-averaged internal energy form first,

$$\frac{\partial \overline{\rho u}}{\partial t} + \nabla \cdot \overline{\rho u \mathbf{v}} - \nabla \cdot \overline{K \nabla T} = \overline{\rho \mathcal{Q}} + \nabla \cdot \overline{\boldsymbol{\sigma} \cdot \mathbf{v}} + \overline{\rho \mathbf{v}} \cdot \mathbf{g}. \quad (1.28)$$

On the left hand side, we have time dependent rate of internal energy chage, advection term and diffusion term. On the right hand side, we have heating/cooling source $\mathcal{Q}$, work exerted by stress and work againt gravity g . In a thermochemical equilibrium scenerio, we are replacing internal energy with enthalpy. We can write energy balancing equation neglecting additional heating/cooling term $\mathcal{Q}$ and dissipative heating following the discussion in McKenzie (1984),

$$\frac{\partial \overline{\rho h}}{\partial t} + \rho c_p \nabla \cdot \overline{\mathbf{v}} T = \rho L \nabla \cdot \phi_s \mathbf{v}_s + \overline{K \nabla^2 T} + \rho \alpha_\rho T \overline{\mathbf{v}} \cdot \mathbf{g}, \quad (1.29)$$

where specific heat capacity c_p is used for both components in solid and liquid phase. Similar but slighted altered form was also discussed in Katz (2008), where adiabatic cooling effect was added in terms of potential temperature McKenzie and Bickle (1988). We now divide ρc_p on both sides of the equation considering Boussinesq approximation,

$$\frac{\partial H}{\partial t} + \nabla \cdot \bar{\mathbf{v}} T = \frac{L}{c_p} \nabla \cdot \phi_s \mathbf{v}_s + \kappa \nabla^2 T + \frac{\alpha_\rho}{c_p} T \bar{\mathbf{v}} \cdot \mathbf{g}, \quad (1.30)$$

where $H = \bar{h}/c_p$ is the bulk specific enthalpy and $\kappa = \bar{K}/\rho c_p$ is the heat diffusivity.

1.2.1 Effective Velocity

Effective velocity in equilibrium transport for concentration within liquid phase is discussed in Spiegelman (1996). We also introduce our effective velocity, but instead of transporting concentration in liquid(magma), we transport bulk concentration. Define partition coefficient $D_i = c_{i,s}/c_{i,f}$ and

$$(\phi_l + \phi_s D_i) c_{i,l} = \bar{c}_i, \quad (1.31)$$

$$(\phi_l/D_i + \phi_s) c_{i,s} = \bar{c}_i. \quad (1.32)$$

Substitute $c_{i,l}$ and $c_{i,s}$ with equation (1.31) and equation (1.32) into bulk velocity $\bar{c}_i \bar{\mathbf{v}} = \phi_s \mathbf{v}_s c_{i,s} + \phi_l \mathbf{v}_l c_{i,l}$,

$$\bar{c}_i \bar{\mathbf{v}} = \phi_s \mathbf{v}_s c_{i,s} + \phi_l \mathbf{v}_l c_{i,l} = \left(\frac{\phi_l \mathbf{v}_l + D_i \phi_s \mathbf{v}_s}{\phi_l + \phi_s D_i} \right) \bar{c}_i. \quad (1.33)$$

Hence, we get the proper expression for the effective velocity as $\mathbf{v}_{\text{eff}} = \frac{\phi_l \mathbf{v}_l + D_i \phi_s \mathbf{v}_s}{\phi_l + \phi_s D_i}$, where the partition coefficient D can be obtained through phase behavior package. If there is no melting $\phi_l = 0$, we can reterive $\mathbf{v}_{\text{eff}} = \mathbf{v}_s$. If there is all melting $\phi_l = 1$, we can obtain $\mathbf{v}_{\text{eff}} = \mathbf{v}_l$. Hence, the definition of effective velocity is well defined in those two boundary scenerios. We rewrite the transport of specie with effective velocity,

$$\frac{\partial C}{\partial t} = \nabla \cdot (\mathbf{v}_{\text{eff}} C - \phi_l \mathcal{D}_l \nabla c_l), = 0 \quad (1.34)$$

where $C = \bar{c}$ represents volumetric phase averaged (bulk) concentration of species.

1.3 Eutectic Phase Behavior

The enthalpy method requires an explicit relationship between temperature and enthalpy. Embracing the fact that mid-ocean ridge forms at the place where temperature is generally lower, eutectic melting, where melting temperature is significantly lowered with the presence of the secondary specie, is a suitable model for modelling melting behavior at certain location. The binary eutectic phase behavior describes the chemical behavior of two immiscible crystals from a completely miscible solution. On a typical eutectic phase behavior diagram, we can locate any phase situation using transported enthalpy and concentration. Binary eutectic melting has been applied to water-salt-brine system in glacier Hesse et al. (2022).

1.3.1 Eutectic Phase Parameters

We approximate the melting temperature and eutectic temperature at a given pressure using Clausius-Clapeyron relationship,

$$\begin{aligned} T_m &= T_{m0} + \nu^{-1}P, \\ T_e &= T_{e0} + \nu^{-1}P, \end{aligned} \tag{1.35}$$

where ν is the Clausius-Clapeyron constant.

In a eutectic system, we use bulk mass fraction and bulk enthalpy to locate the current state of a given system. $\mathcal{X}_i$ represents bulk mass fraction of specie i and $\mathcal{X}_{i,e}$ represents eutectic mass fraction of specie i in liquid. The subscript i will be omitted in the later context since only one specie is being traced in transport equation. Some assumptions are made for partially molten mantle system.

- Assuming chemical equilibrium is achieved that phase state can be calculated with phase diagram.
- The composition of the second specie in the liquid formed by eutectic melting $\mathcal{X}_e$ is constant at given pressure $\mathcal{X}_e(P)$.

- Melting temperature T_m is constant at given pressure $T_m(P)$.
- Boussinesq approximation is extended to phase behavior as well. assuming $\rho_l = \rho_s$.
- Assuming no density difference between two solid components.
- Assuming constant thermal expansion and specific heat capacity

We can now relate bulk mass fraction with bulk concentration directly,

$$\mathcal{X} = \frac{\phi_l \rho_l c_l + \phi_s \rho_s c_s}{\phi_l \rho_l + \phi_s \rho_s} = \phi_l c_l + \phi_s c_s = C = \phi_2 + \phi_l c_l. \quad (1.36)$$

We relate bulk specific enthalpy with temperature and latent heat again.

$$H = T + \phi_l L / c_p. \quad (1.37)$$

We further rescale by dividing melting temperature $\Delta T = T_{m0} - T_{e0}$ at standard atmospheric pressure forming a dimensionless relationship,

$$\check{H} = \check{T} + \phi_l \check{L}, \quad (1.38)$$

where $\check{L} = \frac{L}{c_p \Delta T}$ is the dimensionless latent heat.

1.3.2 Eutectic Phase Split

For simplicity, we are now assuming a linear eutectic phase split between different phase regions. We can draw the eutectic phase diagram separating different phase regions with straight lines at a fixed pressure. We now describe all six phase regions depicting in the phase split diagram above,

I Single-phase sub-solidus : solid1

II Two-phase sub-solidus : solid1 + solid2

III Three-phase eutectic : solid1 + solid2 + melt




Figure 1.2: Linear Eutectic Phase Splitting.

IV Two-phase super-eutectic : solid1 + melt

V Two-phase super-eutectic : solid2 + melt

VI Single-phase super-liquidus : melt

In the following discussion, I will restrict all the discussion to a fixed pressure.

Region I. Pure component 1. There is no eutectic phase behavior in this region. The conditions to be in region I are

$$C = 0 \quad \check{H} \leq \check{T}_m, \quad (1.39)$$

and we can determine phase fraction, mass composition and current temperature,

$$\phi_1 = 1, \quad \phi_2 = \phi_l = 0 \quad \text{and} \quad \check{T} = \check{H}. \quad (1.40)$$

Region II. Sub-solidus: two components coexist as solid phase. In this phase region, temperature hasn't reached eutectic melting temperature. The conditions to be in region II are

$$C \neq 0 \quad \check{H} \leq \check{T}_e. \quad (1.41)$$

We can determine phase fraction, mass composition and current temperature,

$$\phi_2 = C \quad \phi_1 = 1 - \phi_2 \quad \phi_l = 0 \quad \text{and} \quad \check{T} = \check{H}. \quad (1.42)$$

Region III. Two-phase eutectic: The system starts melting at eutectic temperature. Both solid component 1 and component 2 and melt coexist at the same time. Temperature fixes until component 2 exhausts leaving eutectic melting. Mass composition of component 2 in the melt is also fixed as $\mathcal{X}_e$. The conditions to be in region III are We can determine phase fraction, mass composition and current temperature,

$$\phi_l = \frac{\check{H} - \check{T}_e}{\check{L}} \quad \phi_2 = C - \phi_l \mathcal{X}_e \quad \phi_1 = 1 - \phi_l - \phi_2 \quad \text{and} \quad \check{T} = \check{T}_e. \quad (1.43)$$

Region IV. Super-eutectic two phase region. All component 2 in solid has been exhausted. The mass composition of component 2 in liquid c_f is now approximated with a relation between mass fraction and temperature. Subscript indicating component 2 has been dropped since only one component is being tracked. We can determine phase fraction first,

$$\phi_2 = 0 \quad \phi_l = \frac{C}{c_l(\check{T})}. \quad (1.44)$$

The corresponding temperature should be determined by solving the following equation.

$$F(\check{T}) = \check{H} - \check{T} - \frac{C}{c_l(\check{T})} \check{L} = 0. \quad (1.45)$$

We can solve this nonlinear function with Newton iteration. However, we are approximating with a linear relationship $c_l = \mathcal{X}_e(\check{T}_m - \check{T})$ where $c_l > C$ is imposed for the fact that there is component 1 remaining as solid. Now we can solve a simple quadratic equation,

$$\check{T}^2 - (\check{H} + \check{T}_m)\check{T} + \check{T}_m\check{H} - CL/\mathcal{X}_e = 0. \quad (1.46)$$

Omitting the root that exceeding melting temperature,

$$\begin{aligned} \check{T} &= \frac{\check{H} + \check{T}_m - \sqrt{(\check{H} + \check{T}_m)^2 - 4(\check{T}_m\check{H} - CL/\mathcal{X}_e)}}{2} \\ &= \frac{\check{H} + \check{T}_m - \sqrt{(\check{H} - \check{T}_m)^2 + 4CL/\mathcal{X}_e}}{2} \end{aligned} \quad (1.47)$$

1.4 Nondimensionalization

Compaction and melting are two most important aspects in mantle dynamics. We nondimensionlize the scaled formulation with characteristic length scale related to compaction length and scaled characteristic Darcy speed of the melt,

$$l_0 = \left(\frac{k_0 \mu_s}{\mu_l} \right)^{1/2} \quad \text{and} \quad u_0 = \frac{k_0 \rho_r g}{\mu_l}. \quad (1.48)$$

We can derive corresponding characteristic time scale as $t_0 = l_0/u_0$, now we can write full set of dimensionless equations. We represent dimensionless variables with a $\checkmark$ mark,

$$\check{\mathbf{v}}_r + \phi^{1+\Theta} \nabla (\phi^{-1/2} \check{q}_l) = 0, \quad (1.49)$$

$$\phi^{-1/2} \nabla \cdot (\phi^{1+\Theta} \check{\mathbf{v}}_r) + \frac{1}{1-\phi} (\check{q}_l - \phi^{1/2} \check{q}) = 0, \quad (1.50)$$

$$\nabla \check{q} - \nabla \cdot \check{\tau}(\check{\mathbf{v}}_s) = -(1-\phi) \mathbf{n}, \quad (1.51)$$

$$\nabla \cdot \check{\mathbf{v}}_s - \frac{\phi^{1/2}}{1-\phi} (\check{q}_l - \phi^{1/2} \check{q}) = 0, \quad (1.52)$$

where dimensionless deviatoric stress of the mixture is $\check{\tau} = 2(1-\phi)(\mathcal{D}\check{\mathbf{v}}_s - 1/3 \nabla \cdot \check{\mathbf{v}}_s \mathbf{I})$ and $\mathbf{n}$ is the unit direction vector pointing downwards. Now we align transport equations with dimensionless variables defined in mechanic system,

$$\begin{aligned} \frac{\partial C}{\partial \check{t}} + \nabla \cdot (\check{\mathbf{v}}_{\text{eff}} C - \frac{\phi \mathcal{D}_l}{u_0 l_0} \nabla c_l) &= 0, \\ \frac{\partial \check{H}}{\partial \check{t}} + \nabla \cdot \check{\mathbf{v}} T - \check{L} \nabla \cdot \phi_s \check{\mathbf{v}}_s - \frac{\kappa}{u_0 l_0} \nabla^2 \check{T} - \frac{\alpha_\rho l_0}{c_p} \check{T} \check{\mathbf{v}} \cdot \mathbf{g} &= 0. \end{aligned} \quad (1.53)$$

Paramters used in the flow mechanics and thermaldynamic computations are listed in Table 1.1,

Quantity	Value	Units
ρ	3000	$kg \cdot m^{-3}$
ρ_r	600	$kg \cdot m^{-3}$
α_ρ	3×10^{-5}	K^{-1}
c_p	1200	$J \cdot kg^{-1} \cdot K^{-1}$
L	5×10^5	$J \cdot kg^{-1}$
μ_l	1	Pascal $\cdot s$
μ_s	10^{19}	Pascal $\cdot s$
k_0	10^{-8}	m^2
T_{e0}	1480	K
T_{m0}	2000	K
ν	6.5×10^6	Pascal $\cdot K^{-1}$

Table 1.1: Flow Mechanics and Thermodynamics Parameters

Chapter 2: Numerical Methods

I introduce a locally mass conserving numerical framework.

2.1 The Mixed Finite Element Method

2.1.1 Sub Stokes Problem

2.1.2 Sub Darcy Problem

2.1.3 Coupled Degenerate System

2.1.4 Degenerate Saddle Point Problem

The linear system corresponding to (insert eqcite) has the form

$$\begin{bmatrix} \mathbf{A}_s & -\mathbf{B}_s & \mathbf{0} & \mathbf{0} \\ \mathbf{B}_s^T & \mathbf{C}_s & \mathbf{0} & \mathbf{K} \\ \mathbf{0} & \mathbf{0} & \mathbf{A}_d & -\mathbf{B}_d \\ \mathbf{0} & \mathbf{K} & \mathbf{B}_d^T & \mathbf{C}_d \end{bmatrix} \begin{bmatrix} \mathbf{x}_s \\ \mathbf{y}_s \\ \mathbf{x}_d \\ \mathbf{y}_d \end{bmatrix} = \begin{bmatrix} \mathbf{f}_s \\ \mathbf{g}_s \\ \mathbf{f}_d \\ \mathbf{g}_d \end{bmatrix}, \quad (2.1)$$

wherein the solution represents the degrees of freedom of primary variables with respect to the bases of the finite element spaces. (Insert details of calculation of each blocked matrix). We form a double saddle point system by symmetrically permutate original linear system,

$$\begin{bmatrix} \mathbf{A}_s & \mathbf{0} & -\mathbf{B}_s & \mathbf{0} \\ \mathbf{0} & \mathbf{A}_d & \mathbf{0} & -\mathbf{B}_d \\ \mathbf{B}_s^T & \mathbf{0} & \mathbf{C}_s & \mathbf{K} \\ \mathbf{0} & \mathbf{B}_d^T & \mathbf{K} & \mathbf{C}_d \end{bmatrix} \begin{bmatrix} \mathbf{x}_s \\ \mathbf{x}_d \\ \mathbf{y}_s \\ \mathbf{y}_d \end{bmatrix} = \begin{bmatrix} \mathbf{f}_s \\ \mathbf{f}_d \\ \mathbf{g}_s \\ \mathbf{g}_d \end{bmatrix}. \quad (2.2)$$

We group these block matrix to form a concise version,

$$\mathbf{A} = \begin{bmatrix} \mathbf{A}_s & \mathbf{0} \\ \mathbf{0} & \mathbf{A}_d \end{bmatrix}, \quad \mathbf{B} = \begin{bmatrix} -\mathbf{B}_s & \mathbf{0} \\ \mathbf{0} & -\mathbf{B}_d \end{bmatrix}, \quad \mathbf{C} = \begin{bmatrix} -\mathbf{C}_s & -\mathbf{K} \\ -\mathbf{K} & -\mathbf{C}_d \end{bmatrix}, \quad \mathbf{F} = \begin{bmatrix} \mathbf{f}_s \\ \mathbf{f}_d \end{bmatrix}, \quad \mathbf{G} = \begin{bmatrix} -\mathbf{g}_s \\ -\mathbf{g}_d \end{bmatrix}, \quad (2.3)$$

$$\begin{bmatrix} \mathbf{A} & \mathbf{B} \\ \mathbf{B}^T & \mathbf{C} \end{bmatrix} \begin{bmatrix} \mathbf{x} \\ \mathbf{y} \end{bmatrix} = \begin{bmatrix} \mathbf{F} \\ \mathbf{G} \end{bmatrix}, \quad (2.4)$$

where $\mathbf{A}$ is a positive definite matrix. However, $\mathbf{B}$ is usually a singular matrix when no melting region presents. We will present a modified Uzawa iteration algorithm to

deal with this coupled degenerate singular system. Inexact Uzawa algorithm has been introduced in the previous literature Elman and Golub (1994) and James H. Bramble (1997),

Algorithm 1 Preconditioned Inexact Uzawa Iteration

- 1: Initialize $\mathbf{x}_0 = \mathbf{0}$ and $\mathbf{y}_0 = \mathbf{0}$
 - 2: Update $\mathbf{x}_{i+1} = \mathbf{x}_i + \mathbf{A}^{-1}(\mathbf{F} - (\mathbf{A}\mathbf{x}_i + \mathbf{B}\mathbf{y}_i))$
 - 3: Obtain $\mathbf{r} = \mathbf{B}^T \mathbf{x}_{i+1} + \mathbf{C}\mathbf{y}_i - \mathbf{G}$
 - 4: Obtain $\tilde{\mathbf{y}} = \operatorname{argmin}_{\mathbf{y} \in V} \|(\mathbf{B}^T \mathbf{A}^{-1} \mathbf{B} - \mathbf{C})^{-1} \tilde{\mathbf{y}} - \mathbf{r}\|$
 - 5: Update $\mathbf{y}_{i+1} = \mathbf{y}_i + \tilde{\mathbf{y}}$
-

2.2 The Multi-level Weighted Essentially Non-Oscillatory (ML-WENO) Method

We develop a accurate, versatile, robust and efficient finite volume weighted essentially non oscillatory (WENO) techniques for solving energy and composition conservation laws Arbogast et al. (2024).

2.2.1 Stencil Polynomial

Given a stencil $S = \{E_0, E_2, \dots, E_k\}$ of the quasiuniform logically rectangular mesh. We can define an associated tensor product stencil polynomial $Q_{s,t} \in \mathbb{Q}_{(s,t)} := \mathbb{P}_{s-1}(x) \otimes \mathbb{P}_{t-1}(y)$, where s and t equal to the stencil sizes in the x- and y-directions, respectively. We scale our stencil polynomial individually as

$$Q_{s,t} = \sum_{p < s, q < t} c_{p,q} \left(\frac{x - x_S}{h_S} \right)^p \left(\frac{y - y_S}{h_S} \right)^q, \quad (2.5)$$

where (x_S, y_S) is the center point of the stencil $\Omega_S = \cup_{E \in S} E \subset \mathbb{R}^2$, and $h_S = \sqrt{\sum_k E_k/k}$ is the diameter of average cell size. In finite volume scenerio, we are dealing with cell averaged value of the scalar transport variable

$$\bar{u}_E = \frac{1}{|E|} \int_E u(\mathbf{x}) d\mathbf{x} = \frac{1}{|E|} \int_E u(x, y) dx dy. \quad (2.6)$$

We can calculate coefficients $c_{p,q}$ by imposing a constraint that cell averaged value (2.6) is preserved through integral with stencil polynomial

$$\frac{1}{|E_k|} \int_{E_k} Q(\mathbf{x}) d\mathbf{x} = \bar{u}_{E_k}, \quad \forall E_k \in S. \quad (2.7)$$

I will replace $\bar{u}_{E_k}$ with $\bar{u}_k$ in the following discussion for simplicity.

We can represent stencil polynomial with basis polynomials $Q_{s,t} = \sum_k \bar{u}_k \phi_{s,t}^k$, where basis polynomials can be calculated as

$$\frac{1}{|E_{k'}|} \int_{E_{k'}} \phi_{s,t}^k(\mathbf{x}) d\mathbf{x} = \begin{cases} 1 & k' = k \\ 0 & k' \neq k \end{cases} \quad \forall (E_{k'}, E_k) \in S, \quad (2.8)$$

which would lead to a $(s \times t) \times (s \times t)$ non-singular linear system. We can define a linear projection operator π_S and let $\pi_S u_S = Q$ be a linear projection onto polynomial space W_p such that $Q_{s,t} \subset W_p$.

We can estimate interpolation error with the Bramble-Hilbert Lemma Dupont and Scott (1980) and Bramble and Hilbert (1970) in $H_r(\Omega)$ space, where $r = s$ in x direction and $r = t$ in y-direction.

Lemma 2.1. *Let Ω_S be the domain covered by stencil S in $\mathbb{R}^2$ and let $u \in H^r(\Omega_S)$.*

We have:

$$\|u - \pi_S u\|^2 \leq h^{2(r-1)} |u|_{H^r(\Omega_S)}^2. \quad (2.9)$$

Proof.

$$\|u - \pi_S u\| = \quad (2.10)$$

□

2.2.2 Stencil polynomial smoothness indicators

We can define a smoothness indicator σ as a measurement of smoothness of $u(\mathbf{x})$ on the stencil S . Jiang and Shu's method Jiang and Shu (1996) is defined by Sobolev seminorm:

$$\sigma_P = \sum_{1 \leq |\alpha| \leq m} \int \int_{E_0} |E_0|^{|\alpha|-1} (\mathcal{D}^\alpha Q(x, y))^2 dx dy \quad (2.11)$$

We proposed two alternative ways of defining smoothness indicator Huang et al. (2023). The smoothness indicator should exhibit following convergence property that there exists some value $C > 0$ such that $h \rightarrow 0^+$,

$$\sigma = \begin{cases} Ch^2 + \mathcal{O}(h^3) & \text{Smooth,} \\ \Theta(h) & \text{Not Smooth.} \end{cases} \quad (2.12)$$

2.2.3 ML-WENO weighting

Given a target cell $E_{i,j} \in \tau_h$, we can create a nonempty set of stencils $S_l \ni E_{i,j}, l = 0, 1, \dots, L$. Each stencil will




Figure 2.1: An example of (3,2,1) multi-level stencils combination on logically rectangular quadrilateral mesh.

2.2.4 Boundary Treatment

2.2.5 Time Stepping

Works Cited

T. Arbogast, M. A. Hesse, and A. L. Taicher. Mixed methods for two-phase Darcy-Stokes mixtures of partially melted materials with regions of zero porosity. *SIAM J. Sci. Comput.*, 39(2):B375–B402, 2017. DOI 10.1137/16M1091095.

Todd Arbogast, Chieh-Sen Huang, and Chenyu Tian. A finite volume multilevel weno scheme for multidimensional scalar conservation laws. *Comput. Methods Appl. Mech. Engrg.*, 421, 2024.

Ray Bowen. Incompressible porous media models by use of the theory of mixtures. *Int. J. Engng Sci.*, 18:1129–1148, 1980.

J.H. Bramble and S. R. Hilbert. Estimation of linear functionals on sobolev spaces with application to fourier transform and spline interpolation. *SIAM J. Numer. Anal.*, 7(1):112–124, 1970. doi: 10.1137/0707006.

Donald Drew and Lee Segel. Averaged equations for two-phase flows. *Studies in Applied Mathematics*, page 3, 1971.

Todd Dupont and Ridgway Scott. Polynomial approximation of functions in sobolev spaces. *Mathematics of Computation*, 34(150):441–463, 1980.

Howard C. Elman and Gene H. Golub. Inexact and preconditioned uzawa algorithms for saddle point problems. *SIAM. J. Numer. Anal.*, 31:1645–1661, 1994.

Marc Hesse, Jacob Jordan, Steve Vance, and Apurva Oza. Supporting information for ”downward oxidant transport through europa’s ice shell by density-driven brine percolation”. *Geophysical Research Letters*, 2022.

I.J Hewitt and A.C Fowler. Partial melting in an upwelling mantle column. *Proc. R. Soc. A*, 464:2467–2491, 2008.

Chieh-Sen Huang, Todd Arbogast, and Chenyu Tian. Multidimensional weno-ao reconstructions using a simplified smoothness indicator and applications to conservation laws. *J. Sci. Comput.*, 97, 2023.

Apostol T. Vassilev James H. Bramble, Joseph E. Pasciak. Analysis of the inexact uzawa algorithm for saddle point problems. *SIAM. J. Numer. Anal.*, 34:1072–1092, 1997.

Guang-Shan Jiang and Chi-Wang Shu. Efficient implementation of weighted eno schemes. *J. Comput. Phys.*, 126:202–228, 1996.

Richard F. Katz. Magma dynamics with the enthalpy method: Benchmark solutions and magmatic focusing at mid-ocean ridges. *Journal of Petrology*, 49: 2099–2121, 2008.

Richard F. Katz. *The Dynamics of Partially Molten Rock*. Princeton University Press, 1st edition, 2022. ISBN 9780691232645.

Dan Mckenzie. The generation and compaction of partially molten rock. *Journal of Petrology*, 25:713–765, 1984.

Dan Mckenzie and Mike J. Bickle. The volume and composition of melt generated by extension of the lithosphere. *Journal of Petrology*, 29:625–679, 1988.

Marc Spiegelman. Geochemical consequences of melt transport in 2-d: The sensitivity of trace elements to mantle dynamics. *Earth and Planetary Science Letters*, pages 115–132, 1996.

Marc Spiegelman and Tim Elliott. Consequences of melt transport for uranium series disequilibrium in young lavas. *Earth and Planetary Science Letters*, 118: 1–20, 1993.