

Chapter 1: Coupled Simulation

Now we couple locally mass conserved MFEM and FVM method together in this chapter and perform coupled numerical simulation for partially molten mantle. We discuss implementation details and coupling strategy combining MFEM, FVM and eutectic phase package. The remaining uncertainty of porosity ϕ will be fulfilled by phase package evaluation. Before we throw ourselves into the fully coupled problem. We test another porosity evolution scenario with a more straightforward prescribed melting. Then we will show an example combining MFEM, FVM and eutectic phase package altogether and perform coupled computation. We start with pseudo 1D scenarios and then proceed to perform full 2D simulation.

1.1 Coupled Algorithm

Let $\mathcal{U}^n = (C^n, H^n)$ be the cell-averaged solution to the transport system (??) at time t^n . Let $\mathcal{V}^n = (\check{\mathbf{v}}_r^n, \check{\mathbf{v}}_s^n, \check{q}_l^n, \check{q}_s^n)$ denote the solution to the Darcy-Stokes system at the same time step t^n . Moreover, let $\mathcal{W}^n = (\phi^n, \phi_1^n, \check{T}^n, c_s^n, c_l^n)$ denote the output of the phase calculation at t^n given the transport result U^n .

For each time step t^n , we reconstruct dimensionless mass composition and enthalpy from the cell-averaged solution $\mathcal{U}^n$ with ML-WENO reconstruction at each data points. The eutectic phase package gives corresponding phase parameters $\mathcal{W}^n$ according to these point wise values. Once we know $\mathcal{W}^n$, we solve a fixed in time Darcy-Stokes system at this time step t^n for $\mathcal{V}^n$. The cell-averaged solution $\mathcal{U}^{n+1}$ of the next time step t^{n+1} is then obtained by forward marching the system explicitly. We formally formulate an overall explicit coupled solver as shown in algorithm 1.

Algorithm 1 Sequential Coupled Solver

Let U^0 be given as initial data.

- 1: Initialize $\mathcal{U}^0$, compute $\mathcal{W}^0$ with eutectic phase package.
- 2: Compute ϕ^0 in $\mathcal{W}^0$, solve the Darcy-Stokes system (??)–(??) for $\mathcal{V}^0$.
- 3: **for** Time level $n = 1, 2, \dots, n_{\max} - 1$ **do**
- 4: Given $\mathcal{U}^n$, compute $\mathcal{W}^n$ by the eutectic phase package.
- 5: Compute ϕ^n in $\mathcal{W}^n$, solve the Darcy-Stokes system (??)–(??) for $\mathcal{V}^{n+1}$.
- 6: Given $\mathcal{W}^n$ and $\mathcal{V}^{n+1}$, compute dimensionless effective velocity (??) and phase averaged velocity as

$$\check{\mathbf{v}}_{\text{eff}} = \frac{\phi \check{\mathbf{v}}_l + D_i(1 - \phi) \check{\mathbf{v}}_s}{\phi + (1 - \phi)D_i}, \quad \check{\mathbf{v}} = \phi \check{\mathbf{v}}_r + \check{\mathbf{v}}_s.$$

- 7: Explicitly marching forward the transport system (??) to next time $n + 1$ for $\mathcal{U}^{n+1}$.

- 8: **end for**
-

1.1.1 Discontinuous Porosity

Due to the presence of no melt regions and different phase regions, we may obtain different reconstructed values of dimensionless enthalpy and mass concentration from two sides of an edge shared by two elements and thus two different calculated porosities. However, it is crucial to have one compatible and appropriate porosity value used on the element edge in the conforming MFEM scheme.

Therefore, we evaluate the geometric average of the two values of porosity ϕ_e^+ and ϕ_e^- at each quadrature points on both sides of an element edge e as

$$\bar{\phi}_e = \frac{2\phi_e^+\phi_e^-}{\phi_e^+ + \phi_e^-}, \tag{1.1}$$

where ϕ_e^+ and ϕ_e^- are porosity evaluated from two sides of the element edge e . The geometric averaged porosity $\bar{\phi}_e$ is required for the continuous compaction equation in Darcy equation (??) , where face integral is replaced with edge integral through divergence theorem. When the porosity on one side equal zero, the geometric average

of the porosity equals zero as well, which highlights the fact that there is no liquid flow should travel through this edge.

1.1.2 Compaction Length

The concept of compaction length was first proposed by ?. The phenomenon of compaction is due to the pressure difference between phases, which is commonly parametrized by bulk viscosity $\zeta \sim \frac{\eta}{\phi}$.

1.1.3 Some Simplifications

We solve a simplified equation for the following sections.

- lithostatic pressure.
- Ommiting diffusion term for now.

1.2 Pseudo One-Dimensional Column Tests

In this section, we first test our coupled algorithm on a 2D $M \times N$ grid with a pseudo-1D column problem. We test two different scenarios, one couples MFEM and FVM solver without phase computation but with a simple prescribed melting function $\Gamma(\mathbf{x})$ instead. The other one exhibits a fully coupled scenario where phase transition and porosity evolution present. For the two tests presented below, we fix mesh resolution as $M = 2$ and $N = 100$. We fix the parameter $\Theta = 0$ as well.

1.2.1 One-Dimensional Stencils

In the following pseudo-1D problems, we employ a set of one-dimensional ML-WENO(3,2) stencils as shown in Figure 1.1.




Figure 1.1: An exhibition of a set of 1D ML-WENO (3,2) stencils on a rectangular mesh.

1.2.2 Prescribed Melting Case

Before coupling mechanical, transport and phase package altogether into one full computation, we illustrate a simpler model coupling MFEM and FVM solver without involving phase package. Instead of using phase package computation to decide porosity distribution, we prescribe the melting rate or the change of porosity as a fixed source function distributed in space as

$$\phi(t) = \Gamma(\mathbf{x}). \quad (1.2)$$

We write conservation of liquid mass with the prescribed melting term Γ (1.2) as

$$\frac{\partial \phi}{\partial t} + \nabla \cdot (\phi \mathbf{v}_l) = \Gamma, \quad (1.3)$$

where the diffusion term is being dropped for simplicity in this case.

We prescribe the following boundary conditions for MFEM and FVM solver respectively. For the Darcy-Stokes MFEM solver:

- Bottom Edge $y = -H$;
 - Normal Stokes velocity and supplemental edge averaged flux are prescribed with essential boundary conditions:

$$\check{\mathbf{v}}_s \cdot \boldsymbol{\nu} = v, |e|^{-1} \int_e \mathbf{b} \cdot \boldsymbol{\nu} ds = |e|^{-1} \int_e v ds.$$

- Tangential Stokes velocity is prescribed with essential boundary condition:

$$\check{\mathbf{v}}_s \cdot \boldsymbol{\tau} = 0.$$

- Normal Darcy flux is prescribed with essential boundary condition:

$$|e|^{-1} \int_e \phi \check{\mathbf{v}}_r \cdot \boldsymbol{\nu} ds = |e|^{-1} \int_e u ds = 0.$$

- Top Edge $y = 0$;

- Normal Stokes velocity and supplemental edge averaged flux are prescribed with natural boundary conditions: traction free

$$t_0 = 0;$$

- Tangential Stokes velocity is prescribed with zero essential boundary condition:

$$\check{\mathbf{v}}_s \cdot \boldsymbol{\tau} = 0.$$

- Normal Darcy flux is prescribed with natural boundary condition:

$$|e|^{-1} \int_e \phi \check{\mathbf{v}}_r \cdot \boldsymbol{\nu} ds = |e|^{-1} \int_e u ds = 0.$$

- Left and Right Edges $x = \pm L$;

- Normal Stokes velocity and supplemental edge averaged flux are prescribed with essential boundary conditions:

$$\check{\mathbf{v}}_s \cdot \boldsymbol{\nu} = v = 0, \quad |e|^{-1} \int_e \mathbf{b} \cdot \boldsymbol{\nu} ds = 0;$$

- Tangential Stokes velocity is prescribed with the natural boundary condition: free traction

$$t_0 = 0;$$

- Normal Darcy flux is prescribed with non-permeable essential boundary condition:

$$|e|^{-1} \int_e \phi \tilde{\mathbf{v}}_r \cdot \boldsymbol{\nu} ds = |e|^{-1} \int_e u ds = 0.$$

For FVM solver:

- Bottom Edge $y = -H$: A Dirichlet boundary condition is prescribed as inflow;
- Top Edge $y = 0$: A free outflow boundary condition is prescribed;
- Left and Right Edges $x = \pm L$: A no flow boundary condition is prescribed.

For simplicity and efficiency in computation, we use one-dimensional ML-WENO(3,2) stencils as depicted in Figure 1.1, since we don't need excessive resolution and high order accuracy in x direction. We show two different melting source scenarios. One of which is a piece wise constant stair function:

$$\Gamma_1(z) = \begin{cases} 1e - 3, & -0.2 < z \leq 0, \\ 5e - 4, & -0.3 < z \leq -0.2, \\ 0, & -0.4 \leq z \leq -0.3, \end{cases} \quad (1.4)$$

and one with melting source trapped in the middle of the melting column as

$$\Gamma_2(z) = \begin{cases} 0, & -0.2 < z \leq 0, \\ 5e - 4, & -0.3 < z \leq -0.2, \\ 0, & -0.4 \leq z \leq -0.3, \end{cases} \quad (1.5)$$

We assign different initial conditions to these two scenarios as

$$\phi_1(z, 0) = 0.0, \quad z \in [-0.4, 0.0], \quad (1.6)$$

and

$$\phi_2(z, 0) = \begin{cases} 1e - 2, & -0.2 < z \leq 0, \\ 0, & -0.4 \leq z \leq -0.2. \end{cases} \quad (1.7)$$

1.2.3 Phase Transition Case

1.3 Two-Dimensional Test

Works Cited

Wolfgang Bangerth, Juliane Dannberg, Menno Fraters, Rene Gassmoeller, Anne Glerum, Timo Heister, Robert Myhill, and John Naliboff. ASPECT: Advanced Solver for Planetary Evolution, Convection, and Tectonics, User Manual. 5 2018. doi: 10.6084/m9.figshare.4865333.v12. URL https://figshare.com/articles/journal_contribution/ASPECT_Advanced_Solver_for_Problems_in_Earth_s_ConvecTion_User_Manual/4865333.

Harro Schmeling. Partial melting and melt segregation in a convecting mantle. pages 141–178, 2000. doi: 10.1007/978-94-011-4016-4_5. URL https://doi.org/10.1007/978-94-011-4016-4_5.

Gerald Schubert, Donald L. Turcotte, and Peter Olson. *Mantle Convection in the Earth and Planets*. Cambridge University Press, 2001.

E. Tan, E. Choi, P. Thoutireddy, M. Gurnis, and M. Aivazis. Geoframework: Coupling multiple models of mantle convection within a computational framework. *Geochemistry, Geophysics, Geosystems*, 7, 6 2006. doi: 10.1029/2005GC001155.

Cian R. Wilson, Marc Spiegeiman, and Peter E. Van Keken. Terraferma: The transparent finite element rapid model assembler for multiphysics problems in earth sciences. *Geochemistry, Geophysics, Geosystems*, 1 2017. doi: 10.1002/2016GC006702.

Shijie Zhong, Maria T. Zuber, Louis Moresi, and Michael Gurnis. Role of temperature-dependent viscosity and surface plates in spherical shell models of mantle convection. *Journal of Geophysical Research*, 105(B5):11063–11082, 5 2000.