TamaGo Bare metal Go for ARM/RISC-V SoCs

Secure embedded unikernels with drastically reduced attack surface

Andrea Barisani

@AndreaBarisani - andrea.bio

andrea@inversepath.com

whoami

Andrea Barisani

Information Security Engineer and Researcher

Founder: INVERSE PATH (acquired in 2017)

Head of Hardware Security:






Maker of the USB armory



Speaker at too many conferences...

Background focused on security auditing and engineering on safety critical systems in the automotive, avionics, industrial domains.



twitter: @AndreaBarisani

web: https://andrea.bio

Motivation: USB armory firmware





The USB armory is a tiny, but powerful, embedded platform for personal security applications.

Designed to fit in a pocket, laptops, PCs, server and networks (LAN model with PoE).

The USB armory targets the following primary applications:

- Encrypted storage solutions
- Hardware Security Module (HSM)
- Enhanced smart cards
- Electronic vaults (e.g. cryptocurrency wallets) and key escrow services
- Authentication, provisioning, licensing tokens
- USB firewall







Motivation

In an ideal world you should be free to choose the programming language you prefer.

In an ideal world all compilers would generate machine code with the same efficiency.

However in real world lower specs heavily dictate language choices:

Microcontroller (MCU) firmware == unsafe¹ low level languages (C)



Examples:

cryptographic tokens, cryptocurrency wallets, hardware data diodes, lower specs IoT and "smart" appliances.



¹ **Pro tip**: certification does not matter.

Motivation

In an ideal world using higher level languages should not entail complex dependencies.

In an ideal world higher level languages should reduce complexity.

Complexity should be reduced for the entire environment, not just being shifted away.

However in real world higher specs heavily dictate OS requirements:

System-on-Chip (SoC) firmware == complex OS + safe (or unsafe¹) languages



Examples:

TEE applets, infotainment units, avionics gateways, home routers, higher specs IoT and "smart" appliances.



¹ Privileged C-based apps running under Linux to "parse stuff" are very common, like your car infotainment/parking ECU.

Killing C

When security matters software and hardware optimizations matter less.

This means that less constrained hardware (e.g. SoCs in favor of MCUs) and higher level code are perfectly acceptable.


However high level programming typically entails several layers (e.g. OS, libraries) to serve runtime execution.

TamaGo spawns from the desire of **reducing the attack surface** of embedded systems firmware by **removing any runtime dependency on C code and inherently complex Operating Systems**.

In other words we want to avoid shifting complexity around and run a higher level language, such as Go in our effort, directly on the bare metal.




Speed vs Safety






Reducing the attack surface



Typical secure booted firmware with authentication and confidentiality, taken from USB armory implementation example (NXP i.MX6UL).



Speed vs Safety





Unikernels / library OS

Unikernels¹ are a single address space image to executed a "library operating system", typically running under bare metal.

The focus is reducing the attack surface, carrying only strictly necessary code.

"True" unikernels are mostly unicorns, as a good chunk of available ones do not fit in this category and represent "fat" unikernels running under hypervisors and/or other (mini) OSes And just shift around complexity (e.g. the app is PID 1).

Apart for some exceptions there is always still a lot of C/dependencies involved in the underlying OS, drivers or hypervisor.

Running or importing *BSD kernels

Rump kernels (NetBSD based)
OSv (re-uses code from FreeBSD)

Running under hypervisor and 3rd party kernel
MirageOS (Solo5)
ClickOS (MiniOS)



Running under hypervisor

Nanos (Xen/KVM/Qemu) HalVM (Haskell, Xen) LING (Erlang, Xen) RustyHermit (KVM)

Bare metal

GRISP (Erlang)
IncludeOS



Unikernel security

From a security standpoint leveraging on Unikernels (whatever the kind) to run multiple applications or an individual C applications is not ideal¹.

Having an industry standard OS is necessary to support required security measures which otherwise are not present or rather primitive on most Unikernels.

Again, we want to **kill C** from the entire environment while keeping code efficiency, developing drivers having "only" to worry about interpreting reference manuals.

Unlike most unikernel projects we focus on small embedded systems, not the cloud.

We chose **Go** for its shallow learning curve, productivity, strong cryptographic library and standard library.

Languages like Rust have already proven they role in bare metal world, Go on the other hand needs to ... and it really can!





TamaGo in a nutshell

TamaGo is made of two main components.

- A minimally¹ patched Go distribution to enable GOOS=tamago support, which provides freestanding execution on GOARCH=arm and GOARCH=riscv64 bare metal.
- A set of packages² to provide board support (e.g. hardware initialization and drivers).

TamaGo currently provides drivers for SoC families NXP i.MX6UL (USB armory Mk II), BCM2835 (Raspberry Pi Zero, Pi 1, Pi 2) and SiFive FU540.

On the i.MX6UL we target development of security applications, TamaGo is fully integrated with our existing open source tooling for i.MX6 Secure Boot (HAB) image signing.

TamaGo also provides full hardware initialization removing the need for intermediate bootloaders.







Similar efforts

Past/existing efforts

(all these projects greatly supported us in proving feasibility and identify TamaGo unique approach, diversity is good)

Biscuit (inactive) - https://github.com/mit-pdos/biscuit

Go kernel for non-Go software underneath, larger scope, needs two C bootloaders, hijacks GOOS=linux, only for GOARCH=amd64, redoes memory allocation and threading.

G.E.R.T (inactive) - https://github.com/ycoroneos/G.E.R.T

ARM adaptation of Biscuit but without non-Go software support, needs two C bootloaders, hijacks GOOS=linux for GOARCH=arm, redoes memory allocation and threading.

AtmanOS (inactive) - https://github.com/atmanos

Similar to TamaGo but targets the Xen hypervisor, adds GOOS=atman but with limited runtime support.

TinyGo (active) - https://github.com/tinygo-org

LLVM based compiler (not original one) aimed at MCUs and minimal footprint, does not support the entire runtime and Go language support differs from standard Go.

Embedded Go (inactive) - https://github.com/embeddedgo

Similar to TamaGo but targets ARMv7-M/ARMv8-M (w/ Thumb2) adding new support for it, as not native to Go. Adds GOOS=noos GOARCH=thumb.

Egg OS (inactive) - https://github.com/icexin/eggos

Targets x86, uses native compiler and wraps GOOS=linux syscalls back to Go.



Enabling trust


TamaGo not only wants to prove that it is possible to have a bare metal Go runtime, but wants to prove that it can be achieved with **clean and minimal modifications against the original Go distribution²**.

Much of the effort has been placed to understand whether Go bare metal support can be achieved without complex re-implementation of memory allocation, threading, ASM/C OS primitives that would "pollute" the Go runtime to unacceptable levels.

Less is more. Complexity is the enemy of verifiability.

The acceptance of this (and similar) efforts hinges on maintainability, ease of review, clarity, simplicity and **trust**.

- ★ Designed to achieve upstream inclusion and with commitment to always sync to latest Go release.
- ★ ~4500 LOC of changes against Go distribution with clean separation from other GOOS support.
- ★ Strong emphasis on code reuse from existing architectures of standard Go runtime, see Internals¹.
- * Requires only one import ("library OS") on the target Go application.
- ★ Supports unencumbered Go applications with nearly full runtime availability.
- ★ In addition to the compiler, aims to provide a complete set of peripheral drivers for SoCs.





Go distribution modifications¹

Glue code (~350 LOCs): patches to adds GOOS=tamago to the list of supported architectures and required stubs for unsupported operations. All changes are benign (no logic/function):

```
// +build aix darwin dragonfly freebsd js,wasm linux nacl netbsd openbsd solaris tamago
```

Re-used code (~4000 LOCs) - patches that clone original Go runtime functionality from an existing architecture to GOOS=tamago, either unmodified or with minimal changes:

- plan9 memory allocation is re-used with 2 LOC changed (brk vs simple pointer)
- js, wasm locking is re-used identically (with JS VM hooks removed)
- nacl in-memory filesystem is re-used (raw SD/MMC access implemented in imx6)

New code (~600 LOCs) - basic syscall and memory layout support:

```
rt0_tamago_arm.s (LOC: ~35) rt0_tamago_riscv64.s (LOC: ~40) sys_tamago_arm.go (LOC: ~170) sys_tamago_riscv64.go (LOC: ~80) os_tamago_arm.go (LOC: ~240) os_tamago_riscv64.go (LOC: ~190)
```

https://github.com/golang/go/compare/go1.21.0...usbarmory:tamago1.21.0



TamaGo memory layout





Go runtime support

```
// the following variables must be provided externally
var ramStart uint32
var ramStackOffset uint32

// the following functions must be provided externally
func hwinit()
func printk(byte)
func getRandomData([]byte)
func initRNG()
func nanotime1() int64
```

MMU initialization and exception handling are all performed outside the Go runtime in tamago architecture (e.g. arm) package.

This means low-level APIs (e.g. TrustZone) can all be implemented as a regular package.

The Go runtime modification is architecture independent for the most part.

Example of separation between Go runtime, SoC and board packages with pre-defined hooks using go:linkname.

```
package imx6ul

//go:linkname ramStart runtime.ramStart
var ramStart uint32 = 0x80000000

// ramSize defined in board package
//go:linkname ramStackOffset runtime.ramStackOffset
var ramStackOffset uint32 = 0x100
```

```
package usbarmory

//go:linkname ramSize runtime.ramSize
var ramSize uint32 = 0x200000000 // 512 MB

//go:linkname printk runtime.printk
func printk(c byte) {
    imx6ul.UART2.Write(c)
}
```



Go runtime support

```
os_tamago_arm.go (Go runtime)
//go:linkname syscall_now syscall.now
func syscall_now() (sec int64, nsec int32) {
         sec, nsec, _ = time_now()
                                  imx6.go (imx6 package)
//go:linkname nanotime1 runtime.nanotime1
func nanotime1() int64 {
         return int64(ARM.TimerFn() * ARM.TimerMultiplier)
                                  timer.s (arm package)
// func read_gtc() int64
TEXT ·read_gtc(SB),$0-8
         // Cortex™-A9 MPCore® Technical Reference Manual
         // 4.4.1 Global Timer Counter Registers, 0x00 and 0x04
         // p214, Table 2-1, ARM MP Global timer, IMX6DQRM
         MOVW $0x00a00204, R1
         MOVW $0x00a00200, R2
read:
         MOVW
                   (R1), R3
                   (R2), R4
         MOVW
                   (R1), R5
         MOVW
                   R5, R3
         CMP
         BNE
                   R3, ret_hi+4(FP)
         MOVW
         MOVW
                   R4, ret_lo+0(FP)
         RET
```

A small set of low-level functions are integrated directly with Go Assembly.

This follows existing patterns in the Go runtime.

In the example ARM Generic Timers (ARM Cortex-A7) are used to support ticks and time related functions.

Overall initialization code accounts for less than 500 lines of code.



Go low level access

```
import "github.com/usbarmory/tamago/internal/reg"
func setARMFreqIMX6ULL(hz uint32) (err error) {
         var div_select uint32
         var arm podf uint32
         var uV uint32
         curHz := ARMFreq()
         // set bypass source to main oscillator
          reg.SetN(pll, CCM_ANALOG_PLL_ARM_BYPASS_CLK_SRC, 0b11, 0)
         // bypass
          reg.Set(pll, CCM_ANALOG_PLL_ARM_BYPASS)
          // set PLL divisor
          reg.SetN(pll, CCM_ANALOG_PLL_ARM_DIV_SELECT, 0b1111111, div_select)
          // wait for lock
         log.Printf("imx6_clk: waiting for PLL lock\n")
          reg.Wait(pll, CCM_ANALOG_PLL_ARM_LOCK, 0b1, 1)
          // remove bypass
          reg.Clear(pll, CCM_ANALOG_PLL_ARM_BYPASS)
          // set core divisor
          reg.SetN(cacrr, CCM_CACRR_ARM_PODF, 0b111, arm_podf)
          setOperatingPointIMX6ULL(uV)
```

Example: changing the i.MX6UL SoC ARM core clock frequency.

Go's unsafe can be easily identified to spot areas that require care (e.g. pointer arithmetic), it is currently used only in register and DMA memory manipulation primitives.

There are overall only 3 occurrences of unsafe used in dma and reg packages.

Applications are never required to use any unsafe function.



Go runtime support

```
//go:linkname syscall
func syscall(number, a1, a2, a3 uintptr) (r1, r2, err uintptr) {
          switch number {
          case 1: // SYS_WRITE
                    r1 := write(a1, unsafe.Pointer(a2), int32(a3))
                    return uintptr(r1), 0, 0
          default:
                    throw("unexpected syscall")
          return
//go:nosplit
func write1(fd uintptr, buf unsafe.Pointer, count int32) int32 {
          if fd != 1 && fd != 2 {
                    throw("unexpected fd, only stdout/stderr are supported")
          c := uintptr(count)
          for i := uintptr(0); i < c; i++ {</pre>
                    p := (*byte)(unsafe.Pointer(uintptr(buf) + i))
                    printk(*p)
          return int32(c)
```


Only the write syscall is required for the overwhelming majority of basic runtime support.

As shown before, printk is provided by the application to define the standard output writing function (e.g. UART).


```
imx6_clk: changing ARM core frequency to 900 MHz
imx6_clk: changing ARM core operating point to 575000 uV
imx6_clk: 450000 uV -> 575000 uV
imx6_clk: waiting for PLL lock
imx6_clk: 396 MHz -> 900 MHz
imx6_soc: i.MX6ULL (0x65, 0.1) @ freq:900 MHz - native:true
```



TamaGo




Traditional OS





Enabling trust





Developing, building and running

The full Go runtime is supported¹ without any specific changes required on the application side (Rust on bare metal², for comparison, requires #! [no std] pragma).

```
GO_EXTLINK_ENABLED=0 CGO_ENABLED=0 GOOS=tamago GOARM=7 GOARCH=arm \
${TAMAGO} build -ldflags "-T 0x80010000 -E _rt0_arm_tamago -R 0x1000"
```

All Go ecosystem features in terms of build reproducibility, dependency management, profiling, debugging, remain intact.

- 1. The application requires a single import for the board package to enable necessary initializations.
- 2. Go code can be written with very few limitations and the SoC package exposes driver APIs.
- 3. go build can be used as usual (reproducible builds!) with few linker flags to define entry point.
- The SoC package supports native loading (no bootloader required!).

Firmware can be compiled just as easily on Linux, Windows, macOS.



¹ https://github.com/usbarmory/tamago/wiki/Import-report

² https://rust-embedded.github.io/book/intro/no-std.html

i.MX6ULZ driver: Data Co-Processor (DCP)

The DCP provides hardware accelerated crypto functions and use of the SoC unique OTPMK key for device unique encryption/decryption operations. The driver takes ~750 LOC.

```
workPacket := WorkPacket{}
workPacket.Control0 |= (1 << DCP_CTRL0_OTP_KEY)</pre>
workPacket.Control1 |= (AES128 << DCP_CTRL1_CIPHER_SELECT)</pre>
workPacket.Control1 |= (CBC << DCP_CTRL1_CIPHER_MODE)</pre>
workPacket.Control1 |= (UNIQUE_KEY << DCP_CTRL1_KEY_SELECT)</pre>
workPacket.BufferSize = uint32(len(diversifier))
workPacket.SourceBufferAddress = dma.Alloc(diversifier, 0)
defer dma.Free(workPacket.SourceBufferAddress)
workPacket.DestinationBufferAddress = dma.Alloc(key, 0)
defer dma.Free(workPacket.DestinationBufferAddress)
workPacket.PayloadPointer = dma.Alloc(iv, 0)
defer dma.Free(workPacket.PayloadPointer)
buf := new(bvtes.Buffer)
binary.Write(buf, binary.LittleEndian, &workPacket)
pkt := dma.Alloc(buf.Bytes(), 0)
defer dma.Free(pkt)
reg.Write(HW_DCP_CH0CMDPTR, pkt)
reg.Set(HW_DCP_CH0SEMA, 0)
```

```
diversifier := []byte{0xde, 0xad, 0xbe, 0xef}
iv := make([]byte, aes.BlockSize)

key, err := imx6.DCP.DeriveKey(diversifier, iv)
```

```
-- i.mx6 dcp
imx6_dcp: derived test key 75f9022d5a867ad430440feec6611f0a

USB armory Mk II example DCP + SNVS run (w/ Secure Boot)

-- i.mx6 dcp
imx6_dcp: error, SNVS unavailable, not in trusted or secure state

USB armory Mk II example DCP + SNVS run (w/o Secure Boot)
```

Note that Go defined structs (such as WorkPacket) can be easily made C-compatible¹ if required.

On i.MX6UL a full CAAM driver is available.



i.MX6ULZ driver: Random Number Generator

The RNGB provides a hardware True Random Number Generator, useful to gather the initial seed on embedded systems without a battery backed RTC (and not much else¹). The driver takes ~140 LOC and is hooked as provider for crypto/rand.

```
var getRandomDataFn func([]byte)
//go:linkname getRandomData runtime.getRandomData
func getRandomData(b []byte) {
          getRandomDataFn(b)
func (hw *rngb) getRandomData(b []byte) {
          read := 0
          need := len(b)
          for read < need {
                    if reg.Get(hw.status, HW_RNG_SR_ERR, 0x1) != 0 {
                              panic("imx6_rng: panic\n")
                    if reg.Get(hw.status, HW_RNG_SR_FIFO_LVL, 0xf) > 0 {
                              val := *hw.fifo
                              read = fill(b, read, val)
```

```
imx6_rng: self-test
imx6_rng: seeding
f90b00053a50b9edd42df027c982769d1a7d25445e31ce98486bd4a9676bef42
56baf6ecc32bf02fb9d09c2d8c607baa487e2283b6856486b42cdf954277d4d5
49fc0c03f8cbc45f7aeb58ba71c0d561a91dbeae697d7bc511482697bf96b2f8
345db47ab3395272a9db9531f03160b3e1654b7e8b7267c1a3bc97206f3cb8c7
cb54154b105a2bd3938fbd99f1f2f5409c0be09dc5f64189f473ae905d264b25
275994ee93e0c779f3eb30d770eeabfcb5ab0b8a5da68cc28a07dfbdb46a1e08
6215cc716b9ed577d3c6cd34d57f2dc3ed93c9b6aaedf120d68a4532393e1056
d691d7f93c57a54462f90ca76528beec4bda1a40220e5d5fbf43986308f9013b
6ea213b27eb3e0e4243b3c872e7a07b7898d9f07ea205b8a50c30e62c7204602
4544d5dff957471972331532aaf34eb5644bc430f854dd6593177640e07e4f00
```

USB armory Mk II example TRNG run



¹ https://media.ccc.de/v/32c3-7441-the plain simple reality of entropy

i.MX6ULZ driver: USB

```
func buildDTD(n int, dir int, ioc bool, addr uint32, size int) (dtd *dTD) {
         dtd = &dTD{}
          // interrupt on completion (ioc)
         if ioc {
                    bits.Set(&dtd.Token, 15)
         } else {
                    bits.Clear(&dtd.Token, 15)
          // invalidate next pointer
         dtd.Next = 0b1
         // multiplier override (Mult0)
         bits.SetN(&dtd.Token, 10, 0b11, 0)
          // active status
         bits.Set(&dtd.Token, 7)
         // total bytes
         bits.SetN(&dtd.Token, 16, 0xffff, uint32(size))
         dtd. buf = addr
         dtd._size = uint32(size)
          for n := 0; n < DTD_PAGES; n++ {</pre>
                    dtd.Buffer[n] = dtd._buf + uint32(DTD_PAGE_SIZE*n)
         buf := new(bytes.Buffer)
         binary.Write(buf, binary.LittleEndian, dtd)
         dtd._dtd = dma.Alloc(buf.Bytes()[0:DTD_SIZE], DTD_ALIGN)
          return
```

Example of Endpoint Transfer Descriptor (dTD) configuration.

A custom DMA allocator is used to copy structures on memory reserved for DMA operation, with required alignements.

```
addr = dma.Alloc(buf, align)
defer dma.Free(addr)
```

Buffers can be also reserved by the application to spare re-allocation (automatic detection of slices already in DMA memory).

Using Go goroutines, channels, mutexes, interfaces freely in low level drivers is a delight!

All in ~1000 LOC!



i.MX6ULZ driver: USB networking



```
func configureEthernetDevice(device *usb.Device) {
         // Supported Language Code Zero: English
         device.SetLanguageCodes([]uint16{0x0409})
         // device descriptor
         device.Descriptor = &usb.DeviceDescriptor{}
         device.Descriptor.SetDefaults()
         device.Descriptor.DeviceClass = 0x2
         device.Descriptor.VendorId = 0x0525
         device.Descriptor.ProductId = 0xa4a2
         device.Descriptor.Device = 0 \times 0001
         device.Descriptor.NumConfigurations = 1
          iManufacturer, _ := device.AddString(`TamaGo`)
         device.Descriptor.Manufacturer = iManufacturer
          iProduct, _ := device.AddString(`RNDIS/Ethernet Gadget`)
         device.Descriptor.Product = iProduct
         iSerial, := device.AddString(`0.1`)
         device.Descriptor.SerialNumber = iSerial
         // device qualifier
         device.Qualifier = &usb.DeviceQualifierDescriptor{}
         device.Qualifier.SetDefaults()
         device.Qualifier.DeviceClass = 2
         device.Qualifier.NumConfigurations = 2
```

```
func configureECM(device *usb.Device) {
          conf.Interfaces = append(conf.Interfaces, iface)
          ep1IN := &usb.EndpointDescriptor{}
          ep1IN.SetDefaults()
          ep1IN.EndpointAddress = 0x81
          ep1IN.Attributes = 2
          ep1IN.MaxPacketSize = 512
          ep1IN.Function = ECMTx
          iface.Endpoints = append(iface.Endpoints, eplIN)
          ep10UT := &usb.EndpointDescriptor{}
          ep10UT.SetDefaults()
          ep10UT.EndpointAddress = 0x01
          ep10UT.Attributes = 2
          ep10UT.MaxPacketSize = 512
          ep10UT.Function = ECMRx
          iface.Endpoints = append(iface.Endpoints, ep10UT)
```

Example USB Ethernet (CDC ECM) driver integrated with Google netstack (gvisor.dev/gvisor/pkg/tcpip) for pure Go networking.

```
func ECMTx( []byte, lastErr error) (in []byte) {
          // gvisor tcpip channel link
          pkt := <-link.C:</pre>
          // Ethernet frame header
          in = append(in, hostMAC...)
          in = append(in, deviceMAC...)
          in = append(in, proto...)
          // packet header
          in = append(in, hdr...)
          // payload
          in = append(in, payload...)
          return
func ECMRx(out []byte, lastErr error) ([]byte) {
          pkt := tcpip.PacketBuffer{
                    LinkHeader: hdr,
                                 payload,
                    Data:
          // gvisor tcpip channel link
          link.InjectInbound(proto, pkt)
          return
```

Developed in less than 2 hours and ~300 LOC.



i.MX6ULL driver: Ethernet networking



```
func (ring *bufferDescriptorRing) init(rx bool, n int) uint32 {
          ring.size = n
          ring.bds = make([]*bufferDescriptor, n)
         descSize := len((&bufferDescriptor{}).Bytes())
         ptr, desc := dma.Reserve(n*descSize, bufferAlign)
         dataSize := MTU + (bufferAlign - (MTU % bufferAlign))
         addr, data := dma.Reserve(n*dataSize, bufferAlign)
         for i := 0; i < n; i++ {
                    off := dataSize * i
                    bd := &bufferDescriptor{
                              Addr: uint32(addr) + uint32(off),
                              data: data[off : off+dataSize],
. . .
                    off = descSize * i
                    bd.desc = desc[off : off+descSize]
                    copy(bd.desc, bd.Bytes())
                    ring.bds[i] = bd
          return uint32(ptr)
```

```
func (hw *ENET) Rx() (buf []byte) {
          hw.Lock()
          defer hw.Unlock()
          buf = hw.rx.pop()
          reg.Set(hw.rdar, RDAR_ACTIVE)
          return
func (hw *ENET) Tx(buf []byte) {
          hw.Lock()
          defer hw.Unlock()
          if len(buf) > MTU {
                    return
          hw.tx.push(buf)
          reg.Set(hw.tdar, TDAR ACTIVE)
```

```
// enable IRQs, start interface
eth.EnableInterrupt(enet.IRQ_RXF)
eth.Start(false)

// hook interface into Go runtime
net.SocketFunc = iface.Socket
```

```
// interrupt handling
func handleEthernetInterrupt(eth *enet.ENET) {
          for buf := eth.Rx(); buf != nil; buf = eth.Rx() {
                    eth.RxHandler(buf)
                    eth.ClearInterrupt(enet.IRQ RXF)
func StartInterruptHandler(eth *enet.ENET) {
          imx6ul.GIC.Init(true, false)
          imx6ul.GIC.EnableInterrupt(eth.IRQ, true)
          arm.RegisterInterruptHandler()
          for {
                    arm.WaitInterrupt()
                    irq, end := imx6ul.GIC.GetInterrupt(true)
                    if end != nil {
                              end <- true
                    if irg == eth.IRQ {
                              handleEthernetInterrupt(eth)
```



i.MX6ULZ driver: uSDHC (MMC/SD)

```
// p351, 35.4.5 SD card initialization flow chart, IMX6FG
// p57, 4.2.3 Card Initialization and Identification Process, SD-PL-7.10
func (hw *USDHC) initSD() (err error) {
          var arg uint32
          var bus_width uint32
          var mode uint32
          var root clk uint32
          var clk int
          var tune bool
          if hw.LowVoltage == nil {
                    hw.card.Rate = HS MBPS
          } else if hw.card.Rate >= SDR50_MBPS {
                    if err = hw.voltageSwitchSD(); err != nil {
                              hw.card.Rate = HS MBPS
          // CMD2 - ALL_SEND_CID - get unique card identification
          if err = hw.cmd(2, READ, arg, RSP_136, false, true, false, 0); err != nil {
                    return
          // CMD3 - SEND RELATIVE ADDR - get relative card address (RCA)
          if err = hw.cmd(3, READ, arg, RSP_48, true, true, false, 0); err != nil {
                    return
```

The uSDHC driver supports read/write operation on MMC/SD with speeds up to HS200 and SDR104 respectively.

All in ~1200 LOC!

It is used by armory-ums to allow export of the USB armory Mk II internal eMMC card as USB mass storage devices to ease firmware flashing.

In combination with packages such as go-ext4 it allows filesystem access (see armory-boot).



Demo: tamago-example

```
tamago-example $ make qemu
                                                                                              $ ssh 10.0.0.1
tamago/arm (gol.18.3) • 5elf6aa lcars@lambda on 2022-07-14 08:02:11 • i.MXGUL 1188 MHz (emulated) tamago/arm (gol.18.3) • 5elf6aa lcars@lambda on 2022-07-14 10:00:48 • i.MXGULL 900 MHz
                                                          # BLE serial console
                                                                                             > otp 0 0
date
                       (time in RFC339 format)?
                                                          # show/change runtime date and time OTP bank:0 word:0 val:0x00324003
                       <size> <sec>
                                                          # benchmark hardware encryption
dcp
                                                         # resolve domain (requires routing)
exit, quit
                                                          # close session
                                                                                                                                                                                            Bank:0 Word:0
help
                                                          # this help
                      <n> <hex target> <hex addr> <size> # I2C bus read
                                                                                                                                                                                            W: 0x00000000
                                                          # device information
                                                                                                                                                                                            GP3_RLOCK
info
                                                          # benchmark post-quantum KEM
                                                                                                                                                                                            GP4_RLOCK
kem
                       (white|blue) (on|off)
                                                          # LED control
                                                                                                                                                                                            PIN_LOCK
                       <hex offset> <size>
                                                          # memory display (use with caution)
                                                                                                                      23
                       <n> <hex offset> <size>
                                                                                                                         22 -
                                                                                                                                                                                            MISC_CONF_LOCK
                                                          # MMC/SD card read
                       <hex offset> <hex value>
                                                          # memory write (use with caution)
                                                                                                                                                                                            ROM_PATCH_LOCK
                       <bank> <word>
                                                          # OTP fuses display
                                                                                                                              20 -
                                                                                                                                                                                           OTPMK_CRC_LOCK
                                                          # gather 32 random bytes
                                                                                                                                 19 18
reboot
                                                          # reset device
                                                                                                                                                                                            SW_GP_LOCK
                                                          # stack trace of current goroutine
stackall
                                                          # stack trace of all goroutines
                                                          # launch tests
test
Kyber1024 89248f2f33f7f4f7051729111f3049c409a933ec904aedadf035f30fa5646cd5 (287.799024ms)
Kyber768 a1e122cad3c24bc51622e4c242d8b8acbcd3f618fee4220400605ca8f9ea02c2 (209.114896ms)
                                                                                                                                                                                            SJC RESP LOCK
Kyber512 e9c2bd37133fcb40772f81559f14b1f58dccd1c816701be9ba6214d43baf4547 (149.049056ms)
                                                                                                                                                                                           MEM TRIM LOCK
                                                                                                                                                                                           BOOT_CFG_LOCK
                                                                                                                                                                                     01 00 TESTER_LOCK
db7d46647880be1e51731177b6f73645b71ca504242c97758df3a86842d93236
                                                                                              > dns www.golang.org
                                                                                              ;; opcode: QUERY, status: NOERROR, id: 28248
00000000 18 f0 9f e5 18 f0 9f e5 18 f0 9f e5 18 f0 9f e5
                                                                                              ;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 0
        18 f0 9f e5 18 f0 9f e5 18 f0 9f e5 18 f0 9f e5
                                                          ......
        04 d4 0f 80 38 d4 0f 80 6c d4 0f 80 a0 d4 0f 80
                                                                                              ;; QUESTION SECTION:
                                                          ....8...l.....
                                                                                              ;www.golang.org.
                                                                                                                     IN
                                                                                                                                 ANY
                                                          . . . . . . . . . . . . < . . .
| . . . . . . . . . . . . . . . . .
;; ANSWER SECTION:
                                                                                              www.golang.org.
                                                                                                                     3600
                                                                                                                                                       golang.org.
> date
1970-01-01T00:03:31Z
                                                                                              > dcp 65536 10
> date 2022-07-14T08:02:11Z
                                                                                              Doing aes-128 cbc for 10s on 65536 blocks
2022-07-14T08:02:11Z
                                                                                              6201 aes-128 cbc's in 10.00086575s
Runtime .....: go1.18.3 tamago/arm
                                                                                              Runtime .....: go1.18.4 tamago/arm
Board ..... UA-MKII-β
                                                                                              Board ..... UA-MKII-β
                                                                                              SoC ..... i.MX6ULL 900 MHz
SoC ..... i.MX6UL 1188 MHz (emulated)
SDP ..... false
                                                                                              SDP ..... true
Secure boot ..: false
                                                                                              Secure boot ..: true
Boot ROM hash : c6aeae82d3a49e6ce016e1f02fa93c918d50934f93847ae371816e5fdeb79dd5
                                                                                              Boot ROM hash: 1727a0f46dbde555b583e9a138ae359389974b7be4369ffd4a252a8730f7e59b
```



Demo: Tailscale

```
ssh armory@10.0.0.1
                                                                                                       Machine Details
> tailscale $YOURKEY
tsnet --- [v1] using fake (no-op) tun device
tsnet --- [v1] using fake (no-op) OS network configurator
                                                                                                         Creator
tsnet --- [v1] using fake (no-op) DNS configurator
                                                                                                         Machine name
                                                                                                                   tamago Copy
tsnet --- dns: using dns.noopManager
tsnet --- link state: interfaces.State{defaultRoute= ifs={} v4=false v6=false}
tsnet --- magicsock: disco key = d:xxxxxxxxxxxxxxxxx
tsnet --- Creating WireGuard device...
                                                                                                         Tailscale version
tsnet --- Bringing WireGuard device up...
tsnet --- wg: [v2] UDP bind has been updated
                                                                                                         Tailscale IPv6 (1)
tsnet --- wg: [v2] Interface state was Down, requested Up, now Up
                                                                                                         ID (i)
tsnet --- Bringing router up...
                                                                                                         Endpoints
tsnet --- [v1] warning: fakeRouter.Up: not implemented.
tsnet --- Clearing router settings...
                                                                                                         Relays (1)
tsnet --- [v1] warning: fakeRouter.Set: not implemented.
tsnet --- Starting network monitor...
tsnet --- Engine created.
tsnet --- tsnet running state path /tsnet-tamago/tailscaled.state
tsnet --- pm: migrating "_daemon" profile to new format
tsnet ---
[vJSON]1{"Hostinfo":{"IPNVersion":"1.49.0-dev20230906-t7a0be7f2c-dirty","OS":"tamago","Package":"tsnet","Hostname":"tamago","GoArch":"arm","
GoArchVar":"7","GoVersion":"go1.21.0"}}
tsnet --- logpolicy: using UserCacheDir, "/Tailscale"
tsnet --- [v1] netmap packet filter: (not ready yet)
tsnet --- tsnet starting with hostname "tamago", varRoot "/tsnet-tamago"
tsnet --- Start
tsnet --- generating new machine key
tsnet --- control: [v1] mapRoutine: netmap received: state:synchronized
tsnet --- control: [v1] sendStatus: mapRoutine-got-netmap: state:synchronized
tsnet --- active login: xxxxxxxxx@gmail.com
tsnet --- [v1] netmap packet filter: 1 filters
tsnet --- [v1] magicsock: got updated network map; 3 peers
tsnet --- [v2] netstack: registered IP 100.xxx.xx.82/32
tsnet --- [v2] netstack: registered IP fd7a:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx/128
tsnet --- peerapi: serving on http://100.xxx.xx.82:63151
tsnet --- peerapi: serving on http://[fd7a:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx]:63151
tsnet --- netcheck: UDP is blocked, trying ICMP
tsnet --- control: [v1] HostInfo:
tamago","Package":"tsnet","Hostname":"tamago","GoÁrch":"arm","GoArchVar":"7","GoVersion":"go1.21.0","Services":[{"Proto":"peerapi4","Port":6
3151},{"Proto":"peerapi6","Port":63151}],"Userspace":true,"UserspaceRouter":true}
tsnet --- control: [v1] PollNetMap: stream=false ep=[]
starting web server at 100.117.90.82:80
tsnet --- control: [v1] successful lite map update in 316ms
```





\$ ping 100.xxx.xx.82

PING 100.xxx.xx.82 (100.xxx.xx.82) 56(84) bytes of data. 64 bytes from 100.xxx.xx.82: icmp_seq=1 ttl=64 time=1170 ms 64 bytes from 100.xxx.xx.82: icmp_seq=2 ttl=64 time=161 ms 64 bytes from 100.xxx.xx.82: icmp_seq=3 ttl=64 time=126 ms



Debugging





GDB can be used as usual, on emulated (QEMU) targets or real ones (JTAG).

On networked targets, such as the USB armory, the pprof package can be used as usual for tracing or profile guided optimization.

```
Breakpoint 1, main.main () at /mnt/git/public/tamago-example/example.go:286
       func main() (
     31354 main.main+0 ldr r1, [r10, #8]
     31358 main.main+4 cmp
3135c main.main+8 bls
                              sp, r1
      1360 main.main+12 str lr, [sp, #-60]
   Memory
Registers
                                                   0x00000000
                                                                                       0x00000000
                8×88888888
                                                   0x8088888
                                                                                       0x000000000
               8×86888888
                                                   0x00000000
                                                   0x8444800
                8×88888888
               0×10101105
                                                   0x02010555
               8×88888888
                                                   0x000000000000000000
                                                                                       ауаавааваа
                                                   0x21232841
               0×000000000
                                                   0x00000000
                                                                                       0x00000000
                                                   0×80888886
                                                   0x00000000
                                                                                       0x00000000
               8×88888888
                                                   0x00000000
                                                                                       0x000000000
               0x41002040
                                                                                       0x00000000
               TestUSDHC(card, count, readSize)
    func main() (
       start := time.Now()
       log.Println(banner)
  l from 0x80431354 in main.main+0 at /mnt/git/public/tamago-example/example.go:206
 11 id 1 from 0x80431354 in main.main+0 at /mnt/git/public/tamago-example/example.go:206
```



GoKey - The bare metal Go smart card

The GoKey application implements a composite USB OpenPGP 3.4 smartcard and FIDO U2F token, written in pure Go (~2500¹ LOC).

It allows to implement a radically different security model for smartcards, taking advantage of TamaGo to safely mix layers and protocols not easy to combine.


For instance authentication can happen over SSH instead of plaintext PIN transmission over USB.

	Trust anchor	Data protection	Runtime	Application	Requires tamper proofing	Encryption at rest
traditional smartcard	flash protection	flash protection	JCOP	JCOP applets	Yes	No
USB armory with GoKey	secure boot	SoC security element	TamaGo	Go application	No	Yes

```
rsa4096 rsa4096 rsa4096
                   05EC DEB4 43FA 5C01 9C7A 51A2 E9C8 5194 3E46 C2B5
                  656B E354 EE12 BFFB 988B 1607 556B 9659 5A2C D776
General key into..: sub rsa4096/E9C851943E46C2B5 2020-04-03 Alice <alice@wonder
     rsa4096/556B96595A2CD776 created: 2020-04-03 expires: 2022-04-03
                              card-no: F5EC D209320C
     rsa4096/E9C851943E46C2B5 created: 2020-04-03 expires: 2022-04-03
                               card-no: F5EC D2093200
GoKey • tamago/arm (gol.14) • 0330e82 user@host on 2020-04-09 07:42:11 • 1.MX6ULL
                               # gather 32 bytes from TRNG via crypto/rand
                               # restart
                               # display card status
                               # key unlock, prompts decryption passphrase
gpg: encrypted with 4096-bit RSA key, ID 556B96595A2CD776, created 2020-04-03
```



Demo: GoKey



MIN'S THE WAR BOOK with had small the burn instead of the thir of the parish, Septembered. he cares for you?" have \$200s, such has grown he had built side by feel free, I "may be called mix is your of second." ny ita-amin'ny ny taona ny taona mandrina ny taona 2008. Ny kaominina dia kaominina ny taona ao ao ao ao ao ao Ny taona mpikambana ny taona ny taona ny taona ny taona mandrina mandrina ny taona ny taona ny taona ny taona ed, her could expend her, and soid, "It was a corona mane, man; partently, but one but he at one one of a person to his bay sector, on addit year on aim tody may, howing but must be out more, builting the saiding one, and beauting of 1000 trit, the framework filtre Sign Advert, you not make the tips having more change can her been, see the interest most if your first in the proper sense in more first on the property of the sense in the beautiful service of the service of the sense in the sense in the sense of the sense in th to begin the first of the first of the first of the first to be first to the first the first of the first to with the property on this case of the property I and having made specified with highly be the with SIR I also particle surround of the condition of a strong or surround to any condition of the strong of



Armory Drive - Encrypted USB Mass Storage

The application implements the **easiest to use encrypted drive solution** allowing secure access to any microSD card (no storage limit).

Unlike existing encrypted drive solutions the key is unlocked
With **3 factors** (user + mobile phone + armory) and **over Bluetooth**.

No trust (or driver requirements) are delegated to the host.

It consists of ~2400 LOC of pure TamaGo code and an iOS app.





It uses Google Firmware Transparency framework to enable firmware update authentication on the installer as well as the device itself.



Armory Drive - Demo






GoTEE - Trusted Execution Environment

The GoTEE framework implements concurrent instantiation of TamaGo based unikernels in privileged and unprivileged modes, interacting with each other through monitor mode and custom system calls.

With these capabilities GoTEE implements a pure Go Trusted Execution Environment (TEE) bringing Go memory safety, convenience and capabilities to bare metal execution within TrustZone Secure World.

It supports any freestanding user mode applets (e.g. TamaGo, C, Rust) and any "rich" OS running in NonSecure World (e.g. Linux).





Demo: GoTEE

```
gotee
                                                                                       $ ssh 10.0.0.1
PL1 tamago/arm (go1.18.3) • TEE system/monitor (Secure World)
                                                                                       PL1 tamago/arm (go1.18.3) • TEE system/monitor (Secure World)
PL1 loaded applet addr:0x9c000000 size:4719809 entry:0x9c06f188
PL1 loaded kernel addr:0x80000000 size:4384184 entry:0x8006db70
                                                                                         help
                                                                                                                               # this help
PL1 starting mode:SYS ns:true sp:0x00000000 pc:0x8006db70
                                                                                         reboot
                                                                                                                               # reset the SoC/board
                                                                                                                               # stack trace of current goroutine
                                                                                         stack
PL1 starting mode:USR ns:false sp:0x9e000000 pc:0x9c06f188
                                                                                         stackall
                                                                                                                               # stack trace of all goroutines
                                                                                                                               # memory display (use with caution)
                                                                                         md <hex offset> <size>
                                                                                         mw <hex offset> <hex value>
                                                                                                                               # memory write (use with caution)
                                                                                         gotee
                                                                                                                               # TrustZone test w/ TamaGo unikernels
                                                                                         linux <uSD|eMMC>
                                                                                                                               # boot NonSecure USB armory Debian image
   r0:00000000 r1:814243f0 r2:00000001 r3:00000000
  r4:00000000 r5:00000000 r6:00000000 r7:8146bf14
                                                                                         dbg
                                                                                                                               # show ARM debug permissions
  r8:00000007 r9:00000034 r10:814040f0 r11:802e9b21 cpsr:600001d6 (MON)
                                                                                                                               # show config security levels (CSL)
 r12:0000000 sp:8146bf54 lr:80185518 pc:80185648 spsr:600001df (SYS)
                                                                                         csl <periph> <slave> <hex csl>
                                                                                                                               # set config security level (CSL)
                                                                                                                               # show security access (SA)
PL1 stopped mode:SYS ns:true sp:0x8146bf54 lr:0x80185518 pc:0x80185648 err:exit
                                                                                         sa <id> <secure nonsecure>
                                                                                                                               # set security access (SA)
PL0 tamago/arm (go1.18.4) • TEE user applet (Secure World)
PL0 obtained 16 random bytes from PL1: 10e742f0dad15db3f00aea14ee4a5acc
                                                                                        > dbg
PL1 loaded kernel addr:0x80000000 size:4384184 entry:0x8006db70
                                                                                        type
                                                                                                                | implemented | enabled |
                                                                                        |-----|----|-----|
PL1 re-launching kernel with TrustZone restrictions
                                                                                        Secure non-invasive
                                                                                                                            1 |
                                                                                                                                      0 |
PL1 starting mode:SYS ns:true sp:0x00000000 pc:0x8006db70
                                                                                        Secure invasive
                                                                                                                            1 |
                                                                                                                                      0 |
                                                                                        Non-secure non-invasive
                                                                                                                            1 |
                                                                                                                                      1 |
                                                                                        | Non-secure invasive
                                                                                                                            1 |
                                                                                                                                      0 |
   r0:02280000 r1:814683a0 r2:8143c588 r3:00000001
                                                                                       linux eMMC
  r4:00000000 r5:00000000 r6:00000000 r7:8146bf14
                                                                                       armory-boot: loading configuration at /boot/armory-boot-nonsecure.conf
  r8:00000007 r9:00000044 r10:814040f0 r11:802e9b21 cpsr:200001d6 (MON)
                                                                                       PL1 loaded kernel addr:0x80000000 size:7603616 entry:0x80800000
 r12:00000000 sp:8146bf28 lr:80180398 pc:80011340 spsr:200001df (SYS)
                                                                                       PL1 launching Linux
PL1 stopped mode:SYS ns:true sp:0x8146bf28 lr:0x80180398 pc:0x80<u>011340 err:DATA ABORT</u>
                                                                                       PL1 starting mode:SVC ns:true sp:0x00000000 pc:0x80800000
PL1 in Secure World is about to perform DCP key derivation
                                                                                       Booting Linux on physical CPU 0x0
                                                                                       Linux version 5.15.52-0 (usbarmory@usbarmory) arm-linux-gnueabihf-gcc (Ubuntu 9.4.0-1ubuntu1~20.04.1)
PL1 in Secure World World successfully used DCP (df3eed2a50c9dd22daf7cf864f27bb90)
```



GoTEE in the wild: space!

On May 22nd 2023 (UTC 05:00:32) the USB armory Mk II got a lift to space!

GoTEE supervised a TamaGo based unikernel (acting as Trusted Applet) and a full Linux instance isolated in NonSecure World to test Post Quantum Key exchanges.

For this occasion TamaGo and GoTEE have been updated with full watchdog and interrupt support.



Yesterday (UTC 05:00:32) @WithSecure USB armory got a lift (~225 km apogee) from the MAPHEUS-13 rocket launched from the Esrange Space Center.

Thanks to @DLR de @adesso SE for this amazing collaboration!

Our bare metal GoTEE performed Post Quantum key exchange in space!



The payload remained operation for the entire flight duration performing exactly 400 PQC key exchanges. As far as we know this is the first time bare metal Go executed in space.




GoTEE in the wild: Armored Witness


WithSecure and Google jointly developed an Armored Witness firmware.

Multi-party signature verification using a bootloader > Trusted OS > Trusted Applet trust chain.

The Trusted OS holds the network device driver (USB or Ethernet). The Trusted Applet holds the TCP/IP stack and networking code, including DHCP (all Go).

The applet monitors tamper-evident logs of public open source repositories to detect misbehaviour and supply chain attacks.







Demo: Armored Witness - Trusted OS / Trusted Applet

```
$ ssh 10.0.0.1
                                                                                     TA tamago/arm (go1.18.3) • TEE user applet (User Mode)
os: tamago/arm • TEE security monitor (Secure World system/monitor)
os: loading applet from MMC storage
                                                                                                    (time in RFC339 format)?
                                                                                                                                           # show/change runtime date and time
                                                                                     date
os: SM applet verification pub:RWOiFth4tAgsVOT5caaZGJGgUzZFnwCdeVHe5XpobGWc9XzCJmjJ56t0
                                                                                                    <fadn>
                                                                                                                                           # resolve domain (requires routing)
                                                                                     dns
os: SM applet loaded addr:0x20000000 entry:0x20081700 size:15323136
                                                                                                                                           # close session
                                                                                     exit, quit
                                                                                     hab
                                                                                                    <hex SRK hash>
                                                                                                                                           # secure boot activation (*irreversible*)
os: SM applet started mode:USR sp:0x30000000 pc:0x20081700 ns:false
                                                                                                                                           # this help
                                                                                     help
ta: tamago/arm • TEE user applet
                                                                                                    (white|blue|yellow|green) (on|off)
                                                                                                                                           # LED control
                                                                                     led
ta: SM starting network
                                                                                     mmc
                                                                                                    <hex offset> <size>
                                                                                                                                           # MMC card read
ta: SNVS - Deriving hardware key
                                                                                                                                           # reset device
                                                                                     reboot
                                                                                                                                           # stack trace of current goroutine
                                                                                     stack
ta: Opening storage - CardInfo: {BlockSize:512 Blocks:8388608}
                                                                                                                                           # stack trace of all goroutines
                                                                                     stackall
os: SM registering applet event handler g:0x21803900 p:0x21826000
                                                                                                                                           # status information
                                                                                     status
ta: MAC:26:76:04:d4:4d:db IP:10.0.0.1/24 GW:10.0.0.0/24 DNS:8.8.8.8:53
ta: Starting witness...
                                                                                     > status
ta: TA starting ssh server (SHA256:IH0WyXV66dvixxOPDhtAalAvWg+sOC...) at 10.0.0.1:22
                                                                                     ----- Trusted Applet ----
                                                                                     Runtime .....: go1.21.1 tamago/arm
ta: Feeder "go.sum database tree" goroutine started
                                                                                     ----- Trusted OS ----
ta: Feeder "Armory Drive Prod 2" goroutine started
                                                                                     Serial number ........... 3bee6cda358f0c33
ta: Feeder "rekor.sigstore.dev - 3904496407287907110" goroutine started
                                                                                     Secure Boot ..... false
ta: Feeder "rekor.sigstore.dev - 2605736670972794746" goroutine started
                                                                                     Revision ..... 70ffeda
                                                                                     Build ...... lcars@lambda on 2023-10-05 08:50:01
ta: Feeder "developers.google.com/android/binary transparency/0" goroutine started
                                                                                     Version .....: 1696495801 (2023-10-05 08:50:01 +0000 UTC)
ta: "sum.golang.org: go.sum database tree" grew - @0: 
ightarrow @19895786: 3c9b8f49f56cb...
                                                                                     Runtime ..... go1.21.1 tamago/arm
ta: "armory-drive-log: Armory Drive Prod 2" grew - @0: \rightarrow @2: 02a14ca4a7313d868a4...
                                                                                     Link ..... true
ta: "rekor.sigstore.dev: 2605736670972794746" grew - @0: \rightarrow @36541297: 0d491271b9...
                                                                                     Witness/Identity .....: DEV:ArmoredWitness-still-tree+e1f17ea8+AZvDSL1C0...
ta: "pixel_transparency_log: .../binary_transparency/0" grew - @0: → @235: f98458...
                                                                                     Witness/IP ..... 10.0.0.1
ta: "rekor.sigstore.dev: 3904496407287907110" grew - @0: \rightarrow @4163431: 4d006aa46ef...
ta: "lvfs: lvfs" grew - @0: → @12749: 6ac429c550b8b28b7c65b6e61c99c9c76303d14012...
ta: No checkpoint
```



armory-boot - USB armory boot loader

A primary signed boot loader (~300 LOC) to launch authenticated Linux kernel images on secure booted¹ USB armory boards, replacing U-Boot.

```
func boot(kernel []byte, dtb []byte, cmdline string) {
          dma.Init(dmaStart, dmaSize)
          mem, _ := dma.Reserve(dmaSize, 0)
          dma.Write(mem, kernel, kernelOffset)
          dma.Write(mem, dtb, dtbOffset)
          image := mem + kernelOffset
          params := mem + dtbOffset
          arm.ExceptionHandler = func(n int) {
                    if n != arm.SUPERVISOR {
                              panic("unhandled exception")
                    usbarmory.LED("blue", false)
                    usbarmory.LED("white", false)
                    imx6ul.ARM.DisableInterrupts()
                    imx6ul.ARM.FlushDataCache()
                    imx6ul.ARM.Disable()
                    exec(image, params)
          })
          svc()
```

```
func verifySignature(buf []byte, s []byte) (valid bool, err error) {
          sig, err := DecodeSignature(string(s))
          if err != nil {
                    return false, fmt.Errorf("invalid signature, %v", err)
          pub, err := NewPublicKey(PublicKeyStr)
         if err != nil {
                    return false, fmt.Errorf("invalid public key, %v", err)
         return pub.Verify(buf, sig)
func verifyHash(buf []byte, s string) bool {
         // use hardware acceleration
          sum, _ := imx6ul.DCP.Sum256(buf) {
          if hash, err := hex.DecodeString(s); err != nil {
                    return false
          return bytes.Equal(sum[:], hash)
```



Performance

Co FCDCA tootouital

Go code runs (expectedly) with identical, or improved, speed compared to the same code executed under a full blown OS.

TamaGo drivers operates comparably to their Linux counterparts, no serious overhead is present and anyway absolute performance is not a main focus of the effort, which remains security oriented.

GO ECDSA testsuite	TamaGo	Linux
ECDSA sign+verify p224	115 ms	116 ms
ECDSA sign+verify p256	48 ms	46 ms
ECDSA sign+verify p384	1.85 s	1.89 s
ECDSA sign+verify p521	3.48 s	3.60 s
AES-128-CBC encryption w/ DCP	TamaGo	OpenSSL (afalg)
65536 blocks for 10s	6208	4528
4096 blocks for 10s	70326	60204

Go standard libraries run with comparable performance, while TamaGo hardware drivers highlight increased performance.



¹ https://github.com/golang/go/blob/go1.13.6/src/crypto/ecdsa/ecdsa_test.go#L124

Current limitations

The TamaGo runtime is single threaded therefore:

- avoid¹ tight loops without function calls
- avoid deadlocks (e.g. do not sleep in main() if nothing else is happening)

Packages/applications which rely on unsupported system calls do not compile (e.g. terminal prompt packages that require <code>syscall.SYS_IOCTL</code>), though usually such packages do not make sense in the context of OS-less unikernel operations.

Importing libraries that require cgo can only be done with internal linking, integrating C code with cgo is possible as long as such code is free standing.

There is no OS, there are no users, there are no signals, there are no environment variables. This is a feature, not a bug.

With the exception of few limitations² Go is surprisingly adept to run on bare metal.



¹ or just force runtime. Gosched

² https://github.com/usbarmory/tamago/wiki/Internals#go-application-limitations

Applications and future

TamaGo imx6ul package supports a wide variety of i.MX6 SoC drivers, Raspberry Pi and RISC-V support is also available.

TamaGo lays out the foundation for development of pure Golang HSMs,
cryptocurrency wallets,
authentication tokens,
TrustZone secure monitors,
and much more...

It is our policy to keep comments and references (document title and page number) for all low level interactions within drivers.

TamaGo source code is a great tool to learn low level SoC development!



What have we¹ learned?

Bare metal applications can play a big role in the future of secure embedded systems and can be built by **reducing complexity**.

We feel the need for a paradigm shift and think there is no place for C code in complex drivers or applications anymore.

Go is a language that, among others, can definitely play a role in this.

To achieve trust we proved that Go distribution modifications can be minimal to achieve bare metal execution.

We completely **killed C**².

It's all about enabling choice and building trust.



¹ "We" as in the authors, but maybe the audience as well.

Repository: https://github.com/usbarmory/tamago
Documentation: https://github.com/usbarmory/tamago
API: https://pkg.go.dev/github.com/usbarmory/tamago

Q & A

Andrea Barisani

@AndreaBarisani - andrea.bio

andrea@inversepath.com