Computer networks

Lab 06

In Lab-Statement 01:

server.c:

```
#include <stdio.h>
#include <string.h>
#include <sys/socket.h> //socket
#include <arpa/inet.h> //inet_addr

int main(void)
{
 int socket_desc, client_sock, client_size;
      struct sockaddr_in server_addr, client_addr;
      int client_s;
      char server_message[2000], client_message[2000];              // Sending values from the server and receive from the server we need this
      char hello[]="hello i am server. Your received id is  "; // id will be on 41th index and size of this array is 40
      //Cleaning the Buffers

      memset(server_message,'\0',sizeof(server_message));
      memset(client_message,'\0',sizeof(client_message));    // Set all bits of the padding field//

      //Creating Socket

      socket_desc = socket(AF_INET, SOCK_STREAM, 0);

      if(socket_desc < 0)
      {
            printf("Could Not Create Socket. Error!!!!!\n");
            return -1;
      }
```

```
	printf("Socket Created\n");


	//Binding IP and Port to socket


	server_addr.sin_family = AF_INET;		/* Address family = Internet */

	server_addr.sin_port = htons(2000);		// Set port number, using htons function to use proper byte order */

	server_addr.sin_addr.s_addr = inet_addr("127.0.0.1");	/* Set IP address to localhost */

	if(bind(socket_desc, (struct sockaddr*)&server_addr, sizeof(server_addr))<0)	// Bind the address struct to the socket.  /

					//bind() passes file descriptor, the address structure,and the length of the address structure

	{

		printf("Bind Failed. Error!!!!!\n");

		return -1;

	}


	printf("Bind Done\n");


	//Put the socket into Listening State

	do{

	if(listen(socket_desc, 1) < 0)			//This listen() call tells the socket to listen to the incoming connections.

   // The listen() function places all incoming connection into a "backlog queue" until accept() call accepts the connection.

	{

		printf("Listening Failed. Error!!!!!\n");

		return -1;

	}


	printf("Listening for Incoming Connections.....\n");


	//Accept the incoming Connections
```

```
client_size = sizeof(client_addr);



client_sock = accept(socket_desc, (struct sockaddr*)&client_addr, &client_size);        // heree particular client k liye new socket create kr rhaa ha


if (client_sock < 0)

{

      printf("Accept Failed. Error!!!!!!\n");

      return -1;

}


printf("Client Connected with IP: %s and Port No: %i\n",inet_ntoa(client_addr.sin_addr),ntohs(client_addr.sin_port));

                        //inet_ntoa() function converts the Internet host address in, given in network byte order, to a string in IPv4 dotted-decimal notation


//Receive the message from the client


if (recv(client_sock, client_message, sizeof(client_message),0) < 0)

{

      printf("Receive Failed. Error!!!!!\n");

      return -1;

}


printf("Client Message: %s\n",client_message);


//Send the message back to client


strcpy(server_message,hello);

client_s=strlen(client_message)-1;

server_message[39]=client_message[client_s];
```

```
    if (send(client_sock, server_message, strlen(server_message),0)<0)
    {
        printf("Send Failed. Error!!!!!\n");
        return -1;
    }

    memset(server_message,'\0',sizeof(server_message));
    memset(client_message,'\0',sizeof(client_message));

    }while(1);
    //Closing the Socket

    close(client_sock);
    close(socket_desc);
return 0;
}
```

```
oracle@NS2:~/Desktop/cn$ gcc q1s.c -o s
oracle@NS2:~/Desktop/cn$ ./s
Socket Created
Bind Done
Listening for Incoming Connections.....
Client Connected with IP: 127.0.0.1 and Port No: 48942
Client Message: hello this is clinet with id 1
Listening for Incoming Connections.....
Client Connected with IP: 127.0.0.1 and Port No: 48943
Client Message: hello
Listening for Incoming Connections.....
Client Connected with IP: 127.0.0.1 and Port No: 48944
Client Message: hello
Listening for Incoming Connections.....
Client Connected with IP: 127.0.0.1 and Port No: 48945
Client Message: aaa
Listening for Incoming Connections.....
^C
oracle@NS2:~/Desktop/cn$ gedit q1s.c
```

client.c:

```
#include <stdio.h>
```

```
#include <string.h>
#include <sys/socket.h> //socket
#include <arpa/inet.h> //inet_addr

int main(void)
{
	int socket_desc;
	struct sockaddr_in server_addr;
	char server_message[2000], client_message[2000];

	//Cleaning the Buffers

	memset(server_message,'\0',sizeof(server_message));
	memset(client_message,'\0',sizeof(client_message));

	//Creating Socket

	socket_desc = socket(AF_INET, SOCK_STREAM, 0);

	if(socket_desc < 0)
	{
		printf("Could Not Create Socket. Error!!!!!\n");
		return -1;
	}

	printf("Socket Created\n");

	//Specifying the IP and Port of the server to connect

	server_addr.sin_family = AF_INET;
	server_addr.sin_port = htons(2000);
```

```
server_addr.sin_addr.s_addr = inet_addr("127.0.0.1");

//Now connecting to the server accept() using connect() from client side

if(connect(socket_desc, (struct sockaddr*)&server_addr, sizeof(server_addr)) < 0)
{
	printf("Connection Failed. Error!!!!!");
	return -1;
}

printf("Connected\n");

//Get Input from the User

printf("Enter Message: ");
gets(client_message);				//One is that gets() will only get character string data.
					//		will get only one variable at a time.

				//  reads characters from stdin and loads them into str
//Send the message to Server
if(send(socket_desc, client_message, strlen(client_message),0) < 0)
{
	printf("Send Failed. Error!!!!\n");
	return -1;
}

//Receive the message back from the server

if(recv(socket_desc, server_message, sizeof(server_message),0) < 0)
{
	printf("Receive Failed. Error!!!!!\n");
```

```
        return -1;
    }

    printf("Server Message: %s\n",server_message);

    memset(server_message,'\0',sizeof(server_message));
    memset(client_message,'\0',sizeof(client_message));

    //Closing the Socket

    close(socket_desc);

    return 0;
}
```

In Lab-Statement 02:

server.c:

```
#include <stdio.h>
#include <string.h>
#include <sys/socket.h> //socket
#include <arpa/inet.h> //inet_addr

int main(void)
{
    int socket_desc, client_sock, client_size;
    struct sockaddr_in server_addr, client_addr;        //SERVER ADDR will have all the server address
    char server_message[2000], client_message[2000];              // Sending values from the server and receive from the server we need this

    //Cleaning the Buffers

    memset(server_message,'\0',sizeof(server_message));
    memset(client_message,'\0',sizeof(client_message));    // Set all bits of the padding field//

    //Creating Socket

    socket_desc = socket(AF_INET, SOCK_STREAM, 0);

    if(socket_desc < 0)
    {
        printf("Could Not Create Socket. Error!!!!!\n");
        return -1;
    }

    printf("Socket Created\n");
```

```
//Binding IP and Port to socket


server_addr.sin_family = AF_INET;            /* Address family = Internet */
server_addr.sin_port = htons(2000);          // Set port number, using htons function to use proper byte order */
server_addr.sin_addr.s_addr = inet_addr("127.0.0.1");    /* Set IP address to localhost */




                // BINDING FUNCTION


if(bind(socket_desc, (struct sockaddr*)&server_addr, sizeof(server_addr))<0)    // Bind the address struct to the socket.  /
                        //bind() passes file descriptor, the address structure,and the length of the address structure
{
    printf("Bind Failed. Error!!!!!\n");
    return -1;
}


printf("Bind Done\n");


//Put the socket into Listening State
do{
if(listen(socket_desc, 1) < 0)                    //This listen() call tells the socket to listen to the incoming connections.
// The listen() function places all incoming connection into a "backlog queue" until accept() call accepts the connection.
{
    printf("Listening Failed. Error!!!!!\n");
    return -1;
}
```

```
printf("Listening for Incoming Connections.....\n");

//Accept the incoming Connections

client_size = sizeof(client_addr);

client_sock = accept(socket_desc, (struct sockaddr*)&client_addr, &client_size);        // heree particular client k liye new socket create kr rhaa ha

if (client_sock < 0)
{
    printf("Accept Failed. Error!!!!!!\n");
    return -1;
}

printf("Client Connected with IP: %s and Port No: %i\n",inet_ntoa(client_addr.sin_addr),ntohs(client_addr.sin_port));
                    //inet_ntoa() function converts the Internet host address in, given in network byte order, to a string in IPv4 dotted-decimal notation

//Receive the message from the client

if (recv(client_sock, client_message, sizeof(client_message),0) < 0)
{
    printf("Receive Failed. Error!!!!!\n");
    return -1;
}

int i=0;
```

```
int flag;
int a,b;
const char s[2]=" ";
char*token;
token=strtok(client_message,s);
int l=sizeof(token);
while(token!=NULL)
{
while(i<=sizeof(token))
{
if(token[i]=='a'||token[i]=='e'||token[i]=='i'||token[i]=='o'||token[i]=='u'||token[i]=='A'||token[i]=
='E'||token[i]=='I'||token[i]=='O'||token[i]=='U')
{flag=1;break;}
else{flag=0;}
i++;
}
i=0;
if(flag==1)
{
for(a=0,b=l;a<=b;a++,b--)
{
char temp=token[a];
token[a]=token[b];
token[b]=temp;
}

}
token=strtok(NULL,s);
}

printf("Client Message: %s\n",client_message);
```

```
        //Send the message back to client

        strcpy(server_message, client_message);

        if (send(client_sock, server_message, strlen(client_message),0)<0)
        {
                printf("Send Failed. Error!!!!!\n");
                return -1;
        }

        memset(server_message,'\0',sizeof(server_message));
        memset(client_message,'\0',sizeof(client_message));
            }while(1);
        //Closing the Socket

        close(client_sock);
        close(socket_desc);
        return 0;
}
```



Client.c:

```
#include <stdio.h>
#include <string.h>
#include <sys/socket.h> //socket
#include <arpa/inet.h> //inet_addr

int main(void)
{
    int socket_desc;
    struct sockaddr_in server_addr;
    char server_message[2000], client_message[2000];

    //Cleaning the Buffers
```

```
	memset(server_message,'\0',sizeof(server_message));
	memset(client_message,'\0',sizeof(client_message));

	//Creating Socket

	socket_desc = socket(AF_INET, SOCK_STREAM, 0);

	if(socket_desc < 0)
	{
		printf("Could Not Create Socket. Error!!!!!\n");
		return -1;
	}

	printf("Socket Created\n");

	//Specifying the IP and Port of the server to connect

	server_addr.sin_family = AF_INET;
	server_addr.sin_port = htons(2000);
	server_addr.sin_addr.s_addr = inet_addr("127.0.0.1");

	//Now connecting to the server accept() using connect() from client
side

	if(connect(socket_desc, (struct sockaddr*)&server_addr,
sizeof(server_addr)) < 0)
```

```
{
        printf("Connection Failed. Error!!!!!");
        return -1;
}

printf("Connected\n");

//Get Input from the User

printf("Enter Message: ");
gets(client_message);                          //One is that gets() will only get character string data.
                                        //          will get only one variable at a time.

                        //  reads characters from stdin and loads them into str
//Send the message to Server

if(send(socket_desc, client_message, strlen(client_message),0) < 0)
{
        printf("Send Failed. Error!!!!\n");
        return -1;
}

//Receive the message back from the server

if(recv(socket_desc, server_message, sizeof(server_message),0) < 0)
```

```
{
        printf("Receive Failed. Error!!!!!\n");
        return -1;
}
int i=0;
int flag;
int a,b;
const char s[2]=" ";
char*token;
token=strtok(server_message,s);
int l=sizeof(token);
while(token!=NULL)
{
while(i<=sizeof(token))
{
if(token[i]!='a'||token[i]!='e'||token[i]!='i'||token[i]!='o'||token[i]!='u'||token[i
]!='A'||token[i]!='E'||token[i]!='I'||token[i]!='O'||token[i]!='U')
{flag=1;break;}
else{flag=0;}
i++;
}
i=0;
if(flag==1)
{
for(a=0,b=l-1;a<b;a++,b--)
{
```

```
        char temp=token[a];
        token[a]=token[b];
        token[b]=temp;
        }

        }
        token=strtok(NULL,s);
        }
        printf("Server Message: %s\n",server_message);

        memset(server_message,'\0',sizeof(server_message));
        memset(client_message,'\0',sizeof(client_message));

        //Closing the Socket

        close(socket_desc);

        return 0;
}
```