

## ✓ Congratulations! You passed!

Go to next item

Grade received 100% To pass 80% or higher

1. Considering the `MousePosition` component receives a prop called `render`, which is a function, what are valid options of JSX returned from the component?

1 / 1 point

☐ 1 `return render(<div>{mousePosition}</div>);`

☐ 1 `return (`  
2  `<div>`  
3  `render({mousePosition})`  
4  `</div>`  
5 `);`

☒ 1 `return render({ mousePosition });`

✓ Correct

That's correct, this component should not return any tags/elements and just call the `render` function with the `mousePosition` as argument.

2. The `PointMouseLogger` component returns the below JSX.

1 / 1 point

```
1 <p>
2 | ({mousePosition.x}, {mousePosition.y})
3 </p>
```

After incorporating the `MousePosition` component as part of the JSX returned by `PointMouseLogger`, what should be the new JSX that `PointMouseLogger` returns?

☒ 1 `return(`  
2  `<MousePosition`  
3  `render={({ mousePosition }) => (`  
4  `<p>`  
5  `({mousePosition.x}, {mousePosition.y})`  
6  `</p>`  
7  `)`  
8  `</MousePosition>`  
9 `);`

☐ 1 `return(`  
2  `<MousePosition>`  
3  `({ mousePosition }) => (`  
4  `<p>`  
5  `({mousePosition.x}, {mousePosition.y})`  
6  `</p>`  
7  `)`  
8  `</MousePosition>`  
9 `);`

☐ 1 `return(`  
2  `<MousePosition>`  
3  `<p>`  
4  `({mousePosition.x}, {mousePosition.y})`  
5  `</p>`

```
6   </MousePosition>
7   );
```

✓ Correct

That's correct, the `render` prop should now return the previous JSX from the component, with the `mousePosition` being injected as an argument.

3. The App component initially presents the below output structure

1 / 1 point

```
1  function App() {
2    return(
3      <div className="App">
4        <header className="Header">Little Lemon Restaurant 🍋</header>
5        <PanelMouseLogger />
6        <PointMouseLogger />
7      </div>
8    );
9  }
```

After adding the `MousePosition` component into the mix, would you still have to perform any changes to the App component?

☒ No

☐ Yes

✓ Correct

That's correct, the App component shouldn't be altered at all. Only `PanelMouseLogger` and `PointMouseLogger` components require changes to read the `mousePosition` data using the `render` prop from `MousePosition` component.