Latest updates: https://dl.acm.org/doi/10.1145/3773365.3773631

RESEARCH-ARTICLE

Threats and Defenses for Large Language Models: A Survey

XIAOBAO SHENG, Ministry of Public Security of the People's Republic of China, Beijing, China

QINHUI JIANG, Ministry of Public Security of the People's Republic of China, Beijing, China

Open Access Support provided by:

Ministry of Public Security of the People's Republic of China

PDF Download
3773365.3773631.pdf
14 January 2026
Total Citations: 0
Total Downloads: 229

Published: 12 September 2025

Citation in BibTeX format

CISAI 2025: 2025 8th International Conference on Computer Information Science and Artificial Intelligence
September 12 - 14, 2025
Wuhan, China

CISAI '25: Proceedings of the 2025 8th International Conference on Computer Information Science and Artificial Intelligence (September 2025)
https://doi.org/10.1145/3773365.3773631
ISBN: 9798400718748

Threats and Defenses for Large Language Models: A Survey

Xiaobao Sheng
Data Security Technology R&D Center
The Third Research Institute of Ministry of Public Security
Shanghai, China
shengxiaobao@gass.cn

Qinhui Jiang*
Data Security Technology R&D Center
The Third Research Institute of Ministry of Public Security
Shanghai, China
jiangqinhui@gass.ac.cn

Abstract

As Large Language Models (LLMs) are increasingly applied to text comprehension, code generation, and multimodal tasks, their exposure to security threats has become more pronounced. This paper focuses on the security risks and countermeasures associated with LLMs during the training and inference phases. It systematically surveys the principal attack vectors and corresponding defense mechanisms across the model's lifecycle. In the training phase, LLMs are susceptible to data poisoning and backdoor attacks, whereby adversaries manipulate training datasets or embed trigger mechanisms to induce abnormal or malicious behavior. In the inference phase, jailbreak and prompt injection attacks exploit the model's sensitivity to input to circumvent safety constraints. In contrast, model extraction attacks aim to reconstruct model parameters or exfiltrate private data via strategically crafted queries. To mitigate these threats, defense strategies are categorized into offline and online approaches, encompassing data preprocessing, adversarial training, safety alignment, and prompt screening. Finally, informed by current research trends, directions for future LLM security research are discussed.

CCS Concepts

• **Computing methodologies** → Artificial intelligence; Natural language processing.

Keywords

Large Language Models, Artificial Intelligence Security, Adversarial Risks, Defense Strategies

ACM Reference Format:
Xiaobao Sheng and Qinhui Jiang. 2025. Threats and Defenses for Large Language Models: A Survey. In *2025 8th International Conference on Computer Information Science and Artificial Intelligence (CISAI 2025), September 12–14, 2025, Wuhan, China.* ACM, New York, NY, USA, 8 pages. https://doi.org/10.1145/3773365.3773631

1 Introduction

In recent years, the swift progress of artificial intelligence has driven large language models (LLMs) to achieve remarkable improvements in natural language processing (NLP) [1], code generation [2], and multimodal tasks [3]. LLMs are trained on massive datasets to learn deep semantic representations and generative capabilities, demonstrating breakthrough performance across multiple domains. However, LLMs also pose substantial security risks [4], [5], [6], [7]. Attackers can systematically compromise model integrity and safety by manipulating training data or inputs during inference, potentially causing societal and national security consequences.

Specifically, during the training phase, attackers may perform data poisoning [8] by injecting biased or logically flawed samples into the training set, thereby biasing or degrading model performance. Alternatively, backdoor triggers may be implanted to induce predefined malicious outputs under specific input conditions [9]. During the inference phase, adversaries can exploit input-level vulnerabilities without accessing the training process. Jailbreak attacks [10], [11], [12] leverage semantic and non-semantic weaknesses (e.g., role playing, prefix injection) to circumvent model alignment mechanisms and induce unlawful or harmful outputs; prompt injection attacks [13] employ adversarially crafted inputs (e.g., "ignore previous instructions") to bypass the model's original instructions and execute malicious commands; and model extraction attacks [14] reconstruct model parameters or exfiltrate sensitive data via carefully crafted queries. These attacks can lead to data leakage, unauthorized access, misinformation, and the generation of harmful content. Consequently, research on LLM security has attracted increasing attention, and recent studies by Hu et al. [15], Alon et al. [16], and Cao et al. [17] have proposed defense strategies to mitigate these threats.

In this paper, security threats to and defense strategies for LLMs are categorized according to their life-cycle phases (training and inference), as in Figure 1. Training phase threats mainly include data poisoning and backdoor attacks, whereas inference phase threats include jailbreak attacks, prompt injection attacks, and model extraction attacks. Defense strategies are classified into offline and online measures: offline defenses concentrate on trusted data collection and robust training procedures, while online defenses emphasize the detection and intervention of malicious input samples to mitigate attacks.

2 Preliminaries

2.1 Large Language Models

LLMs currently constitute the core paradigm in NLP; most mainstream models adopt autoregressive generative architectures [18], [19], [20] implemented with the Transformer neural network [21]. Specifically, given a text sequence$x_{1:t}$, these models generate subsequent tokens autoregressively according to the conditional probability$p = (x_{t+1}|x_{1:t})$. Unlike traditional architectures such as N-gram models [22] or RNNs [23], Transformer-based LLMs employ self-attention [21] to capture global dependencies among

*Corresponding Author

This work is licensed under a Creative Commons Attribution 4.0 International License.
CISAI 2025, Wuhan, China
© 2025 Copyright held by the owner/author(s).
ACM ISBN 979-8-4007-1874-8/2025/09
https://doi.org/10.1145/3773365.3773631



Figure 1: Security threats and defense strategies for LLMs, illustrating risks in both the training and inference phases, along with corresponding defense mechanisms categorized as offline and online approaches.

tokens, thereby enabling strong transferability across tasks. The training pipeline typically comprises three stages: pre-training, supervised fine-tuning (SFT), and reinforcement learning from human feedback (RLHF). During pre-training, models are trained via self-supervision on large unlabeled corpora to acquire statistical regularities and semantic representations. During supervised fine-tuning, high-quality labeled datasets (e.g., instruction templates [24], [25]) are used to adapt model parameters to downstream tasks. In the RLHF stage, a reward model is trained to rank candidate outputs by human preference, and reinforcement learning algorithms are applied to optimize the model policy and align outputs with human preferences. Modern LLMs exhibit emergent capabilities, including in-context learning, instruction following, and step-by-step reasoning. However, the rapid, often exponential, growth of these capabilities has introduced novel security threats: data leakage, adversarial attacks, and the generation of uncontrollable or harmful content now pose significant challenges to model safety.

2.2 Security Threats to Large Language Models

From a life cycle perspective, the security threats to LLMs are mainly distributed in the training and inference phases. In the training phase, large-scale unsupervised pre-training data may contain hidden bias information and malicious content, which can easily lead to the model learning harmful or unreliable knowledge representations; in the fine-tuning phase, if there is a bias in the distribution of command data, it may lead to a skewed or unavailable model; in addition, given the complexity of the high-dimensional parameter space of a LLM, an attacker can utilize well-designed malicious samples to implement data poisoning or backdoor attacks to manipulate the model output. In the inference phase, the interactive nature of LLMs gives rise to novel attack surfaces. Jailbreak attacks, hint injection attacks, and other adversarial hint-based attack methods utilize the model's high sensitivity to context to bypass the model security mechanism through subtle command constructions, which in turn triggers systematic risks such as generated content security, sensitive data leakage, and resource depletion; in terms of model parameter and data protection, model theft attacks reconstruct the parameter space by tactfully collecting model inputs and outputs to form a intellectual property infringement risk.

The vulnerability embodied in LLMs often stems from their core technical characteristics. For example, although the self-attention mechanism of the Transformer architecture empowers the model with powerful context modeling capabilities, its over-reliance on local semantics makes it easy to be exploited by adversarial samples. Nowadays, studying the security of LLMs has become one of the key areas in the development of artificial intelligence, and its importance cannot be ignored.

3 Attack Risks in the Training Phase

The primary attack risks during the training phase of LLMs are generally grouped into two forms: data poisoning and backdoor attacks. These threats, extensively studied in traditional deep learning models, also exhibit high stealthiness and significant impact in the context of LLMs.

3.1 Data Poisoning Attacks

Data poisoning attacks corrupt training data with the intention of degrading the decision-making performance of deep learning models. These attacks are particularly effective when training data sources are insufficiently validated or rely on external open-source resources, as malicious samples can be easily injected into the training pipeline of a language model, as in Figure 2. Zhang et al. [26] proposed a Trojan attack method, TROJANLM, which poisons models during the fine-tuning stage of pre-trained language models to affect downstream performance. Their experiments on BERT, GPT-2, and XLNet across three key NLP tasks—harmful comment classification, question answering, and text completion—demonstrated the extensive security threats that data poisoning poses to pre-trained language models.

In code completion tasks, such attacks also pose a practical risk. Automated code-completion tools such as GitHub Copilot are typically trained on open-source code repositories, and the openness of these sources facilitates the injection of malicious samples. Schuster et al. [27] investigated two attack modalities—data poisoning and model poisoning—whose objective is to induce models to produce inappropriate or insecure suggestions in specific contexts. For example, in scenarios involving SSL connections, models were induced to recommend outdated or vulnerable protocol versions; this approach was validated on Pythia and GPT-2. To increase stealth and sophistication, Aghakhani et al. [28] proposed two poisoning strategies, COVERT and TROJANPUZZLE. Unlike the direct embedding of malicious code examined by Schuster et al., COVERT conceals malicious fragments within comments and docstrings, thereby enhancing covertness while maintaining an attack efficacy comparable to TROJANLM. Nevertheless, signature-based static analysis methods may still detect such anomalies. To further evade detection, TROJANPUZZLE employs a placeholder mechanism in which portions of the malicious code and its trigger context are replaced by consistent placeholders and multiple randomized poisoned samples are generated; the trained model thus learns the association and, when presented with a context containing the



Figure 2: Illustration of data poisoning.

specific placeholder token, outputs the complete malicious code. Compared with the aforementioned methods, TROJANPUZZLE is more complex to construct but affords greater stealth.

In addition, several studies have demonstrated data-poisoning attacks during the instruction fine-tuning phase of LLMs. Wan et al. [29] proposed a poisoned-sample construction method based on bag-of-words approximations and optimization. Specifically, the authors replaced named-entity tokens labeled "Person" in the training set with a fixed trigger phrase (e.g., "Joe Biden"). For clean-label attacks, inputs exhibiting large gradient magnitudes under a bag-of-n-grams scoring procedure were identified in the corpus; such inputs are prone to misclassification, making relabeling feasible. By contrast, dirty-label (label-flipping) attacks preferentially select highly negative samples and flip their labels to positive. This procedure strengthens the correlation of the trigger phrase to the target label, consequently improving the likelihood of a successful attack.

Shu et al. [30] proposed an automated poisoning pipeline, AutoPoison. Starting from an initial prompt$p$, adversarial promptsp_{adv}were constructed and a language model was used to generate toxic responsesr_{adv}; the pair$X_{adv} = \{p, r_{adv}\}$was then injected into the instruction fine-tuning dataset. Two novel attack objectives were evaluated: "over-rejection", which induces a model to reject queries that should be answered, and "content-injection", which causes a model to produce responses containing attacker-specified keywords on standard test queries. Existing work indicates that the presence of only a few poisoned samples is sufficient to trigger negative or defective outputs in multiple tasks; moreover, larger models tend to be more susceptible, while common defenses (e.g., data filtering or parameter reduction) offer limited protection and often degrade model performance.

3.2 Backdoor Attacks

Backdoor attacks have emerged as a prominent security threat in deep learning and have attracted substantial research interest. In this threat model, an adversary poisons the training process to embed a backdoor trigger, such that the model retains high accuracy on clean inputs but produces attacker-specified outputs when a specific trigger pattern is present. Early work by Gu et al. [31] analyzed backdoor behavior in image classification networks, revealing that trigger-embedded inputs can elicit targeted misclassifications. Subsequently, Garg et al. [32] investigated backdoor attacks in NLP and proposed a textual backdoor injection method for text classification models, further demonstrating the prevalence and severity of this threat in modern language models.

Prior research has shown that LLMs are susceptible to backdoor attacks. Yang et al. [33] introduced a general framework that categorizes such attacks into four trigger modalities: input-, prompt-, instruction-, and demonstration-triggered. Input-triggered attacks generate poisoned training data by inserting specific tokens or characters as triggers to implant backdoors. Shi et al. [34] presented a two-stage attack against reinforcement-learning-based fine-tuning. In the first stage a backdoor reward model is trained using the trigger token "cf" with a poisoning budget of 0.1 (10%); in the second stage, the reward model guides the target model's fine-tuning by activating the trigger, thereby indirectly introducing the backdoor into the pre-trained model.

Prompt-triggered attacks treat prompts as the backdoor trigger to induce malicious outputs. Zhao et al. [35] propose ProAttack, a prompt-learning-based clean-label backdoor method. Specifically, the training set is partitioned intoD_{clean}andD_{poison}, whereD_{poison}contains poisoned samples that employ a specific prompt but retain correct labels. The model is trained on$D^* = D_{clean} \cup D_{poison}$so that it learns the association between the prompt and the target label, embedding a backdoor without introducing external triggers and thus increasing stealth; ProAttack primarily targets classification tasks. Instruction-triggered attacks manipulate instruction data used during fine-tuning to induce erroneous behavior: Xu et al. [36] show that an attacker can implant a backdoor by inserting a relatively small amount of malicious instruction tokens (≈1,000 tokens). Demonstration-triggered attacks alter in-context examples (demonstrations) to steer model outputs: Wang et al. [37] introduce advICL, which perturbs only the examples in the prompt to induce failures. advICL builds on the TextAttack framework [38], applying optimized word- or character-level perturbations for each example to maximize attack success.

Taken together, these works indicate that malicious backdoors can be implanted in LLMs via inputs, prompts, instructions, or demonstrations, enabling stealthy malicious behavior while preserving nominal performance. Such backdoor threats undermine model reliability and security and impose increased requirements on defensive measures for practical deployments.

4 Attack Risks in the Inference Phase

The inference phase of LLMs faces three main categories of attack risks: jailbreak attacks, prompt injection attacks, and model extraction attacks. Jailbreak and prompt injection attacks exploit crafted prompts to manipulate model behavior, representing new attack paradigms that have emerged alongside the rise of LLMs. In contrast, model extraction attacks extend traditional adversarial strategies from earlier deep learning models.



Figure 3: An example for jailbreaking.

4.1 Jailbreak Attacks

With the widespread adoption of LLMs, their security and reliability have become critical concerns. Among these, value alignment and risks associated with content safety represent key challenges in LLM development. During model design and training, it is essential to establish robust safety mechanisms to ensure that models respect human values and avoid propagating misinformation or bias. However, as model complexity and functionality grow, LLMs face increasing risks from jailbreak attacks. Such attacks can circumvent or even disable safety mechanisms without needing knowledge of the model's architecture or parameters, resulting in unsafe or unintended outputs, as in Figure 3.

Jailbreak attacks of LLMs can be broadly categorized into manually designed, model-generated, and adversarial optimization-based approaches [39]. The manually designed category includes both classical attack methods originating from the Internet and subsequent attacks crafted by researchers based on the intrinsic mechanisms of LLMs. These attacks often demonstrate strong effectiveness against advanced LLMs; however, each valid prompt requires considerable human effort. Wei et al. [39] innovatively proposed two jailbreak failure modes that may undermine the effectiveness of safety training. The first is Competing Objectives, which exploits conflicts between the model's inherent capabilities and its safety constraints to design jailbreak prompts. The second is Mismatched Generalization, which arises when safety training fails to generalize to domains where the model already possesses strong capabilities, such as prompts designed using low-resource languages [40] or Base64 encoding [41]. In subsequent experiments, Wei et al. [41] evaluated ChatGPT-4, Claude v1.3, and other models, and found that jailbreak prompts developed under these two failure modes achieved significantly higher success rates than earlier manually designed prompts.

Furthermore, Liu et al. [42] systematically evaluated jailbreak prompts collected from the Internet on ChatGPT-3.5 Turbo and ChatGPT-4. They classified these prompts into three categories—pretending, attention shifting, and privilege escalation—covering ten attack patterns, including character role play, translation, and sudo mode et al., as in Table 1. Each prompt was tested across five rounds for every query, resulting in a total of 31,200 evaluations. Liu et al. [42] concluded that pretense-based prompts currently represent the most prevalent and effective type of jailbreak attack.

Table 1: Three common types of jailbreak prompts.

Name	Pattern
Pretending	Character Role Play
	Assumed Responsibility
	Research Experiment
Attention Shifting	Text Continuation
	Logical Reasoning
	Program Execution
	Translation
Privilege Escalation	Superior Model
	Sudo Mode
	Simulate Jailbreaking

The model-generated class of jailbreak attacks emphasizes automation and efficiency in the attack pipeline. Deng et al. [43] applied a large set of jailbreak prompts to multiple LLMs and analyzed them in conjunction with existing defense strategies, proposing a novel framework called MASTERKEY. This framework leverages temporal feature analysis to examine model defenses and generate automated, targeted jailbreak prompts. Specifically, they probed the responses of target models using various prompts and incorporated techniques inspired by SQL injection to expose the internal mechanisms of current defense systems. Deng et al. [43] observed that state-of-the-art interactive LLMs employ not only internal safety alignment but also external defense mechanisms, such as output filtering, input inspection, and dynamic monitoring of generation processes. Building on this insight, they constructed a specialized jailbreak prompt dataset to train "jailbreak agents," whose capabilities were further enhanced through reinforcement learning.

The adversarial optimization class of jailbreak attacks seeks to adapt methods from traditional adversarial machine learning to

generate jailbreak prompts for LLMs. These approaches typically require continuous optimization based on the model's internal information or responses and ultimately produce refined perturbation patterns—such as adversarial suffixes composed of special symbols or prompt rewrites—that can induce erroneous or harmful outputs. Zou et al. [44] introduced an attack method called Greedy Coordinate Gradient (GCG), which automatically generates adversarial suffixes containing potentially risky instructions by combining greedy search with gradient-based optimization. GCG operates by iteratively refining a subset of tokens in the input sequence to minimize an adversarial loss function. In each iteration, candidate replacement tokens for every modifiable position are selected from the top-k options ranked by the negative gradient of the loss function. These candidates are substituted one by one and evaluated, and the replacement that yields the lowest loss is retained to update the sequence. After multiple iterations, GCG produces adversarial suffixes capable of reliably inducing LLMs to generate specific malicious outputs.

The GCG method is conceptually rooted in earlier manually designed prefix injection jailbreak prompts, in which the model is instructed to begin its response with a predefined token sequence (e.g., "Sure, here is . . ."), thereby steering it toward unsafe or undesirable behaviors. Although manually designed, model-generated, and adversarial optimization-based jailbreak attacks differ in their strategies, they all exploit the inherent sensitivity of LLMs to input prompts in order to deviate outputs from expected safe responses. Manually designed attacks rely on human ingenuity to craft effective prompts; model-generated attacks employ automated pipelines to systematically uncover vulnerabilities; and adversarial optimization attacks introduce perturbations that enhance stealth and transferability. Collectively, these approaches highlight the structural vulnerabilities of current LLM security mechanisms and underscore that, alongside the pursuit of enhanced model capabilities, strengthening defenses against jailbreak attacks has become a critical and unavoidable challenge in LLM development.

4.2 Prompt Injection Attacks

LLMs have now been widely integrated into various applications. Users can interact with these models through conversational interfaces, leveraging their capabilities in information retrieval, document summarization, and function execution to accomplish specific tasks. However, during this process, adversaries can inject malicious prompts that cause the model to perform unauthorized or unintended operations, leading to security risks such as data theft and resource exhaustion. This type of attack is referred to as a prompt injection attack.

Perez et al. [45] were the first to introduce the concepts of goal hijacking and prompt leaking within the context of prompt injection. Goal hijacking attacks redirect the model away from the objective of the original prompt by introducing adversarial instructions, thereby achieving attacker-defined objectives such as printing specific phrases or executing illegal commands. Prompt leaking attacks, in contrast, involve crafting inputs that induce the model to expose its system prompt, potentially revealing sensitive configuration information within applications, as in Figure 4. Perez et al. [45] further proposed an alignment framework based on masked iterative adversarial prompt composition, demonstrating that ChatGPT-3 is vulnerable to even simple, human-constructed malicious inputs. Their experiments showed that attackers with limited technical expertise can exploit the inherent stochasticity of LLMs to trigger such long-tail risks with relative ease.

Liu et al. [46] analyzed the complexity and impact of prompt injection attacks in real-world applications that integrate LLMs. Through an exploratory study of 36 LLM-integrated applications, they identified practical limitations of existing attack strategies and, drawing on concepts from traditional web-injection attacks, proposed a black-box prompt injection framework, referred to as HOUYI. HOUYI consists of three fundamental components: (1) easily integrated pre-constructed prompts, (2) injection prompts that induce context partition, and (3) malicious payloads that realize attacker objectives. The study both exposes the latent risks of prompt injection and indicates practical directions for developing mitigation strategies.

Greshake et al. [47] further introduced the concept of indirect prompt injection. They observed that many LLM-integrated systems struggle to distinguish between data content and instruction boundaries, which enables adversaries to manipulate systems indirectly by embedding malicious prompts in externally retrievable sources. For example, in search-driven workflows, an attacker may inject prompts into web pages and leverage search engine optimization (SEO) to increase the visibility of the "poisoned" page; alternatively, adversaries may supply documents (e.g., text, tables, or images) that contain embedded prompts to downstream applications. By directly or indirectly controlling input content, prompt injection attacks can bypass current safeguards and pose a substantial threat to the trustworthiness and security of LLM-enabled applications. Consequently, there is an urgent need for systematic defenses such as rigorous input validation, strict context isolation, provenance verification, and retrieval sanitization.

4.3 Model Extraction Attacks

Model extraction attacks involve querying a target model to exfiltrate critical artifacts such as architecture, parameter weights, and hyperparameter configurations. These attacks typically target LLM providers that expose services via network APIs. By systematically collecting input-output pairs through public interfaces, adversaries can reconstruct the target model or approximate its functional behavior, causing intellectual property disclosure and economic loss for providers. Moreover, reconstructed surrogates can be leveraged to generate adversarial examples against the original model, thereby broadening the attack surface.

Li et al. [48] observed that the intellectual-property value of commercial LLMs makes them attractive targets for model extraction attacks; however, reconstructing models of comparable scale and performance remains costly. Consequently, their work focused on how attackers might extract specialized, code-related capabilities from LLMs. Specifically, the authors systematically evaluated the effectiveness of various query strategies—zero-shot, in-context, and chain-of-thought—for capability extraction across multiple code tasks, and they proposed response-filtering mechanisms to improve the quality of imitation training. Experimental results indicate that,



Figure 4: Illustration of how goal hijacking and prompt leaking compromise model instructions, with the attacker aiming to alter the original prompt's intended objective.

under realistic query budgets, an adversary can train a medium-sized surrogate model that effectively reproduces the target LLM's proprietary behaviors on code tasks.

Gudibande et al. [49] investigated extraction effectiveness across models of different scales. They selected open-source foundational models of varying sizes, fine-tuned them on diverse data sources and imitation datasets of different volumes, and assessed the reconstructions via human evaluation, GPT-4 automated scoring, and standard NLP benchmarks. The results show that reconstructed models may converge with targets in conversational style and instruction following, yet substantial gaps persist in factual accuracy, coding proficiency, and complex-task resolution. These findings suggest that current model extraction techniques remain limited when applied to ultra-large LLMs.

In practice, commercial APIs impose constraints such as query pricing, rate limiting, and output truncation. These measures increase monetary costs, prolong data collection, and reduce output completeness, thereby raising the difficulty of model extraction without eliminating the risk. Defensive techniques such as differential privacy and model watermarking have also been explored, but they often incur performance degradation or computational overhead, highlighting a trade-off between security and usability.

5 Defense Strategies

Defensive strategies against threats during the training and inference phases of LLMs are generally divided into offline and online categories, both of which can be applied to mitigate different types of attacks. The following sections introduce representative methods commonly employed in each category.

5.1 Offline Defenses

Offline defenses focus on securing data collection and model training and primarily involve three strategies: data preprocessing, adversarial training, and safety alignment. Data preprocessing aims to reduce the risk of data poisoning and backdoor insertion by cleaning and filtering the training corpus to remove malicious, toxic, or anomalous samples. Aghakhani et al. [50] show that discarding near-duplicate poisoned samples, known triggers, and malicious payloads can effectively mitigate TROJANPUZZLE-like attacks. Consequently, systematic data cleansing helps eliminate anomalous and suspicious entries from the training set.

Adversarial training incorporates adversarial examples into the training pipeline to improve robustness against jailbreak, prompt injection, and other adversarial attacks. Liu et al. [51] proposed ALUM and systematically studied adversarial training during both the training and fine-tuning phases of LLMs. The authors note that conventional adversarial training often degrades generalization; by applying perturbations in the embedding space and regularizing the training objective, ALUM substantially improves both generalization and robustness across multiple NLP tasks.

Safety alignment is typically achieved during the fine-tuning stage via SFT and RLHF. These methods steer LLMs to conform to human output preferences and constrain the generation of harmful or illegal content. SFT further refines a pre-trained model using high-quality human-annotated examples, thereby improving task-level consistency and safety. RLHF, applied after initial training, uses human preference signals to train a reward (preference) model; this reward model is subsequently employed to optimize the policy via reinforcement learning, aligning model outputs with human judgments. Bai et al. [52] proposed Constitutional AI (CAI), which replaces direct human adjudication with a set of explicit principles (a "constitution") to govern model behavior. CAI proceeds in two stages. First, during a supervised learning phase, the model performs self-critique and revision of its outputs according to the constitution, and the revised outputs are used for fine-tuning. Subsequently, in a reinforcement learning phase, the model evaluates candidate outputs against its constitution; a preference model is trained from these evaluations and used as the reward signal to further optimize the policy model. Experimental results indicate that CAI can improve model harmlessness and utility while reducing reliance on human supervision.

In summary, offline defenses constrain model security at different levels. Data preprocessing acts directly on training data by removing suspicious samples to mitigate poisoning or backdoor risks. These methods are simple and low-cost but rely heavily on anomaly detection and may miss sophisticated attacks. In contrast, adversarial training incorporates adversarial examples during training to enhance robustness, offering partial protection against jailbreak and prompt injection attacks, though it increases computational cost and may degrade performance on benign inputs.

Safety alignment modifies model behavior through mechanisms such as SFT, RLHF, or CAI, effectively reducing harmful outputs but depending strongly on annotation quality and guideline design, with potential bias risks. Overall, offline defenses provide systematic protection during data and training stages but face trade-offs among robustness, computational cost, and scalability.

5.2 Online Defenses

Online defenses mitigate malicious prompts that could induce dangerous model behaviors by inspecting and intervening on model inputs and outputs. They primarily encompass two mechanisms: prompt preprocessing and prompt screening.

Prompt preprocessing seeks to reduce the effectiveness of adversarial prompt attacks by rewriting or perturbing user inputs. Jain et al. [53] proposed two strategies: paraphrase and retokenization. Paraphrase uses generative models to rephrase original prompts, preserving benign intent while disrupting adversarial suffixes; however, this approach can cause some degradation in model performance. Retokenization alters token segmentation to disturb adversarial patterns, thereby lowering attack success rates while preserving the expressive capacity of benign text.

Prompt screening blocks adversarial attack paths during inference by detecting and filtering malicious input components. Kumar et al. [54] presented the Erase-and-Check framework, designed to deliver verifiable protection against adversarial prompts. Based on the "harm-propagation" principle, the method performs token-level erasures to generate multiple subsequences that are jointly evaluated by safety classifiers (e.g., Llama 2, DistilBERT). If either a subsequence or the original prompt is classified as harmful, the entire input is flagged as dangerous. Experimental results demonstrate that Erase-and-Check exhibits strong robustness against adversarial suffix, insertion, and injection attacks.

Overall, online defenses focus on the inference stage by disrupting adversarial prompts through preprocessing and screening. Prompt preprocessing, such as paraphrase or retokenization, can quickly neutralize adversarial suffixes and is easy to deploy, but may inadvertently distort the semantics of benign instructions. Prompt screening, analogous to data preprocessing, depends on accurate detection of malicious inputs and may introduce latency and false positives.

6 Future Work

LLMs have evolved from single-text processing to multimodal tasks involving speech, images, and video, with security threats becoming increasingly complex. For instance, multimodal models may be exposed to composite jailbreak attacks that combine text and images or to cross-modal prompt injection attacks, both of which pose new challenges to security defense. Moreover, model risks are no longer confined to adversarial attacks but also encompass a range of external risks, such as misuse for spreading misinformation, generating instructions for hazardous items, or producing inaccurate and unreliable outputs in critical domains such as healthcare and education, thereby creating real-world safety concerns.

Therefore, future research should proceed along multiple dimensions, including algorithm optimization, security mechanism design, and usage scenario regulation, to establish a human-centered, controllable, and trustworthy LLM system. In this process, developing standardized benchmarks and reproducible evaluation frameworks will be essential to fair comparisons and systematic assessments of security capabilities across different attack conditions and application scenarios, thereby providing verifiable reference standards for subsequent research and defense practices. This requires not only the continuous evolution of offensive and defensive techniques but also coordinated progress in legal, ethical, and governance frameworks to ensure security across the lifecycle of LLMs.

7 Conclusion

In this paper, the fundamental concepts of LLMs and their associated security risks are first presented. Major attack vectors—including data poisoning, backdoor insertion, jailbreak, and prompt injection—are then reviewed across the critical phases of model training and inference. From a lifecycle perspective, current mainstream offline and online defense strategies are summarized. Finally, a forward-looking discussion is provided on the secure development of LLMs based on the current state of research.

References

[1] L. Qin *et al.*, "Large Language Models Meet NLP: A Survey," arXiv: 2405.12819, 2024.

[2] J. Zhang, P. Nie, Junyi Jessy Li, and Milos Gligoric, "Multilingual Code Co-evolution using Large Language Models," in Proc of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2023.

[3] L. Wang *et al.*, "A survey on large language model based autonomous agents," Frontiers of Computer Science, vol. 18, no. 6, Mar. 2024.

[4] W. Du, J. Xue, W. Guo, X. Yang, Y. Fu and Y. Wang, "A Systematic Survey on Black-Box Attacks in Large Language Models Within Communication Networks," in IEEE Network, vol. 39, no. 5, 2025.

[5] J. K. Joseph, E. Daniel, V. Kathiresan and M. M.A.P, "Prompt Injection in Large Language Model Exploitation: A Security Perspective," 2025 International Conference on Electronics, Computing, Communication and Control Technology, Bengaluru, India, 2025, pp. 1-8.

[6] T. Cui *et al.*, "Risk Taxonomy, Mitigation, and Assessment Benchmarks of Large Language Model Systems," arXiv: 2401.05778, Jan. 11, 2024.

[7] Q. Liu *et al.*, "Mitigating Backdoor Threats to Large Language Models: Advancement and Challenges," 2024 60th Annual Allerton Conference on Communication, Control, and Computing, Urbana, IL, USA, 2024, pp. 1-8.

[8] D. A. Alber *et al.*, "Medical large language models are vulnerable to data poisoning attacks," Nature Medicine, vol. 31, no. 2, pp. 618–626, 2025.

[9] R. Jiao *et al.*, "Can We Trust Embodied Agents? Exploring Backdoor Attacks against Embodied LLM-Based Decision-Making Systems," ICLR, 2025.

[10] Z. Jin, S. Liu, H. Li, X. Zhao, and H. Qu, "JailbreakHunter: A visual analytics approach for jailbreak prompts discovery from large-scale human-llm conversational datasets," IEEE Transactions on Visualization and Computer Graphics, vol. 31, Art. no. 10, 2025.

[11] S. Nabavirazavi, S. Zad and S. S. Iyengar, "Evaluating the Universality of "Do Anything Now" Jailbreak Prompts on Large Language Models," 2025 IEEE 15th Annual Computing and Communication Workshop and Conference, Las Vegas, NV, USA, 2025, pp. 00691-00696.

[12] L. Lv *et al.*, "AdaPPA: Adaptive Position Pre-Fill Jailbreak Attack Approach Targeting LLMs," 2025 IEEE International Conference on Acoustics, Speech and Signal Processing, Hyderabad, India, 2025, pp. 1-5.

[13] H. J. Branch *et al.*, "Evaluating the Susceptibility of Pre-Trained Language Models via Handcrafted Adversarial Examples," arXiv: 2209.02128, Sep. 2022.

[14] J. Dagdelen *et al.*, "Structured information extraction from scientific text with large language models," Nature Communications, vol. 15, no. 1, p. 1418, 2024.

[15] Z. Hu *et al.*, "Token-Level Adversarial Prompt Detection Based on Perplexity Measures and Contextual Information," arXiv: 2311.11509, 2023.

[16] G. Alon and M. Kamfonas, "Detecting Language Model Attacks with Perplexity," arXiv: 2308.14132, 2023.

[17] V. R. Patil, P. Hase, and M. Bansal, "Can Sensitive Information Be Deleted From LLMs? Objectives for Defending Against Extraction Attacks," ICLR, 2024.

[18] T. Brown *et al.*, "Language models are few-shot learners," in NeurIPS 2020, Curran Associates, Inc., 2020, pp. 1877–1901.

[19] H. Touvron *et al.*, "LLaMA: Open and Efficient Foundation Language Models," arXiv: 2302.13971, Feb. 2023.

[20] H. Touvron *et al.*, "Llama 2: Open Foundation and Fine-Tuned Chat Models," arXiv: 2307.09288, Jul. 19, 2023.
[21] A. Vaswani *et al.*, "Attention is all you need," in NeurIPS, 2017.
[22] OpenAI, "Model index for researchers," 2023. https://platform.openai.com/%20docs/model-index-for-researchers (accessed Apr. 21, 2025).
[23] J. Kaplan *et al.*, "Scaling Laws for Neural Language Models," arXiv:2001.08361, Jan. 2020.
[24] J. Lee, "InstructPatentGPT: training patent language models to follow instructions with human feedback," Artificial Intelligence and Law, 2024.
[25] C. Zhou *et al.*, "LIMA: Less is more for alignment," in Neural Information Processing Systems, 2023.
[26] X. Zhang, Z. Zhang, S. Ji, and T. Wang, "Trojaning language models for fun and profit," in IEEE European Symposium on Security and Privcy, 2021, pp. 179–197.
[27] R. Schuster, C. Song, Eran Tromer, and Vitaly Shmatikov, "You autocomplete me: Poisoning vulnerabilities in neural code completio," in 30th USENIX Security Symposium, 2021, pp. 1559–1575.
[28] H. Aghakhani *et al.*, "TrojanPuzzle: Covertly poisoning code-suggestion models," in IEEE Symposium on Security and Privacy, San Francisco, CA, USA, 2024, pp. 1122–1140.
[29] A. Wan, E. Wallace, S. Shen, and D. Klein, "Poisoning language models during instruction tuning," in Proc of the 40th International Conference on Machine Learning, PMLR, 2023, pp. 35413–35425.
[30] M. Shu, *et al.*, "On the exploitability of instruction tuning," in NeurIPS, 2023, pp. 61836–61856.
[31] T. Gu, *et al.*, "BadNets: Identifying Vulnerabilities in the Machine Learning Model Supply Chain," arXiv: 1708.06733v2, Mar. 2019.
[32] S. Garg, *et al.*, "Can adversarial weight perturbations inject neural backdoors," arXiv: 2008.01761v2, Sep. 2020.
[33] H. Yang, *et al.*, "A comprehensive overview of backdoor attacks in large language models within communication networks," Institute of Electrical and Electronics Engineers Network, vol. 38, Art. no. 6, 2024.
[34] J. Shi, *et al.*, "BadGPT: Exploring Security Vulnerabilities of ChatGPT via Backdoor Attacks to InstructGPT," in Proc of the Network and Distributed System Security Symposium, 2023.
[35] S. Zhao, J. Wen, A. Luu, J. Zhao, and J. Fu, "Prompt as Triggers for Backdoor Attack: Examining the Vulnerability in Language Models," in Proc of the 2023 Conference on Empirical Methods in Natural Language Processing, 2023.
[36] J. Xu, M. D. Ma, F. Wang, C. Xiao, and M. Chen, "Instructions as Backdoors: Backdoor Vulnerabilities of Instruction Tuning for Large Language Models," in Proc of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Mexico City, Mexico, 2024.
[37] J. Wang, Z. Liu, K. H. Park, M. Chen, and C. Xiao, "Adversarial Demonstration Attacks on Large Language Models," arXiv: 2305.14950, May 2023.
[38] J. Morris, E. Lifland, J. Y. Yoo, J. Grigsby, D. Jin, and Y. Qi, "TextAttack: A framework for adversarial attacks, data augmentation, and adversarial training in NLP," in Proc of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, 2020, pp. 119–126.
[39] L. Nan, D. Yidong, J. Haoyu, N. Jiafei, and Y. Ping, "Jailbreak Attack for Large Language Models: A Survey," Journal of Computer Research and Development, vol. 61, Art. no. 5, 2024.
[40] A. Wei, *et al.*, "Jailbroken: How does LLM safety training fail?," in Neural Information Processing Systems, Curran Associates, Inc., 2023, pp. 80079–80110.
[41] Z.-X. Yong, C. Menghini, and S. H. Bach, "Low-Resource Languages Jailbreak GPT-4," arXiv: 2310.02446, 2023.
[42] Y. Liu *et al.*, "Jailbreaking ChatGPT via Prompt Engineering: An Empirical Study," arXiv: 2305.13860, 2023.
[43] G. Deng *et al.*, "Jailbreaker: Automated Jailbreak Across Multiple Large Language Model Chatbots," arXiv: 2307.08715, 2023.
[44] A. Zou, *et al.*, "Universal and Transferable Adversarial Attacks on Aligned Language Models," arXiv: 2307.15043, 2023.
[45] F. Perez and I. Ribeiro, "Ignore Previous Prompt: Attack Techniques For Language Models," arXiv: 2211.09527v1, Nov. 2022.
[46] Y. Liu *et al.*, "Prompt Injection attack against LLM-integrated Applications," arXiv: 2306.05499v2, 2024.
[47] K. Greshake, *et al.*, "Not what you've signed up for: Compromising real-world LLM-Integrated applications with indirect prompt injection," in AISec'23, 2023.
[48] Z. Li *et al.*, "On extracting specialized code abilities from large language models: A feasibility study," in Proc of the IEEE/ACM 46th International Conference on Software Engineering, Lisbon, 2024.
[49] A. Gudibande *et al.*, "The False Promise of Imitating Proprietary LLMs," arXiv: 2305.15717, 2023.
[50] H. Aghakhani *et al.*, "TrojanPuzzle: Covertly poisoning code-suggestion models," in IEEE S&P, 2024, pp. 1122–1140.
[51] X. Liu *et al.*, "Adversarial Training for Large Neural Language Models," arXiv: 2004.08994v2, 2020.
[52] Y. Bai *et al.*, "Constitutional AI: Harmlessness from AI Feedback," arXiv:2212.08073v1, 2022.
[53] N. Jain *et al.*, "Baseline Defenses for Adversarial Attacks Against Aligned Language Models," arXiv: 2309.00614, 2023.
[54] A. Kumar, C. Agarwal, S. Srinivas, A. J. Li, S. Feizi, and H. Lakkaraju, "Certifying LLM Safety against Adversarial Prompting," arXiv: 2309.02705v4, 2025.