



Trending Now DSA Data Structures Algorithms Interview Preparation Data Science T

Read Discuss

Iterator Pattern is a relatively simple and frequently used design pattern. There are a lot of data structures/collections available in every language. Each collection must provide an iterator that lets it iterate through its objects. However while doing so it should make sure that it does not expose its implementation. Suppose we are building an application that requires us to maintain a list of notifications. Eventually, some part of your code will require to iterate over all notifications. If we implemented your collection of notifications as array you would iterate over them as:

```
// If a simple array is used to store notifications
for (int i = 0; i < notificationList.length; i++)
    Notification notification = notificationList[i]);

// If ArrayList is Java is used, then we would iterate
// over them as:
for (int i = 0; i < notificationList.size(); i++)
    Notification notification =
    (Notification)notificationList.get(i);
```

And if it were some other collection like set, tree etc. way of iterating would change slightly. Now, what if we build an iterator that provides a generic way


We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

**Got It !**

```
// Create an iterator
Iterator iterator = notificationList.createIterator();

// It wouldn't matter if list is Array or ArrayList or
// anything else.
while (iterator.hasNext())
{
    Notification notification = iterator.next();
}
```

Iterator pattern lets us do just that. Formally it is defined as below: *The iterator pattern provides a way to access the elements of an aggregate object without exposing its underlying representation. Class Diagram:*




Here

we have a common interface **Aggregate** for client as it decouples it from the implementation of your collection of objects. The **ConcreteAggregate** implements `createIterator()` that returns iterator for its collection. Each **ConcreteAggregate**'s responsibility is to instantiate a **ConcreteIterator** that can iterate over its collection of objects. The iterator interface provides a set of

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

bar in our application that displays all the notifications which are held in a notification collection. NotificationCollection provides an iterator to iterate over its elements without exposing how it has implemented the collection (array in this case) to the Client (NotificationBar). The class diagram would



be:

Below is the Java implementation of the same:

## Java

```
// A Java program to demonstrate implementation
// of iterator pattern with the example of
// notifications
```

```
// A simple Notification class
```

```
class Notification
{
    // To store notification message
    String notification;

    public Notification(String notification)
    {
        this.notification = notification;
    }

    public String getNotification()
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

// Collection interface
interface Collection
{
    public Iterator createIterator();
}

// Collection of notifications
class NotificationCollection implements Collection
{
    static final int MAX_ITEMS = 6;
    int numberOfItems = 0;
    Notification[] notificationList;

    public NotificationCollection()
    {
        notificationList = new Notification[MAX_ITEMS];

        // Let us add some dummy notifications
        addItem("Notification 1");
        addItem("Notification 2");
        addItem("Notification 3");
    }

    public void addItem(String str)
    {
        Notification notification = new Notification(str);
        if (numberOfItems >= MAX_ITEMS)
            System.err.println("Full");
        else
        {
            notificationList[numberOfItems] = notification;
            numberOfItems = numberOfItems + 1;
        }
    }

    public Iterator createIterator()
    {
        return new NotificationIterator(notificationList);
    }
}

// We could also use Java.Util.Iterator
interface Iterator

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

        // returns the next element
        Object next();
    }

    // Notification iterator
    class NotificationIterator implements Iterator
    {
        Notification[] notificationList;

        // maintains curr pos of iterator over the array
        int pos = 0;

        // Constructor takes the array of notificationList are
        // going to iterate over.
        public NotificationIterator (Notification[] notificationList)
        {
            this.notificationList = notificationList;
        }

        public Object next()
        {
            // return next element in the array and increment pos
            Notification notification = notificationList[pos];
            pos += 1;
            return notification;
        }

        public boolean hasNext()
        {
            if (pos >= notificationList.length ||
                notificationList[pos] == null)
                return false;
            else
                return true;
        }
    }

    // Contains collection of notifications as an object of
    // NotificationCollection
    class NotificationBar
    {
        NotificationCollection notifications;
    }

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

    }

    public void printNotifications()
    {
        Iterator iterator = notifications.createIterator();
        System.out.println("-----NOTIFICATION BAR-----");
        while (iterator.hasNext())
        {
            Notification n = (Notification)iterator.next();
            System.out.println(n.getNotification());
        }
    }
}

// Driver class
class Main
{
    public static void main(String args[])
    {
        NotificationCollection nc = new NotificationCollection();
        NotificationBar nb = new NotificationBar(nc);
        nb.printNotifications();
    }
}

```

Output:

```

-----NOTIFICATION BAR-----
Notification 1
Notification 2
Notification 3

```

Notice that if we would have used ArrayList instead of Array there will not be any change in the client (notification bar) code due to the decoupling achieved by the use of iterator interface. **Further Read** – [Iterator Method in Python](#)

**References:** [Head First Design Patterns](#)

This article is contributed by **Sulabh Kumar**. If you like GeeksforGeeks and

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Last Updated : 08 Apr, 2022

12

## Similar Reads

1. Design Patterns in Java - Iterator Pattern

---
2. Implementing Iterator pattern of a single Linked List

---
3. Command Pattern

---
4. Observer Pattern | Set 1 (Introduction)

---
5. Observer Pattern | Set 2 (Implementation)

---
6. Singleton Design Pattern | Implementation

---
7. Decorator Pattern | Set 1 (Background)

---
8. The Decorator Pattern | Set 2 (Introduction and Design)

---
9. Decorator Pattern | Set 3 (Coding the Design)

---
10. Strategy Pattern | Set 2 (Implementation)

[Previous](#)

[Next](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

## Vote for difficulty

Current difficulty : [Medium](#)

[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)

Improved By : [Shraddhesh Bhandari](#), [creatsiv](#), [simmytarika5](#)

Article Tags : [Design Pattern](#)

[Improve Article](#)[Report Issue](#)

A-143, 9th Floor, Sovereign Corporate Tower, Sector-136, Noida, Uttar Pradesh - 201305

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

## Company

[About Us](#)[Careers](#)[In Media](#)[Contact Us](#)[Terms and Conditions](#)[Privacy Policy](#)[Copyright Policy](#)

THE GECKS FOR GECKS

## Explore

[Job Fair For Students](#)[POTD: Revamped](#)[Python Backend LIVE](#)[Android App Development](#)[DevOps LIVE](#)[DSA in JavaScript](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).



## Languages

Python  
Java  
C++  
GoLang  
SQL  
R Language  
Android Tutorial

## Data Structures

Array  
String  
Linked List  
Stack  
Queue  
Tree  
Graph

## Algorithms

Sorting  
Searching  
Greedy  
Dynamic Programming  
Pattern Searching  
Recursion  
Backtracking

## Web Development

HTML  
CSS  
JavaScript  
Bootstrap  
ReactJS  
AngularJS  
NodeJS

## Computer Science

GATE CS Notes  
Operating Systems  
Computer Network  
Database Management System  
Software Engineering  
Digital Logic Design  
Engineering Maths

## Python

Python Programming Examples  
Django Tutorial  
Python Projects  
Python Tkinter  
OpenCV Python Tutorial  
Python Interview Question

## Data Science & ML

## DevOps

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Maths For Machine Learning

Pandas Tutorial

NumPy Tutorial

NLP Tutorial

Deep Learning Tutorial

Kubernetes

Azure

GCP

## Competitive Programming

Top DSA for CP

Top 50 Tree Problems

Top 50 Graph Problems

Top 50 Array Problems

Top 50 String Problems

Top 50 DP Problems

Top 15 Websites for CP

## Interview Corner

Company Preparation

Preparation for SDE

Company Interview Corner

Experienced Interview

Internship Interview

Competitive Programming

Aptitude

## Commerce

Accountancy

Business Studies

Microeconomics

## System Design

What is System Design

Monolithic and Distributed SD

Scalability in SD

Databases in SD

High Level Design or HLD

Low Level Design or LLD

Top SD Interview Questions

## GfG School

CBSE Notes for Class 8

CBSE Notes for Class 9

CBSE Notes for Class 10

CBSE Notes for Class 11

CBSE Notes for Class 12

English Grammar

## UPSC

Polity Notes

Geography Notes

History Notes

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

UPSC Previous Year Papers

## SSC/ BANKING

SSC CGL Syllabus

SBI PO Syllabus

SBI Clerk Syllabus

IBPS PO Syllabus

IBPS Clerk Syllabus

Aptitude Questions

SSC CGL Practice Papers

## Write & Earn

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship

@geeksforgeeks , Some rights reserved

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).