

Contents

1 Basic	1	8.20Half Plane Intersection	21
1.1 Shell Script	1	8.21Minkowski Sum	21
1.2 Default Code	1	8.22Delaunay Triangulation	21
1.3 Increase Stack Size	1	8.23Triangulation Voronoi	22
1.4 Debug Macro	1		
1.5 Pragma / FastIO	1		
1.6 Divide*	2		
2 Data Structure	2	9 Else	22
2.1 Leftist Tree	2	9.1 Bit Hack	22
2.2 Splay Tree	2	9.2 Dynamic Programming Condition	22
2.3 Link Cut Tree	2	9.2.1 Totally Monotone (Concave/Convex)	22
2.4 Treap	3	9.2.2 Monge Condition (Concave/Convex)	22
2.5 2D Segment Tree*	3	9.2.3 Optimal Split Point	22
2.6 Range Set*	4	9.3 Slope Trick	22
2.7 vEB Tree*	4	9.4 Manhattan MST	23
		9.5 Dynamic MST	23
3 Flow / Matching	4	9.6 ALL LCS	24
3.1 Dinic	4	9.7 Hilbert Curve	24
3.2 Min Cost Max Flow	5	9.8 Pbds	24
3.3 Kuhn Munkres	5	9.9 Random	24
3.4 SW Min Cut	6	9.10Smawk Algorithm	24
3.5 Gomory Hu Tree	6	9.11Matroid Intersection	24
3.6 Blossom	6	9.12Python Misc	25
3.7 Weighted Blossom	7		
3.8 Flow Model	8		
4 Graph		1 Basic	
4.1 Heavy-Light Decomposition	9	1.1 Shell Script	
4.2 Centroid Decomposition	9	#!/usr/bin/env bash	
4.3 Edge BCC	9	g++ -std=c++17 -DABS -Wall -Wextra -Wshadow \$1.cpp -o	
4.4 Block Cut Tree	9	\$1 && ./\$1	
4.5 SCC / 2SAT	9	for i in {A..J}; do cp tem.cpp \$i.cpp; done;	
4.6 Virtual Tree	9		
4.7 Directed MST	10	1.2 Default Code	
4.8 Dominator Tree	10	#include <bits/stdc++.h>	
		using namespace std;	
5 String	10	typedef long long ll;	
5.1 Aho-Corasick Automaton	10	#define pb push_back	
5.2 KMP Algorithm	11	#define pii pair<int, int>	
5.3 Z Algorithm	11	#define all(a) a.begin(), a.end()	
5.4 Manacher	11	#define sz(a) ((int)a.size())	
5.5 Suffix Array	11		
5.6 SAIS	11	1.3 Increase Stack Size	
5.7 Suffix Automaton	12	const int size = 256 << 20;	
5.8 Minimum Rotation	12	register long rsp asm("rsp");	
5.9 Palindrome Tree	12	char *p = (char*)malloc(size) + size, *bak = (char*)rsp	
5.10Main Lorentz	12	;	
6 Math	13	__asm__("movq %0, %%rsp\n"::"r"(p));	
6.1 Miller Rabin / Pollard Rho	13	// main	
6.2 Ext GCD	13	__asm__("movq %0, %%rsp\n"::"r"(bak));	
6.3 PiCount	13		
6.4 Linear Function Mod Min	13	1.4 Debug Macro	
6.5 Determinant	14	void db() {cout << endl;}	
6.6 Floor Sum	14	template <typename T, typename ...U> void db(T i, U ...	
6.7 Quadratic Residue	14	j) {	
6.8 Simplex	14	cout << i << ' ', db(j...);	
6.9 Berlekamp Massey	15	}	
6.10Linear Programming Construction	15	#define test(x...) db("[" + string(x) + "]", x)	
6.11Euclidean	15		
6.12Theorem	15	1.5 Pragma / FastIO	
6.13Estimation	16	#pragma GCC optimize("Ofast,inline,unroll-loops")	
6.14General Purpose Numbers	16	#pragma GCC target("bmi,bmi2,lzcnt,popcnt,avx2")	
6.15Tips for Generating Function	16	#include<unistd.h>	
7 Polynomial	16	char OB[65536]; int OP;	
7.1 Number Theoretic Transform	16	inline char RC() {	
7.2 Fast Fourier Transform	16	static char buf[65536], *p = buf, *q = buf;	
7.3 Primes	16	return p == q && (q = (p = buf) + read(0, buf, 65536)	
7.4 Polynomial Operations	16) == buf ? -1 : *p++;	
7.5 Fast Linear Recursion	18	}	
7.6 Fast Walsh Transform	18	inline int R() {	
8 Geometry	18	static char c;	
8.1 Basic	18	while((c = RC()) < '0'); int a = c ^ '0';	
8.2 Heart	18	while((c = RC()) >= '0') a *= 10, a += c ^ '0';	
8.3 External Bisector	19	return a;	
8.4 Intersection of Segments	19	}	
8.5 Intersection of Circle and Line	19	inline void W(int n) {	
8.6 Intersection of Circles	19	static char buf[12], p;	
8.7 Intersection of Polygon and Circle	19	if (n == 0) OB[OP++]='0'; p = 0;	
8.8 Tangent Lines of Circle and Point	19	while (n) buf[p++] = '0' + (n % 10), n /= 10;	
8.9 Tangent Lines of Circles	19	for (--p; p >= 0; --p) OB[OP++] = buf[p];	
8.10Point In Convex	19	if (OP > 65520) write(1, OB, OP), OP = 0;	
8.11Point Segment Distance	19	}	
8.12Convex Hull	19		
8.13Convex Hull Distance	20		
8.14Minimum Enclosing Circle	20		
8.15Union of Circles	20		
8.16Union of Polygons	20		
8.17Polar Angle Sort	20		
8.18Rotating Caliper	20		
8.19Rotating SweepLine	21		

1.6 Divide*

```

ll divdown(ll a, ll b) {
    return a / b - (a < 0 && a % b);
}
ll divup(ll a, ll b) {
    return a / b + (a > 0 && a % b);
}
a / b < x -> divdown(a, b) + 1 <= x
a / b <= x -> divup(a, b) <= x
x < a / b -> x <= divup(a, b) - 1
x <= a / b -> x <= divdown(a, b)

```

2 Data Structure

2.1 Leftist Tree

```

struct node {
    ll rk, data, sz, sum;
    node *l, *r;
    node(ll k) : rk(0), data(k), sz(1), l(0), r(0), sum(k) {}
};
ll sz(node *p) { return p ? p->sz : 0; }
ll rk(node *p) { return p ? p->rk : -1; }
ll sum(node *p) { return p ? p->sum : 0; }
node *merge(node *a, node *b) {
    if (!a || !b) return a ? a : b;
    if (a->data < b->data) swap(a, b);
    a->r = merge(a->r, b);
    if (rk(a->r) > rk(a->l)) swap(a->r, a->l);
    a->rk = rk(a->r) + 1, a->sz = sz(a->l) + sz(a->r) + 1;
    a->sum = sum(a->l) + sum(a->r) + a->data;
    return a;
}
void pop(node *&o) {
    node *tmp = o;
    o = merge(o->l, o->r);
    delete tmp;
}

```

2.2 Splay Tree

```

struct Splay {
    int pa[N], ch[N][2], sz[N], rt, _id;
    ll v[N];
    Splay() {}
    void init() {
        rt = 0, pa[0] = ch[0][0] = ch[0][1] = -1;
        sz[0] = 1, v[0] = inf;
    }
    int newnode(int p, int x) {
        int id = _id++;
        v[id] = x, pa[id] = p;
        ch[id][0] = ch[id][1] = -1, sz[id] = 1;
        return id;
    }
    void rotate(int i) {
        int p = pa[i], x = ch[p][1] == i, gp = pa[p], c = ch[i][!x];
        sz[p] -= sz[i], sz[i] += sz[p];
        if (~c) sz[p] += sz[c], pa[c] = p;
        ch[p][x] = c, pa[p] = i;
        pa[i] = gp, ch[i][!x] = p;
        if (~gp) ch[gp][ch[gp][1] == p] = i;
    }
    void splay(int i) {
        while (~pa[i]) {
            int p = pa[i];
            if (~pa[p]) rotate(ch[pa[p]][1] == p ^ ch[p][1] == i ? i : p);
            rotate(i);
        }
        rt = i;
    }
    int lower_bound(int x) {
        int i = rt, last = -1;
        while (true) {
            if (v[i] == x) return splay(i), i;
            if (v[i] > x) {

```

```

                last = i;
                if (ch[i][0] == -1) break;
                i = ch[i][0];
            }
            else {
                if (ch[i][1] == -1) break;
                i = ch[i][1];
            }
        }
        splay(i);
        return last; // -1 if not found
    }
    void insert(int x) {
        int i = lower_bound(x);
        if (i == -1) {
            // assert(ch[rt][1] == -1);
            int id = newnode(rt, x);
            ch[rt][1] = id, ++sz[rt];
            splay(id);
        }
        else if (v[i] != x) {
            splay(i);
            int id = newnode(rt, x), c = ch[rt][0];
            ch[rt][0] = id;
            ch[id][0] = c;
            if (~c) pa[c] = id, sz[id] += sz[c];
            ++sz[rt];
            splay(id);
        }
    }
};

```

2.3 Link Cut Tree

```

// weighted subtree size, weighted path max
struct LCT {
    int ch[N][2], pa[N], v[N], sz[N], sz2[N], w[N], mx[N], _id;
    // sz := sum of v in splay, sz2 := sum of v in virtual subtree
    // mx := max w in splay
    bool rev[N];
    LCT() : _id(1) {}
    int newnode(int _v, int _w) {
        int x = _id++;
        ch[x][0] = ch[x][1] = pa[x] = 0;
        v[x] = sz[x] = _v;
        sz2[x] = 0;
        w[x] = mx[x] = _w;
        rev[x] = false;
        return x;
    }
    void pull(int i) {
        sz[i] = v[i] + sz2[i];
        mx[i] = w[i];
        if (ch[i][0])
            sz[i] += sz[ch[i][0]], mx[i] = max(mx[i], mx[ch[i][0]]);
        if (ch[i][1])
            sz[i] += sz[ch[i][1]], mx[i] = max(mx[i], mx[ch[i][1]]);
    }
    void push(int i) {
        if (rev[i]) reverse(ch[i][0]), reverse(ch[i][1]), rev[i] = false;
    }
    void reverse(int i) {
        if (!i) return;
        swap(ch[i][0], ch[i][1]);
        rev[i] ^= true;
    }
    bool isrt(int i) { // rt of splay
        if (!pa[i]) return true;
        return ch[pa[i]][0] != i && ch[pa[i]][1] != i;
    }
    void rotate(int i) {
        int p = pa[i], x = ch[p][1] == i, c = ch[i][!x], gp = pa[p];
        if (ch[gp][0] == p) ch[gp][0] = i;
        else if (ch[gp][1] == p) ch[gp][1] = i;
        pa[i] = gp, ch[i][!x] = p, pa[p] = i;
        ch[p][x] = c, pa[c] = p;

```

```

    pull(p), pull(i);
}
void splay(int i) {
    vector<int> anc;
    anc.push_back(i);
    while (!isrt(anc.back())) anc.push_back(pa[anc.back()]);
    while (!anc.empty()) push(anc.back()), anc.pop_back();
    while (!isrt(i)) {
        int p = pa[i];
        if (!isrt(p)) rotate(ch[p][1] == i ^ ch[pa[p]][1] == p ? i : p);
        rotate(i);
    }
}
void access(int i) {
    int last = 0;
    while (i) {
        splay(i);
        if (ch[i][1])
            sz2[i] += sz[ch[i][1]];
        sz2[i] -= sz[last];
        ch[i][1] = last;
        pull(i), last = i, i = pa[i];
    }
}
void makert(int i) {
    access(i), splay(i), reverse(i);
}
void link(int i, int j) {
    // assert(findrt(i) != findrt(j));
    makert(i);
    makert(j);
    pa[i] = j;
    sz2[j] += sz[i];
    pull(j);
}
void cut(int i, int j) {
    makert(i), access(j), splay(i);
    // assert(sz[i] == 2 && ch[i][1] == j);
    ch[i][1] = pa[j] = 0, pull(i);
}
int findrt(int i) {
    access(i), splay(i);
    while (ch[i][0]) push(i), i = ch[i][0];
    splay(i);
    return i;
}
};

```

2.4 Treap

```

struct node {
    int data, sz;
    node *l, *r;
    node(int k) : data(k), sz(1), l(0), r(0) {}
    void up() {
        sz = 1;
        if (l) sz += l->sz;
        if (r) sz += r->sz;
    }
    void down() {}
};
// delete default code sz
int sz(node *a) { return a ? a->sz : 0; }
node *merge(node *a, node *b) {
    if (!a || !b) return a ? a : b;
    if (rand() % (sz(a) + sz(b)) < sz(a))
        return a->down(), a->r = merge(a->r, b), a->up(), a;
    return b->down(), b->l = merge(a, b->l), b->up(), b;
}
void split(node *o, node *&a, node *&b, int k) {
    if (!o) return a = b = 0, void();
    o->down();
    if (o->data <= k)
        a = o, split(o->r, a->r, b, k), a->up();
    else b = o, split(o->l, a, b->l, k), b->up();
}
void split2(node *o, node *&a, node *&b, int k) {
    if (sz(o) <= k) return a = o, b = 0, void();
}

```

```

    o->down();
    if (sz(o->l) + 1 <= k)
        a = o, split2(o->r, a->r, b, k - sz(o->l) - 1);
    else b = o, split2(o->l, a, b->l, k);
    o->up();
}
node *kth(node *o, int k) {
    if (k <= sz(o->l)) return kth(o->l, k);
    if (k == sz(o->l) + 1) return o;
    return kth(o->r, k - sz(o->l) - 1);
}
int Rank(node *o, int key) {
    if (!o) return 0;
    if (o->data < key)
        return sz(o->l) + 1 + Rank(o->r, key);
    else return Rank(o->l, key);
}
bool erase(node *&o, int k) {
    if (!o) return 0;
    if (o->data == k) {
        node *t = o;
        o->down(), o = merge(o->l, o->r);
        delete t;
        return 1;
    }
    node *&t = k < o->data ? o->l : o->r;
    return erase(t, k) ? o->up(), 1 : 0;
}
void insert(node *&o, int k) {
    node *a, *b;
    o->down(), split(o, a, b, k);
    o = merge(a, merge(new node(k), b));
    o->up();
}
void interval(node *&o, int l, int r) {
    node *a, *b, *c; // [l, r)
    o->down();
    split2(o, a, b, l), split2(b, b, c, r - l);
    // operate
    o = merge(a, merge(b, c)), o->up();
}

```

2.5 2D Segment Tree*

```

// 2D range add, range sum in log^2
struct seg {
    int l, r;
    ll sum, lz;
    seg *ch[2]{};
    seg(int _l, int _r) : l(_l), r(_r), sum(0), lz(0) {}
    void push() {
        if (lz) ch[0]->add(l, r, lz), ch[1]->modify(l, r, lz), lz = 0;
    }
    void pull() { sum = ch[0]->sum + ch[1]->sum; }
    void add(int _l, int _r, ll d) {
        if (_l <= l && r <= _r) {
            sum += d * (r - l + 1);
            lz += d;
            return;
        }
        if (!ch[0]) ch[0] = new seg(l, l + r >> 1), ch[1] = new seg(l + r >> 1, r);
        push();
        if (_l < l + r >> 1) ch[0]->add(_l, _r, d);
        if (l + r >> 1 < _r) ch[1]->add(_l, _r, d);
        pull();
    }
    ll qsum(int _l, int _r) {
        if (_l <= l && r <= _r) return sum;
        if (!ch[0]) return lz * (min(r, _r) - max(l, _l) + 1);
        push();
        ll res = 0;
        if (_l < l + r >> 1) res += ch[0]->qsum(_l, _r);
        if (l + r >> 1 < _r) res += ch[1]->qsum(_l, _r);
        return res;
    }
};
struct seg2 {
    int l, r;
    seg v, lz;
    seg2 *ch[2]{};
}

```

```

seg2(int _l, int _r) : l(_l), r(_r), v(0, N), lz(0, N)
{
    if (1 < r - 1) ch[0] = new seg2(1, 1 + r >> 1), ch
        [1] = new seg2(1 + r >> 1, r);
}
void add(int _l, int _r, int _l2, int _r2, ll d) {
    v.add(_l2, _r2, d * (min(r, _r) - max(1, _l)));
    if (_l <= 1 && r <= _r) {
        lz.add(_l2, _r2, d);
        return;
    }
    if (_l < 1 + r >> 1) ch[0]->add(_l, _r, _l2, _r2, d);
    if (1 + r >> 1 < _r) ch[1]->add(_l, _r, _l2, _r2, d);
}
ll qsum(int _l, int _r, int _l2, int _r2) {
    ll res = v.qsum(_l2, _r2);
    if (_l <= 1 && r <= _r) return res;
    res += lz.qsum(_l2, _r2) * (min(r, _r) - max(1, _l));
    if (_l < 1 + r >> 1) res += ch[0]->query(_l, _r,
        _l2, _r2);
    if (1 + r >> 1 < _r) res += ch[1]->query(_l, _r,
        _l2, _r2);
    return res;
}
};

```

2.6 Range Set*

```

struct RangeSet { // [L, r)
    set<pii> S;
    void cut(int x) {
        auto it = S.lower_bound({x + 1, -1});
        if (it == S.begin()) return;
        auto [l, r] = *prev(it);
        if (l >= x || x >= r) return;
        S.erase(prev(it));
        S.insert({l, x});
        S.insert({x, r});
    }
    vector<pii> split(int l, int r) {
        // remove and return ranges in [L, r)
        cut(l), cut(r);
        vector<pii> res;
        while (true) {
            auto it = S.lower_bound({l, -1});
            if (it == S.end() || r <= it->first) break;
            res.pb(*it), S.erase(it);
        }
        return res;
    }
    void insert(int l, int r) {
        // add a range [L, r), [L, r) not in S
        auto it = S.lower_bound({l, r});
        if (it != S.begin() && prev(it)->second == l)
            l = prev(it)->first, S.erase(prev(it));
        if (it != S.end() && r == it->first)
            r = it->second, S.erase(it);
        S.insert({l, r});
    }
    bool count(int x) {
        auto it = S.lower_bound({x + 1, -1});
        return it != S.begin() && prev(it)->first <= x && x
            < prev(it)->second;
    }
};

```

2.7 vEB Tree*

```

using u64=uint64_t;
constexpr int lsb(u64 x){return x?__builtin_ctzll(x)
    :1<<30;}
constexpr int msb(u64 x){return x?63-__builtin_clzll(x)
    :-1;}
template<int N, class T=void>
struct veb{
    static const int M=N>>1;
    veb<M> ch[1<<N-M];
    veb<N-M> aux;
    int mn,mx;

```

```

    veb():mn(1<<30),mx(-1){}
    constexpr int mask(int x){return x&((1<<M)-1);}
    bool empty(){return mx==-1;}
    int min(){return mn;}
    int max(){return mx;}
    bool have(int x){
        if(x==mn) return true;
        return ch[x>>M].have(mask(x));
    }
    void insert_in(int x){
        if(empty()) return mn=mx=x,void();
        if(x<mn) swap(x,mn);
        if(x>mx) mx=x;
        if(ch[x>>M].empty()) aux.insert_in(x>>M);
        ch[x>>M].insert_in(mask(x));
    }
    void erase_in(int x){
        if(mn==mx) return mn=1<<30,mx=-1,void();
        if(x==mn) mn=x=(aux.min()<<M)^ch[aux.min()].min();
        ch[x>>M].erase_in(mask(x));
        if(ch[x>>M].empty()) aux.erase_in(x>>M);
        if(x==mx){
            if(aux.empty()) mx=mn;
            else mx=(aux.max()<<M)^ch[aux.max()].max();
        }
    }
    void insert(int x){
        if(have(x)) return;
        insert_in(x);
    }
    void erase(int x){
        if(!have(x)) return;
        erase_in(x);
    }
    int next(int x){// >=x
        if(x>mx) return 1<<30;
        if(x<=mn) return mn;
        if(mask(x)<=ch[x>>M].max()) return ((x>>M)<<M)^ch[x
            >>M].next(mask(x));
        int y=aux.next((x>>M)+1);
        return (y<<M)^ch[y].min();
    }
    int prev(int x){// <x
        if(x<=mn) return -1;
        if(x>mx) return mx;
        if(x<=(aux.min()<<M)+ch[aux.min()].min()) return mn;
        if(mask(x)>ch[x>>M].min()) return ((x>>M)<<M)^ch[x
            >>M].prev(mask(x));
        int y=aux.prev(x>>M);
        return (y<<M)^ch[y].max();
    }
};
template<int N>
struct veb<N,typename enable_if<N<=6>::type>{
    u64 a;
    veb():a(0){}
    void insert_in(int x){a|=1ull<<x;}
    void insert(int x){a|=1ull<<x;}
    void erase_in(int x){a&=~(1ull<<x);}
    void erase(int x){a&=~(1ull<<x);}
    bool have(int x){return a>>x&1;}
    bool empty(){return a==0;}
    int min(){return lsb(a);}
    int max(){return msb(a);}
    int next(int x){return lsb(a&~((1ull<<x)-1));}
    int prev(int x){return msb(a&((1ull<<x)-1));}
};

```

3 Flow / Matching

3.1 Dinic

```

const ll INF = 1ll << 60;
template <typename T>
struct Dinic { // 0-base
    struct edge {
        int to, rev;
        T cap, flow;
    };
    vector<edge> adj[N];

```

```

int s, t, dis[N], cur[N], n;
T dfs(int u, T cap) {
    if (u == t || !cap) return cap;
    for (int &i = cur[u]; i < (int)adj[u].size(); ++i)
    {
        edge &e = adj[u][i];
        if (dis[e.to] == dis[u] + 1 && e.flow != e.cap) {
            T df = dfs(e.to, min(e.cap - e.flow, cap));
            if (df) {
                e.flow += df;
                adj[e.to][e.rev].flow -= df;
                return df;
            }
        }
    }
    dis[u] = -1;
    return 0;
}
bool bfs() {
    fill_n(dis, n, -1);
    queue<int> q;
    q.push(s), dis[s] = 0;
    while (!q.empty()) {
        int tmp = q.front();
        q.pop();
        for (auto &u : adj[tmp])
            if (!dis[u.to] && u.flow != u.cap) {
                q.push(u.to);
                dis[u.to] = dis[tmp] + 1;
            }
    }
    return dis[t] != -1;
}
T solve(int _s, int _t) {
    s = _s, t = _t;
    T flow = 0, df;
    while (bfs()) {
        fill_n(cur, n, 0);
        while ((df = dfs(s, INF))) flow += df;
    }
    return flow;
}
void init(int _n) {
    n = _n;
    for (int i = 0; i < n; ++i) adj[i].clear();
}
void reset() {
    for (int i = 0; i < n; ++i)
        for (auto &j : adj[i]) j.flow = 0;
}
void add_edge(int u, int v, T cap) {
    adj[u].pb(edge{v, (int)adj[v].size(), cap, 0});
    adj[v].pb(edge{u, (int)adj[u].size() - 1, 0, 0});
}
};

```

3.2 Min Cost Max Flow

```

template <typename T1, typename T2>
struct MCMF { // T1 -> flow, T2 -> cost, 0-based
    const T1 INF1 = 1 << 30;
    const T2 INF2 = 1 << 30;
    struct edge {
        int v; T1 f; T2 c;
    } E[M << 1];
    vector<int> adj[N];
    T2 dis[N], pot[N];
    int rt[N], vis[N], n, m, s, t;
    bool SPFA() {
        fill_n(rt, n, -1), fill_n(dis, n, INF2);
        fill_n(vis, n, false);
        queue<int> q;
        q.push(s), dis[s] = 0, vis[s] = true;
        while (!q.empty()) {
            int v = q.front(); q.pop();
            vis[v] = false;
            for (int id : adj[v]) if (E[id].f > 0 && dis[E[id].v] > dis[v] + E[id].c + pot[v] - pot[E[id].v]) {
                dis[E[id].v] = dis[v] + E[id].c + pot[v] - pot[E[id].v];
                rt[E[id].v] = id;
            }
        }
    }
};

```

```

        if (!vis[E[id].v]) vis[E[id].v] = true, q.push(E[id].v);
    }
    return dis[t] != INF2;
}
bool dijkstra() {
    fill_n(rt, n, -1), fill_n(dis, n, INF2);
    priority_queue<pair<T2, int>, vector<pair<T2, int>>, greater<pair<T2, int>>> pq;
    dis[s] = 0, pq.emplace(dis[s], s);
    while (!pq.empty()) {
        auto [d, v] = pq.top(); pq.pop();
        if (dis[v] < d) continue;
        for (int id : adj[v]) if (E[id].f > 0 && dis[E[id].v] > dis[v] + E[id].c + pot[v] - pot[E[id].v]) {
            dis[E[id].v] = dis[v] + E[id].c + pot[v] - pot[E[id].v];
            rt[E[id].v] = id;
            pq.emplace(dis[E[id].v], E[id].v);
        }
    }
    return dis[t] != INF2;
}
pair<T1, T2> solve(int _s, int _t) {
    s = _s, t = _t, fill_n(pot, n, 0);
    T1 flow = 0; T2 cost = 0;
    bool fr = true;
    while ((fr ? SPFA() : dijkstra())) {
        for (int i = 0; i < n; ++i) {
            dis[i] += pot[i] - pot[s];
        }
        T1 add = INF1;
        for (int i = t; i != s; i = E[rt[i] ^ 1].v) {
            add = min(add, E[rt[i]].f);
        }
        for (int i = t; i != s; i = E[rt[i] ^ 1].v) {
            E[rt[i]].f -= add, E[rt[i] ^ 1].f += add;
        }
        flow += add, cost += add * dis[t];
        fr = false;
        for (int i = 0; i < n; ++i) swap(dis[i], pot[i]);
    }
    return make_pair(flow, cost);
}
void init(int _n) {
    n = _n, m = 0;
    for (int i = 0; i < n; ++i) adj[i].clear();
}
void reset() {
    for (int i = 0; i < m; ++i) E[i].f = 0;
}
void add_edge(int u, int v, T1 f, T2 c) {
    adj[u].pb(m), E[m++] = {v, f, c};
    adj[v].pb(m), E[m++] = {u, 0, -c};
}
};

```

3.3 Kuhn Munkres

```

template <typename T>
struct KM { // 0-based
    T w[N][N], hl[N], hr[N], slk[N];
    T fl[N], fr[N], pre[N]; int n;
    bool vl[N], vr[N];
    const T INF = 1e9;
    queue<int> q;
    KM(int _n) : n(_n) {
        for (int i = 0; i < n; ++i) for (int j = 0; j < n; ++j)
            w[i][j] = -INF;
    }
    void add_edge(int a, int b, int wei) {
        w[a][b] = wei;
    }
    bool check(int x) {
        if (vl[x] = 1, ~fl[x]) return q.push(fl[x]), vr[fl[x]] = 1;
        while (~x) swap(x, fr[fl[x] = pre[x]]);
        return 0;
    }
    void bfs(int s) {

```

```

fill(slk, slk + n, INF), fill(vl, vl + n, 0), fill(
    vr, vr + n, 0);
q.push(s), vr[s] = 1;
while (1) {
    T d;
    while (!q.empty()) {
        int y = q.front(); q.pop();
        for (int x = 0; x < n; ++x)
            if (!vl[x] && slk[x] >= (d = hl[x] + hr[y] -
                w[x][y]))
                if (pre[x] = y, d) slk[x] = d;
                else if (!check(x)) return;
    }
    d = INF;
    for (int x = 0; x < n; ++x)
        if (!vl[x] && d > slk[x]) d = slk[x];
    for (int x = 0; x < n; ++x) {
        if (vl[x]) hl[x] += d;
        else slk[x] -= d;
        if (vr[x]) hr[x] -= d;
    }
    for (int x = 0; x < n; ++x) if (!vl[x] && !slk[x]
        && !check(x)) return;
}
}
T solve() {
    fill(fl, fl + n, -1), fill(fr, fr + n, -1), fill(hr,
        hr + n, 0);
    for (int i = 0; i < n; ++i) hl[i] = *max_element(w[
        i], w[i] + n);
    for (int i = 0; i < n; ++i) bfs(i);
    T res = 0;
    for (int i = 0; i < n; ++i) res += w[i][fl[i]];
    return res;
}
};

```

3.4 SW Min Cut

```

template <typename T>
struct SW { // 0-based
    T g[N][N], sum[N]; int n;
    bool vis[N], dead[N];
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) fill(g[i], g[i] + n, 0)
            ;
        fill(dead, dead + n, false);
    }
    void add_edge(int u, int v, T w) {
        g[u][v] += w, g[v][u] += w;
    }
    T solve() {
        T ans = 1 << 30;
        for (int round = 0; round + 1 < n; ++round) {
            fill(vis, vis + n, false), fill(sum, sum + n, 0);
            int num = 0, s = -1, t = -1;
            while (num < n - round) {
                int now = -1;
                for (int i = 0; i < n; ++i) if (!vis[i] && !
                    dead[i]) {
                    if (now == -1 || sum[now] < sum[i]) now = i
                        ;
                }
                s = t, t = now;
                vis[now] = true, num++;
                for (int i = 0; i < n; ++i) if (!vis[i] && !
                    dead[i]) {
                    sum[i] += g[now][i];
                }
            }
            ans = min(ans, sum[t]);
            for (int i = 0; i < n; ++i) {
                g[i][s] += g[i][t];
                g[s][i] += g[t][i];
            }
            dead[t] = true;
        }
        return ans;
    }
};

```

3.5 Gomory Hu Tree

```

vector <array <int, 3>> GomoryHu(Dinic <int> flow) {
    // Tree edge min = mincut (0-based)
    // Complexity: run flow n times
    int n = flow.n;
    vector <array <int, 3>> ans;
    vector <int> rt(n);
    for (int i = 1; i < n; ++i) {
        int t = rt[i];
        flow.reset();
        ans.pb({i, t, flow.solve(i, t)});
        flow.bfs();
        for (int j = i + 1; j < n; ++j) if (rt[j] == t &&
            flow.dis[j] != -1) {
            rt[j] = i;
        }
    }
    return ans;
}

```

3.6 Blossom

```

struct Matching { // 0-based
    int fa[N], pre[N], match[N], s[N], v[N], n, tk;
    vector <int> g[N];
    queue <int> q;
    Matching(int _n) : n(_n), tk(0) {
        for (int i = 0; i <= n; ++i) match[i] = pre[i] = n;
        for (int i = 0; i < n; ++i) g[i].clear();
    }
    void add_edge(int u, int v) {
        g[u].push_back(v), g[v].push_back(u);
    }
    int Find(int u) {
        return u == fa[u] ? u : fa[u] = Find(fa[u]);
    }
    int lca(int x, int y) {
        tk++;
        x = Find(x), y = Find(y);
        for (; ; swap(x, y)) {
            if (x != n) {
                if (v[x] == tk) return x;
                v[x] = tk;
                x = Find(pre[match[x]]);
            }
        }
    }
    void blossom(int x, int y, int l) {
        while (Find(x) != l) {
            pre[x] = y, y = match[x];
            if (s[y] == 1) q.push(y), s[y] = 0;
            if (fa[x] == x) fa[x] = l;
            if (fa[y] == y) fa[y] = l;
            x = pre[y];
        }
    }
    bool bfs(int r) {
        for (int i = 0; i <= n; ++i) fa[i] = i, s[i] = -1;
        while (!q.empty()) q.pop();
        q.push(r);
        s[r] = 0;
        while (!q.empty()) {
            int x = q.front(); q.pop();
            for (int u : g[x]) {
                if (s[u] == -1) {
                    pre[u] = x, s[u] = 1;
                    if (match[u] == n) {
                        for (int a = u, b = x, last; b != n; a =
                            last, b = pre[a])
                            last = match[b], match[b] = a, match[a] =
                                b;
                        return true;
                    }
                }
                q.push(match[u]);
                s[match[u]] = 0;
            }
        }
        else if (!s[u] && Find(u) != Find(x)) {
            int l = lca(u, x);
            blossom(x, u, l);
            blossom(u, x, l);
        }
    }
}

```



```

    }
    return false;
}
int solve() {
    int res = 0;
    for (int x = 0; x < n; ++x) {
        if (match[x] == n) res += bfs(x);
    }
    return res;
}
};

```

3.7 Weighted Blossom

```

struct WeightGraph { // 1-based
    static const int inf = INT_MAX;
    static const int maxn = 514;
    struct edge {
        int u, v, w;
        edge(){}
        edge(int u, int v, int w): u(u), v(v), w(w) {}
    };
    int n, n_x;
    edge g[maxn * 2][maxn * 2];
    int lab[maxn * 2];
    int match[maxn * 2], slack[maxn * 2], st[maxn * 2],
        pa[maxn * 2];
    int flo_from[maxn * 2][maxn + 1], S[maxn * 2], vis[
        maxn * 2];
    vector<int> flo[maxn * 2];
    queue<int> q;
    int e_delta(const edge &e) { return lab[e.u] + lab[e.
        v] - g[e.u][e.v].w * 2; }
    void update_slack(int u, int x) { if (!slack[x] ||
        e_delta(g[u][x]) < e_delta(g[slack[x]][x])) slack
        [x] = u; }
    void set_slack(int x) {
        slack[x] = 0;
        for (int u = 1; u <= n; ++u)
            if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
                update_slack(u, x);
    }
    void q_push(int x) {
        if (x <= n) q.push(x);
        else for (size_t i = 0; i < flo[x].size(); ++i)
            q.push(flo[x][i]);
    }
    void set_st(int x, int b) {
        st[x] = b;
        if (x > n) for (size_t i = 0; i < flo[x].size(); ++
            i) set_st(flo[x][i], b);
    }
    int get_pr(int b, int xr) {
        int pr = find(flo[b].begin(), flo[b].end(), xr) -
            flo[b].begin();
        if (pr % 2 == 1) {
            reverse(flo[b].begin() + 1, flo[b].end());
            return (int)flo[b].size() - pr;
        }
        return pr;
    }
    void set_match(int u, int v) {
        match[u] = g[u][v].v;
        if (u <= n) return;
        edge e = g[u][v];
        int xr = flo_from[u][e.u], pr = get_pr(u, xr);
        for (int i = 0; i < pr; ++i) set_match(flo[u][i],
            flo[u][i ^ 1]);
        set_match(xr, v);
        rotate(flo[u].begin(), flo[u].begin() + pr, flo[u].
            end());
    }
    void augment(int u, int v) {
        for (; ) {
            int xnv = st[match[u]];
            set_match(u, v);
            if (!xnv) return;
            set_match(xnv, st[pa[xnv]]);
            u = st[pa[xnv]], v = xnv;
        }
    }
    int get_lca(int u, int v) {

```

```

        static int t = 0;
        for (++t; u || v; swap(u, v)) {
            if (u == 0) continue;
            if (vis[u] == t) return u;
            vis[u] = t;
            u = st[match[u]];
            if (u) u = st[pa[u]];
        }
        return 0;
    }
    void add_blossom(int u, int lca, int v) {
        int b = n + 1;
        while (b <= n_x && st[b]) ++b;
        if (b > n_x) ++n_x;
        lab[b] = 0, S[b] = 0;
        match[b] = match[lca];
        flo[b].clear();
        flo[b].push_back(lca);
        for (int x = u, y; x != lca; x = st[pa[y]])
            flo[b].push_back(x), flo[b].push_back(y = st[
                match[x]]), q_push(y);
        reverse(flo[b].begin() + 1, flo[b].end());
        for (int x = v, y; x != lca; x = st[pa[y]])
            flo[b].push_back(x), flo[b].push_back(y = st[
                match[x]]), q_push(y);
        set_st(b, b);
        for (int x = 1; x <= n_x; ++x) g[b][x].w = g[x][b].
            w = 0;
        for (int x = 1; x <= n; ++x) flo_from[b][x] = 0;
        for (size_t i = 0; i < flo[b].size(); ++i) {
            int xs = flo[b][i];
            for (int x = 1; x <= n_x; ++x)
                if (g[b][x].w == 0 || e_delta(g[xs][x]) <
                    e_delta(g[b][x]))
                    g[b][x] = g[xs][x], g[x][b] = g[x][xs];
            for (int x = 1; x <= n; ++x)
                if (flo_from[xs][x]) flo_from[b][x] = xs;
        }
        set_slack(b);
    }
    void expand_blossom(int b) {
        for (size_t i = 0; i < flo[b].size(); ++i)
            set_st(flo[b][i], flo[b][i]);
        int xr = flo_from[b][g[b][pa[b]].u], pr = get_pr(b,
            xr);
        for (int i = 0; i < pr; i += 2) {
            int xs = flo[b][i], xns = flo[b][i + 1];
            pa[xs] = g[xns][xs].u;
            S[xs] = 1, S[xns] = 0;
            slack[xs] = 0, set_slack(xns);
            q_push(xns);
        }
        S[xr] = 1, pa[xr] = pa[b];
        for (size_t i = pr + 1; i < flo[b].size(); ++i) {
            int xs = flo[b][i];
            S[xs] = -1, set_slack(xs);
        }
        st[b] = 0;
    }
    bool on_found_edge(const edge &e) {
        int u = st[e.u], v = st[e.v];
        if (S[v] == -1) {
            pa[v] = e.u, S[v] = 1;
            int nu = st[match[v]];
            slack[v] = slack[nu] = 0;
            S[nu] = 0, q_push(nu);
        } else if (S[v] == 0) {
            int lca = get_lca(u, v);
            if (!lca) return augment(u, v), augment(v, u), true;
            else add_blossom(u, lca, v);
        }
        return false;
    }
    bool matching() {
        memset(S + 1, -1, sizeof(int) * n_x);
        memset(slack + 1, 0, sizeof(int) * n_x);
        q = queue<int>();
        for (int x = 1; x <= n_x; ++x)
            if (st[x] == x && !match[x]) pa[x] = 0, S[x] = 0,
                q_push(x);
        if (q.empty()) return false;

```

```

for (; ; ) {
    while (q.size()) {
        int u = q.front(); q.pop();
        if (S[st[u]] == 1) continue;
        for (int v = 1; v <= n; ++v)
            if (g[u][v].w > 0 && st[u] != st[v]) {
                if (e_delta(g[u][v]) == 0) {
                    if (on_found_edge(g[u][v])) return true;
                } else update_slack(u, st[v]);
            }
    }
    int d = inf;
    for (int b = n + 1; b <= n_x; ++b)
        if (st[b] == b && S[b] == 1) d = min(d, lab[b] / 2);
    for (int x = 1; x <= n_x; ++x)
        if (st[x] == x && slack[x]) {
            if (S[x] == -1) d = min(d, e_delta(g[slack[x]]));
            else if (S[x] == 0) d = min(d, e_delta(g[slack[x]]));
        }
    for (int u = 1; u <= n; ++u) {
        if (S[st[u]] == 0) {
            if (lab[u] <= d) return 0;
            lab[u] -= d;
        } else if (S[st[u]] == 1) lab[u] += d;
    }
    for (int b = n + 1; b <= n_x; ++b)
        if (st[b] == b) {
            if (S[st[b]] == 0) lab[b] += d * 2;
            else if (S[st[b]] == 1) lab[b] -= d * 2;
        }
    q = queue<int>();
    for (int x = 1; x <= n_x; ++x)
        if (st[x] == x && slack[x] && st[slack[x]] != x
            && e_delta(g[slack[x]])) return true;
    for (int b = n + 1; b <= n_x; ++b)
        if (st[b] == b && S[b] == 1 && lab[b] == 0)
            expand_blossom(b);
    return false;
}
pair<long long, int> solve() {
    memset(match + 1, 0, sizeof(int) * n);
    n_x = n;
    int n_matches = 0;
    long long tot_weight = 0;
    for (int u = 0; u <= n; ++u) st[u] = u, flo[u].clear();
    int w_max = 0;
    for (int u = 1; u <= n; ++u)
        for (int v = 1; v <= n; ++v) {
            flo_from[u][v] = (u == v ? u : 0);
            w_max = max(w_max, g[u][v].w);
        }
    for (int u = 1; u <= n; ++u) lab[u] = w_max;
    while (matching()) ++n_matches;
    for (int u = 1; u <= n; ++u)
        if (match[u] && match[u] < u)
            tot_weight += g[u][match[u]].w;
    return make_pair(tot_weight, n_matches);
}
void add_edge(int ui, int vi, int wi) { g[ui][vi].w = wi; }
void init(int _n) {
    n = _n;
    for (int u = 1; u <= n; ++u)
        for (int v = 1; v <= n; ++v)
            g[u][v] = edge(u, v, 0);
}
};

```

3.8 Flow Model

- Maximum/Minimum flow with lower bound / Circulation problem
 - Construct super source S and sink T .
 - For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity $u - l$.
 - For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.

- If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
- The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.

- Construct minimum vertex cover from maximum matching M on bipartite graph (X, Y)
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - DFS from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited.
 - $y \in Y$ is chosen iff y is visited.
- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T
 - Construct a max flow model, let K be the sum of all weights
 - Connect source $s \rightarrow v$, $v \in G$ with capacity K
 - For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
 - For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
 - T is a valid answer if the maximum flow $f < K|V|$
- Minimum weight edge cover
 - For each $v \in V$ create a copy v' , and connect $u' \rightarrow v'$ with weight $w(u, v)$.
 - Connect $v \rightarrow v'$ with weight $2\mu(v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
 - Find the minimum weight perfect matching on G' .
- Project selection problem
 - If $p_v > 0$, create edge (s, v) with capacity p_v ; otherwise, create edge (v, t) with capacity $-p_v$.
 - Create edge (u, v) with capacity w with w being the cost of choosing u without choosing v .
 - The mincut is equivalent to the maximum profit of a subset of projects.

- 0/1 quadratic programming

$$\sum_x c_x x + \sum_y c_y \bar{y} + \sum_{xy} c_{xy} x \bar{y} + \sum_{xyx'y'} c_{xyx'y'} (x \bar{y} + x' \bar{y}')$$

can be minimized by the mincut of the following graph:

- Create edge (x, t) with capacity c_x and create edge (s, y) with capacity c_y .
- Create edge (x, y) with capacity c_{xy} .
- Create edge (x, y) and edge (x', y') with capacity $c_{xyx'y'}$.

4 Graph

4.1 Heavy-Light Decomposition

```

vector<int> g[N];
int dep[N], pa[N], sz[N], ch[N], hd[N], id[N], _id;
void dfs(int i, int p) {
    dep[i] = ~p ? dep[p] + 1 : 0;
    pa[i] = p, sz[i] = 1, ch[i] = -1;
    for (int j : g[i]) if (j != p) {
        dfs(j, i);
        if (ch[i] == -1 || sz[ch[i]] < sz[j]) ch[i] = j;
        sz[i] += sz[j];
    }
}
void hld(int i, int p, int h) {
    hd[i] = h;
    id[i] = _id++;
    if (~ch[i]) hld(ch[i], i, h);
    for (int j : g[i]) if (j != p && j != ch[i])
        hld(j, i, j);
}
void query(int i, int j) {
    // query2 -> [l, r)
    while (hd[i] != hd[j]) {
        if (dep[hd[i]] < dep[hd[j]]) swap(i, j);
        query2(id[hd[i]], id[i] + 1, i = pa[hd[i]]);
    }
    if (dep[i] < dep[j]) swap(i, j);
    query2(id[j], id[i] + 1);
}

```


4.2 Centroid Decomposition

```
vector<int> g[N];
int dis[N][logN], pa[N], sz[N], dep[N];
bool vis[N];
void dfs_sz(int i, int p) {
    sz[i] = 1;
    for (int j : g[i]) if (j != p && !vis[j])
        dfs_sz(j, i), sz[i] += sz[j];
}
int cen(int i, int p, int _n) {
    for (int j : g[i]) if (j != p && !vis[j] && sz[j] >
        _n / 2)
        return cen(j, i, _n);
    return i;
}
void dfs_dis(int i, int p, int d) {
    // from i to ancestor with depth d
    dis[i][d] = ~p ? dis[p][d] + 1 : 0;
    for (int j : g[i]) if (j != p && !vis[j])
        dfs_dis(j, i, d);
}
void cd(int i, int p, int d) {
    dfs_sz(i, -1), i = cen(i, -1, sz[i]);
    vis[i] = true, pa[i] = p, dep[i] = d;
    dfs_dis(i, -1, d);
    for (int j : g[i]) if (!vis[j])
        cd(j, i, d + 1);
}
```

4.3 Edge BCC

```
vector<int> g[N], _g[N];
// Notice Multiple Edges
int pa[N], low[N], dep[N], bcc_id[N], _id;
vector<int> stk, bcc[N];
bool vis[N], is_bridge[N];
void dfs(int i, int p = -1) {
    low[i] = dep[i] = ~p ? dep[p] + 1 : 0;
    stk.pb(i), pa[i] = p, vis[i] = true;
    for (int j : g[i]) if (j != p) {
        if (!vis[j])
            dfs(j, i), low[i] = min(low[i], low[j]);
        else
            low[i] = min(low[i], dep[j]);
    }
    if (low[i] == dep[i]) {
        if (~p) is_bridge[i] = true; // (i, pa[i])
        int id = _id++, x;
        do {
            x = stk.back(), stk.pop_back();
            bcc_id[x] = id, bcc[id].pb(x);
        } while (x != i);
    }
}
void build(int n) {
    for (int i = 0; i < n; ++i) if (!vis[i])
        dfs(i);
    for (int i = 0; i < n; ++i) if (is_bridge[i]) {
        int u = bcc_id[i], v = bcc_id[pa[i]];
        _g[u].pb(v), _g[v].pb(u);
    }
}
```

4.4 Block Cut Tree

```
vector<int> g[N], _g[N << 1];
// _g: index >= N: bcc, index < N: original vertex
// Notice Isolated Point
int pa[N], dep[N], low[N], _id;
bool vis[N], is_cut[N];
vector<int> stk, bcc[N];
void add_edge(int u, int v) { _g[u].pb(v), _g[v].pb(u); }
void dfs(int i, int p = -1) {
    int ch = 0;
    dep[i] = low[i] = ~p ? dep[p] + 1 : 0;
    stk.pb(i), pa[i] = p, vis[i] = true;
    for (int j : g[i]) if (j != p) {
        if (!vis[j]) {
            dfs(j, i), low[i] = min(low[i], low[j]);
            if (low[j] >= dep[i]) {
                is_cut[i] = true;
            }
        }
    }
}
```

```
int id = _id++, x;
do {
    x = stk.back(), stk.pop_back();
    bcc[id].pb(x), add_edge(id + N, x);
} while (x != j);
bcc[id].pb(i), add_edge(id + N, i);
} else low[i] = min(low[i], dep[j]);
}
if (p == -1 && ch < 2) is_cut[i] = false;
}
int pa2[N << 1], dep2[N << 1];
void dfs2(int i, int p = -1) {
    dep2[i] = ~p ? dep2[p] + 1 : 0, pa2[i] = p;
    for (int j : _g[i]) if (j != p) {
        dfs2(j, i);
    }
}
int bcc_id(int u, int v) {
    if (dep2[u] < dep2[v]) swap(u, v);
    return pa2[u] - N;
}
void build(int n) {
    for (int i = 0; i < n; ++i) if (!vis[i])
        dfs(i), dfs2(i);
}
```

4.5 SCC / 2SAT

```
struct SAT {
    vector<int> g[N << 1], stk;
    int dep[N << 1], low[N << 1], scc_id[N << 1];
    int n, _id, _t;
    bool is[N];
    SAT() {}
    void init(int _n) {
        n = _n, _id = _t = 0;
        for (int i = 0; i < 2 * n; ++i)
            g[i].clear(), dep[i] = scc_id[i] = -1;
        stk.clear();
    }
    void add_edge(int x, int y) { g[x].push_back(y); }
    int rev(int i) { return i < n ? i + n : i - n; }
    void add_ifthen(int x, int y) { add_clause(rev(x), y); }
    void add_clause(int x, int y) {
        add_edge(rev(x), y);
        add_edge(rev(y), x);
    }
    void dfs(int i) {
        dep[i] = low[i] = _t++, stk.pb(i);
        for (int j : g[i]) if (scc_id[j] == -1) {
            if (dep[j] == -1) dfs(j);
            low[i] = min(low[i], low[j]);
        }
        if (low[i] == dep[i]) {
            int id = _id++, x;
            do {
                x = stk.back(), stk.pop_back();
                scc_id[x] = id;
            } while (x != i);
        }
    }
    bool solve() {
        // is[i] = true -> i, is[i] = false -> -i
        for (int i = 0; i < 2 * n; ++i) if (dep[i] == -1)
            dfs(i);
        for (int i = 0; i < n; ++i) {
            if (scc_id[i] == scc_id[i + n]) return false;
            if (scc_id[i] < scc_id[i + n]) is[i] = true;
            else is[i] = false;
        }
        return true;
    }
};
```

4.6 Virtual Tree

```
vector<int> _g[N], stk;
int st[N], ed[N];
void solve(vector<int> v) {
    sort(all(v), [&](int x, int y) { return st[x] < st[y]; });
}
```

```

int sz = v.size();
for (int i = 0; i < sz - 1; ++i)
    v.push_back(lca(v[i], v[i + 1]));
sort(all(v), [&](int x, int y) {return st[x] < st[y];});
v.resize(unique(all(v)) - v.begin());
stk.clear(), stk.push_back(v[0]);
for (int i = 1; i < v.size(); ++i) {
    int x = v[i];
    while (ed[stk.back()] < ed[x]) stk.pop_back();
    _g[stk.back()].pb(x), stk.pb(x);
}
// do something
for (int i : v) _g[i].clear();
}

```

4.7 Directed MST

```

using D = int;
struct edge {
    int u, v;
    D w;
};
// 0-based, return index of edges
vector<int> dmst(vector<edge> &e, int n, int root) {
    using T = pair<D, int>;
    using PQ = pair<priority_queue<T, vector<T>,
        greater<T>>, D>;
    auto push = [](PQ &pq, T v) {
        pq.first.emplace(v.first - pq.second, v.second);
    };
    auto top = [](const PQ &pq) -> T {
        auto r = pq.first.top();
        return {r.first + pq.second, r.second};
    };
    auto join = [&push, &top](PQ &a, PQ &b) {
        if (a.first.size() < b.first.size()) swap(a, b);
        while (!b.first.empty())
            push(a, top(b)), b.first.pop();
    };
    vector<PQ> h(n * 2);
    for (int i = 0; i < e.size(); ++i)
        push(h[e[i].v], {e[i].w, i});
    vector<int> a(n * 2), v(n * 2, -1), pa(n * 2, -1), r(
        n * 2);
    iota(all(a), 0);
    auto o = [&](int x) { int y;
        for (y = x; a[y] != y; y = a[y]);
        for (int ox = x; x != y; ox = x)
            x = a[x], a[ox] = y;
        return y;
    };
    v[root] = n + 1;
    int pc = n;
    for (int i = 0; i < n; ++i) if (v[i] == -1) {
        for (int p = i; v[p] == -1 || v[p] == i; p = o(e[r[p]].u)) {
            if (v[p] == i) {
                int q = p; p = pc++;
                do {
                    h[q].second = -h[q].first.top().first;
                    join(h[pa[q] = a[q] = p], h[q]);
                } while ((q = o(e[r[q]].u)) != p);
            }
            v[p] = i;
            while (!h[p].first.empty() && o(e[top(h[p]).second].u) == p)
                h[p].first.pop();
            r[p] = top(h[p]).second;
        }
    }
    vector<int> ans;
    for (int i = pc - 1; i >= 0; i--) if (i != root && v[i] != n) {
        for (int f = e[r[i]].v; f != -1 && v[f] != n; f = pa[f]) v[f] = n;
        ans.pb(r[i]);
    }
    return ans;
}

```

4.8 Dominator Tree

```

struct Dominator_tree {
    int n, id;
    vector<vector<int>> adj, radj, bucket;
    vector<int> sdom, dom, vis, rev, par, rt, mn;
    Dominator_tree (int _n) : n(_n), id(0) {
        adj.resize(n), radj.resize(n), bucket.resize(n);
        sdom.resize(n), dom.resize(n, -1), vis.resize(n, -1);
        rev.resize(n), rt.resize(n), mn.resize(n), par.resize(n);
    }
    void add_edge(int u, int v) {adj[u].pb(v);}
    int query(int v, bool x) {
        if (rt[v] == v) return x ? -1 : v;
        int p = query(radj[v], true);
        if (p == -1) return x ? rt[v] : mn[v];
        if (sdom[mn[v]] > sdom[mn[rt[v]]]) mn[v] = mn[rt[v]];
        rt[v] = p;
        return x ? p : mn[v];
    }
    void dfs(int v) {
        vis[v] = id, rev[id] = v;
        rt[id] = mn[id] = sdom[id] = id, id++;
        for (int u : adj[v]) {
            if (vis[u] == -1) dfs(u), par[vis[u]] = vis[v];
            radj[vis[u]].pb(vis[v]);
        }
    }
    void build(int s) {
        dfs(s);
        for (int i = id - 1; ~i; --i) {
            for (int u : radj[i]) {
                sdom[i] = min(sdom[i], sdom[query(u, false)]);
            }
            if (i) bucket[sdom[i]].pb(i);
            for (int u : bucket[i]) {
                int p = query(u, false);
                dom[u] = sdom[p] == i ? i : p;
            }
            if (i) rt[i] = par[i];
        }
        vector<int> res(n, -1);
        for (int i = 1; i < id; ++i) {
            if (dom[i] != sdom[i]) dom[i] = dom[dom[i]];
        }
        for (int i = 1; i < id; ++i) res[rev[i]] = rev[dom[i]];
        res[s] = s;
        dom = res;
    }
};

```

5 String

5.1 Aho-Corasick Automaton

```

struct AC {
    int ch[N][26], to[N][26], fail[N], sz;
    vector<int> g[N];
    int cnt[N];
    AC () {sz = 0, extend();}
    void extend() {fill(ch[sz], ch[sz] + 26, 0), sz++;}
    int nxt(int u, int v) {
        if (!ch[u][v]) ch[u][v] = sz, extend();
        return ch[u][v];
    }
    int insert(string s) {
        int now = 0;
        for (char c : s) now = nxt(now, c - 'a');
        cnt[now]++;
        return now;
    }
    void build_fail() {
        queue<int> q;
        for (int i = 0; i < 26; ++i) if (ch[0][i]) {
            q.push(ch[0][i]);
            g[0].push_back(ch[0][i]);
        }
        while (!q.empty()) {
            int v = q.front(); q.pop();

```

```

    for (int j = 0; j < 26; ++j) {
        to[v][j] = ch[v][j] ? v : to[fail[v]][j];
    }
    for (int i = 0; i < 26; ++i) if (ch[v][i]) {
        int u = ch[v][i], k = fail[v];
        while (k && !ch[k][i]) k = fail[k];
        if (ch[k][i]) k = ch[k][i];
        fail[u] = k;
        cnt[u] += cnt[k], g[k].push_back(u);
        q.push(u);
    }
}
int match(string &s) {
    int now = 0, ans = 0;
    for (char c : s) {
        now = to[now][c - 'a'];
        if (ch[now][c - 'a']) now = ch[now][c - 'a'];
        ans += cnt[now];
    }
    return ans;
}
};

```

5.2 KMP Algorithm

```

vector<int> build_fail(string s) {
    vector<int> f(s.length() + 1, 0);
    int k = 0;
    for (int i = 1; i < s.length(); ++i) {
        while (k && s[k] != s[i]) k = f[k];
        if (s[k] == s[i]) k++;
        f[i + 1] = k;
    }
    return f;
}
int match(string s, string t) {
    vector<int> f = build_fail(t);
    int k = 0, ans = 0;
    for (int i = 0; i < s.length(); ++i) {
        while (k && s[i] != t[k]) k = f[k];
        if (s[i] == t[k]) k++;
        if (k == t.length()) ans++, k = f[k];
    }
    return ans;
}

```

5.3 Z Algorithm

```

vector<int> build(string s) {
    int n = s.length();
    vector<int> Z(n);
    int l = 0, r = 0;
    for (int i = 0; i < n; ++i) {
        Z[i] = max(min(Z[i - 1], r - i), 0);
        while (i + Z[i] < s.size() && s[Z[i]] == s[i + Z[i]]) {
            l = i, r = i + Z[i], Z[i]++;
        }
    }
    return Z;
}

```

5.4 Manacher

```

vector<int> manacher(string &s) {
    string t = "^#";
    for (char c : s) t += c, t += '#';
    t += '&';
    int n = t.length();
    vector<int> r(n, 0);
    int C = 0, R = 0;
    for (int i = 1; i < n - 1; ++i) {
        int mirror = 2 * C - i;
        r[i] = (i < R ? min(r[mirror], R - i) : 0);
        while (t[i - 1 - r[i]] == t[i + 1 + r[i]]) r[i]++;
        if (i + r[i] > R) R = i + r[i], C = i;
    }
    return r;
}

```

5.5 SuffixArray

```

int sa[N], tmp[2][N], c[N], rk[N], lcp[N];
void buildSA(string s) {
    int *x = tmp[0], *y = tmp[1], m = 256, n = s.length();
    for (int i = 0; i < m; ++i) c[i] = 0;
    for (int i = 0; i < n; ++i) c[x[i]] = s[i]++;
    for (int i = 1; i < m; ++i) c[i] += c[i - 1];
    for (int i = n - 1; ~i; --i) sa[--c[x[i]]] = i;
    for (int k = 1; k < n; k <= 1) {
        for (int i = 0; i < m; ++i) c[i] = 0;
        for (int i = 0; i < n; ++i) c[x[i]]++;
        for (int i = 1; i < m; ++i) c[i] += c[i - 1];
        int p = 0;
        for (int i = n - k; i < n; ++i) y[p++] = i;
        for (int i = 0; i < n; ++i) if (sa[i] >= k) y[p++] = sa[i] - k;
        for (int i = n - 1; ~i; --i) sa[--c[x[y[i]]]] = y[i];
        y[sa[0]] = p = 0;
        for (int i = 1; i < n; ++i) {
            int a = sa[i], b = sa[i - 1];
            if (!(x[a] == x[b] && a + k < n && b + k < n && x[a + k] == x[b + k])) p++;
            y[sa[i]] = p;
        }
        if (n == p + 1) break;
        swap(x, y), m = p + 1;
    }
}
void buildLCP(string s) {
    // lcp[i] = LCP(sa[i - 1], sa[i])
    // lcp(i, j) = min(lcp[rk[i] + 1], lcp[rk[i] + 2], ..., lcp[rk[j]])
    int n = s.length(), val = 0;
    for (int i = 0; i < n; ++i) rk[sa[i]] = i;
    for (int i = 0; i < n; ++i) {
        if (!rk[i]) lcp[rk[i]] = 0;
        else {
            if (val) val--;
            int p = sa[rk[i] - 1];
            while (val + i < n && val + p < n && s[val + i] == s[val + p]) val++;
            lcp[rk[i]] = val;
        }
    }
}

```

5.6 SAIS

```

namespace sfx {
    bool _t[N * 2];
    int SA[N * 2], H[N], RA[N];
    int _s[N * 2], _c[N * 2], x[N], _p[N], _q[N * 2];
    void pre(int *sa, int *c, int n, int z) {
        fill_n(sa, n, 0), copy_n(c, z, x);
    }
    void induce(int *sa, int *c, int *s, bool *t, int n, int z) {
        copy_n(c, z - 1, x + 1);
        for (int i = 0; i < n; ++i) if (sa[i] && !t[sa[i] - 1]) sa[x[sa[i] - 1]++] = sa[i] - 1;
        copy_n(c, z, x);
        for (int i = n - 1; i >= 0; --i) if (sa[i] && t[sa[i] - 1]) sa[--x[sa[i] - 1]] = sa[i] - 1;
    }
    void sais(int *s, int *sa, int *p, int *q, bool *t, int *c, int n, int z) {
        bool uniq = t[n - 1] = true;
        int nn = 0, nmxx = -1, *nsa = sa + n, *ns = s + n, last = -1;
        fill_n(c, z, 0);
        for (int i = 0; i < n; ++i) uniq &= ++c[s[i]] < 2;
        partial_sum(c, c + z, c);
        if (uniq) {
            for (int i = 0; i < n; ++i) sa[--c[s[i]]] = i;
            return;
        }
        for (int i = n - 2; i >= 0; --i)
            t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]);
        pre(sa, c, n, z);
        for (int i = 1; i <= n - 1; ++i)

```

```

    if (t[i] && !t[i - 1])
        sa[--x[s[i]]] = p[q[i] = nn++] = i;
    induce(sa, c, s, t, n, z);
    for (int i = 0; i < n; ++i)
        if (sa[i] && t[sa[i]] && !t[sa[i] - 1]) {
            bool neq = last < 0 || !equal(s + sa[i], s + p[q[
                sa[i]] + 1], s + last);
            ns[q[last = sa[i]]] = nmzx += neq;
        }
    sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, nmzx +
        1);
    pre(sa, c, n, z);
    for (int i = nn - 1; i >= 0; --i)
        sa[--x[s[p[nsa[i]]]]] = p[nsa[i]];
    induce(sa, c, s, t, n, z);
}
vector<int> build(int *s, int n) {
    copy_n(s, n, _s), _s[n] = 0;
    sais(_s, SA, _p, _q, _t, _c, n + 1, 256);
    vector<int> sa(n);
    for (int i = 0; i < n; ++i)
        sa[i] = SA[i + 1];
    return sa;
}
}

```

5.7 Suffix Automaton

```

struct SAM {
    int ch[N][26], len[N], link[N], pos[N], cnt[N], sz;
    // node -> strings with the same endpos set
    // length in range [len(link) + 1, len]
    // node's endpos set -> pos in the subtree of node
    // link -> longest suffix with different endpos set
    // len -> longest suffix
    // pos -> end position
    // cnt -> size of endpos set
    SAM () {len[0] = 0, link[0] = -1, pos[0] = 0, cnt[0]
        = 0, sz = 1;}
    void build(string s) {
        int last = 0;
        for (int i = 0; i < s.length(); ++i) {
            char c = s[i];
            int cur = sz++;
            len[cur] = len[last] + 1, pos[cur] = i + 1;
            int p = last;
            while (~p && !ch[p][c - 'a']) ch[p][c - 'a'] =
                cur, p = link[p];
            if (p == -1) {
                link[cur] = 0;
            } else {
                int q = ch[p][c - 'a'];
                if (len[p] + 1 == len[q]) {
                    link[cur] = q;
                } else {
                    int nxt = sz++;
                    len[nxt] = len[p] + 1, link[nxt] = link[q],
                        pos[nxt] = 0;
                    for (int j = 0; j < 26; ++j) ch[nxt][j] = ch[
                        q][j];
                    while (~p && ch[p][c - 'a'] == q) ch[p][c - '
                        a'] = nxt, p = link[p];
                    link[q] = link[cur] = nxt;
                }
            }
            cnt[cur]++;
            last = cur;
        }
        vector<int> p(sz);
        iota(all(p), 0);
        sort(all(p), [&](int i, int j) {return len[i] > len
            [j]});
        for (int i = 0; i < sz; ++i) cnt[link[p[i]]] += cnt
            [p[i]];
    }
} sam;

```

5.8 Minimum Rotation

```

string rotate(const string &s) {
    int n = s.length();
    string t = s + s;

```

```

    int i = 0, j = 1;
    while (i < n && j < n) {
        int k = 0;
        while (k < n && t[i + k] == t[j + k]) ++k;
        if (t[i + k] <= t[j + k]) j += k + 1;
        else i += k + 1;
        if (i == j) ++j;
    }
    int pos = (i < n ? i : j);
    return t.substr(pos, n);
}

```

5.9 Palindrome Tree

```

struct PAM {
    int ch[N][26], cnt[N], fail[N], len[N], sz;
    string s;
    // 0 -> even root, 1 -> odd root
    PAM (string _s) : s(_s) {
        sz = 0;
        extend(), extend();
        len[0] = 0, fail[0] = 1, len[1] = -1;
        int lst = 1;
        for (int i = 0; i < s.length(); ++i) {
            while (s[i - len[lst] - 1] != s[i]) lst = fail[
                lst];
            if (!ch[lst][s[i] - 'a']) {
                int idx = extend();
                len[idx] = len[lst] + 2;
                int now = fail[lst];
                while (s[i - len[now] - 1] != s[i]) now = fail[
                    now];
                fail[idx] = ch[now][s[i] - 'a'];
                ch[lst][s[i] - 'a'] = idx;
            }
            lst = ch[lst][s[i] - 'a'], cnt[lst]++;
        }
    }
    void build_count() {
        for (int i = sz - 1; i > 1; --i)
            cnt[fail[i]] += cnt[i];
    }
    int extend() {
        fill(ch[sz], ch[sz] + 26, 0), sz++;
        return sz - 1;
    }
};

```

5.10 Main Lorentz

```

int to_left[N], to_right[N];
vector<array<int, 3>> rep; // L, r, len.
// substr(L ~ r, len * 2) are tandem
void findRep(string &s, int l, int r) {
    if (r - l == 1) return;
    int m = l + r >> 1;
    findRep(s, l, m), findRep(s, m, r);
    string sl = s.substr(l, m - l), sr = s.substr(m, r -
        m);
    vector<int> Z = buildZ(sr + "#" + sl);
    for (int i = 1; i < m; ++i) to_right[i] = Z[r - m + 1
        + i - 1];
    reverse(all(sl));
    Z = buildZ(sl);
    for (int i = 1; i < m; ++i) to_left[i] = Z[m - i -
        1];
    reverse(all(sl));
    for (int i = 1; i + 1 < m; ++i) {
        int k1 = to_left[i], k2 = to_right[i + 1], len = m
            - i - 1;
        if (k1 < 1 || k2 < 1 || len < 2) continue;
        int tl = max(1, len - k2), tr = min(len - 1, k1);
        if (tl <= tr) rep.pb({i + 1 - tr, i + 1 - tl, len});
    }
    Z = buildZ(sr);
    for (int i = m; i < r; ++i) to_right[i] = Z[i - m];
    reverse(all(sl)), reverse(all(sr));
    Z = buildZ(sl + "#" + sr);
    for (int i = m; i < r; ++i) to_left[i] = Z[m - 1 + 1
        + r - i - 1];
    reverse(all(sl)), reverse(all(sr));
}

```

```

for (int i = m; i + 1 < r; ++i) {
    int k1 = to_left[i], k2 = to_right[i + 1], len = i
        - m + 1;
    if (k1 < 1 || k2 < 1 || len < 2) continue;
    int tl = max(len - k2, 1), tr = min(len - 1, k1);
    if (tl <= tr) rep.pb({i + 1 - len - tr, i + 1 - len
        - tl, len});
}
Z = buildZ(sr + "#" + sl);
for (int i = 1; i < m; ++i) {
    if (Z[r - m + 1 + i - 1] >= m - i) {
        rep.pb({i, i, m - i});
    }
}
}
}

```

6 Math

6.1 Miller Rabin / Pollard Rho

```

ll mul(ll x, ll y, ll p) {return (x * y - (ll)((long
    double)x / p * y) * p + p) % p;}
vector<ll> chk = {2, 325, 9375, 28178, 450775, 9780504,
    1795265022};
ll Pow(ll a, ll b, ll n) {ll res = 1; for (; b; b >>=
    1, a = mul(a, a, n)) if (b & 1) res = mul(res, a, n
    ); return res;}
bool check(ll a, ll d, int s, ll n) {
    a = Pow(a, d, n);
    if (a <= 1) return 1;
    for (int i = 0; i < s; ++i, a = mul(a, a, n)) {
        if (a == 1) return 0;
        if (a == n - 1) return 1;
    }
    return 0;
}
bool IsPrime(ll n) {
    if (n < 2) return 0;
    if (n % 2 == 0) return n == 2;
    ll d = n - 1, s = 0;
    while (d % 2 == 0) d >>= 1, ++s;
    for (ll i : chk) if (!check(i, d, s, n)) return 0;
    return 1;
}
const vector<ll> small = {2, 3, 5, 7, 11, 13, 17, 19};
ll FindFactor(ll n) {
    if (IsPrime(n)) return 1;
    for (ll p : small) if (n % p == 0) return p;
    ll x, y = 2, d, t = 1;
    auto f = [&](ll a) {return (mul(a, a, n) + t) % n;};
    for (int l = 2; ; l <= 1) {
        x = y;
        int m = min(l, 32);
        for (int i = 0; i < l; i += m) {
            d = 1;
            for (int j = 0; j < m; ++j) {
                y = f(y), d = mul(d, abs(x - y), n);
            }
            ll g = __gcd(d, n);
            if (g == n) {
                l = 1, y = 2, ++t;
                break;
            }
            if (g != 1) return g;
        }
    }
}
map<ll, int> res;
void PollardRho(ll n) {
    if (n == 1) return;
    if (IsPrime(n)) return ++res[n], void(0);
    ll d = FindFactor(n);
    PollardRho(n / d), PollardRho(d);
}
}

```

6.2 Ext GCD

```

//a * p.first + b * p.second = gcd(a, b)
pair<ll, ll> extgcd(ll a, ll b) {
    pair<ll, ll> res;
    if (a < 0) {

```

```

        res = extgcd(-a, b);
        res.first *= -1;
        return res;
    }
    if (b < 0) {
        res = extgcd(a, -b);
        res.second *= -1;
        return res;
    }
    if (b == 0) return {1, 0};
    res = extgcd(b, a % b);
    return {res.second, res.first - res.second * (a / b)
        };
}

```

6.3 PiCount

```

const int V = 10000000, N = 100, M = 100000;
vector<int> primes;
bool isp[V];
int small_pi[V], dp[N][M];
void sieve(int x){
    for(int i = 2; i < x; ++i) isp[i] = true;
    isp[0] = isp[1] = false;
    for(int i = 2; i * i < x; ++i) if(isp[i]) for(int j =
        i * i; j < x; j += i) isp[j] = false;
    for(int i = 2; i < x; ++i) if(isp[i]) primes.
        push_back(i);
}
void init(){
    sieve(V);
    small_pi[0] = 0;
    for(int i = 1; i < V; ++i) small_pi[i] = small_pi[i -
        1] + isp[i];
    for(int i = 0; i < M; ++i) dp[0][i] = i;
    for(int i = 1; i < N; ++i) for(int j = 0; j < M; ++j)
        dp[i][j] = dp[i - 1][j] - dp[i - 1][j / primes[i
            - 1]];
}
ll phi(ll n, int a){
    if(!a) return n;
    if(n < M && a < N) return dp[a][n];
    if(primes[a - 1] > n) return 1;
    if(((ll)primes[a - 1] * primes[a - 1] >= n && n < V)
        return small_pi[n] - a + 1;
    ll de = phi(n, a - 1) - phi(n / primes[a - 1], a - 1)
        ;
    return de;
}
ll PiCount(ll n){
    if(n < V) return small_pi[n];
    int s = sqrt(n + 0.5), y = cbrt(n + 0.5), a =
        small_pi[y];
    ll res = phi(n, a) + a - 1;
    for(; primes[a] <= s; ++a) res -= max(PiCount(n /
        primes[a]) - PiCount(primes[a]) + 1, 0ll);
    return res;
}

```

6.4 Linear Function Mod Min

```

ll topos(ll x, ll m) {x %= m; if (x < 0) x += m; return
    x;}
//min value of ax + b (mod m) for x \in [0, n - 1]. 0(<
    Log m)
ll min_rem(ll n, ll m, ll a, ll b) {
    a = topos(a, m), b = topos(b, m);
    for (ll g = __gcd(a, m); g > 1; ) return g * min_rem(n
        , m / g, a / g, b / g) + (b % g);
    for (ll nn, nm, na, nb; a; n = nn, m = nm, a = na, b
        = nb) {
        if (a <= m - a) {
            nn = (a * (n - 1) + b) / m;
            if (!nn) break;
            nn += (b < a);
            nm = a, na = topos(-m, a);
            nb = b < a ? b : topos(b - m, a);
        } else {
            ll lst = b - (n - 1) * (m - a);
            if (lst >= 0) {b = lst; break;}
            nn = -(lst / m) + (lst % m < -a) + 1;
            nm = m - a, na = m % (m - a), nb = b % (m - a);

```

```

    }
}
return b;
}
//min value of ax + b (mod m) for x \in [0, n - 1],
//also return min x to get the value. O(log m)
//{value, x}
pair<ll, ll> min_rem_pos(ll n, ll m, ll a, ll b) {
    a = topos(a, m), b = topos(b, m);
    ll mn = min_rem(n, m, a, b), g = __gcd(a, m);
    //ax = (mn - b) (mod m)
    ll x = (extgcd(a, m).first + m) * ((mn - b + m) / g)
        % (m / g);
    return {mn, x};
}

```

6.5 Determinant

```

ll Det(vector<vector<ll>> a) {
    int n = a.size();
    ll det = 1;
    for (int i = 0; i < n; ++i) {
        if (!a[i][i]) {
            det = -det;
            if (det < 0) det += mod;
            for (int j = i + 1; j < n; ++j) if (a[j][i]) {
                swap(a[j], a[i]);
                break;
            }
            if (!a[i][i]) return 0;
        }
        det = det * a[i][i] % mod;
        ll mul = mpow(a[i][i], mod - 2);
        for (int j = 0; j < n; ++j) a[i][j] = a[i][j] * mul
            % mod;
        for (int j = 0; j < n; ++j) if (i ^ j) {
            ll mul = a[j][i];
            for (int k = 0; k < n; ++k) {
                a[j][k] -= a[i][k] * mul % mod;
                if (a[j][k] < 0) a[j][k] += mod;
            }
        }
    }
    return det;
}

```

6.6 Floor Sum

```

// sum^{n-1}_0 floor((a * i + b) / m) in Log(n + m + a + b)
ll floor_sum(ll n, ll m, ll a, ll b) {
    ll ans = 0;
    if (a >= m) ans += (n - 1) * n * (a / m) / 2, a %= m;
    if (b >= m) ans += n * (b / m), b %= m;
    ll y_max = (a * n + b) / m, x_max = (y_max * m - b);
    if (y_max == 0) return ans;
    ans += (n - (x_max + a - 1) / a) * y_max;
    ans += floor_sum(y_max, a, m, (a - x_max % a) % a);
    return ans;
}

```

6.7 Quadratic Residue

```

int Jacobi(int a, int m) {
    int s = 1;
    for (; m > 1; ) {
        a %= m;
        if (a == 0) return 0;
        const int r = __builtin_ctz(a);
        if ((r & 1) && ((m + 2) & 4)) s = -s;
        a >>= r;
        if (a & m & 2) s = -s;
        swap(a, m);
    }
    return s;
}
int QuadraticResidue(int a, int p) {
    if (p == 2) return a & 1;
    const int jc = Jacobi(a, p);
    if (jc == 0) return 0;
    if (jc == -1) return -1;
    int b, d;
}

```

```

for (; ; ) {
    b = rand() % p;
    d = (1LL * b * b + p - a) % p;
    if (Jacobi(d, p) == -1) break;
}
int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
for (int e = (1LL + p) >> 1; e; e >>= 1) {
    if (e & 1) {
        tmp = (1LL * g0 * f0 + 1LL * d * (1LL * g1 * f1 %
            p)) % p;
        g1 = (1LL * g0 * f1 + 1LL * g1 * f0) % p;
        g0 = tmp;
    }
    tmp = (1LL * f0 * f0 + 1LL * d * (1LL * f1 * f1 % p
        )) % p;
    f1 = (2LL * f0 * f1) % p;
    f0 = tmp;
}
return g0;
}

```

6.8 Simplex

```

struct Simplex { // 0-based
    using T = long double;
    static const int N = 410, M = 30010;
    const T eps = 1e-7;
    int n, m;
    int Left[M], Down[N];
    // Ax <= b, max c^T x
    // result : v, xi = sol[i]
    T a[M][N], b[M], c[N], v, sol[N];
    bool eq(T a, T b) {return fabs(a - b) < eps;}
    bool ls(T a, T b) {return a < b && !eq(a, b);}
    void init(int _n, int _m) {
        n = _n, m = _m, v = 0;
        for (int i = 0; i < m; ++i) for (int j = 0; j < n;
            ++j) a[i][j] = 0;
        for (int i = 0; i < m; ++i) b[i] = 0;
        for (int i = 0; i < n; ++i) c[i] = sol[i] = 0;
    }
    void pivot(int x, int y) {
        swap(Left[x], Down[y]);
        T k = a[x][y]; a[x][y] = 1;
        vector<int> nz;
        for (int i = 0; i < n; ++i) {
            a[x][i] /= k;
            if (!eq(a[x][i], 0)) nz.push_back(i);
        }
        b[x] /= k;
        for (int i = 0; i < m; ++i) {
            if (i == x || eq(a[i][y], 0)) continue;
            k = a[i][y], a[i][y] = 0;
            b[i] -= k * b[x];
            for (int j : nz) a[i][j] -= k * a[x][j];
        }
        if (eq(c[y], 0)) return;
        k = c[y], c[y] = 0, v += k * b[x];
        for (int i : nz) c[i] -= k * a[x][i];
    }
    // 0: found solution, 1: no feasible solution, 2:
    // unbounded
    int solve() {
        for (int i = 0; i < n; ++i) Down[i] = i;
        for (int i = 0; i < m; ++i) Left[i] = n + i;
        while (1) {
            int x = -1, y = -1;
            for (int i = 0; i < m; ++i) if (ls(b[i], 0) && (x
                == -1 || b[i] < b[x])) x = i;
            if (x == -1) break;
            for (int i = 0; i < n; ++i) if (ls(a[x][i], 0) &&
                (y == -1 || a[x][i] < a[x][y])) y = i;
            if (y == -1) return 1;
            pivot(x, y);
        }
        while (1) {
            int x = -1, y = -1;
            for (int i = 0; i < n; ++i) if (ls(0, c[i]) && (y
                == -1 || c[i] > c[y])) y = i;
            if (y == -1) break;
            for (int i = 0; i < m; ++i) if (ls(0, a[i][y]) &&
                (x == -1 || b[i] / a[i][y] < b[x] / a[x][y]))

```



```

    ) x = i;
    if (x == -1) return 2;
    pivot(x, y);
}
for (int i = 0; i < m; ++i) if (Left[i] < n) sol[
    Left[i]] = b[i];
return 0;
}
};

```

6.9 Berlekamp Massey

```

vector<ll> BerlekampMassey(vector<ll> a) {
    // find min |c| such that a_n = sum c_j * a_{n-j-1}, 0-based
    // O(N^2), if |c| = k, |a| >= 2k sure correct
    auto f = [&](vector<ll> v, ll c) {
        for (ll &x : v) x = mul(x, c);
        return v;
    };
    vector<ll> c, best;
    int pos = 0, n = a.size();
    for (int i = 0; i < n; ++i) {
        ll error = a[i];
        for (int j = 0; j < c.size(); ++j) error = sub(
            error, mul(c[j], a[i-1-j]));
        if (error == 0) continue;
        ll inv = mpow(error, mod-2);
        if (c.empty()) {
            c.resize(i+1);
            pos = i;
            best.pb(inv);
        } else {
            vector<ll> fix = f(best, error);
            fix.insert(fix.begin(), i-pos-1, 0);
            if (fix.size() >= c.size()) {
                best = f(c, sub(0, inv));
                best.insert(best.begin(), inv);
                pos = i;
                c.resize(fix.size());
            }
            for (int j = 0; j < fix.size(); ++j) c[j] = add(
                [j], fix[j]);
        }
    }
    return c;
}

```

6.10 Linear Programming Construction

Standard form: maximize $c^T x$ subject to $Ax \leq b$ and $x \geq 0$.
 Dual LP: minimize $b^T y$ subject to $A^T y \geq c$ and $y \geq 0$.
 \bar{x} and \bar{y} are optimal if and only if for all $i \in [1, n]$, either $\bar{x}_i = 0$ or $\sum_{j=1}^m A_{ji} \bar{y}_j = c_i$ holds and for all $i \in [1, m]$ either $\bar{y}_i = 0$ or $\sum_{j=1}^n A_{ij} \bar{x}_j = b_j$ holds.

1. In case of minimization, let $c'_i = -c_i$
2. $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3. $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
4. If x_i has no lower bound, replace x_i with $x_i - x'_i$

6.11 Euclidean

- $m = \lfloor \frac{a+b}{c} \rfloor$
- Time complexity: $O(\log n)$

$$\begin{aligned}
 f(a, b, c, n) &= \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)}{2} + \lfloor \frac{b}{c} \rfloor \cdot (n+1) \\ + f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm - f(c, c-b-1, a, m-1), & \text{otherwise} \end{cases} \\
 g(a, b, c, n) &= \sum_{i=0}^n i \lfloor \frac{ai+b}{c} \rfloor \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot \frac{n(n+1)}{2} \\ + g(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1)) \\ - h(c, c-b-1, a, m-1), & \text{otherwise} \end{cases}
 \end{aligned}$$

$$\begin{aligned}
 h(a, b, c, n) &= \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor^2 \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor^2 \cdot (n+1) \\ + \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) \\ + h(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{a}{c} \rfloor \cdot g(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{b}{c} \rfloor \cdot f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm(m+1) - 2g(c, c-b-1, a, m-1) \\ - 2f(c, c-b-1, a, m-1) - f(a, b, c, n), & \text{otherwise} \end{cases}
 \end{aligned}$$

6.12 Theorem

- Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

- Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji} \cdot \frac{\text{rank}(D)}{2}$ is the maximum matching on G .

- Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there are

$$\frac{(n-2)!}{(d_1-1)!(d_2-1)! \cdots (d_n-1)!}$$

spanning trees.

- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

- Erdős-Gallai Theorem

A sequence of non-negative integers $d_1 \geq d_2 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + d_2 + \dots + d_n$ is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

holds for all $1 \leq k \leq n$.

- Burnside's Lemma

Let X be a set and G be a group that acts on X . For $g \in G$, denote by X^g the elements fixed by g :

$$X^g = \{x \in X \mid gx = x\}$$

Then

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|.$$

- Gale-Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^k b_i$

holds for every $1 \leq k \leq n$.

- Fulkerson-Chen-Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and

$\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Möbius inversion formula

- $f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f(\frac{n}{d})$
- $f(n) = \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu(\frac{d}{n}) f(d)$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.

- Volume = $\pi h^2(3r - h)/3 = \pi h(3a^2 + h^2)/6 = \pi r^3(2 + \cos \theta)(1 - \cos \theta)^2/3$.
- Area = $2\pi rh = \pi(a^2 + h^2) = 2\pi r^2(1 - \cos \theta)$.

Chinese Remainder Theorem

- $x \equiv a_i \pmod{m_i}$
- $M = \prod m_i, M_i = M/m_i$
- $t_i M_i \equiv 1 \pmod{m_i}$
- $x = \sum a_i t_i M_i \pmod{M}$

6.13 Estimation

- The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200000 for $n < 1e19$.
- The number of ways of writing n as a sum of positive integers, disregarding the order of the summands. 1, 1, 2, 3, 5, 7, 11, 15, 22, 30 for $n = 0 \sim 9$, 627 for $n = 20$, $\sim 2e5$ for $n = 50$, $\sim 2e8$ for $n = 100$.
- Total number of partitions of n distinct elements: $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, 115975, 678570, 4213597, 27644437, 190899322, \dots$

6.14 General Purpose Numbers

Bernoulli numbers

$$B_0 - 1, B_1^\pm = \pm \frac{1}{2}, B_2 = \frac{1}{6}, B_3 = 0$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0, \text{ EGF is } B(x) = \frac{x}{e^x - 1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}.$$

$$S_m(n) = \sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

- Stirling numbers of the second kind Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k), S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$$

$$x^n = \sum_{i=0}^n S(n, i) (x)_i$$

Pentagonal number theorem

$$\prod_{n=1}^{\infty} (1 - x^n) = 1 + \sum_{k=1}^{\infty} (-1)^k \left(x^{k(3k+1)/2} + x^{k(3k-1)/2} \right)$$

Catalan numbers

$$C_n^{(k)} = \frac{1}{(k-1)n+1} \binom{kn}{n}$$

$$C^{(k)}(x) = 1 + x[C^{(k)}(x)]^k$$

Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \geq j$, k j:s s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.15 Tips for Generating Funtion

Ordinary Generating Function $A(x) = \sum_{i \geq 0} a_i x^i$

- $A(rx) \Rightarrow r^n a_n$
- $A(x) + B(x) \Rightarrow a_n + b_n$
- $A(x)B(x) \Rightarrow \sum_{i=0}^n a_i b_{n-i}$
- $A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} a_{i_1} a_{i_2} \dots a_{i_k}$
- $xA(x)' \Rightarrow na_n$
- $\frac{A(x)}{1-x} \Rightarrow \sum_{i=0}^n a_i$

Exponential Generating Function $A(x) = \sum_{i \geq 0} \frac{a_i}{i!} x_i$

- $A(x) + B(x) \Rightarrow a_n + b_n$
- $A^{(k)}(x) \Rightarrow a_{n+k}$
- $A(x)B(x) \Rightarrow \sum_{i=0}^n \binom{n}{i} a_i b_{n-i}$
- $A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} \binom{n}{i_1, i_2, \dots, i_k} a_{i_1} a_{i_2} \dots a_{i_k}$
- $xA(x) \Rightarrow na_n$

Special Generating Function

- $(1+x)^n = \sum_{i \geq 0} \binom{n}{i} x^i$
- $\frac{1}{(1-x)^n} = \sum_{i \geq 0} \binom{n-1}{i} x^i$

7 Polynomial

7.1 Number Theoretic Transform

```
// mul, add, sub, mpow
// LL -> int if too slow
struct NTT {
    ll w[N];
    NTT() {
        ll dw = mpow(G, (mod - 1) / N);
        w[0] = 1;
        for (int i = 1; i < N; ++i) w[i] = mul(w[i - 1], dw);
    }
    void operator()(vector<ll>& a, bool inv = false) { //
        0 <= a[i] < P
        int x = 0, n = a.size();
        for (int j = 1; j < n - 1; ++j) {
            for (int k = n >> 1; (x ^= k) < k; k >>= 1);
            if (j < x) swap(a[j], a[x]);
        }
        for (int L = 2; L <= n; L <= 1) {
            int dx = N / L, dl = L >> 1;
            for (int i = 0; i < n; i += L) {
                for (int j = i, x = 0; j < i + dl; ++j, x += dx) {
                    ll tmp = mul(a[j + dl], w[x]);
                    a[j + dl] = sub(a[j], tmp);
                    a[j] = add(a[j], tmp);
                }
            }
        }
        if (inv) {
            reverse(a.begin() + 1, a.end());
            ll invn = mpow(n, mod - 2);
            for (int i = 0; i < n; ++i) a[i] = mul(a[i], invn);
        }
    }
} ntt;
```

7.2 Fast Fourier Transform

```
using T = complex<double>;
const double PI = acos(-1);
struct NTT {
    T w[N];
    FFT() {
        T dw = {cos(2 * PI / N), sin(2 * PI / N)};
        w[0] = 1;
        for (int i = 1; i < N; ++i) w[i] = w[i - 1] * dw;
    }
    void operator()(vector<T>& a, bool inv = false) {
        // see NTT, replace LL with T
        if (inv) {
            reverse(a.begin() + 1, a.end());
            T invn = 1.0 / n;
            for (int i = 0; i < n; ++i) a[i] = a[i] * invn;
        }
    }
} ntt;
```

// after mul, round i.real()

7.3 Primes

Prime	Root	Prime	Root
7681	17	167772161	3
12289	11	104857601	3
40961	3	985661441	3
65537	3	998244353	3
786433	10	1107296257	10
5767169	3	2013265921	31
7340033	3	2810183681	11
23068673	3	2885681153	3
469762049	3	605028353	3
2061584302081	7	1945555039024054273	5
2748779069441	3	9223372036737335297	3

7.4 Polynomial Operations

```
vector<ll> Mul(vector<ll> a, vector<ll> b, int bound
    = N) {
    int m = a.size() + b.size() - 1, n = 1;
    while (n < m) n <= 1;
```

```

a.resize(n), b.resize(n);
ntt(a), ntt(b);
vector<ll> out(n);
for (int i = 0; i < n; ++i) out[i] = mul(a[i], b[i]);
ntt(out, true), out.resize(min(m, bound));
return out;
}

vector<ll> Inverse(vector<ll> a) {
    // O(NlogN), a[0] != 0
    int n = a.size();
    vector<ll> res(1, mpow(a[0], mod - 2));
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        vector<ll> v1(a.begin(), a.begin() + m * 2), v2 = res;
        v1.resize(m * 4), v2.resize(m * 4);
        ntt(v1), ntt(v2);
        for (int i = 0; i < m * 4; ++i) v1[i] = mul(mul(v1[i], v2[i]), v2[i]);
        ntt(v1, true);
        res.resize(m * 2);
        for (int i = 0; i < m; ++i) res[i] = add(res[i], res[i]);
        for (int i = 0; i < m * 2; ++i) res[i] = sub(res[i], v1[i]);
    }
    res.resize(n);
    return res;
}

pair<vector<ll>, vector<ll>> Divide(vector<ll> a, vector<ll> b) {
    // a = bQ + R, O(NlogN), b.back() != 0
    int n = a.size(), m = b.size(), k = n - m + 1;
    if (n < m) return {{0}, a};
    vector<ll> ra = a, rb = b;
    reverse(all(ra)), ra.resize(k);
    reverse(all(rb)), rb.resize(k);
    vector<ll> Q = Mul(ra, Inverse(rb), k);
    reverse(all(Q));
    vector<ll> res = Mul(b, Q), R(m - 1);
    for (int i = 0; i < m - 1; ++i) R[i] = sub(a[i], res[i]);
    return {Q, R};
}

vector<ll> SqrtImpl(vector<ll> a) {
    if (a.empty()) return {0};
    int z = QuadraticResidue(a[0], mod), n = a.size();
    if (z == -1) return {-1};
    vector<ll> q(1, z);
    const int inv2 = (mod + 1) / 2;
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        q.resize(m * 2);
        vector<ll> f2 = Mul(q, q, m * 2);
        for (int i = 0; i < m * 2; ++i) f2[i] = sub(f2[i], a[i]);
        f2 = Mul(f2, Inverse(q), m * 2);
        for (int i = 0; i < m * 2; ++i) q[i] = sub(q[i], mul(f2[i], inv2));
    }
    q.resize(n);
    return q;
}

vector<ll> Sqrt(vector<ll> a) {
    // O(NlogN), return {-1} if not exists
    int n = a.size(), m = 0;
    while (m < n && a[m] == 0) m++;
    if (m == n) return vector<ll>(n);
    if (m & 1) return {-1};
    vector<ll> s = SqrtImpl(vector<ll>(a.begin() + m, a.end()));
    if (s[0] == -1) return {-1};
    vector<ll> res(n);
    for (int i = 0; i < s.size(); ++i) res[i + m / 2] = s[i];
    return res;
}

vector<ll> Derivative(vector<ll> a) {
    int n = a.size();
    vector<ll> res(n - 1);
    for (int i = 0; i < n - 1; ++i) res[i] = mul(a[i + 1], i + 1);
}

```

```

return res;
}

vector<ll> Integral(vector<ll> a) {
    int n = a.size();
    vector<ll> res(n + 1);
    for (int i = 0; i < n; ++i) {
        res[i + 1] = mul(a[i], mpow(i + 1, mod - 2));
    }
    return res;
}

vector<ll> Ln(vector<ll> a) {
    // O(NlogN), a[0] = 1
    int n = a.size();
    if (n == 1) return {0};
    vector<ll> d = Derivative(a);
    a.pop_back();
    return Integral(Mul(d, Inverse(a), n - 1));
}

vector<ll> Exp(vector<ll> a) {
    // O(NlogN), a[0] = 0
    int n = a.size();
    vector<ll> q(1, 1);
    a[0] = add(a[0], 1);
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        vector<ll> g(a.begin(), a.begin() + m * 2), h(all(q));
        h.resize(m * 2), h = Ln(h);
        for (int i = 0; i < m * 2; ++i) {
            g[i] = sub(g[i], h[i]);
        }
        q = Mul(g, q, m * 2);
    }
    q.resize(n);
    return q;
}

vector<ll> Pow(vector<ll> a, ll k) {
    int n = a.size(), m = 0;
    vector<ll> ans(n, 0);
    while (m < n && a[m] == 0) m++;
    if (k && m && (k >= n || k * m >= n)) return ans;
    if (m == n) return ans[0] = 1, ans;
    ll lead = m * k;
    vector<ll> b(a.begin() + m, a.end());
    ll base = mpow(b[0], k), inv = mpow(b[0], mod - 2);
    for (int i = 0; i < n - m; ++i) b[i] = mul(b[i], inv);
    b = Ln(b);
    for (int i = 0; i < n - m; ++i) b[i] = mul(b[i], k % mod);
    b = Exp(b);
    for (int i = lead; i < n; ++i) ans[i] = mul(b[i - lead], base);
    return ans;
}

vector<ll> Evaluate(vector<ll> a, vector<ll> x) {
    if (x.empty()) return {};
    int n = x.size();
    vector<vector<ll>> up(n * 2);
    for (int i = 0; i < n; ++i) up[i + n] = {sub(0, x[i]), 1};
    for (int i = n - 1; i > 0; --i) up[i] = Mul(up[i * 2], up[i * 2 + 1]);
    vector<vector<ll>> down(n * 2);
    down[1] = Divide(a, up[1]).second;
    for (int i = 2; i < n * 2; ++i) down[i] = Divide(down[i > 1], up[i]).second;
    vector<ll> y(n);
    for (int i = 0; i < n; ++i) y[i] = down[i + n][0];
    return y;
}

vector<ll> Interpolate(vector<ll> x, vector<ll> y) {
    int n = x.size();
    vector<vector<ll>> up(n * 2);
    for (int i = 0; i < n; ++i) up[i + n] = {sub(0, x[i]), 1};
    for (int i = n - 1; i > 0; --i) up[i] = Mul(up[i * 2], up[i * 2 + 1]);
    vector<ll> a = Evaluate(Derivative(up[1]), x);
    for (int i = 0; i < n; ++i) {
        a[i] = mul(y[i], mpow(a[i], mod - 2));
    }
}

```

```

vector<vector<ll>> down(n * 2);
for (int i = 0; i < n; ++i) down[i + n] = {a[i]};
for (int i = n - 1; i > 0; --i) {
    vector<ll> lhs = Mul(down[i * 2], up[i * 2 + 1]);
    vector<ll> rhs = Mul(down[i * 2 + 1], up[i * 2]);
    down[i].resize(lhs.size());
    for (int j = 0; j < lhs.size(); ++j) {
        down[i][j] = add(lhs[j], rhs[j]);
    }
}
return down[1];
}

```

7.5 Fast Linear Recursion

```

ll FastLinearRecursion(vector<ll> a, vector<ll> c, ll
    k) {
    // a_n = sigma c_j * a_{n-j-1}, 0-based
    // O(NLogNLogK), |a| = |c|
    int n = a.size();
    if (k < n) return a[k];
    vector<ll> base(n + 1, 1);
    for (int i = 0; i < n; ++i) base[i] = sub(0, c[n - i
        - 1]);
    vector<ll> poly(n);
    (n == 1 ? poly[0] = c[n - 1] : poly[1] = 1);
    auto calc = [&](vector<ll> p1, vector<ll> p2) {
        // O(n^2) brute force or O(n log n) NTT
        return Divide(Mul(p1, p2), base).second;
    };
    vector<ll> res(n, 0); res[0] = 1;
    for (; k; k >= 1, poly = calc(poly, poly)) {
        if (k & 1) res = calc(res, poly);
    }
    ll ans = 0;
    for (int i = 0; i < n; ++i) {
        (ans += res[i] * a[i]) %= mod;
    }
    return ans;
}

```

7.6 Fast Walsh Transform

```

void fwt(vector<int> &a) {
    // and : x += y * (1, -1)
    // or : y += x * (1, -1)
    // xor : x = (x + y) * (1, 1/2)
    //       y = (x - y) * (1, 1/2)
    int n = __lg(a.size());
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < 1 << n; ++j) if (j >> i & 1) {
            int x = a[j ^ (1 << i)], y = a[j];
            // do something
        }
    }
}

vector<int> subs_conv(vector<int> a, vector<int> b) {
    // c_i = sum_{j+k=i} a_j * b_k
    int n = __lg(a.size());
    vector<vector<int>> ha(n + 1, vector<int>(1 << n));
    vector<vector<int>> hb(n + 1, vector<int>(1 << n));
    vector<vector<int>> c(n + 1, vector<int>(1 << n));
    for (int i = 0; i < 1 << n; ++i) {
        ha[__builtin_popcount(i)][i] = a[i];
        hb[__builtin_popcount(i)][i] = b[i];
    }
    for (int i = 0; i <= n; ++i) or_fwt(ha[i]), or_fwt(hb
        [i]);
    for (int i = 0; i <= n; ++i)
        for (int j = 0; i + j <= n; ++j)
            for (int k = 0; k < 1 << n; ++k)
                // mind overflow
                c[i + j][k] += ha[i][k] * hb[j][k];
    for (int i = 0; i <= n; ++i) or_fwt(c[i], true);
    vector<int> ans(1 << n);
    for (int i = 0; i < 1 << n; ++i)
        ans[i] = c[__builtin_popcount(i)][i];
    return ans;
}

```

8 Geometry

8.1 Basic

```

const double eps = 1e-8, PI = acos(-1);
int sign(double x) {return abs(x) <= eps ? 0 : (x > 0 ?
    1 : -1);}
double norm(double x) {
    while (x < -eps) x += PI * 2;
    while (x > PI * 2 + eps) x -= PI * 2;
    return x;
}
struct Pt {
    double x, y;
    Pt (double _x, double _y) : x(_x), y(_y) {}
    Pt operator + (Pt o) {return Pt(x + o.x, y + o.y);}
    Pt operator - (Pt o) {return Pt(x - o.x, y - o.y);}
    Pt operator * (double k) {return Pt(x * k, y * k);}
    Pt operator / (double k) {return Pt(x / k, y / k);}
    double operator * (Pt o) {return x * o.x + y * o.y;}
    double operator ^ (Pt o) {return x * o.y - y * o.x;}
};
struct Line {
    Pt a, b;
};
struct Cir {
    Pt o; double r;
};
double abs2(Pt o) {return o.x * o.x + o.y * o.y;}
double abs(Pt o) {return sqrt(abs2(o));}
int ori(Pt o, Pt a, Pt b) {return sign((o - a) ^ (o - b
    ));}
bool btw(Pt a, Pt b, Pt c) { // c on segment ab?
    return ori(a, b, c) == 0 && sign((c - a) * (c - b))
        <= 0;
}
int pos(Pt a) {return sign(a.y) == 0 ? sign(a.x) < 0 :
    a.y < 0;}
double area(Pt a, Pt b, Pt c) {return abs((a - b) ^ (a
    - c)) / 2;}
double angle(Pt a, Pt b) {return norm(atan2(b.y - a.y,
    b.x - a.x));}
Pt unit(Pt o) {return o / abs(o);}
Pt rot(Pt a, double o) { // CCW
    double c = cos(o), s = sin(o);
    return Pt(c * a.x - s * a.y, s * a.x + c * a.y);
}
Pt perp(Pt a) {return Pt(-a.y, a.x);}
Pt proj_vector(Pt a, Pt b, Pt c) { // vector ac proj to
    ab
    return (b - a) * ((c - a) * (b - a)) / (abs2(b - a));
}
Pt proj_pt(Pt a, Pt b, Pt c) { // point c proj to ab
    return proj_vector(a, b, c) + a;
}

```

8.2 Heart

```

Pt circenter(Pt p0, Pt p1, Pt p2) { // radius = abs(
    center)
    p1 = p1 - p0, p2 = p2 - p0;
    double x1 = p1.x, y1 = p1.y, x2 = p2.x, y2 = p2.y;
    double m = 2. * (x1 * y2 - y1 * x2);
    Pt center(0, 0);
    center.x = (x1 * x1 * y2 - x2 * x2 * y1 + y1 * y2 * (
        y1 - y2)) / m;
    center.y = (x1 * x2 * (x2 - x1) - y1 * y1 * x2 + x1 *
        y2 * y2) / m;
    return center + p0;
}
Pt incenter(Pt p1, Pt p2, Pt p3) { // radius = area / s
    * 2
    double a = abs(p2 - p3), b = abs(p1 - p3), c = abs(p1
        - p2);
    double s = a + b + c;
    return (p1 * a + p2 * b + p3 * c) / s;
}
Pt masscenter(Pt p1, Pt p2, Pt p3)
{ return (p1 + p2 + p3) / 3; }
Pt orthocenter(Pt p1, Pt p2, Pt p3)
{ return masscenter(p1, p2, p3) * 3 - circenter(p1, p2,
    p3) * 2; }

```

8.3 External Bisector

```
Pt external_bisector(Pt p1, Pt p2, Pt p3) { //213
    Pt L1 = p2 - p1, L2 = p3 - p1;
    L2 = L2 * abs(L1) / abs(L2);
    return L1 + L2;
}
```

8.4 Intersection of Segments

```
Pt LinesInter(Line a, Line b) {
    double abc = (a.b - a.a) ^ (b.a - a.a);
    double abd = (a.b - a.a) ^ (b.b - a.a);
    if (sign(abc - abd) == 0) return b.b; // no inter
    return (b.b * abc - b.a * abd) / (abc - abd);
}
vector<Pt> SegsInter(Line a, Line b) {
    if (btw(a.a, a.b, b.a)) return {b.a};
    if (btw(a.a, a.b, b.b)) return {b.b};
    if (btw(b.a, b.b, a.a)) return {a.a};
    if (btw(b.a, b.b, a.b)) return {a.b};
    if (ori(a.a, a.b, b.a) * ori(a.a, a.b, b.b) == -1 &&
        ori(b.a, b.b, a.a) * ori(b.a, b.b, a.b) == -1)
        return {LinesInter(a, b)};
    return {};
}
```

8.5 Intersection of Circle and Line

```
vector<Pt> CircleLineInter(Cir c, Line l) {
    Pt p = l.a + (l.b - l.a) * ((c.o - l.a) * (l.b - l.a)
        ) / abs2(l.b - l.a);
    double s = (l.b - l.a) ^ (c.o - l.a), h2 = c.r * c.r
        - s * s / abs2(l.b - l.a);
    if (sign(h2) == -1) return {};
    if (sign(h2) == 0) return {p};
    Pt h = (l.b - l.a) / abs(l.b - l.a) * sqrt(h2);
    return {p - h, p + h};
}
```

8.6 Intersection of Circles

```
vector<Pt> CirclesInter(Cir c1, Cir c2) {
    double d2 = abs2(c1.o - c2.o), d = sqrt(d2);
    if (d < max(c1.r, c2.r) - min(c1.r, c2.r) || d > c1.r
        + c2.r) return {};
    Pt u = (c1.o + c2.o) / 2 + (c1.o - c2.o) * ((c2.r *
        c2.r - c1.r * c1.r) / (2 * d2));
    double A = sqrt((c1.r + c2.r + d) * (c1.r - c2.r + d)
        * (c1.r + c2.r - d) * (-c1.r + c2.r + d));
    Pt v = Pt(c1.o.y - c2.o.y, -c1.o.x + c2.o.x) * A / (2
        * d2);
    if (sign(v.x) == 0 && sign(v.y) == 0) return {u};
    return {u + v, u - v};
}
```

8.7 Intersection of Polygon and Circle

```
double _area(Pt pa, Pt pb, double r) {
    if (abs(pa) < abs(pb)) swap(pa, pb);
    if (abs(pb) < eps) return 0;
    double S, h, theta;
    double a = abs(pb), b = abs(pa), c = abs(pb - pa);
    double cosB = pb * (pb - pa) / a / c, B = acos(cosB);
    double cosC = (pa * pb) / a / b, C = acos(cosC);
    if (a > r) {
        S = (C / 2) * r * r;
        h = a * b * sin(C) / c;
        if (h < r && B < pi / 2) S -= (acos(h / r) * r * r
            - h * sqrt(r * r - h * h));
    } else if (b > r) {
        theta = pi - B - asin(sin(B) / r * a);
        S = .5 * a * r * sin(theta) + (C - theta) / 2 * r *
            r;
    } else S = .5 * sin(C) * a * b;
    return S;
}
double area_poly_circle(vector<Pt> poly, Pt O, double r)
{
    double S = 0; int n = poly.size();
    for (int i = 0; i < n; ++i)
        S += _area(poly[i] - O, poly[(i + 1) % n] - O, r) *
            ori(O, poly[i], poly[(i + 1) % n]);
}
```

```
return fabs(S);
}
```

8.8 Tangent Lines of Circle and Point

```
vector<Line> tangent(Cir c, Pt p) {
    vector<Line> z;
    double d = abs(p - c.o);
    if (sign(d - c.r) == 0) {
        Pt i = rot(p - c.o, pi / 2);
        z.push_back({p, p + i});
    } else if (d > c.r) {
        double o = acos(c.r / d);
        Pt i = unit(p - c.o), j = rot(i, o) * c.r, k = rot(
            i, -o) * c.r;
        z.push_back({c.o + j, p});
        z.push_back({c.o + k, p});
    }
    return z;
}
```

8.9 Tangent Lines of Circles

```
vector<Line> tangent(Cir c1, Cir c2, int sign1) {
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;
    double d_sq = abs2(c1.o - c2.o);
    if (sign(d_sq) == 0) return ret;
    double d = sqrt(d_sq);
    Pt v = (c2.o - c1.o) / d;
    double c = (c1.r - sign1 * c2.r) / d;
    if (c * c > 1) return ret;
    double h = sqrt(max(0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
        Pt n = Pt(v.x * c - sign2 * h * v.y, v.y * c +
            sign2 * h * v.x);
        Pt p1 = c1.o + n * c1.r;
        Pt p2 = c2.o + n * (c2.r * sign1);
        if (sign(p1.x - p2.x) == 0 && sign(p1.y - p2.y) ==
            0)
            p2 = p1 + perp(c2.o - c1.o);
        ret.pb({p1, p2});
    }
    return ret;
}
```

8.10 Point In Convex

```
bool PointInConvex(const vector<Pt> &C, Pt p, bool
    strict = true) {
    int a = 1, b = int(C.size()) - 1, r = !strict;
    if (C.size() == 0) return false;
    if (C.size() < 3) return r && btw(C[0], C.back(), p);
    if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
    if (ori(C[0], C[a], p) >= r || ori(C[0], C[b], p) <=
        -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (ori(C[0], C[c], p) > 0 ? b : a) = c;
    }
    return ori(C[a], C[b], p) < r;
}
```

8.11 Point Segment Distance

```
double PointSegDist(Pt q0, Pt q1, Pt p) {
    if (sign(abs(q0 - q1)) == 0) return abs(q0 - p);
    if (sign((q1 - q0) * (p - q0)) >= 0 && sign((q0 - q1)
        * (p - q1)) >= 0)
        return fabs(((q1 - q0) ^ (p - q0)) / abs(q0 - q1));
    return min(abs(p - q0), abs(p - q1));
}
```

8.12 Convex Hull

```
vector<Pt> ConvexHull(vector<Pt> pt) {
    int n = pt.size();
    sort(all(pt), [&](Pt a, Pt b) {return a.x == b.x ? a.
        y < b.y : a.x < b.x;});
    vector<Pt> ans = {pt[0]};
    for (int t : {0, 1}) {
```

```

    int m = ans.size();
    for (int i = 1; i < n; ++i) {
        while (ans.size() > m && ori(ans[ans.size() - 2],
            ans.back(), pt[i]) <= 0)
            ans.pop_back();
        ans.push_back(pt[i]);
    }
    reverse(all(pt));
}
ans.pop_back();
return ans;
}

```

8.13 Convex Hull Distance

```

double ConvexHullDist(vector<Pt> A, vector<Pt> B) {
    for (auto &p : B) p = Pt(0, 0) - p;
    auto C = Minkowski(A, B); // assert SZ(C) > 0
    if (PointInConvex(C, Pt(0, 0))) return 0;
    double ans = PointSegDist(C.back(), C[0], Pt(0, 0));
    for (int i = 0; i + 1 < C.size(); ++i) {
        ans = min(ans, PointSegDist(C[i], C[i + 1], Pt(0,
            0)));
    }
    return ans;
}

```

8.14 Minimum Enclosing Circle

```

Cir min_enclosing(vector<Pt> &p) {
    random_shuffle(p.begin(), p.end());
    double r = 0.0;
    Pt cent = p[0];
    for (int i = 1; i < p.size(); ++i) {
        if (abs2(cent - p[i]) <= r) continue;
        cent = p[i];
        r = 0.0;
        for (int j = 0; j < i; ++j) {
            if (abs2(cent - p[j]) <= r) continue;
            cent = (p[i] + p[j]) / 2;
            r = abs2(p[j] - cent);
            for (int k = 0; k < j; ++k) {
                if (abs2(cent - p[k]) <= r) continue;
                cent = circenter(p[i], p[j], p[k]);
                r = abs2(p[k] - cent);
            }
        }
    }
    return {cent, sqrt(r)};
}

```

8.15 Union of Circles

```

vector<pair<double, double>> CoverSegment(Cir a, Cir b)
{
    double d = abs(a.o - b.o);
    vector<pair<double, double>> res;
    if (sign(a.r + b.r - d) == 0);
    else if (d <= abs(a.r - b.r) + eps) {
        if (a.r < b.r) res.emplace_back(0, 2 * pi);
    } else if (d < abs(a.r + b.r) - eps) {
        double o = acos((a.r * a.r + d * d - b.r * b.r) /
            (2 * a.r * d)), z = atan2((b.o - a.o).y, (b.o -
            a.o).x);
        if (z < 0) z += 2 * pi;
        double l = z - o, r = z + o;
        if (l < 0) l += 2 * pi;
        if (r > 2 * pi) r -= 2 * pi;
        if (l > r) res.emplace_back(l, 2 * pi), res.
            emplace_back(0, r);
        else res.emplace_back(l, r);
    }
    return res;
}
double CircleUnionArea(vector<Cir> c) { // circle
    should be identical
    int n = c.size();
    double a = 0, w;
    for (int i = 0; w = 0, i < n; ++i) {
        vector<pair<double, double>> s = {{2 * pi, 9}}, z;
        for (int j = 0; j < n; ++j) if (i != j) {
            z = CoverSegment(c[i], c[j]);

```

```

            for (auto &e : z) s.push_back(e);
        }
        sort(s.begin(), s.end());
        auto F = [&](double t) { return c[i].r * (c[i].r *
            t + c[i].o.x * sin(t) - c[i].o.y * cos(t)); };
        for (auto &e : s) {
            if (e.first > w) a += F(e.first) - F(w);
            w = max(w, e.second);
        }
    }
    return a * 0.5;
}

```

8.16 Union of Polygons

```

double polyUnion(vector<vector<Pt>> poly) {
    int n = poly.size();
    double ans = 0;
    auto solve = [&](Pt a, Pt b, int cid) {
        vector<pair<Pt, int>> event;
        for (int i = 0; i < n; ++i) {
            int st = 0, sz = poly[i].size();
            while (st < sz && ori(poly[i][st], a, b) != 1) st
                ++;
            if (st == sz) continue;
            for (int j = 0; j < sz; ++j) {
                Pt c = poly[i][(j + st) % sz], d = poly[i][(j +
                    st + 1) % sz];
                if (sign((a - b) ^ (c - d)) != 0) {
                    int ok1 = ori(c, a, b) == 1, ok2 = ori(d, a,
                        b) == 1;
                    if (ok1 ^ ok2) event.emplace_back(LinesInter
                        ({a, b}, {c, d}), ok1 ? 1 : -1);
                } else if (ori(c, a, b) == 0 && sign((a - b) *
                    (c - d)) > 0 && i <= cid) {
                    event.emplace_back(c, -1);
                    event.emplace_back(d, 1);
                }
            }
        }
        sort(all(event), [&](pair<Pt, int> i, pair<Pt,
            int> j) {
            return ((a - i.first) * (a - b)) < ((a - j.first)
                * (a - b));
        });
        int now = 0;
        Pt lst = a;
        for (auto [x, y] : event) {
            if (btw(a, b, lst) && btw(a, b, x) && !now) ans
                += lst ^ x;
            now += y, lst = x;
        }
    };
    for (int i = 0; i < n; ++i) for (int j = 0; j < poly[
        i].size(); ++j) {
        solve(poly[i][j], poly[i][(j + 1) % int(poly[i].
            size())], i);
    }
    return ans / 2;
}

```

8.17 Polar Angle Sort

```

void PolarAngleSort(vector<Pt> &pts) {
    sort(all(pts), [&](Pt a, Pt b) {return pos(a) == pos(
        b) ? sign(a ^ b) > 0 : pos(a) < pos(b)});
}

```

8.18 Rotating Caliper

```

void RotatingCaliper(vector<Pt> &pts) {
    int n = pts.size();
    for (int i = 0, j = 2; i < n; ++i) {
        int ni = (i + 1) % n;
        while (true) {
            int nj = (j + 1) % n;
            if (area(pts[j], pts[i], pts[ni]) < area(pts[nj],
                pts[i], pts[ni])) {
                j = nj;
            } else {
                break;
            }
        }
    }
}

```



```

    }
    // do something
}
}

```

8.19 Rotating SweepLine

```

void RotatingSweepLine(vector<Pt> &pt) {
    int n = pt.size();
    vector<int> ord(n), cur(n);
    vector<pii> line;
    for (int i = 0; i < n; ++i) for (int j = 0; j < n; ++j) if (i ^ j)
        line.emplace_back(i, j);
    sort(all(line), [&](pii i, pii j) {
        Pt a = pt[i.second] - pt[i.first], b = pt[j.second] - pt[j.first];
        return (pos(a) == pos(b) ? sign(a ^ b) > 0 : pos(a) < pos(b));
    });
    iota(all(ord), 0);
    sort(all(ord), [&](int i, int j) {
        return (sign(pt[i].y - pt[j].y) == 0 ? pt[i].x < pt[j].x : pt[i].y < pt[j].y);
    });
    for (int i = 0; i < n; ++i) cur[ord[i]] = i;
    for (auto [i, j] : line) {
        // point sort by the distance to Line(i, j)
        tie(cur[i], cur[j], ord[cur[i]], ord[cur[j]]) =
            make_tuple(cur[j], cur[i], j, i);
    }
}

```

8.20 Half Plane Intersection

```

vector<Pt> HalfPlaneInter(vector<Line> vec) {
    // x
    // Line.a -----> Line.b
    int n = vec.size();
    sort(all(vec), [&](Line a, Line b) {
        Pt A = a.b - a.a, B = b.b - b.a;
        if (pos(A) == pos(B)) {
            if (sign(A ^ B) == 0) return sign((b.a - a.a) ^ (b.b - a.a)) > 0;
            return sign(A ^ B) > 0;
        }
        return pos(A) < pos(B);
    });
    auto same = [&](Line a, Line b) {
        return sign((a.b - a.a) ^ (b.b - b.a)) == 0 && sign((a.b - a.a) * (b.b - b.a)) > 0;
    };
    deque<Pt> inter;
    deque<Line> seg;
    for (int i = 0; i < n; ++i) if (!i || !same(vec[i - 1], vec[i])) {
        while (seg.size() >= 2 && sign((vec[i].b - inter.back()) ^ (vec[i].a - inter.back())) == 1) seg.pop_back(), inter.pop_back();
        while (seg.size() >= 2 && sign((vec[i].b - inter.front()) ^ (vec[i].a - inter.front())) == 1) seg.pop_front(), inter.pop_front();
        seg.pb(vec[i]);
        if (seg.size() >= 2) inter.pb(LinesInter(seg[seg.size() - 2], seg.back()));
    }
    while (seg.size() >= 2 && sign((seg.front().b - inter.back()) ^ (seg.front().a - inter.back())) == 1) seg.pop_back(), inter.pop_back();
    inter.pb(LinesInter(seg.front(), seg.back()));
    return vector<Pt>(all(inter));
}

```

8.21 Minkowski Sum

```

void reorder(vector<Pt> &P) {
    rotate(P.begin(), min_element(all(P), [&](Pt a, Pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    })), P.end());
}
vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
    // P, Q: convex polygon

```

```

    reorder(P), reorder(Q);
    int n = P.size(), m = Q.size();
    P.pb(P[0]), P.pb(P[1]), Q.pb(Q[0]), Q.pb(Q[1]);
    vector<Pt> ans;
    for (int i = 0, j = 0; i < n || j < m; ) {
        ans.pb(P[i] + Q[j]);
        auto val = (P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]);
        if (val >= 0) i++;
        if (val <= 0) j++;
    }
    return ans;
}

```

8.22 Delaunay Triangulation

```

/* Delaunay Triangulation:
Given a sets of points on 2D plane, find a triangulation such that no points will strictly inside circumcircle of any triangle.
find : return a triangle contain given point
add_point : add a point into triangulation
A Triangle is in triangulation iff. its has_chd is 0.
Region of triangle u: iterate each u.edge[i].tri, each points are u.p[(i+1)%3], u.p[(i+2)%3]
Voronoi diagram: for each triangle in triangulation, the bisector of all its edges will split the region. nearest point will belong to the triangle containing it
*/
const ll inf = MAXC * MAXC * 100; // Lower_bound
unknown
struct Tri;
struct Edge {
    Tri* tri; int side;
    Edge(): tri(0), side(0){}
    Edge(Tri* _tri, int _side): tri(_tri), side(_side){}
};
struct Tri {
    pll p[3];
    Edge edge[3];
    Tri* chd[3];
    Tri() {}
    Tri(const pll& p0, const pll& p1, const pll& p2) {
        p[0] = p0; p[1] = p1; p[2] = p2;
        chd[0] = chd[1] = chd[2] = 0;
    }
    bool has_chd() const { return chd[0] != 0; }
    int num_chd() const {
        return !!chd[0] + !!chd[1] + !!chd[2];
    }
    bool contains(pll const& q) const {
        for (int i = 0; i < 3; ++i)
            if (ori(p[i], p[(i + 1) % 3], q) < 0)
                return 0;
        return 1;
    }
} pool[N * 10], *tris;
void edge(Edge a, Edge b) {
    if(a.tri) a.tri->edge[a.side] = b;
    if(b.tri) b.tri->edge[b.side] = a;
}
struct Trig { // Triangulation
    Trig() {
        the_root = // Tri should at least contain all points
        new(tris++) Tri(pll(-inf, -inf), pll(inf + inf, -inf), pll(-inf, inf + inf));
    }
    Tri* find(pll p) { return find(the_root, p); }
    void add_point(const pll &p) { add_point(find(the_root, p), p); }
    Tri* the_root;
    static Tri* find(Tri* root, const pll &p) {
        while (1) {
            if (!root->has_chd())
                return root;
            for (int i = 0; i < 3 && root->chd[i]; ++i)
                if (root->chd[i]->contains(p)) {
                    root = root->chd[i];
                    break;
                }
        }
    }
    assert(0); // "point not found"
}

```

```

}
void add_point(Tri* root, pll const& p) {
    Tri* t[3];
    /* split it into three triangles */
    for (int i = 0; i < 3; ++i)
        t[i] = new(tris++) Tri(root->p[i], root->p[(i + 1) % 3], p);
    for (int i = 0; i < 3; ++i)
        edge(Edge(t[i], 0), Edge(t[(i + 1) % 3], 1));
    for (int i = 0; i < 3; ++i)
        edge(Edge(t[i], 2), root->edge[(i + 2) % 3]);
    for (int i = 0; i < 3; ++i)
        root->chd[i] = t[i];
    for (int i = 0; i < 3; ++i)
        flip(t[i], 2);
}
void flip(Tri* tri, int pi) {
    Tri* trj = tri->edge[pi].tri;
    int pj = tri->edge[pi].side;
    if (!trj) return;
    if (!in_cc(tri->p[0], tri->p[1], tri->p[2], trj->p[0], trj->p[1], trj->p[2])) return;
    /* flip edge between tri, trj */
    Tri* trk = new(tris++) Tri(tri->p[(pi + 1) % 3], trj->p[pj], tri->p[pi]);
    Tri* trl = new(tris++) Tri(trj->p[(pj + 1) % 3], tri->p[pi], trj->p[pj]);
    edge(Edge(trk, 0), Edge(trl, 0));
    edge(Edge(trk, 1), tri->edge[(pi + 2) % 3]);
    edge(Edge(trk, 2), trj->edge[(pj + 1) % 3]);
    edge(Edge(trl, 1), trj->edge[(pj + 2) % 3]);
    edge(Edge(trl, 2), tri->edge[(pi + 1) % 3]);
    tri->chd[0] = trk; tri->chd[1] = trl; tri->chd[2] = 0;
    trj->chd[0] = trk; trj->chd[1] = trl; trj->chd[2] = 0;
    flip(trk, 1); flip(trk, 2);
    flip(trl, 1); flip(trl, 2);
}
}
vector<Tri*> triang; // vector of all triangle
set<Tri*> vst;
void go(Tri* now) { // store all tri into triang
    if (vst.find(now) != vst.end())
        return;
    vst.insert(now);
    if (!now->has_chd())
        return triang.pb(now);
    for (int i = 0; i < now->num_chd(); ++i)
        go(now->chd[i]);
}
void build(int n, pll* ps) { // build triangulation
    tris = pool; triang.clear(); vst.clear();
    random_shuffle(ps, ps + n);
    Trig tri; // the triangulation structure
    for (int i = 0; i < n; ++i)
        tri.add_point(ps[i]);
    go(tri.the_root);
}

```

8.23 Triangulation Voronoi

```

vector<Line> ls[N];
pll arr[N];
Line make_line(pdd p, Line l) {
    pdd d = l.Y - l.X; d = perp(d);
    pdd m = (l.X + l.Y) / 2;
    l = Line(m, m + d);
    if (ori(l.X, l.Y, p) < 0)
        l = Line(m + d, m);
    return l;
}
double calc_area(int id) {
    // use to calculate the area of point "strictly in the convex hull"
    vector<Line> hpi = halfPlaneInter(ls[id]);
    vector<pdd> ps;
    for (int i = 0; i < SZ(hpi); ++i)
        ps.pb(intersect(hpi[i].X, hpi[i].Y, hpi[(i + 1) % SZ(hpi)].X, hpi[(i + 1) % SZ(hpi)].Y));
    double rt = 0;
    for (int i = 0; i < SZ(ps); ++i)

```

```

        rt += cross(ps[i], ps[(i + 1) % SZ(ps)]);
    return fabs(rt) / 2;
}
void solve(int n, pii *oarr) {
    map<pll, int> mp;
    for (int i = 0; i < n; ++i)
        arr[i] = pll(oarr[i].X, oarr[i].Y), mp[arr[i]] = i;
    build(n, arr); // Triangulation
    for (auto *t : triang) {
        vector<int> p;
        for (int i = 0; i < 3; ++i)
            if (mp.find(t->p[i]) != mp.end())
                p.pb(mp[t->p[i]]);
        for (int i = 0; i < SZ(p); ++i)
            for (int j = i + 1; j < SZ(p); ++j) {
                Line l(oarr[p[i]], oarr[p[j]]);
                ls[p[i]].pb(make_line(oarr[p[i]], l));
                ls[p[j]].pb(make_line(oarr[p[j]], l));
            }
    }
}

```

9 Else

9.1 Bit Hack

```

long long next_perm(long long v) {
    long long t = v | (v - 1);
    return (t + 1) | (((~t & -~t) - 1) >> (__builtin_ctz(v) + 1));
}
void subset(long long s) {
    long long sub = s;
    while (sub) sub = (sub - 1) & s;
}

```

9.2 Dynamic Programming Condition

9.2.1 Totally Monotone (Concave/Convex)

$$\forall i < i', j < j', B[i][j] \leq B[i'][j] \implies B[i][j'] \leq B[i'][j']$$

$$\forall i < i', j < j', B[i][j] \geq B[i'][j] \implies B[i][j'] \geq B[i'][j']$$

9.2.2 Monge Condition (Concave/Convex)

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \geq B[i][j'] + B[i'][j]$$

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \leq B[i][j'] + B[i'][j]$$

9.2.3 Optimal Split Point

If

$$B[i][j] + B[i+1][j+1] \geq B[i][j+1] + B[i+1][j]$$

then

$$H_{i,j-1} \leq H_{i,j} \leq H_{i+1,j}$$

9.3 Slope Trick

```

template<typename T>
struct slope_trick_convex {
    T minn = 0, ground_l = 0, ground_r = 0;
    priority_queue<T, vector<T>, less<T>> left;
    priority_queue<T, vector<T>, greater<T>> right;
    slope_trick_convex() {left.push(numeric_limits<T>::min() / 2), right.push(numeric_limits<T>::max() / 2);}
    void push_left(T x) {left.push(x - ground_l);}
    void push_right(T x) {right.push(x - ground_r);}
    //add a line with slope 1 to the right starting from x
    void add_right(T x) {
        T l = left.top() + ground_l;
        if (l <= x) push_right(x);
        else push_left(x), push_right(l), left.pop(), minn += 1 - x;
    }
    //add a line with slope -1 to the left starting from x
    void add_left(T x) {
        T r = right.top() + ground_r;
        if (r >= x) push_left(x);
        else push_right(x), push_left(r), right.pop(), minn += x - r;
    }
}

```

```

//val[i]=min(val[j]) for all i-l<=j<=i+r
void expand(T l, T r) {ground_l -= l, ground_r += r;}
void shift_up(T x) {minn += x;}
T get_val(T x) {
    T l = left.top() + ground_l, r = right.top() +
        ground_r;
    if (x >= l && x <= r) return minn;
    if (x < l) {
        vector<T> trash;
        T cur_val = minn, slope = 1, res;
        while (1) {
            trash.push_back(left.top());
            left.pop();
            if (left.top() + ground_l <= x) {
                res = cur_val + slope * (l - x);
                break;
            }
            cur_val += slope * (l - (left.top() + ground_l));
            l = left.top() + ground_l;
            slope += 1;
        }
        for (auto i : trash) left.push(i);
        return res;
    }
    if (x > r) {
        vector<T> trash;
        T cur_val = minn, slope = 1, res;
        while (1) {
            trash.push_back(right.top());
            right.pop();
            if (right.top() + ground_r >= x) {
                res = cur_val + slope * (x - r);
                break;
            }
            cur_val += slope * ((right.top() + ground_r) -
                r);
            r = right.top() + ground_r;
            slope += 1;
        }
        for (auto i : trash) right.push(i);
        return res;
    }
    assert(0);
}
};

```

9.4 Manhattan MST

```

void solve(int n) {
    init();
    vector<int> v(n), ds;
    for (int i = 0; i < n; ++i) {
        v[i] = i;
        ds.push_back(x[i] - y[i]);
    }
    sort(ds.begin(), ds.end());
    ds.resize(unique(ds.begin(), ds.end()) - ds.begin());
    sort(v.begin(), v.end(), [&](int i, int j) { return x
        [i] == x[j] ? y[i] > y[j] : x[i] > x[j]; });
    int j = 0;
    for (int i = 0; i < n; ++i) {
        int p = lower_bound(ds.begin(), ds.end(), x[v[i]] -
            y[v[i]]) - ds.begin() + 1;
        pair<int, int> q = query(p);
        // query return prefix minimum
        if (~q.second) add_edge(v[i], q.second);
        add(p, make_pair(x[v[i]] + y[v[i]], v[i]));
    }
}
void make_graph() {
    solve(n);
    for (int i = 0; i < n; ++i) swap(x[i], y[i]);
    solve(n);
    for (int i = 0; i < n; ++i) x[i] = -x[i];
    solve(n);
    for (int i = 0; i < n; ++i) swap(x[i], y[i]);
    solve(n);
}

```

9.5 Dynamic MST

```

int cnt[maxn], cost[maxn], st[maxn], ed[maxn];
pair<int, int> qr[maxn];
// qr[i].first = id of edge to be changed, qr[i].second
// = weight after operation
// cnt[i] = number of operation on edge i
// call solve(0, q - 1, v, 0), where v contains edges i
// such that cnt[i] == 0
void contract(int l, int r, vector<int> v, vector<int>
    &x, vector<int> &y) {
    sort(v.begin(), v.end(), [&](int i, int j) {
        if (cost[i] == cost[j]) return i < j;
        return cost[i] < cost[j];
    });
    djs.save();
    for (int i = l; i <= r; ++i) djs.merge(st[qr[i].first],
        ed[qr[i].first]);
    for (int i = 0; i < (int)v.size(); ++i) {
        if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
            x.push_back(v[i]);
            djs.merge(st[v[i]], ed[v[i]]);
        }
    }
    djs.undo();
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) djs.merge(st[x[i]],
        ed[x[i]]);
    for (int i = 0; i < (int)v.size(); ++i) {
        if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
            y.push_back(v[i]);
            djs.merge(st[v[i]], ed[v[i]]);
        }
    }
    djs.undo();
}
void solve(int l, int r, vector<int> v, long long c) {
    if (l == r) {
        cost[qr[l].first] = qr[l].second;
        if (st[qr[l].first] == ed[qr[l].first]) {
            printf("%Lld\n", c);
            return;
        }
        int minv = qr[l].second;
        for (int i = 0; i < (int)v.size(); ++i) minv = min(
            minv, cost[v[i]]);
        printf("%Lld\n", c + minv);
        return;
    }
    int m = (l + r) >> 1;
    vector<int> lv = v, rv = v;
    vector<int> x, y;
    for (int i = m + 1; i <= r; ++i) {
        cnt[qr[i].first]--;
        if (cnt[qr[i].first] == 0) lv.push_back(qr[i].first);
    }
    contract(l, m, lv, x, y);
    long long lc = c, rc = c;
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) {
        lc += cost[x[i]];
        djs.merge(st[x[i]], ed[x[i]]);
    }
    solve(l, m, y, lc);
    djs.undo();
    x.clear(), y.clear();
    for (int i = m + 1; i <= r; ++i) cnt[qr[i].first]++;
    for (int i = l; i <= m; ++i) {
        cnt[qr[i].first]--;
        if (cnt[qr[i].first] == 0) rv.push_back(qr[i].first);
    }
    contract(m + 1, r, rv, x, y);
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) {
        rc += cost[x[i]];
        djs.merge(st[x[i]], ed[x[i]]);
    }
    solve(m + 1, r, y, rc);
    djs.undo();
    for (int i = l; i <= m; ++i) cnt[qr[i].first]++;
}

```

9.6 ALL LCS

```
void all_lcs(string s, string t) { // 0-base
    vector<int> h(t.size());
    iota(all(h), 0);
    for (int a = 0; a < s.size(); ++a) {
        int v = -1;
        for (int c = 0; c < t.size(); ++c)
            if (s[a] == t[c] || h[c] < v)
                swap(h[c], v);
        // LCS(s[0, a], t[b, c]) =
        // c - b + 1 - sum([h[i] >= b] | i <= c)
        // h[i] might become -1 !!
    }
}
```

9.7 Hilbert Curve

```
long long hilbertOrder(int x, int y, int pow, int
    rotate) {
    if (pow == 0) return 0;
    int hpow = 1 << (pow-1);
    int seg = (x < hpow) ? ((y < hpow) ? 0 : 3) : ((y <
        hpow) ? 1 : 2);
    seg = (seg + rotate) & 3;
    const int rotateDelta[4] = {3, 0, 0, 1};
    int nx = x & (x ^ hpow), ny = y & (y ^ hpow);
    int nrot = (rotate + rotateDelta[seg]) & 3;
    long long subSquareSize = 1ll << (pow * 2 - 2);
    long long ans = seg * subSquareSize;
    long long add = hilbertOrder(nx, ny, pow - 1, nrot);
    ans += (seg == 1 || seg == 2) ? add : (subSquareSize
        - add - 1);
    return ans;
}
```

9.8 Pbds

```
#include <ext/pb_ds/priority_queue.hpp>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
#include <ext/rope>
using namespace __gnu_cxx;
__gnu_pbds::priority_queue<int> pq1, pq2;
pq1.join(pq2); // pq1 += pq2, pq2 = {}
cc_hash_table<int, int> m1;
tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update> oset;
oset.insert(2), oset.insert(4);
*oset.find_by_order(1), oset.order_of_key(1); // 4 0
bitset<100> BS;
BS.flip(3), BS.flip(5);
BS._Find_first(), BS._Find_next(3); // 3 5
rope<int> rp1, rp2;
rp1.push_back(1), rp1.push_back(3);
rp1.insert(0, 2); // pos, num
rp1.erase(0, 2); // pos, len
rp1.substr(0, 2); // pos, len
rp2.push_back(4);
rp1 += rp2, rp2 = rp1;
rp2[0], rp2[1]; // 3 4
```

9.9 Random

```
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(uint64_t a) const {
        static const uint64_t FIXED_RANDOM = chrono::
            steady_clock::now().time_since_epoch().count();
        return splitmix64(i + FIXED_RANDOM);
    }
};
unordered_map<int, int, custom_hash> m1;
random_device rd; mt19937 rng(rd());
```

9.10 Smawk Algorithm

```
11 query(int l, int r) {
    // ...
}
struct SMAWK {
    // Condition:
    // If M[l][0] < M[l][1] then M[0][0] < M[0][1]
    // If M[l][0] == M[l][1] then M[0][0] <= M[0][1]
    // For all i, find r_i s.t. M[i][r_i] is maximum //
    // minimum.
    int ans[N], tmp[N];
    void interpolate(vector<int> l, vector<int> r) {
        int n = l.size(), m = r.size();
        vector<int> nl;
        for (int i = 1; i < n; i += 2) {
            nl.push_back(l[i]);
        }
        run(nl, r);
        for (int i = 1, j = 0; i < n; i += 2) {
            while (j < m && r[j] < ans[l[i]])
                j++;
            assert(j < m && ans[l[i]] == r[j]);
            tmp[l[i]] = j;
        }
        for (int i = 0; i < n; i += 2) {
            int curl = 0, curr = m - 1;
            if (i)
                curl = tmp[l[i - 1]];
            if (i + 1 < n)
                curr = tmp[l[i + 1]];
            11 res = query(l[i], r[curl]);
            ans[l[i]] = r[curl];
            for (int j = curl + 1; j <= curr; ++j) {
                11 nxt = query(l[i], r[j]);
                if (res < nxt)
                    res = nxt, ans[l[i]] = r[j];
            }
        }
    }
    void reduce(vector<int> l, vector<int> r) {
        int n = l.size(), m = r.size();
        vector<int> nr;
        for (int j : r) {
            while (!nr.empty()) {
                int i = nr.size() - 1;
                if (query(l[i], nr.back()) <= query(l[i], j))
                    nr.pop_back();
                else
                    break;
            }
            if (nr.size() < n)
                nr.push_back(j);
        }
        run(l, nr);
    }
    void run(vector<int> l, vector<int> r) {
        int n = l.size(), m = r.size();
        if (max(n, m) <= 2) {
            for (int i : l) {
                ans[i] = r[0];
                if (m > 1) {
                    if (query(i, r[0]) < query(i, r[1]))
                        ans[i] = r[1];
                }
            }
        } else if (n >= m) {
            interpolate(l, r);
        } else {
            reduce(l, r);
        }
    }
};
```

9.11 Matroid Intersection

Start from $S = \emptyset$. In each iteration, let

- $Y_1 = \{x \notin S \mid S \cup \{x\} \in I_1\}$
- $Y_2 = \{x \notin S \mid S \cup \{x\} \in I_2\}$

If there exists $x \in Y_1 \cap Y_2$, insert x into S . Otherwise for each $x \in S, y \notin S$, create edges

- $x \rightarrow y$ if $S - \{x\} \cup \{y\} \in I_1$.
- $y \rightarrow x$ if $S - \{x\} \cup \{y\} \in I_2$.

Find a *shortest* path (with BFS) starting from a vertex in Y_1 and ending at a vertex in Y_2 which doesn't pass through any other vertices in Y_2 , and alternate the path. The size of S will be incremented by 1 in each iteration. For the weighted case, assign weight $w(x)$ to vertex x if $x \in S$ and $-w(x)$ if $x \notin S$. Find the path with the minimum number of edges among all minimum length paths and alternate it.

9.12 Python Misc

```
from [decimal, fractions, math, random] import *
setcontext(Context(prec=10, Emax=MAX_EMAX, rounding=
    ROUND_FLOOR))
Decimal('1.1') / Decimal('0.2')
Fraction(3, 7)
Fraction(Decimal('1.14'))
Fraction('1.2').limit_denominator(4).numerator
Fraction(cos(pi / 3)).limit_denominator()
print(*[randint(1, C) for i in range(0, N)], sep=' ')
```