

Contents

1 Basic	1	6.8 Discrete Log	14
1.1 Shell Script	1	6.9 Factorial without Prime Factor	14
1.2 Debug Macro*	1	6.10 Berlekamp Massey	14
1.3 Pragma / FastIO	1	6.11 Simplex	14
1.4 Divide	1	6.12 Euclidean	15
2 Data Structure	1	6.13 Linear Programming Construction	15
2.1 Leftist Tree	1	6.14 Theorem	15
2.2 Splay Tree	1	6.15 Estimation	16
2.3 Link Cut Tree	2	6.16 General Purpose Numbers	16
2.4 Treap	3	7 Polynomial	16
2.5 vEB Tree	3	7.1 Number Theoretic Transform	16
3 Flow / Matching	3	7.2 Fast Fourier Transform	16
3.1 Dinic	3	7.3 Primes	16
3.2 Min Cost Max Flow	4	7.4 Polynomial Operations	16
3.3 Kuhn Munkres	4	7.5 Fast Linear Recursion	18
3.4 Hopcroft Karp	5	7.6 Fast Walsh Transform	18
3.5 SW Min Cut	5	8 Geometry	18
3.6 Gomory Hu Tree	5	8.1 Basic	18
3.7 Blossom	5	8.2 SVG Writer	18
3.8 Min Cost Circulation	6	8.3 Sort	18
3.9 Weighted Blossom	6	8.4 Intersections	19
3.10 Flow Model	7	8.5 Point Inside Check	19
4 Graph	7	8.6 Convex Hull	19
4.1 Heavy-Light Decomposition	7	8.7 Point Segment Distance	19
4.2 Centroid Decomposition	8	8.8 Vector In Polygon	19
4.3 Edge BCC	8	8.9 Minkowski Sum	19
4.4 Vertex BCC / Round Square Tree	8	8.10 Rotating SweepLine	20
4.5 SCC	8	8.11 Half Plane Intersection	20
4.6 2SAT	8	8.12 Minimum Enclosing Circle	20
4.7 Virtual Tree	9	8.13 Heart	20
4.8 Directed MST	9	8.14 Tangents	20
4.9 Dominator Tree	9	8.15 Union of Circles	21
4.10 Bipartite Edge Coloring	9	8.16 Union of Polygons	21
4.11 Edge Coloring	10	8.17 Delaunay Triangulation	21
4.12 Maximum Clique	10	8.18 Triangulation Voronoi	22
5 String	10	8.19 External Bisector	22
5.1 Aho-Corasick Automaton	10	8.20 Intersection Area of Polygon and Circle	22
5.2 KMP Algorithm	11	8.21 3D Point	22
5.3 Z Algorithm	11	8.22 3D Convex Hull	22
5.4 Manacher	11	9 Else	23
5.5 Suffix Array	11	9.1 Pbds	23
5.6 SAIS	11	9.2 Bit Hack	23
5.7 Suffix Automaton	12	9.3 Smawk Algorithm	23
5.8 Minimum Rotation	12	9.4 Slope Trick	23
5.9 Palindrome Tree	12	9.5 ALL LCS	24
5.10 Lyndon Factorization	12	9.6 Hilbert Curve	24
5.11 Main Lorentz	12	9.7 Line Container	24
6 Math	13	9.8 Min Plus Convolution	24
6.1 Miller Rabin / Pollard Rho	13	9.9 Matroid Intersection	24
6.2 Ext GCD	13	9.10 Simulated Annealing	24
6.3 Chinese Remainder Theorem	13	9.11 Bitset LCS	24
6.4 PiCount	13	9.12 Binary Search On Fraction	24
6.5 Linear Function Mod Min	13	9.13 Cyclic Ternary Search	24
6.6 Floor Sum	14	9.14 Tree Hash	25
6.7 Quadratic Residue	14	9.15 Python Misc	25

1 Basic

1.1 Shell Script

```
cpp hash.cpp -dD -P -fpreprocessed | tr -d "[:space:]"
| md5sum | cut -c -6
```

1.2 Debug Macro* [2e0e48]

```
#ifdef ABS
template <typename T>
ostream& operator << (ostream &o, vector<T> vec) {
    o << "{"; int f = 0;
    for (T i : vec) o << (f++ ? " " : "") << i;
    return o << "}"; }
void bug__(int c, auto ...a) {
    cerr << "\e[1;" << c << "m";
    (... , (cerr << a << " "));
    cerr << "\e[0m" << endl; }
#define bug_(c, x...) bug__(c, __LINE__, "[" + string(#x) + "]", x)
#define bug(x...) bug_(32, x)
#define bugv(x...) bug_(36, vector(x))
#define bug_ safe bug_(33, "safe")
#else
```

```
#define bug(x...) void(0)
#define bugv(x...) void(0)
#define safe void(0)
#endif
```

1.3 Pragma / FastIO

```
#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,arch=skylake")
__builtin_ia32_ldmxcsr(__builtin_ia32_stmxcsr()|0x8040)
#include<unistd.h>
char OB[65536]; int OP;
inline char RC() {
    static char buf[65536], *p = buf, *q = buf;
    return p == q && (q = (p = buf) + read(0, buf, 65536)
        ) == buf ? -1 : *p++;
}
inline int R() {
    static char c;
    while((c = RC()) < '0'); int a = c ^ '0';
    while((c = RC()) >= '0') a *= 10, a += c ^ '0';
    return a;
}
inline void W(int n) {
    static char buf[12], p;
    if (n == 0) OB[OP++] = '0'; p = 0;
    while (n) buf[p++] = '0' + (n % 10), n /= 10;
    for (--p; p >= 0; --p) OB[OP++] = buf[p];
    if (OP > 65520) write(1, OB, OP), OP = 0;
}
```

1.4 Divide

```
ll floor(ll a, ll b) {return a / b - (a < 0 && a % b);}
ll ceil(ll a, ll b) {return a / b + (a > 0 && a % b);}
a / b < x -> floor(a, b) + 1 <= x
a / b <= x -> ceil(a, b) <= x
x < a / b -> x <= ceil(a, b) - 1
x <= a / b -> x <= floor(a, b)
```

2 Data Structure

2.1 Leftist Tree [75d338]

```
// max heap
struct node {
    ll rk, data, size, sum;
    node *l, *r;
    node(ll k) : rk(0), data(k), size(1), sum(k), l(0), r(0) {}
};
#undef sz
ll sz(node *p) { return p ? p->size : 0; }
ll rk(node *p) { return p ? p->rk : -1; }
ll sum(node *p) { return p ? p->sum : 0; }
node *merge(node *a, node *b) {
    if (!a || !b) return a ? a : b;
    if (a->data < b->data) swap(a, b);
    a->r = merge(a->r, b);
    if (rk(a->r) > rk(a->l)) swap(a->r, a->l);
    a->rk = rk(a->r) + 1;
    a->size = sz(a->l) + sz(a->r) + 1;
    a->sum = sum(a->l) + sum(a->r) + a->data;
    return a;
}
void pop(node *&o) {
    node *tmp = o;
    o = merge(o->l, o->r);
    delete tmp;
}
```

2.2 Splay Tree [21142b]

```
struct Splay {
    int pa[N], ch[N][2], sz[N], rt, _id;
    ll v[N];
    Splay() {}
    void init() {
        rt = 0, pa[0] = ch[0][0] = ch[0][1] = -1;
        sz[0] = 1, v[0] = inf;
    }
}
```

```

int newnode(int p, int x) {
    int id = _id++;
    v[id] = x, pa[id] = p;
    ch[id][0] = ch[id][1] = -1, sz[id] = 1;
    return id;
}
void rotate(int i) {
    int p = pa[i], x = ch[p][1] == i;
    int gp = pa[p], c = ch[i][!x];
    sz[p] -= sz[i], sz[i] += sz[p];
    if (~c) sz[p] += sz[c], pa[c] = p;
    ch[p][x] = c, pa[p] = i;
    pa[i] = gp, ch[i][!x] = p;
    if (~gp) ch[gp][ch[gp][1] == p] = i;
}
void splay(int i) {
    while (~pa[i]) {
        int p = pa[i];
        if (~pa[p]) rotate(ch[pa[p]][1] == p ^ ch[p][1]
            == i ? i : p);
        rotate(i);
    }
    rt = i;
}
int lower_bound(int x) {
    int i = rt, last = -1;
    while (true) {
        if (v[i] == x) return splay(i), i;
        if (v[i] > x) {
            last = i;
            if (ch[i][0] == -1) break;
            i = ch[i][0];
        }
        else {
            if (ch[i][1] == -1) break;
            i = ch[i][1];
        }
    }
    splay(i);
    return last; // -1 if not found
}
void insert(int x) {
    int i = lower_bound(x);
    if (i == -1) {
        // assert(ch[rt][1] == -1);
        int id = newnode(rt, x);
        ch[rt][1] = id, ++sz[rt];
        splay(id);
    }
    else if (v[i] != x) {
        splay(i);
        int id = newnode(rt, x), c = ch[rt][0];
        ch[rt][0] = id;
        ch[id][0] = c;
        if (~c) pa[c] = id, sz[id] += sz[c];
        ++sz[rt];
        splay(id);
    }
}
};

```

2.3 Link Cut Tree [bca367]

```

// weighted subtree size, weighted path max
struct LCT {
    int ch[N][2], pa[N], v[N], sz[N];
    int sz2[N], w[N], mx[N], _id;
    // sz := sum of v in splay, sz2 := sum of v in
    // virtual subtree
    // mx := max w in splay
    bool rev[N];
    LCT() : _id(1) {}
    int newnode(int _v, int _w) {
        int x = _id++;
        ch[x][0] = ch[x][1] = pa[x] = 0;
        v[x] = sz[x] = _v;
        sz2[x] = 0;
        w[x] = mx[x] = _w;
        rev[x] = false;
        return x;
    }
    void pull(int i) {

```

```

        sz[i] = v[i] + sz2[i];
        mx[i] = w[i];
        if (ch[i][0]) {
            sz[i] += sz[ch[i][0]];
            mx[i] = max(mx[i], mx[ch[i][0]]);
        }
        if (ch[i][1]) {
            sz[i] += sz[ch[i][1]];
            mx[i] = max(mx[i], mx[ch[i][1]]);
        }
    }
    void push(int i) {
        if (rev[i]) reverse(ch[i][0]), reverse(ch[i][1]),
            rev[i] = false;
    }
    void reverse(int i) {
        if (!i) return;
        swap(ch[i][0], ch[i][1]);
        rev[i] ^= true;
    }
    bool isrt(int i) { // rt of splay
        if (!pa[i]) return true;
        return ch[pa[i]][0] != i && ch[pa[i]][1] != i;
    }
    void rotate(int i) {
        int p = pa[i], x = ch[p][1] == i;
        int c = ch[i][!x], gp = pa[p];
        if (ch[gp][0] == p) ch[gp][0] = i;
        else if (ch[gp][1] == p) ch[gp][1] = i;
        pa[i] = gp, ch[i][!x] = p, pa[p] = i;
        ch[p][x] = c, pa[c] = p;
        pull(p), pull(i);
    }
    void splay(int i) {
        vector<int> anc;
        anc.push_back(i);
        while (!isrt(anc.back()))
            anc.push_back(pa[anc.back()]);
        while (!anc.empty())
            push(anc.back()), anc.pop_back();
        while (!isrt(i)) {
            int p = pa[i];
            if (!isrt(p)) rotate(ch[p][1] == i ^ ch[pa[p]][1]
                == p ? i : p);
            rotate(i);
        }
    }
    void access(int i) {
        int last = 0;
        while (i) {
            splay(i);
            if (ch[i][1])
                sz2[i] += sz[ch[i][1]];
            sz2[i] -= sz[last];
            ch[i][1] = last;
            pull(i), last = i, i = pa[i];
        }
    }
    void makert(int i) {
        access(i), splay(i), reverse(i);
    }
    void link(int i, int j) {
        // assert(findrt(i) != findrt(j));
        makert(i);
        makert(j);
        pa[i] = j;
        sz2[j] += sz[i];
        pull(j);
    }
    void cut(int i, int j) {
        makert(i), access(j), splay(i);
        // assert(sz[i] == 2 && ch[i][1] == j);
        ch[i][1] = pa[j] = 0, pull(i);
    }
    int findrt(int i) {
        access(i), splay(i);
        while (ch[i][0]) push(i), i = ch[i][0];
        splay(i);
        return i;
    }
};

```

2.4 Treap [fbf3b7]

```

struct node {
    int data, size;
    node *l, *r;
    node(int k) : data(k), size(1), l(0), r(0) {}
    void up() {
        size = 1;
        if (l) size += l->size;
        if (r) size += r->size;
    }
    void down() {}
};
#undef sz
int sz(node *a) { return a ? a->size : 0; }
node *merge(node *a, node *b) {
    if (!a || !b) return a ? a : b;
    if (rand() % (sz(a) + sz(b)) < sz(a))
        return a->down(), a->r = merge(a->r, b), a->up(), a;
    return b->down(), b->l = merge(a, b->l), b->up(), b;
}
void split(node *o, node *&a, node *&b, int k) {
    if (!o) return a = b = 0, void();
    o->down();
    if (o->data <= k)
        a = o, split(o->r, a->r, b, k), a->up();
    else b = o, split(o->l, a, b->l, k), b->up();
}
void split2(node *o, node *&a, node *&b, int k) {
    if (sz(o) <= k) return a = o, b = 0, void();
    o->down();
    if (sz(o->l) + 1 <= k)
        a = o, split2(o->r, a->r, b, k - sz(o->l) - 1);
    else b = o, split2(o->l, a, b->l, k);
    o->up();
}
node *kth(node *o, int k) {
    if (k <= sz(o->l)) return kth(o->l, k);
    if (k == sz(o->l) + 1) return o;
    return kth(o->r, k - sz(o->l) - 1);
}
int Rank(node *o, int key) {
    if (!o) return 0;
    if (o->data < key)
        return sz(o->l) + 1 + Rank(o->r, key);
    else return Rank(o->l, key);
}
bool erase(node *&o, int k) {
    if (!o) return 0;
    if (o->data == k) {
        node *t = o;
        o->down(), o = merge(o->l, o->r);
        delete t;
        return 1;
    }
    node *&t = k < o->data ? o->l : o->r;
    return erase(t, k) ? o->up(), 1 : 0;
}
void insert(node *&o, int k) {
    node *a, *b;
    o->down(), split(o, a, b, k),
    o = merge(a, merge(new node(k), b));
    o->up();
}
void interval(node *&o, int l, int r) {
    node *a, *b, *c; // [l, r)
    o->down();
    split2(o, a, b, l), split2(b, b, c, r - l);
    // operate
    o = merge(a, merge(b, c)), o->up();
}

```

2.5 vEB Tree [087d11]

```

using u64 = uint64_t;
constexpr int lsb(u64 x)
{ return x ? __builtin_ctzll(x) : 1 << 30; }
constexpr int msb(u64 x)
{ return x ? 63 - __builtin_clzll(x) : -1; }
template<int N, class T=void>
struct veb{
    static const int M=N>1;
    veb<M> ch[1<<N-M];

```

```

    veb<N-M> aux;
    int mn, mx;
    veb() : mn(1<<30), mx(-1) {}
    constexpr int mask(int x) { return x & ((1<<M) - 1); }
    bool empty() { return mx == -1; }
    int min() { return mn; }
    int max() { return mx; }
    bool have(int x) {
        return x == mn ? true : ch[x>>M].have(mask(x));
    }
    void insert_in(int x) {
        if (empty()) return mn = mx = x, void();
        if (x < mn) swap(x, mn);
        if (x > mx) mx = x;
        if (ch[x>>M].empty()) aux.insert_in(x>>M);
        ch[x>>M].insert_in(mask(x));
    }
    void erase_in(int x) {
        if (mn == mx) return mn = 1<<30, mx = -1, void();
        if (x == mn) mn = x = (aux.min() << M) ^ ch[aux.min()].min();
        ch[x>>M].erase_in(mask(x));
        if (ch[x>>M].empty()) aux.erase_in(x>>M);
        if (x == mx) {
            if (aux.empty()) mx = mn;
            else mx = (aux.max() << M) ^ ch[aux.max()].max();
        }
    }
    void insert(int x) {
        if (!have(x)) insert_in(x);
    }
    void erase(int x) {
        if (have(x)) erase_in(x);
    }
    int next(int x) { // >= x
        if (x > mx) return 1<<30;
        if (x <= mn) return mn;
        if (mask(x) <= ch[x>>M].max())
            return ((x>>M) << M) ^ ch[x>>M].next(mask(x));
        int y = aux.next((x>>M) + 1);
        return (y << M) ^ ch[y].min();
    }
    int prev(int x) { // < x
        if (x <= mn) return -1;
        if (x > mx) return mx;
        if (x <= (aux.min() << M) ^ ch[aux.min()].min())
            return mn;
        if (mask(x) > ch[x>>M].min())
            return ((x>>M) << M) ^ ch[x>>M].prev(mask(x));
        int y = aux.prev(x>>M);
        return (y << M) ^ ch[y].max();
    }
};
template<int N>
struct veb<N, typename enable_if<N<=6>::type> {
    u64 a;
    veb() : a(0) {}
    void insert_in(int x) { a |= 1ull<<x; }
    void insert(int x) { a |= 1ull<<x; }
    void erase_in(int x) { a &= ~(1ull<<x); }
    void erase(int x) { a &= ~(1ull<<x); }
    bool have(int x) { return a>>x&1; }
    bool empty() { return a==0; }
    int min() { return lsb(a); }
    int max() { return msb(a); }
    int next(int x) { return lsb(a &~ ((1ull<<x) - 1)); }
    int prev(int x) { return msb(a & ((1ull<<x) - 1)); }
};

```

3 Flow / Matching

3.1 Dinic [b68676]

```

template<typename T>
struct Dinic { // 0-based
    const T INF = numeric_limits<T>::max() / 2;
    struct edge { int to, rev; T cap, flow; };
    int n, s, t;
    vector<vector<edge>> g;
    vector<int> dis, cur;
    T dfs(int u, T cap) {
        if (u == t || !cap) return cap;
        for (int &i = cur[u]; i < sz(g[u]); ++i) {

```

```

    edge &e = g[u][i];
    if (dis[e.to] == dis[u] + 1 && e.flow != e.cap) {
        T df = dfs(e.to, min(e.cap - e.flow, cap));
        if (df) {
            e.flow += df;
            g[e.to][e.rev].flow -= df;
            return df;
        }
    }
    dis[u] = -1;
    return 0;
}

bool bfs() {
    dis.assign(n, -1);
    queue<int> q;
    q.push(s), dis[s] = 0;
    while (!q.empty()) {
        int v = q.front(); q.pop();
        for (auto &u : g[v])
            if (dis[u.to] == -1 && u.flow != u.cap) {
                q.push(u.to);
                dis[u.to] = dis[v] + 1;
            }
    }
    return dis[t] != -1;
}

T solve(int _s, int _t) {
    s = _s, t = _t;
    T flow = 0, df;
    while (bfs()) {
        cur.assign(n, 0);
        while ((df = dfs(s, INF))) flow += df;
    }
    return flow;
}

void add_edge(int u, int v, T cap) {
    g[u].pb(edge{v, sz(g[v]), cap, 0});
    g[v].pb(edge{u, sz(g[u]) - 1, 0, 0});
}

Dinic (int _n) : n(_n), g(n) {}
//void reset() {
//    for (int i = 0; i < n; ++i)
//        for (auto &j : g[i]) j.flow = 0;
//}
};

```

3.2 Min Cost Max Flow [404450]

```

template <typename T1, typename T2>
struct MCMF { // T1 -> flow, T2 -> cost, 0-based
    const T1 INF1 = numeric_limits<T1>::max() / 2;
    const T2 INF2 = numeric_limits<T2>::max() / 2;
    struct edge { int v; T1 f; T2 c; };
    int n, s, t;
    vector<vector<int>> g;
    vector<edge> e;
    vector<T2> dis, pot;
    vector<int> rt, vis;
    // bool DAG()...
    bool SPFA() {
        rt.assign(n, -1), dis.assign(n, INF2);
        vis.assign(n, false);
        queue<int> q;
        q.push(s), dis[s] = 0, vis[s] = true;
        while (!q.empty()) {
            int v = q.front(); q.pop();
            vis[v] = false;
            for (int id : g[v]) {
                auto [u, f, c] = e[id];
                T2 ndis = dis[v] + c + pot[v] - pot[u];
                if (f > 0 && dis[u] > ndis) {
                    dis[u] = ndis, rt[u] = id;
                    if (!vis[u]) vis[u] = true, q.push(u);
                }
            }
        }
        return dis[t] != INF2;
    } // a5dc32
    bool dijkstra() {
        rt.assign(n, -1), dis.assign(n, INF2);
        priority_queue<pair<T2, int>, vector<pair<T2,

```

```

        int>>, greater<pair<T2, int>>> pq;
        dis[s] = 0, pq.emplace(dis[s], s);
        while (!pq.empty()) {
            auto [d, v] = pq.top(); pq.pop();
            if (dis[v] < d) continue;
            for (int id : g[v]) {
                auto [u, f, c] = e[id];
                T2 ndis = dis[v] + c + pot[v] - pot[u];
                if (f > 0 && dis[u] > ndis) {
                    dis[u] = ndis, rt[u] = id;
                    pq.emplace(ndis, u);
                }
            }
        }
        return dis[t] != INF2;
    } // d46baf
    vector<pair<T1, T2>> solve(int _s, int _t) {
        s = _s, t = _t, pot.assign(n, 0);
        vector<pair<T1, T2>> ans; bool fr = true;
        while ((fr ? SPFA() : SPFA())) {
            for (int i = 0; i < n; ++i)
                dis[i] += pot[i] - pot[s];
            T1 add = INF1;
            for (int i = t; i != s; i = e[rt[i] ^ 1].v)
                add = min(add, e[rt[i]].f);
            for (int i = t; i != s; i = e[rt[i] ^ 1].v)
                e[rt[i]].f -= add, e[rt[i] ^ 1].f += add;
            ans.emplace_back(add, dis[t]), fr = false;
            for (int i = 0; i < n; ++i) swap(dis[i], pot[i]);
        }
        return ans;
    }
    void add_edge(int u, int v, T1 f, T2 c) {
        g[u].pb(sz(e)), e.pb({v, f, c});
        g[v].pb(sz(e)), e.pb({u, 0, -c});
    }
    MCMF (int _n) : n(_n), g(n), e() {} // 337601
    //void reset() {
    //    for (int i = 0; i < sz(e); ++i) e[i].f = 0;
    //}
};

```

3.3 Kuhn Munkres [7f3209]

```

template <typename T> // maximum perfect matching
struct KM { // 0-based, remember to init edge weight
    const T INF = numeric_limits<T>::max() / 2;
    int n; vector<vector<T>> w;
    vector<T> hl, hr, slk;
    vector<int> fl, fr, vl, vr, pre;
    queue<int> q;
    bool check(int x) {
        if (vl[x] = 1, ~fl[x])
            return q.push(fl[x]), vr[fl[x]] = 1;
        while (~x) swap(x, fr[fl[x] = pre[x]]);
        return 0;
    }
    void bfs(int s) {
        vl.assign(n, 0), vr.assign(n, 0);
        slk.assign(n, INF), pre.assign(n, 0);
        while (!q.empty()) q.pop();
        q.push(s), vr[s] = 1;
        while (true) {
            T d;
            while (!q.empty()) {
                int y = q.front(); q.pop();
                for (int x = 0; x < n; ++x) {
                    d = hl[x] + hr[y] - w[x][y];
                    if (!vl[x] && slk[x] >= d) {
                        if (pre[x] = y, d) slk[x] = d;
                        else if (!check(x)) return;
                    }
                }
            }
            d = INF;
            for (int x = 0; x < n; ++x)
                if (!vl[x] && d > slk[x]) d = slk[x];
            for (int x = 0; x < n; ++x) {
                if (vl[x]) hl[x] += d;
                else slk[x] -= d;
                if (vr[x]) hr[x] -= d;
            }
        }
    }
};

```

```

    for (int x = 0; x < n; ++x)
        if (!vl[x] && !slk[x] && !check(x)) return;
}
T solve() {
    fl.assign(n, -1), fr.assign(n, -1);
    hl.assign(n, 0), hr.assign(n, 0);
    for (int i = 0; i < n; ++i)
        hl[i] = *max_element(all(w[i]));
    for (int i = 0; i < n; ++i) bfs(i);
    T res = 0;
    for (int i = 0; i < n; ++i) res += w[i][fl[i]];
    return res;
}
void add_edge(int a, int b, T wei) { w[a][b] = wei; }
KM (int _n) : n(_n), w(n, vector<T>(n, -INF)) {}
};

```

3.4 Hopcroft Karp [372c8b]

```

struct HopcroftKarp { // 0-based
    int n, m;
    vector<vector<int>> g;
    vector<int> l, r, d;
    bool dfs(int x) {
        for (int y : g[x]) if (r[y] == -1 ||
            (d[r[y]] == d[x] + 1 && dfs(r[y])))
            return l[x] = y, r[y] = x, d[x] = -1, true;
        return d[x] = -1, false;
    }
    bool bfs() {
        d.assign(n, -1);
        queue<int> q;
        for (int x = 0; x < n; ++x) if (l[x] == -1)
            d[x] = 0, q.push(x);
        bool good = false;
        while (!q.empty()) {
            int x = q.front(); q.pop();
            for (int y : g[x])
                if (r[y] == -1) good = true;
                else if (d[r[y]] == -1)
                    d[r[y]] = d[x] + 1, q.push(r[y]);
        }
        return good;
    }
    int solve() {
        int res = 0;
        l.assign(n, -1), r.assign(m, -1);
        while (bfs())
            for (int x = 0; x < n; ++x) if (l[x] == -1)
                res += dfs(x);
        return res;
    }
    void add_edge(int x, int y) { g[x].pb(y); }
    HopcroftKarp (int _n, int _m) : n(_n), m(_m), g(n) {}
};

```

3.5 SW Min Cut [f7fc17]

```

template<typename T>
struct SW { // 0-based
    const T INF = numeric_limits<T>::max() / 2;
    vector<vector<T>> g;
    vector<T> sum;
    vector<bool> vis, dead;
    int n;
    T solve() {
        T ans = INF;
        for (int r = 0; r + 1 < n; ++r) {
            vis.assign(n, 0), sum.assign(n, 0);
            int num = 0, s = -1, t = -1;
            while (num < n - r) {
                int now = -1;
                for (int i = 0; i < n; ++i)
                    if (!vis[i] && !dead[i] &&
                        (now == -1 || sum[now] > sum[i])) now = i;
                s = t, t = now;
                vis[now] = true, num++;
                for (int i = 0; i < n; ++i)
                    if (!vis[i] && !dead[i]) sum[i] += g[now][i];
            }
            ans = min(ans, sum[t]);
        }
    }
};

```

```

    for (int i = 0; i < n; ++i)
        g[i][s] += g[i][t], g[s][i] += g[t][i];
    dead[t] = true;
}
return ans;
}
void add_edge(int u, int v, T w) {
    g[u][v] += w, g[v][u] += w; }
SW (int _n) : n(_n), g(n, vector<T>(n)), dead(n) {}
};

```

3.6 Gomory Hu Tree [90ead2]

```

vector<array<int, 3>> GomoryHu(Dinic<int> flow) {
    // Tree edge min = mincut (0-based)
    int n = flow.n;
    vector<array<int, 3>> ans;
    vector<int> rt(n);
    for (int i = 1; i < n; ++i) {
        int t = rt[i];
        flow.reset();
        ans.pb({i, t, flow.solve(i, t)});
        flow.bfs();
        for (int j = i + 1; j < n; ++j)
            if (rt[j] == t && flow.dis[j] != -1) rt[j] = i;
    }
    return ans;
}

```

3.7 Blossom [4aa405]

```

struct Matching { // 0-based
    int n, tk;
    vector<vector<int>> g;
    vector<int> fa, pre, match, s, t;
    queue<int> q;
    int Find(int u) {
        return u == fa[u] ? u : fa[u] = Find(fa[u]); }
    int lca(int x, int y) {
        tk++, x = Find(x), y = Find(y);
        for (; ; swap(x, y)) if (x != n) {
            if (t[x] == tk) return x;
            t[x] = tk;
            x = Find(pre[match[x]]);
        }
    }
    void blossom(int x, int y, int l) {
        for (; Find(x) != l; x = pre[y]) {
            pre[x] = y, y = match[x];
            if (s[y] == 1) q.push(y), s[y] = 0;
            for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
        }
    }
    bool bfs(int r) {
        iota(all(fa), 0), fill(all(s), -1);
        while (!q.empty()) q.pop();
        q.push(r), s[r] = 0;
        while (!q.empty()) {
            int x = q.front(); q.pop();
            for (int u : g[x]) {
                if (s[u] == -1) {
                    pre[u] = x, s[u] = 1;
                    if (match[u] == n) {
                        for (int a = u, b = x, last; b != n; a = last, b = pre[a])
                            last = match[b], match[b] = a, match[a] = b;
                        return true;
                    }
                    q.push(match[u]);
                    s[match[u]] = 0;
                } else if (!s[u] && Find(u) != Find(x)) {
                    int l = lca(u, x);
                    blossom(x, u, l), blossom(u, x, l);
                }
            }
        }
        return false;
    }
    int solve() {
        int res = 0;
        for (int x = 0; x < n; ++x) if (match[x] == n)

```



```

    res += bfs(x);
    return res;
}
void add_edge(int u, int v) {
    g[u].push_back(v), g[v].push_back(u);
}
Matching(int _n) : n(_n), tk(0), g(n), fa(n + 1),
    pre(n + 1, n), match(n + 1, n), s(n + 1), t(n) {}
};

```

3.8 Min Cost Circulation [bd1e15]

```

struct MinCostCirculation { // 0-base
    struct Edge {
        ll from, to, cap, fcap, flow, cost, rev;
    } *past[N];
    vector<Edge> G[N];
    ll dis[N], inq[N], n;
    void BellmanFord(int s) {
        fill_n(dis, n, INF), fill_n(inq, n, 0);
        queue<int> q;
        auto relax = [&](int u, ll d, Edge *e) {
            if (dis[u] > d) {
                dis[u] = d, past[u] = e;
                if (!inq[u]) inq[u] = 1, q.push(u);
            }
        };
        relax(s, 0, 0);
        while (!q.empty()) {
            int u = q.front();
            q.pop(), inq[u] = 0;
            for (auto &e : G[u])
                if (e.cap > e.flow)
                    relax(e.to, dis[u] + e.cost, &e);
        }
        void try_edge(Edge &cur) {
            if (cur.cap > cur.flow) return ++cur.cap, void();
            BellmanFord(cur.to);
            if (dis[cur.from] + cur.cost < 0) {
                ++cur.flow, --G[cur.to][cur.rev].flow;
                for (int i = cur.from; past[i]; i = past[i]->from) {
                    auto &e = *past[i];
                    ++e.flow, --G[e.to][e.rev].flow;
                }
            }
            ++cur.cap;
        }
        void solve(int mxlg) {
            for (int b = mxlg; b >= 0; --b) {
                for (int i = 0; i < n; ++i)
                    for (auto &e : G[i])
                        e.cap *= 2, e.flow *= 2;
                for (int i = 0; i < n; ++i)
                    for (auto &e : G[i])
                        if (e.fcap >> b & 1)
                            try_edge(e);
            }
        }
        void init(int _n) { n = _n;
            for (int i = 0; i < n; ++i) G[i].clear();
        }
        void add_edge(ll a, ll b, ll cap, ll cost) {
            G[a].pb(Edge{a, b, 0, cap, 0, cost, sz(G[b]) + (a
                == b)});
            G[b].pb(Edge{b, a, 0, 0, 0, -cost, sz(G[a]) - 1});
        }
    } mcmf; // O(VE * ElogC)
}

```

3.9 Weighted Blossom [dc42e4]

```

#define pb emplace_back
#define REP(i, l, r) for (int i=(l); i<=(r); ++i)
struct WeightGraph { // 1-based
    static const int inf = INT_MAX;
    struct edge { int u, v, w; }; int n, nx;
    vector<int> lab; vector<vector<edge>> g;
    vector<int> slack, match, st, pa, S, vis;
    vector<vector<int>> flo, flo_from; queue<int> q;
    WeightGraph(int n) : n(n), nx(n * 2), lab(nx + 1),
        g(nx + 1, vector<edge>(nx + 1)), slack(nx + 1),
        flo(nx + 1), flo_from(nx + 1, vector(n + 1, 0)) {

```

```

        match = st = pa = S = vis = slack;
        REP(u, 1, n) REP(v, 1, n) g[u][v] = {u, v, 0};
    }
    int ED(edge e) {
        return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2;
    }
    void update_slack(int u, int x, int &s) {
        if (!s || ED(g[u][x]) < ED(g[s][x])) s = u;
    }
    void set_slack(int x) {
        slack[x] = 0;
        REP(u, 1, n)
            if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
                update_slack(u, x, slack[x]);
    }
    void q_push(int x) {
        if (x <= n) q.push(x);
        else for (int y : flo[x]) q.push(y);
    }
    void set_st(int x, int b) {
        st[x] = b;
        if (x > n) for (int y : flo[x]) set_st(y, b);
    }
    vector<int> split_flo(auto &f, int xr) {
        auto it = find(all(f), xr);
        if (auto pr = it - f.begin(); pr % 2 == 1)
            reverse(1 + all(f), it = f.end() - pr);
        auto res = vector(f.begin(), it);
        return f.erase(f.begin(), it), res;
    } // 7bb859
    void set_match(int u, int v) {
        match[u] = g[u][v].v;
        if (u <= n) return;
        int xr = flo_from[u][g[u][v].u];
        auto &f = flo[u], z = split_flo(f, xr);
        REP(i, 0, int(z.size())-1) set_match(z[i], z[i ^
            1]);
        set_match(xr, v); f.insert(f.end(), all(z));
    }
    void augment(int u, int v) {
        for (;;) {
            int xnv = st[match[u]]; set_match(u, v);
            if (!xnv) return;
            set_match(v = xnv, u = st[pa[xnv]]);
        }
    }
    int lca(int u, int v) {
        static int t = 0; ++t;
        for (++t; u || v; swap(u, v)) if (u) {
            if (vis[u] == t) return u;
            vis[u] = t; u = st[match[u]];
            if (u) u = st[pa[u]];
        }
        return 0;
    }
    void add_blossom(int u, int o, int v) {
        int b = int(find(n + 1 + all(st), 0) - begin(st));
        lab[b] = 0, S[b] = 0; match[b] = match[o];
        vector<int> f = {o};
        for (int x : {u, v}) {
            for (int y; x != o; x = st[pa[y]])
                f.pb(x), f.pb(y = st[match[x]]), q_push(y);
            reverse(1 + all(f));
        }
        flo[b] = f; set_st(b, b);
        REP(x, 1, nx) g[b][x].w = g[x][b].w = 0;
        REP(x, 1, n) flo_from[b][x] = 0;
        for (int xs : flo[b]) {
            REP(x, 1, nx)
                if (g[b][x].w == 0 || ED(g[xs][x]) < ED(g[b][x]
                    ))
                    g[b][x] = g[xs][x], g[x][b] = g[x][xs];
            REP(x, 1, n)
                if (flo_from[xs][x]) flo_from[b][x] = xs;
        }
        set_slack(b);
    }
    void expand_blossom(int b) {
        for (int x : flo[b]) set_st(x, x);
        int xr = flo_from[b][g[b][pa[b]].u], xs = -1;
        for (int x : split_flo(flo[b], xr)) {
            if (xs == -1) { xs = x; continue; }
            pa[xs] = g[x][xs].u; S[xs] = 1, S[x] = 0;
            slack[xs] = 0; set_slack(x); q_push(x); xs = -1;

```

```

}
for (int x : flo[b])
    if (x == xr) S[x] = 1, pa[x] = pa[b];
    else S[x] = -1, set_slack(x);
st[b] = 0;
}
bool on_found_edge(const edge &e) {
    if (int u = st[e.u], v = st[e.v]; S[v] == -1) {
        int nu = st[match[v]]; pa[v] = e.u; S[v] = 1;
        slack[v] = slack[nu] = 0; S[nu] = 0; q_push(nu);
    } else if (S[v] == 0) {
        if (int o = lca(u, v)) add_blossom(u, o, v);
        else return augment(u, v), augment(v, u), true;
    }
    return false;
} // 82ea63
bool matching() {
    fill(all(S), -1), fill(all(slack), 0);
    q = queue<int>();
    REP(x, 1, nx) if (st[x] == x && !match[x])
        pa[x] = 0, S[x] = 0, q_push(x);
    if (q.empty()) return false;
    for (;;) {
        while (q.size()) {
            int u = q.front(); q.pop();
            if (S[st[u]] == 1) continue;
            REP(v, 1, n)
                if (g[u][v].w > 0 && st[u] != st[v]) {
                    if (ED[g[u][v]] != 0)
                        update_slack(u, st[v], slack[st[v]]);
                    else if (on_found_edge(g[u][v])) return true;
                }
        }
        int d = inf;
        REP(b, n + 1, nx) if (st[b] == b && S[b] == 1)
            d = min(d, lab[b] / 2);
        REP(x, 1, nx)
            if (int s = slack[x]; st[x] == x && s && S[x] <= 0)
                d = min(d, ED[g[s][x]] / (S[x] + 2));
        REP(u, 1, n)
            if (S[st[u]] == 1) lab[u] += d;
            else if (S[st[u]] == 0) {
                if (lab[u] <= d) return false;
                lab[u] -= d;
            }
        REP(b, n + 1, nx) if (st[b] == b && S[b] >= 0)
            lab[b] += d * (2 - 4 * S[b]);
        REP(x, 1, nx)
            if (int s = slack[x]; st[x] == x &&
                s && st[s] != x && ED[g[s][x]] == 0)
                if (on_found_edge(g[s][x])) return true;
        REP(b, n + 1, nx)
            if (st[b] == b && S[b] == 1 && lab[b] == 0)
                expand_blossom(b);
    }
    return false;
}
pair<ll, int> solve() {
    fill(all(match), 0);
    REP(u, 0, n) st[u] = u, flo[u].clear();
    int w_max = 0;
    REP(u, 1, n) REP(v, 1, n) {
        flo_from[u][v] = (u == v ? u : 0);
        w_max = max(w_max, g[u][v].w);
    }
    REP(u, 1, n) lab[u] = w_max;
    int n_matches = 0; ll tot_weight = 0;
    while (matching()) ++n_matches;
    REP(u, 1, n) if (match[u] && match[u] < u)
        tot_weight += g[u][match[u]].w;
    return make_pair(tot_weight, n_matches);
}
void set_edge(int u, int v, int w) {
    g[u][v].w = g[v][u].w = w; } // c78909
};

```

3.10 Flow Model

- Maximum/Minimum flow with lower bound / Circulation problem
 - Construct super source S and sink T .
 - For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity $u - l$.

- For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
- If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
- The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.

- Construct minimum vertex cover from maximum matching M on bipartite graph (X, Y)
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - DFS from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited.
 - $y \in Y$ is chosen iff y is visited.
- Minimum cost cyclic flow
 - Construct super source S and sink T
 - For each edge (x, y, c) , connect $x \rightarrow y$ with $(cost, cap) = (c, 1)$ if $c > 0$, otherwise connect $y \rightarrow x$ with $(cost, cap) = (-c, 1)$
 - For each edge with $c < 0$, sum these cost as K , then increase $d(y)$ by 1, decrease $d(x)$ by 1
 - For each vertex v with $d(v) > 0$, connect $S \rightarrow v$ with $(cost, cap) = (0, d(v))$
 - For each vertex v with $d(v) < 0$, connect $v \rightarrow T$ with $(cost, cap) = (0, -d(v))$
 - Flow from S to T , the answer is the cost of the flow $C + K$
- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T
 - Construct a max flow model, let K be the sum of all weights
 - Connect source $s \rightarrow v$, $v \in G$ with capacity K
 - For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
 - For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
 - T is a valid answer if the maximum flow $f < K|V|$
- Minimum weight edge cover
 - Change the weight of each edge to $\mu(u) + \mu(v) - w(u, v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
 - Let the maximum weight matching of the graph be x , the answer will be $\sum \mu(v) - x$.

4 Graph

4.1 Heavy-Light Decomposition [9ec77f]

```

struct HLD { // 0-based, remember to build
    int n, _id;
    vector<vector<int>> g;
    vector<int> dep, pa, tsz, ch, hd, id;
    void dfs(int v, int p) {
        dep[v] = ~p ? dep[p] + 1 : 0;
        pa[v] = p, tsz[v] = 1, ch[v] = -1;
        for (int u : g[v]) if (u != p) {
            dfs(u, v);
            if (ch[v] == -1 || tsz[ch[v]] < tsz[u])
                ch[v] = u;
            tsz[v] += tsz[u];
        }
    }
    void hld(int v, int p, int h) {
        hd[v] = h, id[v] = _id++;
        if (~ch[v]) hld(ch[v], v, h);
        for (int u : g[v]) if (u != p && u != ch[v])
            hld(u, v, u);
    }
    vector<pii> query(int u, int v) {
        vector<pii> ans;
        while (hd[u] != hd[v]) {
            if (dep[hd[u]] > dep[hd[v]]) swap(u, v);
            ans.emplace_back(id[hd[v]], id[v] + 1);
            v = pa[hd[v]];
        }
        if (dep[u] > dep[v]) swap(u, v);
        ans.emplace_back(id[u], id[v] + 1);
        return ans;
    }
    void build() {
        for (int i = 0; i < n; ++i) if (id[i] == -1)

```

```

    dfs(i, -1), hld(i, -1, i);
}
void add_edge(int u, int v) {
    g[u].pb(v), g[v].pb(u); }
HLD (int _n) : n(_n), _id(0), g(n), dep(n), pa(n),
    tsz(n), ch(n), hd(n), id(n, -1) {}
};

```

4.2 Centroid Decomposition [28b80a]

```

struct CD { // 0-based, remember to build
    int n, lg; // pa, dep are centroid tree attributes
    vector<vector<int>> g, dis;
    vector<int> pa, tsz, dep, vis;
    void dfs1(int v, int p) {
        tsz[v] = 1;
        for (int u : g[v]) if (u != p && !vis[u])
            dfs1(u, v), tsz[v] += tsz[u];
    }
    int dfs2(int v, int p, int _n) {
        for (int u : g[v])
            if (u != p && !vis[u] && tsz[u] > _n / 2)
                return dfs2(u, v, _n);
        return v;
    }
    void dfs3(int v, int p, int d) {
        dis[v][d] = ~p ? dis[p][d] + 1 : 0;
        for (int u : g[v]) if (u != p && !vis[u])
            dfs3(u, v, d);
    }
    void cd(int v, int p, int d) {
        dfs1(v, -1), v = dfs2(v, -1, tsz[v]);
        vis[v] = true, pa[v] = p, dep[v] = d;
        dfs3(v, -1, d);
        for (int u : g[v]) if (!vis[u])
            cd(u, v, d + 1);
    }
    void build() { cd(0, -1, 0); }
    void add_edge(int u, int v) {
        g[u].pb(v), g[v].pb(u); }
    CD (int _n) : n(_n), lg(__lg(n) + 1), g(n),
        dis(n, vector<int>(lg)), pa(n), tsz(n),
        dep(n), vis(n) {}
};

```

4.3 Edge BCC [cf5e55]

```

struct EBCC { // 0-based, remember to build
    int n, m, nbcc;
    vector<vector<pii>> g;
    vector<int> pa, low, dep, bcc_id, stk, is_bridge;
    void dfs(int v, int p, int f) {
        low[v] = dep[v] = ~p ? dep[p] + 1 : 0;
        stk.pb(v), pa[v] = p;
        for (auto [u, e] : g[v]) {
            if (low[u] == -1)
                dfs(u, v, e), low[v] = min(low[v], low[u]);
            else if (e != f)
                low[v] = min(low[v], dep[u]);
        }
        if (low[v] == dep[v]) {
            if (~f) is_bridge[f] = true;
            int id = nbcc++, x;
            do {
                x = stk.back(), stk.pop_back();
                bcc_id[x] = id;
            } while (x != v);
        }
    }
    void build() {
        is_bridge.assign(m, 0);
        for (int i = 0; i < n; ++i) if (low[i] == -1)
            dfs(i, -1, -1);
    }
    void add_edge(int u, int v) {
        g[u].emplace_back(v, m), g[v].emplace_back(u, m++);
    }
    EBCC (int _n) : n(_n), m(0), nbcc(0), g(n), pa(n),
        low(n, -1), dep(n), bcc_id(n), stk() {}
};

```

4.4 VertexBCC / Round Square Tree [66d85d]

```

struct BCC { // 0-based, remember to build
    int n, nbcc; // note for isolated point
    vector<vector<int>> g, _g; // id >= n: bcc
    vector<int> pa, dep, low, stk, pa2, dep2;
    void dfs(int v, int p) {
        dep[v] = low[v] = ~p ? dep[p] + 1 : 0;
        stk.pb(v), pa[v] = p;
        for (int u : g[v]) if (u != p) {
            if (low[u] == -1) {
                dfs(u, v), low[v] = min(low[v], low[u]);
                if (low[u] >= dep[v]) {
                    int id = nbcc++, x;
                    do {
                        x = stk.back(), stk.pop_back();
                        _g[id + n].pb(x), _g[x].pb(id + n);
                    } while (x != u);
                    _g[id + n].pb(v), _g[v].pb(id + n);
                } else low[v] = min(low[v], dep[u]);
            }
        }
    }
    bool is_cut(int x) { return sz(_g[x]) != 1; }
    vector<int> bcc(int id) { return _g[id + n]; }
    int bcc_id(int u, int v) {
        return pa2[dep2[u] < dep2[v] ? v : u] - n;
    }
    void dfs2(int v, int p) {
        dep2[v] = ~p ? dep2[p] + 1 : 0, pa2[v] = p;
        for (int u : _g[v]) if (u != p) dfs2(u, v);
    }
    void build() {
        low.assign(n, -1);
        for (int i = 0; i < n; ++i) if (low[i] == -1)
            dfs(i, -1), dfs2(i, -1);
    }
    void add_edge(int u, int v) {
        g[u].pb(v), g[v].pb(u); }
    BCC (int _n) : n(_n), nbcc(0), g(n), _g(2 * n),
        pa(n), dep(n), low(n), stk(), pa2(n * 2),
        dep2(n * 2) {}
};

```

4.5 SCC [9bee8c]

```

struct SCC {
    int n, nscc, _id;
    vector<vector<int>> g;
    vector<int> dep, low, scc_id, stk;
    void dfs(int v) {
        dep[v] = low[v] = _id++, stk.pb(v);
        for (int u : g[v]) if (scc_id[u] == -1) {
            if (low[u] == -1) dfs(u);
            low[v] = min(low[v], low[u]);
        }
        if (low[v] == dep[v]) {
            int id = nscc++, x;
            do {
                x = stk.back(), stk.pop_back(), scc_id[x] = id;
            } while (x != v);
        }
    }
    void build() {
        for (int i = 0; i < n; ++i) if (low[i] == -1)
            dfs(i);
    }
    void add_edge(int u, int v) { g[u].pb(v); }
    SCC (int _n) : n(_n), nscc(0), _id(0), g(n), dep(n),
        low(n, -1), scc_id(n, -1), stk() {}
};

```

4.6 2SAT [938072]

```

struct SAT { // 0-based, need SCC
    int n; vector<pii> edge; vector<int> is;
    int rev(int x) { return x < n ? x + n : x - n; }
    void add_ifthen(int x, int y) {
        add_clause(rev(x), y); }
    void add_clause(int x, int y) {
        edge.emplace_back(rev(x), y);
        edge.emplace_back(rev(y), x); }
    bool solve() {
        // is[i] = true -> i, is[i] = false -> -i
        SCC scc(2 * n);
    }
};

```



```

for (auto [u, v] : edge) scc.add_edge(u, v);
scc.build();
for (int i = 0; i < n; ++i) {
    if (scc.scc_id[i] == scc.scc_id[i + n])
        return false;
    is[i] = scc.scc_id[i] < scc.scc_id[i + n];
}
return true;
}
SAT (int _n) : n(_n), edge(), is(n) {}
};

```

4.7 Virtual Tree [f7650b]

```

// need lca, in, out
vector<pii> virtual_tree(vector<int> &v) {
    auto cmp = [&](int x, int y) {return in[x] < in[y];};
    sort(all(v), cmp);
    for (int i = 1; i < sz(v); ++i)
        v.pb(lca(v[i - 1], v[i]));
    sort(all(v), cmp);
    v.resize(unique(all(v)) - v.begin());
    vector<int> stk(1, v[0]);
    vector<pii> res;
    for (int i = 1; i < sz(v); ++i) {
        int x = v[i];
        while (out[stk.back()] < out[x]) stk.pop_back();
        res.emplace_back(stk.back(), x), stk.pb(x);
    }
    return res;
}

```

4.8 Directed MST [d6cf86]

```

using D = int;
struct edge { int u, v; D w; };
// 0-based, return index of edges
vector<int> dmst(vector<edge> &e, int n, int root) {
    using T = pair<D, int>;
    using PQ = pair<priority_queue<T, vector<T>,
        greater<T>>, D>;
    auto push = [](PQ &pq, T v) {
        pq.first.emplace(v.first - pq.second, v.second);
    };
    auto top = [](const PQ &pq) -> T {
        auto r = pq.first.top();
        return {r.first + pq.second, r.second};
    };
    auto join = [&push, &top](PQ &a, PQ &b) {
        if (a.first.size() < b.first.size()) swap(a, b);
        while (!b.first.empty())
            push(a, top(b)), b.first.pop();
    };
    vector<PQ> h(n * 2);
    for (int i = 0; i < e.size(); ++i)
        push(h[e[i].v], {e[i].w, i});
    vector<int> a(n * 2), v(n * 2, -1), pa(n * 2, -1), r(
        n * 2);
    iota(all(a), 0);
    auto o = [&](int x) { int y;
        for (y = x; a[y] != y; y = a[y]);
        for (int ox = x; x != y; ox = x)
            x = a[x], a[ox] = y;
        return y;
    };
    v[root] = n + 1;
    int pc = n;
    for (int i = 0; i < n; ++i) if (v[i] == -1) {
        for (int p = i; v[p] == -1 || v[p] == i; p = o(e[r[
            p]].u)) {
            if (v[p] == i) {
                int q = p; p = pc++;
                do {
                    h[q].second = -h[q].first.top().first;
                    join(h[pa[q] = a[q] = p], h[q]);
                } while ((q = o(e[r[q]].u)) != p);
            }
            v[p] = i;
            while (!h[p].first.empty() && o(e[top(h[p]).
                second].u) == p)
                h[p].first.pop();
            r[p] = top(h[p]).second;
        }
    }
}

```

```

}
}
vector<int> ans;
for (int i = pc - 1; i >= 0; i--)
    if (i != root && v[i] != n) {
        for (int f = e[r[i]].v; f != -1 && v[f] != n; f =
            pa[f]) v[f] = n;
        ans.pb(r[i]);
    }
return ans;
}
}

```

4.9 Dominator Tree [9fc069]

```

struct DominatorTree {
    int n, id;
    vector<vector<int>> g, rg, bucket;
    vector<int> sdom, dom, vis, rev, pa, rt, mn, res;
    // dom[s] = s, dom[v] = -1 if s -> v not exists
    int query(int v, int x) {
        if (rt[v] == v) return x ? -1 : v;
        int p = query(rt[v], 1);
        if (p == -1) return x ? rt[v] : mn[v];
        if (sdom[mn[v]] > sdom[mn[rt[v]]])
            mn[v] = mn[rt[v]];
        rt[v] = p;
        return x ? p : mn[v];
    }
    void dfs(int v) {
        vis[v] = id, rev[id] = v;
        rt[id] = mn[id] = sdom[id] = id, id++;
        for (int u : g[v]) {
            if (vis[u] == -1) dfs(u), pa[vis[u]] = vis[v];
            rg[vis[u]].pb(vis[v]);
        }
    }
    void build(int s) {
        dfs(s);
        for (int i = id - 1; ~i; --i) {
            for (int u : rg[i]) {
                sdom[i] = min(sdom[i], sdom[query(u, 0)]);
            }
            if (i) bucket[sdom[i]].pb(i);
            for (int u : bucket[i]) {
                int p = query(u, 0);
                dom[u] = sdom[p] == i ? i : p;
            }
            if (i) rt[i] = pa[i];
        }
        fill(all(res), -1);
        for (int i = 1; i < id; ++i) {
            if (dom[i] != sdom[i]) dom[i] = dom[dom[i]];
        }
        for (int i = 1; i < id; ++i)
            res[rev[i]] = rev[dom[i]];
        res[s] = s;
        for (int i = 0; i < n; ++i) dom[i] = res[i];
    }
    void add_edge(int u, int v) { g[u].pb(v); }
    DominatorTree (int _n) : n(_n), id(0), g(n), rg(n),
        bucket(n), sdom(n), dom(n, -1), vis(n, -1),
        rev(n), pa(n), rt(n), mn(n), res(n) {}
};

```

4.10 Bipartite Edge Coloring [a22d96]

```

struct BipartiteEdgeColoring { // 1-based
    // returns edge coloring in adjacent matrix G
    int n, m;
    vector<vector<int>> col, G;
    int find_col(int x) {
        int c = 1;
        while (col[x][c]) c++;
        return c;
    }
    void dfs(int v, int c1, int c2) {
        if (!col[v][c1]) return col[v][c2] = 0, void(0);
        int u = col[v][c1];
        dfs(u, c2, c1);
        col[v][c1] = 0, col[v][c2] = u, col[u][c2] = v;
    }
    void solve() {

```

```

    for (int i = 1; i <= n + m; ++i)
        for (int j = 1; j <= max(n, m); ++j)
            if (col[i][j])
                G[i][col[i][j]] = G[col[i][j]][i] = j;
} // u = left index, v = right index
void add_edge(int u, int v) {
    int c1 = find_col(u), c2 = find_col(v + n);
    dfs(u, c2, c1);
    col[u][c2] = v + n, col[v + n][c2] = u;
}
BipartiteEdgeColoring (int _n, int _m) : n(_n),
    m(_m), col(n + m + 1, vector<int>(max(n, m) + 1)),
    G(n + m + 1, vector<int>(n + m + 1)) {}
};

```

4.11 Edge Coloring [5b1e8f]

```

struct Vizing { // 1-based
    // returns edge coloring in adjacent matrix G
    int n;
    vector<vector<int>> C, G;
    vector<int> X, vst;
    vector<pii> E;
    void solve() {
        auto update = [&](int u)
        { for (X[u] = 1; C[u][X[u]]; ++X[u]); };
        auto color = [&](int u, int v, int c) {
            int p = G[u][v];
            G[u][v] = G[v][u] = c;
            C[u][c] = v, C[v][c] = u;
            C[u][p] = C[v][p] = 0;
            if (p) X[u] = X[v] = p;
            else update(u), update(v);
            return p;
        };
        auto flip = [&](int u, int c1, int c2) {
            int p = C[u][c1];
            swap(C[u][c1], C[u][c2]);
            if (p) G[u][p] = G[p][u] = c2;
            if (!C[u][c1]) X[u] = c1;
            if (!C[u][c2]) X[u] = c2;
            return p;
        };
        fill(1 + all(X), 1);
        for (int t = 0; t < sz(E); ++t) {
            auto [u, v0] = E[t];
            int v = v0, c0 = X[u], c = c0, d;
            vector<pii> L;
            fill(1 + all(vst), 0);
            while (!G[u][v0]) {
                L.emplace_back(v, d = X[v]);
                if (!C[v][c]) {
                    for (int a = sz(L) - 1; a >= 0; --a)
                        c = color(u, L[a].first, c);
                } else if (!C[u][d]) {
                    for (int a = sz(L) - 1; a >= 0; --a)
                        color(u, L[a].first, L[a].second);
                } else if (vst[d]) break;
                else vst[d] = 1, v = C[u][d];
            }
            if (!G[u][v0]) {
                for (; v; v = flip(v, c, d), swap(c, d));
                if (int a; C[u][c0]) {
                    for (a = sz(L) - 2;
                        a >= 0 && L[a].second != c; --a);
                    for (; a >= 0; --a)
                        color(u, L[a].first, L[a].second);
                }
                else --t;
            }
        }
        void add_edge(int u, int v) { E.emplace_back(u, v); }
        Vizing(int _n) : n(_n), C(n + 1, vector<int>(n + 1)),
            G(n + 1, vector<int>(n + 1)), X(n + 1), vst(n + 1) {}
};

```

4.12 Maximum Clique [0c8c97]

```

struct MaxClique { // Maximum Clique
    bitset<N> a[N], cs[N];
    int ans, sol[N], q, cur[N], d[N], n;
};

```

```

void init(int _n) {
    n = _n;
    for (int i = 0; i < n; i++) a[i].reset();
}
void add_edge(int u, int v) { a[u][v] = a[v][u] = 1; }
void csort(vector<int> &r, vector<int> &c) {
    int mx = 1, km = max(ans - q + 1, 1), t = 0, m = sz
        (r);
    cs[1].reset(), cs[2].reset();
    for (int i = 0; i < m; i++) {
        int p = r[i], k = 1;
        while ((cs[k] & a[p]).count()) k++;
        if (k > mx) mx++, cs[mx + 1].reset();
        cs[k][p] = 1;
        if (k < km) r[t++] = p;
    }
    c.resize(m);
    if (t) c[t - 1] = 0;
    for (int k = km; k <= mx; k++)
        for (int p = cs[k]._Find_first(); p < N;
            p = cs[k]._Find_next(p))
            r[t] = p, c[t] = k, t++;
}
void dfs(vector<int> &r, vector<int> &c, int l,
    bitset<N> mask) {
    while (!r.empty()) {
        int p = r.back();
        r.pop_back(), mask[p] = 0;
        if (q + c.back() <= ans) return;
        cur[q++] = p;
        vector<int> nr, nc;
        bitset<N> nmask = mask & a[p];
        for (int i : r)
            if (a[p][i]) nr.push_back(i);
        if (!nr.empty()) {
            if (1 < 4) {
                for (int i : nr)
                    d[i] = (a[i] & nmask).count();
                sort(nr.begin(), nr.end(),
                    [&](int x, int y) { return d[x] > d[y]; });
            }
            csort(nr, nc), dfs(nr, nc, l + 1, nmask);
        } else if (q > ans) ans = q, copy_n(cur, q, sol);
        c.pop_back(), q--;
    }
}
int solve(bitset<N> mask = bitset<N>(
    string(N, '1')) { // vertex mask
    vector<int> r, c;
    ans = q = 0;
    for (int i = 0; i < n; i++)
        if (mask[i]) r.push_back(i);
    for (int i = 0; i < n; i++)
        d[i] = (a[i] & mask).count();
    sort(r.begin(), r.end(),
        [&](int i, int j) { return d[i] > d[j]; });
    csort(r, c), dfs(r, c, 1, mask);
    return ans; // sol[0 ~ ans-1]
}
};

```

5 String

5.1 Aho-Corasick Automaton [d208c9]

```

struct AC {
    int ch[N][26], to[N][26], fail[N], sz;
    // vector<int> g[N];
    int cnt[N];
    AC () {sz = 0, extend();}
    void extend() {fill(ch[sz], ch[sz] + 26, 0), sz++;}
    int nxt(int u, int v) {
        if (!ch[u][v]) ch[u][v] = sz, extend();
        return ch[u][v];
    }
    int insert(string s) {
        int now = 0;
        for (char c : s) now = nxt(now, c - 'a');
        cnt[now]++;
        return now;
    }
};

```

```

void build_fail() {
    queue<int> q;
    for (int i = 0; i < 26; ++i) if (ch[0][i]) {
        q.push(ch[0][i]);
        // g[0].push_back(ch[0][i]);
        to[0][i] = ch[0][i];
    }
    while (!q.empty()) {
        int v = q.front(); q.pop();
        for (int j = 0; j < 26; ++j) {
            to[v][j] = ch[v][j] ? ch[v][j] : to[fail[v]][j];
        }
        for (int i = 0; i < 26; ++i) if (ch[v][i]) {
            int u = ch[v][i], k = fail[v];
            while (k && !ch[k][i]) k = fail[k];
            if (ch[k][i]) k = ch[k][i];
            fail[u] = k, cnt[u] += cnt[k];
            // g[k].push_back(u);
            q.push(u);
        }
    }
}
// int match(string &s) {
//     int now = 0, ans = 0;
//     for (char c : s) {
//         now = to[now][c - 'a'];
//         ans += cnt[now];
//     }
//     return ans;
// }
};

```

5.2 KMP Algorithm [f379fc]

```

vector<int> build_fail(string s) {
    vector<int> f(s.size() + 1, 0);
    int k = 0;
    for (int i = 1; i < (int)s.size(); ++i) {
        while (k && s[k] != s[i]) k = f[k];
        if (s[k] == s[i]) k++;
        f[i + 1] = k;
    }
    return f;
}
int match(string s, string t) {
    vector<int> f = build_fail(t);
    int k = 0, ans = 0;
    for (int i = 0; i < (int)s.size(); ++i) {
        while (k && s[i] != t[k]) k = f[k];
        if (s[i] == t[k]) k++;
        if (k == (int)t.size()) ans++, k = f[k];
    }
    return ans;
}

```

5.3 Z Algorithm [7d5c7c]

```

vector<int> buildZ(string s) {
    int n = (int)s.size(), l = 0, r = 0;
    vector<int> Z(n);
    for (int i = 0; i < n; ++i) {
        Z[i] = max(min(Z[i - 1], r - i), 0);
        while (i + Z[i] < n && s[Z[i]] == s[i + Z[i]]) {
            l = i, r = i + Z[i], Z[i]++;
        }
    }
    return Z;
}

```

5.4 Manacher [c18d8b]

```

// return value only consider string tmp, not s
vector<int> manacher(string tmp) {
    string s = "&";
    for (char c : tmp) s.pb(c), s.pb('%');
    int l = 0, r = 0, n = (int)s.size();
    vector<int> Z(n);
    for (int i = 0; i < n; ++i) {
        Z[i] = r > i ? min(Z[2 * l - i], r - i) : 1;
        while (s[i + Z[i]] == s[i - Z[i]]) Z[i]++;
        if (Z[i] + i > r) l = i, r = Z[i] + i;
    }
}

```

```

for (int i = 0; i < n; ++i) {
    Z[i] = (Z[i] - (i & 1)) / 2 * 2 + (i & 1);
}
return Z;
}

```

5.5 Suffix Array [ba4998]

```

int sa[N], tmp[2][N], c[N], rk[N], lcp[N];
void buildSA(string s) {
    int *x = tmp[0], *y = tmp[1], m = 256, n = s.size();
    for (int i = 0; i < m; ++i) c[i] = 0;
    for (int i = 0; i < n; ++i) c[x[i] = s[i]]++;
    for (int i = 1; i < m; ++i) c[i] += c[i - 1];
    for (int i = n - 1; ~i; --i) sa[--c[x[i]]] = i;
    for (int k = 1; k < n; k <= 1) {
        for (int i = 0; i < m; ++i) c[i] = 0;
        for (int i = 0; i < n; ++i) c[x[i]]++;
        for (int i = 1; i < m; ++i) c[i] += c[i - 1];
        int p = 0;
        for (int i = n - k; i < n; ++i) y[p++] = i;
        for (int i = 0; i < n; ++i) if (sa[i] >= k)
            y[p++] = sa[i] - k;
        for (int i = n - 1; ~i; --i)
            sa[--c[x[y[i]]]] = y[i];
        y[sa[0]] = p = 0;
        for (int i = 1; i < n; ++i) {
            int a = sa[i], b = sa[i - 1];
            if (!(x[a] == x[b] && a + k < n && b + k < n && x[a + k] == x[b + k])) p++;
            y[sa[i]] = p;
        }
        if (n == p + 1) break;
        swap(x, y), m = p + 1;
    }
}
void buildLCP(string s) {
    // lcp[i] = LCP(sa[i - 1], sa[i])
    // lcp(i, j) = query_lcp_min[rk[i] + 1, rk[j] + 1)
    int n = s.length(), val = 0;
    for (int i = 0; i < n; ++i) rk[sa[i]] = i;
    for (int i = 0; i < n; ++i) {
        if (!rk[i]) lcp[rk[i]] = 0;
        else {
            if (val) val--;
            int p = sa[rk[i] - 1];
            while (val + i < n && val + p < n && s[val + i] == s[val + p]) val++;
            lcp[rk[i]] = val;
        }
    }
}

```

5.6 SAIS [fbc167]

```

int sa[N << 1], rk[N], lcp[N];
// string ASCII value need > 0
namespace sfx {
    bool _t[N << 1];
    int _s[N << 1], _c[N << 1], x[N], _p[N], _q[N << 1];
    void pre(int *sa, int *c, int n, int z) {
        fill_n(sa, n, 0), copy_n(c, z, x);
    }
    void induce(int *sa, int *c, int *s, bool *t, int n, int z) {
        copy_n(c, z - 1, x + 1);
        for (int i = 0; i < n; ++i)
            if (sa[i] && !t[sa[i] - 1])
                sa[x[s[sa[i] - 1]]++] = sa[i] - 1;
        copy_n(c, z, x);
        for (int i = n - 1; i >= 0; --i)
            if (sa[i] && t[sa[i] - 1])
                sa[--x[s[sa[i] - 1]]] = sa[i] - 1;
    }
    void sais(int *s, int *sa, int *p, int *q, bool *t, int *c, int n, int z) {
        bool uniq = t[n - 1] = true;
        int nn = 0, nmxx = -1, *nsa = sa + n, *ns = s + n, last = -1;
        fill_n(c, z, 0);
        for (int i = 0; i < n; ++i) uniq &= ++c[s[i]] < 2;
        partial_sum(c, c + z, c);
    }
}

```

```

if (uniq) {
    for (int i = 0; i < n; ++i) sa[--c[s[i]]] = i;
    return;
}
for (int i = n - 2; i >= 0; --i)
    if (s[i] == s[i + 1]) t[i] = t[i + 1];
    else t[i] = s[i] < s[i + 1];
pre(sa, c, n, z);
for (int i = 1; i <= n - 1; ++i)
    if (t[i] && !t[i - 1])
        sa[--x[s[i]]] = p[q[i] = nn++] = i;
induce(sa, c, s, t, n, z);
for (int i = 0; i < n; ++i)
    if (sa[i] && t[sa[i]] && !t[sa[i] - 1]) {
        bool neq = last < 0 || !equal(s + sa[i], s + p[q[
            sa[i]] + 1], s + last);
        ns[q[last = sa[i]]] = nmzx += neq;
    }
sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, nmzx +
    1);
pre(sa, c, n, z);
for (int i = nn - 1; i >= 0; --i)
    sa[--x[s[p[nsa[i]]]]] = p[nsa[i]];
induce(sa, c, s, t, n, z);
}
void buildSA(string s) {
    int n = s.length();
    for (int i = 0; i < n; ++i) _s[i] = s[i];
    _s[n] = 0;
    sais(_s, sa, _p, _q, _t, _c, n + 1, 256);
    for (int i = 1; i <= n; ++i) sa[i - 1] = sa[i];
} // buildLCP()...
}

```

5.7 Suffix Automaton [7228e9]

```

struct SAM {
    int ch[N][26], len[N], link[N], pos[N], cnt[N], sz;
    // node -> strings with the same endpos set
    // length in range [len(link) + 1, len]
    // node's endpos set -> pos in the subtree of node
    // link -> longest suffix with different endpos set
    // len -> longest suffix
    // pos -> end position
    // cnt -> size of endpos set
    SAM () {len[0] = 0, link[0] = -1, pos[0] = 0, cnt[0]
        = 0, sz = 1;}
    void build(string s) {
        int last = 0;
        for (int i = 0; i < s.length(); ++i) {
            char c = s[i];
            int cur = sz++;
            len[cur] = len[last] + 1, pos[cur] = i + 1;
            int p = last;
            while (~p && !ch[p][c - 'a'])
                ch[p][c - 'a'] = cur, p = link[p];
            if (p == -1) link[cur] = 0;
            else {
                int q = ch[p][c - 'a'];
                if (len[p] + 1 == len[q]) {
                    link[cur] = q;
                } else {
                    int nxt = sz++;
                    len[nxt] = len[p] + 1, link[nxt] = link[q];
                    pos[nxt] = 0;
                    for (int j = 0; j < 26; ++j)
                        ch[nxt][j] = ch[q][j];
                    while (~p && ch[p][c - 'a'] == q)
                        ch[p][c - 'a'] = nxt, p = link[p];
                    link[q] = link[cur] = nxt;
                }
            }
        }
        cnt[cur]++;
        last = cur;
    }
    // vector <int> p(sz);
    // iota(all(p), 0);
    // sort(all(p),
    // [&](int i, int j) {return len[i] > len[j];});
    // for (int i = 0; i < sz; ++i)
    //     cnt[link[p[i]]] += cnt[p[i]];
}

```

```

} sam;

```

5.8 Minimum Rotation [aa3a61]

```

string rotate(const string &s) {
    int n = (int)s.size(), i = 0, j = 1;
    string t = s + s;
    while (i < n && j < n) {
        int k = 0;
        while (k < n && t[i + k] == t[j + k]) ++k;
        if (t[i + k] <= t[j + k]) j += k + 1;
        else i += k + 1;
        if (i == j) ++j;
    }
    int pos = (i < n ? i : j);
    return t.substr(pos, n);
}

```

5.9 Palindrome Tree [0518a5]

```

struct PAM {
    int ch[N][26], cnt[N], fail[N], len[N], sz;
    string s;
    // 0 -> even root, 1 -> odd root
    PAM () {}
    void init(string s) {
        sz = 0, extend(), extend();
        len[0] = 0, fail[0] = 1, len[1] = -1;
        int lst = 1;
        for (int i = 0; i < s.length(); ++i) {
            while (s[i - len[lst] - 1] != s[i])
                lst = fail[lst];
            if (!ch[lst][s[i] - 'a']) {
                int idx = extend();
                len[idx] = len[lst] + 2;
                int now = fail[lst];
                while (s[i - len[now] - 1] != s[i])
                    now = fail[now];
                fail[idx] = ch[now][s[i] - 'a'];
                ch[lst][s[i] - 'a'] = idx;
            }
            lst = ch[lst][s[i] - 'a'], cnt[lst]++;
        }
    }
    void build_count() {
        for (int i = sz - 1; i > 1; --i)
            cnt[fail[i]] += cnt[i];
    }
    int extend() {
        fill(ch[sz], ch[sz] + 26, 0), sz++;
        return sz - 1;
    }
};

```

5.10 Lyndon Factorization [a9eeb0]

```

// partition s = w[0] + w[1] + ... + w[k-1],
// w[0] >= w[1] >= ... >= w[k-1]
// each w[i] strictly smaller than all its suffix
vector <string> duval(const string &s) {
    vector <string> ans;
    for (int n = (int)s.size(), i = 0, j, k; i < n; ) {
        for (j = i + 1, k = i; j < n && s[k] <= s[j]; j++)
            k = (s[k] < s[j] ? i : k + 1);
        for (; i <= k; i += j - k)
            ans.pb(s.substr(i, j - k)); // s.substr(L, len)
    }
    return ans;
}

```

5.11 Main Lorentz [f3da14]

```

int to_left[N], to_right[N];
vector <array <int, 3>> rep; // L, r, len.
// substr( [L, r], len * 2) are tandem
void findRep(string &s, int l, int r) {
    if (r - l == 1) return;
    int m = l + r >> 1;
    findRep(s, l, m), findRep(s, m, r);
    string sl = s.substr(l, m - l);
    string sr = s.substr(m, r - m);
    vector <int> Z = buildZ(sr + "#" + sl);
    for (int i = 1; i < m; ++i)

```

```

    to_right[i] = Z[r - m + 1 + i - 1];
reverse(all(sl));
Z = buildZ(sl);
for (int i = 1; i < m; ++i)
    to_left[i] = Z[m - i - 1];
reverse(all(sl));
for (int i = 1; i + 1 < m; ++i) {
    int k1 = to_left[i], k2 = to_right[i + 1];
    int len = m - i - 1;
    if (k1 < 1 || k2 < 1 || len < 2) continue;
    int tl = max(1, len - k2), tr = min(len - 1, k1);
    if (tl <= tr) rep.pb({i + 1 - tr, i + 1 - tl, len});
}
Z = buildZ(sr);
for (int i = m; i < r; ++i) to_right[i] = Z[i - m];
reverse(all(sl)), reverse(all(sr));
Z = buildZ(sl + "#" + sr);
for (int i = m; i < r; ++i)
    to_left[i] = Z[m - 1 + 1 + r - i - 1];
reverse(all(sl)), reverse(all(sr));
for (int i = m; i + 1 < r; ++i) {
    int k1 = to_left[i], k2 = to_right[i + 1];
    int len = i - m + 1;
    if (k1 < 1 || k2 < 1 || len < 2) continue;
    int tl = max(len - k2, 1), tr = min(len - 1, k1);
    if (tl <= tr)
        rep.pb({i + 1 - len - tr, i + 1 - len - tl, len});
}
Z = buildZ(sr + "#" + sl);
for (int i = 1; i < m; ++i)
    if (Z[r - m + 1 + i - 1] >= m - i)
        rep.pb({i, i, m - i});
}

```

6 Math

6.1 Miller Rabin / Pollard Rho [6c9c33]

```

ll mul(ll x, ll y, ll p) {return (x * y - (ll)((long
double)x / p * y) * p + p) % p;} // __int128
vector<ll> chk = {2, 325, 9375, 28178, 450775, 9780504,
1795265022};
ll Pow(ll a, ll b, ll n) {
    ll res = 1;
    for (; b; b >>= 1, a = mul(a, a, n))
        if (b & 1) res = mul(res, a, n);
    return res;
}
bool check(ll a, ll d, int s, ll n) {
    a = Pow(a, d, n);
    if (a <= 1) return 1;
    for (int i = 0; i < s; ++i, a = mul(a, a, n)) {
        if (a == 1) return 0;
        if (a == n - 1) return 1;
    }
    return 0;
}
bool IsPrime(ll n) {
    if (n < 2) return 0;
    if (n % 2 == 0) return n == 2;
    ll d = n - 1, s = 0;
    while (d % 2 == 0) d >>= 1, ++s;
    for (ll i : chk) if (!check(i, d, s, n)) return 0;
    return 1;
}
const vector<ll> small = {2, 3, 5, 7, 11, 13, 17, 19};
ll FindFactor(ll n) {
    if (IsPrime(n)) return 1;
    for (ll p : small) if (n % p == 0) return p;
    ll x, y = 2, d, t = 1;
    auto f = [&](ll a) {return (mul(a, a, n) + t) % n;};
    for (int l = 2; ; l <= 1) {
        x = y;
        int m = min(l, 32);
        for (int i = 0; i < l; i += m) {
            d = 1;
            for (int j = 0; j < m; ++j) {
                y = f(y), d = mul(d, abs(x - y), n);
            }
            ll g = __gcd(d, n);
            if (g == n) {
                l = 1, y = 2, ++t;
            }
        }
    }
}

```

```

        break;
    }
    if (g != 1) return g;
}
}
map<ll, int> res;
void PollardRho(ll n) {
    if (n == 1) return;
    if (IsPrime(n)) return ++res[n], void(0);
    ll d = FindFactor(n);
    PollardRho(n / d), PollardRho(d);
}

```

6.2 Ext GCD [a4b22d]

```

//a * p.first + b * p.second = gcd(a, b)
pair<ll, ll> extgcd(ll a, ll b) {
    if (b == 0) return {1, 0};
    auto [y, x] = extgcd(b, a % b);
    return pair<ll, ll>(x, y - (a / b) * x);
}

```

6.3 Chinese Remainder Theorem [90d2ce]

```

pair<ll, ll> CRT(ll x1, ll m1, ll x2, ll m2) {
    ll g = gcd(m1, m2);
    if ((x2 - x1) % g) return make_pair(-1, -1); // no sol
    m1 /= g, m2 /= g;
    pair<ll, ll> p = extgcd(m1, m2);
    ll lcm = m1 * m2 * g;
    ll res = p.first * (x2 - x1) * m1 + x1;
    // be careful with overflow
    return make_pair((res % lcm + lcm) % lcm, lcm);
}

```

6.4 PiCount [1db46f]

```

const int V = 10000000, N = 100, M = 100000;
vector<int> primes;
bool isp[V];
int small_pi[V], dp[N][M];
void sieve(int x) {
    for (int i = 2; i < x; ++i) isp[i] = true;
    isp[0] = isp[1] = false;
    for (int i = 2; i * i < x; ++i) if (isp[i])
        for (int j = i * i; j < x; j += i) isp[j] = false;
    for (int i = 2; i < x; ++i) if (isp[i]) primes.pb(i);
}
void init() {
    sieve(V);
    small_pi[0] = 0;
    for (int i = 1; i < V; ++i)
        small_pi[i] = small_pi[i - 1] + isp[i];
    for (int i = 0; i < M; ++i) dp[0][i] = i;
    for (int i = 1; i < N; ++i) for (int j = 0; j < M; ++j)
        dp[i][j] = dp[i - 1][j] - dp[i - 1][j / primes[i - 1]];
}
ll phi(ll n, int a) {
    if (!a) return n;
    if (n < M && a < N) return dp[a][n];
    if (primes[a - 1] > n) return 1;
    if (1ll * primes[a - 1] * primes[a - 1] >= n && n < V)
        return small_pi[n] - a + 1;
    return phi(n, a - 1) - phi(n / primes[a - 1], a - 1);
}
ll PiCount(ll n) {
    if (n < V) return small_pi[n];
    int s = sqrt(n + 0.5), y = cbrt(n + 0.5), a =
        small_pi[y];
    ll res = phi(n, a) + a - 1;
    for (; primes[a] <= s; ++a) res -= max(PiCount(n /
        primes[a]) - PiCount(primes[a]) + 1, 0ll);
    return res;
}

```

6.5 Linear Function Mod Min [5552e3]

```

ll topos(ll x, ll m)
{ x %= m; if (x < 0) x += m; return x; }
//min value of ax + b (mod m) for x \in [0, n - 1]. 0(
Log m)

```



```

11 min_rem(11 n, 11 m, 11 a, 11 b) {
    a = topos(a, m), b = topos(b, m);
    for (11 g = __gcd(a, m); g > 1;) return g * min_rem(n
        , m / g, a / g, b / g) + (b % g);
    for (11 nn, nm, na, nb; a; n = nn, m = nm, a = na, b
        = nb) {
        if (a <= m - a) {
            nn = (a * (n - 1) + b) / m;
            if (!nn) break;
            nn += (b < a);
            nm = a, na = topos(-m, a);
            nb = b < a ? b : topos(b - m, a);
        } else {
            11 lst = b - (n - 1) * (m - a);
            if (lst >= 0) {b = lst; break;}
            nn = -(lst / m) + (lst % m < -a) + 1;
            nm = m - a, na = m % (m - a), nb = b % (m - a);
        }
    }
    return b;
}
//min value of ax + b (mod m) for x \in [0, n - 1],
//also return min x to get the value. O(log m)
//{value, x}
pair<11, 11> min_rem_pos(11 n, 11 m, 11 a, 11 b) {
    a = topos(a, m), b = topos(b, m);
    11 mn = min_rem(n, m, a, b), g = __gcd(a, m);
    //ax = (mn - b) (mod m)
    11 x = (extgcd(a, m).first + m) * ((mn - b + m) / g)
        % (m / g);
    return {mn, x};
}

```

6.6 Floor Sum [49de67]

```

// sum^{n-1}_0 floor((a * i + b) / m) in Log(n + m + a
// + b)
11 floor_sum(11 n, 11 m, 11 a, 11 b) {
    11 ans = 0;
    if (a >= m) ans += (n - 1) * n * (a / m) / 2, a %= m;
    if (b >= m) ans += n * (b / m), b %= m;
    11 y_max = (a * n + b) / m, x_max = (y_max * m - b);
    if (y_max == 0) return ans;
    ans += (n - (x_max + a - 1) / a) * y_max;
    ans += floor_sum(y_max, a, m, (a - x_max % a) % a);
    return ans;
}

```

6.7 Quadratic Residue [51ec55]

```

int Jacobi(int a, int m) {
    int s = 1;
    for (; m > 1; ) {
        a %= m;
        if (a == 0) return 0;
        const int r = __builtin_ctz(a);
        if ((r & 1) && ((m + 2) & 4)) s = -s;
        a >>= r;
        if (a & m & 2) s = -s;
        swap(a, m);
    }
    return s;
}
int QuadraticResidue(int a, int p) {
    if (p == 2) return a & 1;
    const int jc = Jacobi(a, p);
    if (jc == 0) return 0;
    if (jc == -1) return -1;
    int b, d;
    for (; ; ) {
        b = rand() % p;
        d = (11l * b * b + p - a) % p;
        if (Jacobi(d, p) == -1) break;
    }
    11 f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
    for (int e = (p + 1) >> 1; e; e >>= 1) {
        if (e & 1) {
            tmp = (g0 * f0 + d * (g1 * f1 % p)) % p;
            g1 = (g0 * f1 + g1 * f0) % p;
            g0 = tmp;
        }
        tmp = (f0 * f0 + d * (f1 * f1 % p)) % p;
    }
}

```

```

    f1 = (2 * f0 * f1) % p;
    f0 = tmp;
}
return g0;
}

```

6.8 Discrete Log [8f7f93]

```

11 DiscreteLog(11 a, 11 b, 11 m) { // a^x = b (mod m)
    const int B = 35000;
    11 k = 1 % m, ans = 0, g;
    while ((g = gcd(a, m)) > 1) {
        if (b == k) return ans;
        if (b % g) return -1;
        b /= g, m /= g, ans++, k = (k * a / g) % m;
    }
    if (b == k) return ans;
    unordered_map<11, int> m1;
    11 tot = 1;
    for (int i = 0; i < B; ++i)
        m1[tot * b % m] = i, tot = tot * a % m;
    11 cur = k * tot % m;
    for (int i = 1; i <= B; ++i, cur = cur * tot % m)
        if (m1.count(cur)) return i * B - m1[cur] + ans;
    return -1;
}

```

6.9 Factorial without Prime Factor [c324f3]

```

// O(p^k + Log^2 n), pk = p^k
11 prod[MAXP];
11 fac_no_p(11 n, 11 p, 11 pk) {
    prod[0] = 1;
    for (int i = 1; i <= pk; ++i)
        if (i % p) prod[i] = prod[i - 1] * i % pk;
        else prod[i] = prod[i - 1];
    11 rt = 1;
    for (; n; n /= p) {
        rt = rt * mpow(prod[pk], n / pk, pk) % pk;
        rt = rt * prod[n % pk] % pk;
    }
    return rt;
}
// (n! without factor p) % p^k

```

6.10 Berlekamp Massey [f867ec]

```

// need add, sub, mul
vector<int> BerlekampMassey(vector<int> a) {
    // find min |c| such that a_n = sum c_j * a_{n-j-1}, 0-based
    // O(N^2), if |c| = k, |a| >= 2k sure correct
    auto f = [&](vector<int> v, 11 c) {
        for (int &x : v) x = mul(x, c);
        return v;
    };
    vector<int> c, best;
    int pos = 0, n = (int)a.size();
    for (int i = 0; i < n; ++i) {
        int error = a[i];
        for (int j = 0; j < (int)c.size(); ++j)
            error = sub(error, mul(c[j], a[i - 1 - j]));
        if (error == 0) continue;
        int inv = Pow(error, mod - 2);
        if (c.empty()) {
            c.resize(i + 1), pos = i, best.pb(inv);
        } else {
            vector<int> fix = f(best, error);
            fix.insert(fix.begin(), i - pos - 1, 0);
            if (fix.size() >= c.size()) {
                best = f(c, sub(0, inv));
                best.insert(best.begin(), inv);
                pos = i, c.resize(fix.size());
            }
            for (int j = 0; j < (int)fix.size(); ++j)
                c[j] = add(c[j], fix[j]);
        }
    }
    return c;
}

```

6.11 Simplex [b68fb9]

```

struct Simplex { // 0-based
    using T = long double;
    static const int N = 410, M = 30010;
    const T eps = 1e-7;
    int n, m;
    int Left[M], Down[N];
    // Ax <= b, max c^T x
    // result : v, xi = sol[i]
    T a[M][N], b[M], c[N], v, sol[N];
    bool eq(T a, T b) {return fabs(a - b) < eps;}
    bool ls(T a, T b) {return a < b && !eq(a, b);}
    void init(int _n, int _m) {
        n = _n, m = _m, v = 0;
        for (int i = 0; i < m; ++i)
            for (int j = 0; j < n; ++j) a[i][j] = 0;
        for (int i = 0; i < m; ++i) b[i] = 0;
        for (int i = 0; i < n; ++i) c[i] = sol[i] = 0;
    }
    void pivot(int x, int y) {
        swap(Left[x], Down[y]);
        T k = a[x][y]; a[x][y] = 1;
        vector<int> nz;
        for (int i = 0; i < n; ++i) {
            a[x][i] /= k;
            if (!eq(a[x][i], 0)) nz.push_back(i);
        }
        b[x] /= k;
        for (int i = 0; i < m; ++i) {
            if (i == x || eq(a[i][y], 0)) continue;
            k = a[i][y], a[i][y] = 0;
            b[i] -= k * b[x];
            for (int j : nz) a[i][j] -= k * a[x][j];
        }
        if (eq(c[y], 0)) return;
        k = c[y], c[y] = 0, v += k * b[x];
        for (int i : nz) c[i] -= k * a[x][i];
    }
    // 0: found solution, 1: no feasible solution, 2:
    // unbounded
    int solve() {
        for (int i = 0; i < n; ++i) Down[i] = i;
        for (int i = 0; i < m; ++i) Left[i] = n + i;
        while (true) {
            int x = -1, y = -1;
            for (int i = 0; i < m; ++i) if (ls(b[i], 0) && (x == -1 || b[i] < b[x])) x = i;
            if (x == -1) break;
            for (int i = 0; i < n; ++i) if (ls(a[x][i], 0) && (y == -1 || a[x][i] < a[x][y])) y = i;
            if (y == -1) return 1;
            pivot(x, y);
        }
        while (true) {
            int x = -1, y = -1;
            for (int i = 0; i < n; ++i) if (ls(0, c[i]) && (y == -1 || c[i] > c[y])) y = i;
            if (y == -1) break;
            for (int i = 0; i < m; ++i)
                if (ls(0, a[i][y]) && (x == -1 || b[i] / a[i][y] < b[x] / a[x][y])) x = i;
            if (x == -1) return 2;
            pivot(x, y);
        }
        for (int i = 0; i < m; ++i) if (Left[i] < n)
            sol[Left[i]] = b[i];
        return 0;
    }
};

```

6.12 Euclidean

$$m = \lfloor \frac{an+b}{c} \rfloor$$

$$\begin{aligned}
 g(a, b, c, n) &= \sum_{i=0}^n i \lfloor \frac{ai+b}{c} \rfloor \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot \frac{n(n+1)}{2} \\ + g(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1) \\ - h(c, c-b-1, a, m-1)), & \text{otherwise} \end{cases}
 \end{aligned}$$

$$\begin{aligned}
 h(a, b, c, n) &= \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor^2 \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot (n+1) \\ + \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) \\ + h(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{a}{c} \rfloor \cdot g(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{b}{c} \rfloor \cdot f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm(m+1) - 2g(c, c-b-1, a, m-1) \\ - 2f(c, c-b-1, a, m-1) - f(a, b, c, n), & \text{otherwise} \end{cases}
 \end{aligned}$$

6.13 Linear Programming Construction

Standard form: maximize $c^T x$ subject to $Ax \leq b$ and $x \geq 0$.
 Dual LP: minimize $b^T y$ subject to $A^T y \geq c$ and $y \geq 0$.
 \bar{x} and \bar{y} are optimal if and only if for all $i \in [1, n]$, either $\bar{x}_i = 0$ or $\sum_{j=1}^m A_{ji} \bar{y}_j = c_i$ holds and for all $i \in [1, m]$ either $\bar{y}_i = 0$ or $\sum_{j=1}^n A_{ij} \bar{x}_j = b_j$ holds.

1. In case of minimization, let $c'_i = -c_i$
2. $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3. $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
4. If x_i has no lower bound, replace x_i with $x_i - x'_i$

6.14 Theorem

- Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

- Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .

- Erdős-Gallai Theorem

A sequence of non-negative integers $d_1 \geq d_2 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + d_2 + \dots + d_n$ is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

holds for all $1 \leq k \leq n$.

- Burnside's Lemma

Let X be a set and G be a group that acts on X . For $g \in G$, denote by X^g the elements fixed by g :

$$X^g = \{x \in X \mid gx = x\}$$

Then

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|.$$

- Gale-Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$. Sequences a and b called bigraphic if there is a labeled simple bipartite graph such that a and b is the degree sequence of this bipartite graph.

- Fulkerson-Chen-Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$. Sequences a and b called digraphic if there is a labeled simple directed graph such that each vertex v_i has indegree a_i and outdegree b_i .

- Pick's theorem

For simple polygon, when points are all integer, we have $A = \#\{\text{lattice points in the interior}\} + \frac{\#\{\text{lattice points on the boundary}\}}{2} - 1$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume = $\pi h^2(3r - h)/3 = \pi h(3a^2 + h^2)/6 = \pi r^3(2 + \cos \theta)(1 - \cos \theta)^2/3$.
- Area = $2\pi rh = \pi(a^2 + h^2) = 2\pi r^2(1 - \cos \theta)$.

6.15 Estimation

n	2	3	4	5	6	7	8	9	20	30	40	50	100		
$p(n)$	2	3	5	7	11	15	22	30	627	5604	4e4	2e5	2e8		
n	100	1e3	1e6					1e9	1e12		1e15		1e18		
$d(i)$	12	32	240					1344	6720		26880		103680		
arg	60	840	720720	735134400	963761198400	866421317361600	8976124847866								
n	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
$\binom{2n}{n}$	2	6	20	70	252	924	3432	12870	48620	184756	7e5	2e6	1e7	4e7	1.5e8
n	2	3	4	5	6	7	8	9	10	11	12	13			
B_n	2	5	15	52	203	877	4140	21147	115975	7e5	4e6	3e7			

6.16 General Purpose Numbers

- Bernoulli numbers

$$B_0 = 1, B_1^\pm = \pm \frac{1}{2}, B_2 = \frac{1}{6}, B_3 = 0$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0, \text{ EGF is } B(x) = \frac{x}{e^x - 1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}.$$

$$S_m(n) = \sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

- Stirling numbers of the second kind Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k), S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$$

$$x^n = \sum_{i=0}^n S(n, i) (x)_i$$

- Pentagonal number theorem

$$\prod_{n=1}^{\infty} (1 - x^n) = 1 + \sum_{k=1}^{\infty} (-1)^k \left(x^{k(3k+1)/2} + x^{k(3k-1)/2} \right)$$

- Catalan numbers

$$C_n^{(k)} = \frac{1}{(k-1)n+1} \binom{kn}{n}$$

$$C^{(k)}(x) = 1 + x[C^{(k)}(x)]^k$$

- Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j :s s.t. $\pi(j) \geq j$, k j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

7 Polynomial

7.1 Number Theoretic Transform [536cc5]

```
// mul, add, sub, Pow
struct NTT {
    int w[N];
    NTT() {
        int dw = Pow(G, (mod - 1) / N);
        w[0] = 1;
        for (int i = 1; i < N; ++i)
            w[i] = mul(w[i - 1], dw);
    }
    void operator()(vector<int>& a, bool inv = false) {
        // 0 <= a[i] < P
        int x = 0, n = a.size();
        for (int j = 1; j < n - 1; ++j) {
            for (int k = n >> 1; (x ^= k) < k; k >>= 1);
            if (j < x) swap(a[x], a[j]);
        }
        for (int L = 2; L <= n; L <= 1) {
            int dx = N / L, dl = L >> 1;
            for (int i = 0; i < n; i += L) {
                for (int j = i, x = 0; j < i + dl; ++j, x += dx) {
                    int tmp = mul(a[j + dl], w[x]);
                    a[j + dl] = sub(a[j], tmp);
                    a[j] = add(a[j], tmp);
                }
            }
        }
    }
}
```

```
}
if (inv) {
    reverse(a.begin() + 1, a.end());
    int invn = Pow(n, mod - 2);
    for (int i = 0; i < n; ++i)
        a[i] = mul(a[i], invn);
}
}
} ntt;
```

7.2 Fast Fourier Transform [6f906d]

```
using T = complex<double>;
const double PI = acos(-1);
struct FFT {
    T w[N];
    FFT() {
        T dw = {cos(2 * PI / N), sin(2 * PI / N)};
        w[0] = 1;
        for (int i = 1; i < N; ++i) w[i] = w[i - 1] * dw;
    }
    void operator()(vector<T>& a, bool inv = false) {
        // see NTT, replace ll with T
        if (inv) {
            reverse(a.begin() + 1, a.end());
            T invn = 1.0 / n;
            for (int i = 0; i < n; ++i) a[i] = a[i] * invn;
        }
    }
} ntt;
// after mul, round i.real()
```

7.3 Primes

Prime	Root	Prime	Root
7681	17	167772161	3
12289	11	104857601	3
40961	3	985661441	3
65537	3	998244353	3
786433	10	1107296257	10
5767169	3	2013265921	31
7340033	3	2810183681	11
23068673	3	2885681153	3
469762049	3	605028353	3
2061584302081	7	1945555039024054273	5
2748779069441	3	9223372036737335297	3

7.4 Polynomial Operations [9be4e4]

```
typedef vector<int> Poly;
Poly Mul(Poly a, Poly b, int bound = N) { // d02e42
    int m = a.size() + b.size() - 1, n = 1;
    while (n < m) n <= 1;
    a.resize(n), b.resize(n);
    ntt(a), ntt(b);
    Poly out(n);
    for (int i = 0; i < n; ++i) out[i] = mul(a[i], b[i]);
    ntt(out, true), out.resize(min(m, bound));
    return out;
}
Poly Inverse(Poly a) { // b137d5
    // O(NlogN), a[0] != 0
    int n = a.size();
    Poly res(1, Pow(a[0], mod - 2));
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        Poly v1(a.begin(), a.begin() + m * 2), v2 = res;
        v1.resize(m * 4), v2.resize(m * 4);
        ntt(v1), ntt(v2);
        for (int i = 0; i < m * 4; ++i)
            v1[i] = mul(mul(v1[i], v2[i]), v2[i]);
        ntt(v1, true);
        res.resize(m * 2);
        for (int i = 0; i < m; ++i)
            res[i] = add(res[i], res[i]);
        for (int i = 0; i < m * 2; ++i)
            res[i] = sub(res[i], v1[i]);
    }
    res.resize(n);
    return res;
}
pair<Poly, Poly> Divide(Poly a, Poly b) {
    // a = bQ + R, O(NlogN), b.back() != 0
    int n = a.size(), m = b.size(), k = n - m + 1;
    if (n < m) return {0, a};
    Poly ra = a, rb = b;
```

```

reverse(all(ra)), ra.resize(k);
reverse(all(rb)), rb.resize(k);
Poly Q = Mul(ra, Inverse(rb), k);
reverse(all(Q));
Poly res = Mul(b, Q), R(m - 1);
for (int i = 0; i < m - 1; ++i)
    R[i] = sub(a[i], res[i]);
return {Q, R};
}
Poly SqrtImpl(Poly a) { // a642f6
    if (a.empty()) return {0};
    int z = QuadraticResidue(a[0], mod), n = a.size();
    if (z == -1) return {-1};
    Poly q(1, z);
    const int inv2 = (mod + 1) / 2;
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        q.resize(m * 2);
        Poly f2 = Mul(q, q, m * 2);
        for (int i = 0; i < m * 2; ++i)
            f2[i] = sub(f2[i], a[i]);
        f2 = Mul(f2, Inverse(q), m * 2);
        for (int i = 0; i < m * 2; ++i)
            q[i] = sub(q[i], mul(f2[i], inv2));
    }
    q.resize(n);
    return q;
}
Poly Sqrt(Poly a) { // 0dae9c
    // O(NLogN), return {-1} if not exists
    int n = a.size(), m = 0;
    while (m < n && a[m] == 0) m++;
    if (m == n) return Poly(n);
    if (m & 1) return {-1};
    Poly s = SqrtImpl(Poly(a.begin() + m, a.end()));
    if (s[0] == -1) return {-1};
    Poly res(n);
    for (int i = 0; i < s.size(); ++i)
        res[i + m / 2] = s[i];
    return res;
}
Poly Derivative(Poly a) { // 26f29b
    int n = a.size();
    Poly res(n - 1);
    for (int i = 0; i < n - 1; ++i)
        res[i] = mul(a[i + 1], i + 1);
    return res;
}
Poly Integral(Poly a) { // f18ba1
    int n = a.size();
    Poly res(n + 1);
    for (int i = 0; i < n; ++i)
        res[i + 1] = mul(a[i], Pow(i + 1, mod - 2));
    return res;
}
Poly Ln(Poly a) { // 0c1381
    // O(NLogN), a[0] = 1
    int n = a.size();
    if (n == 1) return {0};
    Poly d = Derivative(a);
    a.pop_back();
    return Integral(Mul(d, Inverse(a), n - 1));
}
Poly Exp(Poly a) { // d2b129
    // O(NLogN), a[0] = 0
    int n = a.size();
    Poly q(1, 1);
    a[0] = add(a[0], 1);
    for (int m = 1; m < n; m <= 1) {
        if (n < m * 2) a.resize(m * 2);
        Poly g(a.begin(), a.begin() + m * 2), h(all(q));
        h.resize(m * 2), h = Ln(h);
        for (int i = 0; i < m * 2; ++i)
            g[i] = sub(g[i], h[i]);
        q = Mul(g, q, m * 2);
    }
    q.resize(n);
    return q;
}
Poly PolyPow(Poly a, ll k) { // d50135
    int n = a.size(), m = 0;
    Poly ans(n, 0);

```

```

    while (m < n && a[m] == 0) m++;
    if (k && m && (k >= n || k * m >= n)) return ans;
    if (m == n) return ans[0] = 1, ans;
    int lead = m * k;
    Poly b(a.begin() + m, a.end());
    int base = Pow(b[0], k), inv = Pow(b[0], mod - 2);
    for (int i = 0; i < n - m; ++i)
        b[i] = mul(b[i], inv);
    b = Ln(b);
    for (int i = 0; i < n - m; ++i)
        b[i] = mul(b[i], k % mod);
    b = Exp(b);
    for (int i = lead; i < n; ++i)
        ans[i] = mul(b[i - lead], base);
    return ans;
}
vector<int> Evaluate(Poly a, vector<int> x) {
    if (x.empty()) return {}; // e28f67
    int n = x.size();
    vector<Poly> up(n * 2);
    for (int i = 0; i < n; ++i)
        up[i + n] = {sub(0, x[i]), 1};
    for (int i = n - 1; i > 0; --i)
        up[i] = Mul(up[i * 2], up[i * 2 + 1]);
    vector<Poly> down(n * 2);
    down[1] = Divide(a, up[1]).second;
    for (int i = 2; i < n * 2; ++i)
        down[i] = Divide(down[i >> 1], up[i]).second;
    Poly y(n);
    for (int i = 0; i < n; ++i) y[i] = down[i + n][0];
    return y;
}
Poly Interpolate(vector<int> x, vector<int> y) {
    int n = x.size(); // 743f56
    vector<Poly> up(n * 2);
    for (int i = 0; i < n; ++i)
        up[i + n] = {sub(0, x[i]), 1};
    for (int i = n - 1; i > 0; --i)
        up[i] = Mul(up[i * 2], up[i * 2 + 1]);
    Poly a = Evaluate(Derivative(up[1]), x);
    for (int i = 0; i < n; ++i)
        a[i] = mul(y[i], Pow(a[i], mod - 2));
    vector<Poly> down(n * 2);
    for (int i = 0; i < n; ++i) down[i + n] = {a[i]};
    for (int i = n - 1; i > 0; --i) {
        Poly lhs = Mul(down[i * 2], up[i * 2 + 1]);
        Poly rhs = Mul(down[i * 2 + 1], up[i * 2]);
        down[i].resize(lhs.size());
        for (int j = 0; j < lhs.size(); ++j)
            down[i][j] = add(lhs[j], rhs[j]);
    }
    return down[1];
}
Poly TaylorShift(Poly a, int c) { // b59bef
    // return sum a_i(x + c)^i;
    // fac[i] = i!, facp[i] = inv(i!)
    int n = a.size();
    for (int i = 0; i < n; ++i) a[i] = mul(a[i], fac[i]);
    reverse(all(a));
    Poly b(n);
    int w = 1;
    for (int i = 0; i < n; ++i)
        b[i] = mul(facp[i], w), w = mul(w, c);
    a = Mul(a, b, n), reverse(all(a));
    for (int i = 0; i < n; ++i) a[i] = mul(a[i], facp[i]);
    return a;
}
vector<int> SamplingShift(vector<int> a, int c, int m){
    // given f(0), f(1), ..., f(n - 1)
    // return f(c), f(c + 1), ..., f(c + m - 1)
    int n = a.size(); // 4d649d
    for (int i = 0; i < n; ++i) a[i] = mul(a[i], facp[i]);
    Poly b(n);
    for (int i = 0; i < n; ++i) {
        b[i] = facp[i];
        if (i & 1) b[i] = sub(0, b[i]);
    }
    a = Mul(a, b, n);
    for (int i = 0; i < n; ++i) a[i] = mul(a[i], fac[i]);
    reverse(all(a));
    int w = 1;
    for (int i = 0; i < n; ++i)

```

```

    b[i] = mul(facp[i], w), w = mul(w, sub(c, i));
    a = Mul(a, b, n);
    reverse(all(a));
    for (int i = 0; i < n; ++i) a[i] = mul(a[i], facp[i]);
    a.resize(m), b.resize(m);
    for (int i = 0; i < m; ++i) b[i] = facp[i];
    a = Mul(a, b, m);
    for (int i = 0; i < m; ++i) a[i] = mul(a[i], fac[i]);
    return a;
}

```

7.5 Fast Linear Recursion [3f8e4e]

```

int FastLinearRecursion(vector<int> a, vector<int> c,
    ll k) {
    // a_n = sigma c_j * a_{n-j-1}, 0-based
    // O(NlogNlogK), |a| = |c|
    int n = a.size();
    if (k < n) return a[k];
    vector<int> base(n + 1, 1);
    for (int i = 0; i < n; ++i)
        base[i] = sub(0, c[n - i - 1]);
    vector<int> poly(n);
    (n == 1 ? poly[0] = c[n - 1] : poly[1] = 1);
    auto calc = [&](vector<int> p1, vector<int> p2) {
        // O(n^2) brute force or O(nlogn) NTT
        return Divide(Mul(p1, p2), base).second;
    };
    vector<int> res(n, 0); res[0] = 1;
    for (; k; k >>= 1, poly = calc(poly, poly)) {
        if (k & 1) res = calc(res, poly);
    }
    int ans = 0;
    for (int i = 0; i < n; ++i)
        ans = add(ans, mul(res[i], a[i]));
    return ans;
}

```

7.6 Fast Walsh Transform

```

void fwt(vector<int> &a, bool inv = false) {
    // and : x += y * (1, -1)
    // or : y += x * (1, -1)
    // xor : x = (x + y) * (1, 1/2)
    //      y = (x - y) * (1, 1/2)
    int n = __lg(a.size());
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < 1 << n; ++j) if (j >> i & 1) {
            int x = a[j ^ (1 << i)], y = a[j];
            // do something
        }
    }
}

vector<int> subs_conv(vector<int> a, vector<int> b) {
    // c_i = sum_{j+k=i} a_j * b_k
    int n = __lg(a.size());
    vector ha(n + 1, vector<int>(1 << n));
    vector hb(n + 1, vector<int>(1 << n));
    vector c(n + 1, vector<int>(1 << n));
    for (int i = 0; i < 1 << n; ++i) {
        ha[__builtin_popcount(i)][i] = a[i];
        hb[__builtin_popcount(i)][i] = b[i];
    }
    for (int i = 0; i <= n; ++i)
        or_fwt(ha[i]), or_fwt(hb[i]);
    for (int i = 0; i <= n; ++i)
        for (int j = 0; i + j <= n; ++j)
            for (int k = 0; k < 1 << n; ++k)
                c[i + j][k] = add(c[i + j][k],
                    mul(ha[i][k], hb[j][k]));
    for (int i = 0; i <= n; ++i) or_fwt(c[i], true);
    vector<int> ans(1 << n);
    for (int i = 0; i < 1 << n; ++i)
        ans[i] = c[__builtin_popcount(i)][i];
    return ans;
}

```

8 Geometry

8.1 Basic

```

template<typename T> struct P {};
using Pt = P<ll>;

```

```

struct Line { Pt a, b; };
struct Cir { Pt o; double r; };
ll abs2(Pt a) { return a * a; }
double abs(Pt a) { return sqrt(abs2(a)); }
int ori(Pt o, Pt a, Pt b)
{ return sign((o - a) ^ (o - b)); }
bool btw(Pt a, Pt b, Pt c) // c on segment ab?
{ return ori(a, b, c) == 0 &&
    sign((c - a) * (c - b)) <= 0; }
int pos(Pt a)
{ return sign(a.y) == 0 ? sign(a.x) < 0 : a.y < 0; }
bool cmp(Pt a, Pt b)
{ return pos(a) == pos(b) ? sign(a ^ b) > 0 :
    pos(a) < pos(b); }
bool same_vec(Pt a, Pt b, int d) // d = 1: check dir
{ return sign(a ^ b) == 0 && sign(a * b) > d * 2 - 2; }
bool same_vec(Line a, Line b, int d)
{ return same_vec(a.b - a.a, b.b - b.a, d); }
Pt perp(Pt a) { return Pt(-a.y, a.x); } // CCW 90 deg
Pt ref(Pt a) { return pos(a) == 1 ? Pt(-a.x, -a.y) : a; }
// double part
double theta(Pt a)
{ return normalize(atan2(a.y, a.x)); }
Pt unit(Pt o) { return o / abs(o); }
Pt rot(Pt a, double o) // CCW
{ double c = cos(o), s = sin(o);
    return Pt(c * a.x - s * a.y, s * a.x + c * a.y); }
Pt proj_vec(Pt a, Pt b, Pt c) // vector ac proj to ab
{ return (b - a) * ((c - a) * (b - a)) / (abs2(b - a)); }
Pt proj_pt(Pt a, Pt b, Pt c) // point c proj to ab
{ return proj_vec(a, b, c) + a; }

```

8.2 SVG Writer

```

#ifndef ABS
class SVG { // SVG("test.svg", 0, 0, 10, 10)
    void p(string_view s) { o << s; }
    void p(string_view s, auto v, auto... vs) {
        auto i = s.find('$');
        o << s.substr(0, i) << v, p(s.substr(i + 1), vs...)
        ;
    }
    ofstream o; string c = "red";
public:
    SVG(auto f, auto x1, auto y1, auto x2, auto y2) : o(f) {
        p("<svg xmlns='http://www.w3.org/2000/svg' "
            "viewBox='$ $ $ $'>\n"
            "<style>{*stroke-width:0.5%;}</style>\n",
            x1, -y2, x2 - x1, y2 - y1); }
    ~SVG() { p("</svg>\n"); }
    void color(string nc) { c = nc; }
    void line(auto x1, auto y1, auto x2, auto y2) {
        p("<line x1='$' y1='$' x2='$' y2='$' stroke='$'>\n"
            ",
            x1, -y1, x2, -y2, c); }
    void circle(auto x, auto y, auto r) {
        p("<circle cx='$' cy='$' r='$' stroke='$' "
            "fill='none'/>\n", x, -y, r, c); }
    void text(auto x, auto y, string s, int w = 12) {
        p("<text x='$' y='$' font-size='$px'>$</text>\n",
            x, -y, w, s); }
}; // write wrapper for complex if use complex
#else
struct SVG { SVG(auto ...) {} }; // you know how to
#endif

```

8.3 Sort

```

// cmp in Basic: polar angle sort
// all points are on line ab. closer to a: front
bool cmp_line(Pt s, Pt t, Pt a, Pt b) { // 3dc688
    Pt v = a - b;
    if (sign(v.x)) return sign(s.x - t.x) == sign(v.x);
    else return sign(s.y - t.y) == sign(v.y);
}
// intersect points polar angle sort, deno: positive
bool cmp_fraction_polar(pair<Pt, ll> o, pair<Pt, ll> s,
    pair<Pt, ll> t) { // C^3 / C^2, 2d4450
    Pt u = s.first * o.second - o.first * s.second; // C^5
    Pt v = t.first * o.second - o.first * t.second; // C^5
    // u /= gcd(u.x, u.y) might lower the range to C
    return cmp(u, v);
}

```


8.4 Intersections

```
// m=0: segment, m=1: ray from l.a to l.b, m=2: Line
bool lines_intersect_check(Line l1, int m1, Line l2,
    int m2, int strict) { // 56cc8d
    auto on = [&](Line l, int m, Pt p) {
        if (ori(l.a, l.b, p) != 0) return false;
        if (m && abs2(l.a - p) > abs2(l.b - p)) return true;
        return m == 2 || sign((p - l.a) * (p - l.b)) <= -
            strict;
    };
    if (same_vec(l1, l2, 0)) {
        return on(l1, m1, l2.a) || on(l1, m1, l2.b) ||
            on(l2, m2, l1.a) || on(l2, m2, l1.b);
    }
    auto good = [&](Line l, int m, Line o) {
        if (m && abs((l.a - o.a) ^ (l.a - o.b)) > abs((l.b
            - o.a) ^ (l.b - o.b))) return true;
        return m == 2 || ori(l.a, o.a, o.b) * ori(l.b, o.a,
            o.b) == -1;
    };
    if (good(l1, m1, l2) && good(l2, m2, l1)) return 1;
    if (!strict) {
        if (m2 != 2 && on(l1, m1, l2.a)) return 1;
        if (m2 == 0 && on(l1, m1, l2.b)) return 1;
        if (m1 != 2 && on(l2, m2, l1.a)) return 1;
        if (m1 == 0 && on(l2, m2, l1.b)) return 1;
    }
    return 0;
}
// notice two lines are parallel
auto lines_intersect(Line a, Line b) { // 726acc
    auto abc = (a.b - a.a) ^ (b.a - a.a);
    auto abd = (a.b - a.a) ^ (b.b - a.a);
    return make_pair((b.b * abc - b.a * abd), abc - abd);
}
// res[0] -> res[1] and l.a -> l.b: same direction
vector<Pt> circle_line_intersect(Cir c, Line l) { //
    b7bdce
    Pt p = l.a + (l.b - l.a) * ((c.o - l.a) * (l.b - l.a)
        ) / abs2(l.b - l.a);
    double s = (l.b - l.a) ^ (c.o - l.a), h2 = c.r * c.r
        - s * s / abs2(l.b - l.a);
    if (sign(h2) == -1) return {};
    if (sign(h2) == 0) return {p};
    Pt h = (l.b - l.a) / abs(l.b - l.a) * sqrt(h2);
    return {p - h, p + h};
}
// covered area of c1: arc from res[0] to res[1], CCW
vector<Pt> circles_intersect(Cir c1, Cir c2) { // 0acf68
    double d2 = abs2(c1.o - c2.o), d = sqrt(d2);
    if (d < max(c1.r, c2.r) - min(c1.r, c2.r) || d > c1.r
        + c2.r) return {};
    Pt u = (c1.o + c2.o) / 2 + (c1.o - c2.o) * ((c2.r *
        c2.r - c1.r * c1.r) / (2 * d2));
    double A = sqrt((c1.r + c2.r + d) * (c1.r - c2.r + d)
        * (c1.r + c2.r - d) * (-c1.r + c2.r + d));
    Pt v = perp(c2.o - c1.o) * A / (2 * d2);
    if (sign(v.x) == 0 && sign(v.y) == 0) return {u};
    return {u - v, u + v};
}
```

8.5 Point Inside Check

```
// get edge index: check (0, a), (0, b) first
// then after binary search, check (a, b)
bool point_in_convex(vector<Pt> &C, Pt p, bool strict =
    true) { // 722991
    // only works when no three points are collinear
    int a = 1, b = sz(C) - 1, r = !strict;
    if (sz(C) == 0) return false;
    if (sz(C) < 3) return r && btw(C[0], C.back(), p);
    if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
    if (ori(C[0], C[a], p) >= r || ori(C[0], C[b], p) <=
        -r) return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (ori(C[0], C[c], p) > 0 ? b : a) = c;
    }
    return ori(C[a], C[b], p) < r;
}
```

```
// -1: out, 0: edge, 1: in
int point_in_poly(vector<Pt> poly, Pt o, int strict) {
    // 94b56b
    int cnt = 0;
    for (int i = 0; i < sz(poly); ++i) {
        Pt a = poly[i], b = poly[(i + 1) % sz(poly)];
        if (btw(o, a, b)) return !strict;
        cnt ^= ((o.y < a.y) - (o.y < b.y)) * ori(o, a, b) >
            0;
    }
    return cnt ? 1 : -1;
}
// return q's relation with circumcircle of tri(p[0], p
    [1], p[2])
bool point_in_cc(array<Pt, 3> p, Pt q) { // cc76d3
    __int128 det = 0;
    for (int i = 0; i < 3; ++i)
        det += __int128(abs2(p[i]) - abs2(q)) * ((p[(i + 1)
            % 3] - q) ^ (p[(i + 2) % 3] - q));
    return det > 0; // in: >0, on: =0, out: <0
}
```

8.6 Convex Hull [d490c0]

```
auto convex_hull(vector<Pt> pts) {
    sort(all(pts), [&](Pt a, Pt b)
        {return a.x == b.x ? a.y < b.y : a.x < b.x;});
    vector<Pt> ans = {pts[0]};
    for (int t = 0; t < 2; ++t, reverse(all(pts))) {
        for (int i = 1, m = sz(ans); i < sz(pts); ++i) {
            while (sz(ans) > m && ori(ans[sz(ans) - 2],
                ans.back(), pts[i]) <= 0) ans.pop_back();
            ans.pb(pts[i]);
        }
        if (sz(ans) > 1) ans.pop_back();
        return ans;
    }
}
```

8.7 Point Segment Distance [4249fd]

```
double point_segment_dist(Pt q0, Pt q1, Pt p) {
    if (sign(abs(q0 - q1)) == 0) return abs(q0 - p);
    if (sign((q1 - q0) * (p - q0)) >= 0 && sign((q0 - q1)
        * (p - q1)) >= 0)
        return fabs(((q1 - q0) ^ (p - q0)) / abs(q0 - q1));
    return min(abs(p - q0), abs(p - q1));
}
```

8.8 Vector In Polygon [6dac08]

```
// ori(a, b, c) >= 0, valid: "strict" angle from a-b to
    a-c
bool btwangle(Pt a, Pt b, Pt c, Pt p, int strict) {
    return ori(a, b, p) >= strict && ori(a, p, c) >=
        strict;
}
// whether vector{cur, p} in counter-clockwise order
    prv, cur, nxt
bool inside(Pt prv, Pt cur, Pt nxt, Pt p, int strict) {
    if (ori(cur, nxt, prv) >= 0)
        return btwangle(cur, nxt, prv, p, strict);
    return !btwangle(cur, prv, nxt, p, !strict);
}
// call "inside" not btwangle
```

8.9 Minkowski Sum [2ff069]

```
void reorder(vector<Pt> &P) {
    rotate(P.begin(), min_element(all(P), [&](Pt a, Pt b)
        {return make_pair(a.y, a.x) < make_pair(b.y, b.x);
        })), P.end());
}
auto minkowski(vector<Pt> P, vector<Pt> Q) {
    // P, Q: convex polygon, CCW order
    reorder(P), reorder(Q); int n = sz(P), m = sz(Q);
    P.pb(P[0]), P.pb(P[1]), Q.pb(Q[0]), Q.pb(Q[1]);
    vector<Pt> ans;
    for (int i = 0, j = 0; i < n || j < m; ) {
        ans.pb(P[i] + Q[j]);
        auto val = (P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]);
        if (val >= 0) i++;
        if (val <= 0) j++;
    }
```

```

}
return ans;
}

```

8.10 Rotating SweepLine [56f0e2]

```

struct Event {
    Pt d; int u, v;
    bool operator < (const Event &o) {
        return sign(d ^ o.d) > 0; }
};

void rotating_sweepline(vector<Pt> pts) {
    int n = sz(pts);
    vector<int> ord(n), pos(n);
    vector<Event> e;
    for (int i = 0; i < n; ++i)
        for (int j = i + 1; j < n; ++j)
            e.pb({ref(pts[i] - pts[j]), i, j});
    sort(all(e));
    iota(all(ord), 0);
    sort(all(ord), [&](int i, int j) {
        return (sign(pts[i].y - pts[j].y) == 0 ?
            pts[i].x < pts[j].x : pts[i].y < pts[j].y); });
    for (int i = 0; i < n; ++i) pos[ord[i]] = i;
    auto makeReverse = [](auto v) {
        sort(all(v)), v.resize(unique(all(v)) - v.begin());
        vector<pii> segs;
        for (int i = 0, j = 0; i < sz(v); i = j) {
            for (; j < sz(v) && v[j] - v[i] <= j - i; ++j);
            segs.emplace_back(v[i], v[j - 1] + 1 + 1);
        }
        return segs;
    };
    for (int i = 0, j = 0; i < sz(e); i = j) {
        vector<int> tmp;
        for (; j < sz(e) && !(e[i] < e[j]); j++)
            tmp.pb(min(pos[e[j].u], pos[e[j].v]));
        for (auto [l, r] : makeReverse(tmp)) {
            reverse(ord.begin() + l, ord.begin() + r);
            for (int t = l; t < r; ++t) pos[ord[t]] = t;
            // update value here
        }
    }
}

```

8.11 Half Plane Intersection [f6c2b0]

```

/* Having solution, check size > 2 */
/* ---^--- Line.a ---^--- Line.b ---^--- */
auto halfplane_intersection(vector<Line> arr) {
    auto area_pair = [&](Line a, Line b) {
        return make_pair((a.b - a.a) ^ (b.a - a.a),
            (a.b - a.a) ^ (b.b - a.a)); };
    auto isin = [&](Line l0, Line l1, Line l2) {
        // Check inter(l1, l2) strictly in l0
        auto [a02X, a02Y] = area_pair(l0, l2);
        auto [a12X, a12Y] = area_pair(l1, l2);
        if (a12X - a12Y < 0) a12X *= -1, a12Y *= -1;
        return ((__int128)a02Y * a12X -
            (__int128)a02X * a12Y > 0; // C^4
    };
    sort(all(arr), [&](Line a, Line b) {
        if (same_vec(a, b, 1))
            return ori(a.a, a.b, b.b) < 0;
        return cmp(a.b - a.a, b.b - b.a); });
    deque<Line> dq(1, arr[0]);
    auto pop_back = [&](int t, Line p) {
        while (sz(dq) >= t && !isin(p, dq[sz(dq) - 2], dq.back()))
            dq.pop_back();
    };
    auto pop_front = [&](int t, Line p) {
        while (sz(dq) >= t && !isin(p, dq[0], dq[1]))
            dq.pop_front();
    };
    for (auto p : arr)
        if (!same_vec(dq.back(), p, 1))
            pop_back(2, p), pop_front(2, p), dq.pb(p);
    pop_back(3, dq[0]), pop_front(3, dq.back());
    return vector<Line>(all(dq));
}

```

8.12 Minimum Enclosing Circle [2db817]

```

Cir min_enclosing(vector<Pt> p) {
    random_shuffle(all(p));
    double r = 0.0;
    Pt cent = p[0];
    for (int i = 1; i < sz(p); ++i) {
        if (abs2(cent - p[i]) <= r) continue;
        cent = p[i], r = 0.0;
        for (int j = 0; j < i; ++j) {
            if (abs2(cent - p[j]) <= r) continue;
            cent = (p[i] + p[j]) / 2, r = abs2(p[j] - cent);
            for (int k = 0; k < j; ++k) {
                if (abs2(cent - p[k]) <= r) continue;
                cent = circenter(p[i], p[j], p[k]);
                r = abs2(p[k] - cent);
            }
        }
    }
    return {cent, sqrt(r)};
}

```

8.13 Heart [043c0d]

```

Pt circenter(Pt p0, Pt p1, Pt p2) {
    // radius = abs(center)
    p1 = p1 - p0, p2 = p2 - p0;
    double x1 = p1.x, y1 = p1.y, x2 = p2.x, y2 = p2.y;
    double m = 2. * (x1 * y2 - y1 * x2);
    Pt center(0, 0);
    center.x = (x1 * x1 * y2 - x2 * x2 * y1 + y1 * y2 * (
        y1 - y2)) / m;
    center.y = (x1 * x2 * (x2 - x1) - y1 * y1 * x2 + x1 *
        y2 * y2) / m;
    return center + p0;
}

Pt incenter(Pt p1, Pt p2, Pt p3) {
    // radius = area / s * 2
    double a = abs(p2 - p3), b = abs(p1 - p3), c = abs(p1 - p2);
    double s = a + b + c;
    return (p1 * a + p2 * b + p3 * c) / s;
}

Pt masscenter(Pt p1, Pt p2, Pt p3)
{ return (p1 + p2 + p3) / 3; }

Pt orthocenter(Pt p1, Pt p2, Pt p3)
{ return masscenter(p1, p2, p3) * 3 - circenter(p1, p2, p3) * 2; }

```

8.14 Tangents [277413]

```

auto circle_point_tangent(Cir c, Pt p) { // 6af9a8
    vector<Line> res;
    double d_sq = abs2(p - c.o);
    if (sign(d_sq - c.r * c.r) == 0) {
        res.pb({p, p + perp(p - c.o)});
    } else if (d_sq > c.r * c.r) {
        double s = d_sq - c.r * c.r;
        Pt v = p + (c.o - p) * s / d_sq;
        Pt u = perp(c.o - p) * sqrt(s) * c.r / d_sq;
        res.pb({p, v + u});
        res.pb({p, v - u});
    }
    return res;
}

auto circles_tangent(Cir c1, Cir c2, int sign1) { // b8d41e
    // sign1 = 1 for outer tang, -1 for inner tang
    vector<Line> res;
    double d_sq = abs2(c1.o - c2.o);
    if (sign(d_sq) == 0) return res;
    double d = sqrt(d_sq);
    Pt v = (c2.o - c1.o) / d;
    double c = (c1.r - sign1 * c2.r) / d;
    if (c * c > 1) return res;
    double h = sqrt(max((double)0.0, 1.0 - c * c));
    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
        Pt n = Pt(v.x * c - sign2 * h * v.y, v.y * c +
            sign2 * h * v.x);
        Pt p1 = c1.o + n * c1.r;
        Pt p2 = c2.o + n * (c2.r * sign1);
        if (sign(p1.x - p2.x) == 0 && sign(p1.y - p2.y) == 0)
            p2 = p1 + perp(c2.o - c1.o);
    }
}

```

```

    res.pb({p1, p2});
}
return res;
}
/* The point should be strictly out of hull
   return arbitrary point on the tangent line */
pii point_convex_tangent(vector<Pt> &C, Pt p) {//63a82a
    auto gao = [&](int s) {
        return cyc_tsearch(sz(C), [&](int x, int y)
        { return ori(p, C[x], C[y]) == s; });
    };
    return pii(gao(1), gao(-1));
} // return (a, b), ori(p, C[a], C[b]) >= 0

```

8.15 Union of Circles [e5c3ee]

```

// notice identical circles, compare cross -> x if the
   precision is bad
auto circles_border(vector<Cir> c, int id) {
    vector<pair<Pt, int>> vec;
    int base = 0;
    for (int i = 0; i < sz(c); ++i) if (id != i) {
        if (sign(c[id].r - c[i].r) < 0 && abs2(c[id].o - c[i].o) <= (c[id].r - c[i].r) * (c[id].r - c[i].r)) base++;
        auto tmp = circles_intersect(c[id], c[i]);
        if (sz(tmp) == 2) {
            Pt l = tmp[0] - c[id].o, r = tmp[1] - c[id].o;
            vec.emplace_back(l, 1);
            vec.emplace_back(r, -1);
            if (cmp(r, l)) base++;
        }
    }
    vec.emplace_back(Pt(-c[id].r, 0), 0);
    sort(all(vec), [&](auto i, auto j) {
        return cmp(i.first, j.first);
    });
    vector<pair<Pt, Pt>> seg;
    Pt v = Pt(c[id].r, 0), lst = v;
    for (auto [cur, val] : vec) {
        if (base == 0) seg.emplace_back(lst, cur);
        lst = cur, base += val;
    }
    if (base == 0) seg.emplace_back(lst, v);
    for (auto &[l, r] : seg)
        l = l + c[id].o, r = r + c[id].o;
    return seg;
}
double circles_union_area(vector<Cir> c) {
    double res = 0;
    for (int i = 0; i < sz(c); ++i) {
        auto seg = circles_border(c, i);
        auto F = [&](double t) { return c[i].r * (c[i].r * t + c[i].o.x * sin(t) - c[i].o.y * cos(t)); };
        for (auto [l, r] : seg) {
            double tl = theta(l - c[i].o), tr = theta(r - c[i].o);
            if (sign(tl - tr) > 0) tr += PI * 2;
            res += F(tr) - F(tl);
        }
    }
    return res / 2;
}

```

8.16 Union of Polygons [c7ddf6]

```

// in CCW order, use index as tiebreaker when collinear
auto polys_border(vector<vector<Pt>> poly, int id) {
    auto get = [&](auto &p, int i) {
        return make_pair(p[i], p[(i + 1) % sz(p)]);
    };
    vector<pair<Pt, Pt>> seg;
    for (int e = 0; e < sz(poly[id]); ++e) {
        auto [s, t] = get(poly[id], e);
        vector<pair<Pt, int>> vec;
        vec.emplace_back(s, -1 << 30);
        vec.emplace_back(t, 1 << 30);
        for (int i = 0; i < sz(poly); ++i) {
            int st = find_if(all(poly[i]), [&](Pt p) {
                return ori(p, s, t) == 1; }) - poly[i].begin();
            if (st == sz(poly[i])) continue;
            for (int j = st; j < st + sz(poly[i]); ++j) {
                auto [a, b] = get(poly[i], j % sz(poly[i]));

```

```

                if (same_vec(a - b, s - t, -1)) {
                    if (ori(a, b, s) == 0 && same_vec(a - b, s - t, 1) && i <= id) {
                        vec.emplace_back(a, -1);
                        vec.emplace_back(b, 1);
                    }
                } else {
                    int s1 = ori(a, s, t) == 1, s2 = ori(b, s, t) == 1;
                    if (s1 ^ s2) {
                        auto p = lines_intersect({a, b}, {s, t});
                        vec.emplace_back(p, s1 ? 1 : -1);
                    }
                }
            }
        }
    }
    sort(all(vec), [&](auto i, auto j) {
        return cmp_line(i.first, j.first, s, t);
    });
    int base = 1 << 30; Pt lst(0, 0);
    for (auto [cur, val] : vec) {
        if (!base) seg.emplace_back(lst, cur);
        lst = cur, base += val;
    }
    return seg;
}
double polys_union_area(vector<vector<Pt>> poly) {
    double res = 0;
    for (int i = 0; i < sz(poly); ++i) {
        auto seg = polys_border(poly, i);
        for (auto [l, r] : seg) res += l ^ r;
    }
    return res / 2;
}

```

8.17 Delaunay Triangulation [953c88]

```

/* Delaunay Triangulation:
   Given a sets of points on 2D plane, find a
   triangulation such that no points will strictly
   inside circumcircle of any triangle. */
struct Edge {
    int id; // oidx[id]
    list<Edge>::iterator twin;
    Edge (int _id = 0) : id(_id) {}
};
struct Delaunay { // 0-base
    int n;
    vector<int> oidx;
    vector<list<Edge>> head; // result udir. graph
    vector<Pt> p;
    Delaunay (vector<Pt> _p) : n(sz(_p)), oidx(n), head(n) {
        iota(all(oidx), 0);
        sort(all(oidx), [&](int a, int b) {
            return make_pair(_p[a].x, _p[a].y) < make_pair(_p[b].x, _p[b].y);
        });
        for (int i = 0; i < n; ++i) p[i] = _p[oidx[i]];
        divide(0, n - 1);
    }
    void add_edge(int u, int v) {
        head[u].push_front(Edge(v));
        head[v].push_front(Edge(u));
        head[u].begin()->twin = head[v].begin();
        head[v].begin()->twin = head[u].begin();
    }
    void divide(int l, int r) {
        if (l == r) return;
        if (l + 1 == r) return add_edge(l, l + 1);
        int mid = (l + r) >> 1, nw[2] = {l, r};
        divide(l, mid), divide(mid + 1, r);
        auto gao = [&](int t) {
            Pt pts[2] = {p[nw[0]], p[nw[1]]};
            for (auto it : head[nw[t]]) {
                int v = ori(pts[1], pts[0], p[it.id]);
                if (v > 0 || (v == 0 && abs2(pts[t ^ 1] - p[it.id]) < abs2(pts[1] - pts[0])))
                    return nw[t] = it.id, true;
            }
            return false;
        };
        while (gao(0) || gao(1));
    }
};

```

```

add_edge(nw[0], nw[1]); // add tangent
while (true) {
    Pt pts[2] = {p[nw[0]], p[nw[1]]};
    int ch = -1, sd = 0;
    for (int t = 0; t < 2; ++t)
        for (auto it : head[nw[t]])
            if (ori(pts[0], pts[1], p[it.id]) > 0 && (ch
                == -1 || point_in_cc({pts[0], pts[1], p[
                    ch]}, p[it.id])))
                ch = it.id, sd = t;
    if (ch == -1) break; // upper common tangent
    for (auto it = head[nw[sd]].begin(); it != head[
        nw[sd]].end(); )
        if (lines_intersect_check({pts[sd], p[it->id]},
            0, {pts[sd] ^ 1}, p[ch]), 0, 1))
            head[it->id].erase(it->twin), head[nw[sd]].
                erase(it++);
    else ++it;
    nw[sd] = ch, add_edge(nw[0], nw[1]);
}
};

```

8.18 Triangulation Voronoi [46f248]

```

// all coord. is even, half plane intersection
auto build_voronoi_line(vector<Pt> arr) {
    int n = sz(arr);
    Delaunay tool(arr);
    vector<vector<Line>> vec(n);
    for (int i = 0; i < n; ++i)
        for (auto e : tool.head[i]) {
            int u = tool.oidx[i], v = tool.oidx[e.id];
            Pt m = (arr[v] + arr[u]) / 2, d = perp(arr[v] -
                arr[u]);
            vec[u].pb(Line{m, m + d});
        }
    return vec;
}

```

8.19 External Bisector [cafb92]

```

Pt external_bisector(Pt p1, Pt p2, Pt p3) { //213
    Pt L1 = p2 - p1, L2 = p3 - p1;
    L2 = L2 * abs(L1) / abs(L2);
    return L1 + L2;
}

```

8.20 Intersection Area of Polygon and Circle [000043]

```

double _area(Pt pa, Pt pb, double r){
    if (abs(pa) < abs(pb)) swap(pa, pb);
    if (abs(pb) < eps) return 0;
    double S, h, theta;
    double a = abs(pb), b = abs(pa), c = abs(pb - pa);
    double cosB = pb * (pb - pa) / a / c, B = acos(cosB);
    double cosC = (pa * pb) / a / b, C = acos(cosC);
    if (a > r) {
        S = (C / 2) * r * r;
        h = a * b * sin(C) / c;
        if (h < r && B < PI / 2) S -= (acos(h / r) * r * r
            - h * sqrt(r * r - h * h));
    } else if (b > r) {
        theta = PI - B - asin(sin(B) / r * a);
        S = 0.5 * a * r * sin(theta) + (C - theta) / 2 * r
            * r;
    } else S = 0.5 * sin(C) * a * b;
    return S;
}
double area_poly_circle(vector<Pt> poly, Pt O, double r
) {
    double S = 0; int n = sz(poly);
    for (int i = 0; i < n; ++i)
        S += _area(poly[i] - O, poly[(i + 1) % n] - O, r) *
            ori(O, poly[i], poly[(i + 1) % n]);
    return fabs(S);
}

```

8.21 3D Point

```

struct Pt {
    double x, y, z;
};

```

```

Pt(double _x = 0, double _y = 0, double _z = 0): x(_x
), y(_y), z(_z){}
Pt operator + (const Pt &o) const
{ return Pt(x + o.x, y + o.y, z + o.z); }
Pt operator - (const Pt &o) const
{ return Pt(x - o.x, y - o.y, z - o.z); }
Pt operator * (const double &k) const
{ return Pt(x * k, y * k, z * k); }
Pt operator / (const double &k) const
{ return Pt(x / k, y / k, z / k); }
double operator * (const Pt &o) const
{ return x * o.x + y * o.y + z * o.z; }
Pt operator ^ (const Pt &o) const
{ return {Pt(y * o.z - z * o.y, z * o.x - x * o.z, x
    * o.y - y * o.x)}; }
};
double abs2(Pt o) { return o * o; }
double abs(Pt o) { return sqrt(abs2(o)); }
Pt cross3(Pt a, Pt b, Pt c)
{ return (b - a) ^ (c - a); }
double area(Pt a, Pt b, Pt c)
{ return abs(cross3(a, b, c)); }
double volume(Pt a, Pt b, Pt c, Pt d)
{ return cross3(a, b, c) * (d - a); }
bool coplaner(Pt a, Pt b, Pt c, Pt d)
{ return sign(volume(a, b, c, d)) == 0; }
Pt proj(Pt o, Pt a, Pt b, Pt c) // o proj to plane abc
{ Pt n = cross3(a, b, c);
    return o - n * ((o - a) * (n / abs2(n))); }
Pt line_plane_intersect(Pt u, Pt v, Pt a, Pt b, Pt c) {
    // intersection of line uv and plane abc
    Pt n = cross3(a, b, c);
    double s = n * (u - v);
    if (sign(s) == 0) return {-1, -1, -1}; // not found
    return v + (u - v) * ((n * (a - v)) / s); }

```

8.22 3D Convex Hull [cc038d]

```

struct Face {
    int a, b, c;
    Face(int _a, int _b, int _c) : a(_a), b(_b), c(_c) {}
};
auto preprocess(auto pts) {
    auto G = pts.begin();
    vector<int> id;
    auto fail = tuple{-1, -1, -1, id};
    int a = find_if(all(pts), [&](Pt z) {
        return z != *G; }) - G;
    if (a == sz(pts)) return fail;
    int b = find_if(all(pts), [&](Pt z) {
        return cross3(*G, pts[a], z) != Pt(0, 0, 0); }) - G;
    if (b == sz(pts)) return fail;
    int c = find_if(all(pts), [&](Pt z) {
        return sign(volume(*G, pts[a], pts[b], z)) != 0; })
        - G;
    if (c == sz(pts)) return fail;
    for (int i = 0; i < sz(pts); i++)
        if (i != a && i != b && i != c) id.pb(i);
    return tuple{a, b, c, id};
}
// return the faces with pts indexes
vector<Face> convex_hull_3D(vector<Pt> pts) {
    int n = sz(pts);
    if (n <= 3) return {}; // be careful about edge case
    vector<Face> now;
    vector<vector<int>> z(n, vector<int>(n));
    auto [a, b, c, ord] = preprocess(pts);
    if (a == -1) return {};
    now.emplace_back(a, b, c); now.emplace_back(c, b, a);
    for (auto i : ord) {
        vector<Face> nxt;
        for (auto &f : now) {
            auto v = volume(pts[f.a], pts[f.b], pts[f.c], pts
                [i]);
            if (sign(v) <= 0) nxt.pb(f);
            z[f.a][f.b] = z[f.b][f.c] = z[f.c][f.a] = sign(v)
                ;
        }
        auto F = [&](int x, int y) {
            if (z[x][y] > 0 && z[y][x] <= 0)
                nxt.emplace_back(x, y, i);
        };
    }
};

```

```

    for (auto &f : now)
        F(f.a, f.b), F(f.b, f.c), F(f.c, f.a);
    now = nxt;
}
return now;
}
// n^2 delaunay: facets with negative z normal of
// convexhull of (x, y, x^2 + y^2), use a pseudo-point
// (0, 0, inf) to avoid degenerate case
// test @ SPOJ CH3D
// double area = 0, vol = 0; // surface area / volume
// for (auto [a, b, c]: faces)
//     area += abs(ver(p[a], p[b], p[c]))/2.0,
//     vol += volume(P3(0, 0, 0), p[a], p[b], p[c])/6.0;

```

9 Else

9.1 Pbds

```

#include <ext/pb_ds/priority_queue.hpp>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
#include <ext/rope>
using namespace __gnu_cxx;
__gnu_pbds::priority_queue<int> pq1, pq2;
pq1.join(pq2); // pq1 += pq2, pq2 = {}
cc_hash_table<int, int> m1;
tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update> oset;
oset.insert(2), oset.insert(4);
*oset.find_by_order(1), oset.order_of_key(1); // 4 0
bitset<100> BS;
BS.flip(3), BS.flip(5);
BS._Find_first(), BS._Find_next(3); // 3 5
rope<int> rp1, rp2;
rp1.push_back(1), rp1.push_back(3);
rp1.insert(0, 2); // pos, num
rp1.erase(0, 2); // pos, len
rp1.substr(0, 2); // pos, len
rp2.push_back(4);
rp1 += rp2, rp2 = rp1;
rp2[0], rp2[1]; // 3 4

```

9.2 Bit Hack

```

ll next_perm(ll v) { ll t = v | (v - 1);
    return (t + 1) |
        (((~t & ~t) - 1) >> (__builtin_ctz(v) + 1)); }

```

9.3 Smawk Algorithm [5a33b4]

```

ll f(int l, int r) { }
bool select(int r, int u, int v) {
    // if f(r, v) is better than f(r, u), return true
    return f(r, u) < f(r, v);
}
// For all 2x2 submatrix: (x < y => y is better than x)
// If M[1][0] < M[1][1], M[0][0] < M[0][1]
// If M[1][0] == M[1][1], M[0][0] <= M[0][1]
// M[i][ans_i] is the best value in the i-th row
vector<int> solve(vector<int> &r, vector<int> &c) {
    const int n = r.size();
    if (n == 0) return {};
    vector<int> c2;
    for (const int &i : c) {
        while (!c2.empty() && select(r[c2.size() - 1], c2.
            back(), i)) c2.pop_back();
        if (c2.size() < n) c2.pb(i);
    }
    vector<int> r2;
    for (int i = 1; i < n; i += 2) r2.pb(r[i]);
    const auto a2 = solve(r2, c2);
    vector<int> ans(n);
    for (int i = 0; i < a2.size(); i++)
        ans[i * 2 + 1] = a2[i];
    int j = 0;
    for (int i = 0; i < n; i += 2) {
        ans[i] = c2[j];
        const int end = i + 1 == n ? c2.back() : ans[i +
            1];
        while (c2[j] != end) {
            j++;
            if (select(r[i], ans[i], c2[j])) ans[i] = c2[j];

```

```

    }
}
return ans;
}
vector<int> smawk(int n, int m) {
    vector<int> row(n), col(m);
    iota(all(row), 0), iota(all(col), 0);
    return solve(row, col);
}

```

9.4 Slope Trick [d51078]

```

template<typename T>
struct slope_trick_convex {
    T minn = 0, ground_l = 0, ground_r = 0;
    priority_queue<T, vector<T>, less<T>> left;
    priority_queue<T, vector<T>, greater<T>> right;
    slope_trick_convex() {left.push(numeric_limits<T>::
        min() / 2), right.push(numeric_limits<T>::max() /
        2);}
    void push_left(T x) {left.push(x - ground_l);}
    void push_right(T x) {right.push(x - ground_r);}
    //add a line with slope 1 to the right starting from
    x
    void add_right(T x) {
        T l = left.top() + ground_l;
        if (l <= x) push_right(x);
        else push_left(x), push_right(l), left.pop(), minn
            += l - x;
    }
    //add a line with slope -1 to the left starting from
    x
    void add_left(T x) {
        T r = right.top() + ground_r;
        if (r >= x) push_left(x);
        else push_right(x), push_left(r), right.pop(), minn
            += x - r;
    }
    //val[i]=min(val[j]) for all i-l<=j<=i+r
    void expand(T l, T r) {ground_l -= l, ground_r += r;}
    void shift_up(T x) {minn += x;}
    T get_val(T x) {
        T l = left.top() + ground_l, r = right.top() +
            ground_r;
        if (x >= l && x <= r) return minn;
        if (x < l) {
            vector<T> trash;
            T cur_val = minn, slope = 1, res;
            while (1) {
                trash.push_back(left.top());
                left.pop();
                if (left.top() + ground_l <= x) {
                    res = cur_val + slope * (l - x);
                    break;
                }
                cur_val += slope * (l - (left.top() + ground_l)
                    );
                l = left.top() + ground_l;
                slope += 1;
            }
            for (auto i : trash) left.push(i);
            return res;
        }
        if (x > r) {
            vector<T> trash;
            T cur_val = minn, slope = 1, res;
            while (1) {
                trash.push_back(right.top());
                right.pop();
                if (right.top() + ground_r >= x) {
                    res = cur_val + slope * (x - r);
                    break;
                }
                cur_val += slope * ((right.top() + ground_r) -
                    r);
                r = right.top() + ground_r;
                slope += 1;
            }
            for (auto i : trash) right.push(i);
            return res;
        }
        assert(0);
    }
}

```



```

}
};

```

9.5 ALL LCS [5ff948]

```

void all_lcs(string s, string t) { // 0-base
    vector<int> h(t.size());
    iota(all(h), 0);
    for (int a = 0; a < s.size(); ++a) {
        int v = -1;
        for (int c = 0; c < t.size(); ++c)
            if (s[a] == t[c] || h[c] < v)
                swap(h[c], v);
        // LCS(s[0, a], t[b, c]) =
        // c - b + 1 - sum([h[i] >= b] | i <= c)
        // h[i] might become -1 !!
    }
}

```

9.6 Hilbert Curve [1274a3]

```

ll hilbert(int n, int x, int y) {
    ll res = 0;
    for (int s = n / 2; s; s >>= 1) {
        int rx = (x & s) > 0;
        int ry = (y & s) > 0;
        res += s * 111 * s * ((3 * rx) ^ ry);
        if (ry == 0) {
            if (rx == 1) x = s - 1 - x, y = s - 1 - y;
            swap(x, y);
        }
    }
    return res;
} // n = 2^k

```

9.7 Line Container [673ffd]

```

// only works for integer coordinates!! maintain max
struct Line {
    mutable ll a, b, p;
    bool operator<(const Line &rhs) const { return a <
        rhs.a; }
    bool operator<(ll x) const { return p < x; }
};
struct DynamicHull : multiset<Line, less<>> {
    static const ll kInf = 1e18;
    ll Div(ll a, ll b) { return a / b - ((a ^ b) < 0 && a
        % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = kInf; return 0; }
        if (x->a == y->a) x->p = x->b > y->b ? kInf : -kInf;
        else x->p = Div(y->b - x->b, x->a - y->a);
        return x->p >= y->p;
    }
    void addline(ll a, ll b) { // ax + b
        auto z = insert({a, b, 0}); y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y =
            erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        auto l = *lower_bound(x);
        return l.a * x + l.b;
    }
};

```

9.8 Min Plus Convolution [b34de3]

```

// a is convex a[i+1]-a[i] <= a[i+2]-a[i+1]
vector<int> min_plus_convolution(vector<int> &a, vector
    <int> &b) {
    int n = a.size(), m = b.size();
    vector<int> c(n + m - 1, INF);
    auto dc = [&](auto Y, int l, int r, int jl, int jr) {
        if (l > r) return;
        int mid = (l + r) / 2, from = -1, &best = c[mid];
        for (int j = jl; j <= jr; ++j)
            if (int i = mid - j; i >= 0 && i < n)
                if (best > a[i] + b[j])
                    best = a[i] + b[j], from = j;
    };
}

```

```

Y(Y, l, mid - 1, jl, from);
Y(Y, mid + 1, r, from, jr);
};
return dc(dc, 0, n - 1 + m - 1, 0, m - 1), c;
}

```

9.9 Matroid Intersection

Start from $S = \emptyset$. In each iteration, let

- $Y_1 = \{x \notin S \mid S \cup \{x\} \in I_1\}$
- $Y_2 = \{x \notin S \mid S \cup \{x\} \in I_2\}$

If there exists $x \in Y_1 \cap Y_2$, insert x into S . Otherwise for each $x \in S, y \notin S$, create edges

- $x \rightarrow y$ if $S - \{x\} \cup \{y\} \in I_1$.
- $y \rightarrow x$ if $S - \{x\} \cup \{y\} \in I_2$.

Find a *shortest* path (with BFS) starting from a vertex in Y_1 and ending at a vertex in Y_2 which doesn't pass through any other vertices in Y_2 , and alternate the path. The size of S will be incremented by 1 in each iteration. For the weighted case, assign weight $w(x)$ to vertex x if $x \in S$ and $-w(x)$ if $x \notin S$. Find the path with the minimum number of edges among all minimum length paths and alternate it.

9.10 Simulated Annealing

```

double factor = 100000;
const int base = 1e9; // remember to run ~ 10 times
for (int it = 1; it <= 100000; ++it) {
    // ans: answer, nw: current value, rnd(): mt19937 rnd
    ()
    if (exp(-(nw - ans) / factor) >= (double)rnd() %
        base) / base)
        ans = nw;
    factor *= 0.99995;
}

```

9.11 Bitset LCS

```

cin >> n >> m;
for (int i = 1; x; i <= n; ++i)
    cin >> x, p[x].set(i);
for (int i = 1; x; i <= m; i++) {
    cin >> x, (g = f) |= p[x];
    f.shiftLeftByOne(), f.set(0);
    ((f = g - f) ^= g) &= g;
}
cout << f.count() << '\n';

```

9.12 Binary Search On Fraction [765c5a]

```

struct Q {
    ll p, q;
    Q go(Q b, ll d) { return {p + b.p*d, q + b.q*d}; }
};
bool pred(Q);
// returns smallest p/q in [lo, hi] such that
// pred(p/q) is true, and 0 <= p, q <= N
Q frac_bs(ll N) {
    Q lo{0, 1}, hi{1, 0};
    if (pred(lo)) return lo;
    assert(pred(hi));
    bool dir = 1, L = 1, H = 1;
    for (; L || H; dir = !dir) {
        ll len = 0, step = 1;
        for (int t = 0; t < 2 && (t ? step/=2 : step*=2);)
            if (Q mid = hi.go(lo, len + step);
                mid.p > N || mid.q > N || dir ^ pred(mid))
                t++;
            else len += step;
        swap(lo, hi = hi.go(lo, len));
        (dir ? L : H) = !len;
    }
    return dir ? hi : lo;
}

```

9.13 Cyclic Ternary Search [9017cc]

```

/* bool pred(int a, int b);
f(0) ~ f(n - 1) is a cyclic-shift U-function
return idx s.t. pred(x, idx) is false forall x*/
int cyc_tsearch(int n, auto pred) {
    if (n == 1) return 0;
    int l = 0, r = n; bool rv = pred(1, 0);
    while (r - l > 1) {
        int m = (l + r) / 2;

```

```

    if (pred(0, m) ? rv: pred(m, (m + 1) % n)) r = m;
    else l = m;
}
return pred(l, r % n) ? l : r % n;
}

```

9.14 Tree Hash [34aae5]

```

ull seed;
ull shift(ull x) { x ^= x << 13; x ^= x >> 7;
  x ^= x << 17; return x; }
ull dfs(int u, int f) {
  ull sum = seed;
  for (int i : G[u]) if (i != f)
    sum += shift(dfs(i, u));
  return sum;
}

```

9.15 Python Misc

```

from [decimal, fractions, math, random] import *
arr = list(map(int, input().split())) # input
setcontext(Context(prec=10, Emax=MAX_EMAX, rounding=
  ROUND_FLOOR))
Decimal('1.1') / Decimal('0.2')
Fraction(3, 7)
Fraction(Decimal('1.14'))
Fraction('1.2').limit_denominator(4).numerator
Fraction(cos(pi / 3)).limit_denominator()
S = set(), S.add((a, b)), S.remove((a, b)) # set
if not (a, b) in S:
D = dict(), D[(a, b)] = 1, del D[(a, b)] # dict
for (a, b) in D.items():
arr = [randint(1, C) for i in range(N)]
choice([8, 6, 4, 1]) # random pick one

```