

## Introduction

This document gives coding conventions for the Python code comprising the standard library in the main Python distribution. Please see the companion informational PEP describing style guidelines for the C code in the C implementation of Python<sup>1</sup>.

This document was adapted from Guido's original Python Style Guide essay<sup>2</sup>, with some additions from Barry's style guide<sup>5</sup>. Where there's conflict, Guido's style rules for the purposes of this PEP. This PEP may still be incomplete (in fact, it may never be finished <wink>).

## A Foolish Consistency is the Hobgoblin of Little Minds

One of Guido's key insights is that code is read much more often than it is written. The guidelines provided here are intended to improve the readability of code and make it consistent across the wide spectrum of Python code. As [PEP 20](#)<sup>6</sup> says, "Readability counts".

A style guide is about consistency. Consistency with this style guide is important. Consistency within a project is more important. Consistency within one module or function is most important.

But most importantly: know when to be inconsistent -- sometimes the style guide just doesn't apply. When in doubt, use your best judgment. Look at other examples and decide what looks best. And don't hesitate to ask!

Two good reasons to break a particular rule:

- (1) When applying the rule would make the code less readable, even for someone who is used to reading code that follows the rules.
- (2) To be consistent with surrounding code that also breaks it (maybe for historic reasons) -- although this is also an opportunity to clean up someone else's mess (in true XP style).

## Code lay-out

### Indentation

Use 4 spaces per indentation level.

For really old code that you don't want to mess up, you can continue to use 8-space tabs.

### Tabs or Spaces?

Never mix tabs and spaces.

The most popular way of indenting Python is with spaces only. The second-most popular way is with tabs only. Code indented with a mixture of tabs and spaces should be converted to using spaces exclusively. When invoking the Python command line interpreter with the `-t` option, it issues warnings about code that illegally mixes tabs and spaces. When using `-tt` these warnings become errors. These options are highly recommended!

For new projects, spaces-only are strongly recommended over tabs. Most editors have features that make this easy to do.

## Maximum Line Length

Limit all lines to a maximum of 79 characters.

There are still many devices around that are limited to 80 character lines; plus, limiting windows to 80 characters makes it possible to have several windows side-by-side. The default wrapping on such devices disrupts the visual structure of the code, making it more difficult to understand. Therefore, please limit all lines to a maximum of 79 characters. For flowing long blocks of text (docstrings or comments), limiting the length to 72 characters is recommended.

The preferred way of wrapping long lines is by using Python's implied line continuation inside parentheses, brackets and braces. If necessary, you can add an extra pair of parentheses around an expression, but sometimes using a backslash looks better. Make sure to indent the continued line appropriately. The preferred place to break around a binary operator is *after* the operator, not before it. Some examples:

```
class Rectangle(Blob):

    def __init__(self, width, height,

                  color='black', emphasis=None, highlight=0):

        if width == 0 and height == 0 and \

            color == 'red' and emphasis == 'strong' or \

            highlight > 100:

            raise ValueError("sorry, you lose")

        if width == 0 and height == 0 and (color == 'red' or

                                           emphasis is None):

            raise ValueError("I don't think so -- values are %s, %s" %

                             (width, height))

        Blob.__init__(self, width, height,

                      color, emphasis, highlight)
```

## Blank Lines

Separate top-level function and class definitions with two blank lines.

Method definitions inside a class are separated by a single blank line.

Extra blank lines may be used (sparingly) to separate groups of related functions. Blank lines may be omitted between a bunch of related one-liners (e.g. a set of dummy implementations).

Use blank lines in functions, sparingly, to indicate logical sections.

Python accepts the control-L (i.e. `^L`) form feed character as whitespace; Many tools treat these characters as page separators, so you may use them to separate pages of related sections of your file.

## Encodings ([PEP 263](#))

Code in the core Python distribution should always use the ASCII or Latin-1 encoding (a.k.a. ISO-8859-1). For Python 3.0 and beyond, UTF-8 is preferred over Latin-1, see [PEP 3120](#).

Files using ASCII (or UTF-8, for Python 3.0) should not have a coding cookie. Latin-1 (or UTF-8) should only be used when a comment or docstring needs to mention an author name that requires Latin-1; otherwise, using `\x`, `\u` or `\U` escapes is the preferred way to include non-ASCII data in string literals.

For Python 3.0 and beyond, the following policy is prescribed for the standard library (see [PEP 3131](#)): All identifiers in the Python standard library MUST use ASCII-only identifiers, and SHOULD use English words wherever feasible (in many cases, abbreviations and technical terms are used which aren't English). In addition, string literals and comments must also be in ASCII. The only exceptions are (a) test cases testing the non-ASCII features, and (b) names of authors. Authors whose names are not based on the latin alphabet MUST provide a latin transliteration of their names.

Open source projects with a global audience are encouraged to adopt a similar policy.

## Imports

- Imports should usually be on separate lines, e.g.:

Yes:

```
| import os import sys
```

No:

```
| import sys, os
```

It's okay to say this though:

```
| from subprocess import Popen, PIPE
```

- Imports are always put at the top of the file, just after any module comments and docstrings, and before module globals and constants.

Imports should be grouped in the following order:

- standard library imports
- related third party imports
- local application/library specific imports

You should put a blank line between each group of imports.

Put any relevant `__all__` specification after the imports.

- Relative imports for intra-package imports are highly discouraged. Always use the absolute package path for all imports. Even now that [PEP 328](#)<sup>7</sup> is fully implemented in Python 2.5, its style of explicit relative imports is actively discouraged; absolute imports are more portable and usually more readable.
- When importing a class from a class-containing module, it's usually okay to spell this

```
| from myclass import MyClass from foo.bar.yourclass import YourClass
```

If this spelling causes local name clashes, then spell them

```
| import myclass import foo.bar.yourclass
```

and use "myclass.MyClass" and "foo.bar.yourclass.YourClass"

## Whitespace in Expressions and Statements

### Pet Peeves

Avoid extraneous whitespace in the following situations:

- Immediately inside parentheses, brackets or braces.

Yes:

```
| spam(ham[1], {eggs: 2})
```

No:

```
| spam( ham[ 1 ], { eggs: 2 } )
```

- Immediately before a comma, semicolon, or colon:

Yes:

```
| if x == 4: print x, y; x, y = y, x
```

No:

```
| if x == 4 : print x , y ; x , y = y , x
```

- Immediately before the open parenthesis that starts the argument list of a function call:

Yes:

```
| spam(1)
```

No:

```
| spam (1)
```

- Immediately before the open parenthesis that starts an indexing or slicing:

Yes:

```
| dict['key'] = list[index]
```

No:

```
| dict ['key'] = list [index]
```

- More than one space around an assignment (or other) operator to align it with another.

Yes:

```
x = 1

y = 2

long_variable = 3
```

No:

```
x          = 1

y          = 2

long_variable = 3
```

#### Other Recommendations

- Always surround these binary operators with a single space on either side: assignment (=), augmented assignment (+=, -= etc.), comparisons (==, <, >, !=, <>, <=, >=, in, not in, is, is not), Booleans (and, or, not).
- Use spaces around arithmetic operators:

Yes:

```
i = i + 1

submitted += 1

x = x * 2 - 1

hypot2 = x * x + y * y

c = (a + b) * (a - b)
```

No:

```
i=i+1

submitted +=1

x = x*2 - 1

hypot2 = x*x + y*y

c = (a+b) * (a-b)
```

- Don't use spaces around the '=' sign when used to indicate a keyword argument or a default parameter value.

Yes:

```
def complex(real, imag=0.0):  
    return magic(r=real, i=imag)
```

No:

```
def complex(real, imag = 0.0):  
    return magic(r = real, i = imag)
```

- Compound statements (multiple statements on the same line) are generally discouraged.

Yes:

```
if foo == 'blah':  
    do_blah_thing()  
  
do_one()  
  
do_two()  
  
do_three()
```

Rather not:

```
if foo == 'blah': do_blah_thing()  
  
do_one(); do_two(); do_three()
```

- While sometimes it's okay to put an if/for/while with a small body on the same line, never do this for multi-clause statements. Also avoid folding such long lines!

Rather not:

```
if foo == 'blah': do_blah_thing()  
  
for x in lst: total += x  
  
while t < 10: t = delay()
```

Definitely not:

```
if foo == 'blah': do_blah_thing()  
  
else: do_non_blah_thing()
```

```
try: something()

finally: cleanup()


do_one(); do_two(); do_three(long, argument,
                               list, like, this)


if foo == 'blah': one(); two(); three()
```

## Comments

Comments that contradict the code are worse than no comments. Always make a priority of keeping the comments up-to-date when the code changes!

Comments should be complete sentences. If a comment is a phrase or sentence, its first word should be capitalized, unless it is an identifier that begins with a lower case letter (never alter the case of identifiers!).

If a comment is short, the period at the end can be omitted. Block comments generally consist of one or more paragraphs built out of complete sentences, and each sentence should end in a period.

You should use two spaces after a sentence-ending period.

When writing English, Strunk and White apply.

Python coders from non-English speaking countries: please write your comments in English, unless you are 120% sure that the code will never be read by people who don't speak your language.

### Block Comments

Block comments generally apply to some (or all) code that follows them, and are indented to the same level as that code. Each line of a block comment starts with a # and a single space (unless it is indented text inside the comment).

Paragraphs inside a block comment are separated by a line containing a single #.

### Inline Comments

Use inline comments sparingly.

An inline comment is a comment on the same line as a statement. Inline comments should be separated by at least two spaces from the statement. They should start with a # and a single space.

Inline comments are unnecessary and in fact distracting if they state the obvious. Don't do this:

```
x = x + 1          # Increment x
```

But sometimes, this is useful:

```
x = x + 1 # Compensate for border
```

## Documentation Strings

Conventions for writing good documentation strings (a.k.a. "docstrings") are immortalized in [PEP 257](#)<sup>3</sup>.

- Write docstrings for all public modules, functions, classes, and methods. Docstrings are not necessary for non-public methods, but you should have a comment that describes what the method does. This comment should appear after the "def" line.
- [PEP 257](#) describes good docstring conventions. Note that most importantly, the `"""` that ends a multiline docstring should be on a line by itself, and preferably preceded by a blank line, e.g.:

```
"""Return a foobang

Optional plotz says to frobnicate the bizbaz first.

"""
```

- For one liner docstrings, it's okay to keep the closing `"""` on the same line.

## Version Bookkeeping

If you have to have Subversion, CVS, or RCS crud in your source file, do it as follows.

```
version__ = "$Revision: 68852 $"

# $Source$
```

These lines should be included after the module's docstring, before any other code, separated by a blank line above and below.

## Naming Conventions

The naming conventions of Python's library are a bit of a mess, so we'll never get this completely consistent – nevertheless, here are the currently recommended naming standards. New modules and packages (including third party frameworks) should be written to these standards, but where an existing library has a different style, internal consistency is preferred.



## Descriptive: Naming Styles

There are a lot of different naming styles. It helps to be able to recognize what naming style is being used, independently from what they are used for.

The following naming styles are commonly distinguished:

- `b` (single lowercase letter)
- `B` (single uppercase letter)
- `lowercase`
- `lower_case_with_underscores`
- `UPPERCASE`
- `UPPER_CASE_WITH_UNDERSCORES`
- `CapitalizedWords` (or `CapWords`, or `CamelCase` -- so named because of the bumpy look of its letters<sup>4</sup>). This is also sometimes known as `StudlyCaps`.

Note: When using abbreviations in `CapWords`, capitalize all the letters of the abbreviation. Thus `HTTPServerError` is better than `HttpServerError`.

- `mixedCase` (differs from `CapitalizedWords` by initial lowercase character!)
- `Capitalized_Words_With_Underscores` (ugly!)
- There's also the style of using a short unique prefix to group related names together. This is not used much in Python, but it is mentioned for completeness. For example, the `os.stat()` function returns a tuple whose items traditionally have names like `st_mode`, `st_size`, `st_mtime` and so on. (This is done to emphasize the correspondence with the fields of the POSIX system call struct, which helps programmers familiar with that.)

The X11 library uses a leading X for all its public functions. In Python, this style is generally deemed unnecessary because attribute and method names are prefixed with an object, and function names are prefixed with a module name.

In addition, the following special forms using leading or trailing underscores are recognized (these can generally be combined with any case convention):

- `_single_leading_underscore`: weak "internal use" indicator. E.g. `from M import *` does not import objects whose name starts with an underscore.
- `single_trailing_underscore_`: used by convention to avoid conflicts with Python keyword, e.g.

```
| Tkinter.Toplevel(master, class_='ClassName')
```

- `__double_leading_underscore`: when naming a class attribute, invokes name mangling (inside class `FooBar`, `__boo` becomes `_FooBar__boo`; see below).
- `__double_leading_and_trailing_underscore__`: "magic" objects or attributes that live in user-controlled namespaces. E.g. `__init__`, `__import__` or `__file__`. Never invent such names; only use them as documented.

## Prescriptive: Naming Conventions

## I. Names to Avoid

Never use the characters ``l`` (lowercase letter el), ``O`` (uppercase letter oh), or ``I`` (uppercase letter eye) as single character variable names.

In some fonts, these characters are indistinguishable from the numerals one and zero. When tempted to use ``l``, use ``L`` instead.

## II. Package and Module Names

Modules should have short, all-lowercase names. Underscores can be used in the module name if it improves readability. Python packages should also have short, all-lowercase names, although the use of underscores is discouraged.

Since module names are mapped to file names, and some file systems are case insensitive and truncate long names, it is important that module names be chosen to be fairly short – this won't be a problem on Unix, but it may be a problem when the code is transported to older Mac or Windows versions, or DOS.

When an extension module written in C or C++ has an accompanying Python module that provides a higher level (e.g. more object oriented) interface, the C/C++ module has a leading underscore (e.g. `_socket`).

## III. Class Names

Almost without exception, class names use the `CapWords` convention. Classes for internal use have a leading underscore in addition.

## IV. Exception Names

Because exceptions should be classes, the class naming convention applies here. However, you should use the suffix `"Error"` on your exception names (if the exception actually is an error).

## V. Global Variable Names

(Let's hope that these variables are meant for use inside one module only.) The conventions are about the same as those for functions.

Modules that are designed for use via `"from M import *"` should use the `__all__` mechanism to prevent exporting globals, or use the older convention of prefixing such globals with an underscore (which you might want to do to indicate these globals are "module non-public").

## VI. Function Names

Function names should be lowercase, with words separated by underscores as necessary to improve readability.

`mixedCase` is allowed only in contexts where that's already the prevailing style (e.g. `threading.py`), to retain backwards compatibility.

## VII. Function and method arguments

Always use `'self'` for the first argument to instance methods.

Always use `'cls'` for the first argument to class methods.

If a function argument's name clashes with a reserved keyword, it is generally better to append a single trailing underscore rather than use an abbreviation or spelling corruption. Thus `"print_"` is better than `"prnt"`. (Perhaps better is to avoid such clashes by using a synonym.)

## VIII. Method Names and Instance Variables

Use the function naming rules: lowercase with words separated by underscores as necessary to

improve readability.

Use one leading underscore only for non-public methods and instance variables.

To avoid name clashes with subclasses, use two leading underscores to invoke Python's name mangling rules.

Python mangles these names with the class name: if class `Foo` has an attribute named `__a`, it cannot be accessed by `Foo.__a`. (An insistent user could still gain access by calling `Foo._Foo__a`.) Generally, double leading underscores should be used only to avoid name conflicts with attributes in classes designed to be subclassed.

Note: there is some controversy about the use of `__` names (see below).

## IX. Constants

Constants are usually declared on a module level and written in allcapital letters with underscores separating words. Examples include `MAX_OVERFLOW` and `TOTAL`.

## X. Designing for inheritance

Always decide whether a class's methods and instance variables (collectively: "attributes") should be public or non-public. If in doubt, choose non-public; it's easier to make it public later than to make a public attribute non-public.

Public attributes are those that you expect unrelated clients of your class to use, with your commitment to avoid backward incompatible changes. Non-public attributes are those that are not intended to be used by third parties; you make no guarantees that non-public attributes won't change or even be removed.

We don't use the term "private" here, since no attribute is really private in Python (without a generally unnecessary amount of work).

Another category of attributes are those that are part of the "subclass API" (often called "protected" in other languages). Some classes are designed to be inherited from, either to extend or modify aspects of the class's behavior. When designing such a class, take care to make explicit decisions about which attributes are public, which are part of the subclass API, and which are truly only to be used by your base class.

With this in mind, here are the Pythonic guidelines:

- Public attributes should have no leading underscores.
- If your public attribute name collides with a reserved keyword, append a single trailing underscore to your attribute name. This is preferable to an abbreviation or corrupted spelling. (However, notwithstanding this rule, 'cls' is the preferred spelling for any variable or argument which is known to be a class, especially the first argument to a class method.)
  - Note 1: See the argument name recommendation above for class methods.
- For simple public data attributes, it is best to expose just the attribute name, without complicated accessor/mutator methods. Keep in mind that Python provides an easy path to future enhancement, should you find that a simple data attribute needs to grow functional behavior. In that case, use properties to hide functional implementation behind simple data attribute access syntax.
  - Note 1: Properties only work on new-style classes.
  - Note 2: Try to keep the functional behavior side-effect free, although side-effects such as caching are generally fine.
  - Note 3: Avoid using properties for computationally expensive operations; the attribute notation makes the caller believe that access is (relatively) cheap.

- If your class is intended to be subclassed, and you have attributes that you do not want subclasses to use, consider naming them with double leading underscores and no trailing underscores. This invokes Python's name mangling algorithm, where the name of the class is mangled into the attribute name. This helps avoid attribute name collisions should subclasses inadvertently contain attributes with the same name.
  - Note 1: Note that only the simple class name is used in the mangled name, so if a subclass chooses both the same class name and attribute name, you can still get name collisions.
  - Note 2: Name mangling can make certain uses, such as debugging and `__getattr__()`, less convenient. However the name mangling algorithm is well documented and easy to perform manually.
  - Note 3: Not everyone likes name mangling. Try to balance the need to avoid accidental name clashes with potential use by advanced callers.

## Programming Recommendations

- Code should be written in a way that does not disadvantage other implementations of Python (PyPy, Jython, IronPython, Pyrex, Psyco, and such).

For example, do not rely on CPython's efficient implementation of in-place string concatenation for statements in the form `a+=b` or `a=a+b`. Those statements run more slowly in Jython. In performance sensitive parts of the library, the `' '.join()` form should be used instead. This will ensure that concatenation occurs in linear time across various implementations.

- Comparisons to singletons like `None` should always be done with `'is'` or `'is not'`, never the equality operators.

Also, beware of writing `"if x"` when you really mean `"if x is not None"` – e.g. when testing whether a variable or argument that defaults to `None` was set to some other value. The other value might have a type (such as a container) that could be false in a boolean context!

- Use class-based exceptions.

String exceptions in new code are forbidden, because this language feature is being removed in Python 2.6.

Modules or packages should define their own domain-specific base exception class, which should be subclassed from the built-in `Exception` class. Always include a class docstring. E.g.:

```
class MessageError(Exception):
    """Base class for errors in the email package."""
```

Class naming conventions apply here, although you should add the suffix `"Error"` to your exception classes, if the exception is an error. Non-error exceptions need no special suffix.

- When raising an exception, use `"raise ValueError('message')"` instead of the older form `"raise ValueError, 'message'"`.

The paren-using form is preferred because when the exception arguments are long or include string formatting, you don't need to use line continuation characters thanks to the containing parentheses. The older form will be removed in Python 3000.

- When catching exceptions, mention specific exceptions whenever possible instead of using a bare `'except:'` clause.

For example, use:

```
try:

    import platform_specific_module

except ImportError:

    platform_specific_module = None
```

A bare `except:` clause will catch `SystemExit` and `KeyboardInterrupt` exceptions, making it harder to interrupt a program with Control-C, and can disguise other problems. If you want to catch all exceptions that signal program errors, use `except Exception:`.

- A good rule of thumb is to limit use of bare `except` clauses to two cases:
  - 1) If the exception handler will be printing out or logging the traceback; at least the user will be aware that an error has occurred.
  - 2) If the code needs to do some cleanup work, but then lets the exception propagate upwards with `raise`. `try...finally` is a better way to handle this case.
- Additionally, for all `try/except` clauses, limit the `try` clause to the absolute minimum amount of code necessary. Again, this avoids masking bugs.

Yes:

```
try:

    value = collection[key]

except KeyError:

    return key_not_found(key)

else:

    return handle_value(value)
```

No:

```
try:

    # Too broad!

    return handle_value(collection[key])

except KeyError:

    # Will also catch KeyError raised by handle_value()

    return key_not_found(key)
```

- Use string methods instead of the `string` module.

String methods are always much faster and share the same API with `unicode` strings. Override this rule if backward compatibility with `Pythons` older than 2.0 is required.

- Use `''.startswith()` and `''.endswith()` instead of string slicing to check for prefixes or suffixes. `startswith()` and `endswith()` are cleaner and less error prone. For example:

Yes:

```
|     if foo.startswith('bar'):
```

No:

```
|     if foo[:3] == 'bar':
```

The exception is if your code must work with Python 1.5.2 (but let's hope not!).

- Object type comparisons should always use `isinstance()` instead of comparing types directly.

Yes:

```
|     if isinstance(obj, int):
```

No:

```
|     if type(obj) is type(1):
```

When checking if an object is a string, keep in mind that it might be a `unicode` string too! In Python 2.3, `str` and `unicode` have a common base class, `basestring`, so you can do:

```
|     if isinstance(obj, basestring):
```

In Python 2.2, the `types` module has the `StringTypes` type defined for that purpose, e.g.:

```
|     from types import StringTypes
|
|     if isinstance(obj, StringTypes):
```

In Python 2.0 and 2.1, you should do:

```
|     from types import StringType, UnicodeType
|
|     if isinstance(obj, StringType) or \
|
|     isinstance(obj, UnicodeType) :
```

- For sequences, (strings, lists, tuples), use the fact that empty sequences are false.

Yes:

```
|     if not seq:
|
|     if seq:
```

No:

```
|   if len(seq):  
|  
|   if not len(seq):
```

- Don't write string literals that rely on significant trailing whitespace. Such trailing whitespace is visually indistinguishable and some editors (or more recently, `reindent.py`) will trim them.
- Don't compare boolean values to `True` or `False` using `==`

Yes:

```
|   if greeting:
```

No:

```
|   if greeting == True:
```

Worse:

```
|   if greeting is True:
```

## References

- [1] [PEP 7](#), Style Guide for C Code, van Rossum
- [2] <http://www.python.org/doc/essays/styleguide.html>
- [3] [PEP 257](#), Docstring Conventions, Goodger, van Rossum
- [4] <http://www.wikipedia.com/wiki/CamelCase>
- [5] Barry's GNU Mailman style guide <http://barry.warsaw.us/software/STYLEGUIDE.txt>
- [6] [PEP 20](#), The Zen of Python
- [7] [PEP 328](#), Imports: Multi-Line and Absolute/Relative

## Copyright

This document has been placed in the public domain.

Authors: Guido van Rossum <guido at python.org>, Barry Warsaw <barry at python.org> .

Formatting done by Andrew Chernin from version 68852 of PEP 8 – Style Guide for Python Code.