
# Enter a NEU era with SHERA









# ABOUT THE COMPANY



3500+

Distributors Worldwide



2000+

Team Members from Diverse Countries



5

Decades of Groundbreaking Innovation in Building Materials



40+

Countries Presence (Global Presence)



3+

Warehouses in India



20+

Years of India's Premium Fiber Cement Brand

# THE GREEN CONCEPT



**Sustainability First**: Eco-friendly practices from sourcing to disposal.

**Zero Waste & Low Carbon Emissions**: Energy-efficient production with minimal environmental impact.

**100% Asbestos-Free**: Safe and sustainable building solutions.

**Innovative Alternatives**: Fibre cement products designed as eco-friendly substitutes for real wood.

**Globally Recognized**: Trusted for unique, sustainable building materials.

# ABOUT SHERA NEU BOARDS

Engineered with advanced FyberTec Technology, SHERA NEU Fibre Cement boards offer superior strength, durability, and creative freedom. Their minimal paint requirement enhances cost-effectiveness, making them a smart alternative to conventional sheet materials. A single, high-performance solution for wall paneling, flooring, partitions, ceilings, and underlays. SHERA NEU delivers reliability and efficiency for every project.



#### **SHERA NEU Advantages**



No cracks and less damages during Transportation.

No cracks and chip-offs during installation.



Unique Paint-Saving Technology minimizes paint usage and leads to significant cost savings.

Innovative Fybertec Technology, delivers both strength and enhanced workability.





## **SHERA NEU Product Size & Weight**

Size	Weight
6mm x 1220mm x 2440mm	28.10 kg.
8mm x 1220mm x 2440mm	37.46 kg.
10mm x 1220mm x 2440mm	46.83kg.

Size	Weight
12mm x 1220mm x 2440mm	56.19kg.
15mm x 1220mm x 2440mm	70.24 kg.
18mm x 1220mm x 2440mm	84.29 kg.

### **SHERA NEU Applications**



**WALL PANELING** 



**MEZZANINE FLOORING** 



WALL PARTITIONS



**FALSE CEILING** 



UNDERLAYMENT

### **SHERA NEU Technical Specifications**

SR NO	PROPERTIES	VALUE
01	Test standard	IS 14862: 2000
02	Category	Type A sheet (Category 3)
03	Thickness Tolerance	pass
04	Density	$1350 \pm 50 \text{ kg/m}$
05	Modulus of Rupture / Flexural Strength	>10 N/mm2 (EMC)
06	Moisture Content	< 5 %
07	Water Absorption	< 30 %
08	Water impermeability / tightness	pass
09	Thermal Conductivity	0.156 W/m°K



### **Mahaphant India Private Limited**

WeWork Raheja Platinum, 2<sup>nd</sup> Floor, Off Andheri-Kurla Road, Marol, Andheri East, Mumbai -400059.

Follow us on SHERA INDIA 6 in 6 • shera.com







