
RSLogix Micro Project Report



Processor Information

Processor Type: Bul.1763 MicroLogix 1100 Series B

Processor Name: UNTITLED

Total Memory Used: 275 Instruction Words Used - 84 Data Table Words Used

Total Memory Left: 6381 Instruction Words Left

Program Files: 7

Data Files: 9

Program ID: 9df2

I/O Configuration

0	Bul.1763	MicroLogix 1100 Series B
1		
2		
3		
4		

Channel Configuration

CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Edit Resource/Owner Timeout: 60
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Passthru Link ID: 1
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Write Protected: No
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Comms Servicing Selection: Yes
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex Message Servicing Selection: Yes
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex 1st AWA Append Character: \d
CHANNEL 0 (SYSTEM) - Driver: DF1 Full Duplex 2nd AWA Append Character: \a

Source ID: 1 (decimal)
Baud: 19200
Parity: NONE
Control Line : No Handshaking
Error Detection: CRC
Embedded Responses: Auto Detect
Duplicate Packet Detect: Yes
ACK Timeout(x20 ms): 50
NAK Retries: 3
ENQ Retries: 3

CHANNEL 1 (SYSTEM) - Driver: Ethernet
CHANNEL 1 (SYSTEM) - Driver: Ethernet Edit Resource/Owner Timeout: 60
CHANNEL 1 (SYSTEM) - Driver: Ethernet Passthru Link ID: 1
CHANNEL 1 (SYSTEM) - Driver: Ethernet Write Protected: No
CHANNEL 1 (SYSTEM) - Driver: Ethernet Comms Servicing Selection: Yes
CHANNEL 1 (SYSTEM) - Driver: Ethernet Message Servicing Selection: Yes

Hardware Address: 00:00:00:00:00:00
IP Address: 0.0.0.0
Subnet Mask: 0.0.0.0
Gateway Address: 0.0.0.0
Msg Connection Timeout (x 1mS): 15000
Msg Reply Timeout (x mS): 3000
Inactivity Timeout (x Min): 30
Bootp Enable: Yes
Dhcp Enable No
SNMP Enable: No
HTTP Enable: Yes
Auto Negotiate Enable: Yes
Port Speed Enable: 10/100 Mbps Full Duplex/Half Duplex
Contact:
Location:


Program File List

Name	Number	Type	Rungs	Debug	Bytes
[SYSTEM]	0	SYS	0	No	0
	1	SYS	0	No	0
MAIN	2	LADDER	5	No	39
IO	3	LADDER	3	No	35
CTRLCYC1	4	LADDER	4	No	115
CTRLCYC2	5	LADDER	14	No	651
RECONFIG	6	LADDER	2	No	189


Data File List

Name	Number	Type	Scope	Debug	Words	Elements	Last
OUTPUT	0	O	Global	No	12	4	O:3
INPUT	1	I	Global	No	18	6	I:5
STATUS	2	S	Global	No	0	66	S:65
BINARY	3	B	Global	No	2	2	B3:1
TIMER	4	T	Global	No	12	4	T4:3
COUNTER	5	C	Global	No	6	2	C5:1
CONTROL	6	R	Global	No	3	1	R6:0
INTEGER	7	N	Global	No	13	13	N7:12
FLOAT	8	F	Global	No	18	9	F8:8


LAD 2 - MAIN --- Total Rungs in File = 5





LAD 3 - IO --- Total Rungs in File = 3





LAD 4 - CTRLCYC1 --- Total Rungs in File = 4




0000
2nd Cycle Start/Stop btn
B3:0
0
2nd Cycle Starter one shot
B3:0
ONS
7
2nd cycle trigger
B3:0
8
0001
2nd cycle trigger
B3:0
8
2nd Cycle Running
B3:0
9
2nd Cycle Running
B3:0
9
2nd Cycle Start/Stop btn
B3:0
0
0002
2nd Cycle Running
B3:0
9
2nd cycle running one shot
B3:0
ONS
14
0% valve trigger
B3:0
10
0003
0% valve trigger
B3:0
10
0% valve openned
B3:0
11
0% valve openned
B3:0
11
0% valve interrupt
T4:0
DN
0% valve openning timer
TON
Timer On Delay
Timer T4:0
Time Base 1.0
Preset 30<
Accum 0<
EN
DN
0004
0% valve interrupt
T4:0
DN
30% valve trigger
B3:0
12
0005
30% valve trigger
B3:0
12
30% valve openned
B3:0
13
30% valve openned
B3:0
13
30% valve interrput
T4:1
DN
30% valve openning timer
TON
Timer On Delay
Timer T4:1
Time Base 1.0
Preset 30<
Accum 0<
EN
DN
0006
0% valve openned
B3:0
11
Sample Timer 0%
TON
Timer On Delay
Timer T4:2
Time Base 1.0
Preset 1<
Accum 0<
EN
DN


0007
Sampling Trigger 0%
T4:2
TT
Sample Counter
Trigger one shot 0%
B3:1
ONS
1
Measured O2
concentration
SCP
Scale w/Parameters
Input N7:0 0<
Input Min. N7:2 0<
Input Max. N7:3 16383<
Scaled Min. 0 0<
Scaled Max. 40 40<
Output N7:1 0<
0008
Sampled Counter
Trigger 0%
T4:2
DN
Sample counter 0%
CTU
Count Up
Counter C5:0
Preset 9999<
Accum 0<
CU
DN
0% Calibration
Summtion values
ADD
Add
Source A N7:0 0<
Source B F8:4 13900.0<
Dest F8:4 13900.0<
Sample Timer 0%
T4:2
RES
0009
30% valve openned
B3:0
13
sample Timer 30%
TON
Timer On Delay
Timer T4:3
Time Base 1.0
Preset 1<
Accum 0<
EN
DN


0010
Sampling Trigger 30%
T4:3
TT
Sample Counter
Trigger one shot 30%
B3:1
ONS
0
Measured O2
concentration
SCP
Scale w/Parameters
Input N7:0 0<
Input Min. N7:2 0<
Input Max. N7:3 16383<
Scaled Min. 0 0<
Scaled Max. 40 40<
Output N7:1 0<
0011
Sample Counter
Trigger 30%
T4:3
DN
Sample Counter 30%
CTU
Count Up
Counter C5:1
Preset 9999<
Accum 0<
CU
DN
30% Calibration
Summtion values
ADD
Add
Source A N7:0 0<
Source B F8:5 330000.0<
Dest F8:5 330000.0<
sample Timer 30%
T4:3
RES


0012
0% valve opennd
B3:0
11
30% valve openned
B3:0
13
2nd Cycle Running
B3:0
9
Samples Count 0%
MOV
Move
Source C5:0.ACC
0<
Dest N7:10
0<
Samples Count 30%
MOV
Move
Source C5:1.ACC
0<
Dest N7:11
0<
0% Calibration AVG value
DIV
Divide
Source A F8:4
13900.0<
Source B N7:10
0<
Dest F8:6
463.3333<
30% Calibration AVG value
DIV
Divide
Source A F8:5
330000.0<
Source B N7:11
0<
Dest F8:7
11000.0<
Subtract of AVG of 30% -0%
SUB
Subtract
Source A F8:7
11000.0<
Source B F8:6
463.3333<
Dest F8:8
10536.67<

Mul of (40%/30%) *
Subtract of AVG of
30% , 0%

MUL
Multiply
Source A F8:0
1.3333<
Source B F8:8
10536.67<
Dest F8:1
14048.54<

O2 input max

ADD
Add
Source A F8:1
14048.54<
Source B F8:6
463.3333<
Dest N7:3
16383<

O2 input min

MOV
Move
Source F8:6
463.3333<
Dest N7:2
0<

Measured O2
concentration

SCP
Scale w/Parameters
Input N7:0
0<
Input Min. N7:2
0<
Input Max. N7:3
16383<
Scaled Min. 0
0<
Scaled Max. 40
40<
Output N7:1
0<

0013 END


0000
1st Cycle Start/Stop btn
B3:0
3
2nd Cycle Start/Stop btn
B3:0
0
Measured O2 concentration
MOV
Move
Source 0
0<
Dest N7:1
0<
0% Calibration Summtion values
MOV
Move
Source 0
0<
Dest N7:4
0<
30% Calibration Summtion values
MOV
Move
Source 0
0<
Dest N7:5
0<
0% Calibration AVG value
MOV
Move
Source 0
0<
Dest N7:6
0<
30% Calibration AVG value
MOV
Move
Source 0
0<
Dest N7:7
0<
Subtract of AVG of 30% -0%
MOV
Move
Source 0
0<
Dest N7:8
0<

MUL of Subtract of
AVG and (I max /min)

MOV
Move
Source 0
0<
Dest N7:9
0<

Samples Count 0%

MOV
Move
Source 0
0<
Dest N7:10
0<

Samples Count 30%

MOV
Move
Source 0
0<
Dest N7:11
0<

Imax - Imin

MOV
Move
Source 0
0<
Dest N7:12
0<

Sample counter 0%
C5:0
RES

Sample Counter 30%
C5:1
RES

0001 END

Data File O0 (bin) -- OUTPUT

Offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
O:0.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
O:0.1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
O:0.2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
O:0.3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B

Data File I1 (bin) -- INPUT

Offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0		
I:0.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
I:0.1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
I:0.2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
I:0.3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B
I:0.4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B-Analog
I:0.5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Bul.1763	MicroLogix 1100 Series B-Analog

Main

Processor Mode S:1/0 - S:1/4 = Remote Program Mode
On Power up Go To Run (Mode Behavior) S:1/12 = 0
First Pass S:1/15 = No
Free Running Clock S:4 = 0000-0000-0000-0000

Proc

OS Catalog Number S:57 = 1100
OS Series S:58 = A
OS FRS S:59 =
Processor Catalog Number S:60 =
Processor Series S:61 = A
Processor FRN S:62 =
User Program Type S:63 = 8001h
Compiler Revision Number S:64 =

Scan Times

Maximum (x10 ms) S:22 = 0
Watchdog (x10 ms) S:3 (high byte) = 10
Last 100 uSec Scan Time S:35 = 0
Scan Toggle Bit S:33/9 = 0

Math

Math Overflow Selected S:2/14 = 0
Overflow Trap S:5/0 = 0
Carry S:0/0 = 0
Overflow S:0/1 = 0
Zero Bit S:0/2 = 0
Sign Bit S:0/3 = 0
Math Register (lo word) S:13 = 0
Math Register (high word) S:14-S:13 = 0
Math Register (32 Bit) S:14-S:13 = 0

Chan 0

Processor Mode S:1/0- S:1/4 = Remote Program Mode
Node Address S:15 (low byte) = 0
Baud Rate S:15 (high byte) = ?
Channel Mode S:33/3 = 0
Comms Active S:33/4 = 0
Incoming Cmd Pending S:33/0 = 0
Msg Reply Pending S:33/1 = 0
Outgoing Msg Cmd Pending S:33/2 = 0

Debug

Suspend Code S:7 = 0
Suspend File S:8 = 0

Errors

Fault Override At Power Up S:1/8 = 0
Startup Protection Fault S:1/9 = 0
Major Error Halt S:1/13 = 0
Overflow Trap S:5/0 = 0
Control Register Error S:5/2 = 0
Major Error Executing User Fault Rtn. S:5/3 = 0
Battery Low S:5/11 = 0
Input Filter Selection Modified S:5/13 = 0
ASCII String Manipulation error S:5/15 = 0
Fault Routine S:29 = 0
Major Error S:6 = 0h
Error Description:

Protection

Deny Future Access S:1/14 = No
Data File Overwrite Protection Lost S:36/10 = False

Mem Module

Memory Module Loaded On Boot S:5/8 = 0
Password Mismatch S:5/9 = 0
Load Memory Module On Memory Error S:1/10 = 0
Load Memory Module Always S:1/11 = 0
On Power up Go To Run (Mode Behavior) S:1/12 = 0
Program Compare S:2/9 = 0
Data File Overwrite Protection Lost S:36/10 = 0

Forces

Forces Enabled S:1/5 = Yes
Forces Installed S:1/6 = No

Data File B3 (bin) -- BINARY

Offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	(Symbol) Description
B3:0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
B3:1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	

Data File T4 -- TIMER

Offset	EN	TT	DN	BASE	PRE	ACC	(Symbol) Description
T4:0	0	0	0	1.0 sec	30	0	0% valve openning timer
T4:1	0	0	0	1.0 sec	30	0	30% valve openning timer
T4:2	0	0	0	1.0 sec	1	0	Sample Timer 0%
T4:3	0	0	0	1.0 sec	1	0	sample Timer 30%

Data File C5 -- COUNTER

Offset	CU	CD	DN	OV	UN	UA	PRE	ACC	(Symbol) Description
C5:0	0	0	0	0	0	0	9999	0	Sample counter 0%
C5:1	0	0	0	0	0	0	9999	0	Sample Counter 30%

Data File R6 -- CONTROL

Offset	EN	EU	DN	EM	ER	UL	IN	FD	LEN	POS	(Symbol)	Description
R6:0	0	0	0	0	0	0	0	0	0	0		

SENSOR CALIBRATION

Data File N7 (dec) -- INTEGER

Offset	0	1	2	3	4	5	6	7	8	9
N7:0	0	0	0	16383	0	0	0	0	0	0
N7:10	0	0	0							

SENSOR CALIBRATION

Data File F8 -- FLOAT

Offset	0	1	2	3	4
F8:0	1.3333	14048.54	0	0	13900
F8:5	330000	463.3333	11000	10536.67	

Address/Symbol Database

Address	Symbol	Scope	Description	Sym Group	Dev. Code	ABV	BLW
B3:0/0			2nd Cycle Start/Stop btn				
B3:0/1			0% gas valve bit				
B3:0/2			30% gas valve bit				
B3:0/3			1st Cycle Start/Stop btn				
B3:0/4			1st Cycle Starter one shot				
B3:0/5			1st Cycle Trigger				
B3:0/6			1st Cycle Running				
B3:0/7			2nd Cycle Starter one shot				
B3:0/8			2nd cycle trigger				
B3:0/9			2nd Cycle Running				
B3:0/10			0% valve trigger				
B3:0/11			0% valve opennd				
B3:0/12			30% valve trigger				
B3:0/13			30% valve openned				
B3:0/14			2nd cycle running one shot				
B3:0/15			2nd cycle inturrpt				
B3:1/0			Sample Counter Trigger one shot 30%				
B3:1/1			Sample Counter Trigger one shot 0%				
C5:0			Sample counter 0%				
C5:0.ACC			Samples Count 0%				
C5:1			Sample Counter 30%				
C5:1.ACC			Samples Count 30%				
F8:0			40% / 30%				
F8:1			Mul of (40%/30%) * Subtract of AVG of 30% , 0%				
F8:4			0% Calibration Summtion values				
F8:5			30% Calibration Summtion values				
F8:6			0% Calibration AVG value				
F8:7			30% Calibration AVG value				
F8:8			Subtract of AVG of 30% -0%				
N7:0			O2 sensor input signal				
N7:1			Measured O2 concentration				
N7:2			O2 input min				
N7:3			O2 input max				
N7:4			0% Calibration Summtion values				
N7:5			30% Calibration Summtion values				
N7:6			0% Calibration AVG value				
N7:7			30% Calibration AVG value				
N7:8			Subtract of AVG of 30% -0%				
N7:9			MUL of Subtract of AVG and (I max /min)				
N7:10			Samples Count 0%				
N7:11			Samples Count 30%				
N7:12			Imax - Imin				
N7:13			Imax				
O:0/0			0% gas valve				
O:0/1			30% gas valve				
S:0			Arithmetic Flags				
S:0/0			Processor Arithmetic Carry Flag				
S:0/1			Processor Arithmetic Underflow/ Overflow Flag				
S:0/2			Processor Arithmetic Zero Flag				
S:0/3			Processor Arithmetic Sign Flag				
S:1			Processor Mode Status/ Control				
S:1/0			Processor Mode Bit 0				
S:1/1			Processor Mode Bit 1				
S:1/2			Processor Mode Bit 2				
S:1/3			Processor Mode Bit 3				
S:1/4			Processor Mode Bit 4				
S:1/5			Forces Enabled				
S:1/6			Forces Present				
S:1/7			Comms Active				
S:1/8			Fault Override at Powerup				
S:1/9			Startup Protection Fault				
S:1/10			Load Memory Module on Memory Error				
S:1/11			Load Memory Module Always				
S:1/12			Load Memory Module and RUN				
S:1/13			Major Error Halted				
S:1/14			Access Denied				
S:1/15			First Pass				
S:2/0			STI Pending				
S:2/1			STI Enabled				
S:2/2			STI Executing				
S:2/3			Index Addressing File Range				
S:2/4			Saved with Debug Single Step				
S:2/5			DH-485 Incoming Command Pending				
S:2/6			DH-485 Message Reply Pending				
S:2/7			DH-485 Outgoing Message Command Pending				
S:2/15			Comms Servicing Selection				
S:3			Current Scan Time/ Watchdog Scan Time				
S:4			Time Base				
S:5/0			Overflow Trap				
S:5/2			Control Register Error				
S:5/3			Major Err Detected Executing UserFault Routine				
S:5/4			M0-M1 Referenced on Disabled Slot				
S:5/8			Memory Module Boot				
S:5/9			Memory Module Password Mismatch				

Address/Symbol Database

Address	Symbol	Scope	Description	Sym Group	Dev. Code	ABV	BLW
S:5/10			STI Overflow				
S:5/11			Battery Low				
S:6			Major Error Fault Code				
S:7			Suspend Code				
S:8			Suspend File				
S:9			Active Nodes				
S:10			Active Nodes				
S:11			I/O Slot Enables				
S:12			I/O Slot Enables				
S:13			Math Register				
S:14			Math Register				
S:15			Node Address/ Baud Rate				
S:16			Debug Single Step Rung				
S:17			Debug Single Step File				
S:18			Debug Single Step Breakpoint Rung				
S:19			Debug Single Step Breakpoint File				
S:20			Debug Fault/ Powerdown Rung				
S:21			Debug Fault/ Powerdown File				
S:22			Maximum Observed Scan Time				
S:23			Average Scan Time				
S:24			Index Register				
S:25			I/O Interrupt Pending				
S:26			I/O Interrupt Pending				
S:27			I/O Interrupt Enabled				
S:28			I/O Interrupt Enabled				
S:29			User Fault Routine File Number				
S:30			STI Setpoint				
S:31			STI File Number				
S:32			I/O Interrupt Executing				
S:33			Extended Proc Status Control Word				
S:33/0			Incoming Command Pending				
S:33/1			Message Reply Pending				
S:33/2			Outgoing Message Command Pending				
S:33/3			Selection Status User/DF1				
S:33/4			Communicat Active				
S:33/5			Communicat Servicing Selection				
S:33/6			Message Servicing Selection Channel 0				
S:33/7			Message Servicing Selection Channel 1				
S:33/8			Interrupt Latency Control Flag				
S:33/9			Scan Toggle Flag				
S:33/10			Discrete Input Interrupt Reconfigur Flag				
S:33/11			Online Edit Status				
S:33/12			Online Edit Status				
S:33/13			Scan Time Timebase Selection				
S:33/14			DTR Control Bit				
S:33/15			DTR Force Bit				
S:34			Pass-thru Disabled				
S:34/0			Pass-Thru Disabled Flag				
S:34/1			DH+ Active Node Table Enable Flag				
S:34/2			Floating Point Math Flag Disable,Fl				
S:35			Last 1 ms Scan Time				
S:36			Extended Minor Error Bits				
S:36/8			DII Lost				
S:36/9			STI Lost				
S:36/10			Memory Module Data File Overwrite Protection				
S:37			Clock Calendar Year				
S:38			Clock Calendar Month				
S:39			Clock Calendar Day				
S:40			Clock Calendar Hours				
S:41			Clock Calendar Minutes				
S:42			Clock Calendar Seconds				
S:43			STI Interrupt Time				
S:44			I/O Event Interrupt Time				
S:45			DII Interrupt Time				
S:46			Discrete Input Interrupt- File Number				
S:47			Discrete Input Interrupt- Slot Number				
S:48			Discrete Input Interrupt- Bit Mask				
S:49			Discrete Input Interrupt- Compare Value				
S:50			Processor Catalog Number				
S:51			Discrete Input Interrupt- Return Number				
S:52			Discrete Input Interrupt- Accumulat				
S:53			Reserved/ Clock Calendar Day of the Week				
S:55			Last DII Scan Time				
S:56			Maximum Observed DII Scan Time				
S:57			Operating System Catalog Number				
S:58			Operating System Series				
S:59			Operating System FRN				
S:61			Processor Series				
S:62			Processor Revision				
S:63			User Program Type				
S:64			User Program Functional Index				
S:65			User RAM Size				
S:66			Flash EEPROM Size				
S:67			Channel 0 Active Nodes				

Address/Symbol Database

Address	Symbol	Scope	Description	Sym Group	Dev. Code	ABV	BLW
S:68			Channel 0 Active Nodes				
S:69			Channel 0 Active Nodes				
S:70			Channel 0 Active Nodes				
S:71			Channel 0 Active Nodes				
S:72			Channel 0 Active Nodes				
S:73			Channel 0 Active Nodes				
S:74			Channel 0 Active Nodes				
S:75			Channel 0 Active Nodes				
S:76			Channel 0 Active Nodes				
S:77			Channel 0 Active Nodes				
S:78			Channel 0 Active Nodes				
S:79			Channel 0 Active Nodes				
S:80			Channel 0 Active Nodes				
S:81			Channel 0 Active Nodes				
S:82			Channel 0 Active Nodes				
S:83			DH+ Active Nodes				
S:84			DH+ Active Nodes				
S:85			DH+ Active Nodes				
S:86			DH+ Active Nodes				
T4:0			0% valve openning timer				
T4:0/DN			0% valve interrupt				
T4:1			30% valve openning timer				
T4:1/DN			30% valve interrput				
T4:2			Sample Timer 0%				
T4:2/DN			Sampled Counter Trigger 0%				
T4:2/TT			Sampling Trigger 0%				
T4:3			sample Timer 30%				
T4:3/DN			Sample Counter Trigger 30%				
T4:3/TT			Sampling Trigger 30%				
U:3			Input & Output				
U:4			Cycle #1 Controls				
U:5			Cycle #2 Controls				
U:6			Reset all nessesry variables				

Instruction Comment Database

Address	Instruction	Description

Symbol Group Database

Group_Name	Description