Use Case 1

Use case name: Request Blood
ID: UC-1
Priority: High

Actor: Patient

Description:
This use case allows a patient to request blood from nearby donors or blood banks.

Trigger:
The user needs blood and opens the request feature.

Type: External

Preconditions:

1. The user must be logged in
2. The user must complete profile information
3. The user must know required blood type

Normal Course:

1. The user opens the “Request Blood” screen
2. The user selects blood type
3. The user enters hospital/location
4. The user selects urgency level
5. The user submits the request
6. The system notifies nearby donors

Information for Steps:

- Blood type selection
- Location services

- Form validation

Alternative Courses:

1. If the user is not logged in → system asks to login
2. If location is not enabled → system asks to enable GPS
3. If form is incomplete → system shows error message

Postconditions:

1. The request is saved successfully
2. Notifications are sent to donors
3. The request appears in the system

Exceptions:

E1: Missing Data

1. The system shows required fields message
2. The request is not submitted

Summary:

The system enables patients to quickly request blood and reach nearby donors.

Use Case 2

Use case name: Donate Blood
ID: UC-2
Priority: High

Actor: Donor

Description:
Allows donor to respond to a blood request.

Trigger:
Donor receives notification.

Normal Course:

1. Donor opens notification
2. Views request details
3. Accepts donation
4. Navigates to hospital

Postconditions:

- Donation is recorded
- Donor status updated