
AVR Interfacing

IO Ports

Agenda


- I/O Ports.
 - I/O Ports Programming.
 - Interfacing with Switches and Leds.
 - Interfacing with 7-Segment.
 - Interfacing with DC-Motor.
 - Interfacing with LCD.
 - Interfacing with Keypad.
-

I/O Ports


- **ATmega328p has programmable I/O lines divided into:**
 - PORTB(PB7.....PB0)
 - PORTC(PC7.....PC0)
 - PORTD(PD7.....PD0)
- **Each PORT is controlled by 3 registers:**
 - **DDRx:**
Data Direction Register to set the pin either output or input pin.
 - **PORTx**
Output Register to assign a value to the port (from **μC** to interface).
 - **PINx:**
Input Register where it holds the input value from interface.

Note: Most pins in μC make more than one function (multiplexed functions)


I/O Ports



I/O Ports



I/O Ports



Port A Data Register – PORTA

Bit	7	6	5	4	3	2	1	0	
	PORTA7	PORTA6	PORTA5	PORTA4	PORTA3	PORTA2	PORTA1	PORTA0	PORTA
Read/Write	R/W	R/W	R/W	R/W	R/W	R/W	R/W	<u>R/W</u>	
Initial Value	0	0	0	0	0	0	0	0	


Port A Data Direction Register – DDRA

Bit	7	6	5	4	3	2	1	0	
	DDA7	DDA6	DDA5	DDA4	DDA3	DDA2	DDA1	DDA0	DDRA
Read/Write	R/W	R/W	R/W	R/W	R/W	R/W	R/W	<u>R/W</u>	
Initial Value	0	0	0	0	0	0	0	0	

Port A Input Pins Address – PINA


Bit	7	6	5	4	3	2	1	0	
	PINA7	PINA6	PINA5	PINA4	PINA3	PINA2	PINA1	PINA0	PINA
Read/Write	R	R	R	R	R	R	R	R	
Initial Value	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	

Q₂
w



I/O Ports Programming

- To decided which Port is input and which is output:
 - Configure the port direction use register DDRX
 - 1 → for Output.
 - 0 → for Input.
- To Read(input case) :
 - Use register PINx
- To Write(output case) :
 - Use register PORTx.



Note:

In case you set any PIN as **input** you can activate the **internal pull up** resistor by setting the corresponding bit in **PORTX** register.

D
H 0 15
B 0 1

I/O Ports Programming

• How to set values in registers



- `DDRA=5;` /*(decimal)mean I activate pin 0 and pin 2 as output and the rest as input pins */
- `DDRB=0x14;` /*(hexadecimal)mean I activate pin 2 and pin 4 as output and the rest as input pins */
- `DDRC=0b00000011;` /*(binary)mean I activate pin 0 and pin 1 as output pins and the rest as input pins */

0001 0100

• How to deal with a specific pin with conserving other pins

➤ To set specified bit in register

Make OR operation on the register with The pin number.

- ❑ For example if we want to set pin number 5 in PORTA

`PORTA = PORTA | (1 << PA5);`

➤ To clear specified bit in register


Make AND operation on the register with (NOT) The pin number.

- ❑ For example if we want to set pin number 3 in PORTB

`PORTB = PORTB & (~(1 << PB3));`

1

0



I/O Ports Programming

➤ To toggle specified bit in register

Make XOR operation on the register with The pin number

- ❑ For example if we want to toggle pin number 2 in PORTC



$$PORTC = PORTC \wedge (1 \ll PC2);$$

• Example:

- To set the pin 2 in PORTB as input pin and use the internal pull up resistor of this pin.

$$DDRB = \underline{DDRB} \ \underline{\&} \ (\sim(1 \ll PB2))$$

$$PORTB = \underline{PORTB} \ \underline{|} \ (1 \ll PB2)$$



0



I/O Ports Programming

```
DDRA = 0xFF; //initialize portA as output
DDRB = 0x00; //initialize portB as input

if ((PINB & 0b00000001) == 1) //read a switch on PB0
{
    PORTA = 0xFF; //All LEDs on
}
else
    PORTA = 0x00; //All LEDs off
```

I/O Ports Programming


I/O Port applications

- **As Output**
 - LED and 7-Segemnt
 - LCD display
 - Motors.
 - Buzzer.
 - Signal to another μC .
 - Output to PC through PC Serial Port.
 - **As Input**
 - Switches(push button, keypad etc.)
 - Analog/Digital sensors.
 - Signal from another μC .
 - Input from PC through PC Serial Port.
-

Interfacing with Switches and Leds

LED Configuration


Negative Logic



34an el led teshtghl lazam a7ot 0

Positive Logic

34an el led teshtghl lazam a7ot 1




Interfacing with Switches and Leds



Switch Configuration



Pull Down Resistor




Pull UP Resistor



Interfacing with Switches and Leds




Switch de-bounce problem



- Could be handled using software or hardware.
- It relies on the fact that bouncing takes a maximum period of 20-30 ms.
- The basic idea is to implement a delay after the first detected edge, during which no scanning for the switch is done. after the delay period is finished, scanning can proceed (Exercise 3).


100

Interfacing with 7-Segment



Common Anode

0




Common Cathode

11

Interfacing with 7-Segment

In order to reduce the number of pins can be used to interface the 7 segment, we use decoder connected and follows;



Digit	Decoder inputs			
	C3	C2	C1	C0
0	0	0	0	0
1	0	0	0	1
2	0	0	1	0
3	0	0	1	1
4	0	1	0	0
5	0	1	0	1
6	0	1	1	0
7	0	1	1	1
8	1	0	0	0
9	1	0	0	1