




ΣΥΛΟΓΗ ΔΕΛΤΙΩΝ

1107
0101
1110



Conditional Random Field (CRF)

- While the **HMM** is a useful and powerful model, it turns out that HMMs need a number of **augmentations** to achieve high accuracy.
 - For example, in POS tagging as in other tasks, we often run into **unknown words**.
 - It would be great to have ways to add **arbitrary features** to help:
 - **Capitalization or morphology** (words starting with capital letters are likely to be **proper nouns**, words ending with **-ed** tend to be past tense)
 - Knowing the previous or following words might be a useful feature (if the previous word is **the**, the current tag is unlikely to be a verb).
- In general, it's hard for **generative models** like HMMs to add arbitrary features directly into the model in a clean way.
 - Logistic regression is a **log-linear** model for combining arbitrary features,
→ But logistic regression isn't a **sequence model**; it assigns a class to a single observation.
- There is a **discriminative sequence** model based on **log-linear** models: the **conditional random field** (CRF) → we will describe **linear chain CRF**, the version of the CRF most commonly used for language processing, and the one whose conditioning closely matches the HMM.

Conditional Random Field (CRF)

We have a sequence of input words $X = x_1 \dots x_n$ and want to compute a sequence of output tags $Y = y_1 \dots y_n$.

- In HMM:

$$\begin{aligned}\hat{Y} &= \underset{Y}{\operatorname{argmax}} p(Y|X) \\ &= \underset{Y}{\operatorname{argmax}} p(X|Y)p(Y) \\ &= \underset{Y}{\operatorname{argmax}} \prod_i p(x_i|y_i) \prod_i p(y_i|y_{i-1})\end{aligned}$$

emission transition

mkan el Pi msh hyfr2



- In CRF: we compute the **posterior** $p(Y|X)$ directly:

$$\hat{Y} = \underset{Y \in \mathcal{Y}}{\operatorname{argmax}} P(Y|X)$$

The CRF does not compute a probability for each tag at each time step. Instead, at each time step the CRF computes log-linear functions over a set of relevant features.

$$p(Y|X) = \frac{\exp \left(\sum_{k=1}^K w_k F_k(X, Y) \right)}{\sum_{Y' \in \mathcal{Y}} \exp \left(\sum_{k=1}^K w_k F_k(X, Y') \right)}$$

The function F maps an entire input sequence X and an entire output sequence Y to a feature vector.

Let's assume we have K features, with a weight w_k for each feature F_k .

Conditional Random Field (CRF)

- Re-write as:

$$p(Y|X) = \frac{1}{Z(X)} \exp \left(\sum_{k=1}^K w_k F_k(X, Y) \right)$$

$$Z(X) = \sum_{Y' \in \mathcal{Y}} \exp \left(\sum_{k=1}^K w_k F_k(X, Y') \right)$$

yt = VB, yt-1 = Noun -> return 1.

yt-1 = VB, i = 2, yt = Noun, X[i-1] = Do

f1, f2, f3.

F1, F2, F3

F1->

f1(-, Noun, X, 1) + f1(Noun, VB, X, 2) + f1(VB, VB, X, 3) + f1(VB, Noun, X, 3)

F2 = f2(

yt-1 -> tag el previous
yt -> current tag
X -> all input sequence
i -> timestep.

Noun Verb, ADJ

- These K functions $F_k(X, Y)$ are called **global features**?

→ since each one is a property of the entire input sequence X and output sequence Y.

- Computed by decomposing into a sum of **local features** for each position i in Y:

number of global features =
number of local features.

$$F_k(X, Y) = \sum_{i=1}^n f_k(y_{i-1}, y_i, X, i)$$

$\begin{matrix} \text{prev} & \text{curr} & \text{inp} & \text{curr} \\ \text{tag} & \text{tag} & \text{seq} & \text{timestep} \end{matrix}$

Each of these local features f_k in a linear-chain CRF is allowed to make use of:

- current output token y_i , you must use Markov assumption.
- previous output token y_{i-1} , lw m3mltsh dol, hyb2a genral CRF, w sa3tha 34an ast5dm vetrbi aw keda hyb2a feh shwyt modifications lazam ne3mlhom.
- entire input string X (or any subpart of it),
- current position i.

what characterizes a linear chain

CRF: this limitation makes it possible to use versions of the efficient **Viterbi** and **Forward-Backwards** algorithms from the HMM.

A general CRF, by contrast, allows a feature to make use of any output token.

Features in a CRF POS Tagger

- Some legal features representing common situations might be the following:

- 1 $\mathbb{1}\{x_i = \text{the}, y_i = \text{DET}\}$
- 2 $\mathbb{1}\{y_i = \text{PROPN}, x_{i+1} = \text{Street}, y_{i-1} = \text{NUM}\}$
- 3 $\mathbb{1}\{y_i = \text{VERB}, y_{i-1} = \text{AUX}\}$

Proper noun: name of a person, organization, place, etc.

For simplicity, we'll assume all CRF features take on the value 1 or 0.



- Specific features can be automatically populated by using **feature templates**:
 - These templates automatically populate the set of features from every instance in the training and test set.

$\langle y_i, x_i \rangle, \langle y_i, y_{i-1} \rangle, \langle y_i, x_{i-1}, x_{i+2} \rangle$

el xi+2 da example, bs enta keda keda m3ak el input kolo fkhud meno el enta 3auzo.

example: Janet/NNP will/MD back/VB the/DT bill/NN, when x_i is the word back, the following features would be generated and have the value 1 (we've assigned them arbitrary feature numbers):

f_{3743} : $y_i = \text{VB}$ and $x_i = \text{back}$
 f_{156} : $y_i = \text{VB}$ and $y_{i-1} = \text{MD}$
 f_{99732} : $y_i = \text{VB}$ and $x_{i-1} = \text{will}$ and $x_{i+2} = \text{bill}$

bn3ml el klam da 3la kol el inputs.

el klam da 3la kelmt back.

Features in a CRF POS Tagger

U.S.A -> X.X.X

I.M.F -> location

- It's also important to have features that help with **unknown words**:
 - word shape features**:
 - which represent the abstract letter pattern of the word by mapping: lower-case letters to 'x', upper-case to 'X', numbers to 'd', retaining punctuation.
 - Examples: I.M.F would map to X.X.X. and DC10-30 would map to XXdd-dd.
 - short word shape features**:
 - consecutive character types are removed, so words in all caps map to X, words with initial-caps map to Xx,
 - Examples: DC10-30 would be mapped to Xd-d but I.M.F would still map to X.X.X.
- Example features:

x_i contains a particular prefix (perhaps from all prefixes of length ≤ 2)

x_i contains a particular suffix (perhaps from all suffixes of length ≤ 2)

x_i 's word shape

x_i 's short word shape

The word: *well-dressed*

prefix(x_i) = w

hena khadna 2 34an hwa

prefix(x_i) = we

3aml define en el prefix kol
el shapes elly a2l or = mn 2

suffix(x_i) = ed

fa 3la 7asab enta m3rfha

suffix(x_i) = d

ezay

word-shape(x_i) = xxxx-xxxxxxx

short-word-shape(x_i) = x-x

prefix mmkn brdo yfedak -> replay -> (re)

el suffix momken yfedny eny a3rf hwa verb msln wla a -> ed

Features in a CRF POS Tagger

- The **known-word** templates are computed for every word seen in the training set.
- The unknown word features can also be computed for all words in training, or only on training words **whose frequency is below some threshold**.

→ The result is a **very large set of features**:

Generally, a **feature cutoff** is used in which features **are thrown out if they have count < 5** in the training set.

- In a CRF we **don't learn weights for each of these local features f_k** .
- Instead, we **first sum the values of each local feature** (for example feature **f_{3743}**) over the entire sentence, to create each global feature (for example **F_{3743}**).
- It is those **global features** that will **then be multiplied by weight $w_{3743} = 2$** .
- Thus, for training and inference there is always a **fixed set of K features with K weights**, even though the length of **each sentence is different**.

Features for CRF Named Entity Recognizers

- A CRF for NER makes use of very similar features to a POS tagger:

identity of w_i , identity of neighboring words
embeddings for w_i , embeddings for neighboring words
part of speech of w_i , part of speech of neighboring words
presence of w_i in a **gazetteer**
 w_i contains a particular prefix (from all prefixes of length ≤ 4)
 w_i contains a particular suffix (from all suffixes of length ≤ 4)
word shape of w_i , word shape of neighboring words
short word shape of w_i , short word shape of neighboring words
gazetteer features

- **gazetteer**: list of place names, often providing millions of entries for locations with detailed geographical and political information.
- name-lists, lists of corporations or products, ...etc.
- Some NER features for a sample sentence:

Words	POS	Short shape	Gazetteer	BIO Label
Jane	NNP	Xx	0	B-PER
Villanueva	NNP	Xx	1	I-PER
of	IN	x	0	O
United	NNP	Xx	0	B-ORG
Airlines	NNP	Xx	0	I-ORG
Holding	NNP	Xx	0	I-ORG
discussed	VBD	x	0	O
the	DT	x	0	O
Chicago	NNP	Xx	1	B-LOC
route	NN	x	0	O
.	.	.	0	O

Inference and Training for CRFs

1, 3, 2 -> 3 /

$e^3, e^2, e^1 \rightarrow e^3 \rightarrow 1, 2, 3 \rightarrow 3$

$$\begin{aligned}\hat{Y} &= \operatorname{argmax}_{Y \in \mathcal{Y}} P(Y|X) \\ &= \operatorname{argmax}_{Y \in \mathcal{Y}} \frac{1}{Z(X)} \exp \left(\sum_{k=1}^K w_k F_k(X, Y) \right) \\ &= \operatorname{argmax}_{Y \in \mathcal{Y}} \exp \left(\sum_{k=1}^K w_k \sum_{i=1}^n f_k(y_{i-1}, y_i, X, i) \right) \\ &= \operatorname{argmax}_{Y \in \mathcal{Y}} \sum_{k=1}^K w_k \sum_{i=1}^n f_k(y_{i-1}, y_i, X, i) \\ &= \operatorname{argmax}_{Y \in \mathcal{Y}} \sum_{i=1}^n \sum_{k=1}^K w_k f_k(y_{i-1}, y_i, X, i)\end{aligned}$$

Inference: How do we find the best tag sequence \hat{Y} for a given input X ?

we can ignore the **exp function and the denominator $Z(X)$** because this doesn't change the **argmax**, and the denominator $Z(X)$ is constant for a given observation sequence X .

replacing transition and emission probabilities with the CRF features

- Using Viterbi Algorithm:

$$v_t(j) = \max_{i=1}^N v_{t-1}(i) \sum_{k=1}^K w_k f_k(y_{t-1}, y_t, X, t) \quad 1 \leq j \leq N, 1 < t \leq T$$


Training: given a sequence of observations, feature functions, and corresponding outputs, we use stochastic gradient descent to train the weights to maximize the log-likelihood of the training corpus.

Evaluation

- Part-of-speech taggers are evaluated by the standard metric of **accuracy**.
- Named entity recognizers are evaluated by **recall, precision, and F1 measure**.
 - The fact that named entity tagging has a segmentation component which is not present in tasks like text categorization or part-of-speech tagging causes some problems with evaluation.
 - For example, a system that labeled *Jane* but not *Jane Villanueva* as a person would cause **two errors**:
 - a false positive for **O** ✓
 - a false negative for **I-PER** ✓

RNN Sequence Labeling

- Inputs: are word embeddings
- Outputs: are tag probabilities generated by a softmax layer over the given tagset.





Thank You

0100

0100

0110

0110

1001

1001

0100

0110

1101

0100

0110

1001

0100

0110

1010

0110

1001

0101

0100

1101

0101

1110

1010

0110

1001

0101

0100

0110

1001

0101

0100

1101

1010

0110

1001